

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Typical Section No.:

2

of

1

Page

03/06/18

Date:

Toole, Curry, Park & Shiver

Cored by:

Roadway Section: 46050000		Name: SR 20		Lanes: 2-12.0'	
Fin. Proj. ID: 436266-1		From: SR 77		Shoulder Type and Condition: Paved (Fair)	
F.A. Proj. No.:		To: SR 75 (US 231)		Inside: NA	
County: Bay		SR No.: 20	Beg MP: 7.763	End MP: 23.419	Lgth: 15.656
Median Curbed (Y/N): N		Paved	Curb & Gutter (Y/N): N		Outside: 2-5.0' Paved
Other:					

Core No.	Mile Post or Sta. No.	Lane	Wheel Path (Y/N)	Pavement Layer (in.)				Base		Crack			Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Project Comments
				Top	SP2F	ARM1	SP1F	WC	Core Lgth (in.)	SAHM	SLR	Concrete				
1	8.350	R1	Y	1.40	1.50	0.50	0.70	1.00	5.10	7.00			P			
2	8.350	R2	N	2.00	-	-	-	-	2.00		3.50		F			Core taken in shoulder.
3	10.350	R1	Y	1.30	1.00	0.50	0.60	1.20	4.60	8.50			P			
4	12.250	R1	Y	1.50	1.20	0.50	0.60	1.00	4.80	8.00			P			
5	12.250	R2	N	2.00	-	-	-	-	2.00		4.50		F			Core taken in shoulder.
6	14.530	R1	Y	1.40	1.20	0.50	0.50	1.00	4.60	8.00			P			
7	16.350	R1	Y	2.50	-	-	-	-	2.50				F			Core taken on bridge approach
8	16.380	R1	Y	2.75	-	-	-	-	2.75				F			Core taken on bridge approach
9	18.440	R1	Y	1.40	1.20	0.50	0.60	1.20	4.90	7.50			P			
10	18.440	R2	N	2.10	-	-	-	-	2.10		3.00		F			Core taken in shoulder.
11	20.260	R1	Y	1.40	1.30	0.50	0.50	1.20	4.90	8.00			P			Shoulder x-slope 6.00
12	22.330	R1	Y	1.40	1.20	0.50	0.50	1.10	4.70	8.00			P			

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION

2

of

2

Page

04/06/00

[illegible]