

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Tierra, Inc. Date: 01/24/22 Page 1 of 1 Typical Section No.: _____

Roadway Section: 480200001			Name: SR 10A			Lanes: R1, L1, RRTL		
Fin. Proj. ID: 445629-1-52-01			From: SR 8			Shoulder Type and Condition: Paved		
F.A. Proj. No.:			To: SR 10A			Inside: NA		
County: Escambia		SR No.: 10A	Beg MP: 23.715	End MP: 0.045	Lgth: 3.152	Outside:		
Median Curbed (Y / N): N Paved Y Lawn Other:						Curb & Gutter (Y / N): N		

Core No.	Mile Post or Sta. No.	Lane	Wheel Path (Y / N)	Pavement Layer (in.)					Base		Crack			Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	Comments	
				Top FC-9.5	SP	T2	S3	S1	Core Lgth (in.)	SAHM	ABC	Depth (in.)	Type					Class
101	26.645	R1	Y	0.50	0.50	1.75	3.75	-	6.50	7.50	-	6.50	B	III	M	P		Core Thickness Measured in Hole
102	26.685	L1	Y	0.75	1.00	-	1.25	-	3.00	10.00	-	3.00	B	III	S	P		4" Base Attached to Core Bottom
103	0.035	R1	Y	1.00	2.00	-	-	-	3.00	-	9.00	2.50	B	II	S	P		9" Base Attached to Core Bottom
104	0.034	L1	Y	1.00	1.50	-	-	-	2.50	-	8.50	6.50	B	II	S	P		8.5" Base Attached to Core Bottom
105	26.748	RRTL	Y	1.50	0.50	1.00	-	-	3.00	7.75	-	3.25	B	III	M	P		
106	26.791	RRTL	Y	0.75	0.75	-	1.75	-	3.25	7.75	-	3.25	B	III	M	P		
107	26.814	RRTL	Y	2.00	2.00	-	-	-	4.00	8.00	-	4.00	B	III	M	P		