TABLE 1
PAVEMENT CORE AND CONDITION SURVEY
SR 99 (BEULAH ROAD) FROM SR 10A (US 90) TO ISSACS LANE
ESCAMBIA COUNTY, FLORIDA

Cored by: EVERETT PUCKETT Date: 03/09/22 Page: 1 of 1 Typical Section No.:

Roadway Section: 48090000			Name: SR 99 (BEULAH ROAD)		Lanes: 2
Fin. Proj. ID: 433113-5-52-01			From: SR 10A (US 90 / MOBILE HIGHWAY)		Shoulder Type and Condition: VARIES
F. A. Proj. No.: - -			To: ISSACS LANE		Inside: N/A
County: ESCAMBIA	SR No.: SR 99 (BEULAH ROAD)		Beg MP: 0.000	End MP: 2.586 Lgth: 2.586	Outside: VARIES (C&G / GRASS)
Median Curbed (Y / N): N	Paved: N/A	Lawn: N/A			Curb & Gutter (Y / N): VARIES

				Pavement Layer (in.)									Base			Crack							
Core No.	Mile Post or Sta. No.	Lane	Wheel Path (Y / N)	FC-3	FC-9.5	SP-9.5	ARMI	S-1	BIND			Core Lgth. (in.)	LR	SCLY		Depth (in.)	Type	Class	Extent	Pvmt Cond	Rut Depth (in.)	Cross Slope (%)	PROJECT COMMENTS
K-1	0.064	LITL	N	1.0		2.1	0.6	0.7	0.9			5.3		12.0		0.0	A	IB	L	F	0.10	3.10	LIGHT RUTTING
K-2	0.199	R1	Y	1.3			0.6	1.4	0.8			4.1		8.0		0.0	A	IB	L	F	0.10	2.90	LIGHT RUTTING, MODERATE RAVELING
K-3	0.676	L1	Y	0.8		0.6	0.6	0.8	1.0			3.8		4.0		0.0	A	IB	L	F	0.10	3.00	LIGHT RUTTING, MODERATE RAVELING
K-4	1.011	ROTL	Y	1.3		2.8						4.1	7.0			0.0	A	IB	L	F	0.10	2.00	LIGHT RUTTING / CURB AND GUTTER
K-5	1.075	LITL	N		1.0	0.5	0.3	0.8	0.7			3.3		5.0		0.0	A	IB	L	F	0.10	3.10	LIGHT RUTTING
K-6	1.188	RITL	Y		1.7	8.3						10.0		12.0		0.0	A	IB	L	F	0.10	4.00	LIGHT RUTTING / VOIDS IN MIX / NEAR PAVEMENT CHANGE
K-7	1.663	R1	Y		1.0	2.2						3.2	8.0			3.2	B	II	M	F	0.20	2.60	MODERATE RUTTING / MODERATE RAVELING
K-8	1.847	L1	Y		1.0	2.1						3.1	5.0			0.0	A	IB	L	F	0.20	2.70	MODERATE RUTTING / MODERATE RAVELING
K-9	2.145	ROTL	Y		1.0	1.4						2.4	6.0			0.0	A	IB	L	F	0.20	0.70	MOD RUTTING / MOD RAVELING / PAVEMENT GRADE DIFFERENCE R1/ROTL
K-10	2.225	L1	Y		0.8	2.2						3.0	8.0			0.6	A	IB	L	F	0.20	2.70	MODERATE RUTTING / MOD RAVELING / MOD ALLIGATOR CRACKING
K-11	2.225	R1	Y		1.1	2.1						3.2	6.0			3.2	B	III	M	P	0.20	3.00	MOD RUTTING / SEV RAVELING / SEV SPALLING / SEV ALLIGATOR CRK