

Fin. Proj. ID: 436274 -2 -52 -01		From: SR 95	Shoulder Type & Condition
F.A. Proj. No.: D324 042 B		To: CR 95A N PALAFOX STR	Inside:
County: 48	SR No.: SR 750	Beg MP: 0.000 End MP: 0.154 Lgth: 0.154	Outside:
Median Curbed: Paved:[] Lawn:[] Other:[]			Curb & Gutter: Y

Core No.	Mile Post or Sta. No.	Lane	W P h a e t e h l	Pavement Layer (in)					Core Lgth (in)	Base SAHM	Crack				P v o n d t	C R u e t p t h (in)	D C S r l o o s p s e (%)	Comments
				FC	SP	1	C				D e p t h (in)	T y p e	C l a s s	E x t e n t				
1	0.055	R2	N	1.75	1.75				3.50	5.2					G			BASE ATTACHED TO CORE
2	0.071	L1	N	1.25	1.00				2.25	5.2	8.00	B	II	M	F			BASE ATTACH TO CORE CRACK BSE
3	0.109	L2	N	1.75	1.50				3.25	5.2	8.50	B	II	M	F			BASE ATTACH TO CORE CRACK BSE
4	0.122	R1	Y	1.00	1.75				2.75	5.5	8.00	B	II	M	F			BASE ATTACH TO CORE CRACK BSE
5	0.130	RL	N	1.00	1.25				2.25	5.2	2.25	B	II	M	F			BASE ATTACHED TO CORE

Code Descriptions

generated by

Output produced by "pccd3.sas" program.

This request took 1.18 seconds of real time (v9.4 build 1519).