FLORIDA DEPARTMENT OF TRANSPORTATION PAVEMENT CORING REPORTING

PCRPJ03 PCRO003

PAVEMENT EVALUATION CORING AND CONDITION DATA INPUT DATA REPORT

MANDIST	FINPROJ	TYPSECT	MESSAGE
04	446177-1-52-01	01	THE CONTROL CARD IS CORRECT

FLORIDA DEPARTMENT OF TRANSPORTATION PAVEMENT CORING REPORTING

PCRPJ03 PCR0103

PAVEMENT EVALUATION CORING AND CONDITION DATA

FIN PROJ: 446177-1-52-01	NAME :	CORED BY: HRES
TYP SECT: 01	FROM:	DATE: 2020-10-27
	TO:	LANES: @ FEET
FA PROJ:		
COUNTY: PALM BEACH	BEG MP: .00	SHOULDER TYPE
SR NUMBER: SR 7	END MP: 2.00 LENGTH: 2.00	INSIDE:
MEDIAN	PROJECT MEASUREMENT: ENGLISH	OUTSIDE:
MEDIAN: CURBED: NO		CURB & GUTTER: NO

FLORIDA DEPARTMENT OF TRANSPORTATION PAVEMENT CORING REPORTING

PCRPJ03 PCR0203

PAVEMENT EVALUATION CORING AND CONDITION DATA

CORE NO.	MILE POST	VFY		W P-	TOP		PAVEMENT	LAYER	 CORE LNGTH	BASE	SUB		CRACK TYP CLSS		COMMENTS
				I	FC2	S1				LR	ST40				
1	.273	N	R4	Y		5.50			5.50	12.0	12.0	2.30	IB	F	26.68421 -80.20203
2	.288	Ν	L1	Y		13.30			13.30	12.0	12.0	1.40	IB	F	26.68442 -80.20226
3	.748	Ν	L4	Y		4.10			4.10	12.0	12.0			G	26.69108 -80.20186
4	.813	N	R1	Y		3.50			3.50	12.0	12.0	.90	IB	F	26.69200 -80.20157
5	1.276	N	R3	Y		3.00			3.00	12.0	12.0	3.00	IB	F	26.69871 -80.20122
б	1.276	N	L1	Y		3.20			3.20	12.0	12.0	1.00	IB	F	26.69871 -80.20140
7	1.815	N	R1	Y		3.80			3.80	12.0	12.0	1.50	IB	F	26.70650 -80.20100
8	1.867	N	LЗ	Y		6.60			6.60	12.0	12.0			G	26.70727 -80.20115
9	.209	N	OR	Ν		2.70			2.70	6.0	12.0			G	26.68337 -80.20204
10	.608	N	OR	Ν		4.20			4.20	6.0	12.0			G	26.68897 -80.20197
11	.871	N	OR	Ν		2.20			2.20	6.0	12.0			G	26.69295 -80.20144
12	1.186	N	OR	Ν		1.50			1.50	6.0	12.0			G	26.69740 -80.20156
13	1.516	N	OR	Ν		2.00			2.00	6.0	12.0			G	26.70207 -80.20107
14	1.874 .000	Ν	OR	Ν		6.10			6.10	6.0	12.0			G	26.70727 -80.20117

PAVEMENT EVALUATION CORING AND CONDITION DATA

COMMENTS

C	T.	\sim	
S	ъ	Q.	

- BASE IS LIMEROCK (A-1-B). SUBBASE IS FINE SAND
 (A-3). CORES 1, 4, 5 AND 7 WERE PERFORMED ON SR 7
 (NORTHBOUND). CORES 2, 3, 6 AND 8 WERE PERFORMED
 4 ON SR 7 (SOUTHBOUND).
- 5 FOR ALL SHOULDER CORES, BASE IS LIMEROCK (A-1-B).
- 6 FOR SHOULDER CORES 9, 11, 12, 13 AND 14 SUBBASE IS
- 7 FINE SAND (A-3). FOR SHOULDER CORE 10 SUBBASE IS
- 8 SILTY FINE SAND (A-2-4). SHOULDER CORES 9, 11 AND
- 9 13 WERE PERFORMED ON SR 7 (NORTHBOUND). SHOULDER
- 10 CORES 10, 12, AND 14 WERE PERFORMED ON SR 7
- 11 (SOUTHBOUND)
- 12 MILLING RECOMMENDATIONS: MILL 2.50 INCHES AND
- 13 REPAVE WITH 1.25 INCHES SP-9.5 (STRUCTURAL COURSE)
- 14 AND 1.25 INCHES FC-9.5 (FRICTION COURSE).

	CODE DESCRIPTIONS
	TYPE DESCRIPTION
А	ALLIGATORING IN WHEELPATH
В	BLOCK CRACKING
С	COMBINATION OF TYPES
	EXTENT DESCRIPTION
L	LIGHT
М	MEDIUM
S	SEVERE
	CLASS DESCRIPTION

II UNKNOWN

III UNKNOWN

CODE DESCRIPTIONS

SURFACE LAYER	
CODE	DESCRIPTION
====	
ARMI	ASPHALT RUBBER MEMBRANE INTERL
BIND	ASPHALT BINDER COURSE
BRCK	BRICK PAVERS
CONC	PORTLAND CEMENT CONCRETE
CRL	CRACK RELIEF LAYER
FAB	PAVEMENT OVERLAY FABRIC
FC	FRICTION COURSE
FC1	FRICTION COURSE 1
FC2	FRICTION COURSE 2
FC3	FRICTION COURSE 3
FC4	FRICTION COURSE 4
FC5	FRICTION COURSE 5
FC5B	FRICTION COURSE 5 BONDED
FC6	FRICTION COURSE 6
F12M	FRIC. COURSE 12.5 MODIFIED
F125	FRICTION COURSE 12.5
F95	FRICTION COURSE 9.5
F95M	FRIC. COURSE 9.5 MODIFIED
S	TYPE S ASPHALTIC CONCRETE
SAHM	SAND ASPHALT HOT MIX
SP1C	9.5 SUPERPAVE COARSE GRADED
SP1F	9.5 SUPERPAVE FINE GRADED
SP2C	12.5 SUPERPAVE COARSE GRADED
SP2F	12.5 SUPERPAVE FINE GRADED
SP3C	19.0 SUPERPAVE COARSE GRADED
SP3F ST	19.0 SUPERPAVE FINE GRADED SURFACE TREATMENT
SI S1	TYPE S-I ASPHALTIC CONCRETE
S1 S2	TYPE S-II ASPHALTIC CONCRETE
52 S3	TYPE S-III ASPHALIIC CONCRETE
55 T1	TYPE I ASPHALTIC CONCRETE
T2	TYPE II ASPHALTIC CONCRETE
T3	TYPE III ASPHALTIC CONCRETE
UNIM	UNIMPROVED SURFACE
UNKW	UNKNOWN
WC	WEARING COURSE
WC1	WEARING COURSE 1
WC1 WC2	WEARING COURSE 2
WC3	WEARING COURSE 3
WC4	WEARING COURSE 4
WC5	WEARING COURSE 5
WC6	WEARING COURSE 6
WC7	WEARING COURSE 7
WC8	WEARING COURSE 8