

State of Florida Department of Transportation
PAVEMENT EVALUATION AND CONDITION DATA SHEET

Project No.:		238275-2		Cored By:		Ardaman		Date:		12/19/2013		Page No.:		1 of 1						
County:		Lake		Highway Sect. No.:		11010		From:		CSX RR Bridge		To:		Orange County Line						
Road No.:		SR 500 (US 441)		Begin MP:		22.885		End MP:		23.290		Length:		0.405 Miles						
Core No.	MP	Distance from left edge of lane (ft.)	Lane	Wheel Path	Pavement Layers (in.)					Base		Crack				Pavt Cond.	Rut Depth (in)	Cross Slope (%)	Comments	
					FC-5	FC-2	Type-SP	Type-S	Binder	Core Length (in)	Type	Thick-ness (in)	Depth (in)	Type	Class					Extent
1	22.902	11.0	R2	X	0.9			1.5	1.0	3.4	LR	10.9	B	AL	III	S	P			
2	22.993	3.5	RRTL	X	1.2		1.3	1.3		3.8	LR	11.2	---	---	---	---	F			to Robie Avenue - West
3	22.993	1.5	OR	---		0.6		1.2		1.8	LR	5.0	---	---	---	---	F			
4	23.045	10.0	R2	X	0.9			1.3	1.5	3.7	LR	10.8	B	AL	III	S	P			
5	23.228	9.5	R2	X	0.8			1.6	1.3	3.7	LR	9.8	B	AL	III	S	P			
6	23.228	2.0	OR	---	1.5		1.2			2.7	LR	4.1	---	---	---	---	F			
7	23.269	9.0	L2	X	0.7			2.0	1.3	4.0	LR	9.0	B	AL	III	S	P			
8	23.200	3.0	LRTL	X	0.9			2.4		3.3	LR	9.0	---	---	---	---	F			to U-Haul / Storage Facility
9	23.100	4.5	L2	---	1.0			1.6	1.1	3.7	LR	8.1	B	AL	III	S	P			
10	23.069	2.0	OL	---	0.8		1.5			2.3	LR	5.8	---	---	---	---	F			
11	22.946	10.5	L2	X	0.9			1.6	0.5	3.0	LR	11.0	2.6	AL	III	S	P			
12	22.946	2.0	OL	---	1.0		1.3			2.3	LR	3.7	---	---	---	---	F			
13	23.000	2.5	RRTL	X	1.0			2.8		3.8	LR	10.2	---	---	---	---	F			to Robie Avenue - East
14	23.124	10.0	RRTL	X	0.9			3.0		3.9	LR	8.9	---	---	---	---	F			to U-Haul / Storage Facility
15	23.129	2.5	R1	X	0.5			3.6		4.1	LR	9.9	B	BR	II	M	P			
16	23.252	4.0	RRTL	---	0.8			3.0		3.8	LR	10.2	---	---	---	---	F			to MXO at Orange Co. Line
17	23.195	3.0	LLTL	X		0.6		2.9		3.5	LR	10.8	---	---	---	---	G			New Pavement to Dollar General Store
18	23.077	7.0	L1	---	0.7			2.1	1.1	3.9	LR	9.9	B	ST	III	M	P			
19	23.062	6.5	LLTL	---	1.1			2.8		3.9	LR	10.6	0.1	SL	II	L	F			to Robie Avenue - West