

**State of Florida Department of Transportation
PAVEMENT EVALUATION AND CONDITION DATA SHEET**

Project No.:		430658-1		Cored By:		Elipsis Engineering and Consulting		Date:		May 15, 2013		Page No.:		MASTER						
County:		Brevard		Highway Sect. No.:		70022		From:		Eddie Allen Rd		To:		SR 5						
Road No.:		SR 508		Begin MP:		38.636		End MP:		40.000		Length:		1.364						
Core No.	MP	Distance from left edge of lane (ft)	Lane	Wheel Path	Pavement Layer (in.)					Base		Crack				Pavt Cond.	Rut Depth (in)	Cross Slope (%)	Comments	
					FC-3	FC-9.5	Type S	Type II		Core Length (in)	Type	Thick-ness (in)	Depth (in)	Type	Class					Extent
1	38.686	9.0	R2	X	1.8		1.7			3.5	SC	8.0	B	A	III	S	P			Targeted Core/Add-Ons
2	38.894	2.0	R2	X		1.0	0.5	0.9		2.4	SC	10.6	—	—	—	—	G			Targeted Core/Inside Wheelpath RH Curve
3	39.170	9.5	R2	X		1.5		1.8		3.3	SC	7.0	—	—	—	—	G			
4	39.369	5.5	R2		1.2			1.4		2.6	SC	6.4	B	SL	II	M	F			Targeted Core/Add-Ons
5	39.585	9.0	R2	X	1.2			1.5		2.7	SC	8.8	B	ST	III	S	P			
6	39.821	8.5	R2	X	1.8		0.7	0.5		3.0	SC	7.5	B	ST	II	L	F			LH Curve
7	39.871	8.5	L2	X	0.7		2.6			3.3	SC	8.2	—	—	—	—	F			
8	39.510	2.5	L2	X	1.8		0.5			2.3	SC	9.0	B	A	III	S	P			Targeted Core/Inside Wheelpath
9	38.969	2.0	L2	X	1.1		1.0			2.1	SC	7.9	B	A	III	M	P			Targeted Core/Inside Wheelpath
10	38.912	10.5	LR		1.9		1.1			3.0	LR	8.5	—	—	—	—	F			To Air Terminal Parkway
11	38.813	8.5	L2	X	1.8		0.9	1.0		3.7	SC	6.8	B	A	II	S	P			Targeted Core/Outside Wheelpath
12	38.686	8.0	R1	X	2.0		1.3			3.3	SC	7.2	—	—	—	—	F			
13	38.840	2.0	RLTL	X	1.6		0.9			2.5	LR	16.5	—	—	—	—	F			To Air Terminal Parkway
14	39.014	9.0	R1	X	1.4		0.5	0.7		2.6	SC	7.4	—	—	—	—	F			Targeted Core/Outside Wheelpath
15	39.190	2.0	RLTL	X	2.1		1.4			3.5	LR	6.5	—	—	—	—	F			To Babcock St
16	39.411	2.5	R1	X	1.4		0.7	0.8		2.9	SC	7.9	—	—	—	—	F			
17	39.544	9.5	R1	X	1.5			1.1		2.6	SC	8.7	—	—	—	—	F			Targeted Core/Add-Ons
18	39.900	2.5	R1	X	1.1		0.3	1.4		2.8	SC	8.2	—	—	—	—	F			Location moved due to no RLTL at given MP
19	39.900	3.0	RLTL	X	1.4		1.0			2.4	LR	7.6	—	—	—	—	F			Location moved due to no RLTL at given MP
20	39.811	2.5	L1	X	1.2		2.2			3.4	SC	7.1	—	—	—	—	F			
21	39.811	10.0	LLTL	X	0.7		1.6			2.3	LR	17.2	—	—	—	—	F			To Audi/Porsche Dealership
22	39.551	1.5	LLTL		1.4		0.8	0.7		2.9	SC	8.6	B	A	I	L	F			Targeted Core/Add-Ons To Apollo Blvd
23	39.361	2.5	L1	X	1.3		1.3			2.6	SC	7.4	—	—	—	—	F			
24	39.361	8.0	LLTL	X	1.6		0.8			2.4	SC	8.6	—	—	—	—	F			To Babcock St
25	39.111	2.5	LLTL	X	1.5		1.0			2.5	LR	7.8	—	—	—	—	F			To Sears Parking Lot
26	38.734	5.0	L1		1.6			1.0		2.6	SC	8.4	B	ST	II	L	F			