

11/30/22

FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT CORING REPORTING

PCRPJ03
PCRO003

PAVEMENT EVALUATION CORING AND CONDITION DATA
INPUT DATA REPORT

| MANDIST | FINPROJ | TYPSECT | MESSAGE |
|---------|----------------|---------|-----------------------------|
| 06 | 445987-1-52-01 | 01 | THE CONTROL CARD IS CORRECT |

11/30/22

FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT CORING REPORTING

PCRPJ03
PCRO103

PAVEMENT EVALUATION CORING AND CONDITION DATA

| | | |
|--------------------------|------------------------------|------------------------|
| FIN PROJ: 445987-1-52-01 | NAME: | CORED BY: OSCAR CORREA |
| TYP SECT: 01 | FROM: | DATE: 2020-04-20 |
| | TO: | LANES: @ FEET |
| FA PROJ: D622071B | BEG MP: .00 | SHOULDER TYPE |
| COUNTY: MIAMI-DADE | END MP: 5.06 LENGTH: 5.06 | INSIDE: |
| SR NUMBER: SR 9336 | PROJECT MEASUREMENT: ENGLISH | OUTSIDE: |
| MEDIAN: | | CURB & GUTTER: NO |
| CURBED: NO | | |

PAVEMENT EVALUATION CORING AND CONDITION DATA

COMMENTS

SEQ

- 1 RUT DEPTH OF ALL CORES ARE LESS THAN .25"
- 2 SUB GRADE IS LIGHT BROWN LIMEROCK WITH SAND
- 3 THE MILLING AND PAVING RECOMMENDATION IS
- 4 MILL 1.5" AND REPAVE WITH 1.5" OF FC 12.5

CODE DESCRIPTIONS

CRACK TYPE TYPE DESCRIPTION
=====

A ALLIGATORING IN WHEELPATH

B BLOCK CRACKING

C COMBINATION OF TYPES

CRACK EXTNT EXTENT DESCRIPTION
=====

L LIGHT

M MEDIUM

S SEVERE

CRACK CLASS CLASS DESCRIPTION
=====

IB UNKNOWN

II UNKNOWN

III UNKNOWN

CODE DESCRIPTIONS

| SURFACE LAYER CODE ===== | DESCRIPTION ===== |
|-----------------------------------|--------------------------------|
| ARMI | ASPHALT RUBBER MEMBRANE INTERL |
| BIND | ASPHALT BINDER COURSE |
| BRCK | BRICK PAVERS |
| CONC | PORTLAND CEMENT CONCRETE |
| CRL | CRACK RELIEF LAYER |
| FAB | PAVEMENT OVERLAY FABRIC |
| FC | FRICTION COURSE |
| FC1 | FRICTION COURSE 1 |
| FC2 | FRICTION COURSE 2 |
| FC3 | FRICTION COURSE 3 |
| FC4 | FRICTION COURSE 4 |
| FC5 | FRICTION COURSE 5 |
| FC5B | FRICTION COURSE 5 BONDED |
| FC6 | FRICTION COURSE 6 |
| F12M | FRIC. COURSE 12.5 MODIFIED |
| F125 | FRICTION COURSE 12.5 |
| F95 | FRICTION COURSE 9.5 |
| F95M | FRIC. COURSE 9.5 MODIFIED |
| S | TYPE S ASPHALTIC CONCRETE |
| SAHM | SAND ASPHALT HOT MIX |
| SP1C | 9.5 SUPERPAVE COARSE GRADED |
| SP1F | 9.5 SUPERPAVE FINE GRADED |
| SP2C | 12.5 SUPERPAVE COARSE GRADED |
| SP2F | 12.5 SUPERPAVE FINE GRADED |
| SP3C | 19.0 SUPERPAVE COARSE GRADED |
| SP3F | 19.0 SUPERPAVE FINE GRADED |
| ST | SURFACE TREATMENT |
| S1 | TYPE S-I ASPHALTIC CONCRETE |
| S2 | TYPE S-II ASPHALTIC CONCRETE |
| S3 | TYPE S-III ASPHALTIC CONCRETE |
| T1 | TYPE I ASPHALTIC CONCRETE |
| T2 | TYPE II ASPHALTIC CONCRETE |
| T3 | TYPE III ASPHALTIC CONCRETE |
| UNIM | UNIMPROVED SURFACE |
| UNKW | UNKNOWN |
| WC | WEARING COURSE |
| WC1 | WEARING COURSE 1 |
| WC2 | WEARING COURSE 2 |
| WC3 | WEARING COURSE 3 |
| WC4 | WEARING COURSE 4 |
| WC5 | WEARING COURSE 5 |
| WC6 | WEARING COURSE 6 |
| WC7 | WEARING COURSE 7 |
| WC8 | WEARING COURSE 8 |