

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 4/10/23 & 4/11/23 Page 3 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: L1				
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:				
F.A. Proj. No.:		To:				Inside:				
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:			
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N				

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Cros Section	Comments	Latitude	Longitude									
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent							
				FC5																																					
55	16.75	L1	Y	0.9	1.5	3.0	2.4									7.8	9.5		9.5														G						28.04635	-81.83465	
56	15.50	L1	Y	0.9	1.6	3.3	2.2									8.0	8.0		8.0														F						28.02834	-81.83214	
58	13.50	L1	Y	0.9	2.4	1.4										4.7	13.4		13.4														F						28.01094	-81.84858	
60	13.01	L1	Y	1.1	1.7	1.6										4.4	14.9		14.9				Y	C	III	M							P						L1 Crack Core 1	28.01079	-81.85671
61	11.25	L1	Y	1.0	1.8	1.5										4.3	13.9		13.9														P						28.00699	-81.88510	
64	10.00	L1	Y	0.8	1.8	1.8										4.4	12.3		12.3														F						27.99984	-81.90394	
66	8.75	L1	Y	1.1	5.3											6.4	13.4		13.4														P						27.99650	-81.92355	

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 4/11/23 & 4/18/23 Page 5 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: IR				
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:				
F.A. Proj. No.:		To:				Inside:				
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:			
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N				

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude										
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent								
				FC5																																						
40	8.50	IR	N		2.0	1.5										3.5	9.2		9.2														G								27.99622	-81.92763
42	9.40	IR	N		2.1											2.1	5.7		5.7														G								27.99655	-81.91301
44	10.50	IR	N		2.0											2.0	3.3		3.3														G								28.00275	-81.89642
46	11.50	IR	N		1.7											1.7	3.1		3.1							Y	L	II	M		F										28.00789	-81.88106
48	13.50	IR	N		2.0											2.0	5.8		5.8														G								28.01045	-81.84857
50	15.50	IR	N		1.8											1.8	6.1		6.1														G								28.02836	-81.83194
53	16.93	IR	N		1.4											1.4	14.6		14.6														G								28.04911	-81.83446

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 4/10/23 & 4/11/23 Page 7 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: IL			
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:			
F.A. Proj. No.:		To:				Inside:			
County: Polk	SR No.: 570	Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:				
Median Curbed (Y / N): N	Paved, Lawn, Other:				Curb & Gutter (Y / N): N				

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude			
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent	
				FC5																															
54	16.79	IL	N		1.9	0.2										2.1	14.6		14.6										G					28.04702	-81.83462
57	15.48	IL	N		0.8	1.0										1.8	9.8		9.8										G					28.02801	-81.83205
59	13.50	IL	N		1.4	1.1										2.5	3.5		3.5										G					28.01091	-81.84858
62	11.25	IL	N	1.0	1.3	1.0										3.3	13.3		13.3										G					28.00697	-81.88509
63	10.50	IL	N		2.7											2.7	4.3		4.3										G					28.00286	-81.89648
65	9.50	IL	N		2.4											2.4	6.2		6.2										G					27.99689	-81.91136
67	8.75	IL	N		1.4	0.9										2.3	5.9		5.9										G					27.99646	-81.92355

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 4/10/23 & 4/11/23 Page 8 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: OL				
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:				
F.A. Proj. No.:		To:				Inside:				
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:			
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N				

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude								
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent						
				FC5																																				
22	16.35	OL	N		1.4	5.4										6.8	7.8		7.8															F					28.04058	-81.83411
25	15.60	OL	N		2.5	5.4										7.9	6.4		6.4																			28.02969	-81.83242	
29	13.11	OL	N		1.2	0.8										2.0	5.2		5.2																			28.01090	-81.85569	
33	11.55	OL	N		1.7											1.7	11.9		11.9																			28.00843	-81.87961	
34	10.75	OL	N		1.6											1.6	12.2		12.2																			28.00448	-81.89281	
35	9.50	OL	N		1.9											1.9	4.4		4.4																		27.99700	-81.91140		
38	8.56	OL	N		2.3											2.3	4.9		4.9																		27.99653	-81.92736		

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/18/23 Page 9 of 22 Typical Section No.: _____

W.P.I. No.:				Name:				Lanes: EXIT 9 EB OFF RAMP			
Fin. Proj. ID: 449688-1				From:				Shoulder Type and Condition:			
F.A. Proj. No.:				To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28		End MP: 17.10		Length: 8.82		Outside:	
Median Curbed (Y / N): N		Paved, Lawn, Other:						Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude								
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent						
				FC5																																				
68	0.05	RAMP	Y	1.0	1.5											2.5	8.6		8.6																		Exit 9 EB Off Ramp Crack Core 1	27.99595	-81.92836	
69	0.05	IR	N		1.3											1.3	8.3		8.3						Y	C	IB	L	F								Exit 9 EB Off Ramp Crack Core 2	27.99596	-81.92836	
70	0.21	RAMP	Y	1.0	1.0											2.0	10.6		10.6						Y	C	IB	S	P									Exit 9 EB Off Ramp Crack Core 2	27.99598	-81.92581
71	0.21	OR	N		1.5											1.5	4.1		4.1																			27.99595	-81.92581	

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/18/23 Page 10 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: EXIT 9 EB ON RAMP				
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:				
F.A. Proj. No.:		To:				Inside:				
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:			
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N				

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude		
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent
				FC5																														
72	0.23	RAMP	N	0.6	1.7										2.3	7.6		7.6									P					27.99609	-81.92029	
73	0.23	IR	N	1.1	0.8										1.9	3.7		3.7									G					27.99611	-81.92029	
74	0.39	RAMP	Y	0.9	2.2	1.3									4.4	15.2		15.2									F					27.99633	-81.91765	
75	0.39	OR	N		2.4										2.4	5.3		5.3									G					27.99630	-81.91765	

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/19/23 Page 11 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: EXIT 9 WB OFF RAMP			
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:			
F.A. Proj. No.:		To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:		
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude		
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent
				FC5																														
115	0.01	RAMP	Y	0.7	2.3	1.4									4.4	11.8		11.8										P					27.99679	-81.91761
116	0.01	OL	N		3.0										3.0	4.5		4.5										G					27.99680	-81.91761
117	0.17	RAMP	Y	0.6	1.4										2.0	8.2		8.2				Y	C	IB	M		P					27.99690	-81.92030	
118	0.17	IL	N		1.8										1.8	5.2		5.2										G					27.99688	-81.92030

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/19/23 Page 12 of 22 Typical Section No.: _____

W.P.I. No.:				Name:				Lanes: EXIT 9 WB ON RAMP			
Fin. Proj. ID: 449688-1				From:				Shoulder Type and Condition:			
F.A. Proj. No.:				To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28		End MP: 17.10		Length: 8.82		Outside:	
Median Curbed (Y / N): N		Paved, Lawn, Other:						Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude					
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent			
				FC5																																	
119	0.10	RAMP	Y	0.6	1.4											2.0	6.5		6.5																Exit 9 WB On Ramp Crack Core 1	27.99675	-81.92574
120	0.10	IL	N		2.2											2.2	6.7		6.7																Exit 9 WB On Ramp Crack Core 2	27.99673	-81.92574
121	0.13	RAMP	Y	0.3	1.8											2.1	10.2		10.2																	27.99670	-81.92651
122	0.13	OL	N		1.7											1.7	4.3		4.3																27.99673	-81.92651	

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/17/23 Page 13 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: EXIT 10 EB OFF RAMP			
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:			
F.A. Proj. No.:		To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:		
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude										
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent								
				FC5																																						
76	0.06	RAMP	Y	1.1	2.7	0.7									4.5	7.8		7.8																			EXIT 10 EB Off Ramp Crack Core 1	27.99865	-81.90550			
77	0.06	OR	N		1.8										1.8	3.6		3.6																				EXIT 10 EB Off Ramp Crack Core 2	27.99861	-81.90549		
78	0.09	RAMP	Y	1.1	2.0										3.1	8.4		8.4				Y	A	IB	S	P												EXIT 10 EB Off Ramp Crack Core 3	27.99870	-81.90503		
79	0.09	RAMP	Y	1.2	2.3										3.5	10.5		10.5				Y	A	IB	S	P												EXIT 10 EB Off Ramp Crack Core 4	27.99870	-81.90503		
80	0.13	RAMP	Y	0.9	1.9										2.8	6.4		6.4						A	IB	S	P												EXIT 10 EB Off Ramp Crack Core 4	27.99871	-81.90433	
81	0.20	RAMP	N	0.8	1.9										2.7	7.4		7.4						C	IB	M	P												EXIT 10 EB Off Ramp Crack Core 4	27.99862	-81.90331	
82	0.20	IR	N		1.6										1.6	4.8		4.8																						EXIT 10 EB Off Ramp Crack Core 4	27.99864	-81.90331

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/18/23 Page 14 of 22 Typical Section No.: _____

W.P.I. No.:				Name:				Lanes: EXIT 10 EB ON RAMP			
Fin. Proj. ID: 449688-1				From:				Shoulder Type and Condition:			
F.A. Proj. No.:				To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28		End MP: 17.10		Length: 8.82		Outside:	
Median Curbed (Y / N): N		Paved, Lawn, Other:						Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude		
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent
				FC5																														
83	0.07	RAMP	Y	0.8	1.2	1.3									3.3	8.2		8.2						Y	C	II	M	P				EXIT 10 EB On Ramp Crack Core 1	28.00058	-81.90041
84	0.07	IR	N	0.8	2.7										3.5	11.1		11.1										G					28.00059	-81.90039
85	0.51	RAMP	N	0.8	2.7										3.5	14.6		14.6					Y	C	II	M	P					EXIT 10 EB On Ramp Crack Core 2	28.00354	-81.89414
86	0.51	OR	N		2.1										2.1	16.3		16.3									G						28.00352	-81.89413

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/18/23 Page 15 of 22 Typical Section No.: _____

W.P.I. No.:				Name:				Lanes: EXIT 10 EB ON RAMP (LOOP)			
Fin. Proj. ID: 449688-1				From:				Shoulder Type and Condition:			
F.A. Proj. No.:				To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28		End MP: 17.10		Length: 8.82		Outside:	
Median Curbed (Y / N): N		Paved, Lawn, Other:						Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude			
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent	
				FC5																															
127	0.05	RAMP	Y	0.8	1.4	0.6										2.8	7.6		7.6										F					27.99898	-81.90168
128	0.05	OR	N		1.9											1.9	8.1		8.1										G					27.99899	-81.90170
129	0.18	RAMP	Y	1.1	1.7											2.8	8.2		8.2										P					27.99959	-81.90311
130	0.18	IR	N		1.6											1.6	5.5		5.5										G					27.99960	-81.90313

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/19/23 Page 16 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: EXIT 10 WB OFF RAMP			
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:			
F.A. Proj. No.:		To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:		
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Dist. Section	Comments	Latitude	Longitude			
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent	
				FC5																															
107	0.07	RAMP	Y	1.0	1.9	0.9										3.8	8.3		8.3										P				Exit 10 WB Off Ramp Crack Core 1	28.00233	-81.89908
108	0.07	OL	N		1.3											1.3	7.0		7.0										G					28.00235	-81.89908
109	0.19	RAMP	Y	0.8	2.4											3.2	9.1		9.1										P					28.00263	-81.90099
110	0.19	IL	N		1.2	1.4										2.6	8.6		8.6										G					28.00261	-81.90100

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/17/23 Page 17 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: EXIT 10 WB ON RAMP			
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:			
F.A. Proj. No.:		To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:		
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude					
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent			
				FC5																																	
111	0.04	RAMP	Y	0.8	2.0											2.8	12.6		12.6																Exit 10 WB On Ramp Crack Core 1	28.00078	-81.90288
112	0.04	OL	N		1.1	0.5										1.6	11.8		11.8																28.00079	-81.90289	
113	0.29	RAMP	Y	0.8	1.7											2.5	8.3		8.3																27.99908	-81.90641	
114	0.29	IL	N		1.6	0.7										2.3	9.1		9.1																27.99906	-81.90640	

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 4/17/23 & 4/18/23 Page 18 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: EXIT 10 WB ON RAMP (LOOP)			
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:			
F.A. Proj. No.:		To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:		
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway	Comments	Latitude	Longitude			
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent	
				FC5																															
123	0.07	RAMP	Y	0.8	1.1										1.9		7.1	7.1			1.9			C	II	S	P							28.00241	-81.90188
124	0.07	IL	N	1.8	1.3										3.1		6.1	6.1									G							28.00242	-81.90189
125	0.21	RAMP	Y	0.6	1.5	1.6									3.7	17.4	17.4				Y		C	II	M	P				EXIT 10 WB ON RAMP LOOP Crack Core 1			28.00129	-81.90101	
126	0.21	OL	N		1.0	0.6									1.6	6.1	6.1									G							28.00128	-81.90100	

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/18/23 Page 19 of 22 Typical Section No.: _____

W.P.I. No.:				Name:				Lanes: EXIT 14 EB OFF RAMP			
Fin. Proj. ID: 449688-1				From:				Shoulder Type and Condition:			
F.A. Proj. No.:				To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28		End MP: 17.10		Length: 8.82		Outside:	
Median Curbed (Y / N): N		Paved, Lawn, Other:						Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Crossthoop (%)	Distress	Comments	Latitude	Longitude			
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent	
				FC5																															
87	0.35	RAMP	Y	0.9	1.5			0.4	1.2							4.0	12.0		12.0														EXIT 14 EB Off Ramp Crack Core 1	28.01020	-81.85712
88	0.35	OR	N		1.7											1.7	5.5		5.5															28.01016	-81.85712
89	0.75	RAMP	Y	1.0	1.1			0.7	1.5							4.3	12.9		12.9															28.01027	-81.85042
90	0.75	IR	N		1.4			0.5	0.5							2.4	5.0		5.0															28.01030	-81.85041
91	1.17	RAMP	Y	0.9	2.0											2.9	11.9		11.9				Y	C	IB	S	P						EXIT 14 EB Off Ramp Crack Core 2	28.00954	-81.84382
92	1.19	RAMP	N		1.0	2.0										3.0	13.2		13.2			1.0		C	II	S	P						EXIT 14 EB Off Ramp Crack Core 3. Delimianiation at 1-inch	28.00958	-81.84348

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 4/18/23 & 4/19/23 Page 20 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: EXIT 14 EB ON RAMP			
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:			
F.A. Proj. No.:		To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:		
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude		
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent
				FC5																														
93	0.29	RAMP	N	0.6	1.2	1.6									3.4	9.0		9.0			1.5			L	II	M	P					28.01291	-81.83131	
94	0.29	OR	N		1.6										1.6	5.6		5.6									G					28.01293	-81.83129	
95	0.49	RAMP	Y	0.8	1.2	1.5									3.5	8.4		8.4									P					28.01557	-81.83237	
96	0.49	IR	N	0.9	1.1	1.7									3.7	9.8		9.8									G					28.01558	-81.83239	

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/18/23 Page 21 of 22 Typical Section No.: _____

W.P.I. No.:				Name:				Lanes: EXIT 14 WB OFF RAMP			
Fin. Proj. ID: 449688-1				From:				Shoulder Type and Condition:			
F.A. Proj. No.:				To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28		End MP: 17.10		Length: 8.82		Outside:	
Median Curbed (Y / N): N		Paved, Lawn, Other:						Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude			
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent	
				FC5																															
97	0.07	RAMP	Y	0.9	2.8											3.7	12.5		12.5									F						28.01734	-81.83235
98	0.07	OL	N		2.5											2.5	7.9		7.9									G						28.01735	-81.83238
99	0.30	RAMP	Y	0.8	1.0	1.8										3.6	13.5		13.5									P			EXIT 14 WB Off Ramp Crack Core 1			28.01425	-81.83317
100	0.30	IL	N		1.5	0.9										2.4	6.4		6.4									G						28.01426	-81.83314

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Ardaman & Associates, Inc. Date: 04/18/23 Page 22 of 22 Typical Section No.: _____

W.P.I. No.:		Name:				Lanes: EXIT 14 WB ON RAMP			
Fin. Proj. ID: 449688-1		From:				Shoulder Type and Condition:			
F.A. Proj. No.:		To:				Inside:			
County: Polk		SR No.: 570		Beg MP: 8.28	End MP: 17.10	Length: 8.82	Outside:		
Median Curbed (Y / N): N		Paved, Lawn, Other:				Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)												Base			Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cross Slope (%)	Driveway Slope	Comments	Latitude	Longitude				
				Top	SP2C	S1	S1	ARMI	S1							Core Lgth (in.)	LR	ABC	Total	Yes / No	Thickness	Depth (in.)	Full	Depth	Type								Class	Extent		
				FC5																																
101	0.06	RAMP	N	1.4	1.9										3.3	13.0		13.0			1.7												EXIT 14 WB ON RAMP CRACK Core 2	28.00978	-81.84310	
102	0.31	RAMP	Y	0.9	1.3			0.4	1.3						3.9	14.6		14.6															EXIT 14 WB ON RAMP CRACK Core 1	28.01032	-81.84709	
103	0.60	RAMP	Y	0.9	1.8			0.3	0.6						3.6	13.7		13.7			2.0													EXIT 14 WB ON RAMP CRACK Core 1	28.01086	-81.85153
104	0.60	OL	N		0.6	1.1									1.7	4.9		4.9																28.01088	-81.85153	
105	0.93	RAMP	Y	1.0	1.4			0.4	1.6						4.4	13.0		13.0																28.01065	-81.85691	
106	0.93	IL	N		1.5										1.5	5.1		5.1																28.01062	-81.85691	