

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Intertek-PSI Date: 10/17/23 Page 2 of 2 Typical Section No.: 1

W.P.I. No.:		Name: SR 528 Exit 3 and John Young Parkway				Lanes: L3, OL, LRTL			
Fin. Proj. ID: 449465-1		From: SR 528 Interchange				Shoulder Type and Condition:			
PSI Proj. No.: 7573161		To: South of Central Florida Parkway				Inside: Paved and Grass			
County: Orange		SR No.: CR431		Beg MP: 36.851	End MP: 37.833	Length: 0.982	Outside: Paved and Grass		
Median Curbed (Y / N): N		Paved, Lawn, Other: Paved, Lawn				Curb & Gutter (Y / N): N			

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)										Base					Stabilized Subgrade	Crack						Pvmt Cond	Depth (in.)	Cross Slope (%)	Cracks	Comments	Latitude	Longitude		
				Top	F125	SP	BIND								LR	ABC	SC	RCA		Total	Yes / No	Thickness	Depth	Fulfil	Type								Class	Extent
				FC5																														
John Young Parkway																																		
28	36.891	L3	X		1.5	2.1									3.6			12.7	12.7	Yes	-	-	-	-	-	-	F						28.40682	-81.42532
27	36.982	L3	X		1.4	2.1									3.5			12.5	12.5	Yes	-	-	-	-	-	-	F						28.40821	-81.42518
26	37.079	L3	X		1.8	2.3									4.1			12.3	12.3	Yes	-	-	-	-	-	-	F						28.40955	-81.42479
23	37.231	L3			1.5	4.0									5.5			12.3	12.3	Yes	-	-	-	-	-	-	F						28.41162	-81.42388
20	37.339	L3			1.6	3.8									5.4			13.3	13.3	Yes	-	-	-	-	-	-	F						28.41308	-81.42330
19	37.387	L3			1.6	2.6									4.2			12.5	12.5	Yes	-	-	-	-	-	-	F						28.41378	-81.42313
17	37.526	L3			1.5	2.1	0.6								4.2	13.5		13.5	13.5	Yes	-	4.2	Y	Br	III	M	P		Branch Crack 30 feet			28.41578	-81.42297	
11	37.833	L3	X	0.6		5.4									12.6	6.6		6.6	6.6	Yes	-	-	-	-	-	-	F						28.42022	-81.42302
13	37.745	L4	X	0.7		3.8									4.5	13.3		13.3	13.3	Yes	-	-	-	-	-	-	F		Delmination at 2.6 inches from the top			28.41895	-81.42303	
25	37.117	LRTL			1.0	3.0									4.0		12.8	12.8	Yes	-	-	-	-	-	-	F						28.41015	-81.42470	
24	37.163	LRTL	X		1.3	2.4	0.9								4.6		11.7	11.7	Yes	-	-	-	-	-	-	F						28.41068	-81.42435	
22	37.259	LRTL			1.3	1.9									3.2		12.0	12.0	Yes	-	-	-	-	-	-	F						28.41203	-81.42374	
21	37.303	LRTL	X		1.3	1.4									2.7		12.3	12.3	Yes	-	-	-	-	-	-	F						28.41260	-81.42347	
18	37.461	LRTL			1.7	3.1									4.8	12.7		12.7	12.7	Yes	-	4.8	Y	Tr	III	S	F		Transverse Crack 11 feet wide.			28.41482	-81.42302	
16	37.564	LRTL			0.9	3.0									3.9	13.5		13.5	13.5	Yes	-	-	-	-	-	-	F						28.41627	-81.42331
15	37.613	LRTL	X		1.4	1.6	0.5								3.5	14.0		14.0	14.0	Yes	-	-	-	-	-	-	F						28.41704	-81.42301
29	36.851	OL			1.3	2.3									3.6		12.5	12.5	Yes	-	-	-	-	-	-	F						28.40626	-81.42535	
14	37.715	OL			2.3	2.7									5.0	20.0		20.0	20.0	Yes	-	-	-	-	-	-	F						28.41853	-81.42305
12	37.759	OL		1.0		2.8									3.8	6.3		6.3	6.3	Yes	-	-	-	-	-	-	F						28.41915	-81.42305
11A	37.833	OL		1.0		3.5									10.0	5.5		5.5	5.5	Yes	-	-	-	-	-	-	F						28.42022	-81.42305

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
PAVEMENT EVALUATION CORING AND CONDITION DATA

Cored by: Intertek-PSI Date: 10/17/23 Page 1 of 2 Typical Section No.: 1

W.P.I. No.:		Name: SR 528 Exit 3 and John Young Parkway				Lanes: Ramp, IR, OR	
Fin. Proj. ID: 449465-1		From: MP 3		Shoulder Type and Condition:			
PSI Proj. No.: 7573161		To: MP 3		Inside: Paved and Grass			
County: Orange	SR No.: 528	Beg MP: 3.000	End MP: 3.200	Length: 0.200	Outside: Paved and Grass		
Median Curbed (Y / N): N	Paved, Lawn, Other: Paved, Lawn				Curb & Gutter (Y / N): N		

Core No.	Mile Post or Sta. No.	Lane	Wheel Path	Pavement Layer Type (in.)										Base				Stabilized Subgrade		Crack					Pvmt Cond	Depth (in.)	Cracks (%)	Cros Section	Comments	Latitude	Longitude		
				Top	F125	SP	BIND								LR	ABC	SC	RCA	Total	Yes / No	Thickness	Depth	Fulth	Type								Class	Extent
				FC5											Core Lgth (in.)							(in.)											
1	-0.087	RAMP R2	X	0.8		5.9						6.7	12.3				12.3	Yes	-	-	-	-	-	-	G							28.42099	-81.42745
5	0.012	RAMP R2	X	0.7		3.4						4.1	12.2				12.2	Yes	-	-	-	-	-	-	G							28.42092	-81.42581
3	-0.051	RAMP R1	X	0.8		2.7						3.5	12.5				12.5	Yes	-	-	-	-	-	-	G							28.42098	-81.42683
8	0.008	RAMP R1		0.6		3.8						4.4	12.3				12.3	Yes	-	-	-	-	-	-	G							28.42105	-81.42458
4	0.031	RAMP R1	X	0.8		3.6						4.4	12.0				12.0	Yes	-	-	-	-	-	-	G							28.42096	-81.42551
10	0.013	RAMP OR				1.7						1.7	6.5				6.5	Yes	-	-	-	-	-	-	G							28.42109	-81.42425
7	0.024	RAMP OR				2.0						2.0	6.5				6.5	Yes	-	-	-	-	-	-	G							28.42089	-81.42568
2	-0.073	RAMP OR				2.1						2.1	7.0				7.0	Yes	-	-	-	-	-	-	G							28.42095	-81.42724
6	0.004	RAMP IR				1.5						1.5	6.5				6.5	Yes	-	-	-	-	-	-	G							28.42099	-81.42539
9	0.006	RAMP IR				1.5						1.5	6.8				6.8	Yes	-	-	-	-	-	-	G							28.42111	-81.42443