FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 1 COUNTY = HARDEE

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T	AADT	SURFTYPE / ASTYPE / RW FY-P / RW FY-F	WKMX-P / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
06010000	0.000	4.955	R	1	1	60					CRACKING	8.0	6.5	6.5	3.5*	3.5*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0												
35 17				2	32.8	12400					RIDE	8.6	8.2	8.3	7.7	7.7	7.5	7.3	8.4	8.3	8.3	8.3	8.3	8.1												
CR 665(0.8R)						FC5M																														
4145471	0.000	4.952	C	2016		0213					CRACKING	10.0	10.0	10.0	9.5			10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5												
WATSON CIVIL CONSTRUCTION,(2020)									SPRIDE		RIDE	7.9	7.8	7.6	7.7			8.9	8.8	8.8	8.7	8.6	8.6	8.5	8.3												
06010000	4.955	9.315	R	1	1	65					CRACKING	8.0	4.5*	4.5*	4.5*	4.5*	2.0*	2.0*	10.0	10.0	10.0	10.0	10.0														
35 17				2	32.8	12400					RIDE	8.6	8.2	8.6	7.9	7.8	7.5	7.4	8.4	8.3	8.3	8.3	8.3														
CR 634(5.0R)						FC5																														
4206331	4.955	10.503	C	2011		0213					CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	7.0	6.5	4.0*												
AJAX PAVING INDUSTRIES OF (2015)									SPRIDE		RIDE		8.5	8.6	8.7	8.6	8.6	8.7	8.7	8.7	8.7	8.7	8.6	8.6	8.4												
06010000	11.165	11.753	R	1	1	55					CRACKING	8.0		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	6.5													
35 17				2	22.7	17900					RIDE	8.6		7.4	7.4	7.3	7.0	7.0	7.0	6.3*	6.9	7.1	7.2	7.1													
FLORIDA CRACKER TRAIL(11.2C)						FC3																														
											CRACKING	6.5	6.5	6.5	6.5	6.5	9.0	9.0	9.0	9.0	9.0	5.5*	5.5*	5.5*	4.0*												
		(2019)									RIDE	7.2	7.3	6.8	6.8	6.6	7.2	7.1	7.1	6.9	6.8	6.8	6.6	6.7	6.4*												
4462051	11.183	11.753	C	2027		0012																														
06010000	15.292	15.560	R	1	1	50					CRACKING	10.0	9.5	9.5	8.0	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0													
35 17				2	20.3	24000					RIDE	8.6	8.2	8.6	8.0	7.9		7.9	7.7	7.2	7.9	8.0	7.9	7.9													
KD REVELL RD(15.3R)						FC125M																														
4448831	15.269	15.930	C	2022		0012					CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	7.0	6.5	6.5	10.0	10.0	10.0	10.0	9.0												
AJAX PAVING INDUSTRIES OF (2023)									SPRIDE		RIDE	7.8	7.8	7.7	7.7	7.7	7.7	7.8	7.6	7.7	7.9	8.0	8.0	7.9	7.6												
06010000	15.560	15.882	R	1	1	55					CRACKING	10.0	9.5	9.5	8.0	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0													
35 17				2	20.3	24000					RIDE	8.6	8.2	8.6	8.0	7.9		7.9	7.7	7.2	7.9	8.0	7.9	7.9													
						FC5M																														
4448831	15.269	15.930	C	2022		0012					CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	7.0	6.5	6.5	10.0	10.0	10.0	10.0	8.5												
AJAX PAVING INDUSTRIES OF (2023)									SPRIDE		RIDE	7.8	7.8	7.7	7.7	7.7	7.7	7.8	7.6	7.7	7.9	8.0	8.0	8.1	7.9												
06010000	15.882	17.890	R	1	1	60					CRACKING	10.0	9.5	9.5	8.0	7.5	7.5	6.5	3.5*	3.5*	3.5*	10.0	10.0	10.0													
35 17				2	20.3	24000					RIDE	8.6	8.2	8.6	8.0	7.9	7.7	7.5	6.8	6.5	6.5	8.5	8.4	8.4													
HEARTLAND WAY(15.9R)						FC5																														
1940282	15.882	17.890	C	2009		0012					CRACKING	10.0	10.0	10.0	10.0	9.0	8.0	6.5	6.5	4.5*	4.5*	4.5*	2.0*	0.8*	0.0*												
PREFERRED MATERIALS, INC. (2011)											RIDE	8.3	8.1	8.5	8.5	8.5	8.5	8.4	8.2	8.3	8.3	8.2	8.0	7.9	7.7												
4462041	15.890	21.500	C	2027		0226																														
06010000	17.890	20.145	R	1	1	60					CRACKING	10.0	10.0	10.0	9.5	9.0	9.0	9.0	7.5	7.5	6.5	10.0	10.0	10.0													
35 17				2	21.0	19100					RIDE	8.9	8.1	8.9	8.3	8.2	8.2	8.0	7.4	7.3	7.6	8.5	8.5	8.4													
SAULS RD(18.7R)						FC5																														
1940192	17.890	20.145	C	2009		0012					CRACKING	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	5.5*	2.5*												
PREFERRED MATERIALS, INC. (2011)											RIDE	8.4	8.3	8.6	8.7	8.6	8.7	8.7	8.6	8.7	8.6	8.6	8.5	8.5	8.3												
4462041	15.890	21.500	C	2027		0226																														
06010000	20.145	21.500	C	1	1	40					CRACKING	7.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	8.5													
35 17				4	17.8	19400					RIDE	7.6	7.4	7.1	6.6	6.5	6.0	5.7		7.1	8.2	8.2	8.1	7.9													
BROWARD ST(20.2R)						FC95M																														
4172491	20.140	21.500	C	2007		0012					CRACKING	8.5	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	5.0*	5.0*	5.0*	4.9*	4.8*	2.5*												
LANE CONSTRUCTION CORPORAT(2009)											RIDE	7.8	7.3	7.3	7.6	7.5	7.4	7.2	7.1	6.9	6.7	6.5	6.6	6.4	6.1												
4462041	15.890	21.500	C	2027		0226																														
06010000	17.890	20.145	L	1	1	60					CRACKING	10.0	9.5	9.5	9.5	7.0	6.5	6.5	3.5*	3.5*	3.5*	10.0	10.0	10.0													
35 17				2	21.0	19100					RIDE	8.7	8.0	8.6	8.0	7.9	7.7	7.6	7.4	6.8	7.2	8.5	8.5	8.4													
SR 62(17.9L)						FC5																														
1940192	17.890	20.145	C	2009		0012					CRACKING	10.0	10.0	10.0	10.0	9.0	7.5	7.5	6.5	3.5*	3.5*	3.5*	2.8*	2.1*	0.0*												
PREFERRED MATERIALS, INC. (2011)											RIDE	8.3	8.1	8.5	8.6	8.5	8.5	8.6	8.5	8.5	8.4	8.2	8.1	8.0	7.8												
4462041	15.890	21.500	C	2027		0226																														
06010000	15.882	17.890	L	1	1	60					CRACKING	10.0	9.5	9.5	9.5	7.0	6.5	6.5	3.5*	3.5*	3.5*	10.0	10.0	10.0													
35 17				2	20.3	24000					RIDE	8.7	8.0	8.6	8.0	7.9	7.7	7.6	7.4	6.8	7.2	8.4	8.5	8.4													
REA RD(16.1C)						FC5																														
1940282	15.882	17.890	C	2009		0012					CRACKING	10.0	10.0	10.0	10.0	9.0	7.5	7.5	6.5	5.5*	3.5*	3.5*	1.8*	2.3*	0.0*												
PREFERRED MATERIALS, INC. (2011)											RIDE	8.3	7.9	8.4	8.5	8.5	8.5	8.4	8.2	8.2	8.0	7.8	7.3	7.0	6.8												
4462041	15.890	21.500	C	2027		0226																														
06010000	15.542	15.882	L	1	1	55					CRACKING	10.0	9.5	9.5	9.5	7.0	6.5	10.0	10.0	10.0	10.0	10.0	9.5	8.0													
35 17				2	20.3	24000					RIDE	8.7	8.0	8.6	8.0	7.9	7.7	7.7	7.6	6.8	7.6	7.6	7.6	7.4													
TROPICANA RD(15.8L)						FC5M																														
4448831	15.269	15.930	C	2022		0012					CRACKING	7.0	7.0	7.0	7.0	6.0*	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	8.5												
AJAX PAVING INDUSTRIES OF (2023)									SPRIDE		RIDE	7.4	6.7	7.0	7.1	7.1	7.1	6.9	7.6	7.4	7.9	8.0	8.0	8.3	8.1												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 1 COUNTY = HARDEE

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T	AADT	SURFTYPE	WKMX-P	WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
06010000	15.292	15.542	L	1	1	50						CRACKING	10.0	9.5	9.5	9.5	7.0	6.5	10.0	10.0	10.0	10.0	10.0	9.5	8.0												
35 17			2	20.3				24000	RIDE				8.7	8.0	8.6	8.0	7.9	7.7	7.7	7.6	6.8	7.6	7.6	7.6	7.4												
BELL ST(15.3L)									FC125M																												
4448831	15.269	15.930	C	2022				0012	CRACKING				7.0	7.0	7.0	7.0	6.0*	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.0												
AJAX PAVING INDUSTRIES OF				(2023)					SPRIDE				7.4	6.7	7.0	7.1	7.1	7.1	6.9	7.6	7.4	7.9	8.0	8.0	7.6	7.3											
06010000	11.165	11.753	L	1	1	55						CRACKING	8.0		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	6.5												
35 17			2	22.7				17900	RIDE				8.6		7.8	7.8	7.7	7.6	7.7	7.6	6.5	7.4	7.1	7.5	7.5												
FLORIDA CRACKER TRAIL(11.2C)									FC3																												
												CRACKING	6.5	6.5	6.5	6.5	6.5	9.0	9.0	9.0	9.0	7.0	5.5*	5.5*	3.5*	2.0*											
				(2019)					RIDE				7.3	6.9	6.5	6.8	6.6	6.9	6.8	6.7	6.6	6.5	6.6	6.4*	6.4*	6.1*											
4462051	11.183	11.753	C	2027				0012																													
06010000	4.955	9.315	L	1	1	65						CRACKING	8.0	4.5*	4.5*	4.5*	4.5*	2.0*	2.0*	10.0	10.0	10.0	10.0	10.0													
35 17			2	32.8				12400	RIDE				8.6	8.2	8.6	7.9	7.8	7.5	7.4	8.4	8.3	8.3	8.3	8.3													
BEN HILL GRIFFIN RD(5.0L)									FC5																												
4206331	4.955	10.503	C	2011				0213	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	6.8	6.8	4.5*												
AJAX PAVING INDUSTRIES OF				(2015)					SPRIDE					8.2	8.5	8.6	8.6	8.5	8.7	8.6	8.7	8.7	8.7	8.6	8.6	8.4											
06010000	0.000	4.955	L	1	1	60						CRACKING	8.0	6.5	6.5	3.5*	3.5*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0													
35 17			2	32.8				12400	RIDE				8.6	8.2	8.3	7.7	7.7	7.5	7.3	8.4	8.3	8.3	8.3	8.3	8.1												
OAK LN(0.4L)									FC5M																												
4145471	0.000	4.952	C	2016				0213	CRACKING				10.0	10.0	10.0	9.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5												
WATSON CIVIL CONSTRUCTION,				(2020)					SPRIDE				7.9	7.8	7.6	7.7			9.1	9.0	9.0	9.0	8.9	8.9	8.9	8.7											
06010001	0.000	0.608	R	1	1	55						CRACKING																										
35 17			2	24.8				19800	RIDE																												
COLLEGE LN(0.0C)									FC5M																												
												CRACKING							10.0	10.0	10.0	10.0	9.0	7.9	7.3	5.5*											
				(2020)					RIDE										8.5	8.5	8.4	8.5	8.2	8.3	8.2	8.0											
06010001	0.608	1.737	R	1	4	40						CRACKING																										
35 17			2	24.8				19800	RIDE																												
E SEVENTH ST(1.2R)									LDG																												
												CRACKING							9.3	9.5	9.5	9.5	9.4	9.4	9.4	9.0											
				(2020)					RIDE										8.9	9.1	8.9	8.9	8.9	8.9	8.9	8.8											
06010001	1.737	1.843	R	1	1	45						CRACKING																										
35 17			2	24.8				19800	RIDE																												
TURNOUT(1.8R)									FC125M																												
												CRACKING							5.5*	10.0	10.0	10.0	10.0	10.0	9.0	7.5											
				(2021)					RIDE										5.6	6.6	6.8	6.5	6.3	6.3	6.1	5.8											
06010001	1.695	1.843	L	1	1	45						CRACKING																										
35 17			2	24.8				19800	RIDE																												
TURNOUT TO SUWANNEE(1.8L)									FC125M																												
												CRACKING							5.5*	10.0	10.0	10.0	10.0	10.0	9.3	8.0											
				(2021)					RIDE										5.7	7.4	7.1	7.2	7.2	7.0	7.1	6.8											
06010001	0.608	1.695	L	1	4	40						CRACKING																										
35 17			2	24.8				19800	RIDE																												
W NINTH ST(0.9L)									LDG																												
												CRACKING							9.3	9.5	9.5	9.4	9.4	9.3	9.4	9.0											
				(2020)					RIDE										8.9	9.1	8.9	8.9	9.0	9.0	9.0	8.9											
06010001	0.000	0.608	L	1	1	55						CRACKING																										
35 17			2	24.8				19800	RIDE																												
COLLEGE LN(0.0L)									FC5M																												
												CRACKING							10.0	10.0	10.0	10.0	9.0	8.1	7.1	5.5*											
				(2020)					RIDE										8.2	8.1	8.2	8.2	8.1	8.1	8.0	7.8											
06010101	0.000	0.366	C	1	1	55						CRACKING										10.0	10.0	10.0	10.0												
35 17			2	12.5				13500	RIDE													7.6	7.7	7.6	7.6											
RV PARK ENTRANCE(0.0R)									FC4																												
												CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.0	7.0	6.5	7.0	5.0*											
				(2010)					RIDE				7.6	7.2	7.6	7.6	7.5	7.5	7.4	7.4	7.4	7.4	7.4	7.4	7.2	6.9											
4462051	0.000	3.450	C	2027				0012																													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 1 COUNTY = HARDEE

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN	SYS	TYP	SPD	%T	AADT	SURFTYPE / ASTYPE / WKMX-P / WKMX-F	DISTRESS RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
06010101	0.366	1.240	C	1	1	55				CRACKING										10.0	10.0	10.0	10.0													
35 17			3	12.5		13500				RIDE										7.6	7.7	7.6	7.6													
SIDE ROAD(0.5L)									FC2																												
										CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.0	7.0	6.5	6.5													3.5*
										RIDE (2010)	7.6	7.2	7.6	7.6	7.5	7.5	7.4	7.4	7.4	7.4	7.4	7.4	7.7														7.5
4462051	0.000	3.450	C	2027		0012																															
06010101	1.240	3.468	C	1	1	45				CRACKING										10.0	10.0	10.0	10.0													
35 17			3	12.5		13500				RIDE										7.6	7.7	7.6	7.6													
WILL DUKE RD(1.4C)									FC4																												
										CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.0	7.0	6.5	8.0													6.0*
										RIDE (2010)	7.6	7.2	7.6	7.6	7.5	7.5	7.4	7.4	7.4	7.4	7.4	7.4	7.2														6.9
4462051	0.000	3.450	C	2027		0012																															
06010102	0.000	2.180	C	1	1	45				CRACKING										10.0	10.0	10.0	10.0													
35 17			3	13.9		13500				RIDE										7.7	7.7	7.7	7.7													
BELL ST(0.0R)									FC4																												
										CRACKING	9.0	9.0	9.0	9.0	9.0	7.0	6.0*	5.5*	5.5*	5.5*	5.5*	5.5*	5.0*													3.0*
										RIDE (2010)	7.7	7.2	7.3	7.4	7.4	7.1	7.0	6.9	7.0	6.9	6.4	6.4	6.3														6.0
4462051	0.010	3.530	C	2027		0012																															
06010102	2.180	3.136	C	1	1	55				CRACKING										10.0	10.0	10.0	10.0													
35 17			3	13.9		13500				RIDE										7.7	7.7	7.7	7.7													
CAUSEY RD(2.5R)									FC3																												
										CRACKING	9.0	9.0	9.0	9.0	9.0	7.0	6.0*	5.5*	5.5*	5.5*	4.5*	4.7*	4.4*													2.0*
										RIDE (2010)	7.7	7.2	7.3	7.4	7.4	7.1	7.0	6.9	7.0	6.9	7.4	7.4	7.6														7.3
4462051	0.010	3.530	C	2027		0012																															
06010102	3.136	3.539	C	1	1	55				CRACKING										10.0	10.0	10.0	10.0													
35 17			3	13.9		13500				RIDE										7.7	7.7	7.7	7.7													
RV PARK(3.5C)									DGFC																												
										CRACKING	9.0	9.0	9.0	9.0	9.0	7.0	6.0*	5.5*	5.5*	5.5*	4.5*	4.7*	4.1*													2.0*
										RIDE (2010)	7.7	7.2	7.3	7.4	7.4	7.1	7.0	6.9	7.0	6.9	7.4	7.4	6.5														6.2*
4462051	0.010	3.530	C	2027		0012																															
06020000	0.000	3.317	C	1	1	60				CRACKING	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0													
62			2	26.3		5100				RIDE	7.6	7.4	7.4	7.1		8.0	8.0	8.0	8.0	8.1	8.1	8.0	8.0													
ALLAPATTAH RD(2.8R)									FC95																												
1940712	0.094	3.340	C	2004		0012				CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	7.5	7.0	7.0	7.0	7.0	6.9	6.7													4.0*
PREFERRED MATERIALS, INC. (2006)										RIDE	7.7	7.2	7.5	7.8	7.6	7.7	7.5	7.3	7.4	7.2	7.3	7.4	7.3													7.0
06020000	3.317	14.280	C	1	1	60				CRACKING	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0													
62			2	17.2		6000				RIDE	7.8	7.2	7.3	6.7	6.4*	5.7*	5.6*	8.2	8.1	8.2	8.2	8.2	8.1													
BUELL LN(4.6L)									FC125																												
1940372	3.317	14.136	C	2006		0012				CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.0	7.0	7.0	7.0	6.6													4.0*
LANE CONSTRUCTION CORPORAT(2008)									SPRIDE	RIDE	7.9	7.5	7.7	8.1	8.1	8.1	8.0	7.9	7.9	7.8	7.8	7.9	7.9													7.6
06030000	0.000	6.735	C	1	1	60				CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0													
636			2	11.1		5100				RIDE	8.0	7.7	8.0	7.0	6.8		7.9	7.7	7.5	7.6	7.8	7.8	7.7													
SR 35(0.0C)									FC125M																												
4415181	0.006	6.732	C	2021		0012				CRACKING	9.5	9.5	8.0	7.0	6.0*	6.0*	6.0*	3.0*	3.0*	10.0	10.0	9.7	9.6													8.5
HUBBARD CONSTRUCTION COMPA(2023)									SPRIDE	RIDE	7.5	7.1	6.6	7.4	7.4	7.2	7.0	6.6	6.8	8.1	8.0	7.9	7.8													7.5
06030000	6.735	7.065	C	1	1	60				CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0													
636			2	18.7		9600				RIDE	8.0	7.7	8.0	7.0	6.8		7.9	7.7	7.5	7.6	7.8	7.8	7.7													
SR 64(7.0R)									FC125M																												
										CRACKING	9.5	9.5	8.0	7.0	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	8.5													7.5
										RIDE (2026)	7.5	7.1	6.6	7.4	7.6	7.5	7.4	7.2	7.3	7.3	7.2	7.2	6.6														6.3*
06030000	7.065	10.367	C	1	7	60				CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0													
64			2	18.7		9600				RIDE	8.4	8.1	8.5	8.1	8.1	7.9	8.0	8.0	7.9	7.8	7.8	7.5	7.4													
PRESCOTT RD(7.1R)									FC125H																												
4462061	7.060	10.367	C	2024		0012				CRACKING	7.0	7.0	7.0	7.0	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	10.0													9.0
AJAX PAVING INDUSTRIES OF (2026)									SPRIDE	RIDE	7.5	7.2	6.8	7.6	7.6	7.5	7.4	7.2	7.3	7.3	7.2	7.2	8.0													7.7
06030000	10.367	15.932	C	1	1	60				CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0													
64			2	16.6		9000				RIDE	8.7	8.2	8.7	8.1	8.1	8.1	8.0	8.0	7.8	7.9	7.9	8.8	8.7													
MORGAN GRICE RD(10.4L)									FC125M																												
4236371	10.367	15.932	C	2011		0012				CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.0	7.0	6.0*	6.0*	5.5*													3.5*
AJAX PAVING INDUSTRIES OF (2012)										RIDE	8.5	8.1	7.4	8.4	8.4	8.3	8.2	8.0	8.1	8.0	8.0	8.0	8.0													7.7

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 1 COUNTY = HARDEE ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS / %T / RW / FY-P / FY-F	TYP / AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	SPD	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
06050000	0.000	11.815	C	1	1	60	CRACKING	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0															
64			2	25.2	5400		RIDE	8.2	7.8	8.0	7.0	8.1	8.0	8.0	8.0	7.9	7.9	7.9	7.9	7.8															
ROY RD(1.2L)							FC125M																												
4365871	0.000	8.756	C	2018	0012		CRACKING	6.5	6.5	6.5	6.5	6.5	5.5*		10.0	10.0	10.0	10.0	8.8	8.4	7.0															
AJAX PAVING INDUSTRIES OF			(2021)				SPRIDE	7.6	7.2	7.0	7.3	7.1	6.9		8.4	8.4	8.3	8.3	8.2	8.2	7.9															
06050000	11.815	16.570	C	1	1	60	CRACKING	4.0*	4.0*	2.0*	2.0*		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0															
64			2	25.2	5400		RIDE	6.9	6.5	6.8	5.7*		8.2	8.1	8.0	7.8	7.8	7.8	7.7	7.7																
OAK GROVE CEM RD(12.5R)							FC125M																												
4415111	11.816	15.778	C	2023	0012		CRACKING	8.0	8.0	8.0	8.0	6.0*	6.0*	6.0*	3.0*	3.0*	3.0*	3.0*	10.0	9.3	8.5															
AJAX PAVING INDUSTRIES OF			(2025)				SPRIDE	7.5	7.2	6.9	7.1	7.0	6.9	6.7	6.4*	6.4*	5.9*	6.1*	8.0	8.0	7.7															
06050000	16.570	21.100	C	1	1	60	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5															
64			2	22.3	7500		RIDE	8.4	7.9	8.6	8.3	8.2	8.1	8.1	8.0	7.9	7.9	7.8	7.7	7.7															
TURNOUT(16.6L)							FC125R																												
1940811	16.810	23.972	C	2000	0221		CRACKING	9.5	9.5	9.5	9.5	9.5	8.0	7.0	6.0*	5.5*	5.5*	5.5*	5.5*	5.9*	3.0*															
APAC-FLORIDA, INC			(2001)		S		RIDE	7.6	7.4	7.2	7.7	7.7	7.3	7.2	7.1	7.1	6.9	6.9	6.7	6.7	6.4*															
4489251	16.703	22.780	C	2025	0012																														
06050000	21.100	22.780	C	1	1	60	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.0	9.0	9.0	9.0	9.0	9.0	9.0															
64			2	20.9	4600		RIDE	8.4	7.9	8.6	8.3	8.2	8.1	8.1	8.1	7.9	8.1	7.8	7.8	7.8															
STEVE RD(21.5R)							FC125																												
1940811	16.810	23.972	C	2000	0221		CRACKING	9.0	9.0	9.0	9.0	9.0	8.0	8.0	6.5	6.5	6.5	6.5	6.3*	5.7*	2.5*															
APAC-FLORIDA, INC			(2001)		S		RIDE	7.7	7.5	6.8	7.7	7.7	7.5	7.4	7.3	7.1	6.9	7.0	6.8	6.8	6.5															
4489251	16.703	22.780	C	2025	0012																														
06050000	22.780	23.867	C	1	1	60	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5															
64			2	20.9	4600		RIDE	8.4	7.9	8.6	8.3	8.2	8.1	7.8	7.9	7.3	7.2	7.2	7.3	7.7															
CECIL DURRANCE RD(23.1C)							FC125																												
1940811	16.810	23.972	C	2000	0221		CRACKING	9.5	9.5	9.5	9.5	9.5	9.0	9.0	7.0	7.0	7.0	7.0	7.0	6.7	3.5*															
APAC-FLORIDA, INC			(2001)		S		RIDE	7.6	7.0	7.2	7.8	7.6	7.4	7.3	7.1	7.1	7.1	7.1	7.0	6.9	6.6															
06080000	0.071	2.173	C	1	8	60	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.5		10.0	10.0	10.0	9.5															
66			2	33.4	6200		RIDE	8.3	7.6	8.3	7.9	7.8	7.6	7.5	7.4		8.1	8.1	7.9	7.9															
OAK ST(0.1C)							FC125M																												
1940692	0.011	2.173	C	2008	0012		CRACKING	9.5	9.5	9.5	9.5	9.5	7.0	6.0*	5.5*	5.5*	5.5*	5.0*	3.5*																
BETTER ROADS INC.			(2010)				RIDE	7.8	7.4	7.2	7.2	7.1	7.0	6.6	6.4*	6.2*	5.8*	5.9*	5.7*															
4462291	0.147	7.961	C	2024	0012																														
06080000	2.173	7.933	C	1	8	60	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.5	6.5	6.5	6.5	6.5	6.5															
66			2	33.4	6200		RIDE	8.3	7.6	8.3	7.9	7.8	7.6	7.5	7.4	7.9	7.6	7.6	7.5	7.3															
CHARLEY ANDERSON RD(2.2L)							FC125M																												
4272851	2.943	8.731	C	2013	0012		CRACKING		10.0	10.0	10.0	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*																
AJAX PAVING INDUSTRIES OF			(2015)				RIDE		8.7	8.5	8.8	8.5	8.3	8.1	7.9	7.7	7.2	6.8	6.8															
4462291	0.147	7.961	C	2024	0012																														
06080000	7.933	15.692	C	1	7	60	CRACKING	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5															
66			2	33.4	6200		RIDE	7.1	6.7	6.5	5.1*	8.5	8.4	8.4	8.3	8.1	8.3	8.3	8.2	8.2															
CECIL LANGFORD RD(8.2R)							FC125M																												
4489391	7.952	15.682	C	2025	0226		CRACKING	9.5	9.5	9.5	9.5	9.5	8.0	7.0	6.0*	6.0*	6.0*	5.5*	4.7*	10.0	9.0															
AJAX PAVING INDUSTRIES OF			(2026)				SPRIDE	8.3	7.6	8.0	8.3	8.3	8.2	8.1	8.0	7.9	7.9	7.9	7.8	8.3	8.0															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).