FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / %T / RW FY-P / FY-F	SYS / AADT / WKMX-P / WKMX-F	TYP / SURFTYPE / ASTYPE	SPD	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15002000	0.000	0.064	R	4	4	50	CRACKING	7.0	9.4	9.4	9.4	9.4	9.4		9.4	9.5	9.1	9.5	9.4	9.4														
592 I375	0.0	0.1	2	18.5	17000		RIDE	6.3*	6.1*	5.8*	7.4		8.0		7.8	8.1	8.1	7.9	8.0	7.9														
I 275 SB(0.0C)					LDG																													
							CRACKING	9.4	9.4	9.4	9.4	9.4	9.4	9.3	9.4	9.0	9.0	9.4	9.0	9.5	9.0													
				(2008)			RIDE	7.9	7.8	8.3	8.1	8.3	8.1	8.3	8.4	8.3	8.3	8.3	8.4	8.4	8.3													
15002000	0.501	1.166	R	4	2	50	CRACKING	8.8	6.9	7.1	6.9	6.7	6.6		8.2	8.2	8.2	8.1	8.2	8.6														
592 I375	0.5	1.2	2	4.0	24500		RIDE	6.8	6.5	6.1*	5.7*		5.6*		7.3	7.5	7.6	7.8	7.7	7.7														
					LDG																														
							CRACKING	8.6	8.6	8.2	8.2	8.2	8.2	8.0	8.1	7.7	7.7	7.6	7.6	8.4	7.5													
				(2001)			RIDE	7.6	7.7	7.9	7.8	7.7	7.7	7.8	7.8	7.8	7.7	7.7	7.6	8.2	8.1													
4458651	0.112	1.220	C	2023	0227																													
15002000	1.166	1.220	C	4	2	30	CRACKING		4.5*	3.2*	3.2*	0.0*	0.0*		9.4	8.5	7.4	8.2	8.2	4.3*														
592 I375	1.2	1.2	2	4.0	14500		RIDE		5.8	8.4	5.0*		4.6*		6.0	6.8	6.7	7.4	6.5	6.5														
I 375 WB(1.2L)					CONC																													
4087301	0.994	1.318	C	2006	0227		CRACKING	4.3*	4.3*	6.6	6.5	6.4*	8.2	7.6	7.6	7.3	6.3*	5.6*	6.8	7.1	6.5													
KIEWIT INFRASTRUCTURE SOUT				(2008)			RIDE	6.0	6.0	7.3	7.5	7.4	6.8	7.5	7.4	7.7	7.6	7.4	7.5	7.2	7.1													
4458651	0.112	1.220	C	2023	0227																													
15002000	0.899	1.166	L	4	2	50	CRACKING	8.0												8.8														
592 I375	0.9	1.2	2	4.0	24500		RIDE	6.6												6.4*														
I 375 WB(1.2L)					LDG																													
							CRACKING	8.8	8.8	8.7	8.7	8.5	8.5	8.3	8.3	8.8	8.7	8.4	8.4	8.3	7.5													
				(2013)			RIDE	6.4*	6.5	7.6	7.7	7.4	6.7	7.7	7.4	7.2	7.0	7.2	6.8	7.7	7.6													
4458651	0.112	1.220	C	2023	0227																													
15002000	0.312	0.899	L	4	2	50	CRACKING	8.0	7.4	7.6	7.6	7.4	7.4		9.1	9.0	8.7	8.9	8.7	8.4														
592 I375	0.3	0.9	3	4.0	38500		RIDE	6.6	6.8	6.7	6.2*		6.1*		7.5	7.9	7.8	8.2	8.1	7.8														
					LDG																														
4087301	0.303	0.992	C	2006	0227		CRACKING	8.4	8.5	8.4	8.4	8.4	8.2	8.2	8.2	8.9	8.5	8.2	7.7	8.7	8.0													
KIEWIT INFRASTRUCTURE SOUT				(2008)			RIDE	8.1	8.2	8.0	8.2	8.0	7.7	8.2	8.0	8.1	8.0	8.1	7.7	8.5	8.4													
4458651	0.112	1.220	C	2023	0227																													
15002000	0.000	0.312	L	4	2	50	CRACKING	6.0*	9.4	8.8	8.8	8.7	8.7		9.5	9.0	9.0	8.5	8.9	8.9														
592 I375	0.0	0.3	2	4.0	38500		RIDE	6.9	6.9	6.1*	7.7		6.7		7.8	8.3	7.9	8.0	7.7	7.9														
I 275 SB(0.0C)					LDG																													
							CRACKING	8.8	8.7	8.7	8.6	8.8	8.8	8.7	8.7	8.8	8.9	8.8	8.3	8.6	8.0													
				(2008)			RIDE	7.8	8.0	8.2	8.3	7.9	7.9	8.1	8.1	8.1	7.9	7.8	7.3	8.3	8.2													
4458651	0.112	1.220	C	2023	0227																													
15003000	0.298	1.285	R	4	4	50	CRACKING	8.4	7.2	7.3	6.9	6.7	6.6		6.3*	8.6	8.4	8.5	8.3	8.2														
594 I175	0.3	1.3	2	4.0	28500		RIDE	6.8	7.1	6.8	6.5	6.4*	6.3*		6.0*	6.9	7.4	7.7	7.7	7.7														
FIFTH AVE S(1.2R)					LDG																													
4087261	0.607	1.114	C	2007	0227		CRACKING	8.0	7.9	7.7	7.7	7.8	7.8	7.5	7.1	6.4*	6.1*	5.8*	5.7*	5.2*	4.5*													
PHOENIX CONSTRUCTION SERVI				(2009)			RIDE	7.7	7.8	8.0	8.0	7.9	7.9	7.8	7.9	7.9	7.8	7.7	7.7	7.7	7.6													
4458641	0.298	1.285	C	2025	0227																													
15003000	1.285	1.372	C	1	1	30	CRACKING	8.5	7.2	7.3	7.0	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0														
594	1.3	1.4	4	4.0	9000		RIDE	6.7	7.1	6.8																								
4 ST S(1.3R)					DGFC																													
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.3	5.0*													
				(2010)			RIDE													3.7*	3.3*													
15003000	0.298	1.285	L	4	4	50	CRACKING	8.5	7.7	7.6	7.3	7.2	7.0		7.2	8.4	8.3	8.2	8.5	8.1														
594 I175	0.3	1.3	2	4.0	28500		RIDE	6.7	6.8	6.6	6.0*	6.2*	5.9*		6.2*	7.3	7.5	7.6	7.4	7.5														
FOURTH ST S(1.3L)					LDG																													
							CRACKING	7.9	7.7	7.8	7.7	7.6	7.4	7.4	7.3	6.8	6.8	6.6	6.6	6.3*	5.0*													
				(1983)			RIDE	7.2	7.5	7.7	7.5	7.6	7.7	7.8	7.7	7.6	7.7	7.4	7.4	7.5	7.4													
4458641	0.298	1.285	C	2025	0227																													
15007000	0.000	3.058	R	1	1	40	CRACKING	10.0	9.0	7.0	7.0	7.0	6.5	7.5	6.5	6.5	6.5	6.5	6.5	10.0														
595 A19			3	4.0	32000		RIDE	7.3	7.5	7.4	6.4	6.4	6.4	6.0	6.3	6.6	6.4	6.3	6.2	8.0														
SR-686/E BAY DR(0.0R)					FC125R																													
4168361	0.000	2.947	C	2011	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	8.0	7.3	5.5*													
R. E. PURCELL CONSTRUCTION				(2013)		SPR	RIDE	7.9	7.6	7.8	7.8	7.6	7.7	7.6	7.5	7.5	7.4	7.2	7.3	7.3	6.9													
15007000	3.058	3.785	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	6.5	6.5	6.5														
60			2	4.0	42500		RIDE	7.0	6.8	6.9	6.9	6.5	6.6	6.3	6.4	6.2	6.1	6.0	6.0	6.1														
LINCOLN AVE(3.1R)					FC125A																													
4290071	3.063	3.550	C	2014	0012		CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.9	9.0	7.0													
PREFERRED MATERIALS, INC.				(2015)			RIDE	6.2	7.6	7.4	7.4	7.4	7.2	7.0	6.9	6.8	6.9	6.8	6.8	6.6	6.2													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T	AADT	DISTRESS / RATINGS / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2031 (PMRS)
15007000	3.058	3.785	L	1	1	40			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	
60			2	4.0				42500	RIDE	8.1	8.0	7.9	7.4	7.5	7.3	6.6	7.0	6.9	7.0	6.7	6.2	6.5	
S LINCOLN AVE(3.1L)									FC125A														
4290071	3.063	3.550	C	2014				0012	CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.2	8.1	6.0*
PREFERRED MATERIALS, INC. (2015)									RIDE	6.1	7.8	7.7	7.6	7.4	7.6	7.4	7.5	7.5	7.4	7.2	7.3	7.4	7.0
15007000	0.000	3.058	L	1	1	40			CRACKING	10.0	10.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	10.0	
595 A19			3	4.0				32000	RIDE	7.6	7.6	7.4	6.6	6.5	6.4	6.2	6.1	6.5	6.3	6.3	6.1	7.5	
W BAY DR(0.0L)									FC125R														
4168361	0.000	2.947	C	2011				0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	8.0	8.0	7.8	7.3	5.5*
R. E. PURCELL CONSTRUCTION(2013)									SPRIDE	7.5	7.1	7.6	7.6	7.4	7.1	7.3	7.2	7.2	7.0	6.8	7.0	6.8	6.4
15009000	0.000	0.964	R	1	1	40			CRACKING	10.0	10.0	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586			1	8.1				14600	RIDE	6.7	6.3	6.5	6.3	6.1		7.3	8.0	8.0	7.5	7.8	7.7	7.4	
BAYSHORE BLVD(0.0C)									FC125														
2571381	0.000	0.993	C	2004				0221	CRACKING	8.5	8.5	8.5	8.5	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	4.4*	4.2*	1.5*
R. E. PURCELL CONSTRUCTION(2007)									SPRIDE	7.5	7.3	7.1	7.3	7.0	6.9	7.1	6.9	7.1	6.8	6.8	7.0	6.5	6.1
4480411	0.323	2.341	C	2026				0012															
15009000	0.964	2.325	R	1	1	45			CRACKING	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586			2	8.1				26500	RIDE	6.4*	6.4*	6.1*	6.9	7.1		7.5	7.7	7.6	7.6	7.5	7.4	7.3	
CARDINAL RD(1.1R)									FC125														
2568151	1.296	2.334	C	2004				0213	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	8.5	7.0	6.0*	6.0*	6.0*	5.9*	5.8*	3.5*
R. E. PURCELL CONSTRUCTION(2007)									SPRIDE	7.3	7.3	6.8	6.6	6.9	6.5	6.6	6.4	6.5	6.5	6.4	6.4	6.4	6.0
4480411	0.323	2.341	C	2026				0012															
15009000	2.325	2.840	R	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586			3	8.1				33500	RIDE	7.3	7.7	7.0	6.9	6.8	6.5	6.9	7.0	6.4	6.3	6.2	6.3	6.1	
SR 55(2.6C)									FC125														
									CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0
		(2020)							RIDE	6.4	6.6	6.4	6.3	6.6	6.3	7.3	7.4	7.3	7.5	7.4	7.3	7.3	6.9
15009000	2.840	4.298	R	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	
586			3	8.1				33500	RIDE	8.3	8.1	8.0	7.5	7.5	7.4	7.3	7.3	7.2	7.1	7.0	7.2	6.6	
LAKE SHORE LN(3.1R)									FC125M														
4416571	2.840	4.298	C	2022				0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	8.5	7.0	6.0*	6.0*	6.0*	10.0	10.0	9.0
PREFERRED MATERIALS, INC. (2025)									SPRIDE	6.8	6.5	7.1	7.2	7.1	6.9	7.1	6.9	6.9	6.8	6.6	8.3	8.3	7.9
15009000	4.298	5.312	R	1	8	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	
586			3	8.1				19900	RIDE	8.1	8.0	8.0	7.4	7.4	7.0	7.0	7.2	7.1	6.9	6.7	6.7	6.8	
CLEARWATER CITY LIMITS(4.4R)									FC3														
2568311	2.833	5.330	C	1999				0213	CRACKING	9.5	9.5	7.0	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	3.5*			
R E PURCELL				(2001)					S RIDE	6.6	6.4	6.2	6.1	6.2	5.7	6.0	5.7	5.3*	5.4*	5.3*			
15009000	2.867	5.312	L	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	
586			3	8.1				33500	RIDE	8.6	8.5	8.4	7.8	7.8	7.5	7.5	7.7	7.3	7.0	7.0	6.9	6.6	
RODNEY CT(2.9L)									FC125M														
4416571	2.840	4.298	C	2022				0012	CRACKING	9.0	8.5	7.0	7.0	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	10.0	10.0	9.0
PREFERRED MATERIALS, INC. (2025)									SPRIDE	6.7	6.3	6.9	7.3	7.3	7.1	7.2	7.3	7.1	7.0	7.0	8.3	8.3	7.9
15009000	2.325	2.867	L	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586			2	8.1				33500	RIDE	7.2	7.2	7.2	6.8	7.0	6.7	6.6	6.9	6.8	6.8	6.8	6.6	6.4	
SR 55(2.6C)									FC125M														
									CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	10.0	10.0	10.0	10.0	10.0	8.9	9.5	8.0
		(2020)							RIDE	6.2	5.1*	6.0	6.1	6.2	5.9	7.9	7.5	7.3	7.7	7.6	7.8	7.4	7.0
15009000	0.964	2.325	L	1	1	45			CRACKING	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586			2	8.1				26500	RIDE	6.4*	6.4*	6.1*	6.9	7.1		7.2	7.4	7.4	7.4	7.3	7.3	7.2	
CHALLENGER DR(1.0L)									FC125														
2568151	1.296	2.334	C	2004				0213	CRACKING	10.0	10.0	10.0	8.5	8.5	7.5	7.5	6.0*	5.5*	5.5*	3.5*	3.5*	2.1*	0.0*
R. E. PURCELL CONSTRUCTION(2007)									SPRIDE	7.2	7.3	6.9	6.8	6.8	6.6	6.8	6.8	6.6	6.6	6.6	6.6	6.6	6.2
4480411	0.323	2.341	C	2026				0012															
15009000	0.000	0.964	L	1	2	40			CRACKING	10.0	10.0	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586			2	8.1				14600	RIDE	6.7	6.3	6.5	6.3	6.1		7.7	7.0	7.6	7.5	7.8	7.7	7.4	
BAYSHORE BLVD(0.0C)									FC125														
2571381	0.000	0.993	C	2004				0221	CRACKING	8.5	8.5	8.5	8.5	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	4.8*	4.4*	2.0*
R. E. PURCELL CONSTRUCTION(2007)									SPRIDE	7.5	7.3	7.1	7.3	7.0	6.9	7.1	6.9	7.1	6.8	6.6	6.7	6.1	5.7
4480411	0.323	2.341	C	2026				0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15010000	0.000	0.213	C	1	7	35	CRACKING	10.0	10.0	10.0	9.0	8.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0															
595 A19			3	5.3		5600	RIDE	7.5	7.0	7.1	6.3	6.0	5.8	5.2*	5.7	5.7	5.7	6.7	6.3	6.5															
SR 687(0.0C)							FC125																												
							CRACKING	10.0	8.5	8.5	8.5	7.0	6.0*	6.0*	5.5*	5.5*	5.5*	5.5*	5.2*	10.0	9.0													
					(2026)		RIDE	6.4	6.3	6.0	5.9	5.5	5.3*	5.7	5.3*	5.1*	5.2*	5.2*	5.1*	4.8*	4.4*													
15010000	0.213	0.501	C	1	7	35	CRACKING	10.0	10.0	10.0	9.0	8.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0															
595 A19			2	5.3		5600	RIDE	7.5	7.0	7.1	6.3	6.0	5.8	5.2*	5.7	5.7	5.7	6.7	6.3	6.5															
SR 592(0.3R)							FC125M																												
4480361	0.214	0.410	C	2024		0012	CRACKING	10.0	8.5	8.5	8.5	7.0	6.0*	6.0*	5.5*	5.5*	5.5*	5.5*	5.2*	10.0	9.0													
AJAX PAVING INDUSTRIES OF				(2026)			SPRIDE	6.4	6.3	6.0	5.9	5.5	5.3*	5.7	5.3*	5.1*	5.2*	5.2*	5.1*	6.3	5.9													
15010000	0.501	1.343	C	1	7	35	CRACKING	10.0	10.0	10.0	9.0	8.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0															
595 A19			4	5.3		11200	RIDE	7.5	7.0	7.1	6.3	6.0	5.8	5.2*	5.7	5.7	5.7	6.7	6.3	6.5															
10 ST N(0.6R)							FC125M																												
							CRACKING	10.0	8.5	8.5	8.5	7.0	6.0*	6.0*	5.5*	5.5*	5.5*	5.5*	5.2*	10.0	9.0													
					(2026)		RIDE	6.4	6.3	6.0	5.9	5.5	5.3*	5.7	5.3*	5.1*	5.2*	5.2*	5.1*	6.5	6.1													
15010000	1.343	4.638	R	1	7	45	CRACKING	10.0	10.0	8.5	7.0	6.0*	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0															
595 A19			2	3.6		24000	RIDE	7.6	7.1	7.3	6.6	6.6	6.3	6.1	6.1	5.9		7.6	7.4	7.3															
FR 1590053 SB OFF(1.3R)							FC125M																												
4480361	2.520	4.610	R	2024		0012	CRACKING	10.0	10.0	8.5	8.5	8.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.6*	10.0	9.0													
AJAX PAVING INDUSTRIES OF				(2026)			SPRIDE	7.2	7.2	6.5	6.4	6.2	6.0	6.3	6.1	6.1	6.0	5.6	5.7	7.4	7.0													
15010000	4.638	7.944	R	1	4	45	CRACKING	7.2	7.1	7.0	9.3	9.3	9.2	9.3	8.5	8.6	7.9	8.1	7.7	7.7															
595 A19			2	8.4		34000	RIDE	5.8*	5.8*	5.7*	7.1	6.8	6.9	7.0	7.2	6.9	7.1	7.0	6.9	6.8															
EIGHTH AVE N R(4.8R)							CONC																												
2571261	4.514	8.033	C	2002		0012	CRACKING	7.6	7.5	7.4	7.3	7.3	6.8	6.2*	6.4*	5.5*	5.5*	5.6*	5.5*	4.5*	3.5*													
GILBERT SOUTHERN CORP				(2004)			RIDE	6.8	6.7	7.0	7.0	7.0	6.7	6.8	6.8	6.8	6.7	6.5	6.4	6.4	6.3													
4492071	4.638	7.944	C	2025		0227																													
15010000	7.944	8.620	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	7.0	7.0															
595 A19			2	8.5		45000	RIDE	7.0	7.9	8.5	7.7	7.7	7.6	7.5	7.6	7.4	7.3	7.1	7.2	7.2															
CR 1(8.0C)							FC95MR																												
4326981	7.944	8.620	C	2017		0012	CRACKING	7.0	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0													
COASTAL BRIDGE COMPANY, L.				(2020)			SPRIDE	7.0	7.0	7.2	7.0	6.9		7.5	7.5	7.5	7.3	7.3	7.3	7.2	6.8													
15010000	8.620	9.162	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	10.0	10.0	10.0	10.0															
595 A19			3	8.5		45000	RIDE	7.0	7.9	8.5	7.7	7.7	7.6	7.5	7.6	7.4	7.9	7.4	7.1	7.1															
92 ST N(9.0R)							FC125M																												
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	6.5	6.5	6.5	10.0	10.0	9.0													
					(2025)		RIDE	7.1	6.9	6.5	6.9	6.9	5.1*	5.3*	5.0*	5.0*	4.7*	4.8*	5.9	6.2	5.8													
15010000	9.162	9.810	R	1	2	45	CRACKING	7.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0															
595 A19			3	8.5		45000	RIDE	7.1	6.7	7.1	6.3*	6.1*	6.2	5.7	7.5	7.5	7.9	7.4	6.9	6.9															
98 WAY N(9.4R)							FC125																												
2571321	9.052	10.439	C	2006		0012	CRACKING	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5	7.0	7.0	7.0	6.5	4.9*	2.5*													
CONE & GRAHAM, INC.				(2008)			RIDE	6.8	6.8	6.6	6.4	6.3	6.2	6.3	6.4	6.2	6.3	6.0	6.2	5.9	5.5													
4492081	9.141	10.370	C	2029		0012																													
15010000	9.810	10.191	C	1	2	45	CRACKING	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0															
595 A19			2	7.3		9300	RIDE	7.7	7.7	7.6	6.3*	6.7	6.4	5.7	7.5	7.8	6.7	7.7	7.7	7.8															
SR 666(10.1L)							FC125																												
2571321	9.052	10.439	C	2006		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	8.5	7.0	7.0	4.5*													
CONE & GRAHAM, INC.				(2008)			RIDE	7.7	7.7	7.6	7.7	7.5	7.6	7.5	7.5	7.5	7.5	7.5	7.6	5.3*	4.9*													
4492081	9.141	10.370	C	2029		0012																													
15010000	10.191	10.370	R	1	2	45	CRACKING	7.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0															
595 A19			3	8.5		38500	RIDE	7.1	6.7	7.1	6.3*	6.1*	6.2	5.7	7.5	7.5	6.6	6.8	7.4	7.6															
BAY PINES BLVD(10.2R)							FC125																												
2571321	9.052	10.439	C	2006		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	7.0	6.3*	4.0*													
CONE & GRAHAM, INC.				(2008)			RIDE	7.7	7.7	7.5	7.3	7.4	7.1	7.3	7.1	7.1	7.2	7.1	7.0	7.2	6.8													
4492081	9.141	10.370	C	2029		0012																													
15010000	10.370	13.479	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0															
595 A19			3	8.5		41500	RIDE	8.1	8.1	7.9	7.2	7.1	6.7	6.8	7.0	6.8	6.6	6.8	6.7	6.5															
53 AV N(10.4C)							FC95MR																												
4364851	10.370	13.503	C	2020		0012	CRACKING	9.0	9.0	8.0	7.5	7.0	7.0	7.0	6.5	10.0	10.0	10.0	9.6	10.0	8.5													
PREFERRED MATERIALS, INC.				(2022)			SPRIDE	6.6	6.5	6.8	6.8	6.6	6.6	6.6	6.6	8.1	8.0	7.9	7.9	7.9	7.5													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / SURFTYPE / RW FY-P / ASTYPE / RW FY-F	SYS / %T / WKMX-P / WKMX-F	TYP	AADT	SPD	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15010000	13.479	17.066	R	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5													
595 A19			3	8.5	36500			RIDE	8.0	8.0	7.9	7.3	7.2	7.2	7.1	7.2	6.9	6.6	6.8	6.7	6.6													
CR 296(13.5C)					FC125M																													
4376241	13.479	16.930	C	2021		0012		CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	6.5	6.5	10.0	10.0	9.6	10.0	9.0												
PREFERRED MATERIALS, INC.			(2023)			SPRIDE			6.8	6.9	6.8	6.8	6.6	6.6	6.7	6.6	6.6	8.0	8.0	8.0	8.0	7.6												
15010000	13.479	17.066	L	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0													
595 A19			3	8.5	36500			RIDE	7.8	7.8	7.7	7.0	7.1	6.8	6.9	6.3	6.9	6.8	6.8	6.6	6.5													
CR 296(13.5C)					FC125M																													
4376241	13.479	16.930	C	2021		0012		CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	10.0	10.0	9.6	10.0	9.0												
PREFERRED MATERIALS, INC.			(2023)			SPRIDE			6.2	6.5	6.7	6.5	6.5	6.4	6.5	6.4	6.4	7.8	7.8	7.8	7.7	7.3												
15010000	10.370	13.479	L	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5													
595 A19			3	8.5	41500			RIDE	7.9	7.7	7.7	7.0	7.1	6.5	6.8	6.8	6.6	6.6	6.6	5.6	6.3													
53 AV N(10.4C)					FC95MR																													
4364851	10.370	13.503	C	2020		0012		CRACKING	9.5	8.5	8.5	8.5	7.0	7.0	7.0	6.5	10.0	10.0	10.0	9.6	10.0	8.5												
PREFERRED MATERIALS, INC.			(2022)			SPRIDE			6.5	6.2	6.7	6.4	6.5	6.3	6.6	6.5	7.8	7.8	7.7	7.7	7.7	7.3												
15010000	10.191	10.370	L	1	1	45		CRACKING	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	9.5	9.5	10.0	10.0													
595 A19			3	8.5	38500			RIDE	7.7	7.7	7.6	6.7	6.7	6.4	6.3	7.8	7.8	6.6	6.6	7.4	7.0													
010052(10.2L)					FC125																													
2571321	9.052	10.439	C	2006		0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.6	7.0	4.5*												
CONE & GRAHAM, INC.			(2008)			RIDE			7.0	7.2	7.1	7.1	7.3	6.9	6.9	6.8	6.8	6.8	6.7	6.6	6.8	6.4												
4492081	9.141	10.370	C	2029		0012																												
15010000	9.162	9.810	L	1	1	45		CRACKING	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0													
595 A19			3	8.5	45000			RIDE	7.7	7.7	7.6	6.7	6.7	6.4	6.3	7.8	7.8	7.4	7.4	7.1	7.6													
FROM BAY PINES HOSP(9.6L)					FC125																													
2571321	9.052	10.439	C	2006		0012		CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	7.5	7.5	7.0	6.0*	4.3*	2.0*												
CONE & GRAHAM, INC.			(2008)			RIDE			7.7	7.5	6.9	7.0	7.1	7.0	7.0	6.7	7.0	6.9	6.9	6.8	6.7	6.3												
4492081	9.141	10.370	C	2029		0012																												
15010000	8.620	9.162	L	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	10.0	10.0	10.0	10.0													
595 A19			3	8.5	45000			RIDE	7.6	7.4	7.6	7.1	7.1	6.7	6.9	6.9	7.5	7.4	7.4	7.4	7.4													
HOOVER BLVD(9.1L)					FC125M																													
								CRACKING	10.0	10.0	9.0	9.0	8.5	7.5	7.5	7.0	7.0	7.0	7.0	10.0	10.0	9.0												
			(2025)					RIDE	7.4	7.4	7.3	7.2	7.3	7.1	6.9	7.0	6.9	6.9	6.8	7.3	7.3	6.9												
15010000	7.944	8.620	L	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0													
595 A19			3	8.5	45000			RIDE	7.6	7.4	7.6	7.1	7.1	6.7	6.9	6.9	7.5	6.8	6.7	6.3	6.5													
CR 1(8.0C)					FC95MR																													
4326981	7.944	8.620	C	2017		0012		CRACKING	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	9.6	9.0	7.5												
COASTAL BRIDGE COMPANY, L.			(2020)			SPRIDE			6.7	6.3	6.2	5.8	5.9		7.4	7.2	7.2	7.3	7.3	7.0	7.2	6.8												
15010000	4.638	7.944	L	1	4	45		CRACKING	0.0*	7.2	7.2	9.3	9.3	9.3	9.2	9.0	8.3	7.5	7.5	7.5	7.3													
595 A19			2	8.4	34000			RIDE	6.3*	6.2*	6.3*	7.1	6.5	6.8	6.6	7.1	6.9	7.1	7.1	7.0	6.9													
TYRONE BLVD(4.6L)					CONC																													
2571261	4.514	8.033	C	2002		0012		CRACKING	7.0	7.0	6.8	6.5	6.4*	6.3*	6.3*	6.1*	5.5*	5.3*	5.3*	5.9*	4.4*	3.5*												
GILBERT SOUTHERN CORP			(2004)			RIDE			6.8	6.6	7.0	7.0	6.9	6.7	6.8	6.8	6.7	6.7	6.6	6.6	6.5	6.4												
4492071	4.638	7.944	C	2025		0227																												
15010000	1.343	4.638	L	1	7	45		CRACKING	8.5	7.5	7.5	7.0	6.0*	6.0*	6.0*	6.0*	5.5*			10.0	10.0	10.0													
595 A19			2	3.6	24000			RIDE	7.7	7.5	7.4	6.8	6.6	6.3	6.1	6.0	5.8			7.6	7.5	7.3													
21 ST N(1.4L)					FC125M																													
4480361	2.520	4.610	L	2024		0012		CRACKING	10.0	10.0	8.5	8.5	8.5	6.0*	6.0*	6.0*	5.5*	5.5*	5.5*	5.6*	10.0	9.0												
AJAX PAVING INDUSTRIES OF			(2026)			SPRIDE			7.2	7.0	6.7	6.4	6.2	5.9	6.2	6.0	5.9	5.8	5.6	5.6	7.6	7.2												
15010001	0.038	0.840	C	1	1			CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0																						
595F			1	7.8	11500			RIDE	6.5	6.6	6.3*	7.7	7.1	7.3																						
								CRACKING																									6.5	4.0*
			(2004)					RIDE																									5.9*	5.5*
15010002	0.000	0.573	C	1	1			CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0																						
595F			1	7.8	11500			RIDE	6.9	7.0	6.6	7.6	7.2	7.5																						
								CRACKING																									6.5	4.0*
			(2004)					RIDE																									5.6*	5.2*

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	LN	%T	AADT	SURFTYPE / ASTYPE	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15010003 595F	0.000 0.000 0.000	0.724 0.724 0.724	C	1	1	35	1	7.8	11500	RIDE	6.9																										
										CRACKING																											6.5	3.5*
									(2001)	RIDE																											5.2*	4.8*
15010004 595F	0.000 0.000 0.000	1.652 1.652 1.652	C	1	1	35	1	7.8	11500	RIDE	4.8*																										
										CRACKING																											6.5	
										RIDE																											5.2*	
15010053 665	0.000 0.000 0.000	0.487 0.487 0.487	C	1	1	35	2	8.7	1700	RIDE	6.7																										
										CRACKING																											3.5*	0.5*
									(2000)	RIDE																											5.1*	4.7*
4492081	0.000	0.487	C	2029		0012																																
15010101 595 A19 FIFTH AVE N(0.0C)	0.000 0.000 0.000	0.924 0.924 0.924	C	1	1	35	2	5.4	9900	CRACKING RIDE FC125M	6.5 5.6*	6.5 5.5	6.5 5.5	6.5 5.1*	5.5*	5.5* 3.8*	3.5* 3.5*	3.5* 3.8*	10.0 6.5	10.0 6.0	8.5 5.6	8.5 5.8	8.5 6.0														
										CRACKING	8.5	8.5	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5												
									(2021)	RIDE	6.3	5.8	5.9	5.9	5.3*	5.5	5.3*	6.9	7.0	7.0	7.1	7.1	6.8	6.4												
15010101 595 A19 I 375(0.9L)	0.924 0.924 0.924	1.216 1.216 1.216	C	1	1	30	3	4.4	13000	CRACKING RIDE FC125M	6.5 5.6*	6.5 5.5	6.5 5.5	6.5 5.1*	5.5*	5.5* 3.8*	3.5* 3.5*	3.5* 3.8*	10.0 6.5	10.0 6.0	8.5 5.6	8.5 5.8	8.5 6.0														
4364871 PREFERRED MATERIALS, INC.	0.930 0.930 0.930	1.216 1.216 1.216	C	2019		0012				CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	10.0	10.0	10.0	10.0	10.0	8.3	7.0												
									(2021)	SPRIDE	6.3	5.8													5.7	5.3*										
15010102 595 A19 TOM STUART CSWY(0.0L)	0.000 0.000 0.000	0.423 0.423 0.423	C	1	1	45	2	8.5	11500	CRACKING RIDE DGFC									10.0 8.3	10.0 8.5	10.0 8.4	10.0 8.3	10.0 8.1	10.0 7.7												
										CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	6.3*	4.0*												
									(2008)	RIDE	7.9	8.2	7.6	7.7	7.6	7.6	7.8	7.6	7.7	7.4	7.2	7.4	7.5	7.1												
4492081	0.000	0.423	C	2029		0012																																
15020000 595 A19 PLEASANT ST(1.1L)	1.126 1.126 1.126	3.288 3.288 3.288	C	1	1	35	2	10.0	13700	CRACKING RIDE FC125M	6.5 5.6*	6.5 5.7	6.5 5.7	6.5 5.0*		10.0 6.2	10.0 6.0	10.0 6.3	9.5 6.2	9.5 6.2	9.5 6.2	9.5 5.9	9.0 5.9														
4376231 AJAX PAVING INDUSTRIES OF	1.675 1.675 1.675	3.288 3.288 3.288	C	2020		0012				CRACKING	8.5	8.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.1	8.7	7.5												
									(2022)	SPRIDE	5.7	5.5	4.7*	4.6*	4.4*	4.3*	4.2*	4.0*	5.6	5.6	5.5	5.4*	5.3*	4.9*												
15020000 595 A19 MONROE ST(3.3C)	3.288 3.288 3.288	3.523 3.523 3.523	C	1	1	35	2	10.0	17100	CRACKING RIDE FC125M	10.0 7.6	10.0 7.9	10.0 7.6	10.0 7.1	10.0 6.0	10.0 6.4	10.0 6.4	10.0 6.6	9.5 6.5	8.5 6.3	8.5 6.4	8.5 6.2	8.5 6.3														
4376231 AJAX PAVING INDUSTRIES OF	3.288 3.288 3.288	3.462 3.462 3.462	C	2020		0012				CRACKING	8.5	8.5	7.0	6.5	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	9.1	10.0	8.5												
									(2022)	SPRIDE	6.6	6.5	6.0	6.3	5.6	5.9	5.9	5.9	6.0	5.9	6.1	5.9	5.8	5.4*												
15020000 595 A19 JACKSON ST(3.6C)	3.523 3.523 3.523	5.902 5.902 5.902	R	1	1	35	1	10.0	17100	CRACKING RIDE FC125R	10.0 7.1	10.0 7.4	10.0 6.9	10.0 7.0	8.5 6.5	8.5 6.2	8.5 6.1	7.5 6.2	6.5 5.9	6.5 6.1	6.5 5.6	10.0 7.9	10.0 7.9														
2571311 AJAX PAVING INDUSTRIES OF	3.523 3.523 3.523	4.863 4.863 4.863	C	2010		0226				CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	7.8	8.0	6.0*												
									(2012)	SPRIDE	7.8	7.7	7.7	7.6	7.5	7.4	7.3	7.2	7.1	7.0	6.9	6.9	6.9	6.5												
15020000 595 A19 CR 712(5.9R)	5.902 5.902 5.902	7.242 7.242 7.242	R	1	1	45	1	10.0	17100	CRACKING RIDE FC125A	10.0 7.9	10.0 7.9	10.0 7.8	10.0 7.5	10.0 7.7	10.0 7.1	10.0 7.1	10.0 7.0	7.0 7.3	7.0 7.5	7.0 7.5	7.0 7.2	7.0 7.9														
4306601 PREFERRED MATERIALS, INC.	5.902 5.902 5.902	7.242 7.242 7.242	C	2015		0012				CRACKING	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.8	7.0												
									(2017)	RIDE	8.1	7.7	7.7	8.2	8.2	8.1	8.1	8.0	8.0	8.0	8.1	8.0	8.0	7.6												
15020000 595 A19 CR 752(7.4C)	7.242 7.242 7.242	10.672 10.672 10.672	R	1	8	35	1	8.6	19900	CRACKING RIDE FC125R	9.0 7.7	9.0 7.7	9.0 7.5	9.0 7.0	9.0 6.7	9.0 6.7	9.0 6.5	7.5 5.8	4.5* 6.1	4.5* 6.2	4.5* 5.9	4.5* 6.0	10.0 7.6														
										CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	7.0														
									(2013)	RIDE	7.5	7.4	7.3	7.3	7.2	7.1	7.1	7.0	7.0	7.0	6.9	6.9														
4480421	7.242 7.242 7.242	12.637 12.637 12.637	C	2024		0012																																

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYS / %T / FY-P / FY-F	TYP SPD / AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15020000	10.672	12.637	R	1	1 45	CRACKING	6.5	6.5	6.5	6.5	6.5	4.5*			10.0	10.0	10.0	10.0	10.0															
595 A19			1	10.2	13300	RIDE	7.0	6.8	6.7	6.0*	5.9*	5.9			7.8	7.8	7.6	7.7	7.5															
PROGRESS CT(10.7R)					FC4																														
2570781	10.672	12.637	C	2006	0012	CRACKING	10.0	8.5	8.5	7.5	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*	3.8*	3.3*	1.0*													
AJAX PAVING INDUSTRIES, IN	(2009)				SP	RIDE	7.5	7.5	7.2	7.1	7.1	7.0	7.0	6.9	6.8	6.7	6.8	6.8	6.5	6.1													
4480421	7.242	12.637	C	2024	0012																														
15020000	12.637	13.265	R	1	1 35	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.2	13300	RIDE	6.1*	6.0	5.8	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1															
E MORGAN ST(12.8R)					FC95M																														
2571371	12.619	13.290	C	2006	0012	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.8	5.5*	3.0*													
AJAX PAVING INDUSTRIES, IN	(2009)				SP	RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	5.9	5.5													
4480441	12.637	15.225	C	2029	0012																														
15020000	13.265	14.079	C	1	1 30	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.0	16800	RIDE	6.1*	6.0	5.8	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1															
E ORANGE ST(13.3R)					FC95M																														
2571371	13.290	13.745	C	2006	0012	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	5.6*	3.5*													
AJAX PAVING INDUSTRIES, IN	(2009)				SP	RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	5.5	5.1*													
4480441	12.637	15.225	C	2029	0012																														
15020000	14.079	14.407	R	1	1 45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.0	18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1															
ANCLOTE RD E(14.2R)					DGFC																														
						CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.8	10.0	9.0													
	(2026)					RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	6.7	6.3													
4480441	12.637	15.225	C	2029	0012																														
15020000	14.407	14.546	R	1	1 45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.0	18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1															
DIXIE HWY(14.4R)					DGFC																														
						CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.8	3.8*	1.5*													
	(2009)					RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	5.8	5.4*													
4480441	12.637	15.225	C	2029	0012																														
15020000	14.546	14.854	C	1	1 45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.0	18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1															
					DGFC																														
						CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	8.6	7.5													
	(2026)					RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	7.7	7.3													
4480441	12.637	15.225	C	2029	0012																														
15020000	14.854	15.225	R	1	1 45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.0	18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1															
PLAZA DR(14.9R)					DGFC																														
						CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.8	7.0	4.5*													
	(2009)					RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	7.4	7.0													
4480441	12.637	15.225	C	2029	0012																														
15020000	14.854	15.225	L	1	1 45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.0	18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.4	7.2	7.3	7.3	7.1															
SORENO ST(15.0L)					FC95M																														
						CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	7.0	4.5*													
	(2009)					RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	7.4	7.0													
4480441	12.637	15.225	C	2029	0012																														
15020000	14.407	14.546	L	1	1 45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.0	18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.4	7.2	7.3	7.3	7.1															
CR 429(14.4L)					FC95M																														
						CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	5.0*	2.5*													
	(2009)					RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	6.2	5.8													
4480441	12.637	15.225	C	2029	0012																														
15020000	14.079	14.407	L	1	1 45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.0	18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.4	7.2	7.3	7.3	7.1															
OSCAR HILL RD(14.1L)					FC95M																														
						CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	10.0	9.0													
	(2026)					RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	6.1	5.7													
4480441	12.637	15.225	C	2029	0012																														
15020000	12.637	13.265	L	1	1 35	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0															
595 A19			1	10.2	13300	RIDE	6.1*	6.0	5.8	5.3*	5.4*	5.1*	4.7*		7.4	7.2	7.3	7.3	7.1															
APRICOT CT(12.7L)					FC95M																														
2571371	12.619	13.290	C	2006	0012	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	4.9*	2.5*													
AJAX PAVING INDUSTRIES, IN	(2009)				SP	RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	5.5	5.1*													
4480441	12.637	15.225	C	2029	0012																														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T	AADT	SURFTYPE	DISTRESS / RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
15020000 595 A19 WAI LANI RD(10.8L) 2570781 AJAX PAVING INDUSTRIES, IN 4480421	10.672 12.637 1 10.2 7.242	12.637	L	1	8	45	13300	FC4	CRACKING	6.5	6.5	6.5	6.5	6.5	4.5*			10.0	10.0	10.0	10.0	10.0													
									RIDE	7.0	6.8	6.7	6.0*	5.9*	5.9			7.7	7.8	7.6	7.7	7.5													
	10.672 12.637 C 2006						0012		CRACKING	10.0	8.5	8.5	7.5	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*	3.6*													
	(2009) 7.242 12.637 C 2024						0012		SPRIDE	7.5	7.5	7.2	7.1	7.1	7.0	7.0	6.9	6.8	6.7	6.6	6.5													
15020000 595 A19 PALM HARBOR PL(7.3L)	7.242 10.672 1 8.6		L	1	8	35	19900	FC125R	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	4.5*	4.5*	4.5*	10.0												
									RIDE	7.7	7.7	7.5	7.0	6.7	6.7	6.5	6.6	6.2	6.2	5.9	6.0	7.6												
	(2013) 7.242 12.637 C 2024						0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5													
									RIDE	7.5	7.4	7.3	7.3	7.2	7.1	7.1	7.0	7.0	7.0	7.3	7.3													
15020000 595 A19 CAUSEWAY BLVD(5.9L) 4306601 PREFERRED MATERIALS, INC.	5.902 7.242 1 10.0		L	1	1	45	17100	FC125A	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	7.0													
									RIDE	7.9	7.9	7.8	7.5	7.7	7.1	7.1	7.0	7.3	7.5	7.5	7.2	7.9												
	5.902 7.242 C 2015						0012		CRACKING	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	10.0	8.5											
	(2017)								RIDE	8.1	7.7	7.7	8.2	8.2	8.1	8.1	8.0	8.0	8.0	8.1	8.0	8.0	7.6											
15020000 595 A19 JACKSON ST(3.6C) 2571311 AJAX PAVING INDUSTRIES OF	3.523 5.902 1 10.0		L	1	1	35	17100	FC125R	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	6.5	6.5	10.0	10.0												
									RIDE	7.1	7.4	6.9	7.0	6.5	6.2	6.1	6.5	6.3	6.1	5.6	7.9	7.9												
	3.523 4.863 C 2010						0226		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	7.8	7.2	5.0*											
	(2012)								SPRIDE	7.8	7.7	7.7	7.6	7.5	7.4	7.3	7.2	7.1	7.0	6.7	6.8	6.6	6.2											
15020100 595F	0.000 0.123 1 3.0		C	1	1		1500		CRACKING																											
									RIDE																											
									CRACKING														6.6													
									RIDE														5.0*													
15025000 595 A19 CHESTNUT ST(0.0C) 4364881 HUBBARD CONSTRUCTION CO.	0.000 1.347 4 7.3		C	1	1	35	13300	FC125M	CRACKING								10.0	10.0	10.0	10.0	10.0	10.0												
									RIDE								6.8	6.7	6.9	6.8	6.3	6.4												
	0.007 0.697 C 2019						0012		CRACKING	8.5	8.5	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	8.8	8.2	7.0											
	(2021)								SPRIDE	6.5	6.3	5.9	5.5	5.9	5.5	5.5	6.4	6.5	6.3	6.3	6.2	6.4	6.0											
15025000 595 A19 GRANT ST(1.3R) 4364881 HUBBARD CONSTRUCTION CO.	1.347 1.592 3 3.9		C	1	1	35	11500	FC125M	CRACKING								10.0	10.0	10.0	10.0	10.0	10.0												
									RIDE								6.0	6.6	5.6	5.8	5.8	6.0												
	1.314 1.481 C 2019						0012		CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	9.6	10.0	8.5											
	(2021)								SPRIDE	6.0	5.9	4.4*	4.2*	4.3*	4.3*	4.2*	6.7	6.7	6.8	6.7	6.7	6.8	6.4											
15030000 686 A19/S595/SEMINOLE BL(0.0R) 4309011 AJAX PAVING INDUSTRIES OF	0.000 0.531 2 18.5		R	1	1	35	45500	FC125M	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	7.5	7.5	7.5												
									RIDE	7.0	6.6	6.1	5.7	5.7	6.1	5.5	6.1	6.5	5.7	5.5	5.7	5.7												
	0.000 0.531 C 2015						0012		CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	5.5*											
	(2017)								RIDE	5.3*	5.5	5.7	7.4	7.3	7.3	7.2	7.4	7.3	7.2	7.0	7.3	6.9	6.5											
15030000 686 SE HIGHLAND AVE(0.8R) 4309011 AJAX PAVING INDUSTRIES OF	0.531 0.840 3 18.5		R	1	1	40	45500	FC125M	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0												
									RIDE	7.0	6.6	7.8	7.6	7.6	7.4	7.0	7.3	7.3	7.4	7.2	7.0	7.0												
	0.531 0.824 C 2015						0012		CRACKING	8.5	8.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.0	5.5*											
	(2017)								RIDE	6.9	6.8	6.8	8.1	8.1	7.7	7.9	7.9	7.9	7.9	7.4	7.8	7.7	7.3											
15030000 686 COUNTRY CLUB DR(1.0R) 2568921 J. W. CONNER & SONS, INC. 4492051	0.840 2.400 3 18.5		R	1	1	40	62500	FC3	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0												
									RIDE	8.2	8.0	7.8	7.6	7.6	7.4	7.0	7.3	7.3	7.4	7.2	7.0	7.0												
	0.997 2.567 C 1994						0121		CRACKING	8.5	8.5	7.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	6.7	7.0	4.0*											
	(1998) 0.845 2.362 C 2028						0012		S RIDE	6.9	6.8	6.8	6.6	6.8	6.5	6.8	6.4	6.5	6.5	6.4	6.4	6.3	5.9											
15030000 686 BELCHER RD(2.6R) 2568891 OVERSTREET PAVING ASPH PLA 4479171	2.400 3.844 3 4.6		R	1	1	40	62000	FC3	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0												
									RIDE	8.5	8.3	8.3	7.4	7.5	7.1	7.1	7.7	7.5	7.5	7.2	7.3	7.2												
	2.763 3.556 C 1995						0121		CRACKING	8.5	8.5	7.5	7.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*	4.9*	4.6*	1.5*											
	(1997) 2.362 3.570 C 2025						0012		S RIDE	7.3	7.0	7.0	6.9	7.0	6.7	6.8	6.9	6.7	6.9	6.7	6.6	6.8	6.4											

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / US / W_BMP	EMP / G_BMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	LN	%T	AADT	SURFTYPE	RW FY-P	WKMX-P	ASTYPE	RW FY-F	WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15030000	3.844	5.457	R	1	1	45										CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0													
686				3	4.6	26910				RIDE							8.3	8.2	8.2	7.6	7.6	7.7	7.4	7.7	7.7	7.6	7.6	7.4	7.4													
MICHIGAN DR(3.9R)										DGFC																															
2568911	3.780	5.247	C	1995		0121				CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.6	6.2*	3.0*															
COUCH CONSTRUCTION LP				(1998)		S				RIDE							7.3	7.4	7.2	7.1	7.1	7.0	7.0	7.0	7.0	7.2	7.1	7.3	7.2	6.8												
4402471	3.570	5.310	C	2028		0012																																			
15030000	5.457	6.557	R	1	1	50				CRACKING	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0																
686				2	7.3	38500				RIDE							7.9	8.1	8.0	7.2	7.3	7.2	7.2	7.2	7.9	8.0	7.9	7.7	7.3													
46 ST N(5.8R)										DGFC																															
																CRACKING	10.0	9.0	8.5	8.5	7.5	7.0						10.0	10.0	9.0													
				(2025)						RIDE							7.1	7.0	7.2	6.8	6.5	6.4*						8.1	8.1	7.7													
15030000	6.557	6.814	C	1	1	40				CRACKING	10.0	10.0	10.0	6.5	4.5*	7.0	7.0	4.5*	10.0	10.0	10.0	10.0	10.0																
686				2	6.8	11500				RIDE							7.9	8.1	8.0	7.4	7.4	7.2	7.2	6.9	7.9	8.0	8.0	7.8	7.9													
										FC4																															
																CRACKING	10.0	10.0	9.0			10.0	10.0					10.0	10.0	9.0													
				(2025)						RIDE							7.8	7.7	7.1									6.8	6.6	6.2													
15030000	7.841	7.955	C	1	1	45				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	9.0	6.5	6.5	6.5	6.5																
686				2	6.8	11500				RIDE							8.4	8.3	8.5	7.6	8.1	7.7	7.7	7.9	7.9	7.7	7.7	7.5	7.4													
										DGFC																															
																CRACKING	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	6.5													
				(2017)						RIDE							7.6	7.1	7.4	7.7	7.8	7.9	7.5	7.8	7.7	7.0	6.8	6.9	7.2	6.8													
15030000	7.955	8.418	R	1	1	45				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5																
686				3	18.5	40000				RIDE							8.4	8.3	8.2	7.6	7.7	7.7	7.6	7.9	7.9	7.8	7.8	7.6	7.6													
										OGFC																															
																CRACKING	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	8.1	4.5*													
				(2017)						RIDE							7.6	7.1	7.4	7.8	7.8	7.9	7.5	7.8	7.7	8.0	8.3	8.2	8.0	7.8													
15030000	8.418	9.176	R	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5																
686				3	18.5	51500				RIDE							8.4	8.3	8.2	7.6	7.7	7.7	7.6	7.9	7.9	7.8	7.8	7.6	7.6													
CR 683(8.5R)										FC5A																															
																CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.1	7.2	4.0*													
				(2018)						RIDE							7.6	7.1	7.4	7.7	8.1	7.9	8.1	8.0	7.9	7.9	7.8	8.0	8.1	7.9													
15030000	9.176	9.413	R	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5																
686				2	18.5	51500				RIDE							8.4	8.3	8.2	7.6	7.7	7.7	7.6	7.9	7.9	7.8	7.8	7.6	7.6													
										FC5M																															
																CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.1	10.0	9.0													
				(2026)						RIDE							7.6	7.1	7.4	7.7	8.1	7.9	8.1	8.0	7.9	7.9	7.8	8.0	8.3	8.1													
15030000	9.413	10.666	R	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5																
686				2	18.5	19100				RIDE							8.4	8.3	8.2	7.6	7.7	7.7	7.6	7.9	7.9	7.8	7.8	7.6	7.6													
16 ST N(9.7R)										FC5A																															
4290601	9.245	10.698	C	2016		0012				CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.1	8.1	5.0*															
PCS CIVIL LLC				(2018)						RIDE							7.6	7.1	7.4	7.7	8.1	7.9	8.1	8.0	7.9	7.9	7.8	8.0	8.0	7.8												
15030000	9.413	10.666	L	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5																
686				2	18.5	19100				RIDE							8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4													
BELLFLOWER DR(9.7L)										FC5A																															
4290601	9.245	10.698	C	2016		0012				CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.4	7.7	4.5*															
PCS CIVIL LLC				(2018)						RIDE							7.3	7.1	7.7	7.7	8.2	8.2	8.2	8.1	8.1	7.9	7.8	8.1	7.9	7.7												
15030000	9.176	9.413	L	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5																
686				2	18.5	51500				RIDE							8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4													
										FC5M																															
																CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.4	10.0	9.0													
				(2026)						RIDE							7.3	7.1	7.7	7.7	8.2	8.2	8.2	8.1	8.1	7.9	7.8	8.1	8.0	7.8													
15030000	8.930	9.176	L	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5																
686				2	18.5	51500				RIDE							8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4													
										FC5A																															
4290601	8.963	9.245	C	2016		0012				CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.4	8.9	5.5*															
PCS CIVIL LLC				(2018)						RIDE							7.3	7.1	7.7	7.7	8.2	8.2	8.2	8.1	8.1	7.9	7.8	8.1	8.6	8.4												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T	AADT	SURFTYPE	DISTRESS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
15030000	8.418	8.930	L	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5													
686			3	18.5		51500				RIDE	8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4													
FROM LK CARILLON DR(8.5L)									FC5A																												
4290601	8.640	8.963	L	2016		0012				CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.4	8.6	5.5*												
PCS CIVIL LLC				(2018)						RIDE	7.3	7.1	7.7	7.7	8.2	8.2	8.2	8.1	8.1	7.9	7.8	8.1	8.5	8.3												
15030000	7.955	8.418	L	1	1	45				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5													
686			2	18.5		40000				RIDE	8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4													
									FC5A																												
										CRACKING	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.2	9.0	5.5*												
				(2017)						RIDE	7.3	7.1	7.7	7.7	7.7	7.7	7.6	7.8	7.6	7.8	7.8	7.8	7.7	7.5												
15030000	5.667	6.557	L	1	1	50				CRACKING	10.0	9.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0													
686			2	7.3		38500				RIDE	8.4	8.3	8.3	7.4	7.4	6.9	6.9	6.9	8.1	8.1	8.0	7.8	7.9													
FROM AIRPORT PKWY(5.8L)									DGFC																												
										CRACKING	10.0	10.0	9.0	9.0	9.0	9.0						10.0	10.0	9.0												
				(2025)						RIDE	7.9	8.0	7.7	7.5	7.6	7.4						8.0	8.0	7.6												
15030000	5.304	5.667	L	1	1	50				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.5													
686			3	7.3		38500				RIDE	8.3	8.2	8.0	7.5	7.6	7.5	7.3	7.5	7.5	7.4	7.4	7.2	7.1													
									DGFC																												
										CRACKING	7.5	7.5	10.0	10.0	10.0	10.0						10.0	10.0	9.0												
				(2025)						RIDE	7.1	7.2	6.7	6.5	6.4*	6.2*						7.3	7.8	7.4												
15030000	3.844	5.304	L	1	1	45				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.5													
686			3	4.6		26910				RIDE	8.3	8.2	8.0	7.5	7.6	7.5	7.3	7.5	7.5	7.4	7.4	7.2	7.1													
FAIRINGTON DR(3.9L)									DGFC																												
2568911	3.780	5.247	C	1995		0121				CRACKING	7.5	7.5	7.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	6.0*	6.0*	5.4*	2.0*												
COUCH CONSTRUCTION LP				(1998)		S				RIDE	7.1	7.2	7.2	7.3	7.3	7.1	7.1	7.1	6.9	7.0	6.9	6.8	6.8	6.4												
4402471	3.570	5.310	C	2028		0012																															
15030000	2.400	3.844	L	1	1	40				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0													
686			3	4.6		62000				RIDE	7.8	7.8	7.6	7.0	6.7	6.8	6.7	7.1	6.9	6.9	6.9	6.6	6.5													
BEDFORD CIR W(2.9C)									FC3																												
2568891	2.763	3.556	C	1995		0121				CRACKING	8.5	8.5	7.5	7.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*	5.4*	4.9*	1.5*												
OVERSTREET PAVING ASPH PLA				(1997)		S				RIDE	6.5	6.4	6.6	6.6	6.7	6.4	6.5	6.4	6.5	6.5	6.4	6.4	6.4	6.0												
4479171	2.362	3.570	C	2025		0012																															
15030000	0.840	2.400	L	1	1	40				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0													
686			3	18.5		62500				RIDE	7.9	8.0	7.7	7.5	7.4	7.3	7.0	7.0	7.3	6.9	7.0	6.8	6.7													
WERTZ DR(0.9L)									FC3																												
2568921	0.997	2.567	C	1994		0121				CRACKING	9.0	9.0	8.5	8.5	8.5	8.5	8.0	7.0	7.0	7.0	7.0	6.6	6.5	3.5*												
J. W. CONNER & SONS, INC.				(1998)		S				RIDE	6.8	6.8	6.8	6.8	6.7	6.6	6.6	6.6	6.6	6.6	6.4	6.5	6.5	6.1												
4492051	0.845	2.362	C	2028		0012																															
15030000	0.000	0.840	L	1	1	40				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.0	7.0	7.0													
686			3	18.5		45500				RIDE	7.5	7.1	7.0	6.6	6.3	6.0	5.9	6.0	5.8	5.8	5.9	5.7	5.4*													
A19S595S651/MISSOURI(0.0L)									FC125M																												
4309011	0.000	0.531	C	2015		0012				CRACKING	6.5	6.5	6.0*	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	7.0	7.0	5.5*												
AJAX PAVING INDUSTRIES OF				(2017)						RIDE	5.2*	5.4*	5.5	7.4	7.4	7.2	7.2	7.2	7.1	7.1	7.0	6.9	7.3	6.9												
15030018	0.000	0.583	C	1	1	40				CRACKING								10.0	10.0	10.0	8.5	8.5	8.5													
686			2	22.7		16500				RIDE								7.9	7.6	8.1	8.0	7.9	7.9													
15030055 NB OFF(0.0R)									DGFC																												
										CRACKING	8.5		9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.3	7.7	6.0*												
				(2016)						RIDE	7.6		7.1	7.4	7.4	7.2	7.1	7.2	7.0	6.9	6.8	6.9	6.9	6.5												
15030101	0.000	0.125	C	1	1	40				CRACKING								10.0	10.0	10.0	10.0	10.0	10.0													
686			3	18.5		9100				RIDE																											
BON SECOURS ENTR(0.0L)																																					
										CRACKING	10.0	10.0	10.0	10.0		10.0	10.0	10.0	10.0	10.0	10.0	8.7	8.2	6.5												
				(2019)						RIDE														5.7	5.3*												
15030102	0.000	0.108	C	1	1	40				CRACKING								10.0	9.5	8.5	7.5	7.5	7.5													
686			2	18.5		10000				RIDE																											
GANDY BLVD WB(0.0C)									OGFC																												
										CRACKING	7.5	7.5	7.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.7	7.5	4.5*												
				(2018)						RIDE														7.6	7.4												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	AADT	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE
				%T				SURFTYPE	========													
			LN					ASTYPE	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
				FY-P		WKMX-P																
				FY-F		WKMX-F																(PMRS)
15035000	0.000	0.128	C	3	1	45		CRACKING														
686A	0.0	0.1	2	4.0		15750		RIDE														
								CRACKING												10.0	10.0	9.0
				(2025)				RIDE												8.3	8.4	8.0
15035000	0.555	0.706	C	3	1	45		CRACKING														
686A	0.6	0.7	2	4.0		15750		RIDE														
								CRACKING												10.0	10.0	9.0
				(2025)				RIDE												8.3	7.6	7.2
15035000	0.706	2.593	R	3	1	45		CRACKING													10.0	
686A	0.7	2.6	2	4.0		31500		RIDE													7.9	
WB 118 AVE N(1.6C)																						
								CRACKING	10.0	10.0	10.0	10.0	7.5	7.5						10.0	10.0	9.0
				(2025)				RIDE	7.7	7.9	7.9	7.9	7.7	7.7						8.3	8.4	8.0
15035000	2.859	3.021	R	3	1	55		CRACKING							10.0	10.0	10.0	10.0	10.0	9.0	6.5	
686A	2.9	3.0	2	4.0		31500		RIDE							7.7	7.5	7.8	7.6	7.6	7.4	7.1	
								CRACKING	6.5	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*		10.0	10.0	9.0
				(2025)				RIDE	7.1	6.4*	7.0	6.8	7.5	7.3	7.6	7.5	6.9	6.7		8.3	8.0	7.6
15035000	3.021	3.309	R	3	1	55		CRACKING														
686A	3.0	3.3	2	4.0		31500		RIDE														
								CRACKING													10.0	9.0
				(2026)				RIDE													8.1	7.7
15035000	3.610	4.192	R	3	1	55		CRACKING														
686A	3.6	4.2	2	4.0		15750		RIDE														
								CRACKING													10.0	9.0
				(2026)				RIDE													7.9	7.5
15035000	3.607	4.192	L	3	1	55		CRACKING														
686A	3.6	4.2	2	4.0		15750		RIDE														
								CRACKING													10.0	9.0
				(2026)				RIDE													8.3	7.9
15035000	3.021	3.318	L	3	1	55		CRACKING														
686A	3.0	3.3	2	4.0		31500		RIDE														
								CRACKING													10.0	9.0
				(2026)				RIDE													7.9	7.5
15035000	2.929	3.021	L	3	1	55		CRACKING														
686A	2.9	3.0	2	4.0		31500		RIDE														
						FC5M																
								CRACKING					7.5	6.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	8.5
				(2025)				RIDE					7.8	7.6	7.6	7.8	7.7	7.4		8.3	8.5	8.3
15035000	0.706	2.595	L	3	1	45		CRACKING													10.0	
686A	0.7	2.6	2	4.0		31500		RIDE													7.9	
WB 118 AVE N(1.6C)						FC5M																
								CRACKING	10.0	10.0	10.0	10.0	7.5	7.5						10.0	10.0	8.5
				(2025)				RIDE	7.7	7.9	7.9	7.9	7.7	7.7						8.3	8.5	8.3
15036001	0.000	0.467	C	1	1	35		CRACKING														
689			2	8.7		1900		RIDE														
CR 296(0.0C)																						
								CRACKING													8.5	7.5
				(2026)				RIDE													6.5	6.1

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / SURFTYPE / ASTYPE	SYS / %T / FY-P / FY-F	TYP / AADT / WKMX-P / WKMX-F	SPD	DISTRESS / RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15036004	0.000	0.075	C	1	1		CRACKING																												
692			1				RIDE																												
43RD ST N(0.0C)																																			
							CRACKING																												10.0	
							RIDE																												5.5*	
15040000	1.661	4.219	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*															
60			3	4.9	49500		RIDE	7.6	7.5	7.5	7.3	7.1	6.9	6.6	6.7	6.5	6.3	6.3	5.9	5.8															
S GLENWOOD AVE(1.7R)					FC125A																														
4325861	1.789	4.219	C	2016	0012		CRACKING	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.6	7.0														
PREFERRED MATERIALS, INC.			(2019)		SPRIDE		RIDE	5.6	5.3*	5.9	5.8		7.5	7.4	7.3	7.2	7.2	7.1	7.1	6.9	6.5														
15040000	4.219	4.713	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*															
60			3	6.7	55000		RIDE	7.6	7.5	7.5	7.3	7.1	6.9	6.6	6.7	6.5	6.3	6.3	5.9	5.8															
BYPASS DR(4.3R)					FC3																														
							CRACKING	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.7	6.6	5.0*														
			(2017)				RIDE	5.6	5.3*											5.4*	5.0*														
4479181	4.219	6.410	C	2028	0012																														
15040000	4.713	6.376	R	1	2	45	CRACKING	10.0	8.5	8.5	7.0	7.0	6.0*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0															
60			3	6.7	55000		RIDE	8.0	7.9	7.5	6.4*	6.5	6.2	6.1	5.5	8.1	7.5	7.6	7.4	7.2															
SKY HARBOR DR(4.8R)					FC95M																														
4037331	4.680	5.950	C	2007	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	7.0	5.0*	4.7*	2.5*														
AJAX PAVING INDUSTRIES, IN			(2009)		SPRIDE		RIDE	7.3	7.1	7.3	7.3	7.2	7.1	7.0	7.0	6.9	6.9	6.8	6.8	6.6	6.2													
4479181	4.219	6.410	C	2028	0012																														
15040000	6.376	9.443	R	1	1	60	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	6.5	6.5	6.0*															
60			2	6.5	65000		RIDE	8.8	8.7	8.6	7.8	7.9	7.5	8.0	8.0	7.9	7.9	7.9	7.7	7.7															
					FC5A																														
4289621	6.376	9.443	C	2014	0012		CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.4	8.3	4.5*														
PCS CIVIL LLC			(2016)		SPRIDE		RIDE	7.4		8.5	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.3	8.1													
15040000	6.376	9.443	L	1	1	60	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.5	6.0*	6.0*	6.0*	6.0*															
60			2	6.5	65000		RIDE	8.9	8.8	8.5	7.9	7.9	7.4	8.1	8.1	8.1	8.1	7.9	7.9	7.5															
SERVICE RD(8.1L)					FC5A																														
4289621	6.376	9.443	C	2014	0012		CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	8.2	4.5*														
PCS CIVIL LLC			(2016)		SPRIDE		RIDE	7.8	7.6	8.3	8.3	8.3	8.2	8.3	8.3	8.3	8.3	8.3	8.3	8.2	8.0													
15040000	4.680	6.376	L	1	1	45	CRACKING	10.0	8.5	8.5	7.0	6.5	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0															
60			3	6.7	55000		RIDE	6.8	6.8	6.4*	6.1*	5.8*	5.6	5.0*	4.2*	7.4	7.6	8.3	7.8	7.9															
FROM PARK PL(4.7L)					FC95M																														
4037331	4.680	5.950	C	2007	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.3	6.7	4.5*														
AJAX PAVING INDUSTRIES, IN			(2009)		SPRIDE		RIDE	7.3	6.6	7.2	7.1	7.0	7.0	7.0	6.9	6.7	6.6	6.6	6.6	6.5	6.1													
4479181	4.219	6.410	C	2028	0012																														
15040000	4.219	4.680	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*															
60			3	6.7	55000		RIDE	7.9	7.5	7.7	7.6	7.4	6.8	7.0	7.2	7.1	6.7	6.5	6.2	6.2															
BENNIGAN'S L(4.6L)					FC3																														
							CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	6.3*	5.6*	4.0*													
			(2017)				RIDE	6.3	6.1	6.1	7.1	6.9	6.7	6.9	6.8	6.7	6.3	6.0	6.2	6.3	5.9													
4479181	4.219	6.410	C	2028	0012																														
15040000	1.661	4.219	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*															
60			3	4.9	49500		RIDE	7.9	7.5	7.7	7.6	7.4	6.8	7.0	7.2	7.1	6.7	6.5	6.2	6.2															
GLENWOOD AVE S(1.7L)					FC125A																														
4325861	1.789	4.219	C	2016	0012		CRACKING	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.8	7.0														
PREFERRED MATERIALS, INC.			(2019)		SPRIDE		RIDE	6.3	6.1	6.1	6.3		7.5	7.4	7.4	7.3	7.1	7.1	7.1	7.3	6.9													
15045000	0.000	0.167	R	1	7	45	CRACKING							10.0	10.0	10.0	10.0	10.0	10.0	10.0															
60			2	4.9	36500		RIDE							7.8	7.9	8.2	8.1	8.2	7.9	8.0															
CSWY PARKING ENTR(0.0R)					FC125H																														
4416511	0.000	0.167	C	2024	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	5.8*	10.0	9.0														
PREFERRED MATERIALS, INC.			(2026)		SPRIDE		RIDE	8.2	8.1	7.6	7.6	6.9	7.3	7.1	7.3	7.3	7.0	6.9	6.9	8.5	8.1													
15045000	0.606	0.904	C	1	2	35	CRACKING							10.0	10.0	10.0	10.0	10.0	10.0	10.0															
60			2	7.3	21500		RIDE							7.1	6.9	7.3	7.4	7.2	7.1	6.8															
BRIDGE #244(0.6L)					FC125A																														
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
			(2017)				RIDE	7.1	6.6	5.9	6.5	5.9	6.3	6.3	6.6	6.8	6.2	6.0	6.1	6.6	6.2													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYS / %T / FY-P / FY-F	TYP / AADT / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SPD	DISTRESS / RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15045000	0.904	1.400	C	1	1	35	CRACKING									10.0	10.0	8.5	8.5	7.0	7.5	7.5													
60 A19			4	7.3	21500		RIDE									5.0*	4.8*	4.5*	4.5*	4.3*	4.5*	4.2*													
FT HARRISON AVE S(0.9C)					FC125A																													
4290561	0.943	1.285	C	2015	0012		CRACKING	5.5*	5.5*	4.0*	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.7	7.5	6.0*													
AJAX PAVING INDUSTRIES OF (2017)					SPRIDE			3.7*	3.3*	2.9*											4.6*	4.2*												
15045000	1.400	1.697	R	1	1	35	CRACKING									10.0	10.0	10.0	10.0	8.5	8.5	7.5													
60 A19			2	5.7	32000		RIDE									7.3	7.3	7.7	7.8	7.7	7.6	7.3													
M L KING AVE(1.4C)					FC125A																													
4290561	1.402	1.697	C	2015	0012		CRACKING	5.5*	5.5*	4.0*	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	8.2	8.0	6.5													
AJAX PAVING INDUSTRIES OF (2017)					SPRIDE			7.6	7.6	7.3	7.3	7.0	6.7	7.1	7.0	7.1	6.9	7.0	6.8	7.1	6.7													
15045000	1.400	1.697	L	1	1	35	CRACKING									10.0	10.0	8.5	8.5	8.5	8.5	7.5													
60 A19			2	5.7	32000		RIDE									7.1	6.6	6.6	6.7	6.6	6.5	6.9													
COURT ST(1.4L)					FC125A																													
4290561	1.402	1.697	C	2015	0012		CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.8	6.0*													
AJAX PAVING INDUSTRIES OF (2017)					SPRIDE			7.1	7.1	6.5	6.9	6.3	6.5	6.6	6.6	6.7	6.5	6.6	6.7	6.3	5.9													
15045000	0.000	0.167	L	1	7	45	CRACKING									10.0	10.0	10.0	10.0	10.0	10.0	10.0													
60			2	4.9	36500		RIDE									6.3	7.6	7.8	7.8	7.8	7.8	7.7													
CSWY PARKING ENTR(0.0C)					FC125H																													
4416511	0.000	0.167	C	2024	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	6.8	10.0	9.0													
PREFERRED MATERIALS, INC. (2026)					SPRIDE			7.8	7.8	7.2	7.2	6.5	6.8	7.0	6.9	6.7				8.1	7.7													
15045101	0.000	0.764	C	1	1	30	CRACKING									10.0	10.0	8.5	8.5	8.5	8.0	8.0													
60 A19			4	7.3	15500		RIDE									5.4*	5.3*	5.2*	5.3*	4.8*	5.5	5.4*													
CHESTNUT ST(0.0C)					FC125A																													
							CRACKING	5.5*	5.5*	4.0*	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.1	7.6	6.0*													
				(2017)			RIDE	5.7	5.1*	4.2*										4.9*	4.5*													
15050002	0.000	1.133	R	1	7	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5														
580			2	7.2	19900		RIDE	8.4	8.4	8.3	7.9	7.8	7.7	7.5	7.7	7.7	7.6	7.6	7.6	7.4														
ST PETERSBURG DR(0.0R)					FC125M																													
4402481	0.000	0.723	R	2023	0012		CRACKING	9.5	8.5	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*	5.5*		10.0	9.0													
PREFERRED MATERIALS, INC. (2026)					SPRIDE			7.1	7.4	7.0	6.8	6.8	6.8	6.7	6.6	6.7	6.7	6.6		8.3	7.9													
15050002	0.000	1.133	L	1	7	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5														
580			2	7.2	19900		RIDE	8.1	8.1	8.1	8.0	7.5	7.3	7.5	7.3	7.3	7.1	7.0	7.2	6.9														
FOREST LAKES BLVD(0.0L)					FC125M																													
4402481	0.000	0.723	L	2023	0012		CRACKING	7.0	7.0	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.0*		10.0	9.0													
PREFERRED MATERIALS, INC. (2026)					SPRIDE			6.6	6.7	6.4	6.3	6.3	6.3	6.1	6.1	6.1	5.9	6.0		8.1	7.7													
15050003	0.247	2.890	C	1	1	40	CRACKING																											
590			4	9.1	27000		RIDE																											
VINE AVE(0.3L)					FC125																													
							CRACKING											7.0	7.0	7.0	6.0*	5.6*													
							RIDE											5.7	5.7	5.5	5.7	5.7													
15050004	0.000	0.184	C	1	1	40	CRACKING																											
590			2	18.5	11000		RIDE																											
DREW ST(0.0R)					FC125R																													
							CRACKING											5.5*	5.5*	3.0*	3.5*	3.3*													
							RIDE											5.3*	4.9*	4.6*	4.7*	4.4*													
15050004	0.184	1.059	C	1	1	45	CRACKING																											
590			2	18.5	11000		RIDE																											
MARILYN ST(0.4L)					FC125R																													
							CRACKING											8.5	8.5	8.5	8.6	8.1	7.0												
				(2022)			RIDE											6.9	6.8	6.8	6.8	7.0	6.6												
15050004	1.059	1.747	R	1	1	45	CRACKING																											
590			2	18.5	11000		RIDE																											
OLD COACHMAN RD(1.1C)																																		
							CRACKING											8.5	8.5	8.5	8.6	8.5	7.0												
				(2022)			RIDE											6.9	6.8	6.8	6.8	6.3	5.9												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / G_BMP / G_EMP / LN / %T / AADT / INTERSECT AT (MP|SIDE) / SURFTYPE / ITMSEG-P / W_BMP / W_EMP / RW / FY-P / WKMX-P / CONTRACTOR (AGE_ONE YEAR) / ASTYPE / ITMSEG-F / W_BMP / W_EMP / RW / FY-F / WKMX-F		2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE (PMRS)
15050005 0.000 0.991 C 1 1 45	CRACKING																						5.5*	8.0	8.0	7.0	6.7	
590 2 18.5 14500	RIDE																						6.5	7.2	7.1	7.1	6.9	
COACHMAN PLAZA DR(0.1L) DGFC																												
15050005 0.991 2.410 C 1 1 35	CRACKING																						5.5*	5.5*	3.5*	10.0	10.0	9.0
590 2 18.5 6400	RIDE																						6.5	6.0	5.8	6.4	6.5	6.1
LAWRENCE DR(1.0L) FC125H																												
4416561 1.252 2.410 C 2023 0012																												
HUBBARD CONSTRUCTION COMPA(2025)																												
15050005 4.629 5.978 C 1 1 40	CRACKING																						7.0	7.0	7.0	6.8	6.4*	
590 2 18.5 10000	RIDE																						7.3	7.3	6.9	7.2	7.0	
PHILIPPE PARK ENTR(4.7R) FC95																												
4492091 4.629 5.978 C 2029 0012																												
15061000 0.000 0.165 R 1 1 40	CRACKING																					10.0	10.0	10.0	10.0	10.0	10.0	
694 2 4.8 59500	RIDE																					6.8	7.2	7.1	7.0	7.1	7.0	
PINELLAS PARK CITY LIMIT(0.0C) FC125M																												
4416501 0.000 0.177 C 2023 0012	CRACKING	9.0	9.0	9.0	8.0	7.5	6.0*	6.0*	6.0*	3.5*	3.5*	3.5*	10.0	10.0	9.0													
AJAX PAVING INDUSTRIES OF (2025) SPRIDE		7.0	6.7	6.5	6.3	6.5	6.1	6.2	6.0	6.2	5.8	5.7	8.0	8.1	7.7													
15061000 0.165 2.693 R 1 1 45	CRACKING									8.5	6.5	6.5	6.5	6.5	6.5													
694 3 4.8 47500	RIDE									6.0	4.9*	5.6	5.6	5.5	5.3*													
43 ST(0.4C) FC125A																												
4290571 0.200 2.693 C 2014 0012	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.1	7.7	6.0*													
PREFERRED MATERIALS, INC. (2016) SPRIDE		5.3*	5.1*		7.0	6.8	6.6	6.7	6.7	6.6	6.5	6.6	6.3	6.5	6.1													
15061000 2.693 5.130 R 1 1 45	CRACKING									10.0	9.0	9.0	7.5	7.5	7.0													
693 3 4.5 38000	RIDE									6.4	6.2	6.5	6.4	6.3	6.2													
76 AVE(2.8R) FC125A																												
4290581 3.705 6.314 C 2015 0012	CRACKING	7.0	7.0		10.0	10.0	10.0	8.5	7.5	7.0	7.0	7.0	6.0*	6.0*	4.5*													
PREFERRED MATERIALS, INC. (2017) SPRIDE		6.2	6.0		8.1	8.1	7.9	8.0	7.9	7.3	7.2	6.9	6.9	7.0	6.6													
4492101 2.693 5.130 C 2029 0012																												
15061000 5.130 6.314 R 1 1 45	CRACKING									8.5	8.5	8.5	8.5	8.5	8.5													
693 3 6.5 39000	RIDE									7.4	7.6	7.4	7.4	7.4	7.3													
116 AVE(5.3R) FC5A																												
(2022)	CRACKING	8.5	8.5		10.0	10.0	10.0	8.5	7.5	10.0	10.0	10.0	8.6	8.1	6.0*													
	RIDE	7.0	7.2		8.1	8.1	7.9	8.0	7.9	8.3	8.3	8.3	8.3	8.3	8.1													
15061000 6.314 6.607 R 1 1 45	CRACKING										9.0	9.0	9.0	9.0														
693 3 15.9 35000	RIDE										7.5	7.8	7.6	7.2														
LARGO CITY LIMITS(6.4C) FC125H																												
4402451 6.314 6.556 C 2020 0012	CRACKING	7.0	7.0	6.5	6.5	3.5*	0.0*	0.0*	0.0*	10.0	10.0	10.0	8.8	10.0	8.5													
AJAX PAVING INDUSTRIES OF (2022) SPRIDE		7.4	6.8	6.4	5.5	5.2*	4.7*	4.5*	4.1*	6.5	6.6	6.2	6.4	6.4	6.0													
15061000 6.607 6.946 R 1 1 45	CRACKING										9.0	9.0	9.0	9.0														
693 3 15.9 35000	RIDE										7.5	7.8	7.6	7.2														
138 AVE(6.7R) FC5A																												
4290581 6.618 6.946 C 2015 0012	CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	5.5*													
PREFERRED MATERIALS, INC. (2017) SPRIDE		7.4	6.8	6.4	8.4	8.3	8.2	8.4	8.1	8.1	8.0	8.2	8.0	8.1	7.9													
15061000 6.946 7.160 C 1 1 45	CRACKING										10.0	10.0	10.0	10.0	10.0													
693 2 15.9 17000	RIDE																											
CR 376(6.9C) FC4																												
(2009)	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.2	8.5	6.0*													
	RIDE													6.4	6.0													
15061000 6.607 6.946 L 1 1 45	CRACKING										7.5	6.5	6.5	6.5														
693 2 15.9 35000	RIDE										7.1	7.2	7.3	7.2														
4290581 6.618 6.946 C 2015 0012	CRACKING	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.6	5.0*													
PREFERRED MATERIALS, INC. (2017) SPRIDE		7.2	6.8	6.9	8.1	8.3	8.1	8.3	8.3	8.5	8.6	8.6	8.5	7.9	7.7													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15061000	6.314	6.607	L	1	1	45	CRACKING												7.5	6.5	6.5	6.5													
693		3 15.9		35000			RIDE												7.1	7.2	7.3	7.2													
LARGO CITY LIMITS(6.4C)							FC125H																												
4402451	6.314	6.556	C	2020		0012	CRACKING	4.5*	3.5*	3.5*	4.5*	3.5*	3.5*	3.5*	0.0*	10.0	10.0	10.0	9.5	10.0	8.5															
AJAX PAVING INDUSTRIES OF (2022)							SPRIDE	7.2	6.8	6.9	5.2*	4.9*	4.3*	4.0*	3.4*	6.2	6.1	5.9	5.7	6.1	5.7													
15061000	5.130	6.314	L	1	1	45	CRACKING								8.5	8.5	8.5	7.5	7.5	7.5															
693		3 6.5		39000			RIDE								7.4	7.6	7.4	7.4	7.2	7.0															
114 AVE(5.2L)							FC5A																												
4290581	3.705	6.314	C	2015		0012	CRACKING	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	5.5*														
PREFERRED MATERIALS, INC. (2017)							SPRIDE	7.0	7.0		8.3	8.3	8.1	8.2	8.1	8.5	8.4	8.4	8.4	8.5	8.3														
15061000	2.693	5.130	L	1	1	45	CRACKING								10.0	9.0	9.0	9.0	7.5	7.5															
693		3 4.5		38000			RIDE								6.8	6.8	6.3	6.2	6.1	6.0															
78 AVE N(2.9C)							FC125A																												
4290581	3.705	6.314	C	2015		0012	CRACKING	7.0	7.0		10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.5	7.2	7.0	5.5*														
PREFERRED MATERIALS, INC. (2017)							SPRIDE	5.9	5.8		8.3	8.3	8.1	8.2	8.1	7.6	7.5	7.5	7.4	7.4	7.0														
4492101	2.693	5.130	C	2029		0012																													
15061000	0.165	2.693	L	1	1	45	CRACKING								8.5	6.0*	6.0*	6.0*	7.0	7.0															
694		3 4.8		47500			RIDE								6.0	5.6	5.8	5.8	5.6	5.5															
43 ST(0.4C)							FC125A																												
4290571	0.200	2.693	C	2014		0012	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	7.8	7.2	5.5*														
PREFERRED MATERIALS, INC. (2016)							SPRIDE	5.4*			7.1	7.0	6.8	6.9	6.8	6.6	6.6	6.4	6.6	6.6	6.2														
15061000	0.000	0.165	L	1	1	40	CRACKING								10.0	10.0	10.0	10.0	9.0	9.0															
694		2 4.8		59500			RIDE								7.3	7.3	6.6	7.1	7.1	6.8															
PINELLAS PARK CITY LIMIT(0.0C)							FC125M																												
4416501	0.000	0.177	C	2023		0012	CRACKING	9.0	9.0	9.0	9.0	7.5	7.0	6.0*	6.0*	3.5*	3.5*	3.0*	10.0	9.5	8.5															
AJAX PAVING INDUSTRIES OF (2025)							SPRIDE	7.0	6.9	7.1	7.3	7.1	6.8	7.1	6.8	7.1	6.7	7.1	7.8	7.6	7.2														
15061101	0.000	0.187	C	1	1	45	CRACKING									10.0	10.0	10.0	10.0	10.0															
693		2 7.3		900			RIDE																												
MISSING DESCRIPTION I(0.0L)							FC4																												
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.7	9.2	7.5															
		(2018)					RIDE													8.1	7.7															
15070000	0.602	1.200	R	1	1	40	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0															
580		2 4.9		17100			RIDE	7.0	6.8	6.6	6.5	6.3	6.4	6.2	6.5	6.5	6.6	6.6	6.4	6.5															
NEW YORK AVE(0.8R)							FC125M																												
4326991	0.602	1.275	C	2017		0012	CRACKING	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5															
HUBBARD CONSTRUCTION COMPA(2018)							RIDE	6.4	6.4	5.6	5.9	7.3	7.2	7.2	7.3	7.2	7.0	7.0	7.0	6.7	6.3														
15070000	1.200	2.319	R	1	1	45	CRACKING	10.0	10.0	10.0	8.5	7.0	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0															
580		3 3.9		47000			RIDE	7.7	7.6	7.4	7.0	6.8	6.7	5.9	6.5	6.2	6.5	6.1	7.9	8.0															
CROSLEY DR(1.3R)							FC125R																												
4168471	1.414	2.319	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	7.0	7.0	6.0*	4.5*	2.5*															
PREFERRED MATERIALS, INC. (2012)							RIDE	7.9	7.9	7.7	7.7	7.8	7.8	7.6	7.6	7.5	7.5	7.4	7.4	7.2	6.8														
4512371	1.267	3.141	C	2029		0012																													
15070000	2.319	3.202	R	1	1	45	CRACKING	10.0	8.5	7.0	7.0	7.0	7.0	6.5	10.0	10.0	9.0	9.0	10.0	10.0															
580		3 3.9		47000			RIDE	8.1	8.0	7.9	7.3	7.2	6.8	6.8	7.3	7.2	7.1	7.1	8.0	8.2															
CREEK PARK CT(2.3R)							FC125R																												
4113271	2.319	3.202	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.0	7.0	7.0	7.0	6.5	5.5*	3.5*															
PREFERRED MATERIALS, INC. (2012)							RIDE	8.2	8.1	7.9	7.8	7.8	7.8	7.8	7.7	7.6	7.4	7.3	7.4	7.2	6.8														
4512371	1.267	3.141	C	2029		0012																													
15070000	3.202	4.115	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.5	6.5	6.5	6.5	6.5															
580		3 3.9		38000			RIDE	7.1	7.0	6.8	6.6	6.4*	6.3	6.2	6.6	6.7	6.7	6.1	5.9	5.9															
DUNEDIN CITY LIMITS(3.3C)							FC125R																												
4271631	3.179	4.175	C	2013		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	8.6	8.5	6.5															
PREFERRED MATERIALS, INC. (2014)							RIDE	7.8	7.7	7.4	7.4	7.4	7.3	7.3	7.2	7.1	7.3	7.3	7.2	7.3	6.9														
15070000	4.115	5.733	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0															
580		3 11.1		32500			RIDE	7.9	8.4	8.3	7.5	7.8	7.7	7.2	7.4	7.3	6.8	7.1	7.1	7.3															
COUNTRYSIDE BLVD(4.1C)							DGFC																												
4497811	4.149	4.954	R	2022		0226	CRACKING	9.0	9.0	9.0	9.0	8.0	7.0	7.0	7.0	7.0	6.0*	10.0	10.0	9.5	8.5															
AJAX PAVING INDUSTRIES OF (2024)							RIDE	7.4	7.2	7.2	7.4	7.1	7.1	7.2	7.2	7.2	7.2	8.1	8.1	8.1	7.7														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / US / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / SURFTYPE / RW	SYS / %T / FY-P / FY-F	TYP / AADT / WKMX-P / WKMX-F	SPD / ASTYPE	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15070000	5.733	6.370	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5													
580			2	15.8	31500		RIDE	8.0	8.1	8.0	7.6	7.8	7.6	6.9	7.1	7.1	7.0	7.1	6.8	6.7													
BAY HILLS BLVD N(5.8R)					FC125M																												
4289351	5.970	6.852	C	2014	0012		CRACKING	8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	9.1	7.0												
PREFERRED MATERIALS, INC. (2015)							RIDE	6.7	8.4	8.0	7.9	8.0	8.1	8.1	7.9	8.1	8.0	7.8	7.9	8.0	7.6												
15070000	6.774	7.370	R	1	7	45	CRACKING																										
580			2	3.9	35500		RIDE																										
SHORE BLVD(6.9R)					FC125M																												
4402481	6.764	7.370	C	2023	0012		CRACKING									6.0*	6.0*	6.0*		10.0	9.0												
PREFERRED MATERIALS, INC. (2026)						SPR	IDE									5.9	5.7	5.7		8.4	8.0												
15070000	6.774	7.370	L	1	7	45	CRACKING																										
580			2	3.9	35500		RIDE																										
PALM KEY AVE(6.9L)					FC125M																												
4402481	6.764	7.370	C	2023	0012		CRACKING									6.0*	6.0*	6.0*		10.0	9.0												
PREFERRED MATERIALS, INC. (2026)						SPR	IDE									6.2	5.9	5.7		8.1	7.7												
15070000	5.733	6.370	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	6.0*	6.0*													
580			2	15.8	31500		RIDE	8.1	8.2	7.9	7.6	7.5	7.5	7.4	7.3	7.1	7.0	6.9	6.7	6.2													
COUNTRY VILLAS DR(5.9L)					FC125M																												
4289351	5.970	6.852	C	2014	0012		CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.8	8.7	7.0												
PREFERRED MATERIALS, INC. (2015)							RIDE	6.1	8.4	8.0	8.0	8.0	7.9	8.0	8.0	7.9	7.9	7.8	7.7	7.6	7.2												
15070000	4.115	5.733	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5													
580			3	11.1	32500		RIDE	7.7	7.9	8.2	7.7	7.3	7.4	7.0	7.2	7.1	6.9	6.7	6.6	6.8													
COUNTRYSIDE BLVD(4.1C)					DGFC																												
4497811	4.149	4.954	L	2022	0226		CRACKING	8.5	8.5	7.5	7.5	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	9.6	8.5												
AJAX PAVING INDUSTRIES OF (2024)							RIDE	6.6	6.7	6.9	6.9	6.8	6.6	6.7	6.7	6.5	6.5	8.0	8.0	8.1	7.7												
15070000	3.202	4.115	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	6.5	6.5	6.5	6.5													
580			3	3.9	38000		RIDE	7.6	7.6	7.4	6.8	6.8	6.8	6.7	6.6	6.6	6.8	6.8	6.5	6.3													
FR 15150400 FRNT SB(3.3L)					FC125R																												
4271631	3.179	4.175	C	2013	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.9	8.7	7.0												
PREFERRED MATERIALS, INC. (2014)							RIDE	7.7	7.6	7.4	7.2	7.2	7.2	7.2	7.3	7.1	7.1	6.9	7.0	7.1	6.7												
15070000	2.319	3.202	L	1	1	45	CRACKING	10.0	8.5	8.5	8.5	8.5	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0													
580			3	3.9	47000		RIDE	7.2	7.3	7.1	5.1*	6.6	6.4	6.2	7.3	6.6	7.3	7.2	8.2	8.1													
KING ARTHUR CT(2.5L)					FC125R																												
4113271	2.319	3.202	C	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	7.0	7.0	6.5	5.5*	3.5*												
PREFERRED MATERIALS, INC. (2012)							RIDE	8.0	8.1	7.9	7.7	7.7	7.6	7.6	7.6	7.4	7.3	7.3	7.2	7.2	6.8												
4512371	1.267	3.141	C	2029	0012																												
15070000	1.200	2.319	L	1	1	45	CRACKING	10.0	8.5	7.0	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	4.5*	10.0	10.0													
580			3	3.9	47000		RIDE	7.8	7.5	7.6	6.6	7.0	6.4	6.2	6.4	6.5	6.4	6.5	7.4	7.1													
LADY MARION LN(1.2L)					FC125R																												
4168471	1.414	2.319	C	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.0	6.5	5.5*	3.5*												
PREFERRED MATERIALS, INC. (2012)							RIDE	7.0	6.7	7.5	7.3	7.4	7.2	7.1	7.3	7.1	7.0	6.9	6.9	6.6	6.2												
4512371	1.267	3.141	C	2029	0012																												
15070000	0.602	1.200	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0													
580			2	4.9	17100		RIDE	7.5	7.7	7.6	7.0	7.0	6.7	6.5	6.2	6.6	7.0	6.3	5.9	5.6													
BASS BLVD(0.6L)					FC125M																												
4326991	0.602	1.275	C	2017	0012		CRACKING	7.0	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0												
HUBBARD CONSTRUCTION COMPA(2019)							RIDE	6.4	6.3	6.6	6.5		7.6	7.5	7.2	7.4	7.3	7.3	7.0	6.6	6.2												
15070001	0.000	0.479	R	1	8	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	7.0													
580			2	4.9	11500		RIDE	7.5	7.2	7.1	6.2	6.8	7.1	6.0	6.7	7.3	7.2	6.9	7.0	6.9													
BROADWAY ST(0.0C)					FC125M																												
4326991	0.079	0.479	C	2017	0012		CRACKING	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5														
HUBBARD CONSTRUCTION COMPA(2018)							RIDE	6.4	6.7	6.6	6.0	7.8	7.4	7.3	7.3	7.1	7.0	7.1	7.0														
15070001	0.000	0.479	L	1	2	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.0	7.0	7.0													
580			2	4.9	11500		RIDE	7.6	7.7	7.5	6.6	6.4	6.3	6.1	6.7	6.8	7.2	6.9	7.0	6.9													
BROADWAY ST(0.0C)					FC125M																												
4326991	0.079	0.479	C	2017	0012		CRACKING	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.9	6.5												
HUBBARD CONSTRUCTION COMPA(2018)							RIDE	6.4	6.7	6.6	6.0	7.8	7.4	7.3	7.3	7.1	7.0	6.8	7.0	5.4*	5.0*												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD / LN / %T / FY-P / FY-F	AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15080000	0.000	2.135	R	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.5	7.5	7.5													
584			3	18.5		44000		RIDE	8.3	8.7	8.6	8.2	8.2	7.9	7.9	8.3	8.2	8.0	7.9	7.6	7.5													
SR-586/CURLEW RD(0.0R)							FC125M																												
4376261	0.000	2.017	C	2020		0012		CRACKING	7.5	7.5	7.0	6.0*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	9.6	10.0	8.5												
HUBBARD CONSTRUCTION COMPA						(2022)	SPRIDE	RIDE	7.5	7.6	7.8	7.8	7.8	7.7	7.7	7.7	8.2	8.1	8.1	8.0	8.0	7.6												
15080000	2.135	2.513	R	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	6.5	6.5	6.5	6.5	6.5	10.0													
580			4	4.5		55500		RIDE	8.3	8.7	8.6	8.2	8.2	7.9	7.9	8.1	7.8	7.7	7.4	7.3	7.6													
FROM SR 580(2.1R)							FC125M																												
								CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	9.1	10.0	8.5												
						(2022)		RIDE	7.6	7.1	7.1	7.2	7.3	7.0	6.8	6.9	8.0	7.9	7.8	7.7	7.7	7.3												
15080000	2.513	2.974	R	1	1	45		CRACKING																											
580			4	4.5		55500		RIDE																											
							OGFC																												
								CRACKING									7.5	7.5	7.5	7.0	6.6														
								RIDE									7.3	7.3	7.4	7.3	7.3														
4514561	2.513	2.974	C	2029		0012																													
15080000	2.513	2.974	L	1	1	45		CRACKING																											
580			4	4.5		55500		RIDE																											
							OGFC																												
								CRACKING									7.5	7.5	7.5	6.6	6.5														
								RIDE									7.4	7.3	7.3	7.1	7.1														
4514561	2.513	2.974	C	2029		0012																													
15080000	2.135	2.513	L	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.0	4.5*	4.5*	10.0													
580			4	4.5		55500		RIDE	8.9	8.6	8.8	8.0	8.0	7.6	8.0	8.1	8.0	7.9	5.4*	5.3*	7.7													
CORPORATE CENTER ENT(2.5L)							FC125M																												
								CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	9.1	10.0	8.5												
						(2022)		RIDE	7.6	7.1	7.3	7.4	7.5	7.1	7.2	7.2	8.0	8.1	8.0	7.9	7.8	7.4												
15080000	0.000	2.135	L	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.0	9.0	8.5	8.5													
584			3	18.5		44000		RIDE	8.9	8.6	8.8	8.0	8.0	7.6	8.0	8.1	8.0	7.9	7.9	7.9	7.4													
CR-752/TAMPA RD(0.0L)							FC125M																												
4376261	0.000	2.017	C	2020		0012		CRACKING	7.5	7.5	6.0*	6.0*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	9.6	10.0	8.5												
HUBBARD CONSTRUCTION COMPA						(2022)	SPRIDE	RIDE	7.4	7.4	7.7	7.6	7.6	7.4	7.6	7.5	8.3	8.3	8.3	8.1	8.1	7.7												
15090000	0.000	0.895	C	1	1	30		CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0													
687 92			4	5.3		12000		RIDE	5.5*	6.0	5.3*	4.5*	4.0*	3.8*	3.8*	4.1*	6.3	6.4	6.3	6.3	5.9													
DALI BLVD S/5 AVE S(0.0R)							DGFC																												
2570631	0.000	0.895	C	2006		0005		CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.4*	6.5	4.0*												
						(2009)		RIDE	6.0	5.8	5.6	5.7	5.5	5.5	5.3*	5.0*	5.3*	5.2*	5.0*	5.1*	4.9*	4.5*												
15090000	0.895	2.329	R	1	1	35		CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*													
687 92			2	1.9		29000		RIDE	8.4	8.4	7.9	7.6	7.5	6.9	6.9	6.8	6.4	6.1	5.9	5.9	6.0													
SIXTH AVE N(1.0R)							FC95MR																												
4271621	1.138	2.329	C	2013		0012		CRACKING	6.0*		10.0	10.0	10.0	10.0	9.0	7.0	7.0	7.0	7.0	6.8	6.5	4.5*												
PREFERRED MATERIALS, INC.						(2016)	SPRIDE	RIDE	5.8		8.0	7.9	7.9	7.7	7.7	7.7	7.6	7.5	7.5	7.4	7.2	6.8												
4479191	0.812	2.428	C	2027		0012																													
15090000	2.329	6.857	R	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*													
687 92			3	5.3		32500		RIDE	8.1	8.2	8.1	7.5	7.6	7.7	7.4	7.4	7.4	7.5	7.4	7.1	7.1													
THIRTIETH AVE N(2.4C)							FC95MR																												
4271621	2.517	6.605	C	2013		0012		CRACKING	6.0*		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.2	6.5												
PREFERRED MATERIALS, INC.						(2016)	SPRIDE	RIDE	6.9		8.1	8.0	7.9	7.9	8.0	7.8	7.9	7.8	7.7	7.7	7.7	7.3												
15090000	7.645	9.992	R	1	1	55		CRACKING	8.5	8.5	7.0	7.0	7.0	5.0*	5.0*	5.0*	4.5*	4.5*	4.5*	10.0	10.0												
600 92			2	7.0		45505		RIDE	8.6	8.7	8.6	7.8	7.7	7.7	7.7	7.6	7.8	7.6	7.4	8.2	8.3													
GOODWILL INDUST ENT(7.7R)							FC5																												
4168381	7.340	9.992	C	2010		0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	6.5	6.5	5.5*	5.6*	1.0*												
TAMPA PAVEMENT CONSTRUCTOR						(2012)	SPRIDE	RIDE	8.2	8.3	8.4	8.3	8.2	8.2	8.2	8.2	8.2	8.2	8.1	8.1	8.0	7.8												
4512381	7.645	9.992	C	2027		0012																													
15090000	7.645	9.992	L	1	1	55		CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	10.0	10.0													
600 92			2	7.0		45505		RIDE	8.7	8.7	8.6	8.1	8.1	8.0	8.0	7.9	7.9	7.9	7.9	8.3	8.3													
MANGROVE CAY LN NE(7.9L)							FC5																												
4168381	7.340	9.992	C	2010		0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	5.5*	5.1*	0.5*												
TAMPA PAVEMENT CONSTRUCTOR						(2012)	SPRIDE	RIDE	8.3	8.3	8.4	8.3	8.2	8.2	8.4	8.3	8.3	8.3	8.3	8.2	8.0	7.8												
4512381	7.645	9.992	C	2027		0012																													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYS / %T / FY-P / FY-F	TYP SPD / AADT / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15090000	2.329	6.857	L	1	1 45	CRACKING	10.0	10.0	8.5	8.5	8.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	6.0*	6.0*															
687 92			3	5.3	32500	RIDE	8.0	8.1	7.9	7.3	7.4	7.3	7.1	7.1	7.0	7.1	6.9	6.8	6.7															
THIRTIETH AVE N(2.4C)					FC95MR																													
4271621	2.517	6.605	C 2013		0012	CRACKING	6.0*		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.4	8.0	6.0*													
PREFERRED MATERIALS, INC. (2016)					SPRIDE		6.5		8.0	8.0	7.9	7.8	7.8	7.7	7.7	7.7	7.7	7.7	7.6	7.2													
15090000	0.895	2.329	L	1	1 35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.0*	6.0*	6.0*	6.0*	6.0*															
687 92			2	1.9	29000	RIDE	7.8	7.7	7.3	6.6	6.7	6.5	6.5	6.5	6.2	6.0	5.7	5.5	5.3*															
6 AVE N(1.0L)					FC95MR																													
4271621	1.138	2.329	C 2013		0012	CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	7.0	7.0	6.5	6.5	6.4*	6.5	4.5*													
PREFERRED MATERIALS, INC. (2016)					SPRIDE		5.3*		7.8	7.7	7.6	7.5	7.4	7.3	7.3	7.1	7.1	6.8	6.7	6.3													
4479191	0.812	2.428	C 2027		0012																													
15090001	0.000	0.218	C	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5															
687 92			2	4.0	7900	RIDE	7.9	7.5	7.7	7.6	7.3	7.3	7.0	7.5	7.4	7.4	7.3	7.2	7.0															
SR 687(0.0C)					DGFC																													
						CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.0*	6.0*		6.5	3.5*													
				(1999)		RIDE	6.8	7.0	6.3	6.3	6.3	6.2	6.1	6.0	5.9	5.7	5.8		5.2*	4.8*													
15090010	0.000	0.312	R	1	1 55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	8.0	10.0	10.0															
600 92			2	9.3	57000	RIDE	7.0	7.3	7.7	8.0	8.1	7.5	7.7	7.7	7.3	7.6	7.6	8.2	8.2															
W OF ACCESS RD(0.0C)					OGFC																													
4168381	0.000	0.312	C 2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	6.2*	5.8*	1.0*													
TAMPA PAVEMENT CONSTRUCTOR(2012)						RIDE	8.2	8.2	8.3	8.2	8.3	8.2	8.3	8.2	8.2	8.2	8.2	8.3	8.2	8.0													
4512381	0.000	0.312	C 2027		0012																													
15090010	0.000	0.312	L	1	1 55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	10.0	10.0															
600 92			2	9.3	57000	RIDE	7.0	7.3	7.7	8.0	7.7	7.5	8.0	7.9	8.0	8.0	8.1	8.3	8.3															
W OF ACCESS RD(0.0C)					OGFC																													
4168381	0.000	0.312	C 2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	6.5	5.8*	1.0*													
TAMPA PAVEMENT CONSTRUCTOR(2012)						RIDE	8.3	8.3	8.2	8.2	8.1	8.1	8.2	8.0	8.1	7.9	7.9	8.0	7.9	7.7													
4512381	0.000	0.312	C 2027		0012																													
15090101	0.000	0.812	C	1	1 30	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0															
687 92			4	3.6	9600	RIDE	5.4*	5.5	5.3*	4.7*	4.2*	4.3*	4.0*	3.9*	6.4	6.7	6.6	6.6	6.5															
US-19A/SR-595(0.0R)					DGFC																													
4055731	0.000	0.812	C 2006		0012	CRACKING	10.0	10.0	9.0	9.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.1	6.9	4.5*													
				(2009)		RIDE	6.6	6.4	6.2	5.8	5.9	5.9	5.7	5.7	5.6	5.4*	5.2*	5.5	5.5	5.1*													
15100000	0.111	2.624	R	1	1 35	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.5	6.5	6.5	6.5															
699			2	3.9	22500	RIDE		7.8	7.7	7.2	7.1	6.8	6.6	6.8	6.8	6.4	6.3	6.2	6.0															
36 AVE(0.2C)					FC125A																													
4306621	0.227	2.459	C 2015		0012	CRACKING	6.5	5.5*	4.0*	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.4	6.8	5.0*													
PREFERRED MATERIALS, INC. (2017)						RIDE	5.9	5.9	5.3*	7.0	6.9	6.5	6.7	6.5	6.4	6.1	6.0	5.9	5.8	5.4*													
15100000	2.624	2.885	R	1	1 30	CRACKING	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
699			2	8.9	13500	RIDE	7.5	7.5			7.7	7.4	6.8	7.2	6.7	6.7	6.6	6.1	6.3															
76 AVE(2.6R)					FC125																													
2570881	2.544	3.610	C 2001		0213	CRACKING	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	5.8*	3.0*													
APAC-FLORIDA INC				(2005)		SPRIDE	6.6	6.6	5.9	5.9	5.9	5.7	5.7	5.5	5.5	5.3*	5.3*	5.3*	4.1*	3.7*													
4492131	2.595	4.083	C 2028		0012																													
15100000	2.885	3.105	R	1	1 35	CRACKING	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
699			2	8.9	13500	RIDE	7.5	7.5			7.7	7.4	6.8	7.2	6.7	6.7	6.6	6.1	6.3															
80 AVE(2.9R)					DGFC																													
2570881	2.544	3.610	C 2001		0213	CRACKING	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	8.2	5.5*													
APAC-FLORIDA INC				(2005)		SPRIDE	6.6	6.6	5.9	5.9	5.9	5.7	5.7	5.5	5.5	5.3*	5.3*	5.3*	4.6*	4.2*													
4492131	2.595	4.083	C 2028		0012																													
15100000	3.105	3.596	R	1	1 35	CRACKING	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
699			2	8.9	13500	RIDE	7.5	7.5			7.7	7.4	6.8	7.2	6.7	6.7	6.6	6.1	6.3															
85 AVE(3.1C)					FC125																													
2570881	2.544	3.610	C 2001		0213	CRACKING	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	5.8*	3.0*													
APAC-FLORIDA INC				(2005)		SPRIDE	6.6	6.6	5.9	5.9	5.9	5.7	5.7	5.5	5.5	5.3*	5.3*	5.3*	6.4	6.0													
4492131	2.595	4.083	C 2028		0012																													
15100000	3.596	4.083	R	1	1 35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	8.5															
699			2	8.9	13500	RIDE	7.6	7.7	7.2	7.4	7.3	7.1	6.6	6.2	7.2	7.0	6.6	6.5	6.4															
HARRELL AVE(4.0C)					FC3																													
						CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.6	4.5*													
				(1998)		RIDE	6.6	6.6	6.2	6.5	6.5	6.9	6.6	6.6	6.5	6.0	5.9	6.0	6.4	6.0													
4492131	2.595	4.083	C 2028		0012																													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15100000	4.083	4.883	C	1	1	35		CRACKING	6.0*	6.0*	4.5*	3.5*	3.5*	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0														
699			2	8.9	14700			RIDE	7.0	6.9	6.4	5.0*	5.2*	7.5	6.4	6.7	6.6	6.5	6.2	5.9	6.2														
99 AVE(4.1C)							FC125A																													
4314041	4.101	4.835	C	2015		0012		CRACKING	7.0	5.5*	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.5	7.5	6.9	6.0*	4.0*													
PREFERRED MATERIALS, INC.				(2016)				RIDE	5.0*	4.9*	7.5	7.4	7.3	7.2	7.1	7.1	6.9	6.8	6.6	6.7	6.7	6.3													
15100000	4.883	6.000	R	1	1	35		CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	6.5	6.5	6.5														
699			2	8.9	22000			RIDE	7.5	7.8	7.0	6.9	7.0	7.1	6.7	6.8	6.7	6.6	6.6	6.5	6.4														
106 AVE(4.9R)							FC95AR																													
4306611	4.835	6.009	C	2015		0012		CRACKING	6.5	4.5*	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.5	7.5	6.9	6.8	5.0*													
AJAX PAVING INDUSTRIES OF				(2016)				RIDE	6.3	6.2	7.5	7.4	7.3	7.2	7.1	7.1	6.9	6.8	6.6	6.7	6.5	6.1													
15100000	6.000	6.393	R	1	1	35		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0					10.0	10.0															
699			2	8.9	22000			RIDE	7.7	7.9	7.6	7.1	7.1	6.9	6.8					7.5	7.8															
126 AVE(6.0C)							DGFC																													
								CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	6.3*	4.0*													
				(2012)				RIDE	7.8	7.6	7.1	7.0	7.1	6.9	6.9	6.8	6.9	6.8	6.7	6.6	6.8	6.4													
15100000	6.393	6.572	R	1	1	35		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0					10.0	10.0															
699			2	8.9	22000			RIDE	7.7	7.9	7.6	7.1	7.1	6.9	6.8					7.5	7.8															
129 AVE(6.4C)							DGFC																													
								CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	8.9	7.0													
				(2012)				RIDE	7.8	7.6	7.1	7.0	7.1	6.9	6.9	6.8	6.9	6.8	6.7	6.6	6.6	6.2													
15100000	6.572	7.976	R	1	1	35		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5	6.5														
699			2	8.9	22000			RIDE	7.7	7.4	7.2	6.8	6.8	6.6	6.5	6.5	6.7	6.3	6.4	6.3	6.2														
131 AVE(6.6R)							FC125M																													
4289591	6.576	7.955	R	2014		0012		CRACKING	6.5	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	10.0	8.0													
LANE CONSTRUCTION CORPORAT				(2016)				RIDE	6.1	6.0	6.8	6.8	6.6	6.4	6.0	7.0	6.9	6.9	6.9	6.8	6.8	6.4													
15100000	7.976	9.097	R	1	1	40		CRACKING	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	8.5	8.5	8.5	8.5														
666			2	18.5	29500			RIDE	6.8	6.5	6.5	5.5	5.1*	5.1*	4.5*	7.4	6.8	6.8	6.9	6.8	6.5														
E MADEIRA AVE(8.0R)							DGFC																													
2571361	7.976	9.097	C	2006		0012		CRACKING	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	4.2*	3.7*	1.5*													
CONE & GRAHAM, INC.				(2008)				RIDE	6.5	6.4	6.0	5.9	6.0	5.7	6.0	5.7	5.6	5.5	5.3*	5.3*	5.1*	4.7*													
4479201	7.963	9.354	R	2028		0012																														
15100000	9.097	9.354	R	1	1	40		CRACKING	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0														
666			2	18.5	29500			RIDE	6.8	6.5	6.5	5.5	5.1*	5.1*	4.5*	7.4	7.6	7.3	7.4	7.5	7.5														
							DGFC																													
								CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	4.7*	4.1*	1.5*													
				(2008)				RIDE	7.0	7.3	7.1	7.3	7.1	7.1	7.0	7.1	7.0	6.9	6.9	6.9	6.8	6.4													
4479201	7.963	9.354	R	2028		0012																														
15100000	9.097	9.354	L	1	1	40		CRACKING	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0														
666			2	18.5	29500			RIDE	7.0	7.0	7.2	6.4	5.9	6.0	5.7	8.0	8.2	8.3	8.0	8.0	8.2														
							DGFC																													
								CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.5	8.5	7.0	6.0*	5.3*	3.8*	1.5*													
				(2008)				RIDE	7.9	8.1	7.9	7.8	7.9	7.8	7.7	7.8	7.7	7.7	7.7	7.7	7.7	7.3													
15100000	7.976	9.097	L	1	1	40		CRACKING	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	9.5	9.5	9.5	9.5														
666			2	18.5	29500			RIDE	7.0	7.0	7.2	6.4	5.9	6.0	5.7	7.7	7.1	7.3	7.1	7.3	6.8														
FROM MADEIRA WAY(8.0L)							DGFC																													
2571361	7.976	9.097	C	2006		0012		CRACKING	9.5	9.5	8.5	8.0	8.0	8.0	8.0	7.0	7.0	7.0	6.0*	4.6*	3.9*	1.5*													
CONE & GRAHAM, INC.				(2008)				RIDE	7.0	6.9	7.0	6.6	6.2	6.3	6.3	6.1	6.1	6.0	5.9	5.9	5.8	5.4*													
15100000	6.572	7.976	L	1	1	35		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	6.5	6.5	6.5	6.5														
699			2	8.9	22000			RIDE	7.4	7.1	6.9	6.1	6.3	6.4	5.9	6.1	5.9	6.3	6.4	6.3	6.2														
131 AVE(6.6L)							FC125M																													
4289591	6.576	7.955	L	2014		0012		CRACKING	6.5	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.0													
LANE CONSTRUCTION CORPORAT				(2016)				RIDE	6.1	6.0	6.8	6.8	6.6	6.4	6.0	7.0	6.9	7.1	7.1	7.0	6.9	6.5													
15100000	6.393	6.572	L	1	1	35		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0					10.0	10.0															
699			2	8.9	22000			RIDE	7.4	7.3	6.9	6.9	7.1	6.8	6.1					7.4	7.4															
129 AVE(6.4C)							DGFC																													
								CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	4.8*	7.8	5.5*													
				(2012)				RIDE	6.9	7.4	6.9	6.7	6.6	6.6	6.6	6.4	6.6	6.1	6.2	6.1	6.8	6.4													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T / SURFTYPE / FY-P / FY-F	AADT / WKMX-P / WKMX-F	DISTRESS / RATINGS / ASTYPE	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
15100000	6.000	6.393	L	1	1	35			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0					10.0	10.0													
699			2	8.9				22000	RIDE	7.4	7.3	6.9	6.9	7.1	6.8	6.1					7.4	7.4													
126 AVE(6.0C)									DGFC																										
									CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	4.8*	1.7*	0.0*												
							(2012)		RIDE	6.9	7.4	6.9	6.7	6.6	6.6	6.6	6.4	6.6	6.1	6.2	6.1	6.0	5.6												
15100000	4.883	6.000	L	1	1	35			CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	6.5	6.5	6.5												
699			2	8.9				22000	RIDE	7.5	7.3	6.6	6.6	6.7	6.4	6.3	6.2	6.1	6.6	6.6	6.5	6.4												
BILMAR(4.9L)									FC95AR																										
4306611	4.835	6.009	C	2015				0012	CRACKING	6.5	4.5*	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.5	7.5	7.6	7.8	6.0*											
AJAX PAVING INDUSTRIES OF							(2016)		RIDE	6.3	6.2	7.5	7.4	7.3	7.2	7.1	7.1	6.9	6.8	6.6	6.2	6.4	6.0											
15100000	3.596	4.083	L	1	1	35			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	9.5	9.5	8.5	8.5												
699			2	8.9				13500	RIDE	7.2	7.5	7.9	6.8	6.7	6.8	6.4	6.4	6.8	7.0	6.6	6.5	6.4												
HARRELL AVE(4.0C)									FC3																										
									CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	3.5*											
							(1998)		RIDE	6.6	6.6	6.2	6.5	6.5	6.9	6.6	6.6	6.5	6.0	5.9	4.8*	5.5	5.1*											
4492131	2.595	4.083	C	2028				0012																											
15100000	2.624	3.596	L	1	1	35			CRACKING	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0												
699			2	8.9				13500	RIDE	7.5	7.5			7.0	6.3	5.8	5.8	5.3*	6.7	6.6	6.1	6.3												
76 AVE(2.6L)									DGFC																										
2570881	2.544	3.610	C	2001				0213	CRACKING	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.2*	5.5*	3.0*											
APAC-FLORIDA INC				(2005)					SPRIDE	6.6	6.6	5.9	5.9	5.9	5.7	5.7	5.5	5.5	5.3*	5.3*	3.9*	3.8*	3.4*											
4492131	2.595	4.083	C	2028				0012																											
15100000	0.111	2.624	L	1	1	35			CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	6.5	6.5	6.5												
699			2	3.9				22500	RIDE		7.9	7.8	7.3	7.3	7.1	6.8	7.0	7.0	6.4	6.3	6.2	6.0												
36 AVE(0.2C)									FC125A																										
4306621	0.227	2.459	C	2015				0012	CRACKING	6.5	5.5*	4.0*	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.7	7.1	5.5*											
PREFERRED MATERIALS, INC.				(2017)					RIDE	5.9	5.9	5.3*	7.0	6.9	6.5	6.7	6.5	6.4	6.1	6.0	6.9	6.8	6.4											
15110000	0.000	0.925	R	1	1	35			CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	7.5												
693			2	14.4				27000	RIDE	6.1*		7.7	7.0	6.9	6.9	6.6	6.6	6.5	6.5	6.2	6.0	5.8												
BLIND PASS RD(0.0R)									FC125M																										
4348061	0.023	0.924	C	2018				0012	CRACKING	7.0	6.0*	6.0*	6.0*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5											
AJAX PAVING INDUSTRIES OF				(2020)					SPRIDE	5.9	5.7	5.5	5.6	5.7	5.5	6.9	6.9	6.5	6.4	6.2	6.1	6.2	5.8											
15110000	0.925	1.775	R	1	1	35			CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	7.5												
693			3	6.9				29000	RIDE	6.1*		7.7	7.0	6.9	6.9	6.6	6.6	6.5	6.5	6.2	6.0	5.8												
MATHEWS RD S(1.0R)									FC125M																										
4348061	1.247	1.766	C	2018				0012	CRACKING	7.0	6.0*	6.0*	6.0*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	8.8	9.3	8.0											
AJAX PAVING INDUSTRIES OF				(2020)					SPRIDE	5.9	5.7	5.5	5.6	5.7	5.5	7.6	7.6	7.5	7.4	7.6	7.6	7.8	7.4											
15110000	1.119	1.775	L	1	1	35			CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5												
693			3	6.9				29000	RIDE	5.3*		7.7	7.0	7.3	7.1	6.8	6.7	6.8	6.9	6.5	6.5	6.3												
HUFFMAN WAY(1.1L)									FC125M																										
4348061	1.247	1.766	C	2018				0012	CRACKING	8.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	10.0	8.5											
AJAX PAVING INDUSTRIES OF				(2020)					SPRIDE	6.5	6.3	6.4	6.7	6.6	6.5	8.3	8.1	8.2	8.2	8.1	7.9	8.0	7.6											
15110000	0.000	1.119	L	1	1	35			CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5												
693			2	6.9				29000	RIDE	5.3*		7.7	7.0	7.3	7.1	6.8	6.7	6.8	6.9	6.5	6.5	6.3												
SR-699/BLIND PASS RD(0.0L)									FC125M																										
4348061	0.023	0.924	C	2018				0012	CRACKING	8.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	8.6	10.0	8.5											
AJAX PAVING INDUSTRIES OF				(2020)					SPRIDE	6.5	6.3	6.4	6.7	6.6	6.5	7.4	7.3	7.4	6.9	6.8	6.5	7.2	6.8											
15120000	0.000	1.212	R	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5												
688			2	18.5				17500	RIDE	8.0	7.8	7.9	7.5	7.3	7.4	7.4	7.2	7.6	7.7	7.5	7.3	7.5												
SR-699(0.0R)									FC125																										
2570481	0.000	1.212	C	1997				0213	CRACKING	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	5.9*	5.2*	2.0*											
GLF CONSTRUCTION CORPORATI				(2001)					S RIDE	7.4	7.0	6.7	6.7	6.8	6.6	6.4	6.5	6.4	6.4	6.3	6.4	6.5	6.1											
4416541	0.000	1.212	C	2028				0012																											
15120000	1.212	3.596	R	1	1	45			CRACKING	9.0	9.0	9.0	9.0	9.0			10.0	10.0	10.0	10.0	10.0	10.0												
688			3	5.2				39000	RIDE	7.8	7.9	7.7	6.8	6.7			7.8	7.8	7.7	7.7	7.5	7.6											
137 ST(1.4C)									FC125																										
2570501	1.212	3.596	C	2004				0213	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.0	7.0	6.5	6.5	5.5*	5.5*	3.0*											
CENTRAL FLORIDA EXCAVATING				(2008)					SPRIDE	7.3	7.1	7.0	7.0	6.9	6.7	6.7	6.8	6.6	6.5	6.4	6.6	6.4	6.0											
4479211	1.212	3.558	C	2028				0012																											

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD / %T / FY-P / FY-F	AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
15120000	3.596	5.092	R	1	1	45		CRACKING	10.0	8.5	10.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5														
688			3	3.6		69500		RIDE	8.4	8.4	8.0	7.4	7.1	7.0	6.9	6.5	6.8	6.5	6.1	5.6														
117 ST N(3.7R)							FC125M																													
2571551	3.655	4.379	C	2011		0213		CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	7.8	8.5	6.5												
PCS CIVIL LLC				(2015)			SPRIDE			8.1	7.8	7.8	7.8	7.7	7.7	7.7	7.7	7.6	7.4	7.6	7.5	7.1												
15120000	5.092	7.571	R	1	1	45		CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5														
688			3	3.6		66000		RIDE	8.4	8.2	8.0	7.4	7.1	7.0	6.9	6.5	6.8	6.5	6.1	5.6														
GROSS POINTE(5.2R)							FC125M																													
								CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
				(2018)				RIDE					8.1	7.9	7.9	7.9	7.9	7.8	7.9	7.9	7.8	7.4													
15120000	7.571	8.482	R	1	1	45		CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5		10.0	10.0	10.0	10.0														
688			3	6.2		59500		RIDE	8.4	8.1	8.0	7.3	7.3	7.1	6.9	7.4		8.1	8.0	7.9	7.8														
RANCHERO VILLAGE(7.7R)							FC125M																													
								CRACKING	10.0	10.0	9.0	9.0	6.5	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	8.5													
				(2022)				RIDE	7.6	7.6	7.7	7.6	7.7	7.5	7.2	7.0	7.6	7.5	7.5	7.5	7.5	7.1													
15120000	8.482	10.169	R	1	1	45		CRACKING	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*				10.0	10.0	10.0	10.0														
688			4	9.6		51500		RIDE	8.1	7.9	7.8	6.2*	6.3*	6.1				7.6	7.4	7.1	7.5														
FRONTAGE RD 15150200(8.5C)							FC125M																													
								CRACKING	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	9.0	8.0													
				(2024)				RIDE	7.4	6.9	7.1	6.4	6.4	7.1	7.2	7.1	7.0	6.8	7.8	7.8	7.8	7.4													
15120000	10.169	10.566	C	1	1	50		CRACKING	2.0*	2.0*	4.5*	4.5*	3.5*	3.5*				10.0	10.0	10.0	10.0														
688			3	3.6		61000		RIDE	8.1	8.1	7.8	6.2*	6.3*	6.1*				7.6	7.7	7.6	7.2														
FROM EB ROOSEVELT(10.5L)							FC125M																													
								CRACKING	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	10.0	9.2	9.5	8.0													
				(2019)				RIDE	7.5	7.4	7.7			8.0	7.8	7.8	7.8	7.7	7.9	7.9	7.9	7.5													
15120000	10.566	11.671	R	1	1	50		CRACKING	6.5	4.5*	10.0	10.0	10.0	10.0				10.0	10.0	10.0	10.0														
686			3	11.2		47000		RIDE	8.3	8.2	8.4	7.8	7.8	7.7				8.1	8.1	7.9	8.0														
40 ST N(10.6R)							DGFC																													
								CRACKING	10.0					9.0	9.0	9.0	9.0	9.0	9.0	8.1	6.6	5.0*													
				(2019)				RIDE	7.4					7.5	7.4	7.4	7.3	7.3	7.3	7.2	7.3	6.9													
15120000	11.671	12.341	R	1	1	50		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	6.5	6.5	6.5														
688			3	11.2		47000		RIDE	8.7	8.7	8.4	7.8	7.8	7.7	8.0	8.1	8.0	8.0	8.0	7.7	7.6														
TO CARILLON PKWY W(11.8R)							FC5																													
2571471	11.828	12.282	C	2013		0213		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	8.3	8.3	4.0*												
LANE CONSTRUCTION CORPORAT				(2014)			SPRIDE	RIDE	8.3	8.2	8.3	8.5	8.5	8.4	8.5	8.5	8.5	8.3	8.4	8.5	8.6	8.4												
15120000	12.341	12.913	R	1	1	55		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	6.5	6.5	6.5														
688			3	11.2		47000		RIDE	8.7	8.7	8.4	7.8	7.8	7.7	8.0	8.1	8.0	8.0	8.0	7.7	7.6														
FROM CARILLON ENTR(12.4R)							FC5M																													
								CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	10.0	10.0	8.5													
				(2025)				RIDE	8.3	8.2	8.3	8.5	8.5	8.4	8.5	8.5	8.5	8.3	8.4	8.4	8.2	8.0													
15120000	11.671	12.913	L	1	1	55		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	7.5														
688			3	11.2		47000		RIDE	8.7	8.7	8.2	7.2	8.2	8.2	8.2	8.1	8.0	7.9	8.2	8.1	8.0														
EGRET BLVD(11.8L)							FC5																													
								CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	6.7	6.5	2.5*												
				(2014)				RIDE	8.2	8.1	8.3	8.4	8.4	8.3	8.4	8.5	8.3	8.4	8.4	8.3	8.4	8.2												
15120000	10.566	11.671	L	1	1	50		CRACKING	6.5	6.5	6.5	3.5*	3.5*	3.5*				10.0	10.0	10.0	10.0														
686			3	11.2		47000		RIDE	7.9	7.8	7.8	6.9	5.9*	5.3*				8.0	8.0	7.9	7.8														
STONYBROOK DR(10.8L)							FC125M																													
								CRACKING	9.0					10.0	10.0	10.0	9.0	9.0	9.0	9.1	8.6	7.0													
				(2019)				RIDE	6.7					7.9	7.7	7.7	7.5	7.7	7.7	7.6	7.7	7.3													
15120000	8.482	10.169	L	1	1	45		CRACKING	2.0*	2.0*	1.0*	1.0*	1.0*	1.0*				10.0	10.0	10.0	10.0														
688			4	9.6		51500		RIDE	8.1	8.1	7.9	6.8	6.7	6.5				7.8	7.8	7.6	7.6														
FRONTAGE RD 15150200(8.5C)							FC125M																													
								CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	9.5	8.5													
				(2024)				RIDE	7.5	7.4	7.4	7.1	7.2	7.3	7.3	7.2	7.1	7.2	7.9	7.8	7.9	7.5													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T	AADT	DISTRESS / RATINGS / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15120000	7.571	8.482	L	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0	10.0													
688			3	6.2	59500				RIDE	7.9	7.8	7.9	7.5	7.7	7.6	7.1	7.8		7.9	7.9	7.6	7.9													
FOREST LAKE DR(7.7L)									FC125M																										
									CRACKING	10.0	10.0	9.0	9.0	9.0	6.5	6.5	3.5*	10.0	10.0	10.0	9.6	10.0	8.5												
							(2022)		RIDE	7.9	7.8	7.9	7.6	7.8	7.6	7.5	7.4	7.8	7.8	7.6	7.6	7.8	7.4												
15120000	5.092	7.571	L	1	1	45			CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.0	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*													
688			2	3.6	66000				RIDE	8.3	8.3	8.2	7.5	7.5	7.3	6.9	6.8	6.6	6.4	6.2	5.7	5.4*													
OAK CREST APT ENT(5.2L)									FC125M																										
									CRACKING	4.5*				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5												
							(2018)		RIDE	4.8*				8.1	8.0	8.0	7.9	7.8	7.8	7.8	7.8	7.8	7.4												
15120000	3.596	5.092	L	1	1	45			CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0														
688			3	3.6	69500				RIDE	8.6	8.4	8.2	7.7	7.5	7.3	6.9	7.1	6.7	6.9	6.7	6.5														
PALM AVE(3.7L)									FC125M																										
2571551	3.655	4.379	C	2011	0213				CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.1	6.0*												
PCS CIVIL LLC				(2015)					SPRIDE		8.1	7.7	7.7	7.7	7.5	7.6	7.4	7.4	7.4	7.4	7.4	7.4	7.0												
15120000	1.212	3.596	L	1	1	45			CRACKING	10.0	8.5	8.5	8.5	8.5			10.0	10.0	10.0	10.0	10.0	10.0														
688			3	5.2	39000				RIDE	8.4	8.0	8.2	7.4	7.1			7.8	8.1	8.1	8.1	7.9	7.9														
137 ST(1.4C)									FC125																										
2570501	1.212	3.596	C	2004	0213				CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.5	7.5	6.5	7.0	6.7	6.5	4.0*												
CENTRAL FLORIDA EXCAVATING				(2008)					SPRIDE	7.6	7.6	7.1	6.9	7.0	6.9	6.9	7.0	6.7	6.7	6.7	6.8	6.7	6.3												
4479211	1.212	3.558	C	2028	0012																														
15120000	0.000	1.212	L	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5														
688			2	18.5	17500				RIDE	8.4	8.3	8.2	8.0	7.9	7.8	7.5	7.7	8.0	7.9	7.9	7.8	7.7														
CR-183(0.0L)									FC125																										
2570481	0.000	1.212	C	1997	0213				CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.8	6.5	3.5*												
GLF CONSTRUCTION CORPORATI				(2001)					S RIDE	7.7	7.5	7.3	7.3	7.4	7.2	7.3	7.3	7.1	7.1	7.1	7.0	7.2	6.8												
4416541	0.000	1.212	C	2028	0012																														
15140000	0.000	1.512	R	1	1	35			CRACKING	9.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0														
699			2	3.2	14900				RIDE	5.6*	5.4*	5.2*	5.1*	5.0*	4.9*	4.7*	4.8*	4.7*	7.6	7.5	7.3	7.4														
150 AVE(0.0R)									FC125																										
2571291	0.020	1.512	C	2008	0012				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.6	6.8	4.5*												
R. E. PURCELL CONSTRUCTION				(2010)					RIDE	6.9	6.8	6.3	6.4	6.4	6.1	6.0	5.9	5.8	5.9	5.8	5.8	5.7	5.3*												
4520021	0.000	3.356	C	2029	0012																														
15140000	1.512	3.356	R	1	1	35			CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	6.5	6.5	6.5	6.5	6.5														
699			2	3.2	16844				RIDE	7.8	7.6	7.4	7.1	7.1	6.9	6.8	6.7	6.5	6.5	6.2	6.3	6.2														
BATH CLUB CIR(1.5R)									FC125R																										
4271611	1.534	3.356	C	2013	0012				CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	5.7*	4.8*	3.0*												
PREFERRED MATERIALS, INC.				(2015)					SPRIDE	6.0	8.1	7.3	7.3	7.3	7.1	7.0	6.9	6.9	6.7	6.7	6.6	6.6	6.2												
4520021	0.000	3.356	C	2029	0012																														
15140000	3.356	4.061	R	1	1	35			CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5														
699			2	3.2	16844				RIDE	6.6	6.4	6.6	6.5	6.4	6.5	7.4	7.6	7.4	7.4	7.4	7.3	7.3														
CR 694(3.7R)									FC125M																										
4416531	3.356	3.878	C	2023	0012				CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	9.0												
HUBBARD CONSTRUCTION COMPA				(2025)					SPRIDE	7.3	7.1	6.9	6.7	6.8	6.5	6.5	6.4	6.2	6.3	6.2	7.5	7.4	7.0												
15140000	4.061	6.752	C	1	1	30			CRACKING	7.0	7.0	7.0	7.0	6.5	6.5	6.5	4.5*		10.0	10.0	10.0	10.0														
699			2	3.2	13300				RIDE	6.3*	6.3	6.0	5.9	6.0	5.8	5.3*	5.3*		7.8	7.5	7.3	7.2														
193 AVE E(4.2R)									DGFC																										
									CRACKING	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.2*	6.5	4.0*												
							(2010)		RIDE	7.0	6.8	6.1	5.9	5.7	5.5	5.5	5.3*	5.2*	5.1*	5.0*	4.9*	4.8*	4.4*												
4436661	3.957	6.752	C	2029	0012																														
15140000	3.356	4.061	L	1	1	35			CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0														
699			2	3.2	16844				RIDE	5.4*	5.4*	5.2*	5.3*	5.0*	5.6	6.5	5.9	6.5	6.8	6.9	6.5	6.5														
186 AVE(3.5L)									FC125M																										
4416531	3.356	3.878	C	2023	0012				CRACKING	8.5	8.5	8.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	10.0	10.0	9.0												
HUBBARD CONSTRUCTION COMPA				(2025)					SPRIDE	6.4	6.4	5.9	5.8	5.7	5.4*	5.4*	5.2*	5.2*	5.1*	5.1*	7.6	7.5	7.1												
15140000	1.512	3.356	L	1	1	35			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	7.0	6.0*														
699			2	3.2	16844				RIDE	7.5	7.3	6.9	6.6	6.5	6.4	6.1	6.4	6.4	6.1	5.9	5.7	5.5														
176 AVE W(2.4L)									FC125R																										
4271611	1.534	3.356	C	2013	0012				CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.7	6.5	4.5*												
PREFERRED MATERIALS, INC.				(2015)					SPRIDE	5.5	7.6	6.9	6.9	6.8	6.6	6.5	6.4	6.4	6.2	6.2	6.1	6.0	5.6												
4520021	0.000	3.356	C	2029	0012																														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T	AADT	DISTRESS / RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15140000	0.000	1.512	L	1	1	35			CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	8.5	8.5	7.5	10.0	10.0	10.0	10.0													
699			2	3.2	14900				RIDE	5.8*	5.9	5.5	5.8	5.8	5.7	5.6	5.6	6.0	7.6	7.5	7.3	7.4													
MADEIRA BEACH CITY LIMIT(0.0C)									FC125																										
2571291	0.020	1.512	C	2008		0012			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	7.0	4.5*												
R. E. PURCELL CONSTRUCTION(2010)									RIDE	6.9	6.8	6.3	6.4	6.4	6.1	6.0	5.9	5.8	5.8	5.9	5.9	5.7	5.3*												
4520021	0.000	3.356	C	2029		0012																													
15150000	0.867	5.878	R	1	7	40			CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	8.5	8.5	8.5													
55	19		3	4.6	44500				RIDE	7.3		8.1	7.6	7.6	7.5	7.3	7.4	7.3	7.4	7.2	7.1	7.0													
SR 682(0.9C)						FC125M																													
4402461	0.960	5.876	C	2022		0012			CRACKING	7.5	7.0	7.0	7.0	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	3.3*	10.0	9.0												
PREFERRED MATERIALS, INC. (2026)									RIDE	7.0	6.9	6.7	6.5	6.4	6.3	6.3	6.3	6.1	6.0	5.9	5.3*	7.8	7.4												
15150000	5.878	7.032	R	1	1	40			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	7.0	7.0	10.0													
55	19		3	5.6	46000				RIDE	7.9	7.6	7.6	6.7	6.7	6.7	6.6	6.6	6.4	6.5	6.5	6.7	7.9													
23 AV N(5.9C)						FC125R																													
4037311	5.878	7.032	C	2011		0012			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	8.0	7.5	7.1	5.0*												
AJAX PAVING INDUSTRIES OF (2013)						SPRIDE			RIDE	7.8	7.8	7.6	7.1	6.9	6.9	7.1	6.9	6.8	6.8	6.4	4.9*	6.5	6.1												
15150000	7.032	7.320	R	1	1	40			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	7.0	7.0	8.0													
55	19		3	5.6	46000				RIDE	7.9	7.6	7.6	6.7	6.7	6.7	6.6	6.6	6.4	6.5	6.5	6.7	7.0													
44 AVE N(7.3R)						DGFC																													
									CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	10.0	9.0	8.0												
				(2023)					RIDE	7.0	6.9	6.9	6.4	6.4	6.3	6.5	6.4	6.2	7.1	6.9	6.8	6.8	6.4												
15150000	7.320	9.274	R	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.0													
55	19		3	5.1	53500				RIDE	8.3	8.2	8.2	7.9	7.8	7.6	7.4	7.5	7.3	7.4	7.0	7.2	7.0													
46 AVE N(7.4R)						FC125M																													
4376251	8.086	9.274	C	2021		0012			CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	9.1	10.0	9.0												
PREFERRED MATERIALS, INC. (2023)						SPRIDE			RIDE	7.0	6.9	6.9	6.4	6.4	6.3	6.5	6.4	6.2	7.5	7.3	6.4	7.4	7.0												
15150000	9.274	11.086	R	1	1	55			CRACKING	3.5*	3.5*	1.0*	0.0*	10.0	10.0	10.0	10.0	9.0		7.0	7.0	6.5													
55	19		3	5.6	79000				RIDE	7.8	7.7	7.4	5.2*	8.1	8.0	7.9	7.6	8.0		7.6	6.8	6.8													
76 TER(9.3R)						FC5A																													
4314961	9.323	11.086	C	2016		0012			CRACKING	6.5	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.7	9.0	6.0*												
PREFERRED MATERIALS, INC. (2018)						SPRIDE			RIDE	6.8	6.2*	6.9		8.3	8.3	8.4	8.4	8.3	8.3	8.3	7.8	8.4	8.2												
4560541	9.800	33.000	C	2025		0012																													
15150000	11.086	12.507	R	1	1	55			CRACKING	3.5*	3.5*	1.0*	0.0*	10.0	10.0	10.0	10.0	9.0		10.0	10.0	10.0													
55	19		3	7.9	68500				RIDE	7.8	7.7	7.4	5.2*	8.1	8.0	7.9	7.6	8.0		8.2	8.1	7.9													
LAKE BLVD(11.5R)						FC5M																													
2570701	11.119	12.896	C	2006		0213			CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	6.6	5.6*	0.5*												
ARCHER WESTERN CONSTRACTORS(2011)						SPRIDE			RIDE	7.8	7.7	7.7	7.6	7.5	7.5	7.7	7.6	7.6	7.4	7.3	7.4	7.4	7.2												
4560541	9.800	33.000	C	2025		0012																													
15150000	12.507	13.074	R	1	1	55			CRACKING	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	9.0		10.0	10.0	10.0													
55	19		3	7.9	68500				RIDE	7.8	7.7	7.4		8.1	8.0	7.9	7.6	8.0		8.2	8.1	7.9													
FR FRNT RD 15150098(12.7R)						FC5M																													
4560541	12.728	13.341	R	2025		0012			CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	8.5												
				(2025)					RIDE	7.8	7.7	7.7	7.6	7.5	7.5	7.7	7.6	7.6	7.4	7.3	8.3	8.3	8.1												
15150000	13.074	15.830	R	1	1	55			CRACKING	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5													
55	19		3	5.6	103000				RIDE	7.9	7.8	7.8		8.1	8.0	7.9	7.6	8.0	8.0	7.7	7.7	7.4													
						FC5M																													
4308991	12.896	15.927	C	2016		0012			CRACKING	6.5	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	8.9	5.5*												
PREFERRED MATERIALS, INC. (2018)									RIDE	7.2	6.8	7.4		8.7	8.6	8.8	8.8	8.8	8.6	8.6	8.5	8.6	8.4												
4560541	9.800	33.000	C	2025		0012																													
15150000	15.830	18.998	R	1	1	55			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	6.5	4.5*	4.5*																
55	19		3	5.3	131000				RIDE	8.9	8.8	8.7	8.1	8.1	7.9	7.8	7.7	7.6	7.5																
FRONTAGE RD #098(16.0R)						FC5M																													
									CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	5.8*	5.9*	2.5*												
				(2017)					RIDE				8.0	7.9	7.8	8.0	7.9	7.9	7.8	7.7	7.5	7.6	7.4												
4560541	9.800	33.000	C	2025		0012																													
15150000	18.998	20.791	R	1	7	55			CRACKING	10.0	10.0	10.0						10.0	10.0	10.0	10.0	10.0													
55	19		3	5.3	131000				RIDE	8.6	8.6	8.7						7.6	7.7	7.7	7.6	7.6													
						OGFC																													
4560541	13.341	22.998	R	2025		0012			CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	4.5*	4.5*	4.1*	10.0	9.0												
				(2026)					RIDE	7.5	7.5	7.7	7.7	7.6	7.5	7.7	7.7	7.6	7.4	7.2	7.2	8.7	8.5												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15150000	20.791	22.622	R	1	8	55	CRACKING	10.0	10.0	10.0	8.5	8.5	7.5	7.5	6.5	6.5	4.5*	4.5*																	
55	19			3	5.3	116500	RIDE	8.7	8.6	8.6	8.2	8.1	8.0	8.0	8.1	7.6	7.4	7.4																	
EXECUTIVE CENTER ENT(21.4R)							FC5A																												
2568901	20.892	21.947	C	2012		0213	CRACKING			10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5																
RUSSELL ENGINEERING, INC		(2016)					SPRIDE			8.4	8.4	8.4	8.3	8.4	8.4	8.4	8.3	8.3	7.7																
4560541	9.800	33.000	C	2025		0012																													
15150000	22.622	25.650	R	1	8	55	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.5	6.5	6.5	6.5	6.5	6.5															
55	19			3	5.3	105000	RIDE	8.9	8.6	8.9	8.2	8.1	8.0	8.0	8.0	7.8	7.8	7.6	7.4	7.3															
HAMMOCK PINES BLVD(23.1R)							FC5																												
							CRACKING	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5																	
		(2016)					RIDE	7.2		8.4	8.4	8.4	8.3	8.4	8.4	8.4	8.3	8.3																	
4560541	9.800	33.000	C	2025		0012																													
15150000	25.650	25.881	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.5	6.5	6.5	6.5	6.5	6.5															
55	19			4	3.6	78000	RIDE	8.9	8.6	8.9	8.2	8.1	8.0	8.0	8.0	7.8	7.8	7.6	7.4	7.3															
CR 752(25.8C)							FC5																												
4560541	25.665	25.845	R	2025		0012	CRACKING	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	6.2*	9.0	8.0													
		(2026)					RIDE	7.2		8.4	8.4	8.4	8.3	8.4	8.4	8.4	8.3	8.3	8.3	8.0	7.8													
15150000	25.881	31.277	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.5	6.5	6.5	6.5	6.5																
55	19			4	5.3	93000	RIDE	8.9	8.6	8.9	8.2	8.1	8.0	8.0	8.0	7.8	7.8	7.6	7.4																
CORAL LANDING/PUBLIX(26.2R)							FC5																												
4290051	27.877	31.104	C	2013		0012	CRACKING	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	6.2*	4.5*	1.0*													
HUBBARD CONSTRUCTION COMPA		(2016)					SPRIDE	7.1		8.4	8.4	8.4	8.3	8.4	8.4	8.4	8.3	8.3	8.3	8.2	8.0													
4560541	9.800	33.000	C	2025		0012																													
15150000	31.277	31.826	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.5	7.5	7.0															
55	19			3	5.3	63000	RIDE	8.2	8.1	8.1	8.3	8.1	7.9	8.0	7.9	7.6	7.3	7.3	7.0	6.6															
FROM CR-582(31.3R)							FC5																												
4290051	31.275	31.859	C	2013		0012	CRACKING	7.0		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	6.2*	4.5*	1.0*													
HUBBARD CONSTRUCTION COMPA		(2016)					SPRIDE	6.5		8.4	8.4	8.4	8.3	8.4	8.4	8.4	8.3	8.3	8.3	7.2	7.0													
4560541	9.800	33.000	C	2025		0012																													
15150000	31.826	33.146	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0	7.5															
55	19			3	5.3	63000	RIDE	8.7	8.6	8.7	8.3	8.1	7.9	8.0	7.9	7.6	8.0	7.9	7.8	7.6															
E LIVE OAK ST(31.8R)							FC5M																												
4348071	31.826	33.146	C	2017		0012	CRACKING	7.5	4.5*	4.5*	3.5*	0.0*		10.0	10.0	10.0	10.0	10.0	9.0	8.8	6.0*													
PREFERRED MATERIALS, INC.		(2020)					SPRIDE	7.6	7.5	7.6	7.5	7.3		8.4	8.3	8.3	8.2	8.2	8.2	8.3	8.1													
4560541	9.800	33.000	C	2025		0012																													
15150000	31.826	33.146	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5															
55	19			3	5.3	63000	RIDE	8.7	8.4	8.5	7.9	7.8	7.4	7.6	7.4	7.2	7.8	7.8	7.7	7.6															
CR 952(31.8L)							FC5M																												
4348071	31.826	33.146	C	2017		0012	CRACKING	6.5	4.5*	4.5*	3.5*	0.0*		10.0	10.0	10.0	10.0	10.0	9.0	8.8	6.0*													
PREFERRED MATERIALS, INC.		(2020)					SPRIDE	7.4	7.1	7.3	7.1	6.9		8.1	8.1	8.1	8.0	8.0	7.6	8.1	7.9													
4560541	9.800	33.000	C	2025		0012																													
15150000	31.272	31.826	L	1	2	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5															
55	19			3	5.3	63000	RIDE	8.1	8.0	7.9	7.9	7.8	7.4	7.6	7.4	7.2	5.5*	5.3*	5.6*	4.8*													
TARPON AVE(31.3L)							FC5																												
4290051	31.275	31.859	C	2013		0012	CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	4.5*	4.5*	1.0*													
HUBBARD CONSTRUCTION COMPA		(2016)					SPRIDE	5.0*		8.4	8.4	8.4	8.3	8.4	8.4	8.3	8.3	8.2	7.5	7.6	7.4													
4560541	9.800	33.000	C	2025		0012																													
15150000	25.650	31.272	L	1	2	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	6.5	6.5	6.5	6.5	6.5	6.5															
55	19			4	5.3	93000	RIDE	8.9	8.5	8.9	8.2	8.2	7.9	7.7	7.9	7.6	7.6	7.5	7.3	7.1															
CR 752(25.8C)							FC5																												
4290051	27.877	31.104	C	2013		0012	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	4.5*	4.5*	1.0*													
HUBBARD CONSTRUCTION COMPA		(2016)					SPRIDE	7.0		8.4	8.4	8.4	8.3	8.4	8.4	8.3	8.3	8.2	7.5	8.1	7.9													
4560541	9.800	33.000	C	2025		0012																													
15150000	22.622	25.650	L	1	8	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	6.5	6.5	6.5	6.5	6.5	6.5															
55	19			3	5.3	105000	RIDE	8.9	8.5	8.9	8.2	8.2	7.9	7.7	7.9	7.6	7.6	7.5	7.3	7.1															
REPUBLIC DR(23.1L)							FC5																												
							CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5																	
		(2016)					RIDE	7.0		8.4	8.4	8.4	8.3	8.4	8.4	8.3	8.3	8.2																	
4560541	9.800	33.000	C	2025		0012																													
15150000	20.801	22.622	L	1	1	55	CRACKING	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*															
55	19			3	5.3	116500	RIDE	8.3	8.0	7.9	7.6	7.9	7.8	7.7	7.7	7.6	7.4	7.4	7.1	6.9															
FROM FRONTAGE RD(21.3L)							FC5A																												
2568901	20.892	21.947	C	2012		0213	CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	8.4	8.3	4.5*													
RUSSELL ENGINEERING, INC		(2016)					SPRIDE	6.7		8.4	8.4	8.4	8.3	8.4	8.4	8.3	8.3	8.2	8.1	8.0	7.8													
4560541	9.800	33.000	C	2025		0012																													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	LN / %T / FY-P / FY-F	AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15150000	18.998	20.801	L	1	7	55	1		CRACKING	10.0	10.0	10.0																							
55 19			3	5.3	131000			OGFC	RIDE	8.7	8.7	8.7											7.7	7.7	7.7	7.6	7.6									
4560541	15.159	23.133	L	2025	0012				CRACKING	10.0	10.0	10.0	9.0	9.0	7.5	7.5	4.5*	4.5*	4.5*	4.5*	3.6*	10.0	9.0												
				(2026)					RIDE	7.5	6.8	7.7	7.7	7.6	7.6	7.6	7.5	7.6	7.4	7.3	7.3	8.6	8.4												
15150000	15.830	18.998	L	1	1	55			CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5																
55 19			3	5.3	131000			FC5M	RIDE	8.8	8.9	8.8	8.1	8.1	7.9	7.7	7.8	7.6	7.5																
CENTRAL AVE(16.2L)									CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.0	6.3*	3.0*												
				(2017)					RIDE				8.1	8.1	8.0	8.1	8.0	8.0	8.0	7.9	7.9	7.9	7.7												
4560541	9.800	33.000	C	2025	0012																																
15150000	15.148	15.830	L	1	1	55			CRACKING	6.5	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0														
55 19			3	5.3	99000			FC5M	RIDE	7.8	7.6	7.7		8.0	7.9	8.0	7.8	8.0	8.1	7.9	7.8	7.4														
4308991	12.896	15.927	C	2016	0012				CRACKING	7.5	7.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.7	5.5*												
PREFERRED MATERIALS, INC.				(2018)					RIDE	7.5	7.4	7.7		8.6	8.5	8.6	8.7	8.6	8.5	8.5	8.5	8.5	8.3												
4560541	9.800	33.000	C	2025	0012																																
15150000	14.634	15.148	L	1	1	55			CRACKING	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0														
55 19			4	5.6	103000			FC5M	RIDE	8.2	8.0	7.7		8.0	7.9	8.0	7.8	8.0	8.1	7.9	7.8	7.4														
4308991	12.896	15.927	C	2016	0012				CRACKING	7.5	7.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.9	5.5*												
PREFERRED MATERIALS, INC.				(2018)					RIDE	7.5	7.4	7.7		8.6	8.5	8.6	8.7	8.6	8.5	8.5	8.5	8.6	8.4												
4560541	9.800	33.000	C	2025	0012																																
15150000	13.074	14.634	L	1	1	55			CRACKING	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0														
55 19			3	5.6	91500			FC5M	RIDE	8.2	8.0	7.7		8.0	7.9	8.0	7.8	8.0	8.1	7.9	7.8	7.4														
4308991	12.896	15.927	C	2016	0012				CRACKING	7.5	7.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	9.0	6.0*												
PREFERRED MATERIALS, INC.				(2018)					RIDE	7.5	7.4	7.7		8.6	8.5	8.6	8.7	8.6	8.5	8.5	8.5	8.7	8.5												
4560541	9.800	33.000	C	2025	0012																																
15150000	12.570	13.074	L	1	1	55			CRACKING	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0														
55 19			3	7.9	68500			FC5M	RIDE	8.2	8.0	7.7		8.0	7.9	8.0	7.8	8.0		8.3	8.1	8.0														
4560541	12.728	13.341	L	2025	0012				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	10.0	10.0	8.5												
				(2025)					RIDE	7.9	7.8	7.8	7.7	7.7	7.7	7.8	7.8	7.8	7.7	7.7	7.9	7.9	7.7												
15150000	11.086	12.570	L	1	1	55			CRACKING	1.0*	0.0*	0.0*	0.0*	10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0														
55 19			3	7.9	68500			FC5M	RIDE	8.3	8.1	7.9	6.3*	8.0	7.9	8.0	7.8	8.0		8.3	8.1	8.0														
FR FRNT RD 15150200(11.4L)									CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	6.6	6.5	1.5*												
2570701	11.119	12.896	C	2006	0213				RIDE	7.9	7.8	7.8	7.7	7.7	7.7	7.8	7.8	7.8	7.7	7.7	7.7	7.7	7.5												
ARCHER WESTERN CONTRACTORS				(2011)					SPRIDE																												
4560541	9.800	33.000	C	2025	0012																																
15150000	9.274	11.086	L	1	1	55			CRACKING	1.0*	0.0*	0.0*	0.0*	10.0	10.0	10.0	10.0	10.0		8.0	8.0	8.0														
55 19			3	5.6	79000			FC5A	RIDE	8.3	8.1	7.9	6.3*	8.0	7.9	8.0	7.8	8.0		7.7	7.3	7.5														
76 AVE(9.4L)									CRACKING	7.5	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.3	8.6	5.5*												
4314961	9.323	11.086	C	2016	0012				RIDE	7.4	6.7	7.1		8.4	8.4	8.4	8.4	8.3	8.3	8.3	7.5	8.3	8.1												
PREFERRED MATERIALS, INC.				(2018)					SPRIDE																												
4560541	9.800	33.000	C	2025	0012																																
15150000	7.320	9.274	L	1	1	45			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	7.5	7.5														
55 19			3	5.1	53500			FC125M	RIDE	7.9	7.9	7.9	7.6	7.4	7.3	7.3	7.4	7.9	7.2	7.6	7.0	7.2														
50 AVE N(7.6L)									CRACKING	7.5	7.5	6.5	6.5	6.0*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	9.4	10.0	9.0												
4376251	8.086	9.274	C	2021	0012				RIDE	6.8	6.7	6.9	6.6	6.4	6.1	6.5	6.9	6.9	7.4	7.4	6.9	7.4	7.0												
PREFERRED MATERIALS, INC.				(2023)					SPRIDE																												
15150000	7.031	7.320	L	1	1	40			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	7.5	7.5														
55 19			3	5.6	46000			DGFC	RIDE	7.9	7.9	7.9	7.6	7.4	7.3	7.3	7.4	7.9	7.2	7.6	7.0	7.2														
									CRACKING	7.5	7.5	6.5	6.5	6.0*	3.5*	3.5*	3.5*	3.5*	10.0	9.5	9.5	7.9	6.5												
				(2023)					RIDE	6.8	6.7	6.9	6.6	6.4	6.1	6.5	6.9	6.9	7.1	7.3	7.3	7.2	6.8												
15150000	5.878	7.031	L	1	2	40			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	7.5	10.0														
55 19			3	5.6	46000			FC125R	RIDE	7.9	7.9	7.9	7.6	7.4	7.3	7.3	7.4	7.9	7.2	7.6	7.0	8.2														
23 AV N(5.9C)									CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	7.4	7.1	5.0*												
4037311	5.878	7.032	C	2011	0012				RIDE	8.1	7.8	7.5	7.4	7.3	7.0	7.2	7.1	7.0	6.8	6.7	6.0	7.0	6.6												
AJAX PAVING INDUSTRIES OF				(2013)					SPRIDE																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15150000	3.894	5.878	L	1	8	40	CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	7.5													
55 19			3	4.1	38000		RIDE	7.0		8.0	7.4	7.3	7.1	7.1	7.3	7.5	7.1	6.9	6.7	6.5													
FAIRFIELD AVE S(3.9L)					FC125																												
2570951	0.867	5.878	C	2000	0012		CRACKING	7.5	7.5	7.0	6.5	6.5	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	2.8*														
AJAX PAVING INDUSTRIES INC(2003)				SPR	IDE		RIDE	6.6	6.3	6.4	6.2	6.0	5.9	6.0	5.9	5.8	5.6	5.6	5.8														
4402461	0.882	5.876	C	2022	0012																												
15150000	0.867	3.894	L	1	7	40	CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	7.5													
55 19			3	4.6	44500		RIDE	7.0		8.0	7.4	7.3	7.1	7.1	7.3	7.5	7.1	6.9	6.7	6.5													
SR 682(0.9C)					FC125																												
4402461	0.960	5.876	C	2022	0012		CRACKING	7.5	7.5	7.0	6.5	6.5	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	2.8*	10.0	9.0												
PREFERRED MATERIALS, INC. (2026)							RIDE	6.6	6.3	6.4	6.2	6.0	5.9	6.0	5.9	5.8	5.6	5.6	5.8	7.7	7.3												
15150019	0.000	2.844	C	1	1	35	CRACKING																										
55F			2	7.8	11500		RIDE																										
							CRACKING													7.0													
							RIDE													6.3													
15150023	0.000	0.310	C	1	1	35	CRACKING																										
55F			2	7.8	11500		RIDE																										
							CRACKING													7.5													
							RIDE													6.0													
15150023	0.310	0.497	C	1	1	35	CRACKING																										
55F			2	7.8	11500		RIDE																										
							CRACKING													10.0	9.0												
		(2026)					RIDE													6.3	5.9												
15150031	0.000	1.227	C	1	8	35	CRACKING																										
55F			2	7.8	11500		RIDE																										
							CRACKING																										
							RIDE																										
4437801	0.000	2.403	C	2024	0012																												
15150031	1.227	2.403	C	1	1	35	CRACKING																										
55F			1	7.8	11500		RIDE																										
4437801	1.204	2.202	C	2024	0012		CRACKING													9.5	8.5												
PREFERRED MATERIALS, INC. (2026)					SPR	IDE														6.7	6.3												
15150032	0.063	1.396	C	1	8	35	CRACKING																										
55F			2	7.8	11500		RIDE																										
							CRACKING																										
							RIDE																										
4437801	0.063	1.396	C	2024	0012																												
15150098	0.000	0.631	C	1	1	40	CRACKING																										
55F			2	7.8	11500		RIDE																										
							CRACKING													8.0													
							RIDE													5.7													
15150098	0.631	4.285	C	1	1	45	CRACKING																										
55F			2	7.8	11500		RIDE																										
							CRACKING													10.0	9.0												
		(2026)					RIDE													7.3	6.9												
15150098	4.285	5.216	C	1	1	45	CRACKING																										
55F			2	7.8	11500		RIDE																										
							CRACKING													6.0*													
							RIDE													6.0													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS RATINGS / SURFTYPE / ASTYPE	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15150098	5.216	5.546	C	1	1	45	CRACKING																											
55F			2	7.8	11500		RIDE																											
							CRACKING																										8.0	
							RIDE																										7.1	
15150098	5.546	5.815	C	1	7	45	CRACKING																											
55F			1	7.8	11500		RIDE																											
							CRACKING																										10.0	9.0
		(2026)					RIDE																										6.6	6.2
15150098	5.815	6.746	C	1	1	45	CRACKING																											
55F			2	7.8	11500		RIDE																											
							CRACKING																										7.0	
							RIDE																										6.9	
15150200	0.027	4.987	C	1	1	45	CRACKING																											
55F			2	7.8	11500		RIDE																											
							CRACKING																										8.7	7.5
		(2026)					RIDE																										7.0	6.6
15150300	0.000	0.660	C	1	1	35	CRACKING																											
55F			2	7.8	11500		RIDE																											
							CRACKING																										8.0	
							RIDE																										6.2	
15150300	0.660	1.034	C	1	8	35	CRACKING																											
55F			2	7.8	11500		RIDE																											
							CRACKING																											
							RIDE																											
15150400	0.000	0.338	C	1	8	45	CRACKING																											
55F			2	7.8	11500		RIDE																											
							CRACKING																											
							RIDE																											
15150400	0.338	0.941	C	1	1	45	CRACKING																											
55F			2	7.8	11500		RIDE																											
							CRACKING																										7.0	
							RIDE																										6.7	
15150400	0.941	2.135	C	1	1	45	CRACKING																											
55F			2	7.8	11500		RIDE																											
							CRACKING																										9.5	8.5
		(2026)					RIDE																										7.1	6.7
15150701	0.000	0.329	C	1	1	25	CRACKING																											
561			2	8.7	3500		RIDE																											
							CRACKING																										8.0	
							RIDE																										4.5*	
15150702	0.000	0.053	C	1	1		CRACKING																											
531			2	8.7	1000		RIDE																											
							CRACKING																										8.0	
							RIDE																										6.6	

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / SURFTYPE / ASTYPE	SYS / %T / FY-P / FY-F	TYP / AADT / WKMX-P / WKMX-F	SPD	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
15150703 / 596	0.000	0.057	C / 1	1 / 1			CRACKING RIDE																											
							CRACKING RIDE																										10.0 / 6.6	9.0 / 6.2*
15150900 / 55 / SR-682/54 AVE S(0.0R)	0.000	1.102	C / 2	1 / 5.4	1 / 8800	55 / OGFC	CRACKING RIDE	10.0 / 8.1	10.0 / 8.0	10.0 / 7.4	10.0 / 7.3	10.0 / 7.8	9.0 / 7.5	9.0 / 7.2	6.5 / 7.4	6.5 / 7.5	6.5 / 7.6	6.5 / 7.5	6.5 / 7.2	10.0 / 7.6												
4256661 / LANE CONSTRUCTION CORPORAT(2013) / 4491531	0.000	0.775	C 2012 / C 2027		0012 / 0012		CRACKING RIDE	10.0 / 7.5	10.0 / 7.6	10.0 / 7.6	10.0 / 7.5	10.0 / 7.5	10.0 / 7.3	10.0 / 7.5	9.0 / 7.4	6.5 / 7.4	6.5 / 7.4	6.5 / 7.1	6.3* / 7.3	5.4* / 7.2	1.0* / 7.0										
15170000 / 55 I275 / N END OF NEW BRIDGE(4.2R)	4.247	8.535	R / 2	4 / 7.5	1 / 67613	65 / FC5M	CRACKING RIDE	6.5 / 8.5	7.0 / 8.6	7.0 / 8.5	6.5 / 8.1		10.0 / 8.4	10.0 / 8.4	10.0 / 8.3	10.0 / 8.3	10.0 / 8.3	10.0 / 8.3	10.0 / 8.2	10.0 / 8.1											
4458861 / PREFERRED MATERIALS, INC. (2025)	4.247	8.535	C 2023		0012 / SPRIDE		CRACKING RIDE	10.0 / 8.2	10.0 / 8.1	9.0 / 8.1	9.0 / 8.1	9.0 / 7.9	9.0 / 7.9	7.5 / 8.0	6.5 / 8.0	4.5* / 8.0	4.5* / 7.9	4.5* / 7.7	10.0 / 8.7	10.0 / 8.7	9.0 / 8.6										
15170000 / 55 I275 / N OF N TOLL PLAZA(8.5C)	4.247	8.535	L / 2	4 / 7.5	1 / 67613	65 / FC5M	CRACKING RIDE	6.5 / 8.5	7.0 / 8.5	7.0 / 8.5	7.0 / 7.9		10.0 / 8.0	10.0 / 7.9	10.0 / 7.8	10.0 / 8.0	10.0 / 7.9	9.5 / 8.0	9.5 / 7.9	9.5 / 7.8											
4458861 / PREFERRED MATERIALS, INC. (2025)	4.247	8.535	C 2023		0012 / SPRIDE		CRACKING RIDE	9.5 / 7.9	9.0 / 7.9	9.0 / 7.9	9.0 / 7.8	9.0 / 7.9	9.0 / 7.7	9.0 / 7.9	7.5 / 7.9	6.5 / 7.9	6.5 / 7.8	6.5 / 7.7	10.0 / 8.7	10.0 / 8.5	9.0 / 8.4										
15190000 / 93 I275 / 2588041 / COUCH, INC. / 4460091	0.500 / 17.6 / 0.420	2.287 / 19.4 / 1.485	R / 3 / C 1982 / R 2023	4 / 7.3 / (1986) / 0227	2 / 104000 / 0101	65 / LDG	CRACKING RIDE	6.3* / 6.9 / 6.1* / 7.7		7.2 / 8.4 / 5.8* / 8.0	7.1 / 7.7 / 7.3 / 8.2	7.1 / 7.8 / 7.0 / 8.2	7.9 / 7.7 / 6.9 / 8.2	7.9 / 7.8 / 6.9 / 8.6	7.7 / 7.8 / 7.0 / 8.4	7.2 / 7.8 / 6.6 / 8.5	7.4 / 7.9 / 6.7 / 8.3	7.3 / 7.8 / 6.4* / 8.3	6.7 / 7.8 / 5.8* / 8.2	6.4* / 7.9 / 7.4 / 8.7	6.5 / 8.6										
15190000 / 93 I275 / 4460091	2.287 / 19.4 / 0.500	4.429 / 21.6 / 4.425	R / 3 / R 2023	4 / 7.3 / 0227	2 / 115000	65 / LDG	CRACKING RIDE	6.3* / 6.9 / 7.5* / 7.7	5.6* / 6.7 / 7.3* / 7.5	6.3* / 8.4 / 6.2* / 8.0	6.3* / 7.2 / 6.3* / 8.0	6.3* / 7.2 / 6.0* / 7.9	7.5 / 6.6 / 5.7* / 7.7	7.4 / 7.0 / 5.3* / 7.7	7.2 / 7.4 / 5.5* / 7.6	8.0 / 7.2 / 3.7* / 7.9	7.7 / 7.5 / 3.7* / 7.7	7.6 / 7.7 / 3.6* / 7.3	7.4 / 7.6 / 0.5* / 7.1	7.4 / 7.7 / 7.1 / 8.3	6.0* / 8.2										
15190000 / 93 I275 / 2588801 / KIEWIT INFRASTRUCTURE SOUT(2007) / 4541721	5.284 / 22.4 / 5.797 / 5.282	8.867 / 26.0 / 8.840 / 7.358@	R / 3 / C 2004 / C 2028	4 / 7.3 / 0227 / 0227	4 / 173000	65 / LDG	CRACKING RIDE	9.3 / 7.4 / 8.8 / 7.6	9.1 / 7.4 / 8.5 / 6.9	9.1 / 7.3 / 8.4 / 8.2	9.2 / 6.4* / 8.3 / 8.2	9.1 / 6.5 / 8.2 / 8.1	8.2 / 8.0	9.4 / 7.6 / 8.1 / 8.1	9.3 / 7.8 / 8.1 / 8.1	9.3 / 7.9 / 7.6 / 8.1	9.1 / 7.9 / 7.5 / 7.9	9.2 / 7.9 / 7.5 / 7.8	9.0 / 7.9 / 6.9 / 7.8	8.8 / 7.6 / 6.6 / 7.9	6.0* / 7.8										
15190000 / 93 I275 / GEORGIA ELECTRIC CO / 4491091	8.867 / 26.0 / 8.300 / 7.370	10.961 / 28.1 / 18.200 / 14.368	R / 3 / C 1981 / R 2025	4 / 7.3 / (1983) / 0213	4 / 162000 / 0101	65 / LDG	CRACKING RIDE	9.3 / 7.4 / 9.0 / 8.1	9.1 / 7.4 / 8.9 / 7.8	9.1 / 7.3 / 8.8 / 8.6	9.2 / 6.4* / 8.8 / 8.7	9.1 / 6.5 / 8.8 / 8.6	9.2 / 6.7 / 8.7 / 8.5	9.2 / 6.8 / 8.7 / 8.6	9.0 / 6.8 / 8.8 / 8.6	9.1 / 8.1 / 8.9 / 8.7	9.1 / 8.3 / 8.9 / 8.6	9.2 / 8.2 / 9.0 / 8.6	9.0 / 8.1 / 8.8 / 8.6	9.0 / 8.3 / 8.6 / 8.5	7.5 / 8.5										
15190000 / 93 I275 / HUBBARD CONSTRUCTION CO / 4491091	10.961 / 28.1 / 11.115 / 7.370	12.045 / 29.2 / 12.888 / 14.368	R / 4 / C 1999 / R 2025	4 / 7.3 / (2003) / 0213	4 / 140500 / 0213	65 / CONC	CRACKING RIDE	9.3 / 7.4 / 9.2 / 8.0		9.4 / 8.6 / 9.1 / 8.3	9.4 / 8.0 / 9.0 / 8.3	9.4 / 8.2 / 9.0 / 8.3	9.4 / 8.1 / 9.0 / 8.2	9.4 / 8.2 / 9.0 / 8.2	9.3 / 8.1 / 9.0 / 8.2	9.4 / 8.1 / 9.1 / 8.0	9.3 / 7.9 / 9.3 / 8.5	9.2 / 7.8 / 9.0 / 8.4	9.2 / 8.1 / 8.0 / 8.5	8.0 / 8.2										
15190000 / 93 I275 / 4245012 / 4491091	12.045 / 29.2 / 12.185 / 7.370	12.900 / 30.0 / 12.872 / 14.368	R / 4 / C 2017 / R 2025	4 / 7.3 / (2023) / 0213	4 / 140500 / 0213	65 / CONC	CRACKING RIDE	9.3 / 7.4 / 9.3 / 8.1		9.4 / 8.6 / 9.1 / 7.8	9.4 / 8.0 / 9.1 / 8.1		9.4 / 8.1 / 9.1 / 8.1	9.3 / 8.0 / 9.1 / 8.0	9.3 / 8.0 / 9.1 / 8.0	9.5 / 8.2 / 9.1 / 8.2	9.3 / 8.3 / 9.5 / 7.6	9.4 / 7.7 / 9.5 / 7.4	9.3 / 7.9 / 9.3 / 7.9	9.2 / 8.2 / 8.5 / 8.1										
15190000 / 93 I275 / JONES BROS., INC. / 4491091	12.900 / 30.0 / 12.688 / 7.370	13.451 / 30.6 / 15.028 / 14.368	R / 4 / C 2001 / R 2025	4 / 7.3 / (2006) / 0213	4 / 134000 / 0213	65 / CONC	CRACKING RIDE	9.3 / 7.4 / 9.3 / 8.1	9.4 / 7.3 / 9.3 / 7.8	9.3 / 7.3 / 9.1 / 8.1			9.4 / 8.1 / 9.1 / 8.0	9.3 / 8.0 / 9.1 / 8.0	9.3 / 8.0 / 9.1 / 8.0	9.5 / 8.2 / 9.1 / 7.9	9.3 / 8.3 / 9.4 / 8.0	9.4 / 7.7 / 9.3 / 8.0	9.3 / 7.9 / 9.3 / 7.9	9.2 / 8.2 / 8.5 / 7.9										

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T / SURFTYPE / FY-P / ASTYPE / FY-F	AADT / WKMX-P / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
15190000	13.451	14.368	R	4	4	65			CRACKING	10.0	10.0	10.0			9.5	9.5	9.5	9.5	9.4	9.4	9.4	9.4													
93 I275	30.6	31.5	4	7.3	165000			CONC	RIDE	8.4	8.2	8.0			8.1	8.1	8.2	8.4	8.5	8.6	8.2	8.5													
2588701	12.688	15.028	C	2001		0213			CRACKING	9.4	9.4	9.4	9.4	9.4	9.3	9.3	9.3	9.4	9.4	9.4	9.1	9.1	8.5													
JONES BROS., INC.		(2006)							RIDE	8.5	8.5	8.6	8.6	8.6	8.6	8.4	8.5	8.6	8.3	8.3	8.2	8.3	8.2													
4491091	7.370	14.368	R	2025		0213																														
15190000	14.368	16.649	R	4	8	65			CRACKING	10.0	7.0	7.0	6.5		6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
93 I275	31.5	33.8	4	7.3	174000				RIDE	9.0	8.8	8.9	8.1		7.6	8.0	8.2	8.2	8.2	8.2	8.1	8.0													
END OF 15-240-000(14.5R)								FC5M																												
4134131	14.441	16.649	C	2006		0012			CRACKING	10.0	9.0	9.0	9.0	7.5	6.5	3.5*	3.5*	3.5*	3.5*	3.5*															
PREFERRED MATERIALS, INC.		(2007)							RIDE	8.0	7.9	8.1	8.0	8.0	7.9	8.1	8.1	8.0	7.8	8.2															
15190000	15.023	16.649	L	4	8	65			CRACKING	10.0	7.0	7.0	6.5		4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
93 I275	32.2	33.8	4	7.3	174000				RIDE	8.4	8.4	8.4	7.8		7.4	8.1	7.9	8.0	8.0	8.0	7.9	7.8													
								FC5M																												
4134131	14.441	16.649	C	2006		0012			CRACKING	9.0	7.5	6.5	6.5	4.5*	1.0*	1.0*	0.0*																		
PREFERRED MATERIALS, INC.		(2007)							RIDE	7.7	7.5	7.7	7.6	7.5	7.3	7.6	7.6																		
15190000	14.368	15.023	L	4	8	65			CRACKING	10.0	7.0	7.0	6.5		4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
93 I275	31.5	32.2	4	7.3	174000				RIDE	8.4	8.4	8.4	7.8		7.4	8.1	7.9	8.0	8.0	8.0	7.9	7.8													
								FC5M																												
2588701	12.688	15.028	C	2001		0213			CRACKING	9.0	7.5	6.5	6.5	4.5*	1.0*	1.0*	0.0*	0.0*	0.0*	0.0*															
JONES BROS., INC.		(2007)				SPR			RIDE	7.7	7.5	7.7	7.6	7.5	7.3	7.6	7.6	6.8	6.1*	5.5*															
15190000	13.451	14.368	L	4	4	65			CRACKING	10.0	10.0	10.0			9.5	9.5	9.5	9.5	9.5	9.5	9.4	9.4													
93 I275	30.6	31.5	4	7.3	165000			CONC	RIDE	8.6	8.5	8.4			7.0	7.4	7.7	7.1	7.9	8.0	8.0	8.4													
2588701	12.688	15.028	C	2001		0213			CRACKING	9.4	9.3	9.4	9.4	9.4	9.4	9.4	9.4	9.1	9.2	9.2	9.1	8.8	8.0													
JONES BROS., INC.		(2006)							RIDE	8.2	8.2	8.4	8.4	8.4	8.3	8.3	8.3	8.3	8.4	8.4	8.3	8.2	8.1													
4491091	7.358	14.668	L	2025		0213																														
15190000	12.456	13.451	L	4	4	65			CRACKING	8.8	8.6	8.3			9.5	9.5	9.5	9.4	9.2	9.3	9.1	9.1													
93 I275	29.6	30.6	4	7.3	134000			CONC	RIDE	7.2	6.1*	6.4*			7.6	7.5	7.3	7.3	7.3	8.0	7.8	7.9													
2588701	12.688	15.028	C	2001		0213			CRACKING	8.9	8.8	8.6	8.5	8.6	8.4	8.2	8.2	8.4	8.3	8.5	9.1	8.9	8.0													
JONES BROS., INC.		(2006)							RIDE	7.8	7.7	8.1	8.1	8.1	7.9	8.0	7.9	8.1	8.1	8.1	8.2	8.1	8.0													
4491091	7.358	14.668	L	2025		0213																														
15190000	10.961	12.456	L	4	2	65			CRACKING	8.8		9.3	9.3	9.3	9.4	9.3	9.1	9.3	9.0	9.1	8.9	9.0													
93 I275	28.1	29.6	4	7.3	140500			CONC	RIDE	7.2		8.5	7.9	7.9	7.7	7.6	7.9	7.5	7.4	7.5	7.5	7.8													
2588611	11.115	12.888	C	1999		0213			CRACKING	8.9	8.9	8.9	8.8	8.7	8.7	8.7	8.7	8.7	8.6	8.6	8.7	8.6	8.0													
HUBBARD CONSTRUCTION CO		(2003)							RIDE	7.5	7.4	8.1	8.1	8.0	8.0	8.1	8.0	8.1	8.1	8.1	8.2	8.2	8.1													
4491091	7.358	14.668	L	2025		0213																														
15190000	8.867	10.961	L	4	4	65			CRACKING	8.8	8.1	8.0	8.1	8.0	8.8	8.7	8.4	8.7	8.7	8.8	8.7	8.6													
93 I275	26.0	28.1	3	7.3	162000			LDG	RIDE	7.2	6.9	7.2	6.2*	6.2*	6.4*	6.5	6.3*	7.5	7.9	7.6	8.0	8.1													
2587901	8.300	18.200	C	1981		0101			CRACKING	8.5	8.5	8.3	8.3	8.2	8.2	8.1	8.2	8.0	8.1	7.6	7.9	7.6	6.5													
GEORGIA ELECTRIC CO		(1983)							RIDE	8.0	7.2	8.4	8.4	8.3	8.3	8.3	8.4	8.4	8.4	8.2	8.2	8.5	8.4													
4491091	7.358	14.668	L	2025		0213																														
15190000	5.284	8.867	L	4	4	65			CRACKING	8.8	8.1	8.0	8.1	8.0		9.2	8.9	8.6	8.4	8.4	8.1	8.1													
93 I275	22.4	26.0	3	7.3	173000			LDG	RIDE	7.2	6.9	7.2	6.2*	6.2*		7.4	7.6	7.5	7.6	7.6	7.1	7.4													
2588801	5.797	8.840	C	2004		0227			CRACKING	7.9	7.8	7.8	7.7	7.6	7.4	7.3	7.3	6.2*	6.8	6.3*	6.4*	5.7*	5.0*													
KIEWIT INFRASTRUCTURE SOUT		(2007)							RIDE	7.3	7.1	7.9	7.8	7.8	7.6	7.7	7.7	7.7	7.6	7.5	7.4	7.5	7.4													
4541721	5.282	7.358@	C	2028		0227																														
15190000	2.287	4.456	L	4	2	65			CRACKING	6.2*	4.4*	5.7*	5.6*	5.5*	7.5	7.4	6.8	7.6	7.6	7.8	7.4	7.1													
93 I275	19.4	21.6	3	7.3	115000			LDG	RIDE	6.9	6.6	8.2	7.7	7.7	7.5	7.4	7.0	7.5	7.8	8.0	7.6	7.5													
									CRACKING	6.9	6.6	6.3*	6.2*	6.1*	5.5*	5.2*	5.1*	3.9*	4.0*	3.7*	4.1*	7.4	6.5													
		(1983)							RIDE	7.5	7.2	8.1	8.0	7.9	7.8	7.7	7.8	7.9	7.7	7.6	7.4	8.1	8.0													
4460091	2.140	4.000	L	2023		0227																														
15190000	0.500	2.287	L	4	2	65			CRACKING	6.2*		7.8	7.8	7.6	7.9	7.8	7.7	7.7	7.9	8.2	8.3	8.1													
93 I275	17.6	19.4	3	7.3	104000			LDG	RIDE	6.9		8.3	8.0	8.1	7.8	7.8	7.8	7.8	7.9	7.7	7.5	7.8													
2588041	0.420	1.485	C	1982		0101			CRACKING	7.6	7.4	7.4	7.5	7.5	7.4	7.3	7.4	7.7	7.8	7.8	7.5	7.9	7.0													
COUCH, INC.		(1986)							RIDE	7.9	7.8	8.1	8.1	8.3	8.4	8.6	8.7	8.7	8.5	8.5	8.5	9.1	9.0													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	LN	%T	AADT	SURFTYPE / FY-P / ASTYPE / FY-F	DISTRESS / RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15190900	0.000	1.196	R	4	1	65					CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	6.5	6.0*	4.5*	4.5*	10.0													
55 I275	16.5	17.6	2	7.5	67613						RIDE	8.5	8.7	8.7	7.1	6.9	7.7	7.5	8.0	7.8	7.8	7.5	7.2	8.3													
OLD TOLL PLAZA(0.0C)										FC5M																											
4251461	0.515	1.196	C	2012					0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	6.5	4.5*	2.0*												
LANE CONSTRUCTION CORPORAT(2013)										SPRIDE	RIDE	8.2	8.2	8.2	8.2	8.3	8.2	8.3	8.3	8.2	8.2	8.0	8.0	8.0	7.9												
4491531	0.000	1.196	C	2027					0012																												
15190900	0.000	1.196	L	4	1	65					CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	6.5	6.0*	6.0*	10.0													
55 I275	16.5	17.6	2	7.5	67613						RIDE	8.4	8.6	8.6	8.1	8.0	7.9	7.5	7.9	7.9	7.9	7.2	7.6	8.2													
OLD TOLL PLAZA(0.0C)										FC5M																											
4251461	0.515	1.196	C	2012					0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	6.5	5.1*	2.5*												
LANE CONSTRUCTION CORPORAT(2013)										SPRIDE	RIDE	8.1	8.1	7.9	8.2	8.2	8.1	8.2	8.2	8.2	8.1	8.0	8.0	8.0	7.9												
4491531	0.000	1.196	C	2027					0012																												
15190905	0.000	0.390	C	1	1	30					CRACKING																											
663			2	8.7	2900						RIDE																											
											CRACKING														4.3*												
											RIDE														6.4												
4491531	0.000	0.390	C	2027					0012																												
15190908	0.000	2.172	C	4	5						CRACKING																											
93 I275			1								RIDE																											
										CONC																											
											CRACKING														9.4	9.0											
				(2026)							RIDE														8.2	8.1											
15190909	0.000	4.248	C	4	5						CRACKING																											
93 I275			1								RIDE																											
										CONC																											
											CRACKING														8.8	8.5											
				(2026)							RIDE														8.3	8.2											
15200000	5.144	5.845	C	3	1	35					CRACKING	3.5*	3.5*	10.0	10.0	8.5	8.5	10.0	10.0	10.0	8.5	8.5	8.5	8.5													
679			2	4.5	14800						RIDE	7.7	7.5	8.5	7.8	7.9	7.7	7.7	7.7	7.5	7.4	7.2	6.9	6.9													
										FC125M																											
											CRACKING	8.5	7.5	7.0	7.0	6.0*	5.0*	5.0*	5.0*	3.5*	3.5*	10.0	10.0	10.0	9.0												
				(2024)							RIDE	7.1	6.8	6.5	6.7	6.5	6.4	6.2	6.4	6.2	6.2	7.1	7.0	6.9	6.5												
15200000	5.845	8.476	R	3	1	40					CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5													
679			2	4.5	14800						RIDE	8.9	8.8	8.8	8.1	8.1	7.6	7.7	7.6	7.3	7.4	7.3	6.7	6.6													
EAST SHORES BLVD(6.7R)										FC125M																											
4402441	6.148	8.132	C	2022					0012		CRACKING	8.5	7.0	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	9.0												
HUBBARD CONSTRUCTION COMPA(2024)										SPRIDE	RIDE	6.7	6.7	6.9	6.8	6.7	6.4	6.5	6.0	5.9	6.2	7.6	7.5	7.4	7.0												
15200000	8.941	9.960	C	3	1	45					CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.0	7.0	7.0													
679			2	4.5	14800						RIDE	7.1		8.1	7.5	7.3	7.2	7.1	7.2	6.4	6.8	6.7	5.9	6.1													
SCENIC OVERLOOK(9.1C)										DGFC																											
											CRACKING	7.0	7.0	7.0	7.0	6.5	5.5*				10.0	10.0	10.0	10.0	9.0												
				(2023)							RIDE	6.3	6.2	6.3	6.6	6.0	6.0				7.6	7.5	7.4	7.4	7.0												
15200000	5.845	8.476	L	3	1	40					CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5													
679			2	4.5	14800						RIDE	8.7	8.6	8.5	7.8	7.9	7.7	7.5	7.6	7.4	7.5	7.3	6.8	6.7													
EASTSHORE BLVD(6.7L)										FC125M																											
4402441	6.148	8.132	C	2022					0012		CRACKING	8.5	8.0	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	9.0												
HUBBARD CONSTRUCTION COMPA(2024)										SPRIDE	RIDE	6.8	6.6	6.9	6.8	6.7	6.4	6.6	6.4	6.2	6.2	7.2	7.1	6.9	6.5												
15200001	0.000	0.429	R	3	1	35					CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	6.5	6.0*	6.0*	6.0*													
682			2	4.2	19800						RIDE	7.2	8.2	7.8	7.1	6.2	6.6	7.5	6.8	6.3	6.9	6.7	6.7	6.4													
GULF BLVD(0.0R)										FC125R																											
											CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.2	6.8	5.0*												
				(2016)							RIDE	5.9		6.9	6.8	6.8	6.8	6.7	6.7	6.5	6.1	5.9	5.9	6.0	5.6												
15200001	0.925	1.531	R	3	1	45					CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5														
682			2	4.2	19800						RIDE	8.4	8.2	8.2	7.6	7.8	7.6	7.5	7.1	7.4	7.3	7.2	7.1														
BAHIA DEL MAR BLVD(1.0R)										FC125R																											
											CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	10.0	8.0												
				(2016)							RIDE			7.7	7.6	7.6	7.4	7.4	7.4	7.3	7.0	6.9	6.8	7.0	6.6												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / US / G_BMP / G_EMP / LN / %T / AADT / INTERSECT AT (MP|SIDE) / ITMSEG-P / W_BMP / W_EMP / RW / FY-P / WKMX-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F / W_BMP / W_EMP / RW / FY-F / WKMX-F	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
15200001 1.531 2.821 R 3 1 45 682 2 5.3 28500 ESCONDIDA BLVD(1.7R) FC125M 4416521 1.531 2.821 C 2022 0012 AJAX PAVING INDUSTRIES OF (2025)	1	R	45	CRACKING RIDE SPRIDE	9.0 7.7 8.0		10.0 8.8 7.8	10.0 8.4 7.8	10.0 8.4 7.6	10.0 8.3 7.5	10.0 8.3 7.5	10.0 8.2 7.4	10.0 8.2 7.3	10.0 8.3 7.2	10.0 8.3	10.0 8.1 7.8	10.0 8.1 8.0	9.0 7.6
15200001 2.821 3.286 R 3 1 45 682 3 9.0 39500 FROM ECKERD COLLEGE(3.2R) FC125M 4416521 2.970 3.290 C 2022 0012 AJAX PAVING INDUSTRIES OF (2025)	1	R	45	CRACKING RIDE SPRIDE	7.0 6.9 7.6		10.0 8.1 7.6	10.0 7.4 7.6	10.0 7.8 7.5	10.0 7.4 7.1	10.0 7.6 7.3	10.0 8.0 7.1	10.0 7.7 7.0	10.0 7.7 6.9	9.0 7.7	9.0 7.8 8.2	9.0 7.7 8.2	9.0 7.8
15200001 3.286 3.721 C 3 1 45 682 2 9.0 19500 WATER RECLAIM FAC SW(3.3L) FC125M 4348391 3.521 3.721 C 2018 0012 NATIONWIDE MUTUAL INSURANC(2020)	1	C	45	CRACKING RIDE CRACKING RIDE	7.0 6.4* 7.5 6.3	5.5* 6.6	10.0 8.0 4.0* 6.6	10.0 7.4 3.5* 6.6	10.0 7.2 3.5* 6.3	10.0 7.1 3.0* 6.4	10.0 7.6 10.0 8.1	10.0 7.1 10.0 8.0	10.0 7.2 10.0 7.8	10.0 7.3 10.0 7.7	9.0 6.9 10.0 7.7	9.0 6.9 8.4 7.4	8.5 7.2 8.7 7.3	7.0 6.9
15200001 2.821 3.286 L 3 1 45 682 3 9.0 39500 DOLPHIN CAY LN(3.0L) FC125M 4416521 2.970 3.290 C 2022 0012 AJAX PAVING INDUSTRIES OF (2025)	1	L	45	CRACKING RIDE SPRIDE	7.0 6.4* 8.5 7.3	7.5 7.2	10.0 8.0 7.0 7.3	10.0 7.4 7.0 7.2	10.0 7.2 7.0 7.2	10.0 7.1 5.5* 7.1	10.0 7.5 5.5* 6.9	10.0 7.5 5.5* 6.9	10.0 7.8 5.5* 6.8	10.0 7.9 3.0* 6.6	10.0 7.8	10.0 7.4 10.0 8.0	10.0 7.3 10.0 8.0	9.0 7.6
15200001 1.531 2.821 L 3 1 45 682 2 5.3 28500 PLAYA ESCONDIDA ENT(1.7L) FC125M 4416521 1.531 2.821 C 2022 0012 AJAX PAVING INDUSTRIES OF (2025)	1	L	45	CRACKING RIDE SPRIDE	9.0 7.7 8.5 7.4	7.0 7.3	10.0 8.6 6.5 7.4	10.0 8.3 6.5 7.3	10.0 8.0 6.5 7.4	10.0 7.9 6.0* 7.2	10.0 8.0 6.0* 7.2	10.0 8.2 5.5* 7.0	10.0 7.6 5.5* 6.9	9.0 7.6 5.5* 6.8	9.0 7.7	9.0 7.3 10.0 7.7	9.0 7.3 10.0 8.0	9.0 7.6
15200001 0.925 1.531 L 3 1 45 682 2 4.2 19800 BAHIA DEL MAR BLVD(1.0L) FC125R (2016)	1	L	45	CRACKING RIDE CRACKING RIDE	10.0 8.5 10.0 7.9	10.0 7.3 10.0 7.8	10.0 8.3 10.0 7.8	10.0 7.7 10.0 7.8	7.0 7.8 10.0 7.8	7.0 7.6 10.0 7.8	7.0 7.5 10.0 7.7	7.0 7.4 10.0 7.7	6.5 7.5 10.0 7.7	6.5 7.4 10.0 7.5	6.5 7.4 10.0 7.2	6.0* 7.1 9.6 7.5	9.6 7.4	8.0 7.0
15200001 0.000 0.429 L 3 1 35 682 2 4.2 19800 SR-699/GULF BLVD(0.0L) FC125R (2016)	1	L	35	CRACKING RIDE CRACKING RIDE	10.0 8.2 6.0* 5.9	10.0 7.6	10.0 7.8 10.0 6.9	10.0 7.1 10.0 6.8	8.5 6.2 10.0 6.8	8.5 6.6 10.0 6.7	8.5 7.1 10.0 6.5	8.5 7.0 10.0 6.6	7.0 6.3 8.5 6.6	6.5 6.0 8.5 6.4	6.0* 5.6 8.5 6.4	6.0* 6.7 8.1 6.3	6.0* 6.4 7.9 6.3	6.0* 5.9
15200003 0.000 0.418 C 1 1 45 682 2 9.0 19500 SR 55(0.0C) FC125M 4348391 0.179 0.390 C 2018 0012 NATIONWIDE MUTUAL INSURANC(2021)	1	C	45	CRACKING RIDE CRACKING RIDE	7.5 6.4	7.5 6.3	7.0 6.3	7.0 6.0	6.0* 5.9	6.0* 5.8	6.0* 5.8	10.0 7.7 10.0 8.1	8.5 7.1 10.0 8.0	8.5 7.1 10.0 8.0	8.5 7.0 10.0 8.0	8.5 6.8 10.0 7.9	7.5 6.7 10.0 6.3	8.5 5.9
15200100 0.000 0.121 C 1 1 30 661 2 8.7 4500 4491531 0.000 0.075 C 2027 0012		C	30	CRACKING RIDE CRACKING RIDE													8.0 5.3*	
15220000 0.197 1.225 R 1 7 45 60 2 4.9 36500 CAUSEWAY PARKING ENT(1.2R) FC125H (2026)	1	R	45	CRACKING RIDE CRACKING RIDE	6.5 8.4 8.5 7.2	6.5 8.2 7.5 7.1	6.5 8.2 7.0 6.5	6.5 6.7 7.0 6.5	6.5 7.0 7.0 6.4	6.5 7.0 7.0 6.3	10.0 7.3 7.0 6.4	10.0 7.4 5.5* 6.2	8.5 7.3 5.5* 6.2	8.5 7.4 5.5* 6.1	8.5 7.3 5.5* 6.0	8.5 6.9 3.5* 6.0	8.5 7.2 10.0 8.3	9.0 7.9
15220000 0.197 1.225 L 1 7 45 60 2 4.9 36500 FROM ISLAND WAY(0.6L) FC125H (2026)	1	L	45	CRACKING RIDE CRACKING RIDE	6.5 8.4 8.5 7.3	6.5 8.4 8.5 7.1	6.5 8.2 7.0 6.7	6.5 7.9 7.0 6.6	6.5 7.6 7.0 6.3	6.5 7.7 7.0 6.3	10.0 7.5 7.0 6.2	10.0 7.7 5.5* 6.2	8.5 7.6 5.5* 6.2	8.5 7.6 5.5* 6.2	8.5 7.4 5.5* 5.9	8.5 7.2 5.3* 5.9	8.5 7.3 10.0 8.4	9.0 8.0

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 7 COUNTY = PINELLAS ----------

RDWYID / SR / US / G_BMP / G_EMP / LN / %T / AADT / DISTRESS / SURVEYED YEAR															FUTURE
	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013		
INTERSECT AT (MP|SIDE) / SURFTYPE / ========															
ITMSEG-P / W_BMP / W_EMP / RW / FY-P / WKMX-P															
CONTRACTOR (AGE_ONE YEAR) / ASTYPE	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
ITMSEG-F / W_BMP / W_EMP / RW / FY-F / WKMX-F														(PMRS)	
15230000 / 0.000 / 0.587 / R / 1 / 1 / 40	CRACKING	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	9.5	9.5	9.5	9.5	9.5	
693 / 3 / 9.4 / 28500	RIDE	5.4*	5.4*	5.2*	4.8*	4.6*	4.7*	6.2	6.4	6.5	6.3	6.2	6.1	5.9	
PARK ST(0.0C) / FC125M															
4402542 / 0.000 / 0.600 / C / 2022 / 0012	CRACKING	9.0	8.5	8.5	8.0	8.0	8.0	7.0	7.0	6.0*	10.0	10.0	9.5	10.0	9.0
PREFERRED MATERIALS, INC. (2023)	SPRIDE	5.9	5.8	5.1*	5.1*	5.1*	5.0*	5.1*	4.9*	4.8*	7.3	8.2	8.3	8.0	7.6
15230000 / 0.587 / 2.223 / R / 1 / 1 / 40	CRACKING	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	9.5	9.5	9.5	9.5	9.5	
693 / 3 / 2.8 / 39000	RIDE	5.4*	5.4*	5.2*	4.8*	4.6*	4.7*	6.2	6.4	6.5	6.3	6.2	6.1	5.9	
CENTRAL AVE(0.6C) / FC125H															
4402541 / 1.004 / 2.223 / C / 2023 / 0012	CRACKING	9.0	8.5	8.5	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	9.0
HUBBARD CONSTRUCTION COMPA(2025)	SPRIDE	5.9	5.8	5.1*	5.1*	5.1*	5.0*	5.1*	4.9*	4.8*	4.6*	4.7*	6.4	6.5	6.1
15230000 / 2.223 / 5.392 / R / 1 / 1 / 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	10.0	10.0	
693 / 3 / 9.4 / 45500	RIDE	7.3	7.2	7.5	6.8	6.6	6.9	6.5	6.5	6.6	6.5	6.3	7.7	7.5	
26 AVE N(2.4C) / FC125															
4113301 / 2.223 / 5.342 / C / 2011 / 0226	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	6.5	4.5*
AJAX PAVING INDUSTRIES OF (2012)	RIDE	7.7	7.5	7.4	7.3	7.4	7.4	7.3	7.3	7.2	6.9	7.1	7.1	6.9	6.5
4512391 / 2.223 / 5.371 / C / 2029 / 0012															
15230000 / 2.223 / 5.392 / L / 1 / 1 / 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	10.0	10.0	
693 / 3 / 9.4 / 45500	RIDE	7.1	7.3	7.2	6.6	6.2*	6.5	6.1	6.2	6.3	6.1	6.0	8.0	7.7	
26 AVE N(2.4C) / FC125															
4113301 / 2.223 / 5.342 / C / 2011 / 0226	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.0	6.5	6.5	4.5*
AJAX PAVING INDUSTRIES OF (2012)	RIDE	7.3	7.0	7.1	7.1	7.1	6.9	7.2	6.9	7.0	6.9	6.8	6.9	6.7	6.3
4512391 / 2.223 / 5.371 / C / 2029 / 0012															
15230000 / 0.587 / 2.223 / L / 1 / 1 / 40	CRACKING	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
693 / 3 / 2.8 / 39000	RIDE	7.0	6.9	6.5	5.9	5.6	5.0*	7.0	7.0	7.0	6.9	7.0	6.9	7.0	
CENTRAL AVE(0.6C) / FC125H															
4402541 / 1.004 / 2.223 / C / 2023 / 0012	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	9.0
HUBBARD CONSTRUCTION COMPA(2025)	SPRIDE	6.8	6.8	6.1	6.1	6.0	5.9	5.9	6.0	5.6	5.4*	5.4*	6.7	6.6	6.2
15230000 / 0.000 / 0.587 / L / 1 / 1 / 40	CRACKING	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
693 / 3 / 9.4 / 28500	RIDE	7.0	6.9	6.5	5.9	5.6	5.0*	7.0	7.0	7.0	6.9	7.0	6.9	7.0	
PARK ST(0.0C) / FC125M															
4402542 / 0.000 / 0.600 / C / 2022 / 0012	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	10.0	10.0	9.1	10.0	9.0
PREFERRED MATERIALS, INC. (2023)	SPRIDE	6.8	6.8	6.1	6.1	6.0	5.9	5.9	6.0	5.6	8.1	8.2	8.2	8.3	7.9
15240000 / 0.000 / 0.700 / R / 1 / 1 / 50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			9.5	
694 / 3 / 6.4 / 69000	RIDE	8.5	8.3	8.5	7.8	7.9	8.0	7.7	8.0	8.3	8.3			8.0	
BRIDGE #125(0.0C) / FC5M															
4416501 / 0.322 / 0.700 / C / 2023 / 0012	CRACKING	9.5	9.0	7.5	7.5	7.5	7.0	7.0	6.5	6.5	6.0*	6.0*	10.0	10.0	8.5
AJAX PAVING INDUSTRIES OF (2025)	SPRIDE	8.0	8.0	7.6	7.7	7.7	7.7	7.7	7.6	7.5	7.4	7.4	8.4	8.0	7.8
15240000 / 0.700 / 1.842 / R / 1 / 1 / 50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5			10.0	
694 / 3 / 7.1 / 78500	RIDE	8.5	8.3	8.5	7.8	7.9	8.0	7.7	7.9	7.5	7.7			8.0	
	FC5M														
4438071 / 0.935 / 1.600 / C / 2023 / 0012	CRACKING	10.0	10.0	9.0			6.5	6.5	6.5	4.5*	4.5*	3.5*	10.0	10.0	8.5
AJAX PAVING INDUSTRIES OF (2025)	SPRIDE	7.6	7.9	8.0			7.9	8.0	8.2	7.9	7.6	7.4	8.7	8.5	8.3
15240000 / 3.330 / 3.620 / R / 1 / 1 / 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
687 / 3 / 6.4 / 28500	RIDE	7.6	7.8	7.8	7.6	7.4	7.1	7.2	7.2	6.7	6.8	6.6	6.6	6.8	
SANDPIPER(3.5R) / DGFC															
	CRACKING	10.0	10.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.6	7.0
(2019)	RIDE	6.5	6.6	7.1	7.3	6.7								7.7	7.3
15240000 / 3.620 / 5.373 / R / 1 / 1 / 55	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	4.5*	
687 / 2 / 6.4 / 28500	RIDE	9.0	9.0	8.8	8.0	8.1	8.0	7.9	8.0	7.8	7.8	7.4	7.1	7.1	
108 AVE N(3.7R) / FC5A															
4309001 / 3.620 / 5.537 / C / 2015 / 0012	CRACKING	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	8.8	5.5*
LANE CONSTRUCTION CORPORAT(2017)	RIDE	7.0	6.6	7.4	8.5	8.5	8.4	8.5	8.4	8.4	8.4	8.4	8.3	8.3	8.1
4560601 / 3.610 / 5.400 / C / 2026 / 0012															
15240000 / 5.373 / 5.760 / R / 1 / 2 / 55	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	
687 / 2 / 6.4 / 28500	RIDE	8.1	8.1	8.8	8.0	8.1	8.0	7.9	7.9	7.7	7.7	7.7	7.3	6.8	
SCENIC OVERLOOK(5.4R) / FC2															
	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	7.0	6.5	6.0*	6.0*		10.0	10.0	8.5
(2025)	RIDE	6.8	6.8	7.5	7.1	7.1	7.0	6.9	7.2	7.2	7.2		7.3	7.7	7.5

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T	AADT	SURFTYPE / ASTYPE / WKMX-P / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
15240000	5.760	5.883	C	1	2	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0													
687			1	4.0		4600				RIDE	8.1	8.1	8.1	7.6	7.5	7.4	7.9	8.0	7.7	7.7	7.7	7.3	7.4													
RAMP #190071(5.8C)									OGFC																												
										CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.0*	6.0*		10.0	10.0	8.5												
		(2025)								RIDE	7.3	7.2	7.1	7.0	7.2	6.9	6.8	7.1	6.9	6.8		7.4	6.2*	6.0*												
15240000	5.373	5.760	L	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0													
687			2	6.4		28500				RIDE	8.1	8.1	8.8	8.2	8.2	8.2	8.1	8.0	7.7	7.9	7.7	7.6	7.4													
RAMP #190071(5.8C)									FC2																												
										CRACKING	10.0	9.0	9.0	9.0	9.0	6.5	6.5	4.5*				10.0	10.0	8.5												
		(2025)								RIDE	7.4	7.0	7.3	7.1	7.0	7.1	7.5	7.3				7.3	7.4	7.2												
15240000	3.620	5.373	L	1	1	55				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.0	6.5	6.5	4.5*													
687			2	6.4		28500				RIDE	9.1	9.1	8.8	8.2	8.2	8.2	8.1	7.9	7.8	7.6	7.2	7.0	6.7													
ONE HUNDRED TENTH ST L(3.9L)									FC5A																												
4309001	3.620	5.537	C	2015		0012				CRACKING	4.5*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.1	4.5*												
LANE CONSTRUCTION CORPORAT(2017)										RIDE	6.5	6.3*	7.0	8.4	8.4	8.3	8.4	8.3	8.3	8.4	8.3	8.2	8.2	8.0												
4560601	3.610	5.400	C	2026		0012																															
15240000	3.330	3.620	L	1	1	40				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
687			3	6.4		28500				RIDE	8.2	8.5	8.3	7.7	8.1	7.8	7.5	7.8	7.7	7.7	7.4	7.3	7.3													
GANDY BLVD WB(3.4L)									DGFC																												
										CRACKING	10.0	10.0	9.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	9.1	10.0	8.5												
		(2019)								RIDE	7.4	7.3	6.7	5.7									7.5	7.1												
15240000	0.700	1.842	L	1	1	50				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5			10.0													
694			3	7.1		78500				RIDE	8.6	8.6	8.5	8.1	8.1	8.2	7.8	8.0	7.4	7.9			8.2													
									FC5M																													
4438071	0.935	1.600	C	2023		0012				CRACKING	10.0	10.0				6.5	6.5	6.5	4.5*	4.5*	3.5*	10.0	10.0	8.5												
AJAX PAVING INDUSTRIES OF (2025)									SPRIDE		8.2	8.2				7.5	7.6	7.9	7.9	7.9	7.5	8.9	8.8	8.6												
15240000	0.000	0.700	L	1	1	50				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5			7.5													
694			2	6.4		69000				RIDE	8.6	8.6	8.5	8.1	8.1	8.2	7.8	7.9	8.2	8.3			7.8													
BRIDGE #125(0.0C)									FC5M																												
4416501	0.322	0.700	C	2023		0012				CRACKING	7.5	7.5	7.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	10.0	10.0	8.5												
AJAX PAVING INDUSTRIES OF (2025)									SPRIDE		8.1	7.8	7.8	7.7	7.6	7.4	7.3	7.5	7.2	7.3	7.3	8.4	8.6	8.4												
15240001	0.000	0.540	C	1	7	35				CRACKING	8.5	7.0																									
664			2	8.7		2000				RIDE	6.4*	6.9																									
4416501	0.068	0.639	C	2023		0012				CRACKING													10.0	9.0												
AJAX PAVING INDUSTRIES OF (2026)									SPRIDE														7.2	6.8												
15240001	0.540	0.639	C	1	1	35				CRACKING	8.5	7.0																									
664			2	8.7		2000				RIDE	6.4*	6.9																									
										CRACKING													7.8	5.0*												
		(2000)								RIDE													7.2	6.8												
15240002	0.000	0.817	C	1	1	30				CRACKING																											
657			2	8.7		2000				RIDE																											
										CRACKING													10.0	9.0												
		(2026)								RIDE													7.4	7.0												
15240003	0.844	1.051	C	1	1					CRACKING																											
647			2	8.7		200				RIDE																											
										CRACKING													8.1													
										RIDE													6.0*													
15240043	0.000	0.365	C	1	1	30				CRACKING	10.0	10.0	10.0	10.0	10.0	8.5																				
662			2	8.7		6000				RIDE	7.0	6.6	6.6	6.6	7.0	6.4																				
										CRACKING													6.5	3.5*												
		(2001)								RIDE													5.2*	4.8*												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 7 COUNTY = PINELLAS

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / FY-P / FY-F	SYS / %T / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	TYP / AADT	SPD	DISTRESS / RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
15240043 662	0.365	0.605	C 1 2 8.7	1 6000	30		CRACKING RIDE	10.0 7.0	10.0 6.6	10.0 6.6	10.0 6.6	10.0 7.0	8.5 6.4																					
4416501 AJAX PAVING INDUSTRIES OF	0.421	0.605	C 2023 (2026)	SPRIDE	0012		CRACKING RIDE																									10.0 7.9	9.0 7.5
15241000 694 92 15240047 NB OFF(0.0R)	0.000	2.245	R 1 2 9.3	1 FC5A	50 57000		CRACKING RIDE							10.0 8.5	10.0 8.5	10.0 8.4	10.0 8.4	10.0 8.3	8.9 8.3	9.0 8.4	6.5 8.2													
15241000 694 92 I 275 ENT(0.0C)	0.000	2.245	L 1 2 9.3	1 FC5A	50 57000		CRACKING RIDE							10.0 8.5	10.0 8.5	10.0 8.5	10.0 8.4	9.0 8.3	8.3 8.3	8.9 8.5	6.0* 8.3													
15241100 600F	0.000	1.286	C 1 2 6.8	1 	40 5900		CRACKING RIDE																									10.0 6.9	9.0 6.5
15241200 694F	0.000	1.084	C 1 2 6.8	1 	40 5900		CRACKING RIDE																									10.0 7.2	9.0 6.8
15242000 690	0.000 0.0	0.193 0.2	R 3 1 7.3	5 OGFC	40 31500		CRACKING RIDE																									10.0 7.6	9.0 7.4
15242000 690	0.803 0.8	1.088 1.1	R 3 1 7.3	5 OGFC	40 31500		CRACKING RIDE																									10.0 7.9	9.0 7.7
15242000 690	1.850 1.9	2.131 2.1	R 3 2 7.3	5 OGFC	55 31500		CRACKING RIDE																									10.0 8.1	9.0 7.9
15242000 690	1.850 1.9	2.131 2.1	L 3 2 7.3	5 OGFC	55 31500		CRACKING RIDE																									10.0 8.4	9.0 8.2
15242000 690	0.803 0.8	1.088 1.1	L 3 1 7.3	5 OGFC	40 31500		CRACKING RIDE																									10.0 8.1	9.0 7.9
15242000 690	0.000 0.0	0.193 0.2	L 3 1 7.3	5 OGFC	40 31500		CRACKING RIDE																									10.0 6.5	9.0 6.3

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).