

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN - 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	#T	AADT	RATINGS	=====	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP)	(SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-M	ASTYPE	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	(PMRS)
ITMSEG-P	(AGE_ONE)	YEAR	RW	FY-F	WKM-M	F															
CONTRACTOR																					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-M	F															
15002000	0.000	0.064	R	4	4	50	CRACKING	7.0	9.4	9.4	9.4	9.4	9.4		9.4	9.5	9.1	9.5	9.4	9.4	
592 I375	0.0	0.1	2	18.5	17000		RIDE	6.3*	6.1*	5.8*	7.4		8.0		7.8	8.1	8.1	7.9	8.0	7.9	
I 275 SB(0.0C)					LDG																
				(2008)			CRACKING	9.4	9.4	9.4	9.4	9.4	9.4	9.3	9.4	9.0	9.0	9.4	9.0	9.5	9.0
							RIDE	7.9	7.8	8.3	8.1	8.3	8.1	8.3	8.4	8.3	8.3	8.3	8.4	8.4	8.4
15002000	0.501	1.166	R	4	2	50	CRACKING	8.8	6.9	7.1	6.9	6.7	6.6		8.2	8.2	8.2	8.1	8.2	8.6	
592 I375	0.5	1.2	2	4.0	24500		RIDE	6.8	6.5	6.1*	5.7*		5.6*		7.3	7.5	7.6	7.8	7.7	7.7	
				(2001)			CRACKING	8.6	8.6	8.2	8.2	8.2	8.2	8.0	8.1	7.7	7.7	7.6	7.6	8.4	7.5
					LDG		RIDE	7.6	7.7	7.9	7.8	7.7	7.7	7.8	7.8	7.8	7.7	7.7	7.6	8.2	8.1
4458651	0.112	1.220	C	2023	0227																
15002000	1.166	1.220	C	4	2	30	CRACKING		4.5*	3.2*	3.2*	0.0*	0.0*		9.4	8.5	7.4	8.2	8.2	4.3*	
592 I375	1.2	1.2	2	4.0	14500		RIDE		5.8	8.4	5.0*		4.6*		6.0	6.8	6.7	7.4	6.5	6.5	
I 375 WB(1.2L)					CONC																
4087301	0.994	1.318	C	2006	0227		CRACKING	4.3*	4.3*	6.6	6.5	6.4*	8.2	7.6	7.6	7.3	6.3*	5.6*	6.8	7.1	6.5
KIEWIT INFRASTRUCTURE SOUT(2008)							RIDE	6.0	6.0	7.3	7.5	7.4	6.8	7.5	7.4	7.7	7.6	7.4	7.5	7.2	7.1
4458651	0.112	1.220	C	2023	0227																
15002000	0.899	1.166	L	4	2	50	CRACKING	8.0												8.8	
592 I375	0.9	1.2	2	4.0	24500		RIDE	6.6												6.4*	
I 375 WB(1.2L)					LDG																
				(2013)			CRACKING	8.8	8.8	8.7	8.7	8.5	8.5	8.3	8.3	8.8	8.7	8.4	8.4	8.3	7.5
							RIDE	6.4*	6.5	7.6	7.7	7.4	6.7	7.7	7.4	7.2	7.0	7.2	6.8	7.7	7.6
4458651	0.112	1.220	C	2023	0227																
15002000	0.312	0.899	L	4	2	50	CRACKING	8.0	7.4	7.6	7.6	7.4	7.4		9.1	9.0	8.7	8.9	8.7	8.4	
592 I375	0.3	0.9	3	4.0	38500		RIDE	6.6	6.8	6.7	6.2*		6.1*		7.5	7.9	7.8	8.2	8.1	7.8	
				(2008)			CRACKING	8.4	8.5	8.4	8.4	8.4	8.2	8.2	8.2	8.9	8.5	8.2	7.7	8.7	8.0
4087301	0.303	0.992	C	2006	0227		RIDE	8.1	8.2	8.0	8.2	8.0	7.7	8.2	8.0	8.1	8.0	8.1	7.7	8.5	8.4
KIEWIT INFRASTRUCTURE SOUT(2008)																					
4458651	0.112	1.220	C	2023	0227																
15002000	0.000	0.312	L	4	2	50	CRACKING	6.0*	9.4	8.8	8.8	8.7	8.7		9.5	9.0	9.0	8.5	8.9	8.9	
592 I375	0.0	0.3	2	4.0	38500		RIDE	6.9	6.9	6.1*	7.7		6.7		7.8	8.3	7.9	8.0	7.7	7.9	
I 275 SB(0.0C)					LDG																
				(2008)			CRACKING	8.8	8.7	8.7	8.6	8.8	8.8	8.7	8.7	8.8	8.9	8.8	8.3	8.6	8.0
							RIDE	7.8	8.0	8.2	8.3	7.9	7.9	8.1	8.1	8.1	7.9	7.8	7.3	8.3	8.2
4458651	0.112	1.220	C	2023	0227																
15003000	0.298	1.285	R	4	4	50	CRACKING	8.4	7.2	7.3	6.9	6.7	6.6		6.3*	8.6	8.4	8.5	8.3	8.2	
594 I175	0.3	1.3	2	4.0	28500		RIDE	6.8	7.1	6.8	6.5	6.4*	6.3*		6.0*	6.9	7.4	7.7	7.7	7.7	
FIFTH AVE S(1.2R)					LDG																
4087261	0.607	1.114	C	2007	0227		CRACKING	8.0	7.9	7.7	7.7	7.8	7.8	7.5	7.1	6.4*	6.1*	5.8*	5.7*	5.2*	4.5*
PHOENIX CONSTRUCTION SERVI(2009)							RIDE	7.7	7.8	8.0	8.0	7.9	7.9	7.8	7.9	7.9	7.8	7.7	7.7	7.7	7.6
4458641	0.298	1.285	C	2025	0227																
15003000	1.285	1.372	C	1	1	30	CRACKING	8.5	7.2	7.3	7.0	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	
594	1.3	1.4	4	4.0	9000		RIDE	6.7	7.1	6.8											
4 ST S(1.3R)					DGFC																
				(2010)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.3
							RIDE													3.7*	5.0*
																					3.3*
15003000	0.298	1.285	L	4	4	50	CRACKING	8.5	7.7	7.6	7.3	7.2	7.0		7.2	8.4	8.3	8.2	8.5	8.1	
594 I175	0.3	1.3	2	4.0	28500		RIDE	6.7	6.8	6.6	6.0*	6.2*	5.9*		6.2*	7.3	7.5	7.6	7.4	7.5	
FOURTH ST S(1.3L)					LDG																
				(1983)			CRACKING	7.9	7.7	7.8	7.7	7.6	7.4	7.4	7.3	6.8	6.8	6.6	6.6	6.3*	5.0*
							RIDE	7.2	7.5	7.7	7.5	7.6	7.7	7.8	7.7	7.6	7.7	7.4	7.4	7.5	7.4
4458641	0.298	1.285	C	2025	0227																
15007000	0.000	3.058	R	1	1	40	CRACKING	10.0	9.0	7.0	7.0	7.0	6.5	7.5	6.5	6.5	6.5	6.5	6.5	10.0	
595 A19			3	4.0	32000		RIDE	7.3	7.5	7.4	6.4	6.4	6.4	6.0	6.3	6.6	6.4	6.3	6.2	8.0	
SR-686/E BAY DR(0.0R)					FC125R																
4168361	0.000	2.947	C	2011	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	8.0	7.3	5.5*
R. E. PURCELL CONSTRUCTION(2013)					SPRIDE		RIDE	7.9	7.6	7.8	7.8	7.6	7.7	7.6	7.5	7.5	7.4	7.2	7.3	7.3	6.9
15007000	3.058	3.785	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	6.5	6.5	6.5	
60			2	4.0	42500		RIDE	7.0	6.8	6.9	6.9	6.5	6.6	6.3	6.4	6.2	6.1	6.0	6.0	6.1	
LINCOLN AVE(3.1R)					FC125A																
4290071	3.063	3.550	C	2014	0012		CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.9	9.0	7.0
PREFERRED MATERIALS, INC. (2015)							RIDE	6.2	7.6	7.4	7.4	7.4	7.2	7.0	6.9	6.8	6.9	6.8	6.8	6.6	6.2

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)		W_BMP		W_EMP		RW		FY-P		WKM-F		ASTYPE										(PMRS)
		(AGE_ONE YEAR)																				
15007000		3.058	3.785	L	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5		
60					2	4.0	42500 RIDE	8.1	8.0	7.9	7.4	7.5	7.3	6.6	7.0	6.9	7.0	6.7	6.2	6.5		
S LINCOLN AVE(3.1L)						FC125A																
4290071		3.063	3.550	C	2014	0012	CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.2	8.1	6.0*
PREFERRED MATERIALS, INC. (2015)						RIDE																
15007000		0.000	3.058	L	1	1 40	CRACKING	10.0	10.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	
595 A19					3	4.0	32000 RIDE	7.6	7.6	7.4	6.6	6.5	6.4	6.2	6.1	6.5	6.3	6.3	6.1	7.5		
W BAY DR(0.0L)						FC125R																
4168361		0.000	2.947	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	8.0	8.0	8.0	7.8	7.3	5.5*
R. E. PURCELL CONSTRUCTION(2013)						SPRIDE																
							RIDE	7.5	7.1	7.6	7.6	7.4	7.1	7.3	7.2	7.2	7.0	6.8	7.0	6.8	7.0	6.4
15009000		0.000	0.964	R	1	1 40	CRACKING	10.0	10.0	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586					1	8.1	14600 RIDE	6.7	6.3	6.5	6.3	6.1		7.3	8.0	8.0	7.5	7.8	7.7	7.4		
BAYSHORE BLVD(0.0C)						FC125																
2571381		0.000	0.993	C	2004	0221	CRACKING	8.5	8.5	8.5	8.5	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	4.4*	4.2*	1.5*	
R. E. PURCELL CONSTRUCTION(2007)						SPRIDE																
4480411		0.323	2.341	C	2026	0012		7.5	7.3	7.1	7.3	7.0	6.9	7.1	6.9	7.1	6.8	6.8	7.0	6.5	6.1	
15009000		0.964	2.325	R	1	1 45	CRACKING	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586					2	8.1	26500 RIDE	6.4*	6.4*	6.1*	6.9	7.1		7.5	7.7	7.6	7.6	7.5	7.4	7.3		
CARDINAL RD(1.1R)						FC125																
2568151		1.296	2.334	C	2004	0213	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	8.5	7.0	6.0*	6.0*	6.0*	5.9*	5.8*	3.5*	
R. E. PURCELL CONSTRUCTION(2007)						SPRIDE																
4480411		0.323	2.341	C	2026	0012		7.3	7.3	6.8	6.6	6.9	6.5	6.6	6.4	6.5	6.5	6.4	6.4	6.4	6.0	
15009000		2.325	2.840	R	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586					3	8.1	33500 RIDE	7.3	7.7	7.0	6.9	6.8	6.5	6.9	7.0	6.4	6.3	6.2	6.3	6.1		
SR 55(2.6C)						FC125																
							CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0
							RIDE	6.4	6.6	6.4	6.3	6.6	6.3	7.3	7.4	7.3	7.5	7.4	7.3	7.3	6.9	
15009000		2.840	4.298	R	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	
586					3	8.1	33500 RIDE	8.3	8.1	8.0	7.5	7.5	7.4	7.3	7.3	7.2	7.1	7.0	7.2	6.6		
LAKE SHORE LN(3.1R)						FC125M																
4416571		2.840	4.298	C	2022	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	8.5	7.0	6.0*	6.0*	6.0*	10.0	10.0	9.0	
PREFERRED MATERIALS, INC. (2025)						SPRIDE																
								6.8	6.5	7.1	7.2	7.1	6.9	7.1	6.9	6.9	6.8	6.6	8.3	8.3	7.9	
15009000		4.298	5.312	R	1	8 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5		
586					3	8.1	19900 RIDE	8.1	8.0	8.0	7.4	7.4	7.0	7.0	7.2	7.1	6.9	6.7	6.7	6.8		
CLEARWATER CITY LIMITS(4.4R)						FC3																
2568311		2.833	5.330	C	1999	0213	CRACKING	9.5	9.5	7.0	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	3.5*				
R E PURCELL (2001)						S RIDE																
								6.6	6.4	6.2	6.1	6.2	5.7	6.0	5.7	5.3*	5.4*	5.3*				
15009000		2.867	5.312	L	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	
586					3	8.1	33500 RIDE	8.6	8.5	8.4	7.8	7.8	7.5	7.5	7.7	7.3	7.0	7.0	6.9	6.6		
RODNEY CT(2.9L)						FC125M																
4416571		2.840	4.298	C	2022	0012	CRACKING	9.0	8.5	7.0	7.0	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	10.0	10.0	9.0	
PREFERRED MATERIALS, INC. (2025)						SPRIDE																
								6.7	6.3	6.9	7.3	7.3	7.1	7.2	7.3	7.1	7.0	7.0	8.3	8.3	7.9	
15009000		2.325	2.867	L	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586					2	8.1	33500 RIDE	7.2	7.2	7.2	6.8	7.0	6.7	6.6	6.9	6.8	6.8	6.8	6.6	6.4		
SR 55(2.6C)						FC125M																
							CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	10.0	10.0	10.0	10.0	10.0	10.0	8.9	9.5	8.0
							RIDE	6.2	5.1*	6.0	6.1	6.2	5.9	7.9	7.5	7.3	7.7	7.6	7.8	7.4	7.0	
15009000		0.964	2.325	L	1	1 45	CRACKING	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586					2	8.1	26500 RIDE	6.4*	6.4*	6.1*	6.9	7.1		7.2	7.4	7.4	7.4	7.3	7.3	7.2		
CHALLENGER DR(1.0L)						FC125																
2568151		1.296	2.334	C	2004	0213	CRACKING	10.0	10.0	10.0	8.5	8.5	7.5	7.5	6.0*	5.5*	5.5*	3.5*	3.5*	2.1*	0.0*	
R. E. PURCELL CONSTRUCTION(2007)						SPRIDE																
4480411		0.323	2.341	C	2026	0012		7.2	7.3	6.9	6.8	6.8	6.6	6.8	6.8	6.6	6.6	6.6	6.6	6.6	6.6	
15009000		0.000	0.964	L	1	2 40	CRACKING	10.0	10.0	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
586					2	8.1	14600 RIDE	6.7	6.3	6.5	6.3	6.1		7.7	7.0	7.6	7.5	7.8	7.7	7.4		
BAYSHORE BLVD(0.0C)						FC125																
2571381		0.000	0.993	C	2004	0221	CRACKING	8.5	8.5	8.5	8.5	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	4.8*	4.4*	2.0*	
R. E. PURCELL CONSTRUCTION(2007)						SPRIDE																
4480411		0.323	2.341	C	2026	0012		7.5	7.3	7.1	7.3	7.0	6.9	7.1	6.9	7.1	6.8	6.6	6.7	6.1	5.7	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	WKM-X-P	ASTYPE	=====														(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-P	ASTYPE	=====														
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-P	ASTYPE	=====														
15010000	13.479	17.066	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5
595 A19				3	8.5	36500	RIDE	8.0	8.0	7.9	7.3	7.2	7.2	7.1	7.2	6.9	6.6	6.8	6.7	6.6	
CR 296(13.5C)						FC125M															
4376241	13.479	16.930	C	2021	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	6.5	6.5	10.0	10.0	9.6	10.0	9.0
PREFERRED MATERIALS, INC. (2023)						SPRIDE	6.8	6.9	6.8	6.8	6.6	6.6	6.6	6.7	6.6	6.6	8.0	8.0	8.0	8.0	7.6
15010000	13.479	17.066	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0
595 A19				3	8.5	36500	RIDE	7.8	7.8	7.7	7.0	7.1	6.8	6.9	6.3	6.9	6.8	6.8	6.6	6.5	
CR 296(13.5C)						FC125M															
4376241	13.479	16.930	C	2021	0012	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	10.0	10.0	9.6	10.0	9.0
PREFERRED MATERIALS, INC. (2023)						SPRIDE	6.2	6.5	6.7	6.5	6.5	6.5	6.4	6.5	6.4	6.4	6.4	7.8	7.8	7.8	7.7
15010000	10.370	13.479	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5
595 A19				3	8.5	41500	RIDE	7.9	7.7	7.7	7.0	7.1	6.5	6.8	6.8	6.6	6.6	6.6	5.6	6.3	
53 AV N(10.4C)						FC95MR															
4364851	10.370	13.503	C	2020	0012	CRACKING	9.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.5	10.0	10.0	10.0	9.6	10.0	8.5
PREFERRED MATERIALS, INC. (2022)						SPRIDE	6.5	6.2	6.7	6.4	6.5	6.3	6.6	6.5	7.8	7.8	7.7	7.7	7.7	7.7	7.3
15010000	10.191	10.370	L	1	1	45	CRACKING	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	9.5	9.5	10.0	10.0	10.0
595 A19				3	8.5	38500	RIDE	7.7	7.7	7.6	6.7	6.7	6.4	6.3	7.8	7.8	6.6	6.6	7.4	7.0	
010052(10.2L)						FC125															
2571321	9.052	10.439	C	2006	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.6	7.0	4.5*
COME & GRAHAM, INC. (2008)						RIDE	7.0	7.2	7.1	7.1	7.3	6.9	6.9	6.8	6.8	6.8	6.7	6.6	6.8	6.4	
4492081	9.141	10.370	C	2029	0012																
15010000	9.162	9.810	L	1	1	45	CRACKING	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0
595 A19				3	8.5	45000	RIDE	7.7	7.7	7.6	6.7	6.7	6.4	6.3	7.8	7.8	7.4	7.4	7.4	7.1	7.6
FROM BAY PINES HOSP(9.6L)						FC125															
2571321	9.052	10.439	C	2006	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	7.5	7.5	7.0	6.0*	4.3*	2.0*
COME & GRAHAM, INC. (2008)						RIDE	7.7	7.5	6.9	7.0	7.1	7.0	7.0	7.0	6.7	7.0	6.9	6.9	6.8	6.7	6.3
4492081	9.141	10.370	C	2029	0012																
15010000	8.620	9.162	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	10.0	10.0	10.0	10.0	10.0
595 A19				3	8.5	45000	RIDE	7.6	7.4	7.6	7.1	7.1	6.7	6.9	6.9	7.5	7.4	7.4	7.4	7.4	7.4
HOOVER BLVD(9.1L)						FC125M															
						CRACKING	10.0	10.0	9.0	9.0	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	10.0	10.0	9.0
						RIDE	7.4	7.4	7.3	7.2	7.3	7.1	6.9	7.0	6.9	6.9	6.8	7.3	7.3	7.3	6.9
						(2025)															
15010000	7.944	8.620	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0	7.0
595 A19				3	8.5	45000	RIDE	7.6	7.4	7.6	7.1	7.1	6.7	6.9	6.9	7.5	6.8	6.7	6.3	6.5	
CR 1(8.0C)						FC95MR															
4326981	7.944	8.620	C	2017	0012	CRACKING	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	9.6	9.0	7.5
COASTAL BRIDGE COMPANY, L. (2020)						SPRIDE	6.7	6.3	6.2	5.8	5.9		7.4	7.2	7.2	7.3	7.3	7.3	7.0	7.2	6.8
15010000	4.638	7.944	L	1	4	45	CRACKING	0.0*	7.2	7.2	9.3	9.3	9.3	9.2	9.0	8.3	7.5	7.5	7.5	7.3	7.3
595 A19				2	8.4	34000	RIDE	6.3*	6.2*	6.3*	7.1	6.5	6.8	6.6	7.1	6.9	7.1	7.1	7.0	6.9	
TYRONE BLVD(4.6L)						CONC															
2571261	4.514	8.033	C	2002	0012	CRACKING	7.0	7.0	6.8	6.5	6.4*	6.3*	6.3*	6.1*	5.5*	5.3*	5.3*	5.9*	4.4*	3.5*	
GILBERT SOUTHERN CORP (2004)						RIDE	6.8	6.6	7.0	7.0	6.9	6.7	6.8	6.8	6.7	6.7	6.6	6.6	6.5	6.4	
4492071	4.638	7.944	C	2025	0227																
15010000	1.343	4.638	L	1	7	45	CRACKING	8.5	7.5	7.5	7.0	6.0*	6.0*	6.0*	6.0*	5.5*		10.0	10.0	10.0	10.0
595 A19				2	3.6	24000	RIDE	7.7	7.5	7.4	6.8	6.6	6.3	6.1	6.0	5.8		7.6	7.5	7.3	
21 ST N(1.4L)						FC125M															
4480361	2.520	4.610	L	2024	0012	CRACKING	10.0	10.0	8.5	8.5	8.5	6.0*	6.0*	6.0*	5.5*	5.5*	5.5*	5.6*	10.0	9.0	9.0
AJAX PAVING INDUSTRIES OF (2026)						SPRIDE	7.2	7.0	6.7	6.4	6.2	5.9	6.2	6.0	5.9	5.8	5.6	5.6	5.6	7.6	7.2
15010001	0.038	0.840	C	1	1		CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0								
595F				1	7.8	11500	RIDE	6.5	6.6	6.3*	7.7	7.1	7.3								
						CRACKING															
						RIDE															6.5
						(2004)															5.9*
15010002	0.000	0.573	C	1	1		CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0								
595F				1	7.8	11500	RIDE	6.9	7.0	6.6	7.6	7.2	7.5								
						CRACKING															
						RIDE															6.5
						(2004)															5.6*

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 ** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																							
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE			
SR US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	=====	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031		
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-M	P	ASTYPE																
ITMSEG-P	(AGE_ONE YEAR)							2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031		
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM-M	F																	
ITMSEG-F																							
15010003	0.000	0.724	C	1	1	35	CRACKING	10.0															
595F				1	7.8	11500	RIDE	6.9															
				(2001)			CRACKING														6.5	3.5*	
							RIDE														5.2*	4.8*	
15010004	0.000	1.652	C	1	1	35	CRACKING	6.5															
595F				1	7.8	11500	RIDE	4.8*															
							CRACKING														6.5		
							RIDE														5.2*		
15010053	0.000	0.487	C	1	1	35	CRACKING	9.0															
665				2	8.7	1700	RIDE	6.7															
				(2000)			CRACKING														3.5*	0.5*	
							RIDE														5.1*	4.7*	
4492081	0.000	0.487	C	2029		0012																	
15010101	0.000	0.924	C	1	1	35	CRACKING	6.5	6.5	6.5	6.5	5.5*	5.5*	3.5*	3.5*	10.0	10.0	8.5	8.5	8.5			
595 A19				2	5.4	9900	RIDE	5.6*	5.5	5.5	5.1*		3.8*	3.5*	3.8*	6.5	6.0	5.6	5.8	6.0			
FIFTH AVE N(0.0C)						FC125M																	
				(2021)			CRACKING	8.5	8.5	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	
							RIDE	6.3	5.8	5.9	5.9	5.3*	5.5	5.3*	6.9	7.0	7.0	7.1	7.1	6.8	6.4		
15010101	0.924	1.216	C	1	1	30	CRACKING	6.5	6.5	6.5	6.5	5.5*	5.5*	3.5*	3.5*	10.0	10.0	8.5	8.5	8.5			
595 A19				3	4.4	13000	RIDE	5.6*	5.5	5.5	5.1*		3.8*	3.5*	3.8*	6.5	6.0	5.6	5.8	6.0			
I 375(0.9L)						FC125M																	
4364871	0.930	1.216	C	2019		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	10.0	10.0	10.0	10.0	10.0	8.3	7.0		
PREFERRED MATERIALS, INC.				(2021)			SPRIDE	6.3	5.8											5.7	5.3*		
15010102	0.000	0.423	C	1	1	45	CRACKING								10.0	10.0	10.0	10.0	10.0	10.0			
595 A19				2	8.5	11500	RIDE								8.3	8.5	8.4	8.3	8.1	7.7			
TOM STUART CSWY(0.0L)						DGFC																	
				(2008)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	6.3*	4.0*		
							RIDE	7.9	8.2	7.6	7.7	7.6	7.6	7.8	7.6	7.7	7.4	7.2	7.4	7.5	7.1		
4492081	0.000	0.423	C	2029		0012																	
15020000	1.126	3.288	C	1	1	35	CRACKING	6.5	6.5	6.5	6.5			10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.0		
595 A19				2	10.0	13700	RIDE	5.6*	5.7	5.7	5.0*			6.2	6.0	6.3	6.2	6.2	6.2	5.9	5.9		
PLEASANT ST(1.1L)						FC125M																	
4376231	1.675	3.288	C	2020		0012	CRACKING	8.5	8.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.1	8.7	7.5		
AJAX PAVING INDUSTRIES OF				(2022)			SPRIDE	5.7	5.5	4.7*	4.6*	4.4*	4.3*	4.2*	4.0*	5.6	5.6	5.5	5.4*	5.3*	4.9*		
15020000	3.288	3.523	C	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	8.5			
595 A19				2	10.0	17100	RIDE	7.6	7.9	7.6	7.1	6.0	6.4	6.4	6.6	6.5	6.3	6.4	6.2	6.3			
MONROE ST(3.3C)						FC125M																	
4376231	3.288	3.462	C	2020		0012	CRACKING	8.5	8.5	7.0	6.5	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	9.1	10.0	8.5		
AJAX PAVING INDUSTRIES OF				(2022)			SPRIDE	6.6	6.5	6.0	6.3	5.6	5.9	5.9	5.9	6.0	5.9	6.1	5.9	5.8	5.4*		
15020000	3.523	5.902	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.5	6.5	6.5	10.0	10.0			
595 A19				1	10.0	17100	RIDE	7.1	7.4	6.9	7.0	6.5	6.2	6.1	6.2	5.9	6.1	5.6	7.9	7.9			
JACKSON ST(3.6C)						FC125R																	
2571311	3.523	4.863	C	2010		0226	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	7.8	8.0	6.0*		
AJAX PAVING INDUSTRIES OF				(2012)			SPRIDE	7.8	7.7	7.7	7.6	7.5	7.4	7.3	7.2	7.1	7.0	6.9	6.9	6.9	6.5		
15020000	5.902	7.242	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	7.0			
595 A19				1	10.0	17100	RIDE	7.9	7.9	7.8	7.5	7.7	7.1	7.1	7.0	7.3	7.5	7.5	7.2	7.9			
CR 712(5.9R)						FC125A																	
4306601	5.902	7.242	C	2015		0012	CRACKING	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.8	7.0		
PREFERRED MATERIALS, INC.				(2017)			RIDE	8.1	7.7	7.7	8.2	8.2	8.1	8.1	8.0	8.0	8.0	8.1	8.0	8.0	7.6		
15020000	7.242	10.672	R	1	8	35	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	4.5*	4.5*	4.5*	4.5*	10.0			
595 A19				1	8.6	19900	RIDE	7.7	7.7	7.5	7.0	6.7	6.7	6.5	5.8	6.1	6.2	5.9	6.0	7.6			
CR 752(7.4C)						FC125R																	
				(2013)			CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	7.0				
4480421	7.242	12.637	C	2024		0012	RIDE	7.5	7.4	7.3	7.3	7.2	7.1	7.1	7.0	7.0	7.0	6.9	6.9				

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 ** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN - 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-X-P	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW																		
ITMSEG-F	W_BMP	W_EMP	RW																		
15020000	10.672	12.637	R	1	1	45	CRACKING	6.5	6.5	6.5	6.5	6.5	4.5*			10.0	10.0	10.0	10.0	10.0	
595 A19			1	10.2		13300	RIDE	7.0	6.8	6.7	6.0*	5.9*	5.9			7.8	7.8	7.6	7.7	7.5	
PROGRESS CT(10.7R)																					
2570781	10.672	12.637	C	2006		0012	CRACKING	10.0	8.5	8.5	7.5	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*	3.8*	3.3*	1.0*
AJAX PAVING INDUSTRIES, IN(2009)							SPRIDE	7.5	7.5	7.2	7.1	7.1	7.0	7.0	6.9	6.8	6.7	6.8	6.8	6.5	6.1
4480421	7.242	12.637	C	2024		0012															
15020000	12.637	13.265	R	1	1	35	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.2		13300	RIDE	6.1*	6.0	5.8	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1	
E MORGAN ST(12.8R)																					
2571371	12.619	13.290	C	2006		0012	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.8	5.5*	3.0*
AJAX PAVING INDUSTRIES, IN(2009)							SPRIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	5.9	5.5
4480441	12.637	15.225	C	2029		0012															
15020000	13.265	14.079	C	1	1	30	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.0		16800	RIDE	6.1*	6.0	5.8	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1	
E ORANGE ST(13.3R)																					
2571371	13.290	13.745	C	2006		0012	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	5.6*	3.5*
AJAX PAVING INDUSTRIES, IN(2009)							SPRIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	5.5	5.1*
4480441	12.637	15.225	C	2029		0012															
15020000	14.079	14.407	R	1	1	45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.0		18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1	
ANCLOTE RD E(14.2R)																					
							CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.8	10.0	9.0
							RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	6.7	6.3
4480441	12.637	15.225	C	2029		0012															
15020000	14.407	14.546	R	1	1	45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.0		18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1	
DIXIE HWY(14.4R)																					
							CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.8	3.8*	1.5*
							RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	5.8	5.4*
4480441	12.637	15.225	C	2029		0012															
15020000	14.546	14.854	C	1	1	45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.0		18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1	
(2026)																					
							CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	8.6	7.5
							RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	7.7	7.3
4480441	12.637	15.225	C	2029		0012															
15020000	14.854	15.225	R	1	1	45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.0		18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.6	7.2	7.3	7.3	7.1	
PLAZA DR(14.9R)																					
							CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.8	7.0	4.5*
							RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	7.4	7.0
4480441	12.637	15.225	C	2029		0012															
15020000	14.854	15.225	L	1	1	45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.0		18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.4	7.2	7.3	7.3	7.1	
SORENO ST(15.0L)																					
							CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	7.0	4.5*
							RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	7.4	7.0
4480441	12.637	15.225	C	2029		0012															
15020000	14.407	14.546	L	1	1	45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.0		18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.4	7.2	7.3	7.3	7.1	
CR 429(14.4L)																					
							CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	5.0*	2.5*
							RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	6.2	5.8
4480441	12.637	15.225	C	2029		0012															
15020000	14.079	14.407	L	1	1	45	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.0		18200	RIDE	6.1*	6.0*	5.8*	5.3*	5.4*	5.1*	4.7*		7.4	7.2	7.3	7.3	7.1	
OSCAR HILL RD(14.1L)																					
							CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	10.0	9.0
							RIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	6.1	5.7
4480441	12.637	15.225	C	2029		0012															
15020000	12.637	13.265	L	1	1	35	CRACKING	6.5	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	9.0	
595 A19			1	10.2		13300	RIDE	6.1*	6.0	5.8	5.3*	5.4*	5.1*	4.7*		7.4	7.2	7.3	7.3	7.1	
APRICOT CT(12.7L)																					
2571371	12.619	13.290	C	2006		0012	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.6	4.9*	2.5*
AJAX PAVING INDUSTRIES, IN(2009)							SPRIDE	7.1	6.9	6.9	6.9	6.7	6.7	6.5	6.5	6.4	6.1	6.2	6.3	5.5	5.1*
4480441	12.637	15.225	C	2029		0012															

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE
SR	US	G_BMP	G_EMP	LN	*T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)
ITMSEG-P																					
ITMSEG-F																					
15020000	10.672	12.637	L	1	8 45	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	4.5*			10.0	10.0	10.0	10.0	10.0	
595 A19				1	10.2	13300	RIDE	7.0	6.8	6.7	6.0*	5.9*	5.9			7.7	7.8	7.6	7.7	7.5	
WAI LANI RD(10.8L)																					
						FC4															
2570781	10.672	12.637	C	2006	0012	CRACKING	10.0	8.5	8.5	7.5	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*	3.6*		
AJAX PAVING INDUSTRIES, IN(2009)						SPRIDE	7.5	7.5	7.2	7.1	7.1	7.0	7.0	7.0	6.9	6.8	6.7	6.6	6.5		
4480421	7.242	12.637	C	2024	0012																
15020000	7.242	10.672	L	1	8 35	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	4.5*	4.5*	4.5*	10.0	
595 A19				1	8.6	19900	RIDE	7.7	7.7	7.5	7.0	6.7	6.7	6.5	6.6	6.2	6.2	5.9	6.0	7.6	
PALM HARBOR PL(7.3L)																					
						FC125R															
						(2013)															
4480421	7.242	12.637	C	2024	0012																
15020000	5.902	7.242	L	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	7.0	
595 A19				1	10.0	17100	RIDE	7.9	7.9	7.8	7.5	7.7	7.1	7.1	7.0	7.3	7.5	7.5	7.2	7.9	
CAUSEWAY BLVD(5.9L)																					
						FC125A															
4306601	5.902	7.242	C	2015	0012	CRACKING	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	10.0	8.5
PREFERRED MATERIALS, INC. (2017)						RIDE	8.1	7.7	7.7	8.2	8.2	8.1	8.1	8.0	8.0	8.0	8.0	8.1	8.0	8.0	7.6
15020000	3.523	5.902	L	1	1 35	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	6.5	6.5	10.0	10.0		
595 A19				1	10.0	17100	RIDE	7.1	7.4	6.9	7.0	6.5	6.2	6.1	6.5	6.3	6.1	5.6	7.9	7.9	
JACKSON ST(3.6C)																					
						FC125R															
2571311	3.523	4.863	C	2010	0226	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	7.8	7.2	5.0*	
AJAX PAVING INDUSTRIES OF (2012)						SPRIDE	7.8	7.7	7.7	7.6	7.5	7.4	7.3	7.2	7.1	7.0	6.7	6.8	6.6		
15020100	0.000	0.123	C	1	1	CRACKING															
595F				1	3.0	1500	RIDE														
																					6.6
																					5.0*
15025000	0.000	1.347	C	1	1 35	CRACKING									10.0	10.0	10.0	10.0	10.0	10.0	
595 A19				4	7.3	13300	RIDE								6.8	6.7	6.9	6.8	6.3	6.4	
CHESTNUT ST(0.0C)																					
						FC125M															
4364881	0.007	0.697	C	2019	0012	CRACKING	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	8.8	8.2	7.0
HUBBARD CONSTRUCTION CO. (2021)						SPRIDE	6.5	6.3	5.9	5.5	5.9	5.5	5.5	5.5	6.4	6.5	6.3	6.3	6.2	6.4	6.0
15025000	1.347	1.592	C	1	1 35	CRACKING									10.0	10.0	10.0	10.0	10.0	10.0	
595 A19				3	3.9	11500	RIDE								6.0	6.6	5.6	5.8	5.8	6.0	
GRANT ST(1.3R)																					
						FC125M															
4364881	1.314	1.481	C	2019	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	9.6	10.0	8.5
HUBBARD CONSTRUCTION CO. (2021)						SPRIDE	6.0	5.9	4.4*	4.2*	4.3*	4.3*	4.2*	6.7	6.7	6.8	6.7	6.7	6.8	6.8	6.4
15030000	0.000	0.531	R	1	1 35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	7.5	7.5	7.5	
686				2	18.5	45500	RIDE	7.0	6.6	6.1	5.7	5.7	6.1	5.5	6.1	6.5	5.7	5.5	5.7	5.7	
A19/S595/SEMINOLE BL(0.0R)																					
						FC125M															
4309011	0.000	0.531	C	2015	0012	CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	5.5*
AJAX PAVING INDUSTRIES OF (2017)						RIDE	5.3*	5.5	5.7	7.4	7.3	7.3	7.2	7.4	7.3	7.2	7.0	7.3	6.9	6.5	
15030000	0.531	0.840	R	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	
686				3	18.5	45500	RIDE	7.0	6.6	7.8	7.6	7.6	7.4	7.0	7.3	7.3	7.4	7.2	7.0	7.0	
SE HIGHLAND AVE(0.8R)																					
						FC125M															
4309011	0.531	0.824	C	2015	0012	CRACKING	8.5	8.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.0	5.5*
AJAX PAVING INDUSTRIES OF (2017)						RIDE	6.9	6.8	6.8	8.1	8.1	7.7	7.9	7.9	7.9	7.9	7.9	7.4	7.8	7.7	7.3
15030000	0.840	2.400	R	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	
686				3	18.5	62500	RIDE	8.2	8.0	7.8	7.6	7.6	7.4	7.0	7.3	7.3	7.4	7.2	7.0	7.0	
COUNTRY CLUB DR(1.0R)																					
						FC3															
2568821	0.997	2.567	C	1994	0121	CRACKING	8.5	8.5	7.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.7	7.0	4.0*
J. W. CONNER & SONS, INC. (1998)						S RIDE	6.9	6.8	6.8	6.6	6.8	6.5	6.8	6.4	6.5	6.5	6.4	6.4	6.3	5.9	
4492051	0.845	2.362	C	2028	0012																
15030000	2.400	3.844	R	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	
686				3	4.6	62000	RIDE	8.5	8.3	8.3	7.4	7.5	7.1	7.1	7.7	7.5	7.5	7.2	7.3	7.2	
BELCHER RD(2.6R)																					
						FC3															
2568891	2.763	3.556	C	1995	0121	CRACKING	8.5	8.5	7.5	7.5	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*	4.9*	4.6*	1.5*
OVERSTREET PAVING ASPH PLA(1997)						S RIDE	7.3	7.0	7.0	6.9	7.0	6.7	6.8	6.9	6.7	6.9	6.7	6.6	6.8	6.4	
4479171	2.362	3.570	C	2025	0012																

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)		W_BMP W_EMP		RW FY-P		WKMX-P		=====													
CONTRACTOR (AGE_ONE YEAR)		W_BMP W_EMP		RW FY-F		WKMX-F															
15030000	3.844	5.457	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0
686			3	4.6	26910		RIDE	8.3	8.2	8.2	7.6	7.6	7.7	7.4	7.7	7.7	7.6	7.6	7.4	7.4	
MICHIGAN DR(3.9R)																					
2568911	3.780	5.247	C	1995	0121		CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.6	6.2*	3.0*
COUCH CONSTRUCTION LP				(1998)		S RIDE															
4402471	3.570	5.310	C	2028	0012																
15030000	5.457	6.557	R	1	1	50	CRACKING	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0
686			2	7.3	38500		RIDE	7.9	8.1	8.0	7.2	7.3	7.2	7.2	7.2	7.9	8.0	7.9	7.7	7.3	
46 ST N(5.8R)																					
							(2025)												10.0	10.0	9.0
							RIDE	7.1	7.0	7.2	6.8	6.5	6.4*						8.1	8.1	7.7
15030000	6.557	6.814	C	1	1	40	CRACKING	10.0	10.0	10.0	6.5	4.5*	7.0	7.0	4.5*	10.0	10.0	10.0	10.0	10.0	
686			2	6.8	11500		RIDE	7.9	8.1	8.0	7.4	7.4	7.2	7.2	6.9	7.9	8.0	8.0	7.8	7.9	
FC4																					
							(2025)												10.0	10.0	9.0
							RIDE	7.8	7.7	7.1			10.0	10.0					6.8	6.6	6.2
15030000	7.841	7.955	C	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	9.0	6.5	6.5	6.5	6.5	
686			2	6.8	11500		RIDE	8.4	8.3	8.5	7.6	8.1	7.7	7.7	7.9	7.9	7.7	7.7	7.5	7.4	
DGFC																					
							(2017)												6.5	6.5	6.5
							RIDE	7.6	7.1	7.4	7.7	7.8	7.9	7.5	7.8	7.7	7.0	6.8	6.9	7.2	6.8
15030000	7.955	8.418	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5	
686			3	18.5	40000		RIDE	8.4	8.3	8.2	7.6	7.7	7.7	7.6	7.9	7.9	7.8	7.8	7.6	7.6	
OGFC																					
							(2017)												6.5	4.5*	4.5*
							RIDE	7.6	7.1	7.4	7.8	7.8	7.9	7.5	7.8	7.7	8.0	8.3	8.2	8.0	4.5*
15030000	8.418	9.176	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5	
686			3	18.5	51500		RIDE	8.4	8.3	8.2	7.6	7.7	7.7	7.6	7.9	7.9	7.8	7.8	7.6	7.6	
FC5A																					
							(2018)												6.5	4.5*	4.5*
							RIDE	7.6	7.1	7.4	7.7	8.1	7.9	8.1	8.0	7.9	7.9	7.8	8.0	8.1	7.9
15030000	9.176	9.413	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5	
686			2	18.5	51500		RIDE	8.4	8.3	8.2	7.6	7.7	7.7	7.6	7.9	7.9	7.8	7.8	7.6	7.6	
FC5M																					
							(2026)												6.5	4.5*	4.5*
							RIDE	7.6	7.1	7.4	7.7	8.1	7.9	8.1	8.0	7.9	7.9	7.8	8.0	8.3	8.1
15030000	9.413	10.666	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5	
686			2	18.5	19100		RIDE	8.4	8.3	8.2	7.6	7.7	7.7	7.6	7.9	7.9	7.8	7.8	7.6	7.6	
FC5A																					
							(2018)												6.5	4.5*	4.5*
							RIDE	7.6	7.1	7.4	7.7	8.1	7.9	8.1	8.0	7.9	7.9	7.8	8.0	8.0	7.8
15030000	9.413	10.666	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	
686			2	18.5	19100		RIDE	8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4	
FC5A																					
							(2018)												6.5	4.5*	4.5*
							RIDE	7.3	7.1	7.7	7.7	8.2	8.2	8.2	8.1	8.1	7.9	7.8	8.1	7.9	7.7
15030000	9.176	9.413	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	
686			2	18.5	51500		RIDE	8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4	
FC5M																					
							(2026)												6.5	4.5*	4.5*
							RIDE	7.3	7.1	7.7	7.7	8.2	8.2	8.2	8.1	8.1	7.9	7.8	8.1	8.0	7.8
15030000	8.930	9.176	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	
686			2	18.5	51500		RIDE	8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4	
FC5A																					
							(2018)												6.5	4.5*	4.5*
							RIDE	7.3	7.1	7.7	7.7	8.2	8.2	8.2	8.1	8.1	7.9	7.8	8.1	8.6	8.4
4290601	8.963	9.245	C	2016	0012		CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.4	8.9	5.5*
PCS CIVIL LLC				(2018)		RIDE															

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	=====														
ITMSEG-P	(AGE_ONE YEAR)	W_EMP	RW	FY-F	WKM-X-F			2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR																					
ITMSEG-F																					
15030000	8.418	8.930	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	
686			3	18.5		51500	RIDE	8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4	
FROM LK CARILLON DR(8.5L) FC5A																					
4290601	8.640	8.963	L	2016		0012	CRACKING	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.4	8.6	5.5*
PCS CIVIL LLC				(2018)			RIDE	7.3	7.1	7.7	7.7	8.2	8.2	8.2	8.1	8.1	7.9	7.8	8.1	8.5	8.3
15030000	7.955	8.418	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	
686			2	18.5		40000	RIDE	8.5	8.6	8.5	8.0	8.1	8.0	7.7	7.7	7.5	7.7	7.7	7.5	7.4	
(2017) FC5A																					
							CRACKING	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.2	9.0	5.5*
							RIDE	7.3	7.1	7.7	7.7	7.7	7.7	7.6	7.8	7.6	7.8	7.8	7.8	7.7	7.5
15030000	5.667	6.557	L	1	1	50	CRACKING	10.0	9.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	
686			2	7.3		38500	RIDE	8.4	8.3	8.3	7.4	7.4	6.9	6.9	6.9	8.1	8.1	8.0	7.8	7.9	
FROM AIRPORT PKWY(5.8L) DGFC																					
							CRACKING	10.0	10.0	9.0	9.0	9.0	9.0						10.0	10.0	9.0
							RIDE	7.9	8.0	7.7	7.5	7.6	7.4						8.0	8.0	7.6
15030000	5.304	5.667	L	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.5	
686			3	7.3		38500	RIDE	8.3	8.2	8.0	7.5	7.6	7.5	7.3	7.5	7.5	7.4	7.4	7.2	7.1	
(2025) DGFC																					
							CRACKING	7.5	7.5	10.0	10.0	10.0	10.0						10.0	10.0	9.0
							RIDE	7.1	7.2	6.7	6.5	6.4*	6.2*						7.3	7.8	7.4
15030000	3.844	5.304	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.5	
686			3	4.6		26910	RIDE	8.3	8.2	8.0	7.5	7.6	7.5	7.3	7.5	7.5	7.4	7.4	7.2	7.1	
FAIRINGTON DR(3.9L) DGFC																					
2568911	3.780	5.247	C	1995		0121	CRACKING	7.5	7.5	7.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	6.0*	6.0*	5.4*	2.0*
COUCH CONSTRUCTION LP (1998) S RIDE																					
4402471	3.570	5.310	C	2028		0012		7.1	7.2	7.2	7.3	7.3	7.1	7.1	7.1	6.9	7.0	6.9	6.8	6.8	6.4
15030000	2.400	3.844	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	
686			3	4.6		62000	RIDE	7.8	7.8	7.6	7.0	6.7	6.8	6.7	7.1	6.9	6.9	6.9	6.6	6.5	
BEDFORD CIR W(2.9C) FC3																					
2568891	2.763	3.556	C	1995		0121	CRACKING	8.5	8.5	7.5	7.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*	5.4*	4.9*	1.5*
OVERSTREET PAVING ASPH PLA(1997) S RIDE																					
4479171	2.362	3.570	C	2025		0012		6.5	6.4	6.6	6.6	6.7	6.4	6.5	6.4	6.5	6.5	6.4	6.4	6.4	6.0
15030000	0.840	2.400	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	
686			3	18.5		62500	RIDE	7.9	8.0	7.7	7.5	7.4	7.3	7.0	7.0	7.3	6.9	7.0	6.8	6.7	
WERTZ DR(0.9L) FC3																					
2568921	0.997	2.567	C	1994		0121	CRACKING	9.0	9.0	8.5	8.5	8.5	8.5	8.0	7.0	7.0	7.0	7.0	6.6	6.5	3.5*
J. W. CONNER & SONS, INC. (1998) S RIDE																					
4492051	0.845	2.362	C	2028		0012		6.8	6.8	6.8	6.8	6.7	6.6	6.6	6.6	6.6	6.6	6.4	6.5	6.5	6.1
15030000	0.000	0.840	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.0	7.0	7.0	7.0	
686			3	18.5		45500	RIDE	7.5	7.1	7.0	6.6	6.3	6.0	5.9	6.0	5.8	5.8	5.9	5.7	5.4*	
A19S59S651/MISSOURI(0.0L) FC125M																					
4309011	0.000	0.531	C	2015		0012	CRACKING	6.5	6.5	6.0*	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	7.0	7.0	5.5*
AJAX PAVING INDUSTRIES OF (2017) RIDE																					
								5.2*	5.4*	5.5	7.4	7.4	7.2	7.2	7.2	7.1	7.1	7.0	6.9	7.3	6.9
15030018	0.000	0.583	C	1	1	40	CRACKING							10.0	10.0	10.0	8.5	8.5	8.5		
686			2	22.7		16500	RIDE							7.9	7.6	8.1	8.0	7.9	7.9		
15030055 NB OFF(0.0R) DGFC																					
							CRACKING	8.5		9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.3	7.7	6.0*
							RIDE	7.6		7.1	7.4	7.4	7.2	7.1	7.2	7.0	6.9	6.8	6.9	6.9	6.5
15030101	0.000	0.125	C	1	1	40	CRACKING							10.0	10.0	10.0	10.0	10.0	10.0		
686			3	18.5		9100	RIDE														
BON SECOURS ENTR(0.0L)																					
							CRACKING	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	10.0	8.7	8.2
							RIDE													5.7	5.3*
15030102	0.000	0.108	C	1	1	40	CRACKING							10.0	9.5	8.5	7.5	7.5	7.5		
686			2	18.5		10000	RIDE														
GANDY BLVD WB(0.0C) OGFC																					
							CRACKING	7.5	7.5	7.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.7	7.5	4.5*
							RIDE												7.6	7.4	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																								
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE				
SR	US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031			
INTERSECT	AT	(MP		SIDE)	SURFTYPE			=====																
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-X-P																			
CONTRACTOR	(AGE_ONE	YEAR)	ASTYPE																					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F																			
15035000	0.000	0.128	C	3	1	45	CRACKING																	
686A	0.0	0.1	2	4.0	15750		RIDE																	
							(2025)														10.0	10.0	9.0	
																					8.3	8.4	8.0	
15035000	0.555	0.706	C	3	1	45	CRACKING																	
686A	0.6	0.7	2	4.0	15750		RIDE																	
							(2025)															10.0	10.0	9.0
																					8.3	7.6	7.2	
15035000	0.706	2.593	R	3	1	45	CRACKING																	
686A	0.7	2.6	2	4.0	31500		RIDE																	
WB 118 AVE N(1.6C)							(2025)															10.0		
								CRACKING	10.0	10.0	10.0	10.0	7.5	7.5							10.0	10.0	9.0	
								RIDE	7.7	7.9	7.9	7.9	7.7	7.7							8.3	8.4	8.0	
15035000	2.859	3.021	R	3	1	55	CRACKING																	
686A	2.9	3.0	2	4.0	31500		RIDE							10.0	10.0	10.0	10.0	10.0	10.0	9.0	6.5			
							(2025)							CRACKING	6.5	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*
								RIDE	7.1	6.4*	7.0	6.8	7.5	7.3	7.6	7.5	6.9	6.7			10.0	10.0	9.0	
																					8.3	8.0	7.6	
15035000	3.021	3.309	R	3	1	55	CRACKING																	
686A	3.0	3.3	2	4.0	31500		RIDE																	
							(2026)															10.0	9.0	
																						8.1	7.7	
15035000	3.610	4.192	R	3	1	55	CRACKING																	
686A	3.6	4.2	2	4.0	15750		RIDE																	
							(2026)															10.0	9.0	
																						7.9	7.5	
15035000	3.607	4.192	L	3	1	55	CRACKING																	
686A	3.6	4.2	2	4.0	15750		RIDE																	
							(2026)															10.0	9.0	
																						8.3	7.9	
15035000	3.021	3.318	L	3	1	55	CRACKING																	
686A	3.0	3.3	2	4.0	31500		RIDE																	
							(2026)															10.0	9.0	
																						7.9	7.5	
15035000	2.929	3.021	L	3	1	55	CRACKING																	
686A	2.9	3.0	2	4.0	31500		RIDE																	
							(2025)															7.5	6.5	
																						7.8	7.6	
																						6.5	6.5	
																						4.5*	4.5*	
																						4.5*	4.5*	
																						10.0	10.0	
																						8.3	8.5	
																						10.0	10.0	
																						8.3	8.5	
																						8.3	8.3	
15035000	0.706	2.595	L	3	1	45	CRACKING																	
686A	0.7	2.6	2	4.0	31500		RIDE																	
WB 118 AVE N(1.6C)							(2025)															10.0		
																						7.9		
																						10.0	10.0	
																						8.3	8.5	
																						8.3	8.3	
15036001	0.000	0.467	C	1	1	35	CRACKING																	
689			2	8.7	1900		RIDE																	
CR 296(0.0C)							(2026)															8.5	7.5	
																						6.5	6.1	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2013	
INTERSECT AT (MP)	(SIDE)						SURFTYPE	=====														
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	P	ASTYPE															
CONTRACTOR	(AGE_ONE	YEAR)						2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F																
15036004	0.000	0.075	C	1	1		CRACKING															
692							RIDE															
43RD ST N(0.0C)																						
							CRACKING														10.0	
							RIDE														5.5*	
15040000	1.661	4.219	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*		
60				3	4.9	49500	RIDE	7.6	7.5	7.5	7.3	7.1	6.9	6.6	6.7	6.5	6.3	6.3	5.9	5.8		
S GLENWOOD AVE(1.7R)							FC125A															
4325861	1.789	4.219	C	2016		0012	CRACKING	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.6	7.0	
PREFERRED MATERIALS, INC.				(2019)			SPRIDE	5.6	5.3*	5.9	5.8		7.5	7.4	7.3	7.2	7.2	7.1	7.1	6.9	6.5	
15040000	4.219	4.713	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*		
60				3	6.7	55000	RIDE	7.6	7.5	7.5	7.3	7.1	6.9	6.6	6.7	6.5	6.3	6.3	5.9	5.8		
BYPASS DR(4.3R)							FC3															
							CRACKING	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.7	6.6	5.0*	
							RIDE	5.6	5.3*											5.4*	5.0*	
4479181	4.219	6.410	C	2028		0012																
15040000	4.713	6.376	R	1	2	45	CRACKING	10.0	8.5	8.5	7.0	7.0	6.0*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	
60				3	6.7	55000	RIDE	8.0	7.9	7.5	6.4*	6.5	6.2	6.1	5.5	8.1	7.5	7.6	7.4	7.2		
SKY HARBOR DR(4.8R)							FC95M															
4037331	4.680	5.950	C	2007		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	7.0	5.0*	4.7*	2.5*	
AJAX PAVING INDUSTRIES, IN				(2009)			SPRIDE	7.3	7.1	7.3	7.3	7.2	7.1	7.0	7.0	6.9	6.9	6.8	6.8	6.6	6.2	
4479181	4.219	6.410	C	2028		0012																
15040000	6.376	9.443	R	1	1	60	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	6.5	6.5	6.0*		
60				2	6.5	65000	RIDE	8.8	8.7	8.6	7.8	7.9	7.5	8.0	8.0	7.9	7.9	7.9	7.7	7.7	7.7	
							FC5A															
4289621	6.376	9.443	C	2014		0012	CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.4	8.3	4.5*	
PCS CIVIL LLC				(2016)			SPRIDE	7.4		8.5	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.3	8.1	
15040000	6.376	9.443	L	1	1	60	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.5	6.0*	6.0*	6.0*	6.0*		
60				2	6.5	65000	RIDE	8.9	8.8	8.5	7.9	7.9	7.4	8.1	8.1	8.1	8.1	7.9	7.9	7.5		
SERVICE RD(8.1L)							FC5A															
4289621	6.376	9.443	C	2014		0012	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	8.2	4.5*	
PCS CIVIL LLC				(2016)			SPRIDE	7.8	7.6	8.3	8.3	8.3	8.2	8.3	8.3	8.3	8.3	8.3	8.3	8.2	8.0	
15040000	4.680	6.376	L	1	1	45	CRACKING	10.0	8.5	8.5	7.0	6.5	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	
60				3	6.7	55000	RIDE	6.8	6.8	6.4*	6.1*	5.8*	5.6	5.0*	4.2*	7.4	7.6	8.3	7.8	7.9		
FROM PARK PL(4.7L)							FC95M															
4037331	4.680	5.950	C	2007		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.3	6.7	4.5*	
AJAX PAVING INDUSTRIES, IN				(2009)			SPRIDE	7.3	6.6	7.2	7.1	7.0	7.0	7.0	6.9	6.7	6.6	6.6	6.6	6.5	6.1	
4479181	4.219	6.410	C	2028		0012																
15040000	4.219	4.680	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*			
60				3	6.7	55000	RIDE	7.9	7.5	7.7	7.6	7.4	6.8	7.0	7.2	7.1	6.7	6.5	6.2	6.2		
BENNIGAN'S L(4.6L)							FC3															
							CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	6.3*	5.6*	4.0*	
							RIDE	6.3	6.1	6.1	7.1	6.9	6.7	6.9	6.8	6.7	6.3	6.0	6.2	6.3	5.9	
4479181	4.219	6.410	C	2028		0012																
15040000	1.661	4.219	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*		
60				3	4.9	49500	RIDE	7.9	7.5	7.7	7.6	7.4	6.8	7.0	7.2	7.1	6.7	6.5	6.2	6.2		
GLENWOOD AVE S(1.7L)							FC125A															
4325861	1.789	4.219	C	2016		0012	CRACKING	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.8	7.0	
PREFERRED MATERIALS, INC.				(2019)			SPRIDE	6.3	6.1	6.1	6.3		7.5	7.4	7.4	7.3	7.1	7.1	7.1	7.3	6.9	
15045000	0.000	0.167	R	1	7	45	CRACKING							10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
60				2	4.9	36500	RIDE							7.8	7.9	8.2	8.1	8.2	7.9	8.0		
CSWY PARKING ENTR(0.0R)							FC125H															
4416511	0.000	0.167	C	2024		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	5.8*	10.0	9.0	
PREFERRED MATERIALS, INC.				(2026)			SPRIDE	8.2	8.1	7.6	7.6	6.9	7.3	7.1	7.3	7.3	7.0	6.9	6.9	8.5	8.1	
15045000	0.606	0.904	C	1	2	35	CRACKING							10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
60				2	7.3	21500	RIDE							7.1	6.9	7.3	7.4	7.2	7.1	6.8		
BRIDGE #244(0.6L)							FC125A															
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	
							RIDE	7.1	6.6	5.9	6.5	5.9	6.3	6.3	6.6	6.8	6.2	6.0	6.1	6.6	6.2	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)								=====													
ITMSEG-P W_BMP W_EMP RW FY-P WKMX-P																					
CONTRACTOR (AGE_ONE YEAR) ASTYPE																					
ITMSEG-F W_BMP W_EMP RW FY-F WKMX-F																					
15045000	0.904	1.400	C	1	1	35	CRACKING							10.0	10.0	8.5	8.5	7.0	7.5	7.5	
60	A19			4	7.3	21500	RIDE							5.0*	4.8*	4.5*	4.5*	4.3*	4.5*	4.2*	
FT HARRISON AVE S(0.9C)																					
4290561	0.943	1.285	C	2015		0012	CRACKING	5.5*	5.5*	4.0*	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.7	7.5	6.0*
AJAX PAVING INDUSTRIES OF (2017)																					
							SPRIDE	3.7*	3.3*	2.9*										4.6*	4.2*
15045000	1.400	1.697	R	1	1	35	CRACKING							10.0	10.0	10.0	10.0	8.5	8.5	7.5	
60	A19			2	5.7	32000	RIDE							7.3	7.3	7.7	7.8	7.7	7.6	7.3	
M L KING AVE(1.4C)																					
4290561	1.402	1.697	C	2015		0012	CRACKING	5.5*	5.5*	4.0*	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	8.2	8.0	6.5
AJAX PAVING INDUSTRIES OF (2017)																					
							SPRIDE	7.6	7.6	7.3	7.3	7.0	6.7	7.1	7.0	7.1	6.9	7.0	6.8	7.1	6.7
15045000	1.400	1.697	L	1	1	35	CRACKING							10.0	10.0	8.5	8.5	8.5	8.5	7.5	
60	A19			2	5.7	32000	RIDE							7.1	6.6	6.6	6.7	6.6	6.5	6.9	
COURT ST(1.4L)																					
4290561	1.402	1.697	C	2015		0012	CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.8	6.0*
AJAX PAVING INDUSTRIES OF (2017)																					
							SPRIDE	7.1	7.1	6.5	6.9	6.3	6.5	6.6	6.6	6.7	6.5	6.6	6.7	6.3	5.9
15045000	0.000	0.167	L	1	7	45	CRACKING							10.0	10.0	10.0	10.0	10.0	10.0	10.0	
60				2	4.9	36500	RIDE							6.3	7.6	7.8	7.8	7.8	7.8	7.7	
CSWY PARKING ENTR(0.0C)																					
4416511	0.000	0.167	C	2024		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	6.8	10.0	9.0
PREFERRED MATERIALS, INC. (2026)																					
							SPRIDE	7.8	7.8	7.2	7.2	6.5	6.8	7.0	6.9	6.7				8.1	7.7
15045101	0.000	0.764	C	1	1	30	CRACKING							10.0	10.0	8.5	8.5	8.5	8.0	8.0	
60	A19			4	7.3	15500	RIDE							5.4*	5.3*	5.2*	5.3*	4.8*	5.5	5.4*	
CHESTNUT ST(0.0C)																					
							CRACKING	5.5*	5.5*	4.0*	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.1	7.6	6.0*
							RIDE	5.7	5.1*	4.2*										4.9*	4.5*
15050002	0.000	1.133	R	1	7	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	
580				2	7.2	19900	RIDE	8.4	8.4	8.3	7.9	7.8	7.7	7.5	7.7	7.7	7.6	7.6	7.6	7.4	
ST PETERSBURG DR(0.0R)																					
4402481	0.000	0.723	R	2023		0012	CRACKING	9.5	8.5	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*	5.5*		10.0	9.0
PREFERRED MATERIALS, INC. (2026)																					
							SPRIDE	7.1	7.4	7.0	6.8	6.8	6.8	6.7	6.6	6.7	6.7	6.6		8.3	7.9
15050002	0.000	1.133	L	1	7	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5	
580				2	7.2	19900	RIDE	8.1	8.1	8.1	8.0	7.5	7.3	7.5	7.3	7.3	7.1	7.0	7.2	6.9	
FOREST LAKES BLVD(0.0L)																					
4402481	0.000	0.723	L	2023		0012	CRACKING	7.0	7.0	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.0*		10.0	9.0
PREFERRED MATERIALS, INC. (2026)																					
							SPRIDE	6.6	6.7	6.4	6.3	6.3	6.3	6.1	6.1	6.1	5.9	6.0		8.1	7.7
15050003	0.247	2.890	C	1	1	40	CRACKING														
590				4	9.1	27000	RIDE														
VINE AVE(0.3L)																					
							CRACKING									7.0	7.0	7.0	6.0*	5.6*	
							RIDE									5.7	5.7	5.5	5.7	5.7	
15050004	0.000	0.184	C	1	1	40	CRACKING														
590				2	18.5	11000	RIDE														
DREW ST(0.0R)																					
							CRACKING									5.5*	5.5*	3.0*	3.5*	3.3*	
							RIDE									5.3*	4.9*	4.6*	4.7*	4.4*	
15050004	0.184	1.059	C	1	1	45	CRACKING														
590				2	18.5	11000	RIDE														
MARILYN ST(0.4L)																					
							CRACKING									8.5	8.5	8.5	8.6	8.1	7.0
							RIDE									6.9	6.8	6.8	6.8	7.0	6.6
15050004	1.059	1.747	R	1	1	45	CRACKING														
590				2	18.5	11000	RIDE														
OLD COACHMAN RD(1.1C)																					
							CRACKING									8.5	8.5	8.5	8.6	8.5	7.0
							RIDE									6.9	6.8	6.8	6.8	6.3	5.9

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																							
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE			
SR US	G_BMP	G_EMP	LN	*T	ADT	RATINGS		2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013			
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-M	ASTYPE	=====																
ITMSEG-P	(AGE_ONE YEAR)							2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	(PMRS)	
ITMSEG-F																							
15050005	0.000	0.991	C	1	1	45	CRACKING																
590			2	18.5		14500	RIDE																
COACHMAN PLAZA DR(0.1L)							DGFC																
							CRACKING																
							RIDE									5.5*	8.0	8.0	7.0	6.7			
																6.5	7.2	7.1	7.1	6.9			
15050005	0.991	2.410	C	1	1	35	CRACKING																
590			2	18.5		6400	RIDE																
LAWRENCE DR(1.0L)							FC125H																
4416561	1.252	2.410	C	2023		0012	CRACKING																
HUBBARD CONSTRUCTION COMPA(2025)																							
							RIDE									5.5*	5.5*	3.5*	10.0	10.0	9.0		
																6.5	6.0	5.8	6.4	6.5	6.1		
15050005	4.629	5.978	C	1	1	40	CRACKING																
590			2	18.5		10000	RIDE																
PHILIPPE PARK ENTR(4.7R)							FC95																
							CRACKING																
							RIDE									7.0	7.0	7.0	6.8	6.4*			
4492091	4.629	5.978	C	2029		0012										7.3	7.3	6.9	7.2	7.0			
15061000	0.000	0.165	R	1	1	40	CRACKING									10.0	10.0	10.0	10.0	10.0	10.0		
694			2	4.8		59500	RIDE									6.8	7.2	7.1	7.0	7.1	7.0		
PINELLAS PARK CITY LIMIT(0.0C)							FC125M																
4416501	0.000	0.177	C	2023		0012	CRACKING	9.0	9.0	9.0	8.0	7.5	6.0*	6.0*	6.0*	3.5*	3.5*	3.5*	10.0	10.0	9.0		
AJAX PAVING INDUSTRIES OF (2025)							SPRIDE	7.0	6.7	6.5	6.3	6.5	6.1	6.2	6.0	6.2	6.0	6.2	5.8	5.7	8.0	8.1	7.7
15061000	0.165	2.693	R	1	1	45	CRACKING									8.5	6.5	6.5	6.5	6.5	6.5		
694			3	4.8		47500	RIDE									6.0	4.9*	5.6	5.6	5.5	5.3*		
43 ST(0.4C)							FC125A																
4290571	0.200	2.693	C	2014		0012	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.1	7.7	6.0*		
PREFERRED MATERIALS, INC. (2016)							SPRIDE	5.3*	5.1*		7.0	6.8	6.6	6.7	6.7	6.6	6.5	6.6	6.3	6.5	6.1		
15061000	2.693	5.130	R	1	1	45	CRACKING									10.0	9.0	9.0	7.5	7.5	7.0		
693			3	4.5		38000	RIDE									6.4	6.2	6.5	6.4	6.3	6.2		
76 AVE(2.8R)							FC125A																
4290581	3.705	6.314	C	2015		0012	CRACKING	7.0	7.0		10.0	10.0	10.0	8.5	7.5	7.0	7.0	7.0	6.0*	6.0*	4.5*		
PREFERRED MATERIALS, INC. (2017)							SPRIDE	6.2	6.0		8.1	8.1	7.9	8.0	7.9	7.3	7.2	6.9	6.9	7.0	6.6		
4492101	2.693	5.130	C	2029		0012																	
15061000	5.130	6.314	R	1	1	45	CRACKING									8.5	8.5	8.5	8.5	8.5	8.5		
693			3	6.5		39000	RIDE									7.4	7.6	7.4	7.4	7.4	7.3		
116 AVE(5.3R)							FC5A																
							CRACKING	8.5	8.5		10.0	10.0	10.0	8.5	7.5	10.0	10.0	10.0	10.0	8.6	8.1	6.0*	
							RIDE	7.0	7.2		8.1	8.1	7.9	8.0	7.9	8.3	8.3	8.3	8.3	8.3	8.1	8.1	
15061000	6.314	6.607	R	1	1	45	CRACKING																
693			3	15.9		35000	RIDE																
LARGO CITY LIMITS(6.4C)							FC125H																
4402451	6.314	6.556	C	2020		0012	CRACKING	7.0	7.0	6.5	6.5	3.5*	0.0*	0.0*	0.0*	10.0	10.0	10.0	8.8	10.0	8.5		
AJAX PAVING INDUSTRIES OF (2022)							SPRIDE	7.4	6.8	6.4	5.5	5.2*	4.7*	4.5*	4.1*	6.5	6.6	6.2	6.4	6.4	6.0		
15061000	6.607	6.946	R	1	1	45	CRACKING																
693			3	15.9		35000	RIDE																
138 AVE(6.7R)							FC5A																
4290581	6.618	6.946	C	2015		0012	CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	5.5*	
PREFERRED MATERIALS, INC. (2017)							SPRIDE	7.4	6.8	6.4	8.4	8.3	8.2	8.4	8.1	8.1	8.0	8.2	8.0	8.1	8.1	7.9	
15061000	6.946	7.160	C	1	1	45	CRACKING																
693			2	15.9		17000	RIDE																
CR 376(6.9C)							FC4																
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.2	8.5	6.0*		
							RIDE														6.4	6.0	
15061000	6.607	6.946	L	1	1	45	CRACKING																
693			2	15.9		35000	RIDE																
							FC5A																
4290581	6.618	6.946	C	2015		0012	CRACKING	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.6	5.0*		
PREFERRED MATERIALS, INC. (2017)							SPRIDE	7.2	6.8	6.9	8.1	8.3	8.1	8.3	8.3	8.5	8.6	8.6	8.5	8.5	7.9	7.7	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR US	G_BMP	G_EMP	LN	*T	ADT	RATINGS		2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-X-P	ASTYPE	*****															(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F																	
ITMSEG-P																						
ITMSEG-F																						
15061000	6.314	6.607	L	1	1	45	CRACKING										7.5	6.5	6.5	6.5		
693				3	15.9		35000 RIDE										7.1	7.2	7.3	7.2		
LARGO CITY LIMITS(6.4C)																						
4402451	6.314	6.556	C	2020		0012	CRACKING	4.5*	3.5*	3.5*	4.5*	3.5*	3.5*	3.5*	0.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.5
AJAX PAVING INDUSTRIES OF				(2022)			SPRIDE	7.2	6.8	6.9	5.2*	4.9*	4.3*	4.0*	3.4*	6.2	6.1	5.9	5.7	6.1	5.7	
15061000	5.130	6.314	L	1	1	45	CRACKING								8.5	8.5	8.5	7.5	7.5	7.5		
693				3	6.5		39000 RIDE								7.4	7.6	7.4	7.4	7.2	7.0		
114 AVE(5.2L)																						
4290581	3.705	6.314	C	2015		0012	CRACKING	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	5.5*
PREFERRED MATERIALS, INC.				(2017)			SPRIDE	7.0	7.0		8.3	8.3	8.1	8.2	8.1	8.5	8.4	8.4	8.4	8.5	8.3	
15061000	2.693	5.130	L	1	1	45	CRACKING								10.0	9.0	9.0	9.0	7.5	7.5		
693				3	4.5		38000 RIDE								6.8	6.8	6.3	6.2	6.1	6.0		
78 AVE N(2.9C)																						
4290581	3.705	6.314	C	2015		0012	CRACKING	7.0	7.0		10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.5	7.2	7.0	5.5*	
PREFERRED MATERIALS, INC.				(2017)			SPRIDE	5.9	5.8		8.3	8.3	8.1	8.2	8.1	7.6	7.5	7.5	7.4	7.4	7.0	
4492101	2.693	5.130	C	2029		0012																
15061000	0.165	2.693	L	1	1	45	CRACKING								8.5	6.0*	6.0*	6.0*	7.0	7.0		
694				3	4.8		47500 RIDE								6.0	5.6	5.8	5.8	5.6	5.5		
43 ST(0.4C)																						
4290571	0.200	2.693	C	2014		0012	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	7.8	7.2	5.5*	
PREFERRED MATERIALS, INC.				(2016)			SPRIDE	5.4*			7.1	7.0	6.8	6.9	6.8	6.6	6.6	6.4	6.6	6.6		
15061000	0.000	0.165	L	1	1	40	CRACKING								10.0	10.0	10.0	10.0	9.0	9.0		
694				2	4.8		59500 RIDE								7.3	7.3	6.6	7.1	7.1	6.8		
PINELLAS PARK CITY LIMIT(0.0C)																						
4416501	0.000	0.177	C	2023		0012	CRACKING	9.0	9.0	9.0	9.0	7.5	7.0	6.0*	6.0*	3.5*	3.5*	3.0*	10.0	9.5	8.5	
AJAX PAVING INDUSTRIES OF				(2025)			SPRIDE	7.0	6.9	7.1	7.3	7.1	6.8	7.1	6.8	7.1	6.7	7.1	7.8	7.6	7.2	
15061101	0.000	0.187	C	1	1	45	CRACKING									10.0	10.0	10.0	10.0	10.0		
693				2	7.3		900 RIDE															
MISSING DESCRIPTION I(0.0L)																						
				(2018)			CRACKING RIDE	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.7	9.2	7.5
																				8.1	7.7	
15070000	0.602	1.200	R	1	1	40	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	
580				2	4.9		17100 RIDE	7.0	6.8	6.6	6.5	6.3	6.4	6.2	6.5	6.5	6.6	6.6	6.4	6.5		
NEW YORK AVE(0.8R)																						
4326991	0.602	1.275	C	2017		0012	CRACKING	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5
HUBBARD CONSTRUCTION COMPA				(2018)			RIDE	6.4	6.4	5.6	5.9	7.3	7.2	7.2	7.3	7.2	7.0	7.0	7.0	7.0	6.7	6.3
15070000	1.200	2.319	R	1	1	45	CRACKING	10.0	10.0	10.0	8.5	7.0	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	
580				3	3.9		47000 RIDE	7.7	7.6	7.4	7.0	6.8	6.7	5.9	6.5	6.2	6.5	6.5	6.1	7.9	8.0	
CROSLY DR(1.3R)																						
4168471	1.414	2.319	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	7.0	7.0	6.0*	4.5*	2.5*	
PREFERRED MATERIALS, INC.				(2012)			RIDE	7.9	7.9	7.7	7.7	7.8	7.8	7.6	7.6	7.5	7.5	7.4	7.4	7.2	6.8	
4512371	1.267	3.141	C	2029		0012																
15070000	2.319	3.202	R	1	1	45	CRACKING	10.0	8.5	7.0	7.0	7.0	7.0	6.5	10.0	10.0	9.0	9.0	10.0	10.0		
580				3	3.9		47000 RIDE	8.1	8.0	7.9	7.3	7.2	6.8	6.8	7.3	7.2	7.1	7.1	8.0	8.2		
CREEK PARK CT(2.3R)																						
4113271	2.319	3.202	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.0	7.0	7.0	7.0	6.5	5.5*	3.5*	
PREFERRED MATERIALS, INC.				(2012)			RIDE	8.2	8.1	7.9	7.8	7.8	7.8	7.8	7.7	7.6	7.4	7.3	7.4	7.2	6.8	
4512371	1.267	3.141	C	2029		0012																
15070000	3.202	4.115	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.5	6.5	6.5	6.5	6.5		
580				3	3.9		38000 RIDE	7.1	7.0	6.8	6.6	6.4*	6.3	6.2	6.6	6.7	6.7	6.1	5.9	5.9		
DUNEDIN CITY LIMITS(3.3C)																						
4271631	3.179	4.175	C	2013		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	8.6	8.5	6.5	
PREFERRED MATERIALS, INC.				(2014)			RIDE	7.8	7.7	7.4	7.4	7.4	7.3	7.3	7.2	7.1	7.3	7.3	7.2	7.3	6.9	
15070000	4.115	5.733	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
580				3	11.1		32500 RIDE	7.9	8.4	8.3	7.5	7.8	7.7	7.2	7.4	7.3	6.8	7.1	7.1	7.3		
COUNTRYSIDE BLVD(4.1C)																						
4497811	4.149	4.954	R	2022		0226	CRACKING	9.0	9.0	9.0	9.0	8.0	7.0	7.0	7.0	7.0	6.0*	10.0	10.0	9.5	8.5	
AJAX PAVING INDUSTRIES OF				(2024)			RIDE	7.4	7.2	7.2	7.4	7.1	7.1	7.2	7.2	7.2	7.2	8.1	8.1	8.1	7.7	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	
INTERSECT	AT	(MP	SIDE)				*****														
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	P		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR	(AGE_ONE	YEAR)		ASTYPE																	(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	X-F															
15070000	5.733	6.370	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5
580				2	15.8		RIDE	8.0	8.1	8.0	7.6	7.8	7.6	6.9	7.1	7.1	7.0	7.1	6.8	6.7	
BAY HILLS BLVD N(5.8R) FC125M																					
4289351	5.970	6.852	C	2014	0012		CRACKING	8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	9.1	7.0
PREFERRED MATERIALS, INC. (2015) RIDE 6.7 8.4 8.0 7.9 8.0 8.1 8.1 7.9 8.1 8.0 7.8 7.9 8.0 7.8 7.9 8.0 7.6																					
15070000	6.774	7.370	R	1	7	45	CRACKING														
580				2	3.9		RIDE														
SHORE BLVD(6.9R) FC125M																					
4402481	6.764	7.370	C	2023	0012		CRACKING									6.0*	6.0*	6.0*		10.0	9.0
PREFERRED MATERIALS, INC. (2026) SPRIDE 5.9 5.7 5.7 8.4 8.0																					
15070000	6.774	7.370	L	1	7	45	CRACKING														
580				2	3.9		RIDE														
PALM KEY AVE(6.9L) FC125M																					
4402481	6.764	7.370	C	2023	0012		CRACKING									6.0*	6.0*	6.0*		10.0	9.0
PREFERRED MATERIALS, INC. (2026) SPRIDE 6.2 5.9 5.7 8.1 7.7																					
15070000	5.733	6.370	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	6.0*	6.0*	6.0*
580				2	15.8		RIDE	8.1	8.2	7.9	7.6	7.5	7.5	7.4	7.3	7.1	7.0	6.9	6.7	6.7	6.2
COUNTRY VILLAS DR(5.9L) FC125M																					
4289351	5.970	6.852	C	2014	0012		CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.8	8.7	7.0
PREFERRED MATERIALS, INC. (2015) RIDE 6.1 8.4 8.0 8.0 8.0 7.9 8.0 8.0 7.9 8.0 8.0 7.9 7.9 7.8 7.7 7.6 7.2																					
15070000	4.115	5.733	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5
580				3	11.1		RIDE	7.7	7.9	8.2	7.7	7.3	7.4	7.0	7.2	7.1	6.9	6.7	6.6	6.6	6.8
COUNTRYSIDE BLVD(4.1C) DGFC																					
4497811	4.149	4.954	L	2022	0226		CRACKING	8.5	8.5	7.5	7.5	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	9.6	8.5
AJAX PAVING INDUSTRIES OF (2024) RIDE 6.6 6.7 6.9 6.9 6.8 6.6 6.7 6.7 6.5 6.5 8.0 8.0 8.1 7.7																					
15070000	3.202	4.115	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	6.5	6.5	6.5	6.5	6.5
580				3	3.9		RIDE	7.6	7.6	7.4	6.8	6.8	6.7	6.6	6.6	6.8	6.8	6.5	6.5	6.3	
FR 15150400 FRNT SB(3.3L) FC125R																					
4271631	3.179	4.175	C	2013	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.9	8.7	7.0
PREFERRED MATERIALS, INC. (2014) RIDE 7.7 7.6 7.4 7.2 7.2 7.2 7.2 7.3 7.1 7.1 6.9 7.0 7.1 6.7																					
15070000	2.319	3.202	L	1	1	45	CRACKING	10.0	8.5	8.5	8.5	8.5	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
580				3	3.9		RIDE	7.2	7.3	7.1	5.1*	6.6	6.4	6.2	7.3	6.6	7.3	7.2	8.2	8.1	
KING ARTHUR CT(2.5L) FC125R																					
4113271	2.319	3.202	C	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	7.0	7.0	6.5	5.5*	3.5*
PREFERRED MATERIALS, INC. (2012) RIDE 8.0 8.1 7.9 7.7 7.7 7.6 7.6 7.6 7.4 7.3 7.3 7.2 7.2 7.2 7.2 7.2 7.2 7.2 7.2 7.2 6.8																					
4512371	1.267	3.141	C	2029	0012																
15070000	1.200	2.319	L	1	1	45	CRACKING	10.0	8.5	7.0	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	4.5*	10.0	10.0	
580				3	3.9		RIDE	7.8	7.5	7.6	6.6	7.0	6.4	6.2	6.4	6.5	6.4	6.5	7.4	7.1	
LADY MARION LN(1.2L) FC125R																					
4168471	1.414	2.319	C	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.0	6.5	5.5*	3.5*
PREFERRED MATERIALS, INC. (2012) RIDE 7.0 6.7 7.5 7.3 7.4 7.2 7.1 7.3 7.1 7.0 6.9 6.9 6.6 6.2																					
4512371	1.267	3.141	C	2029	0012																
15070000	0.602	1.200	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0
580				2	4.9		RIDE	7.5	7.7	7.6	7.0	7.0	6.7	6.5	6.2	6.6	7.0	6.3	5.9	5.6	
BASS BLVD(0.6L) FC125M																					
4326991	0.602	1.275	C	2017	0012		CRACKING	7.0	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0
HUBBARD CONSTRUCTION COMPA(2019) RIDE 6.4 6.3 6.6 6.5 7.6 7.5 7.2 7.4 7.3 7.3 7.3 7.0 6.6 6.2																					
15070001	0.000	0.479	R	1	8	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	7.0	7.0
580				2	4.9		RIDE	7.5	7.2	7.1	6.2	6.8	7.1	6.0	6.7	7.3	7.2	6.9	7.0	6.9	
BROADWAY ST(0.0C) FC125M																					
4326991	0.079	0.479	C	2017	0012		CRACKING	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5		
HUBBARD CONSTRUCTION COMPA(2018) RIDE 6.4 6.7 6.6 6.0 7.8 7.4 7.3 7.3 7.1 7.0 7.1 7.0 7.1 7.0																					
15070001	0.000	0.479	L	1	2	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.0	7.0	7.0	7.0
580				2	4.9		RIDE	7.6	7.7	7.5	6.6	6.4	6.3	6.1	6.7	6.8	7.2	6.9	7.0	6.9	
BROADWAY ST(0.0C) FC125M																					
4326991	0.079	0.479	C	2017	0012		CRACKING	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.9	6.5
HUBBARD CONSTRUCTION COMPA(2018) RIDE 6.4 6.7 6.6 6.0 7.8 7.4 7.3 7.3 7.1 7.0 6.8 7.0 6.8 7.0 6.8 7.0 5.4* 5.0*																					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																									
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE					
SR	US	G_BMP	G_EMP	LN	#T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031				
INTERSECT AT (MP SIDE)		W_BMP		W_EMP		RW		FY-P		WKM-F		ASTYPE													
ITMSEG-P		W_BMP		W_EMP		RW		FY-F		WKM-F															
CONTRACTOR		(AGE_ONE YEAR)		COMP		(2022)																			
ITMSEG-F		W_BMP		W_EMP		RW																			
15080000	0.000	2.135	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.5	7.5	7.5					
584				3	18.5	44000	RIDE	8.3	8.7	8.6	8.2	8.2	7.9	7.9	8.3	8.2	8.0	7.9	7.6	7.5					
SR-586/CURLEW RD(0.0R)						FC125M																			
4376261	0.000	2.017	C	2020	0012	CRACKING	7.5	7.5	7.0	6.0*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	9.6	10.0	8.5				
HUBBARD CONSTRUCTION COMPA(2022)						SPRIDE		7.5	7.6	7.8	7.8	7.8	7.7	7.7	7.7	8.2	8.1	8.1	8.0	8.0	7.6				
15080000	2.135	2.513	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	6.5	6.5	6.5	6.5	6.5	10.0					
580				4	4.5	55500	RIDE	8.3	8.7	8.6	8.2	8.2	7.9	7.9	8.1	7.8	7.7	7.4	7.3	7.6					
FROM SR 580(2.1R)						FC125M																			
							(2022)	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	9.1	10.0	8.5			
								RIDE	7.6	7.1	7.1	7.2	7.3	7.0	6.8	6.9	8.0	7.9	7.8	7.7	7.7	7.3			
15080000	2.513	2.974	R	1	1	45	CRACKING									7.5	7.5	7.5	7.0	6.6					
580				4	4.5	55500	RIDE									7.3	7.3	7.4	7.3	7.3					
							OGFC																		
								CRACKING																	
								RIDE																	
4514561	2.513	2.974	C	2029	0012																				
15080000	2.513	2.974	L	1	1	45	CRACKING									7.5	7.5	7.5	6.6	6.5					
580				4	4.5	55500	RIDE									7.4	7.3	7.3	7.1	7.1					
							OGFC																		
								CRACKING																	
								RIDE																	
4514561	2.513	2.974	C	2029	0012																				
15080000	2.135	2.513	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.0	4.5*	4.5*	10.0					
580				4	4.5	55500	RIDE	8.9	8.6	8.8	8.0	8.0	7.6	8.0	8.1	8.0	7.9	5.4*	5.3*	7.7					
CORPORATE CENTER ENT(2.5L)						FC125M																			
							(2022)	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	9.1	10.0	8.5				
								RIDE	7.6	7.1	7.3	7.4	7.5	7.1	7.2	7.2	8.0	8.1	8.0	7.9	7.8	7.4			
15080000	0.000	2.135	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.0	9.0	8.5	8.5					
584				3	18.5	44000	RIDE	8.9	8.6	8.8	8.0	8.0	7.6	8.0	8.1	8.0	7.9	7.9	7.9	7.4					
CR-752/TAMPA RD(0.0L)						FC125M																			
4376261	0.000	2.017	C	2020	0012	CRACKING	7.5	7.5	6.0*	6.0*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	9.6	10.0	8.5					
HUBBARD CONSTRUCTION COMPA(2022)						SPRIDE		7.4	7.4	7.7	7.6	7.6	7.4	7.6	7.5	8.3	8.3	8.3	8.1	8.1	7.7				
15090000	0.000	0.895	C	1	1	30	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0					
687 92				4	5.3	12000	RIDE	5.5*	6.0	5.3*	4.5*	4.0*	3.8*	3.8*	4.1*	6.3	6.4	6.3	6.3	5.9					
DALI BLVD S/5 AVE S(0.0R)						DGFC																			
2570631	0.000	0.895	C	2006	0005	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	5.3*	7.0	7.0	7.0	7.0	6.4*	6.5	4.0*				
(2009)						RIDE		6.0	5.8	5.6	5.7	5.5	5.5	5.5	5.0*	5.3*	5.2*	5.0*	5.1*	4.9*	4.5*				
15090000	0.895	2.329	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	8.5	7.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*					
687 92				2	1.9	29000	RIDE	8.4	8.4	7.9	7.6	7.5	6.9	6.9	6.8	6.4	6.1	5.9	5.9	6.0					
SIXTH AVE N(1.0R)						FC95MR																			
4271621	1.138	2.329	C	2013	0012	CRACKING	6.0*		10.0	10.0	10.0	10.0	9.0	7.0	7.0	7.0	7.0	6.8	6.5	4.5*					
PREFERRED MATERIALS, INC. (2016)						SPRIDE		5.8		8.0	7.9	7.9	7.7	7.7	7.6	7.5	7.5	7.4	7.2	6.8					
4479191	0.812	2.428	C	2027	0012																				
15090000	2.329	6.857	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*					
687 92				3	5.3	32500	RIDE	8.1	8.2	8.1	7.5	7.6	7.7	7.4	7.4	7.4	7.5	7.4	7.1	7.1					
THIRTIETH AVE N(2.4C)						FC95MR																			
4271621	2.517	6.605	C	2013	0012	CRACKING	6.0*		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.2	6.5				
PREFERRED MATERIALS, INC. (2016)						SPRIDE		6.9		8.1	8.0	7.9	7.9	8.0	7.8	7.9	7.8	7.7	7.7	7.7	7.3				
15090000	7.645	9.992	R	1	1	55	CRACKING	8.5	8.5	7.0	7.0	7.0	5.0*	5.0*	5.0*	4.5*	4.5*	4.5*	10.0	10.0					
600 92				2	7.0	45505	RIDE	8.6	8.7	8.6	7.8	7.7	7.7	7.7	7.6	7.8	7.6	7.4	8.2	8.3					
GOODWILL INDUST ENT(7.7R)						FC5																			
4168381	7.340	9.992	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	6.5	6.5	5.5*	5.6*	1.0*					
TAMPA PAVEMENT CONSTRUCTOR(2012)						SPRIDE		8.2	8.3	8.4	8.3	8.2	8.2	8.2	8.2	8.2	8.2	8.1	8.1	8.0	7.8				
4512381	7.645	9.992	C	2027	0012																				
15090000	7.645	9.992	L	1	1	55	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	10.0	10.0					
600 92				2	7.0	45505	RIDE	8.7	8.7	8.6	8.1	8.1	8.0	8.0	8.0	7.9	7.9	7.9	7.9	8.3	8.3				
MANGROVE CAY LN NE(7.9L)						FC5																			
4168381	7.340	9.992	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	5.5*	5.1*	0.5*				
TAMPA PAVEMENT CONSTRUCTOR(2012)						SPRIDE		8.3	8.3	8.4	8.3	8.2	8.2	8.4	8.3	8.3	8.3	8.3	8.3	8.2	8.0	7.8			
4512381	7.645	9.992	C	2027	0012																				

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																																		
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE														
SR	US	G_BMP	G_EMP	LN	*T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****																											
ITMSEG-P	(AGE_ONE YEAR)	WKM-F	ASTYPE																															
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM-F																						(PMRS)							
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F																													
15090000	2.329	6.857	L	1	1	45	CRACKING	10.0	10.0	8.5	8.5	8.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	
687 92					3	5.3	32500	RIDE	8.0	8.1	7.9	7.3	7.4	7.3	7.1	7.0	7.1	6.9	6.8	6.7														
THIRTIETH AVE N(2.4C)																																		
4271621	2.517	6.605	C	2013	0012		CRACKING	6.0*		10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.4	8.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	
PREFERRED MATERIALS, INC. (2016) SPRIDE																																		
15090000	0.895	2.329	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	
687 92					2	1.9	29000	RIDE	7.8	7.7	7.3	6.6	6.7	6.5	6.5	6.2	6.0	5.7	5.5	5.3*														
6 AVE N(1.0L)																																		
4271621	1.138	2.329	C	2013	0012		CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	7.0	7.0	6.5	6.5	6.4*	6.5	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	
PREFERRED MATERIALS, INC. (2016) SPRIDE																																		
4479191	0.812	2.428	C	2027	0012		CRACKING	5.3*		7.8	7.7	7.6	7.5	7.4	7.3	7.3	7.1	7.1	6.8	6.7	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*
PREFERRED MATERIALS, INC. (2016) SPRIDE																																		
15090001	0.000	0.218	C	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	
687 92					2	4.0	7900	RIDE	7.9	7.5	7.7	7.6	7.3	7.3	7.0	7.5	7.4	7.4	7.3	7.2	7.0													
SR 687(0.0C)																																		
							DGFC																											
							(1999)	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	
								RIDE	6.8	7.0	6.3	6.3	6.3	6.2	6.1	6.0	5.9	5.7	5.8															
15090010	0.000	0.312	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
600 92					2	9.3	57000	RIDE	7.0	7.3	7.7	8.0	8.1	7.5	7.7	7.3	7.6	7.6	8.2	8.2														
W OF ACCESS RD(0.0C)																																		
4168381	0.000	0.312	C	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	6.2*	5.8*	1.0*													
TAMPA PAVEMENT CONSTRUCTOR(2012) RIDE																																		
4512381	0.000	0.312	C	2027	0012		CRACKING	8.2	8.2	8.3	8.2	8.3	8.2	8.3	8.2	8.2	8.2	8.2	8.3	8.2														
TAMPA PAVEMENT CONSTRUCTOR(2012) RIDE																																		
15090010	0.000	0.312	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
600 92					2	9.3	57000	RIDE	7.0	7.3	7.7	8.0	7.7	7.5	8.0	8.0	8.0	8.1	8.3	8.3														
W OF ACCESS RD(0.0C)																																		
4168381	0.000	0.312	C	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	6.5	5.8*	1.0*													
TAMPA PAVEMENT CONSTRUCTOR(2012) RIDE																																		
4512381	0.000	0.312	C	2027	0012		CRACKING	8.3	8.3	8.2	8.2	8.1	8.1	8.2	8.0	8.1	7.9	7.9	8.0	7.9														
TAMPA PAVEMENT CONSTRUCTOR(2012) RIDE																																		
15090101	0.000	0.812	C	1	1	30	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
687 92					4	3.6	9600	RIDE	5.4*	5.5	5.3*	4.7*	4.2*	4.3*	4.0*	3.9*	6.4	6.7	6.6	6.6	6.5													
US-19A/SR-595(0.0R)																																		
4055731	0.000	0.812	C	2006	0012		CRACKING	10.0	10.0	9.0	9.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.1	6.9	4.5*													
(2009) RIDE																																		
15100000	0.111	2.624	R	1	1	35	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	
699					2	3.9	22500	RIDE		7.8	7.7	7.2	7.1	6.8	6.6	6.8	6.4	6.3	6.2	6.0														
36 AVE(0.2C)																																		
4306621	0.227	2.459	C	2015	0012		CRACKING	6.5	5.5*	4.0*	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.4	6.8	5.0*													
PREFERRED MATERIALS, INC. (2017) RIDE																																		
15100000	2.624	2.885	R	1	1	30	CRACKING	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
699					2	8.9	13500	RIDE	7.5	7.5			7.7	7.4	6.8	7.2	6.7	6.6	6.1	6.3														
76 AVE(2.6R)																																		
2570881	2.544	3.610	C	2001	0213		CRACKING	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	5.8*	3.0*													
APAC-FLORIDA INC (2005) SPRIDE																																		
4492131	2.595	4.083	C	2028	0012		CRACKING	6.6	6.6	5.9	5.9	5.9	5.7	5.7	5.5	5.5	5.3*	5.3*	5.3*	4.1*	3.7*													
APAC-FLORIDA INC (2005) SPRIDE																																		
15100000	2.885	3.105	R	1	1	35	CRACKING	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
699					2	8.9	13500	RIDE	7.5	7.5			7.7	7.4	6.8	7.2	6.7	6.6	6.1	6.3														
80 AVE(2.9R)																																		
2570881	2.544	3.610	C	2001	0213		CRACKING	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	8.2	5.5*													
APAC-FLORIDA INC (2005) SPRIDE																																		
4492131	2.595	4.083	C	2028	0012		CRACKING	6.6	6.6	5.9	5.9	5.9	5.7	5.7	5.5	5.5	5.3*	5.3*	5.3*	4.6*	4.2*													
APAC-FLORIDA INC (2005) SPRIDE																																		
15100000	3.105	3.596	R	1	1	35	CRACKING	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
699					2	8.9	13500	RIDE	7.5	7.5			7.7	7.4	6.8	7.2	6.7	6.6	6.1	6.3														
85 AVE(3.1C)																																		
2570881	2.544	3.610	C	2001	0213		CRACKING	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	5.8*	3.0*													
APAC-FLORIDA INC (2005) SPRIDE																																		
4492131	2.595	4.083	C	2028	0012		CRACKING	6.6	6.6	5.9	5.9	5.9	5.7	5.7	5.5	5.5	5.3*	5.3*	5.3*	6.4	6.0													

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE
SR	US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	(AGE_ONE	YEAR)																			(PMRS)
CONTRACTOR																					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F																
15100000	4.083	4.883	C	1	1	35	CRACKING	6.0*	6.0*	4.5*	3.5*	3.5*	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	
699				2	8.9	14700	RIDE	7.0	6.9	6.4	5.0*	5.2*	7.5	6.4	6.7	6.6	6.5	6.2	5.9	6.2	
99 AVE(4.1C)																					
4314041	4.101	4.835	C	2015		0012	CRACKING	7.0	5.5*	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.5	7.5	6.9	6.0*	4.0*
PREFERRED MATERIALS, INC. (2016)																					
15100000	4.883	6.000	R	1	1	35	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	6.5	6.5	6.5	
699				2	8.9	22000	RIDE	7.5	7.8	7.0	6.9	7.0	7.1	6.7	6.8	6.7	6.6	6.6	6.5	6.5	6.4
106 AVE(4.9R)																					
4306611	4.835	6.009	C	2015		0012	CRACKING	6.5	4.5*	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.5	7.5	6.9	6.8	5.0*
AJAX PAVING INDUSTRIES OF (2016)																					
15100000	6.000	6.393	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0						10.0	10.0
699				2	8.9	22000	RIDE	7.7	7.9	7.6	7.1	7.1	6.9	6.8						7.5	7.8
126 AVE(6.0C)																					
				(2012)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	6.3*	4.0*
RIDE 7.8 7.6 7.1 7.0 7.1 6.9 6.9 6.8 6.9 6.8 6.7 6.6 6.8 6.4																					
15100000	6.393	6.572	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0						10.0	10.0
699				2	8.9	22000	RIDE	7.7	7.9	7.6	7.1	7.1	6.9	6.8						7.5	7.8
129 AVE(6.4C)																					
				(2012)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	8.9	7.0
RIDE 7.8 7.6 7.1 7.0 7.1 6.9 6.9 6.8 6.9 6.8 6.7 6.6 6.6 6.2																					
15100000	6.572	7.976	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5	6.5	
699				2	8.9	22000	RIDE	7.7	7.4	7.2	6.8	6.8	6.6	6.5	6.5	6.7	6.3	6.4	6.3	6.2	
131 AVE(6.6R)																					
4289591	6.576	7.955	R	2014		0012	CRACKING	6.5	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	10.0	8.0
LANE CONSTRUCTION CORPORAT(2016)																					
15100000	7.976	9.097	R	1	1	40	CRACKING	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	8.5	8.5	8.5	8.5	
666				2	18.5	29500	RIDE	6.8	6.5	6.5	5.5	5.1*	5.1*	4.5*	7.4	6.8	6.8	6.9	6.8	6.5	
E MADEIRA AVE(8.0R)																					
2571361	7.976	9.097	C	2006		0012	CRACKING	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	4.2*	3.7*	1.5*
CONE & GRAHAM, INC. (2008)																					
4479201	7.963	9.354	R	2028		0012	RIDE	6.5	6.4	6.0	5.9	6.0	5.7	6.0	5.7	5.6	5.5	5.3*	5.3*	5.1*	4.7*
15100000	9.097	9.354	R	1	1	40	CRACKING	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	
666				2	18.5	29500	RIDE	6.8	6.5	6.5	5.5	5.1*	5.1*	4.5*	7.4	7.6	7.3	7.4	7.5	7.5	
(2008)																					
4479201	7.963	9.354	R	2028		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	4.7*	4.1*	1.5*
RIDE 7.0 7.3 7.1 7.3 7.1 7.1 7.0 7.1 7.0 7.1 7.0 8.5 8.5 6.9 6.9 7.0 6.9 6.9 6.8 6.8 6.4																					
15100000	9.097	9.354	L	1	1	40	CRACKING	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	
666				2	18.5	29500	RIDE	7.0	7.0	7.2	6.4	5.9	6.0	5.7	8.0	8.2	8.3	8.0	8.0	8.2	
(2008)																					
							CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.5	8.5	7.0	6.0*	5.3*	3.8*	1.5*
RIDE 7.9 8.1 7.9 7.8 7.9 7.8 7.7 7.8 7.7 7.7 7.7 7.7 7.7 7.7 7.7 7.7 7.7 7.7 7.7 7.7 7.3																					
15100000	7.976	9.097	L	1	1	40	CRACKING	7.0	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	9.5	9.5	9.5	9.5	
666				2	18.5	29500	RIDE	7.0	7.0	7.2	6.4	5.9	6.0	5.7	7.7	7.1	7.3	7.1	7.3	6.8	
FROM MADEIRA WAY(8.0L)																					
2571361	7.976	9.097	C	2006		0012	CRACKING	9.5	9.5	8.5	8.0	8.0	8.0	8.0	7.0	7.0	7.0	6.0*	4.6*	3.9*	1.5*
CONE & GRAHAM, INC. (2008)																					
15100000	6.572	7.976	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	6.5	6.5	6.5	6.5	
699				2	8.9	22000	RIDE	7.4	7.1	6.9	6.1	6.3	6.4	5.9	6.1	5.9	6.3	6.4	6.3	6.2	
131 AVE(6.6L)																					
4289591	6.576	7.955	L	2014		0012	CRACKING	6.5	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.0
LANE CONSTRUCTION CORPORAT(2016)																					
15100000	6.393	6.572	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0						10.0	10.0
699				2	8.9	22000	RIDE	7.4	7.3	6.9	6.9	7.1	6.8	6.1						7.4	7.4
129 AVE(6.4C)																					
				(2012)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	4.8*	7.8	5.5*
RIDE 6.9 7.4 6.9 6.7 6.6 6.6 6.6 6.6 6.4 6.6 6.6 6.6 6.6 6.6 6.4 6.6 6.1 6.2 6.1 6.8 6.4																					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-X-P	ASTYPE	*****														(PMRS)	
ITMSEG-P	(AGE_ONE YEAR)	YEAR	RW	FY-F	WKM-X-F			2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)	
ITMSEG-F																						
15100000	6.000	6.393	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0						10.0	10.0	
699			2	8.9	22000		RIDE	7.4	7.3	6.9	6.9	7.1	6.8	6.1						7.4	7.4	
126 AVE(6.0C)							DGFC															
				(2012)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	4.8*	1.7*	0.0*	
							RIDE	6.9	7.4	6.9	6.7	6.6	6.6	6.6	6.4	6.6	6.1	6.2	6.1	6.0	5.6	
15100000	4.883	6.000	L	1	1	35	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	
699			2	8.9	22000		RIDE	7.5	7.3	6.6	6.6	6.7	6.4	6.3	6.2	6.1	6.6	6.6	6.5	6.5	6.5	
BILMAR(4.9L)							FC95AR															
4306611	4.835	6.009	C	2015	0012		CRACKING	6.5	4.5*	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.5	7.5	7.6	7.8	6.0*	
AJAX PAVING INDUSTRIES OF				(2016)			RIDE	6.3	6.2	7.5	7.4	7.3	7.2	7.1	7.1	6.9	6.8	6.6	6.2	6.4	6.0	
15100000	3.596	4.083	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	9.5	9.5	8.5	8.5		
699			2	8.9	13500		RIDE	7.2	7.5	7.9	6.8	6.7	6.8	6.4	6.4	6.8	7.0	6.6	6.5	6.4		
HARRELL AVE(4.0C)							FC3															
				(1998)			CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	3.5*	
4492131	2.595	4.083	C	2028	0012		RIDE	6.6	6.6	6.2	6.5	6.5	6.9	6.6	6.6	6.5	6.0	5.9	4.8*	5.5	5.1*	
15100000	2.624	3.596	L	1	1	35	CRACKING	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
699			2	8.9	13500		RIDE	7.5	7.5			7.0	6.3	5.8	5.8	5.3*	6.7	6.6	6.1	6.3		
76 AVE(2.6L)							DGFC															
2570881	2.544	3.610	C	2001	0213		CRACKING	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.2*	5.5*	3.0*	
APAC-FLORIDA INC				(2005)			SPRIDE	6.6	6.6	5.9	5.9	5.9	5.7	5.7	5.5	5.5	5.3*	5.3*	3.9*	3.8*	3.4*	
4492131	2.595	4.083	C	2028	0012																	
15100000	0.111	2.624	L	1	1	35	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	6.5	6.5	6.5		
699			2	3.9	22500		RIDE		7.9	7.8	7.3	7.3	7.1	6.8	7.0	7.0	6.4	6.3	6.2	6.0		
36 AVE(0.2C)							FC125A															
4306621	0.227	2.459	C	2015	0012		CRACKING	6.5	5.5*	4.0*	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.7	7.1	5.5*	
PREFERRED MATERIALS, INC.				(2017)			RIDE	5.9	5.9	5.3*	7.0	6.9	6.5	6.7	6.5	6.4	6.1	6.0	6.9	6.8	6.4	
15110000	0.000	0.925	R	1	1	35	CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	7.5		
693			2	14.4	27000		RIDE	6.1*		7.7	7.0	6.9	6.9	6.6	6.6	6.5	6.5	6.2	6.0	5.8		
BLIND PASS RD(0.0R)							FC125M															
4348061	0.023	0.924	C	2018	0012		CRACKING	7.0	6.0*	6.0*	6.0*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	
AJAX PAVING INDUSTRIES OF				(2020)			SPRIDE	5.9	5.7	5.5	5.6	5.7	5.5	6.9	6.9	6.5	6.4	6.2	6.1	6.2	5.8	
15110000	0.925	1.775	R	1	1	35	CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	7.5		
693			3	6.9	29000		RIDE	6.1*		7.7	7.0	6.9	6.9	6.6	6.6	6.5	6.5	6.2	6.0	5.8		
MATHEWS RD S(1.0R)							FC125M															
4348061	1.247	1.766	C	2018	0012		CRACKING	7.0	6.0*	6.0*	6.0*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.8	9.3	
AJAX PAVING INDUSTRIES OF				(2020)			SPRIDE	5.9	5.7	5.5	5.6	5.7	5.5	7.6	7.6	7.5	7.4	7.6	7.6	7.8	8.0	
15110000	1.119	1.775	L	1	1	35	CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5		
693			3	6.9	29000		RIDE	5.3*		7.7	7.0	7.3	7.1	6.8	6.7	6.8	6.9	6.5	6.5	6.3		
HUFFMAN WAY(1.1L)							FC125M															
4348061	1.247	1.766	C	2018	0012		CRACKING	8.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	10.0	8.5	
AJAX PAVING INDUSTRIES OF				(2020)			SPRIDE	6.5	6.3	6.4	6.7	6.6	6.5	8.3	8.1	8.2	8.2	8.1	7.9	8.0	7.6	
15110000	0.000	1.119	L	1	1	35	CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5		
693			2	6.9	29000		RIDE	5.3*		7.7	7.0	7.3	7.1	6.8	6.7	6.8	6.9	6.5	6.5	6.3		
SR-699/BLIND PASS RD(0.0L)							FC125M															
4348061	0.023	0.924	C	2018	0012		CRACKING	8.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	8.6	10.0	
AJAX PAVING INDUSTRIES OF				(2020)			SPRIDE	6.5	6.3	6.4	6.7	6.6	6.5	7.4	7.3	7.4	6.9	6.8	6.5	7.2	6.8	
15120000	0.000	1.212	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5		
688			2	18.5	17500		RIDE	8.0	7.8	7.9	7.5	7.3	7.4	7.4	7.2	7.6	7.7	7.5	7.3	7.5		
SR-699(0.0R)							FC125															
2570481	0.000	1.212	C	1997	0213		CRACKING	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	5.9*	5.2*	2.0*	
GLF CONSTRUCTION CORPORATI				(2001)			S RIDE	7.4	7.0	6.7	6.7	6.8	6.6	6.4	6.5	6.4	6.4	6.3	6.4	6.5	6.1	
4416541	0.000	1.212	C	2028	0012																	
15120000	1.212	3.596	R	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0			10.0	10.0	10.0	10.0	10.0	10.0		
688			3	5.2	39000		RIDE	7.8	7.9	7.7	6.8	6.7			7.8	7.8	7.7	7.7	7.5	7.6		
137 ST(1.4C)							FC125															
2570501	1.212	3.596	C	2004	0213		CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	6.5	6.5	5.5*	5.5*	3.0*
CENTRAL FLORIDA EXCAVATING				(2008)			SPRIDE	7.3	7.1	7.0	7.0	6.9	6.7	6.7	6.8	6.6	6.5	6.4	6.6	6.4	6.0	
4479211	1.212	3.558	C	2028	0012																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	(AGE_ONE	YEAR)																			(PMRS)
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM-F																
ITMSEG-F																					
15120000	3.596	5.092	R	1	1	45	CRACKING	10.0	8.5	10.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	
688				3	3.6	69500	RIDE	8.4	8.4	8.0	7.4	7.1	7.0	6.9	6.5	6.8	6.5	6.1	5.6		
117 ST N(3.7R)																					
						FC125M															
2571551	3.655	4.379	C	2011	0213		CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	7.8	8.5	6.5
PCS CIVIL LLC				(2015)			SPRIDE		8.1	7.8	7.8	7.8	7.7	7.7	7.7	7.6	7.4	7.6	7.5	7.1	
15120000	5.092	7.571	R	1	1	45	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	
688				3	3.6	66000	RIDE	8.4	8.2	8.0	7.4	7.1	7.0	6.9	6.5	6.8	6.5	6.1	5.6		
GROSS POINTE(5.2R)																					
						FC125M															
				(2018)			CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5
							RIDE					8.1	7.9	7.9	7.9	7.9	7.8	7.9	7.9	7.8	7.4
15120000	7.571	8.482	R	1	1	45	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5		10.0	10.0	10.0	10.0	
688				3	6.2	59500	RIDE	8.4	8.1	8.0	7.3	7.3	7.1	6.9	7.4		8.1	8.0	7.9	7.8	
RANCHERO VILLAGE(7.7R)																					
						FC125M															
				(2022)			CRACKING	10.0	10.0	9.0	9.0	6.5	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	8.5
							RIDE	7.6	7.6	7.7	7.6	7.7	7.5	7.2	7.0	7.6	7.5	7.5	7.5	7.5	7.1
15120000	8.482	10.169	R	1	1	45	CRACKING	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	
688				4	9.6	51500	RIDE	8.1	7.9	7.8	6.2*	6.3*	6.1				7.6	7.4	7.1	7.5	
FRONTAGE RD 15150200(8.5C)																					
						FC125M															
				(2024)			CRACKING	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	9.0	8.0
							RIDE	7.4	6.9	7.1	6.4	6.4	7.1	7.2	7.1	7.0	6.8	7.8	7.8	7.8	7.4
15120000	10.169	10.566	C	1	1	50	CRACKING	2.0*	2.0*	4.5*	4.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	
688				3	3.6	61000	RIDE	8.1	8.1	7.8	6.2*	6.3*	6.1*				7.6	7.7	7.6	7.2	
FROM EB ROOSEVELT(10.5L)																					
						FC125M															
				(2019)			CRACKING	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	10.0	9.2	9.5	8.0
							RIDE	7.5	7.4	7.7			8.0	7.8	7.8	7.8	7.7	7.9	7.9	7.9	7.5
15120000	10.566	11.671	R	1	1	50	CRACKING	6.5	4.5*	10.0	10.0	10.0	10.0				10.0	10.0	10.0	10.0	
686				3	11.2	47000	RIDE	8.3	8.2	8.4	7.8	7.8	7.7				8.1	8.1	7.9	8.0	
40 ST N(10.6R)																					
						DGFC															
				(2019)			CRACKING	10.0					9.0	9.0	9.0	9.0	9.0	9.0	8.1	6.6	5.0*
							RIDE	7.4					7.5	7.4	7.4	7.3	7.3	7.3	7.2	7.3	6.9
15120000	11.671	12.341	R	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	6.5	6.5	6.5	
688				3	11.2	47000	RIDE	8.7	8.7	8.4	7.8	7.8	7.7	8.0	8.1	8.0	8.0	8.0	7.7	7.6	
TO CARILLON PKWY W(11.8R)																					
						FC5															
2571471	11.828	12.282	C	2013	0213		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	8.3	8.3	4.0*
LANE CONSTRUCTION CORPORAT(2014)																					
							SPRIDE	8.3	8.2	8.3	8.5	8.5	8.4	8.5	8.5	8.5	8.3	8.4	8.5	8.6	8.4
15120000	12.341	12.913	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	6.5	6.5	6.5	
688				3	11.2	47000	RIDE	8.7	8.7	8.4	7.8	7.8	7.7	8.0	8.1	8.0	8.0	8.0	7.7	7.6	
FROM CARILLON ENTR(12.4R)																					
						FC5M															
				(2025)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	10.0	10.0	8.5
							RIDE	8.3	8.2	8.3	8.5	8.5	8.4	8.5	8.5	8.5	8.3	8.4	8.4	8.2	8.0
15120000	11.671	12.913	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	7.5	
688				3	11.2	47000	RIDE	8.7	8.7	8.2	7.2	8.2	8.2	8.2	8.1	8.0	7.9	8.2	8.1	8.0	
EGRET BLVD(11.8L)																					
						FC5															
				(2014)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	6.7	6.5	2.5*
							RIDE	8.2	8.1	8.3	8.4	8.4	8.3	8.4	8.5	8.3	8.4	8.4	8.3	8.4	8.2
15120000	10.566	11.671	L	1	1	50	CRACKING	6.5	6.5	6.5	3.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	
686				3	11.2	47000	RIDE	7.9	7.8	7.8	6.9	5.9*	5.3*				8.0	8.0	7.9	7.8	
STONYBROOK DR(10.8L)																					
						FC125M															
				(2019)			CRACKING	9.0					10.0	10.0	10.0	9.0	9.0	9.0	9.1	8.6	7.0
							RIDE	6.7					7.9	7.7	7.7	7.5	7.7	7.7	7.6	7.7	7.3
15120000	8.482	10.169	L	1	1	45	CRACKING	2.0*	2.0*	1.0*	1.0*	1.0*	1.0*				10.0	10.0	10.0	10.0	
688				4	9.6	51500	RIDE	8.1	8.1	7.9	6.8	6.7	6.5				7.8	7.8	7.6	7.6	
FRONTAGE RD 15150200(8.5C)																					
						FC125M															
				(2024)			CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	9.5	8.5
							RIDE	7.5	7.4	7.4	7.1	7.2	7.3	7.3	7.2	7.1	7.2	7.9	7.8	7.9	7.5

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																							
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE			
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031		
INTERSECT AT (MP SIDE)							*****																
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	P		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031		
CONTRACTOR (AGE_ONE YEAR)					ASTYPE																(PMRS)		
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F																	
15120000	7.571	8.482	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0	10.0			
688			3	6.2		59500	RIDE	7.9	7.8	7.9	7.5	7.7	7.6	7.1	7.8		7.9	7.9	7.6	7.9			
FOREST LAKE DR (7.7L)							FC125M																
				(2022)			CRACKING	10.0	10.0	9.0	9.0	9.0	6.5	6.5	3.5*	10.0	10.0	10.0	9.6	10.0	8.5		
							RIDE	7.9	7.8	7.9	7.6	7.8	7.6	7.5	7.4	7.8	7.8	7.6	7.6	7.8	7.4		
15120000	5.092	7.571	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.0	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*			
688			2	3.6		66000	RIDE	8.3	8.3	8.2	7.5	7.5	7.3	6.9	6.8	6.6	6.4	6.2	5.7	5.4*			
OAK CREST APT ENT (5.2L)							FC125M																
				(2018)			CRACKING	4.5*				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5		
							RIDE	4.8*				8.1	8.0	8.0	7.9	7.8	7.8	7.8	7.8	7.8	7.4		
15120000	3.596	5.092	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0				
688			3	3.6		69500	RIDE	8.6	8.4	8.2	7.7	7.5	7.3	6.9	7.1	6.7	6.9	6.7	6.5				
PALM AVE (3.7L)							FC125M																
2571551	3.655	4.379	C	2011		0213	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.1	6.0*		
PCS CIVIL LLC							SPRIDE		8.1	7.7	7.7	7.7	7.5	7.6	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.0	
15120000	1.212	3.596	L	1	1	45	CRACKING	10.0	8.5	8.5	8.5	8.5				10.0	10.0	10.0	10.0	10.0			
688			3	5.2		39000	RIDE	8.4	8.0	8.2	7.4	7.1				7.8	8.1	8.1	8.1	7.9	7.9		
137 ST (1.4C)							FC125M																
2570501	1.212	3.596	C	2004		0213	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.5	7.5	6.5	7.0	6.7	6.5	4.0*		
CENTRAL FLORIDA EXCAVATING (2008)							SPRIDE	7.6	7.6	7.1	6.9	7.0	6.9	6.9	7.0	6.7	6.7	6.7	6.7	6.8	6.8	6.7	6.3
4479211 1.212 3.558 C 2028 0012																							
15120000	0.000	1.212	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5			
688			2	18.5		17500	RIDE	8.4	8.3	8.2	8.0	7.9	7.8	7.5	7.7	7.7	8.0	7.9	7.9	8.5	7.7		
CR-183 (0.0L)							FC125M																
2570481	0.000	1.212	C	1997		0213	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.8	3.5*		
GLF CONSTRUCTION CORPORATI (2001)							S RIDE	7.7	7.5	7.3	7.3	7.4	7.2	7.3	7.3	7.1	7.1	7.1	7.1	7.0	7.2	6.8	
4416541 0.000 1.212 C 2028 0012																							
15140000	0.000	1.512	R	1	1	35	CRACKING	9.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0			
699			2	3.2		14900	RIDE	5.6*	5.4*	5.2*	5.1*	5.0*	4.9*	4.7*	4.8*	4.7*	7.6	7.5	7.3	7.4			
150 AVE (0.0R)							FC125M																
2571291	0.020	1.512	C	2008		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.6	6.8	4.5*		
R. E. PURCELL CONSTRUCTION (2010)							RIDE	6.9	6.8	6.3	6.4	6.4	6.1	6.0	5.9	5.8	5.9	5.8	5.8	5.8	5.7	5.3*	
4520021 0.000 3.356 C 2029 0012																							
15140000	1.512	3.356	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	6.5	6.5	6.5	6.5	6.5			
699			2	3.2		16844	RIDE	7.8	7.6	7.4	7.1	7.1	6.9	6.8	6.7	6.5	6.5	6.5	6.2	6.3	6.2		
BATH CLUB CIR (1.5R)							FC125M																
4271611	1.534	3.356	C	2013		0012	CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	5.7*	4.8*	3.0*		
PREFERRED MATERIALS, INC. (2015)							SPRIDE	6.0	8.1	7.3	7.3	7.3	7.1	7.0	6.9	6.9	6.7	6.7	6.7	6.6	6.6	6.6	
4520021 0.000 3.356 C 2029 0012																							
15140000	3.356	4.061	R	1	1	35	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5			
699			2	3.2		16844	RIDE	6.6	6.4	6.6	6.5	6.4	6.5	7.4	7.6	7.4	7.4	7.4	7.3	7.3			
CR 694 (3.7R)							FC125M																
4416531	3.356	3.878	C	2023		0012	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	9.0		
HUBBARD CONSTRUCTION COMPA (2025)							SPRIDE	7.3	7.1	6.9	6.7	6.8	6.5	6.5	6.4	6.2	6.3	6.2	6.2	7.5	7.4	7.0	
15140000	4.061	6.752	C	1	1	30	CRACKING	7.0	7.0	7.0	7.0	6.5	6.5	6.5	4.5*		10.0	10.0	10.0	10.0			
699			2	3.2		13300	RIDE	6.3*	6.3	6.0	5.9	6.0	5.8	5.3*	5.3*		7.8	7.5	7.3	7.2			
193 AVE E (4.2R)							DGFC																
				(2010)			CRACKING	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.2*	6.5	4.0*		
							RIDE	7.0	6.8	6.1	5.9	5.7	5.5	5.5	5.3*	5.2*	5.1*	5.0*	4.9*	4.8*	4.4*		
4436661 3.957 6.752 C 2029 0012																							
15140000	3.356	4.061	L	1	1	35	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0			
699			2	3.2		16844	RIDE	5.4*	5.4*	5.2*	5.3*	5.0*	5.6	6.5	5.9	6.5	6.8	6.9	6.5	6.5			
186 AVE (3.5L)							FC125M																
4416531	3.356	3.878	C	2023		0012	CRACKING	8.5	8.5	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	9.0		
HUBBARD CONSTRUCTION COMPA (2025)							SPRIDE	6.4	6.4	5.9	5.8	5.7	5.4*	5.4*	5.2*	5.2*	5.1*	5.1*	5.1*	7.6	7.5	7.1	
15140000	1.512	3.356	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	7.0	6.0*			
699			2	3.2		16844	RIDE	7.5	7.3	6.9	6.6	6.5	6.4	6.1	6.4	6.4	6.1	5.9	5.7	5.5			
176 AVE W (2.4L)							FC125M																
4271611	1.534	3.356	C	2013		0012	CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	6.7	6.5	4.5*		
PREFERRED MATERIALS, INC. (2015)							SPRIDE	5.5	7.6	6.9	6.9	6.8	6.6	6.5	6.4	6.4	6.2	6.2	6.2	6.1	6.0	5.6	
4520021 0.000 3.356 C 2029 0012																							

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 ** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-F	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	(AGE_ONE YEAR)	W_EMP	RW	FY-F	WKM-F																(PMRS)
ITMSEG-F																					
15140000	0.000	1.512	L	1	1	35	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	8.5	8.5	7.5	10.0	10.0	10.0	10.0	
699				2	3.2	14900	RIDE	5.8*	5.9	5.5	5.8	5.8	5.7	5.6	5.6	6.0	7.6	7.5	7.3	7.4	
MADEIRA BEACH CITY LIMIT(0.0C) FC125																					
2571291	0.020	1.512	C	2008	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	7.0	4.5*
R. E. PURCELL CONSTRUCTION(2010) RIDE																					
4520021	0.000	3.356	C	2029	0012																

15150000	0.867	5.878	R	1	7	40	CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	8.5	8.5	8.5	
55 19				3	4.6	44500	RIDE	7.3		8.1	7.6	7.6	7.5	7.3	7.4	7.3	7.4	7.2	7.1	7.0	
SR 682(0.9C) FC125M																					
4402461	0.960	5.876	C	2022	0012		CRACKING	7.5	7.0	7.0	7.0	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	3.3*	10.0	9.0
PREFERRED MATERIALS, INC. (2026) RIDE																					
								7.0	6.9	6.7	6.5	6.4	6.3	6.3	6.3	6.1	6.0	5.9	5.3*	7.8	7.4

15150000	5.878	7.032	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	7.0	7.0	10.0	
55 19				3	5.6	46000	RIDE	7.9	7.6	7.6	6.7	6.7	6.7	6.6	6.6	6.4	6.5	6.5	6.7	7.9	
23 AV N(5.9C) FC125R																					
4037311	5.878	7.032	C	2011	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	8.0	7.5	7.1	5.0*
AJAX PAVING INDUSTRIES OF (2013) SPRIDE																					
								7.8	7.8	7.6	7.1	6.9	6.9	7.1	6.9	6.8	6.8	6.4	4.9*	6.5	6.1

15150000	7.032	7.320	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	7.0	7.0	8.0	
55 19				3	5.6	46000	RIDE	7.9	7.6	7.6	6.7	6.7	6.7	6.6	6.6	6.4	6.5	6.5	6.7	7.0	
44 AVE N(7.3R) DGFC																					
								8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	10.0	9.0	8.0
(2023) RIDE																					
								7.0	6.9	6.9	6.4	6.4	6.3	6.5	6.4	6.2	7.1	6.9	6.8	6.8	6.4

15150000	7.320	9.274	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.0	
55 19				3	5.1	53500	RIDE	8.3	8.2	8.2	7.9	7.8	7.6	7.4	7.5	7.3	7.4	7.0	7.2	7.0	
46 AVE N(7.4R) FC125M																					
4376251	8.086	9.274	C	2021	0012		CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	9.1	10.0	9.0
PREFERRED MATERIALS, INC. (2023) SPRIDE																					
								7.0	6.9	6.9	6.4	6.4	6.3	6.5	6.4	6.2	7.5	7.3	6.4	7.4	7.0

15150000	9.274	11.086	R	1	1	55	CRACKING	3.5*	3.5*	1.0*	0.0*	10.0	10.0	10.0	10.0	9.0		7.0	7.0	6.5	
55 19				3	5.6	79000	RIDE	7.8	7.7	7.4	5.2*	8.1	8.0	7.9	7.6	8.0		7.6	6.8	6.8	
76 TER(9.3R) FC5A																					
4314961	9.323	11.086	C	2016	0012		CRACKING	6.5	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.7	9.0	6.0*
PREFERRED MATERIALS, INC. (2018) SPRIDE																					
4560541	9.800	33.000	C	2025	0012			6.8	6.2*	6.9		8.3	8.3	8.4	8.4	8.3	8.3	8.3	7.8	8.4	8.2

15150000	11.086	12.507	R	1	1	55	CRACKING	3.5*	3.5*	1.0*	0.0*	10.0	10.0	10.0	10.0	9.0		10.0	10.0	10.0	
55 19				3	7.9	68500	RIDE	7.8	7.7	7.4	5.2*	8.1	8.0	7.9	7.6	8.0		8.2	8.1	7.9	
LAKE BLVD(11.5R) FC5M																					
2570701	11.119	12.896	C	2006	0213		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	6.6	5.6*	0.5*
ARCHER WESTERN CONTRACTORS(2011) SPRIDE																					
4560541	9.800	33.000	C	2025	0012			7.8	7.7	7.7	7.6	7.5	7.5	7.7	7.6	7.6	7.4	7.3	7.4	7.4	7.2

15150000	12.507	13.074	R	1	1	55	CRACKING	3.5*	3.5*	1.0*		10.0	10.0	10.0	9.0		10.0	10.0	10.0		
55 19				3	7.9	68500	RIDE	7.8	7.7	7.4		8.1	8.0	7.9	7.6	8.0		8.2	8.1	7.9	
FR FRNT RD 15150098(12.7R) FC5M																					
4560541	12.728	13.341	R	2025	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	8.5
(2025) RIDE																					
								7.8	7.7	7.7	7.6	7.5	7.5	7.7	7.6	7.6	7.4	7.3	8.3	8.3	8.1

15150000	13.074	15.830	R	1	1	55	CRACKING	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	
55 19				3	5.6	103000	RIDE	7.9	7.8	7.8		8.1	8.0	7.9	7.6	8.0	8.0	7.7	7.7	7.4	
4308991 12.896 15.927 C 2016 0012 CRACKING 6.5 4.5* 4.5* 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 8.8 8.9 5.5* 8.4																					
PREFERRED MATERIALS, INC. (2018) RIDE 7.2 6.8 7.4 8.7 8.6 8.8 8.8 8.8 8.6 8.6 8.6 8.5 8.5 8.6																					
4560541 9.800 33.000 C 2025 0012																					

15150000	15.830	18.998	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	6.5	4.5*	4.5*				
55 19				3	5.3	131000	RIDE	8.9	8.8	8.7	8.1	8.1	7.9	7.8	7.7	7.6	7.5				
FRONTAGE RD #098(16.0R) FC5M																					
											10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	5.8*	5.9*	2.5*
(2017) CRACKING																					
4560541	9.800	33.000	C	2025	0012		RIDE				8.0	7.9	7.8	8.0	7.9	7.9	7.8	7.7	7.5	7.6	7.4

15150000	18.998	20.791	R	1	7	55	CRACKING	10.0	10.0	10.0						10.0	10.0	10.0	10.0	10.0	
55 19				3	5.3	131000	RIDE	8.6	8.6	8.7						7.6	7.7	7.7	7.6	7.6	
OGFC																					
4560541	13.341	22.998	R	2025	0012		CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	4.5*	4.5*	4.1*	10.0	9.0
(2026) RIDE																					
								7.5	7.5	7.7	7.7	7.6	7.5	7.7	7.6	7.6	7.4	7.2	7.2	8.7	8.5

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	#T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-F	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	(AGE_ONE	YEAR)																			(PMRS)
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM-F																
ITMSEG-F																					
15150000	20.791	22.622	R	1	8	55	CRACKING	10.0	10.0	10.0	8.5	8.5	7.5	7.5	6.5	6.5	4.5*	4.5*			
55 19				3	5.3	116500	RIDE	8.7	8.6	8.6	8.2	8.1	8.0	8.0	8.1	7.6	7.4	7.4			
EXECUTIVE CENTER ENT(21.4R)																					
2568901	20.892	21.947	C	2012		0213	CRACKING			10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5		
RUSSELL ENGINEERING, INC (2016) SPRIDE																					
4560541	9.800	33.000	C	2025		0012															
15150000	22.622	25.650	R	1	8	55	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
55 19				3	5.3	105000	RIDE	8.9	8.6	8.9	8.2	8.1	8.0	8.0	8.0	7.8	7.8	7.6	7.6	7.4	7.3
HAMMOCK PINES BLVD(23.1R)																					
						FC5															
4560541	9.800	33.000	C	2025		0012	CRACKING	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5			
(2016) RIDE																					
15150000	25.650	25.881	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
55 19				4	3.6	78000	RIDE	8.9	8.6	8.9	8.2	8.1	8.0	8.0	8.0	7.8	7.8	7.6	7.4	7.3	
CR 752(25.8C)																					
4560541	25.665	25.845	R	2025		0012	CRACKING	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	6.2*	9.0	8.0
(2026) RIDE																					
15150000	25.881	31.277	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
55 19				4	5.3	93000	RIDE	8.9	8.6	8.9	8.2	8.1	8.0	8.0	8.0	7.8	7.8	7.6	7.4		
CORAL LANDING/PUBLIX(26.2R)																					
4290051	27.877	31.104	C	2013		0012	CRACKING	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	6.2*	4.5*	1.0*
HUBBARD CONSTRUCTION COMPA(2016) SPRIDE																					
4560541	9.800	33.000	C	2025		0012															
15150000	31.277	31.826	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0	7.5	7.0
55 19				3	5.3	63000	RIDE	8.2	8.1	8.1	8.3	8.1	7.9	8.0	7.9	7.6	7.3	7.3	7.0	7.0	6.6
FROM CR-582(31.3R)																					
4290051	31.275	31.859	C	2013		0012	CRACKING	7.0		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	6.2*	4.5*	1.0*
HUBBARD CONSTRUCTION COMPA(2016) SPRIDE																					
4560541	9.800	33.000	C	2025		0012															
15150000	31.826	33.146	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0	7.5	7.0
55 19				3	5.3	63000	RIDE	8.7	8.6	8.7	8.3	8.1	7.9	8.0	7.9	7.6	8.0	7.9	7.8	7.6	7.6
E LIVE OAK ST(31.8R)																					
4348071	31.826	33.146	C	2017		0012	CRACKING	7.5	4.5*	4.5*	3.5*	0.0*		10.0	10.0	10.0	10.0	10.0	9.0	8.8	6.0*
PREFERRED MATERIALS, INC. (2020) SPRIDE																					
4560541	9.800	33.000	C	2025		0012															
15150000	31.826	33.146	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5
55 19				3	5.3	63000	RIDE	8.7	8.4	8.5	7.9	7.8	7.4	7.6	7.4	7.2	7.8	7.8	7.7	7.6	7.6
CR 952(31.8L)																					
4348071	31.826	33.146	C	2017		0012	CRACKING	6.5	4.5*	4.5*	3.5*	0.0*		10.0	10.0	10.0	10.0	10.0	9.0	8.8	6.0*
PREFERRED MATERIALS, INC. (2020) SPRIDE																					
4560541	9.800	33.000	C	2025		0012															
15150000	31.272	31.826	L	1	2	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5	6.5
55 19				3	5.3	63000	RIDE	8.1	8.0	7.9	7.9	7.8	7.4	7.6	7.4	7.2	5.5*	5.3*	5.6*	4.8*	
TARPON AVE(31.3L)																					
4290051	31.275	31.859	C	2013		0012	CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	4.5*	4.5*	1.0*
HUBBARD CONSTRUCTION COMPA(2016) SPRIDE																					
4560541	9.800	33.000	C	2025		0012															
15150000	25.650	31.272	L	1	2	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5	6.5
55 19				4	5.3	93000	RIDE	8.9	8.5	8.9	8.2	8.2	7.9	7.7	7.9	7.6	7.6	7.5	7.3	7.1	
CR 752(25.8C)																					
4290051	27.877	31.104	C	2013		0012	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	4.5*	4.5*	1.0*
HUBBARD CONSTRUCTION COMPA(2016) SPRIDE																					
4560541	9.800	33.000	C	2025		0012															
15150000	22.622	25.650	L	1	8	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
55 19				3	5.3	105000	RIDE	8.9	8.5	8.9	8.2	8.2	7.9	7.7	7.9	7.6	7.6	7.5	7.3	7.1	
REPUBLIC DR(23.1L)																					
						FC5															
4560541	9.800	33.000	C	2025		0012	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5			
(2016) RIDE																					
15150000	20.801	22.622	L	1	1	55	CRACKING	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*
55 19				3	5.3	116500	RIDE	8.3	8.0	7.9	7.6	7.9	7.8	7.7	7.7	7.6	7.4	7.4	7.1	6.9	
FROM FRONTAGE RD(21.3L)																					
2568901	20.892	21.947	C	2012		0213	CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	8.4	8.3	4.5*
RUSSELL ENGINEERING, INC (2016) SPRIDE																					
4560541	9.800	33.000	C	2025		0012															

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT	AT	(MP		SIDE)			SURFTYPE	=====													
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	X-P															
CONTRACTOR	(AGE_ONE	YEAR)		ASTYPE				2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	X-F															(PMRS)
15150000	3.894	5.878	L	1	8	40	CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	7.5
55	19			3	4.1	38000	RIDE	7.0		8.0	7.4	7.3	7.1	7.1	7.3	7.5	7.1	6.9	6.7	6.5	
FAIRFIELD AVE S(3.9L)																					
FC125																					
2570951	0.867	5.878	C	2000	0012		CRACKING	7.5	7.5	7.0	6.5	6.5	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	2.8*		
AJAX PAVING INDUSTRIES INC(2003)							SPRIDE	6.6	6.3	6.4	6.2	6.0	5.9	6.0	5.9	5.8	5.6	5.6	5.8		
4402461	0.882	5.876	C	2022	0012																
15150000	0.867	3.894	L	1	7	40	CRACKING	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	7.5	
55	19			3	4.6	44500	RIDE	7.0		8.0	7.4	7.3	7.1	7.1	7.3	7.5	7.1	6.9	6.7	6.5	
SR 682(0.9C)																					
FC125																					
4402461	0.960	5.876	C	2022	0012		CRACKING	7.5	7.5	7.0	6.5	6.5	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	2.8*	10.0	9.0
PREFERRED MATERIALS, INC. (2026)							RIDE	6.6	6.3	6.4	6.2	6.0	5.9	6.0	5.9	5.8	5.6	5.6	5.8	7.7	7.3
15150019	0.000	2.844	C	1	1	35	CRACKING														
55F				2	7.8	11500	RIDE														
							CRACKING														7.0
							RIDE														6.3
15150023	0.000	0.310	C	1	1	35	CRACKING														
55F				2	7.8	11500	RIDE														
							CRACKING														7.5
							RIDE														6.0
15150023	0.310	0.497	C	1	1	35	CRACKING														
55F				2	7.8	11500	RIDE														
							CRACKING														10.0
							RIDE														9.0
																					6.3
																					5.9
15150031	0.000	1.227	C	1	8	35	CRACKING														
55F				2	7.8	11500	RIDE														
							CRACKING														
							RIDE														
4437801	0.000	2.403	C	2024	0012																
15150031	1.227	2.403	C	1	1	35	CRACKING														
55F				1	7.8	11500	RIDE														
4437801	1.204	2.202	C	2024	0012		CRACKING														9.5
PREFERRED MATERIALS, INC. (2026)							SPRIDE														6.7
																					8.5
																					6.3
15150032	0.063	1.396	C	1	8	35	CRACKING														
55F				2	7.8	11500	RIDE														
							CRACKING														
							RIDE														
4437801	0.063	1.396	C	2024	0012																
15150098	0.000	0.631	C	1	1	40	CRACKING														
55F				2	7.8	11500	RIDE														
							CRACKING														8.0
							RIDE														5.7
15150098	0.631	4.285	C	1	1	45	CRACKING														
55F				2	7.8	11500	RIDE														
							CRACKING														10.0
							RIDE														9.0
																					7.3
																					6.9
15150098	4.285	5.216	C	1	1	45	CRACKING														
55F				2	7.8	11500	RIDE														
							CRACKING														6.0*
							RIDE														6.0

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	
INTERSECT	AT	(MP	SIDE)				SURFTYPE	=====													
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	P	ASTYPE														
CONTRACTOR	(AGE_ONE	YEAR)						2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F															(PMRS)
15150098	5.216	5.546	C	1	1	45	CRACKING														
55F			2	7.8	11500		RIDE														
							CRACKING														8.0
							RIDE														7.1
15150098	5.546	5.815	C	1	7	45	CRACKING														
55F			1	7.8	11500		RIDE														
							(2026)														10.0
							RIDE														9.0
																					6.6
																					6.2
15150098	5.815	6.746	C	1	1	45	CRACKING														
55F			2	7.8	11500		RIDE														
							CRACKING														7.0
							RIDE														6.9
15150200	0.027	4.987	C	1	1	45	CRACKING														
55F			2	7.8	11500		RIDE														
							(2026)														8.7
							RIDE														7.5
																					7.0
																					6.6
15150300	0.000	0.660	C	1	1	35	CRACKING														
55F			2	7.8	11500		RIDE														
							CRACKING														8.0
							RIDE														6.2
15150300	0.660	1.034	C	1	8	35	CRACKING														
55F			2	7.8	11500		RIDE														
							CRACKING														
							RIDE														
15150400	0.000	0.338	C	1	8	45	CRACKING														
55F			2	7.8	11500		RIDE														
							CRACKING														
							RIDE														
15150400	0.338	0.941	C	1	1	45	CRACKING														
55F			2	7.8	11500		RIDE														
							CRACKING														7.0
							RIDE														6.7
15150400	0.941	2.135	C	1	1	45	CRACKING														
55F			2	7.8	11500		RIDE														
							(2026)														9.5
							RIDE														8.5
																					7.1
																					6.7
15150701	0.000	0.329	C	1	1	25	CRACKING														
561			2	8.7	3500		RIDE														
							CRACKING														8.0
							RIDE														4.5*
15150702	0.000	0.053	C	1	1		CRACKING														
531			2	8.7	1000		RIDE														
							CRACKING														8.0
							RIDE														6.6

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 *@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	*T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT	AT	(MP	SIDE)				*****															
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	P		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR	(AGE	ONE	YEAR)		ASTYPE																(PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F																
15150703	0.000	0.057	C	1	1		CRACKING															
596				1			RIDE															
				(2026)			CRACKING													10.0	9.0	
							RIDE													6.6	6.2*	
15150900	0.000	1.102	C	1	55		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	10.0	
55	19			2	5.4		8800 RIDE	8.1	8.0	7.4	7.3	7.8	7.5	7.2	7.4	7.5	7.6	7.5	7.5	7.2	7.6	
SR-682/54	AVE S	(0.0R)					OGFC															
4256661	0.000	0.775	C	2012	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	6.5	6.5	6.5	6.5	6.3*	5.4*	1.0*
LANE CONSTRUCTION	CORPORAT	(2013)					SPRIDE	7.5	7.6	7.6	7.5	7.5	7.3	7.5	7.4	7.4	7.4	7.1	7.3	7.2	7.0	
4491531	0.000	1.102	C	2027	0012																	
15170000	4.247	8.535	R	4	1	65	CRACKING	6.5	7.0	7.0	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
55	1275	12.2	16.5	2	7.5		67613 RIDE	8.5	8.6	8.5	8.1		8.4	8.4	8.3	8.3	8.3	8.3	8.2	8.1		
N END OF NEW BRIDGE	(4.2R)						FC5M															
4458861	4.247	8.535	C	2023	0012		CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	7.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	9.0	
PREFERRED MATERIALS, INC.	(2025)						SPRIDE	8.2	8.1	8.1	8.1	7.9	7.9	8.0	8.0	8.0	7.9	7.7	8.7	8.7	8.6	
15170000	4.247	8.535	L	4	1	65	CRACKING	6.5	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5		
55	1275	12.2	16.5	2	7.5		67613 RIDE	8.5	8.5	8.5	7.9		8.0	7.9	7.8	8.0	7.9	8.0	7.9	7.8		
N OF N TOLL PLAZA	(8.5C)						FC5M															
4458861	4.247	8.535	C	2023	0012		CRACKING	9.5	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	6.5	10.0	10.0	9.0	
PREFERRED MATERIALS, INC.	(2025)						SPRIDE	7.9	7.9	7.9	7.8	7.9	7.7	7.9	7.9	7.9	7.9	7.8	8.7	8.5	8.4	
15190000	0.500	2.287	R	4	2	65	CRACKING	6.3*		7.2	7.1	7.1	7.9	7.9	7.7	7.2	7.4	7.3	6.7	6.4*		
93	1275	17.6	19.4	3	7.3	104000	RIDE	6.9		8.4	7.7	7.8	7.7	7.8	7.8	7.8	7.9	7.8	7.8	7.9		
							LDG															
2588041	0.420	1.485	C	1982	0101		CRACKING	6.1*	6.1*	5.8*	7.3	7.0	6.9	6.9	7.0	6.6	6.7	6.4*	5.8*	7.4	6.5	
COUCH, INC.	(1986)						RIDE	7.7	7.7	8.0	8.2	8.2	8.2	8.6	8.4	8.5	8.3	8.3	8.2	8.7	8.6	
4460091	0.500	4.425	R	2023	0227																	
15190000	2.287	4.429	R	4	2	65	CRACKING	6.3*	5.6*	6.3*	6.3*	6.3*	7.5	7.4	7.2	8.0	7.7	7.6	7.4	7.4		
93	1275	19.4	21.6	3	7.3	115000	RIDE	6.9	6.7	8.4	7.2	7.2	6.6	7.0	7.4	7.2	7.5	7.7	7.6	7.7		
							LDG															
				(1983)			CRACKING	7.1	6.9	6.2*	6.3*	6.0*	5.7*	5.3*	5.5*	3.7*	3.7*	3.6*	0.5*	7.1	6.0*	
4460091	0.500	4.425	R	2023	0227		RIDE	7.5	7.5	8.0	8.0	7.9	7.7	7.7	7.6	7.9	7.7	7.3	7.1	8.3	8.2	
15190000	5.284	8.867	R	4	4	65	CRACKING	9.3	9.1	9.1	9.2	9.1		9.4	9.3	9.3	9.1	9.2	9.0	8.8		
93	1275	22.4	26.0	3	7.3	173000	RIDE	7.4	7.4	7.3	6.4*	6.5		7.6	7.8	7.9	7.9	7.9	7.9	7.6		
							LDG															
2588801	5.797	8.840	C	2004	0227		CRACKING	8.8	8.5	8.4	8.3	8.2	8.2	8.1	8.1	8.1	7.6	7.5	7.5	6.9	6.6*	6.0*
KIEWIT INFRASTRUCTURE SOUT	(2007)						RIDE	7.6	6.9	8.2	8.2	8.1	8.0	8.1	8.1	8.1	8.1	7.9	7.8	7.8	7.9	
4541721	5.282	7.358	@	C	2028	0227																
15190000	8.867	10.961	R	4	4	65	CRACKING	9.3	9.1	9.1	9.2	9.1	9.2	9.2	9.0	9.1	9.1	9.2	9.0	9.0		
93	1275	26.0	28.1	3	7.3	162000	RIDE	7.4	7.4	7.3	6.4*	6.5	6.7	6.8	6.8	8.1	8.3	8.2	8.1	8.3		
							LDG															
2587901	8.300	18.200	C	1981	0101		CRACKING	9.0	8.9	8.8	8.8	8.8	8.7	8.7	8.8	8.9	8.9	9.0	8.8	8.6	7.5	
GEORGIA ELECTRIC CO	(1983)						RIDE	8.1	7.8	8.6	8.7	8.6	8.5	8.6	8.6	8.7	8.6	8.6	8.6	8.6	8.5	
4491091	7.370	14.368	R	2025	0213																	
15190000	10.961	12.045	R	4	4	65	CRACKING	9.3		9.4	9.4	9.4	9.4	9.4	9.3	9.4	9.3	9.4	9.2	9.2		
93	1275	28.1	29.2	4	7.3	140500	RIDE	7.4		8.6	8.0	8.2	8.1	8.2	8.1	8.1	7.9	7.8	7.7	8.1		
							CONC															
2588611	11.115	12.888	C	1999	0213		CRACKING	9.2	9.2	9.1	9.0	9.0	9.0	9.0	9.0	9.1	9.3	9.3	9.0	9.0	8.0	
HUBBARD CONSTRUCTION CO	(2003)						RIDE	8.0	8.0	8.3	8.3	8.3	8.2	8.2	8.2	8.0	8.5	8.4	8.5	8.3	8.2	
4491091	7.370	14.368	R	2025	0213																	
15190000	12.045	12.900	R	4	4	65	CRACKING	9.3		9.4	9.4		9.4	9.3	9.3	9.5	9.3	9.4	9.3	9.2		
93	1275	29.2	30.0	4	7.3	140500	RIDE	7.4		8.6	8.0		8.1	8.0	8.0	8.2	8.3	7.7	7.9	8.2		
							CONC															
4245012	12.185	12.872	C	2017	0213		CRACKING	9.3	9.3	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.5	9.5	9.3	9.2	8.5	
(2023)							RIDE	8.1	7.8	8.1	8.1	8.1	8.0	8.0	7.9	8.2	7.6	7.4	7.9	8.2	8.1	
4491091	7.370	14.368	R	2025	0213																	
15190000	12.900	13.451	R	4	4	65	CRACKING	9.3	9.4	9.3			9.4	9.3	9.3	9.5	9.3	9.4	9.3	9.2		
93	1275	30.0	30.6	4	7.3	134000	RIDE	7.4	7.3	7.3			8.1	8.0	8.0	8.2	8.3	7.7	7.9	8.2		
							CONC															
2588701	12.688	15.028	C	2001	0213		CRACKING	9.3	9.3	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.4	9.3	9.3	8.5
JONES BROS., INC.	(2006)						RIDE	8.1	7.8	8.1	8.1	8.1	8.0	8.0	7.9	8.2	8.0	8.0	7.9	8.0	7.9	
4491091	7.370	14.368	R	2025	0213																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN - 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	FT	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT	AT	(MP	SIDE)				=====															
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	-P		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR	(AGE	ONE	YEAR)		ASTYPE																	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	-F																
15190000	13.451	14.368	R	4	4	65	CRACKING	10.0	10.0	10.0				9.5	9.5	9.5	9.5	9.4	9.4	9.4	9.4	
93 I275	30.6	31.5	4	7.3	165000		RIDE	8.4	8.2	8.0				8.1	8.1	8.2	8.4	8.5	8.6	8.2	8.5	
							CONC															
2588701	12.688	15.028	C	2001	0213		CRACKING	9.4	9.4	9.4	9.4	9.4	9.3	9.3	9.3	9.4	9.4	9.4	9.1	9.1	8.5	
JONES BROS., INC.	(2006)						RIDE	8.5	8.5	8.6	8.6	8.6	8.6	8.4	8.5	8.6	8.3	8.3	8.2	8.3	8.2	
4491091	7.370	14.368	R	2025	0213																	
15190000	14.368	16.649	R	4	8	65	CRACKING	10.0	7.0	7.0	6.5			6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
93 I275	31.5	33.8	4	7.3	174000		RIDE	9.0	8.8	8.9	8.1			7.6	8.0	8.2	8.2	8.2	8.2	8.1	8.0	
							FC5M															
END OF 15-240-000(14.5R)																						
4134131	14.441	16.649	C	2006	0012		CRACKING	10.0	9.0	9.0	9.0	7.5	6.5	3.5*	3.5*	3.5*	3.5*	3.5*				
PREFERRED MATERIALS, INC.	(2007)						RIDE	8.0	7.9	8.1	8.0	8.0	7.9	8.1	8.1	8.0	7.8	8.2				

15190000	15.023	16.649	L	4	8	65	CRACKING	10.0	7.0	7.0	6.5			4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
93 I275	32.2	33.8	4	7.3	174000		RIDE	8.4	8.4	8.4	7.8			7.4	8.1	7.9	8.0	8.0	8.0	7.9	7.8	
							FC5M															
4134131	14.441	16.649	C	2006	0012		CRACKING	9.0	7.5	6.5	6.5	4.5*	1.0*	1.0*	0.0*							
PREFERRED MATERIALS, INC.	(2007)						RIDE	7.7	7.5	7.7	7.6	7.5	7.3	7.6	7.6							

15190000	14.368	15.023	L	4	8	65	CRACKING	10.0	7.0	7.0	6.5			4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
93 I275	31.5	32.2	4	7.3	174000		RIDE	8.4	8.4	8.4	7.8			7.4	8.1	7.9	8.0	8.0	8.0	7.9	7.8	
							FC5M															
2588701	12.688	15.028	C	2001	0213		CRACKING	9.0	7.5	6.5	6.5	4.5*	1.0*	1.0*	0.0*	0.0*	0.0*	0.0*				
JONES BROS., INC.	(2007)						SPRIDE	7.7	7.5	7.7	7.6	7.5	7.3	7.6	7.6	6.8	6.1*	5.5*				

15190000	13.451	14.368	L	4	4	65	CRACKING	10.0	10.0	10.0				9.5	9.5	9.5	9.5	9.5	9.5	9.4	9.4	
93 I275	30.6	31.5	4	7.3	165000		RIDE	8.6	8.5	8.4				7.0	7.4	7.7	7.1	7.9	8.0	8.0	8.4	
							CONC															
2588701	12.688	15.028	C	2001	0213		CRACKING	9.4	9.3	9.4	9.4	9.4	9.4	9.4	9.4	9.4	9.1	9.2	9.2	9.1	8.8	8.0
JONES BROS., INC.	(2006)						RIDE	8.2	8.2	8.4	8.4	8.4	8.3	8.3	8.3	8.3	8.4	8.4	8.3	8.2	8.1	
4491091	7.358	14.668	L	2025	0213																	
15190000	12.456	13.451	L	4	4	65	CRACKING	8.8	8.6	8.3				9.5	9.5	9.5	9.4	9.2	9.3	9.1	9.1	
93 I275	29.6	30.6	4	7.3	134000		RIDE	7.2	6.1*	6.4*				7.6	7.5	7.3	7.3	7.3	8.0	7.8	7.9	
							CONC															
2588701	12.688	15.028	C	2001	0213		CRACKING	8.9	8.8	8.6	8.5	8.6	8.4	8.2	8.2	8.4	8.3	8.5	9.1	8.9	8.0	
JONES BROS., INC.	(2006)						RIDE	7.8	7.7	8.1	8.1	8.1	7.9	8.0	7.9	8.1	8.1	8.1	8.2	8.1	8.0	
4491091	7.358	14.668	L	2025	0213																	
15190000	10.961	12.456	L	4	2	65	CRACKING	8.8		9.3	9.3	9.3	9.4	9.3	9.1	9.3	9.0	9.1	8.9	9.0		
93 I275	28.1	29.6	4	7.3	140500		RIDE	7.2		8.5	7.9	7.9	7.7	7.6	7.9	7.5	7.4	7.5	7.5	7.8		
							CONC															
2588611	11.115	12.888	C	1999	0213		CRACKING	8.9	8.9	8.9	8.8	8.7	8.7	8.7	8.7	8.7	8.6	8.6	8.7	8.6	8.0	
HUBBARD CONSTRUCTION CO	(2003)						RIDE	7.5	7.4	8.1	8.1	8.0	8.0	8.1	8.0	8.1	8.1	8.1	8.2	8.2	8.1	
4491091	7.358	14.668	L	2025	0213																	
15190000	8.867	10.961	L	4	4	65	CRACKING	8.8	8.1	8.0	8.1	8.0	8.8	8.7	8.4	8.7	8.7	8.8	8.7	8.6		
93 I275	26.0	28.1	3	7.3	162000		RIDE	7.2	6.9	7.2	6.2*	6.2*	6.4*	6.5	6.3*	7.5	7.9	7.6	8.0	8.1		
							LDG															
2587901	8.300	18.200	C	1981	0101		CRACKING	8.5	8.5	8.3	8.3	8.2	8.2	8.1	8.2	8.0	8.1	7.6	7.9	7.6	6.5	
GEORGIA ELECTRIC CO	(1983)						RIDE	8.0	7.2	8.4	8.4	8.3	8.3	8.3	8.4	8.4	8.4	8.2	8.2	8.5	8.4	
4491091	7.358	14.668	L	2025	0213																	
15190000	5.284	8.867	L	4	4	65	CRACKING	8.8	8.1	8.0	8.1	8.0		9.2	8.9	8.6	8.4	8.4	8.1	8.1		
93 I275	22.4	26.0	3	7.3	173000		RIDE	7.2	6.9	7.2	6.2*	6.2*		7.4	7.6	7.5	7.6	7.6	7.1	7.4		
							LDG															
2588801	5.797	8.840	C	2004	0227		CRACKING	7.9	7.8	7.8	7.7	7.6	7.4	7.3	7.3	6.2*	6.8	6.3*	6.4*	5.7*	5.0*	
KIEWIT INFRASTRUCTURE SOUT	(2007)						RIDE	7.3	7.1	7.9	7.8	7.8	7.6	7.7	7.7	7.7	7.6	7.5	7.4	7.5	7.4	
4541721	5.282	7.358@	C	2028	0227																	
15190000	2.287	4.456	L	4	2	65	CRACKING	6.2*	4.4*	5.7*	5.6*	5.5*	7.5	7.4	6.8	7.6	7.6	7.8	7.4	7.1		
93 I275	19.4	21.6	3	7.3	115000		RIDE	6.9	6.6	8.2	7.7	7.7	7.5	7.4	7.0	7.5	7.8	8.0	7.6	7.5		
							LDG															
							CRACKING	6.9	6.6	6.3*	6.2*	6.1*	5.5*	5.2*	5.1*	3.9*	4.0*	3.7*	4.1*	7.4	6.5	
4460091	2.140	4.000	L	2023	0227		RIDE	7.5	7.2	8.1	8.0	7.9	7.8	7.7	7.8	7.9	7.7	7.6	7.4	8.1	8.0	
15190000	0.500	2.287	L	4	2	65	CRACKING	6.2*		7.8	7.8	7.6	7.9	7.8	7.7	7.7	7.9	8.2	8.3	8.1		
93 I275	17.6	19.4	3	7.3	104000		RIDE	6.9		8.3	8.0	8.1	7.8	7.8	7.8	7.8	7.9	7.7	7.5	7.8		
							LDG															
2588041	0.420	1.485	C	1982	0101		CRACKING	7.6	7.4	7.4	7.5	7.5	7.4	7.3	7.4	7.7	7.8	7.8	7.5	7.9	7.0	
COUCH, INC.	(1986)						RIDE	7.9	7.8	8.1	8.1	8.3	8.4	8.6	8.7	8.7	8.5	8.5	8.5	9.1	9.0	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 ** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	WT	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)								=====													
ITMSEG-P		W_BMP	W_EMP	RW	FY-P	WKM	X-P														
CONTRACTOR		(AGE_ONE YEAR)		ASTYPE																	
ITMSEG-F		W_BMP	W_EMP	RW	FY-F	WKM	X-F	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031

15200001	1.531	2.821	R	3	1	45	CRACKING	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
682				2	5.3	28500	RIDE	7.7		8.8	8.4	8.4	8.3	8.3	8.2	8.2	8.3	8.3	8.1	8.1	
ESCONDIDA BLVD(1.7R)																					
FC125M																					
4416521	1.531	2.821	C	2022	0012	CRACKING	9.0	9.0	7.0	6.5	6.5	6.0*	6.0*	6.0*	5.5*	5.5*			10.0	10.0	9.0
AJAX PAVING INDUSTRIES OF		(2025)		SPRIDE																	
15200001	2.821	3.286	R	3	1	45	CRACKING	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0
682				3	9.0	39500	RIDE	6.9		8.1	7.4	7.8	7.4	7.6	8.0	7.7	7.7	7.7	7.8	7.8	7.7
FROM ECKERD COLLEGE(3.2R)																					
FC125M																					
4416521	2.970	3.290	C	2022	0012	CRACKING	9.0	9.0	8.5	8.5	8.5	6.0*	6.0*	6.0*	3.5*	3.5*			10.0	10.0	9.0
AJAX PAVING INDUSTRIES OF		(2025)		SPRIDE																	
15200001	3.286	3.721	C	3	1	45	CRACKING	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	
682				2	9.0	19500	RIDE	6.4*		8.0	7.4	7.2	7.1	7.6	7.1	7.2	7.3	6.9	6.9	7.2	
WATER RECLAIM FAC SW(3.3L)																					
FC125M																					
4348391	3.521	3.721	C	2018	0012	CRACKING	7.5	5.5*	4.0*	3.5*	3.5*	3.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.4	8.7	7.0
NATIONWIDE MUTUAL INSURANC		(2020)		RIDE																	
15200001	2.821	3.286	L	3	1	45	CRACKING	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
682				3	9.0	39500	RIDE	6.4*		8.0	7.4	7.2	7.1	7.5	7.5	7.8	7.9	7.8	7.4	7.3	
DOLPHIN CAY LN(3.0L)																					
FC125M																					
4416521	2.970	3.290	C	2022	0012	CRACKING	8.5	7.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	3.0*			10.0	10.0	9.0
AJAX PAVING INDUSTRIES OF		(2025)		SPRIDE																	
15200001	1.531	2.821	L	3	1	45	CRACKING	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	
682				2	5.3	28500	RIDE	7.7		8.6	8.3	8.0	7.9	8.0	8.2	7.6	7.6	7.7	7.3	7.3	
PLAYA ESCONDIDA ENT(1.7L)																					
FC125M																					
4416521	1.531	2.821	C	2022	0012	CRACKING	8.5	7.0	6.5	6.5	6.5	6.0*	6.0*	5.5*	5.5*	5.5*			10.0	10.0	9.0
AJAX PAVING INDUSTRIES OF		(2025)		SPRIDE																	
15200001	0.925	1.531	L	3	1	45	CRACKING	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.0*		
682				2	4.2	19800	RIDE	8.5	7.3	8.3	7.7	7.8	7.6	7.5	7.4	7.5	7.4	7.4	7.1		
BAHIA DEL MAR BLVD(1.0L)																					
FC125R																					
		(2016)		CRACKING																	
				RIDE																	
15200001	0.000	0.429	L	3	1	35	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	6.5	6.0*	6.0*	6.0*	
682				2	4.2	19800	RIDE	8.2	7.6	7.8	7.1	6.2	6.6	7.1	7.0	6.3	6.0	5.6	6.7	6.4	
SR-699/GULF BLVD(0.0L)																					
FC125R																					
		(2016)		CRACKING																	
				RIDE																	
15200003	0.000	0.418	C	1	1	45	CRACKING								10.0	8.5	8.5	8.5	8.5	7.5	
682				2	9.0	19500	RIDE								7.7	7.1	7.1	7.0	6.8	6.7	
SR 55(0.0C)																					
FC125M																					
4348391	0.179	0.390	C	2018	0012	CRACKING	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5
NATIONWIDE MUTUAL INSURANC		(2021)		RIDE																	
15200100	0.000	0.121	C	1	1	30	CRACKING														
661				2	8.7	4500	RIDE														
CRACKING																					
RIDE																					
4491531	0.000	0.075	C	2027	0012																8.0

15220000	0.197	1.225	R	1	7	45	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5
60				2	4.9	36500	RIDE	8.4	8.2	8.2	6.7	7.0	7.0	7.0	7.3	7.4	7.3	7.4	6.9	7.2	
CAUSEWAY PARKING ENT(1.2R)																					
FC125H																					
		(2026)		CRACKING																	
				RIDE																	
15220000	0.197	1.225	L	1	7	45	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5
60				2	4.9	36500	RIDE	8.4	8.4	8.2	7.9	7.6	7.7	7.5	7.7	7.6	7.6	7.4	7.2	7.3	
FROM ISLAND WAY(0.6L)																					
FC125H																					
		(2026)		CRACKING																	
				RIDE																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @# INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	(AGE_ONE	YEAR)																			(PMRS)
CONTRACTOR	ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F															
15230000	0.000	0.587	R	1	1	40	CRACKING	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5
693			3	9.4		28500	RIDE	5.4*	5.4*	5.2*	4.8*	4.6*	4.7*	6.2	6.4	6.5	6.3	6.2	6.1	5.9	
PARK ST(0.0C)																					
4402542	0.000	0.600	C	2022		0012	CRACKING	9.0	8.5	8.5	8.0	8.0	8.0	7.0	7.0	6.0*	10.0	10.0	9.5	10.0	9.0
PREFERRED MATERIALS, INC. (2023)																					
FC125M																					
SPRIDE																					
15230000	0.587	2.223	R	1	1	40	CRACKING	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5
693			3	2.8		39000	RIDE	5.4*	5.4*	5.2*	4.8*	4.6*	4.7*	6.2	6.4	6.5	6.3	6.2	6.1	5.9	
CENTRAL AVE(0.6C)																					
4402541	1.004	2.223	C	2023		0012	CRACKING	9.0	8.5	8.5	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	9.0
HUBBARD CONSTRUCTION COMPA(2025)																					
FC125H																					
SPRIDE																					
15230000	2.223	5.392	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	10.0	10.0	
693			3	9.4		45500	RIDE	7.3	7.2	7.5	6.8	6.6	6.9	6.5	6.5	6.6	6.5	6.3	7.7	7.5	
26 AVE N(2.4C)																					
4113301	2.223	5.342	C	2011		0226	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	6.5	4.5*
AJAX PAVING INDUSTRIES OF (2012)																					
4512391	2.223	5.371	C	2029		0012	RIDE	7.7	7.5	7.4	7.3	7.4	7.4	7.3	7.3	7.2	6.9	7.1	7.1	6.9	6.5
HUBBARD CONSTRUCTION COMPA(2025)																					
15230000	2.223	5.392	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	10.0	10.0	
693			3	9.4		45500	RIDE	7.1	7.3	7.2	6.6	6.2*	6.5	6.1	6.2	6.3	6.1	6.0	8.0	7.7	
26 AVE N(2.4C)																					
4113301	2.223	5.342	C	2011		0226	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.0	6.5	6.5	4.5*
AJAX PAVING INDUSTRIES OF (2012)																					
4512391	2.223	5.371	C	2029		0012	RIDE	7.3	7.0	7.1	7.1	7.1	6.9	7.2	6.9	7.0	6.9	6.8	6.9	6.7	6.3
HUBBARD CONSTRUCTION COMPA(2025)																					
15230000	0.587	2.223	L	1	1	40	CRACKING	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
693			3	2.8		39000	RIDE	7.0	6.9	6.5	5.9	5.6	5.0*	7.0	7.0	7.0	6.9	7.0	6.9	7.0	7.0
CENTRAL AVE(0.6C)																					
4402541	1.004	2.223	C	2023		0012	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	9.0
HUBBARD CONSTRUCTION COMPA(2025)																					
FC125H																					
SPRIDE																					
15230000	0.000	0.587	L	1	1	40	CRACKING	7.0	7.0	7.0	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
693			3	9.4		28500	RIDE	7.0	6.9	6.5	5.9	5.6	5.0*	7.0	7.0	7.0	6.9	7.0	6.9	7.0	7.0
PARK ST(0.0C)																					
4402542	0.000	0.600	C	2022		0012	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	10.0	10.0	9.1	10.0	9.0
PREFERRED MATERIALS, INC. (2023)																					
FC125M																					
SPRIDE																					
15240000	0.000	0.700	R	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			9.5	
694			3	6.4		69000	RIDE	8.5	8.3	8.5	7.8	7.9	8.0	7.7	8.0	8.3	8.3			8.0	
BRIDGE #125(0.0C)																					
4416501	0.322	0.700	C	2023		0012	CRACKING	9.5	9.0	7.5	7.5	7.5	7.0	7.0	6.5	6.5	6.0*	6.0*	10.0	10.0	8.5
AJAX PAVING INDUSTRIES OF (2025)																					
FC5M																					
SPRIDE																					
15240000	0.700	1.842	R	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5		10.0	
694			3	7.1		78500	RIDE	8.5	8.3	8.5	7.8	7.9	8.0	7.7	7.9	7.5	7.7			8.0	
AJAX PAVING INDUSTRIES OF (2025)																					
FC5M																					
SPRIDE																					
15240000	3.330	3.620	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
687			3	6.4		28500	RIDE	7.6	7.8	7.8	7.6	7.4	7.1	7.2	7.2	6.7	6.8	6.6	6.6	6.8	
SANDPIPER(3.5R)																					
DGFC																					
CRACKING																					
RIDE																					
15240000	3.620	5.373	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	4.5*	
687			2	6.4		28500	RIDE	9.0	9.0	8.8	8.0	8.1	8.0	7.9	8.0	7.8	7.8	7.4	7.1	7.1	
108 AVE N(3.7R)																					
4309001	3.620	5.537	C	2015		0012	CRACKING	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	8.8	5.5*
LANE CONSTRUCTION CORPORAT(2017)																					
4560601	3.610	5.400	C	2026		0012	RIDE	7.0	6.6	7.4	8.5	8.5	8.4	8.5	8.4	8.4	8.4	8.4	8.3	8.3	8.1
SCENIC OVERLOOK(5.4R)																					
FC2																					
CRACKING																					
RIDE																					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	%T	AA	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM	W-P	*****														
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	FW	FY-F	WKM	W-F	*****														
ITMSEG-P	W_BMP	W_EMP	FW	FY-F	WKM	W-F	*****														
ITMSEG-F	W_BMP	W_EMP	FW	FY-F	WKM	W-F	*****														
15240000	5.760	5.883	C	1	2	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
687				1	4.0	4600	RIDE	8.1	8.1	8.1	7.6	7.5	7.4	7.9	8.0	7.7	7.7	7.7	7.3	7.4	
RAMP #190071(5.8C)																					
					(2025)		CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.0*	6.0*		10.0	10.0	8.5
							RIDE	7.3	7.2	7.1	7.0	7.2	6.9	6.8	7.1	6.9	6.8		7.4	6.2*	6.0*
15240000	5.373	5.760	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
687				2	6.4	28500	RIDE	8.1	8.1	8.8	8.2	8.2	8.2	8.1	8.0	7.7	7.9	7.7	7.6	7.4	
RAMP #190071(5.8C)																					
					(2025)		CRACKING	10.0	9.0	9.0	9.0	9.0	6.5	6.5	4.5*				10.0	10.0	8.5
							RIDE	7.4	7.0	7.3	7.1	7.0	7.1	7.5	7.3				7.3	7.4	7.2
15240000	3.620	5.373	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.0	6.5	6.5	4.5*	
687				2	6.4	28500	RIDE	9.1	9.1	8.8	8.2	8.2	8.2	8.1	7.9	7.8	7.6	7.2	7.0	6.7	
ONE HUNDRED TENTH ST L(3.9L)																					
4309001	3.620	5.537	C	2015		0012	CRACKING	4.5*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.1	4.5*
LANE CONSTRUCTION CORPORAT(2017)																					
4560601	3.610	5.400	C	2026		0012	RIDE	6.5	6.3*	7.0	8.4	8.4	8.3	8.4	8.3	8.4	8.3	8.2	8.2	8.0	
15240000	3.330	3.620	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
687				3	6.4	28500	RIDE	8.2	8.5	8.3	7.7	8.1	7.8	7.5	7.8	7.7	7.7	7.4	7.3	7.3	
GANDY BLVD WB(3.4L)																					
					(2019)		CRACKING	10.0	10.0	9.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	9.1	10.0	8.5
							RIDE	7.4	7.3	6.7	5.7								7.5	7.1	
15240000	0.700	1.842	L	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5			10.0
694				3	7.1	78500	RIDE	8.6	8.6	8.5	8.1	8.1	8.2	7.8	8.0	7.4	7.9				8.2
FC5M																					
4438071	0.935	1.600	C	2023		0012	CRACKING	10.0	10.0				6.5	6.5	6.5	4.5*	4.5*	3.5*	10.0	10.0	8.5
AJAX PAVING INDUSTRIES OF (2025)																					
							SPRIDE	8.2	8.2				7.5	7.6	7.9	7.9	7.9	7.5	8.9	8.8	8.6
15240000	0.000	0.700	L	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5				7.5
694				2	6.4	69000	RIDE	8.6	8.6	8.5	8.1	8.1	8.2	7.8	7.9	8.2	8.3				7.8
BRIDGE #125(0.0C)																					
4416501	0.322	0.700	C	2023		0012	CRACKING	7.5	7.5	7.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	10.0	10.0	8.5
AJAX PAVING INDUSTRIES OF (2025)																					
							SPRIDE	8.1	7.8	7.8	7.7	7.6	7.4	7.3	7.5	7.2	7.3	7.3	8.4	8.6	8.4
15240001	0.000	0.540	C	1	7	35	CRACKING	8.5	7.0												
664				2	8.7	2000	RIDE	6.4*	6.9												
4416501 AJAX PAVING INDUSTRIES OF (2026)																					
							SPRIDE													10.0	9.0
																				7.2	6.8
15240001	0.540	0.639	C	1	1	35	CRACKING	8.5	7.0												
664				2	8.7	2000	RIDE	6.4*	6.9												
(2000)																					
							CRACKING													7.8	5.0*
							RIDE													7.2	6.8
15240002	0.000	0.817	C	1	1	30	CRACKING														
657				2	8.7	2000	RIDE														
(2026)																					
							CRACKING													10.0	9.0
							RIDE													7.4	7.0
15240003	0.844	1.051	C	1	1		CRACKING														
647				2	8.7	200	RIDE														
(2001)																					
							CRACKING														8.1
							RIDE														6.0*
15240043	0.000	0.365	C	1	1	30	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5							
662				2	8.7	6000	RIDE	7.0	6.6	6.6	6.6	6.6	7.0	6.4							
(2001)																					
							CRACKING													6.5	3.5*
							RIDE													5.2*	4.8*

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 7 COUNTY = PINELLAS -----																								
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE				
SR US	G_BMP	G_EMP	LN	%T	ADT	RATINGS		2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031			
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	=====																	
ITMSEG-P	(AGE_ONE YEAR)							2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031			
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM-X-F																			
ITMSEG-F																								
15240043	0.365	0.605	C	1	1	30	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5											
662			2	8.7	6000		RIDE	7.0	6.6	6.6	6.6	7.0	6.4											
4416501	0.421	0.605	C	2023	0012		CRACKING																10.0	9.0
AJAX PAVING INDUSTRIES OF				(2026)			SPRIDE																7.9	7.5
15241000	0.000	2.245	R	1	1	50	CRACKING																	
694 92			2	9.3	57000		RIDE																	
15240047	NB OFF(0.0R)					FC5A								10.0	10.0	10.0	10.0	10.0	8.9	9.0	6.5			
				(2020)			CRACKING								8.5	8.5	8.4	8.4	8.3	8.3	8.4	8.2		
15241000	0.000	2.245	L	1	1	50	CRACKING																	
694 92			2	9.3	57000		RIDE																	
I 275 ENT(0.0C)							FC5A							10.0	10.0	10.0	10.0	9.0	8.3	8.9	6.0*			
				(2020)			CRACKING								8.5	8.5	8.5	8.4	8.3	8.3	8.5	8.3		
15241100	0.000	1.286	C	1	1	40	CRACKING																	
600F			2	6.8	5900		RIDE																	
				(2026)			CRACKING																10.0	9.0
							RIDE																6.9	6.5
15241200	0.000	1.084	C	1	1	40	CRACKING																	
694F			2	6.8	5900		RIDE																	
				(2026)			CRACKING																10.0	9.0
							RIDE																7.2	6.8
15242000	0.000	0.193	R	3	5	40	CRACKING																	
690	0.0	0.2	1	7.3	31500		RIDE																	
				(2026)			OGFC														10.0	9.0		
							CRACKING																7.6	7.4
							RIDE																	
15242000	0.803	1.088	R	3	5	40	CRACKING																	
690	0.8	1.1	1	7.3	31500		RIDE																	
				(2026)			OGFC														10.0	9.0		
							CRACKING																7.9	7.7
							RIDE																	
15242000	1.850	2.131	R	3	5	55	CRACKING																	
690	1.9	2.1	2	7.3	31500		RIDE																	
				(2026)			OGFC														10.0	9.0		
							CRACKING																8.1	7.9
							RIDE																	
15242000	1.850	2.131	L	3	5	55	CRACKING																	
690	1.9	2.1	2	7.3	31500		RIDE																	
				(2026)			OGFC														10.0	9.0		
							CRACKING																8.4	8.2
							RIDE																	
15242000	0.803	1.088	L	3	5	40	CRACKING																	
690	0.8	1.1	1	7.3	31500		RIDE																	
				(2026)			OGFC														10.0	9.0		
							CRACKING																8.1	7.9
							RIDE																	
15242000	0.000	0.193	L	3	5	40	CRACKING																	
690	0.0	0.2	1	7.3	31500		RIDE																	
				(2026)			OGFC														10.0	9.0		
							CRACKING																6.5	6.3
							RIDE																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).