FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26003000	0.000	2.544	C	1	1	40	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0															
120			4	3.6	13200		RIDE	7.3	7.2	7.5	7.2	7.0	6.8	6.3	6.1	6.4	6.1	6.2	7.8	7.7															
SR 25(0.0C)						FC125R																													
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5	7.5	7.5	6.9	7.0	4.0*													
					(2012)		RIDE	7.3	7.6	7.2	7.3	7.6	7.3	7.2	7.1	7.0	7.0	7.0	6.9	6.8	6.4													
26004000	0.000	1.712	R	1	1	35	CRACKING	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0															
24A			2	3.6	23000		RIDE	6.8	7.1	7.0	6.1	6.4	8.0	7.7	6.7	7.4	7.3	7.3	7.2	7.1															
SR 24(0.0C)						FC125																													
2075552	0.000	0.931	C	2005		0012	CRACKING	9.0	9.0	9.0	9.0	8.0	7.0	7.0	6.5	6.5	6.5	6.5	6.2*	5.9*	2.0*															
PREFERRED MATERIALS, INC.				(2006)			RIDE	7.0	7.3	6.6	6.8	6.9	6.8	6.7	6.8	6.6	6.4	6.5	6.3	6.1	5.7													
2075554	0.000	2.201	C	2027		0012																													
26004000	1.712	2.201	C	1	1	35	CRACKING	4.5*	4.5*	4.5*	2.0*	2.0*	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0															
24A			2	3.6	9100		RIDE	6.0*	6.5	6.0	4.5*	4.5*	8.3	8.3	7.6	8.2	8.2	8.2	7.9	7.6															
SR 331(2.2C)						FC125																													
2075552	1.651	2.201	C	2005		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	7.5	7.5	7.0	7.0	7.0	6.0*	6.5	3.0*															
PREFERRED MATERIALS, INC.				(2006)			RIDE	7.7	8.1	7.3	7.7	7.8	7.7	7.6	7.4	7.7	7.7	7.4	7.5	7.6	7.2													
2075554	0.000	2.201	C	2027		0012																													
26004000	0.000	1.712	L	1	1	35	CRACKING	6.5	6.5	6.5	6.5	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
24A			2	3.6	23000		RIDE	7.5	7.4	7.4	6.4	7.0	8.0	7.5	7.0	6.6	7.3	7.4	7.2	7.1															
SR 24(0.0C)						FC125																													
2075552	0.000	0.931	C	2005		0012	CRACKING	9.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.9*	5.5*	2.0*															
PREFERRED MATERIALS, INC.				(2006)			RIDE	7.0	7.3	6.8	6.4	6.8	6.9	6.8	6.8	6.6	6.5	6.6	6.4	6.4	6.0													
2075554	0.000	2.201	C	2027		0012																													
26005000	0.000	0.400	R	1	1	45	CRACKING	9.5	9.5			10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0																
222			2	2.8	32000		RIDE	7.0	6.7			7.7	7.4	7.4	7.3	7.2	7.2	7.4	7.3	7.3															
						FC125M																													
							CRACKING	9.0	9.0	9.0	9.0		10.0	10.0	8.5	8.5	7.0	7.0	9.5	8.8	8.0													
					(2025)		RIDE	7.3	7.4	6.3	6.1									7.6	7.2													
26005000	0.400	1.204	R	1	8	45	CRACKING	9.5	9.0	9.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0															
222			2	2.8	31500		RIDE	8.4	8.5	7.8	7.6	8.0	7.8	8.5	8.3	8.0	8.2	8.1	7.9	7.9															
NW 92ND CT(0.5C)						FC125M																													
2075452	0.522	3.466	C	2006		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	8.0	7.5	6.5	6.5	6.5	6.5	5.2*																	
PREFERRED MATERIALS, INC.				(2007)			SPRIDE	7.9	7.9	7.6	7.4	7.8	7.7	7.6	7.6	7.6	7.4	7.3	7.1															
4470321	0.400	3.851	C	2024		0012																													
26005000	1.204	2.080	R	1	8	45	CRACKING	9.5	9.0	9.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0															
222			2	2.8	31500		RIDE	8.4	8.5	7.8	7.6	8.0	7.8	8.5	8.3	8.0	8.2	8.1	7.9	7.9															
NW 76 ST(1.6R)						FC125M																													
2075452	0.522	3.466	C	2006		0012	CRACKING	9.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	6.5	6.5	6.5																	
PREFERRED MATERIALS, INC.				(2007)			SPRIDE	7.9	8.5	7.9	7.9	8.1	8.1	8.0	7.9	7.6	7.3	7.3	6.7															
4470321	0.400	3.851	C	2024		0012																													
26005000	2.080	3.631	R	1	8	45	CRACKING	7.0	7.0	5.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.0	9.0															
222			2	2.8	37500		RIDE	8.0	8.0	7.6	7.3	7.0	6.8	8.5	8.3	8.0	8.2	8.1	7.9	7.9															
SIDE ROAD(2.3C)						FC125M																													
2075452	0.522	3.466	C	2006		0012	CRACKING	9.0	9.0	9.0	9.0	8.0	7.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*																	
PREFERRED MATERIALS, INC.				(2007)			SPRIDE	7.9	7.9	7.7	7.7	7.9	7.9	7.9	7.8	7.6	7.4	7.5	7.4															
4470321	0.400	3.851	C	2024		0012																													
26005000	3.631	5.570	R	1	8	45	CRACKING	8.0	8.0	8.0	8.0	7.5	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0															
222			2	2.8	36500		RIDE	8.7	8.6	8.3	7.8	7.4	8.0	8.1	7.8	8.0	8.2	8.1	7.9	7.9															
CR 2053(3.7C)						FC125																													
2076112	3.638	4.733	C	2004		0012	CRACKING	9.0	9.0	9.0	9.0	8.0	7.0	7.0	6.0*	6.0*	5.5*	4.5*	3.5*																	
V. E. WHITEHURST & SONS, I				(2006)			RIDE	7.9	7.9	7.7	7.7	7.9	7.9	7.9	7.9	7.8	7.8	7.8	7.8															
2076115	3.851	5.590	C	2025		0012																													
26005000	5.570	6.716	R	1	1	45	CRACKING	8.0	8.0	7.5	7.5	7.5	6.5	6.0*	4.0*	4.0*	10.0	10.0	10.0	10.0															
222			2	2.8	27500		RIDE	7.3	7.4	7.3	6.7	6.9	6.3	6.0	6.1	5.8	8.3	8.1	8.0	7.9															
NW 23RD TER(5.6R)						FC125M																													
2076113	5.546	10.587	R	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	7.5	7.5	7.5	7.4	7.0	4.0*															
PREFERRED MATERIALS, INC.				(2010)			SPRIDE	7.9	7.9	7.8	7.7	7.9	7.9	7.9	7.8	7.7	7.7	7.6	7.6	7.3	6.9													
26005000	6.716	10.691	R	1	1	45	CRACKING	8.0	7.5	7.5	7.5	6.5	6.5	6.0*	4.0*	4.0*	10.0	10.0	10.0	10.0															
222			2	2.8	16100		RIDE	8.0	8.0	7.9	7.4	7.0	6.8	6.3	6.4	6.1	8.3	8.1	8.0	7.9															
SIXTH ST NW(7.2C)						FC125M																													
2076113	5.546	10.587	R	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	7.5	7.5	7.5	7.4	6.9	4.0*															
PREFERRED MATERIALS, INC.				(2010)			SPRIDE	7.9	7.9	7.8	7.7	7.9	7.9	7.9	7.8	7.7	7.7	7.6	7.6	7.6	7.2													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / US / W_BMP	EMP / G_BMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	LN	%T	AADT	SURFTYPE / RW / FY-P / WKMX-P / ASTYPE / FY-F / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26005000	10.691	10.968	R	1	1	55					CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
222				1	2.8		8300				RIDE	8.2	8.2	7.9	6.7		8.4	8.5	8.4	8.4	8.4	8.4	8.3	8.3													
SIDE ROAD(10.8C)										FC95																											
2077962	10.663	14.236	C	2004			0012				CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	8.0	8.0	7.0	6.5	3.0*											
PREFERRED MATERIALS, INC. (2006)											RIDE	8.3	8.3	7.9	8.0	8.2	8.2	8.1	8.1	8.0	8.0	8.0	7.9	7.5	7.1											
26005000	10.968	11.225	C	1	1	55					CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
222				2	2.8		8300				RIDE	8.2	8.2	7.9	6.7		8.4	8.5	8.4	8.4	8.4	8.4	8.3	8.3													
										FC125M																											
2077962	10.663	14.236	C	2004			0012				CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	8.0	8.0	7.0	6.5	3.0*											
PREFERRED MATERIALS, INC. (2006)											RIDE	8.3	8.3	7.9	8.0	8.2	8.2	8.1	8.1	8.0	8.0	8.0	7.9	8.1	7.7											
26005000	11.225	11.754	R	1	1	55					CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
222				1	2.8		8300				RIDE	8.2	8.2	7.9	6.7		8.7	8.7	8.7	8.4	8.4	8.4	8.3	8.3													
DIV OF FORESTRY(11.6R)										FC95																											
2077962	10.663	14.236	C	2004			0012				CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	8.0	8.0	7.0	6.5	3.0*											
PREFERRED MATERIALS, INC. (2006)											RIDE	8.3	8.3	7.9	8.0	8.2	8.2	8.1	8.1	8.0	8.0	8.0	7.9	7.3	6.9											
26005000	11.754	14.290	C	1	1	55					CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
222				2	2.8		8300				RIDE	8.2	8.2	7.9	6.7		8.8	8.7	8.5	8.4	8.4	8.4	8.3	8.3													
GAINESVILLE CITY LIMITS(11.8L)										FC125M																											
2077962	10.663	14.236	C	2004			0012				CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	8.0	8.0	7.0	7.0	3.5*											
PREFERRED MATERIALS, INC. (2006)											RIDE	8.3	8.3	7.9	8.0	8.2	8.2	8.1	8.1	8.0	8.0	8.0	7.9	8.0	7.6											
26005000	6.716	10.691	L	1	1	45					CRACKING	8.0	7.5	7.5	6.5	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0													
222				2	2.8		16100				RIDE	7.8	8.1	7.8	7.2	7.3	6.7	6.2	6.2	5.9	8.3	8.0	8.0	7.9													
NW 12TH DR(6.7L)										FC125M																											
2076113	5.546	10.587	L	2009			0012				CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5	7.5	7.1	6.6	3.5*											
PREFERRED MATERIALS, INC. (2010)											SPRIDE	7.9	7.9	8.0	7.5	7.9	7.8	7.7	7.7	7.7	7.4	7.6	7.5	7.3	6.9											
26005000	5.570	6.716	L	1	1	45					CRACKING	9.0	8.0	8.0	8.0	8.0	6.0*	6.0*	4.5*	4.5*	10.0	10.0	10.0	10.0													
222				2	2.8		27500				RIDE	7.6	7.6	7.5	7.2	6.8	6.6	6.0	6.6	6.5	8.3	8.0	8.0	7.9													
HANCOCK SQUARE ENT R(5.7C)										FC125M																											
2076113	5.546	10.587	L	2009			0012				CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5	7.5	7.1	7.9	5.0*											
PREFERRED MATERIALS, INC. (2010)											SPRIDE	7.9	7.9	8.0	7.5	7.9	7.8	7.7	7.7	7.7	7.4	7.6	7.5	7.6	7.2											
26005000	3.631	5.570	L	1	8	45					CRACKING	8.0	8.0	8.0	8.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0													
222				2	2.8		36500				RIDE	7.6	7.6	7.5	7.0	7.0	7.8	7.1	7.9	7.8	8.1	8.0	8.0	7.9													
CR 2053(3.7C)										FC125																											
2076112	3.638	4.733	C	2004			0012				CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	5.5*	5.5*	5.5*														
V. E. WHITEHURST & SONS, I(2006)											RIDE	7.7	7.8	8.1	7.6	8.0	8.0	8.0	7.9	7.9	7.8	7.9	7.7														
2076115	3.851	5.590	C	2025			0012																														
26005000	2.080	3.631	L	1	8	45					CRACKING	8.0	8.0	7.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.0													
222				2	2.8		37500				RIDE	8.2	8.0	7.9	7.4	6.9	6.8	8.4	8.3	7.8	8.1	8.0	8.0	7.9													
SIDE ROAD(2.3C)										FC125M																											
2075452	0.522	3.466	C	2006			0012				CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*														
PREFERRED MATERIALS, INC. (2007)											SPRIDE	7.7	7.8	8.1	7.6	8.0	8.0	8.0	7.9	7.9	7.8	7.7	7.6														
4470321	0.400	3.851	C	2024			0012																														
26005000	1.204	2.080	L	1	8	45					CRACKING	8.0	8.0	7.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.0													
222				2	2.8		31500				RIDE	8.2	8.0	7.9	7.4	6.9	6.8	8.4	8.3	7.8	8.1	8.0	8.0	7.9													
NW 78 TER(1.5L)										FC125M																											
											CRACKING	8.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.5	6.5	6.5	6.5														
									(2015)		RIDE	7.7	8.3	7.9	7.4	7.8	7.8	7.5	7.4	7.3	7.1	7.0	6.7														
4470321	0.400	3.851	C	2024			0012																														
26005000	0.400	1.204	L	1	8	45					CRACKING	8.0	8.0	7.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.0													
222				2	2.8		31500				RIDE	8.2	8.0	7.9	7.4	6.9	6.8	8.4	8.3	7.8	8.1	8.0	8.0	7.9													
FRONTAGE RD(0.4L)										FC125M																											
2075452	0.522	3.466	C	2006			0012				CRACKING	8.0	9.0	9.0	9.0	9.0	8.0	6.5	6.5	6.5	4.5*	4.5*	4.3*														
PREFERRED MATERIALS, INC. (2007)											SPRIDE	7.7	7.9	7.9	7.7	7.7	7.8	7.9	7.9	7.8	7.8	7.7	7.6														
4470321	0.400	3.851	C	2024			0012																														
26005000	0.000	0.400	L	1	1	45					CRACKING	9.5	9.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
222				2	2.8		32000				RIDE	7.0	6.7			7.7	7.5	7.6	7.2	7.4	7.2	7.3	7.4	7.4													
										FC125M																											
											CRACKING	10.0	10.0	10.0	10.0		10.0	10.0	8.5	8.5	8.5	8.5	8.5	9.0	7.0											
									(2019)		RIDE	7.2	7.5	6.7	6.4									7.7	7.3											

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26010000	0.000	2.621	R	1	1	65	CRACKING	7.5	7.5	4.5*	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	9.5															
25 441		5.4	2			8200	RIDE	8.5	8.5	8.0	7.4	7.0	6.7	6.1*	8.1	8.1	8.2	8.2	8.1	7.9															
SE 183 PL(0.2R)							FC5M																												
4361571	0.000	11.616	C	2021		0012	CRACKING	9.5	8.0	8.0	6.5	4.5*	4.5*	0.0*	0.0*		10.0	10.0	9.0	10.0	8.5															
PREFERRED MATERIALS, INC. (2023)							SPRIDE	7.8	7.5	8.1	7.9	7.7	7.8	8.1	7.8		9.1	9.0	8.9	8.8	8.6															
26010000	2.621	3.850	R	1	1	45	CRACKING	7.5	7.5	4.5*	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	9.5															
25 441		5.4	2			9600	RIDE	8.5	8.5	8.0	7.4	7.0	6.7	6.1	8.1	8.1	8.2	8.2	8.1	7.9															
EASY ST NE(2.7R)							FC125M																												
4361571	0.000	11.616	C	2021		0012	CRACKING	9.5	8.0	8.0	6.5	4.5*	4.5*	0.0*	0.0*		10.0	10.0	10.0	10.0	8.5															
PREFERRED MATERIALS, INC. (2023)							SPRIDE	7.8	7.5	8.1	7.9	7.7	7.8	8.1	7.8		8.7	8.7	8.7	8.6	8.2															
26010000	3.850	11.400	R	1	1	65	CRACKING	7.5	7.5	4.5*	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	9.5															
25 441		4.7	2			15100	RIDE	8.5	8.5	8.0	7.4	7.0	6.7	6.1*	8.1	8.1	8.2	8.2	8.1	7.9															
PAYNES PARK ENT R(4.2R)							FC5M																												
4361571	0.000	11.616	C	2021		0012	CRACKING	9.5	8.0	8.0	6.5	4.5*	4.5*	0.0*	0.0*		10.0	10.0	9.5	10.0	8.5															
PREFERRED MATERIALS, INC. (2023)							SPRIDE	7.8	7.5	8.1	7.9	7.7	7.8	8.1	7.8		8.9	8.8	8.8	8.7	8.5															
26010000	11.400	13.510	R	1	1	45	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.0															
25 441		5.4	2			18400	RIDE	8.0	8.0	7.8	7.0	6.7	6.4	8.0	7.8	7.8	7.9	7.7	7.6	7.7															
RAMP FROM SR 331(11.5R)							FC125M																												
4470331	11.616	13.499	R	2023		0012	CRACKING	9.0	9.0	9.0	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.0															
ANDERSON COLUMBIA CO., INC(2025)							SPRIDE	7.6	7.3	7.4	7.6	7.4	7.3	7.3	7.1	6.9	6.9	6.8	8.2	7.9	7.5														
26010000	13.510	15.750	R	1	1	35	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5		10.0	10.0	10.0															
25 441		5.4	2			29000	RIDE	7.4	7.1	6.9	6.6	6.5	6.3	5.9	5.9	5.7		8.0	7.8	7.5															
SW 9TH AVE(13.6R)							FC125M																												
2078499	13.444	17.471	R	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	7.0	7.0	7.0	7.0	4.0*														
V. E. WHITEHURST & SONS, I(2011)							SPRIDE	7.5	7.0	7.0	7.3	7.1	7.1	7.1	7.1	7.0	6.9	7.0	7.1	6.6	6.2														
26010000	15.750	17.471	R	1	1	45	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0															
25 441		5.4	2			17900	RIDE	7.4	7.1	6.9	6.6	6.5	6.3	5.9	5.9	5.7	6.2	8.0	7.8	7.5															
LOWES(15.9C)							FC125M																												
2078499	13.444	17.471	R	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	7.0	7.0	7.0	6.5	3.5*														
V. E. WHITEHURST & SONS, I(2011)							SPRIDE	7.5	7.0	7.0	7.3	7.1	7.1	7.1	7.1	7.0	6.9	7.0	7.1	6.9	6.5														
26010000	13.510	17.471	L	1	1	45	CRACKING	7.5	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0															
25 441		5.4	2			17900	RIDE	7.5	7.5	7.3	6.9	6.9	6.6	6.1	5.8	6.2		7.9	7.8	7.6															
DIAMOND RD(13.6L)							FC125M																												
2078499	13.444	17.471	L	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	7.0	7.0	7.0	7.0	4.0*														
V. E. WHITEHURST & SONS, I(2011)							SPRIDE	7.6	7.3	6.8	7.4	7.4	7.3	7.3	7.1	7.3	7.3	7.2	7.3	7.0	6.6														
26010000	11.400	13.510	L	1	1	45	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	8.0															
25 441		5.4	2			18400	RIDE	8.3	8.4	8.0	7.6	7.2	7.0	7.9	6.8	6.8	7.7	7.7	7.6	7.6															
SR 331(11.6C)							FC125M																												
4470331	11.616	13.499	L	2023		0012	CRACKING	8.0	8.0	8.0	7.0	7.0	6.5	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	9.0														
ANDERSON COLUMBIA CO., INC(2025)							SPRIDE	7.6	7.0	7.4	7.4	7.3	7.3	7.2	6.9	6.9	6.9	6.8	8.2	7.9	7.5														
26010000	3.780	11.400	L	1	1	65	CRACKING	7.5	7.5	6.5	6.5	3.5*	0.0*	0.0*	10.0	10.0	10.0	10.0	10.0	9.5															
25 441		4.7	2			15100	RIDE	8.4	8.4	8.1	7.4	6.9	6.6	6.2*	7.0	7.6	8.2	8.2	8.2	8.0															
CR 18(4.5L)							FC5M																												
4361571	0.000	11.616	C	2021		0012	CRACKING	9.5	9.0	8.0	6.5	6.5	4.5*	0.0*	0.0*		10.0	10.0	9.5	10.0	8.5															
PREFERRED MATERIALS, INC. (2023)							SPRIDE	8.0	7.8	8.2	8.2	8.1	8.2	8.3	8.2		8.9	8.8	8.8	8.7	8.5															
26010000	2.621	3.780	L	1	1	45	CRACKING	7.5	7.5	6.5	6.5	3.5*	0.0*	0.0*	10.0	10.0	10.0	10.0	10.0	9.5															
25 441		5.4	2			9600	RIDE	8.4	8.4	8.1	7.4	6.9	6.6	6.2	7.0	7.6	8.2	8.2	8.2	8.0															
CHOLOKKA BLVD(2.9L)							FC125M																												
4361571	0.000	11.616	C	2021		0012	CRACKING	9.5	9.0	8.0	6.5	6.5	4.5*	0.0*	0.0*		10.0	10.0	10.0	10.0	8.5															
PREFERRED MATERIALS, INC. (2023)							SPRIDE	8.0	7.8	8.2	8.2	8.1	8.2	8.3	8.2		8.6	8.8	8.7	8.6	8.2															
26010000	0.000	2.621	L	1	1	65	CRACKING	7.5	7.5	6.5	6.5	3.5*	0.0*	0.0*	10.0	10.0	10.0	10.0	10.0	9.5															
25 441		5.4	2			8200	RIDE	8.4	8.4	8.1	7.4	6.9	6.6	6.2*	7.0	7.6	8.2	8.2	8.2	8.0															
VETERANS WAY(0.7L)							FC5M																												
4361571	0.000	11.616	C	2021		0012	CRACKING	9.5	9.0	8.0	6.5	6.5	4.5*	0.0*	0.0*		10.0	10.0	9.3	10.0	8.5															
PREFERRED MATERIALS, INC. (2023)							SPRIDE	8.0	7.8	8.2	8.2	8.1	8.2	8.3	8.2		9.0	8.9	8.8	8.7	8.5															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	AADT / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	DISTRESS RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2031 (PMRS)
26020000	2.404	2.910	R	1	1	30	15800	CRACKING	4.5*	3.5*	3.5*	7.5	7.5	7.5	7.5	7.5	1.0*	1.0*		10.0	10.0	
20			1	4.0			FC95MR	RIDE	3.2*	3.3*	3.1*		4.9*	4.3*	4.1*	3.6*	3.8*	3.2*		7.9	7.8	
CR 329(2.4C)								CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	8.4	8.0	5.0*
		(2012)						RIDE	7.4	7.5	7.0										7.2	6.8
26020000	2.910	3.250	R	1	1	30	18000	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	
20			1	4.0			FC125M	RIDE	6.4*	6.7	6.1	5.9	5.9	5.8	6.0	5.4*	7.5	7.6	7.3	7.4	7.3	
NW 2ND ST(3.0C)																						
2078421	2.903	3.431	C	2008			0012	CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5	7.5	7.5	7.5	8.5	7.5	4.5*
V. E. WHITEHURST & SONS, I		(2009)						RIDE	7.1	7.3	6.8	7.0	6.8	6.7	6.7	6.6	6.4	6.5	6.4	6.4	7.3	6.9
26020000	3.250	6.180	C	1	1	35	12500	CRACKING	9.5	9.5	9.5	9.5	9.0	9.0	9.0	7.5	10.0	10.0	10.0	10.0	10.0	
20 441			4	4.0			FC125M	RIDE	6.7	6.8	6.7	6.5	6.7	6.6	6.5	5.8	7.5	7.6	7.3	7.4	7.3	
CR 338(3.3L)								CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5	7.5	7.5	7.5	8.5	8.3	5.0*
		(2009)						RIDE	7.1	7.3	6.8	7.0	6.8	6.7	6.7	6.6	6.4	6.5	6.4	6.4	6.4	6.0
26020000	6.180	7.383	R	1	1	45	29000	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	
20 441			2	4.0			FC125M	RIDE	8.9	8.9	8.7	8.3	8.4	8.4	8.3	6.6	8.1	8.1	8.1	8.0	8.1	
NW 50TH AVE(6.2R)																						
4286901	6.172	13.517	R	2014			0012	CRACKING	7.0		10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.0	4.5*
PREFERRED MATERIALS, INC.		(2016)						SPRIDE	8.0		8.6	8.7	8.7	8.9	8.9	8.9	8.9	8.8	8.8	8.5	8.2	7.8
26020000	7.383	7.780	R	1	1	45	21000	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	
20 441			2	5.1			FC125M	RIDE	8.9	8.9	8.7	8.3	8.4	8.4	8.3	6.6	8.1	8.1	8.1	8.0	8.1	
SR 121(7.4R)																						
4286901	6.172	13.517	R	2014			0012	CRACKING	7.0		10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	6.5	4.0*
PREFERRED MATERIALS, INC.		(2016)						SPRIDE	8.0		8.6	8.7	8.7	8.9	8.9	8.9	8.9	8.8	8.8	8.5	8.4	8.0
26020000	7.780	16.884	R	1	1	60	21000	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	
20 441			2	5.1			FC5M	RIDE	8.9	8.9	8.7	8.3	8.4	8.4	8.3	6.6	8.1	8.1	8.1	8.0	8.1	
SIDE ROAD(8.0C)																						
4286901	6.172	13.517	R	2014			0012	CRACKING	7.0		10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.8	7.0	3.5*
PREFERRED MATERIALS, INC.		(2016)						SPRIDE	8.0		8.6	8.7	8.7	8.9	8.9	8.9	8.9	8.8	8.8	8.8	8.8	8.6
26020000	16.884	19.140	R	1	1	45	26500	CRACKING	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	4.5*	10.0	10.0	10.0	10.0	10.0	
20 441			2	5.1			FC125	RIDE	8.2	8.2	7.9	7.4	7.3	7.2	7.0	6.1	8.4	8.3	8.3	8.3	8.3	
NW 125 ST(17.0R)																						
2076483	16.802	19.743	C	2008			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.0	6.0*	6.0*	6.0*	6.0*	4.5*	3.5*	1.9*	0.0*
ANDERSON COLUMBIA CO., INC		(2009)						SPRIDE	8.2	8.3	7.3	7.1	7.9	8.0	7.9	7.9	7.9	7.8	7.9	7.8	7.8	7.4
2076487	16.800	19.700	C	2026			0012															
26020000	19.140	19.471	R	1	1	45	34000	CRACKING	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	4.5*	10.0	10.0	10.0	10.0	10.0	
20 441			2	5.1			FC125	RIDE	8.2	8.2	7.9	7.4	7.3	7.2	7.0	6.1	8.4	8.3	8.3	8.3	8.3	
								CRACKING	10.0	10.0	10.0		10.0	10.0	10.0	9.0	9.0	9.0	9.0	6.8	8.0	6.0*
		(2018)						RIDE	8.2	8.3	7.3										7.6	7.2
2076487	16.800	19.700	C	2026			0012															
26020000	19.471	19.685	R	1	1	45	34000	CRACKING	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	4.5*	10.0	10.0	10.0	10.0	10.0	
20 441			2	5.1			FC125	RIDE	8.2	8.2	7.9	7.4	7.3	7.2	7.0	6.1	8.4	8.3	8.3	8.3	8.3	
NW 167TH BLVD(19.7R)																						
								CRACKING	10.0	10.0	10.0		4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	8.5
		(2023)						RIDE	8.2	8.3	7.3		7.3	7.6	7.7	8.1	7.8	8.2	8.3	8.0	8.3	7.9
2076487	16.800	19.700	C	2026			0012															
26020000	19.685	20.172	R	1	2	45	34000	CRACKING	4.5*	4.5*	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.5	
20 441			2	5.1			FC125M	RIDE	8.6	8.5	8.3	7.2	7.1	8.3	8.1	6.4	8.2	8.3	8.2	8.1	7.9	
SANTA FE HIGH SCHOOL ENT(19.8R)																						
4361731	19.685	25.123	R	2018			0012	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	8.9	9.6	8.0
PREFERRED MATERIALS, INC.		(2020)						SPRIDE	7.6	7.3	7.8	7.6	7.3	7.6	8.7	8.6	8.8	8.7	8.5	8.7	7.9	7.5
26020000	20.172	23.874	R	1	1	65	25000	CRACKING	4.5*	4.5*	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.5	
20 441			2	5.1			FC5M	RIDE	8.6	8.5	8.3	7.2	7.1	8.3	8.1	6.4*	8.2	8.3	8.2	8.1	7.9	
ALACHUA CITY LIMITS(20.2R)																						
4361731	19.685	25.123	R	2018			0012	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.7	10.0	7.5
PREFERRED MATERIALS, INC.		(2020)						SPRIDE	7.6	7.3	7.8	7.6	7.3	7.6	9.1	9.1	9.1	9.1	9.1	9.0	9.1	8.9

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26020000	23.874	25.010	R	1	1	45	CRACKING	10.0	10.0	9.5	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
25 441			2	5.1	11900		RIDE	8.3	8.4	8.3	7.6	7.7	8.5	8.5	7.6	8.1	8.3	8.3	8.2	8.1															
NE 6 ST(24.2C)							FC125M																												
4361731	19.685	25.123	R	2018		0012	CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	10.0	10.0	10.0	10.0	10.0	9.4	10.0	8.5														
PREFERRED MATERIALS, INC. (2020)							SPRIDE	8.0	8.2	7.8	7.9	7.8	7.9	8.7	8.6	8.6	8.6	8.7	8.7	8.4	8.0														
26020000	25.010	25.750	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.5	10.0	10.0	9.0	9.0	9.0	9.0	8.5	8.5															
25 41			1	5.1	13400		RIDE	8.2	8.2	8.3	7.8	7.9	8.5	8.5	8.4	8.4	8.3	8.3	8.2	8.3															
FIFTH ST NW(25.0C)							FC125M																												
4361731	25.264	25.752	R	2018		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	10.0	10.0	10.0	10.0	10.0	9.2	9.5	8.0														
PREFERRED MATERIALS, INC. (2020)							SPRIDE	8.0	8.2	7.9	8.0	7.9	7.9	8.7	8.7	8.7	8.7	8.7	8.6	8.7	8.3														
26020000	25.750	26.493	C	1	1	55	CRACKING	10.0	10.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
25 41			2	5.1	9200		RIDE	8.1	7.8	8.4	7.9	7.8	8.7	8.7	8.3	8.0	8.2	8.2	8.1	8.1															
SIDE ROAD(25.8C)							FC125M																												
4361731	25.752	26.424	C	2018		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	10.0	10.0	10.0	10.0	10.0	9.2	9.0	7.5														
PREFERRED MATERIALS, INC. (2020)							SPRIDE	8.1	8.1	7.7	7.6	7.8	7.8	8.7	8.7	8.7	8.7	8.7	8.6	8.6	8.2														
26020000	25.183	25.750	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.5	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0															
25 41			1	5.1	13400		RIDE	8.2	8.2	8.3	7.8	7.9	8.5	8.6	8.4	8.5	8.2	8.5	8.5	8.2															
NW 244 ST(25.4L)							FC125M																												
4361731	25.264	25.752	L	2018		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	8.0	10.0	10.0	10.0	10.0	10.0	9.2	10.0	8.5														
PREFERRED MATERIALS, INC. (2020)							SPRIDE	8.3	8.3	7.8	7.9	8.2	8.2	8.7	8.7	8.7	8.7	8.7	8.6	8.5	8.1														
26020000	23.874	25.183	L	1	1	45	CRACKING	9.5	9.5	9.5	9.5	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
25 441			2	5.1	11900		RIDE	8.0	7.9	7.5	7.1	6.9	8.4	8.4	8.2	8.1	8.0	8.0	7.8	7.7															
SR 20(24.0L)							FC125M																												
4361731	19.685	25.264	L	2018		0012	CRACKING	10.0	10.0	9.5	9.5	9.5	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5														
PREFERRED MATERIALS, INC. (2020)							SPRIDE	7.6	7.7	7.5	7.6	7.8	7.8	8.6	8.6	8.6	8.5	8.6	8.5	8.5	8.1														
26020000	20.172	23.874	L	1	1	65	CRACKING	4.5*	4.5*	4.5*	4.5*	1.0*	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5															
20 441			2	5.1	25000		RIDE	8.6	8.4	8.4	6.9	6.9	8.3	8.2	8.2	7.9	8.3	8.2	8.1	8.0															
ALACHUA CITY LIMITS(21.1C)							FC5M																												
4361731	19.685	25.264	L	2018		0012	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.8	7.5														
PREFERRED MATERIALS, INC. (2020)							SPRIDE	7.8	7.6	7.9	7.7	7.6	7.8	9.1	9.1	9.1	9.1	9.1	9.1	9.1	8.9														
26020000	19.685	20.172	L	1	2	45	CRACKING	4.5*	4.5*	4.5*	4.5*	1.0*	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5															
20 441			2	5.1	34000		RIDE	8.6	8.4	8.4	6.9	6.9	8.3	8.2	8.2	7.9	8.3	8.2	8.1	8.0															
CR 235A(20.1L)							FC125M																												
4361731	19.685	25.264	L	2018		0012	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.1	7.5														
PREFERRED MATERIALS, INC. (2020)							SPRIDE	7.8	7.6	7.9	7.7	7.6	7.8	8.5	8.5	8.4	8.2	7.9	8.4	7.9	7.5														
26020000	19.471	19.685	L	1	1	45	CRACKING	8.0	8.0	8.0	7.5	6.5	5.5*	5.5*	3.5*	10.0	10.0	10.0	10.0	10.0															
20 441			2	5.1	34000		RIDE	8.0	8.1	7.9	7.5	7.0	7.2	6.9	6.7	8.0	8.4	8.3	8.3	8.2															
							FC125																														
2076483	16.802	19.743	C	2008		0012	CRACKING	10.0	10.0	10.0		4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	1.2*	1.0*	0.0*														
ANDERSON COLUMBIA CO., INC(2009)							SPRIDE	8.1	8.3	7.6		7.6	7.8	7.6	7.7	7.4	6.9			6.7	6.3														
2076487	16.800	19.700	C	2026		0012																													
26020000	19.140	19.471	L	1	1	45	CRACKING	8.0	8.0	8.0	7.5	6.5	5.5*	5.5*	3.5*	10.0	10.0	10.0	10.0	10.0															
20 441			2	5.1	34000		RIDE	8.0	8.1	7.9	7.5	7.0	7.2	6.9	6.7	8.0	8.4	8.3	8.3	8.2															
							FC125																														
							CRACKING	10.0	10.0	10.0		10.0	10.0	10.0	8.5	7.5	7.5	7.5	5.5*	6.5	4.5*														
				(2018)			RIDE	8.1	8.3	7.6										7.9	7.5														
2076487	16.800	19.700	C	2026		0012																													
26020000	16.884	19.140	L	1	1	45	CRACKING	8.0	8.0	8.0	7.5	6.5	5.5*	5.5*	3.5*	10.0	10.0	10.0	10.0	10.0															
20 441			2	5.1	26500		RIDE	8.0	8.1	7.9	7.5	7.0	7.2	6.9	6.7	8.0	8.4	8.3	8.3	8.2															
NW 128 TER(17.2L)							FC125																												
2076483	16.802	19.743	C	2008		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	6.0*	6.0*	6.0*	3.5*	3.5*	1.4*	0.0*														
ANDERSON COLUMBIA CO., INC(2009)							SPRIDE	8.1	8.3	7.6	7.7	8.0	8.0	7.9	7.9	7.9	7.8	7.8	7.8	7.8	7.4														
2076487	16.800	19.700	C	2026		0012																													
26020000	7.780	16.884	L	1	1	60	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	6.5	5.5*	5.5*	5.5*															
20 441			2	5.1	21000		RIDE	8.8	8.9	8.8	8.3	8.4	8.3	8.2	7.6	7.9	8.0	7.9	7.7	7.7															
NW 68TH AVE(7.9L)							FC5M																												
4286901	6.172	13.517	L	2014		0012	CRACKING	5.5*		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	7.3	6.5	3.0*														
PREFERRED MATERIALS, INC. (2016)							SPRIDE	7.4		8.5	8.5	8.6	8.8	8.7	8.8	8.7	8.7	8.7	8.7	8.6	8.4														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD / %T / FY-P / FY-F	AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26020000 20 441 CR 232(6.5C) 4286901 PREFERRED MATERIALS, INC.	6.180 2 4.0 FC125M 6.172 13.517 (2016)	7.780 29000 L 2014 SPRIDE	L	1	1	45 0012	CRACKING RIDE	10.0 8.8 5.5* 7.4	10.0 8.9	10.0 8.8	10.0 8.3	10.0 8.4	10.0 8.3	9.5 8.2	8.0 7.6	8.0 7.9	6.5 8.0	5.5* 7.9	5.5* 7.7	5.5* 7.7	10.0 8.5	10.0 8.8	9.0 8.7	9.0 8.8	9.0 8.7	8.0 8.7	8.0 8.7	7.0 8.4	4.5* 8.5	8.1
26020000 20 CR 329(2.4C) (2012)	2.404 1 4.0 FC95MR	2.910 15800	L	1	1	30	CRACKING RIDE	3.5* 4.1* 10.0 8.0	3.5* 4.0* 10.0 8.0	3.5* 3.9* 10.0 7.4	7.5 10.0	7.5 4.9*	7.5 4.3*	7.5 4.1*	7.5 3.6*	1.0* 3.8*	1.0* 3.2*	9.5	10.0 8.1	10.0 8.3 8.5 7.4	5.5* 7.0
26020064 20 27 NINTH ST NW(0.0C) 4343211 ANDERSON COLUMBIA CO., INC	0.000 2 6.1 FC125R 0.000 1.188 (2018)	1.188 9900 C 2017 SPRIDE	C	1	1	35 0012	CRACKING RIDE	9.0 8.0 7.0 7.2	9.0 7.9 7.2	9.0 8.0 6.8	9.0 7.6 7.2	10.0 8.0 8.0	10.0 7.7 7.8	9.0 6.7 7.9	9.0 6.6 7.7	9.0 7.5 7.8	8.0 7.4 7.6	8.0 7.3 7.7	7.0 7.3 7.7	7.0 7.3 7.6	10.0 7.2	10.0 7.2	10.0 7.2	10.0 7.2	10.0 7.2	10.0 7.2	8.6 7.2	8.1 7.2	6.0*
26030000 45 27 SW 175 AVE(0.0L) 2077987 ANDERSON COLUMBIA CO., INC	0.000 2 11.2 FC125M 0.000 4.161 (2025)	4.161 5400 C 2024 SPRIDE	C	1	1	60 0012	CRACKING RIDE	3.5* 7.6 9.5 7.7	3.5* 7.5 9.5 7.6	3.5* 6.9 9.5 7.4	1.0* 6.5 9.5 7.3	10.0 7.9 8.0 7.6	10.0 7.2 7.5 7.6	10.0 7.6 7.5 7.5	10.0 7.7 5.5* 7.4	10.0 7.8 5.5* 7.3	10.0 7.9 5.5* 7.2	10.0 7.8 3.5* 7.2	9.5 7.7 10.0 8.6	9.5 7.8 10.0 8.4	9.0 8.0
26030000 45 27 ARCHER RD SW(4.2C) 2077982 V. E. WHITEHURST & SONS, I 2077988	4.161 13.080 2 16.5 FC125 0.000 13.515 (2006) 4.211 13.472	C 1 4897 C 2004 RIDE C 2027	C	1	1	60 0012	CRACKING RIDE	5.5* 7.4 9.5 7.7	5.5* 7.4 9.5 7.6	5.5* 6.8 9.5 7.4	5.5* 6.2* 9.5 7.3	10.0 7.9 8.0 7.6	10.0 7.2 7.5 7.6	10.0 7.6 7.5 7.5	10.0 7.7 7.0 7.5	10.0 7.9 7.0 7.5	10.0 7.8 6.0* 7.4	9.5 7.7 6.0* 7.3	9.5 7.8 6.0* 7.3	2.5* 6.9
26030000 45 27 SW 15 AVE(13.1C) 2077982 V. E. WHITEHURST & SONS, I 2077988	13.080 13.530 1 16.5 FC3 0.000 13.515 (2004) 4.211 13.472	R 1 4897 C 2004 RIDE C 2027	R	1	1	40 0012	CRACKING RIDE	10.0 8.8 9.0 7.7	5.5* 7.4 9.0 7.0	5.5* 6.8 9.0 7.4	10.0 7.8 8.5 7.4	10.0 8.1 8.5 7.6	10.0 8.0 8.5 7.5	10.0 7.8 8.5 7.4	9.0 7.3 7.0 7.4	9.0 7.8 7.0 7.1	9.0 8.0 7.0 6.9	9.0 8.0 7.0 7.0	9.0 8.1 7.0 7.0	9.0 7.8 7.0 6.8	3.0* 6.4
26030000 45 27 NEWBERRY RD W(13.6C) 2077791 WHITEHURST, VE AND SON INC 2077793	13.530 14.206 2 5.9 FC3 13.103 26.418 (2000) 13.714 26.376	R 1 9200 C 1998 S C 2026	R	1	1	40 0221 RIDE 0012	CRACKING RIDE	10.0 8.7 9.5 6.9	10.0 8.6 9.5 6.3	10.0 8.5 9.5 6.5	10.0 8.1 9.5 6.5	10.0 8.1 9.5 7.2	10.0 8.0 8.5 7.0	10.0 8.0 8.5 7.0	10.0 7.8 7.0 6.5	10.0 7.8 7.0 6.7	10.0 7.6 6.0* 6.9	10.0 7.6 6.0* 6.8	10.0 7.3 5.0* 6.5	9.5 7.4 4.8* 6.7	0.5* 6.3
26030000 45 27 NW 9 PL(14.4C) 2077791 WHITEHURST, VE AND SON INC 2077793	14.206 14.718 1 5.9 DGFC 13.103 26.418 (2000) 13.714 26.376	R 1 9200 C 1998 S C 2026	R	1	1	60 0221 RIDE 0012	CRACKING RIDE	10.0 8.9 9.5 7.5	10.0 9.0 9.5 6.9	10.0 8.9 9.5 7.1	10.0 8.6 9.5 6.9	10.0 8.7 9.5 7.3	10.0 7.9 9.5 7.3	9.5 7.9 8.5 7.3	9.5 7.8 7.0 7.3	9.5 7.7 7.0 7.2	9.5 7.7 7.0 7.2	9.5 7.7 5.5* 7.2	9.5 7.8 4.5* 7.1	4.0* 7.0	0.0* 6.6
26030000 45 27 WHITEHURST, VE AND SON INC 2077793	14.718 15.025 2 5.9 FC3 13.103 26.418 (2000) 13.714 26.376	C 1 9200 C 1998 S C 2026	C	1	1	60 0221 RIDE 0012	CRACKING RIDE	10.0 8.9 7.0 7.9	10.0 9.0 7.0 7.4	10.0 8.9 7.0 8.0	10.0 8.6 7.0 7.9	10.0 8.7 7.0 8.3	10.0 8.6 7.0 8.1	10.0 8.0 7.0 8.2	10.0 8.2 6.5 8.2	10.0 8.0 6.0* 8.1	9.0 8.2 5.5* 8.1	8.5 7.9 5.5* 8.1	7.5 7.8 5.5* 8.1	7.0 8.0 3.7* 7.9	0.0* 7.5
26030000 45 27 NW 16 AVE(15.2R) 2077791 WHITEHURST, VE AND SON INC 2077793	15.025 15.625 2 5.9 FC3 13.103 26.418 (2000) 13.714 26.376	C 1 9200 C 1998 S C 2026	C	1	1	60 0221 RIDE 0012	CRACKING RIDE	10.0 8.9 7.0 7.9	10.0 9.0 7.0 7.4	10.0 8.9 7.0 8.0	10.0 8.6 7.0 7.9	10.0 8.7 7.0 8.3	10.0 8.6 7.0 8.1	10.0 8.0 7.0 8.2	10.0 8.2 6.5 8.2	10.0 8.0 6.0* 8.1	9.0 8.2 5.5* 8.1	8.5 7.9 5.5* 8.1	7.5 7.8 5.5* 8.1	7.0 8.0 8.1 8.0	3.5* 7.6
26030000 45 27 NW 24 AVE(15.7R) 2077791 WHITEHURST, VE AND SON INC 2077793	15.625 24.995 2 11.2 FC3 13.103 26.418 (2000) 13.714 26.376	C 1 6400 C 1998 S C 2026	C	1	1	60 0221 RIDE 0012	CRACKING RIDE	10.0 8.9 7.0 7.9	10.0 9.0 7.0 7.4	10.0 8.9 7.0 8.0	10.0 8.6 7.0 7.9	10.0 8.7 7.0 8.3	10.0 8.6 7.0 8.1	10.0 8.0 7.0 8.2	10.0 8.2 6.5 8.2	10.0 8.0 6.0* 8.1	9.0 8.2 5.5* 8.1	8.5 7.9 5.5* 8.1	7.5 7.8 5.5* 8.1	7.0 8.0 4.4* 8.0	0.0* 7.6

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2031 (PMRS)
26030000	24.995	25.798	C	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	8.5	8.5	8.5	
45 27			2	11.2	6400		RIDE	8.9	9.0	8.9	8.7	8.7	8.6	7.6	8.6	8.6	8.5	8.1	8.2	7.9	
HOLLY AVE(25.1R)					FC3																
2077791	13.103	26.418	C	1998	0221		CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.9	6.5	2.0*
WHITEHURST, VE AND SON INC(2000)					S		RIDE	7.8	7.5	7.9	7.8	8.4	8.2	8.3	8.1	8.2	8.1	8.0	8.0	8.0	7.6
2077793	13.714	26.376	C	2026	0012																
26030000	25.798	26.418	C	1	1	30	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	7.0	7.0	7.0	
45 27			2	11.2	11000		RIDE	8.2	7.8	7.1	7.6	7.3	7.0	6.0	6.7	6.4	7.0	6.8	6.5	6.3	
FIFTH AVE(25.8L)					FC125M																
4343201	25.798	26.372	C	2017	0012		CRACKING	7.0	7.0	7.0	7.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.5	7.1	5.0*
ANDERSON COLUMBIA CO., INC(2018)					SPRIDE			6.3	6.0	5.6	5.3*									6.4	6.0
2077793	13.714	26.376	C	2026	0012																
26030000	14.206	14.718	L	1	1	60	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	
45 27			1	5.9	9200		RIDE	8.9	9.0	8.9	8.6	8.7	7.7	6.6	7.7	7.7	7.7	7.7	7.7	7.8	
NW 9 PL(14.4C)					UNKW																
2077791	13.103	26.418	C	1998	0221		CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	8.5	7.0	7.0	7.0	5.5*	4.5*	5.1*	0.5*
WHITEHURST, VE AND SON INC(2000)					S		RIDE	7.5	6.9	7.1	6.9	7.3	7.3	7.3	7.3	7.2	7.2	7.2	7.1	6.6	6.2*
2077793	13.714	26.376	C	2026	0012																
26030000	13.530	14.206	L	1	1	40	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	
45 27			2	5.9	9200		RIDE	8.3	8.0	8.3	7.5	7.8	7.8	6.9	7.7	7.8	7.9	7.6	7.6	7.7	
FIRST AVE SW(13.5L)					FC3																
2077791	13.103	26.418	C	1998	0221		CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	6.5	6.5	6.5	6.5	2.0*
WHITEHURST, VE AND SON INC(2000)					S		RIDE	7.5	6.8	7.3	7.5	7.2	7.6	7.6	7.6	7.5	7.4	7.4	7.3	7.3	6.9
2077793	13.714	26.376	C	2026	0012																
26030000	13.080	13.530	L	1	1	40	CRACKING	10.0	5.5*	5.5*	10.0	10.0	10.0	9.5	8.5	8.5	9.0	9.0	9.0	9.0	
45 27			1	16.5	4897		RIDE	8.8	7.4	6.8	7.8	8.1	7.5	6.6	7.5	7.5	8.0	8.0	8.1	7.8	
SW 15 AVE(13.1C)					FC3																
2077982	0.000	13.515	C	2004	0012		CRACKING	9.0	9.0	9.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.7	4.0*
V. E. WHITEHURST & SONS, I(2004)							RIDE	7.7	7.0	7.4	7.4	7.6	7.5	7.4	7.4	7.1	6.9	7.0	7.0	6.4	6.0
2077988	4.211	13.472	C	2027	0012																
26040000	0.000	1.707	C	1	1	60	CRACKING	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	
20 27			2	5.5	9800		RIDE	8.3	8.4	8.4	8.2	8.3	8.3	7.2	7.1	8.0	8.2	8.0	8.0	8.1	
NW 203 PL(0.1R)					FC125R																
4343221	0.000	1.646	C	2017	0012		CRACKING	9.5	9.5	8.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	9.5	7.5
ANDERSON COLUMBIA CO., INC(2018)					SPRIDE			8.0	8.1	7.4	7.4	8.2	8.1	8.1	8.1	8.0	7.9	7.9	7.8	7.8	7.4
26050000	0.000	3.370	R	1	7	45	CRACKING	7.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	
24A			2	13.0	27500		RIDE	7.8	7.8	7.6	7.3	7.2	8.2	8.5	8.4	8.3	8.2	8.2	8.1	8.1	
SR 25(0.0C)					FC125																
4479621	0.013	3.314	C	2024	0012		CRACKING	9.5	9.5	8.5	7.0	7.0	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	10.0	9.0
V. E. WHITEHURST & SONS, I(2026)					SPRIDE			8.0	8.1	8.0	8.0	7.7	7.7	7.8	7.7	7.6	7.6	7.6	7.4	8.5	8.1
26050000	3.370	6.177	R	1	1	45	CRACKING	10.0	10.0	9.0	7.5	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	
24			2	13.0	25000		RIDE	8.5	8.4	8.1	7.6	8.2	8.3	8.1	8.3	8.2	8.3	8.2	8.1	8.1	
RAMP FROM SR 26(3.4R)					FC125M																
2076142	3.964	7.662	C	2006	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.0	7.0	7.0	4.9*	1.5*
PREFERRED MATERIALS, INC. (2008)							RIDE	8.1	8.1	7.6	7.9	7.7	7.7	7.8	7.5	7.6	7.6	7.5	7.5	7.4	7.0
4394892	3.314	6.095	C	2025	0012																
26050000	6.177	6.977	R	1	7	55	CRACKING	10.0	10.0	9.0	7.5	7.5	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	
24			2	13.0	21000		RIDE	8.5	8.4	8.1	7.6	7.3	6.5	6.6	8.3	8.2	8.3	8.2	8.1	8.1	
SIDE ROAD(6.3C)					FC5M																
4479641	6.095	15.912	R	2024	0012		CRACKING	10.0	9.0	9.0	6.5	6.5	4.5*	4.5*	3.5*	3.5*	1.0*	1.0*	1.0*	10.0	9.0
V. E. WHITEHURST & SONS, I(2026)					SPRIDE			8.1	8.0	8.0	7.9	7.5	7.6	7.4	6.9	6.7	6.4*	5.9*	5.8*	8.2	8.0
26050000	6.977	7.588	R	1	8	45	CRACKING	10.0	10.0	9.0	7.5	7.5	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	
24			2	13.0	21000		RIDE	8.5	8.4	8.1	7.6	7.3	6.5	6.6	8.3	8.2	8.3	8.2	8.1	8.1	
BRITTANY ESTATES(7.2R)					DGFC																
2076142	3.964	7.662	C	2006	0012		CRACKING	10.0	9.0	9.0	6.5	6.5	4.5*	4.5*	3.5*	3.5*	1.0*	1.0*	1.0*		
PREFERRED MATERIALS, INC. (2008)							RIDE	8.1	8.0	8.0	7.9	7.5	7.6	7.4	6.9	6.7	6.4	5.9	5.8		
4479641	6.095	16.806	C	2024	0012																
26050000	7.588	15.809	R	1	7	65	CRACKING	8.5	8.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	
24			2	13.0	18300		RIDE	8.7	8.6	8.9	8.4	8.5	8.5	8.4	8.3	8.3	8.3	8.2	8.3	8.2	
NE 54TH AVE(7.6R)					WC2																
4479641	6.095	15.912	R	2024	0012		CRACKING	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	1.0*		10.0	9.0
V. E. WHITEHURST & SONS, I(2026)					SPRIDE			8.1	8.0	8.2	8.3	8.1	8.3	8.3	8.3	8.2	8.0	7.9		8.7	8.3

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP / W_EMP	EMP / G_EMP / W_EMP	RW / LN / RW / RW	SYS / %T / FY-P / FY-F	TYP SPD / AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26050000	15.809	15.950	R	1	8 45	CRACKING	8.5	8.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5																	
24			2	13.0	16300	RIDE	8.2	8.2	8.9	8.4	8.5	8.5	8.4	8.3	8.3	8.3	8.2	8.3	8.2																	
					FC5																															
2078431	7.642	16.765	C	2002	0012	CRACKING	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	1.0*																			
V E WHITEHURST & SONS INC (2003)						SPRIDE	8.1	8.0	8.2	8.3	8.1	8.3	8.3	8.3	8.2	8.0	7.9																			
4479641	6.095	16.806	C	2024	0012																															
26050000	15.950	16.806	C	1	8 35	CRACKING	8.5	8.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0																	
24			2	13.0	7700	RIDE	8.2	8.2	8.6	7.6	7.2	7.4	7.5	7.2	7.3	7.2	7.2	7.1	7.1																	
NE 141 DR(16.0R)					FC125																															
2078431	7.642	16.765	C	2002	0012	CRACKING	7.5	7.5	7.5	7.5	7.5	6.0*	5.5*	5.5*	5.5*	3.5*	3.5*	3.5*																			
V E WHITEHURST & SONS INC (2003)						SPRIDE	7.1	6.9	7.9	8.0	8.2	8.2	8.1	8.1	8.1	7.7	8.1	8.1																			
4479641	6.095	16.806	C	2024	0012																															
26050000	15.809	15.950	L	1	8 45	CRACKING	8.5	8.5	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.0	8.5																	
24			2	13.0	16300	RIDE	8.2	8.2	8.9	8.4	8.5	8.5	8.3	8.4	8.4	8.4	8.4	8.4	8.4																	
					FC5																															
2078431	7.642	16.765	C	2002	0012	CRACKING	8.5	8.5	7.0	7.0	7.0	7.0	7.0	6.5	4.5*	3.5*	3.5*																			
V E WHITEHURST & SONS INC (2003)						SPRIDE	8.3	8.3	8.5	8.4	8.4	8.6	8.6	8.6	8.5	8.5	8.4																			
4479641	6.095	16.806	C	2024	0012																															
26050000	7.509	15.809	L	1	7 65	CRACKING	8.0	8.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.0	8.5																	
24			2	13.0	18300	RIDE	8.2	8.3	8.9	8.4	8.5	8.5	8.3	8.4	8.4	8.4	8.4	8.4	8.4																	
SIDE ROAD(7.6C)					WC2																															
4479641	6.095	15.912	L	2024	0012	CRACKING	8.5	8.5	7.0	7.0	7.0	7.0	7.0	6.5	4.5*	3.5*	3.5*		10.0	9.0																
V. E. WHITEHURST & SONS, I(2026)						SPRIDE	8.3	8.3	8.5	8.4	8.4	8.6	8.6	8.6	8.5	8.5	8.4		8.7	8.3																
26050000	6.911	7.509	L	1	8 45	CRACKING	9.5	9.5	8.0	8.0	7.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0																	
24			2	13.0	21000	RIDE	8.3	8.3	8.1	8.0	8.2	7.9	7.5	8.3	8.2	8.3	8.2	8.2	8.1																	
BRITANY ESTATES(7.2L)					DGFC																															
2076142	3.964	7.662	C	2006	0012	CRACKING	10.0	10.0	8.0	6.5	6.5	4.5*	4.5*	3.5*	3.5*	1.0*	1.0*	1.0*																			
PREFERRED MATERIALS, INC. (2008)						RIDE	8.1	8.1	8.4	8.2	8.1	8.1	7.8	7.5	7.5	7.2	6.9	6.8																			
4479641	6.095	16.806	C	2024	0012																															
26050000	6.177	6.911	L	1	7 55	CRACKING	9.5	9.5	8.0	8.0	7.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0																	
24			2	13.0	21000	RIDE	8.3	8.3	8.1	8.0	8.2	7.9	7.5	8.3	8.2	8.3	8.2	8.2	8.1																	
SIDE ROAD(6.3C)					FC5M																															
4479641	6.095	15.912	L	2024	0012	CRACKING	10.0	10.0	8.0	6.5	6.5	4.5*	4.5*	3.5*	3.5*	1.0*	1.0*	1.0*	10.0	9.0																
V. E. WHITEHURST & SONS, I(2026)						SPRIDE	8.1	8.1	8.4	8.2	8.1	8.1	7.8	7.5	7.5	7.2	6.9	6.8	8.6	8.4																
26050000	5.900	6.177	L	1	8 45	CRACKING	9.5	9.5	8.0	8.0	7.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0																	
24			2	13.0	21000	RIDE	8.3	8.3	8.1	8.0	8.2	7.9	7.5	8.3	8.2	8.3	8.2	8.2	8.1																	
SR 222(6.0C)					FC125M																															
2076142	3.964	7.662	C	2006	0012	CRACKING	10.0	10.0	10.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.9*																			
PREFERRED MATERIALS, INC. (2008)						RIDE	8.1	7.8	7.6	7.3	7.5	7.4	7.4	7.3	7.4	7.3	7.3	7.2																			
4394892	3.314	6.095	C	2025	0012																															
26050000	3.370	5.900	L	1	1 45	CRACKING	9.5	9.5	8.0	8.0	9.0	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0																	
24			2	13.0	25000	RIDE	8.3	8.3	8.1	8.0	7.9	7.6	6.9	8.3	8.2	8.3	8.2	8.2	8.1																	
SR 26(3.4L)					FC125M																															
2076142	3.964	7.662	C	2006	0012	CRACKING	10.0	10.0	10.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.9*	5.5*	2.0*																
PREFERRED MATERIALS, INC. (2008)						RIDE	8.1	7.8	7.6	7.3	7.5	7.4	7.4	7.3	7.4	7.3	7.3	7.2	7.1	6.7														
4394892	3.314	6.095	C	2025	0012																															
26050000	0.000	3.370	L	1	7 45	CRACKING	8.0	8.0	8.0	6.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0																	
24A			2	13.0	27500	RIDE	7.7	7.6	7.5	7.2	7.1	8.5	7.3	7.1	8.1	8.1	8.0	7.9	7.9																	
SR 25(0.0C)					FC125																															
4479621	0.013	3.314	C	2024	0012	CRACKING	9.5	9.5	9.0	7.5	7.5	7.0	5.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	9.0																
V. E. WHITEHURST & SONS, I(2026)						SPRIDE	7.9	8.0	7.6	7.6	7.8	7.8	7.7	7.5	7.4	7.4	7.4	7.3	8.4	8.0														
26050065	0.000	0.091	C	1	1 35	CRACKING	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0																	
24			1	16.7	8000	RIDE																															
SR 200(0.0C)					DGFC																															
						CRACKING	8.0	8.0	8.0	8.0		10.0	10.0	10.0	10.0	10.0	7.0	9.5	8.2	7.0																
		(2025)				RIDE													5.1*	4.7*																
26050065	0.091	0.411	C	1	4 35	CRACKING	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*																	
24			2	16.7	8000	RIDE	5.4*	5.6	5.4*	4.0*	4.2*	4.0*	3.9*	3.6*	4.1*	3.9*	4.0*	3.7*	3.7*																	
ORMOND ST(0.1C)					LDG																															
						CRACKING	0.0*	7.6	4.5*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*																	
						RIDE	3.5*	6.5	6.5	6.2	5.9	5.4*	5.1*	4.8*	4.7*	4.7*	4.6*	4.2*	4.1*																	
4472031	0.095	0.410	C	2027	0217																															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	AADT	DISTRESS / RATINGS / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26050065	0.411	0.645	C	1	8	45		CRACKING	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
24			2	16.7			8000	RIDE	7.9	7.5	8.1	7.7	8.2	8.2	8.3	7.3	8.1	8.3	8.1	8.2	8.1													
FLORIDA AVE(0.4R)								WC2																											
								CRACKING	9.5	9.5	7.0	7.0	5.5*	5.5*	5.5*	5.0*	5.0*	3.0*	4.5*	3.0*														
							(2003)	RIDE	8.2	8.2	8.0	7.9	7.9	7.9	7.8	7.9	7.9	7.7	7.6	7.4														
26050066	0.000	0.160	C	1	1			CRACKING	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	10.0																					
25			2	6.1			3500	RIDE							6.6																					
								CRACKING																											10.0	9.0
							(2026)	RIDE																											6.6	6.2*
26060000	0.000	2.983	R	1	7	55		CRACKING	7.0	7.0	7.0	7.0	7.0	6.0*	5.5*	3.5*	3.5*	10.0	10.0	10.0	10.0														
200 301			2	28.7			18600	RIDE	8.5	8.3	8.4	7.9	7.9	7.6	7.3	7.2	7.0	8.3	8.0	7.9	7.9													
CR 200A(0.8R)								FC5M																											
4343182	0.000	3.000	C	2025			0012	CRACKING	10.0	10.0	9.5	9.5	9.5	7.5	6.5	6.5	4.5*	3.5*	1.0*	0.7*	10.0	9.0													
ANDERSON COLUMBIA CO., INC					(2026)			SPRIDE	7.8	7.9	7.9	7.5	7.4	7.6	7.5	7.4	6.9	6.5	6.2*	6.3*	8.7	8.5												
26060000	2.983	9.927	R	1	1	65		CRACKING	10.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0													
200 301			2	28.7			18600	RIDE	9.0	9.0	8.9	8.4	8.5	8.5	8.4	8.1	7.9	8.4	8.2	8.2	8.2													
CEMETARY ENT(4.1R)								FC5M																											
4343181	2.966	9.927	C	2017			0012	CRACKING	7.0	6.5	6.5	6.5		10.0	10.0	9.0	9.0	9.0	9.0	8.8	9.2	6.5												
ANDERSON COLUMBIA CO., INC					(2019)			SPRIDE	8.1	8.3	8.5	8.3		8.7	8.8	8.7	8.7	8.7	8.7	8.7	8.6	8.4												
26060000	9.927	11.853	R	1	1	45		CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	6.5													
200 301			2	28.7			19000	RIDE	7.7	8.4	8.3	8.1	8.1	7.9	8.1	7.5	7.8	7.8	7.6	7.4	7.3													
BOUNDARY ST(10.6C)								FC125M																											
4305551	9.891	11.853	C	2015			0012	CRACKING	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	6.7	6.1*	4.0*												
ANDERSON COLUMBIA CO., INC					(2016)			SPRIDE	6.8	6.3	8.4	8.2	8.1	8.1	8.0	8.1	8.1	7.8	7.6	7.7	7.5	7.1												
26060000	11.853	12.265	R	1	1	55		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.0	8.0	7.0	7.0													
200 301			2	28.7			20500	RIDE	8.9	8.9	8.8	8.4	8.6	8.5	8.2	7.9	7.9	8.4	8.3	8.3	8.2													
FRONTAGE RD(12.1R)								FC5																											
2077941	2.860	20.816	C	1999			0221	CRACKING	7.0	6.5	6.5	6.5	6.5	6.5	6.0*	4.5*	4.5*	3.5*	3.5*	3.5*	4.6*	0.0*												
ANDERSON COLUMBIA CO., INC					(2000)			SPRIDE	8.2	8.3	8.2	8.4	8.4	8.5	8.6	8.6	8.6	8.6	8.5	8.5	8.1	7.9												
2077943	11.526	20.242	C	2025			0012																												
26060000	12.265	20.242	R	1	8	65		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.0	8.0	7.0	7.0													
200 301			2	28.7			20500	RIDE	8.9	8.9	8.8	8.4	8.6	8.5	8.2	7.9	7.9	8.4	8.3	8.3	8.2													
SE 41 LN(12.9R)								FC5																											
2077941	2.860	20.816	C	1999			0221	CRACKING	7.0	6.5	6.5	6.5	6.5	6.5	6.0*	4.5*	4.5*	3.5*	3.5*	3.5*														
ANDERSON COLUMBIA CO., INC					(2000)			SPRIDE	8.2	8.3	8.2	8.4	8.4	8.5	8.6	8.6	8.6	8.6	8.5	8.5														
2077943	11.526	20.242	C	2025			0012																												
26060000	20.242	20.389	R	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.0	8.0	10.0	10.0													
200 301			2	36.7			15200	RIDE	8.9	8.9	8.8	8.4	8.6	8.5	8.2	7.9	7.9	8.4	8.3	8.4	8.4													
SR 26(20.3C)								DGFC																											
2077564	20.242	26.115	R	2010			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	6.5	6.5	6.5	6.5	3.5*												
PREFERRED MATERIALS, INC.					(2012)			SPRIDE	8.4	8.5	8.1	8.4	8.3	8.5	8.5	8.4	8.4	8.4	8.2	8.3	7.1	6.7												
2077565	20.242	26.115	C	2028			0012																												
26060000	20.389	25.373	R	1	1	65		CRACKING	9.5	9.5	9.5	8.0	8.0	7.0	6.0*	4.5*	4.5*	4.5*	4.5*	10.0	10.0													
200 301			2	36.7			15200	RIDE	8.9	8.9	8.8	8.3	8.4	8.2	8.0	7.5	7.5	7.7	7.4	8.4	8.4													
NE 71 PL(20.5C)								FC5MW																											
2077564	20.242	26.115	R	2010			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	6.5	6.5	6.5	5.5*	0.5*												
PREFERRED MATERIALS, INC.					(2012)			SPRIDE	8.4	8.5	8.1	8.4	8.3	8.5	8.5	8.4	8.4	8.4	8.2	8.3	8.2	8.0												
2077565	20.242	26.115	C	2028			0012																												
26060000	25.373	26.115	R	1	1	45		CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.0	7.0	5.0*	5.0*	5.0*	10.0	10.0													
200 301			2	36.7			15200	RIDE	8.9	9.0	8.6	8.5	8.5	8.4	8.4	7.9	7.6	8.2	8.0	8.4	8.4													
NE 138 AVE(25.5R)								FC125M																											
2077564	20.242	26.115	R	2010			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	6.5	6.5	5.5*	3.9*	1.0*												
PREFERRED MATERIALS, INC.					(2012)			SPRIDE	8.4	8.5	8.1	8.4	8.3	8.5	8.5	8.4	8.4	8.4	8.2	7.6	7.6	7.2												
2077565	20.242	26.115	C	2028			0012																												
26060000	26.115	26.950	R	1	1	45		CRACKING	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0													
200 301			2	36.7			25500	RIDE	8.0		8.0	7.7	8.1	7.8	7.9	6.8	6.9	7.9	8.0	7.8	7.7												
CR 1475(26.3C)								FC125M																											
4323111	26.115	29.546	C	2017			0012	CRACKING	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	9.1	7.0												
V. E. WHITEHURST & SONS, I					(2018)			SPRIDE	7.8	8.1	7.4	7.5	8.6	8.5	8.5	8.4	8.5	8.4	8.4	8.4	8.3	7.9												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26060000	26.950	29.546	R	1	1	65	CRACKING	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5														
200 301			2	36.7		25500	RIDE	8.0		8.5	8.0	8.1	8.1	7.7	7.5	7.4	8.0	7.9	8.0	7.2														
FLEA MARKET ENT(28.0R)							FC5M																												
4323111	26.115	29.546	C	2017		0012	CRACKING	9.5	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.8	5.0*														
V. E. WHITEHURST & SONS, I			(2019)				SPRIDE	7.6	8.0	7.7	7.7		8.7	8.9	8.8	8.8	8.8	8.8	8.7	8.7	8.5														
26060000	26.950	29.546	L	1	1	65	CRACKING	9.0		10.0	10.0	10.0	10.0	9.0	8.0	7.5	7.5	7.5	7.5	7.5															
200 301			2	36.7		25500	RIDE	8.0		8.4	7.8	7.9	7.9	7.4	7.6	7.3	7.7	7.6	7.5	7.4														
UNSIGNED(27.5L)							FC5M																												
4323111	26.115	29.546	C	2017		0012	CRACKING	7.5	6.5	4.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	6.8	4.0*														
V. E. WHITEHURST & SONS, I			(2019)				SPRIDE	7.3	7.1	7.3	7.6		8.8	8.9	8.8	8.8	8.8	8.8	8.7	8.7	8.5														
26060000	26.115	26.950	L	1	1	45	CRACKING	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5															
200 301			2	36.7		25500	RIDE	8.0		8.2	7.7	7.6	7.9	6.6	7.6	8.0	7.9	7.8	7.9	7.8														
KENNARD ST(26.2L)							FC125M																												
4323111	26.115	29.546	C	2017		0012	CRACKING	9.5	9.5	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.7	6.5														
V. E. WHITEHURST & SONS, I			(2018)				SPRIDE	7.9	7.6	7.2	7.4	8.6	8.6	8.5	8.5	8.5	8.5	8.4	8.5	8.4	8.0														
26060000	25.373	26.115	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5	6.5	10.0	10.0															
200 301			2	36.7		15200	RIDE	8.8	8.9	8.7	8.3	8.5	8.3	8.1	8.2	7.5	7.9	8.1	8.4	8.4														
MAIN ST(25.4L)							FC125M																												
2077564	20.242	26.207	L	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	6.5	6.5	6.5	5.5*	4.2*	1.5*														
PREFERRED MATERIALS, INC.			(2012)				SPRIDE	8.3	8.2	8.4	8.4	8.4	8.5	8.5	8.4	8.3	8.3	8.2	7.5	7.5	7.1														
2077565	20.242	26.115	C	2028		0012																													
26060000	20.389	25.373	L	1	1	65	CRACKING	9.5	9.5	9.5	8.0	8.0	8.0	7.0	6.5	4.5*	4.5*	4.5*	10.0	10.0															
200 301			2	36.7		15200	RIDE	8.9	8.9	8.8	8.4	8.4	8.3	7.8	7.8	7.4	7.8	7.3	8.4	8.4														
NE 71 PL(20.5C)							FC5MW																												
2077564	20.242	26.207	L	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	6.5	6.5	6.5	5.5*	3.3*	0.0*														
PREFERRED MATERIALS, INC.			(2012)				SPRIDE	8.3	8.2	8.4	8.4	8.4	8.5	8.5	8.4	8.3	8.3	8.2	8.2	8.0	7.8														
2077565	20.242	26.115	C	2028		0012																													
26060000	20.242	20.389	L	1	1	45	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	8.5	7.5	7.5	7.5	7.5	10.0	10.0															
200 301			2	36.7		15200	RIDE	9.0	9.0	8.9	8.5	8.5	8.5	8.3	7.9	7.9	8.4	8.3	8.4	8.4														
SR 26(20.3C)							DGFC																												
2077564	20.242	26.207	L	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	6.5	6.5	6.5	5.5*	6.5	3.5*														
PREFERRED MATERIALS, INC.			(2012)				SPRIDE	8.3	8.2	8.4	8.4	8.4	8.5	8.5	8.4	8.3	8.3	8.2	8.2	5.4*	5.0*														
2077565	20.242	26.115	C	2028		0012																													
26060000	12.265	20.242	L	1	8	65	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	8.5	7.5	7.5	7.5	7.5	7.0	7.0															
200 301			2	28.7		20500	RIDE	9.0	9.0	8.9	8.5	8.5	8.5	8.3	7.9	7.9	8.4	8.3	8.3	8.3														
SE 24 AVE(13.8L)							FC5																												
2077941	2.860	20.816	C	1999		0221	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	5.5*	3.5*	3.5*	3.5*																	
ANDERSON COLUMBIA CO., INC			(2000)				SPRIDE	8.2	8.1	8.3	8.4	8.4	8.6	8.6	8.6	8.5	8.5	8.5	8.5															
2077943	11.526	20.242	C	2025		0012																													
26060000	11.853	12.265	L	1	1	55	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	8.5	7.5	7.5	7.5	7.5	7.0	7.0															
200 301			2	28.7		20500	RIDE	9.0	9.0	8.9	8.5	8.5	8.5	8.3	7.9	7.9	8.4	8.3	8.3	8.3														
							FC5																												
2077941	2.860	20.816	C	1999		0221	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	5.5*	3.5*	3.5*	3.5*	3.8*	0.0*														
ANDERSON COLUMBIA CO., INC			(2000)				SPRIDE	8.2	8.1	8.3	8.4	8.4	8.6	8.6	8.6	8.5	8.5	8.5	8.5	8.1	7.9														
2077943	11.526	20.242	C	2025		0012																													
26060000	9.927	11.853	L	1	1	45	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	8.0	7.0	7.0	6.5	6.5															
200 301			2	28.7		19000	RIDE	8.2	8.1	7.9	7.9	7.9	7.6	6.8	6.5	6.4	7.5	7.0	6.9	6.9														
JOHNSON RD(10.0L)							FC125M																												
4305551	9.891	11.853	C	2015		0012	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	6.7	4.5*														
ANDERSON COLUMBIA CO., INC			(2016)				SPRIDE	6.8	6.6	8.0	8.1	8.1	8.0	8.0	8.0	8.0	7.7	7.4	7.5	7.3	6.9														
26060000	2.983	9.927	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	8.0	8.0	7.0	7.0	8.0	8.0	7.5	7.5															
200 301			2	28.7		18600	RIDE	8.9	8.9	8.8	8.4	8.5	8.4	8.3	8.0	7.8	8.3	8.2	8.2	8.1														
SE 177 PL(4.4L)							FC5M																												
4343181	2.966	9.927	C	2017		0012	CRACKING	7.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	9.3	9.1	6.5														
ANDERSON COLUMBIA CO., INC			(2019)				SPRIDE	8.0	7.8	8.2	8.2		8.7	8.8	8.8	8.8	8.7	8.7	8.7	8.7	8.5														
26060000	0.000	2.983	L	1	7	55	CRACKING	7.0	7.0	7.0	6.5	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0															
200 301			2	28.7		18600	RIDE	8.1	8.5	8.4	7.7	7.4	7.3	6.4*	6.9	6.5	8.1	7.9	8.0	7.9														
S CR-325(1.2L)							FC5M																												
4343182	0.000	3.000	C	2025		0012	CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	6.5	5.5*	3.5*	2.5*	2.5*	2.5*	10.0	9.0														
ANDERSON COLUMBIA CO., INC			(2026)				SPRIDE	7.8	7.6	7.7	7.7	7.6	7.7	7.7	7.5	7.1	6.8	6.6	6.0*	8.6	8.4														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26070000	0.000	3.030	C	1	1	60	CRACKING	7.0	7.0	6.5	4.5*	4.5*	4.5*	3.5*	10.0	10.0	10.0	9.5	9.0	9.0															
26			2	5.2	11500		RIDE	8.2	8.1	7.6	7.4	7.3	7.0	6.6	8.2	8.2	7.9	8.0	8.0	7.9															
SIDE ROAD(1.6L)						FC125																													
2078503	0.000	1.877	C	2007		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	7.0	7.0	7.0	6.0*	5.2*	2.0*															
ANDERSON COLUMBIA CO., INC(2008)							RIDE	7.8	7.6	7.6	7.3	7.6	7.6	7.5	7.6	7.6	7.4	7.3	7.3	7.3	6.9														
2078502	0.000	4.031	C	2027		0213																													
26070000	3.030	4.190	R	1	1	50	CRACKING	10.0	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
26			2	5.2	21500		RIDE	8.5	8.5		8.2	8.4	8.4	8.3	8.3	8.3	8.3	8.2	8.2	8.0															
SR 45(3.0C)						FC125M																													
4412621	3.030	7.832	R	2021		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	10.0	10.0	10.0	10.0	10.0	8.5															
PREFERRED MATERIALS, INC. (2022)							SPRIDE	8.0	8.2	7.8	7.4	7.7	7.8	7.6	7.6	8.6	8.6	8.6	8.5	8.5	8.1														
2078502	0.000	4.031	C	2027		0213																													
26070000	4.190	7.827	R	1	1	60	CRACKING	10.0	10.0	8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0															
26			2	5.2	23000		RIDE	8.5	8.5	8.4	8.2	8.4	8.4	8.3	8.3	8.3	8.3	8.2	8.2	8.1															
SIDE ROAD(4.2C)						FC5M																													
4412621	3.030	7.832	R	2021		0012	CRACKING	8.0	6.5	6.5	6.5	6.5	4.5*	3.5*	3.5*	10.0	10.0	10.0	9.5	10.0	8.0															
PREFERRED MATERIALS, INC. (2022)							SPRIDE	8.1	7.9	8.2	8.2	8.1	8.2	8.3	8.3	9.1	9.0	9.0	8.9	8.8	8.6														
26070000	7.827	9.830	R	1	1	50	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5															
26			2	5.2	23000		RIDE		8.6	8.5	8.3	8.3	8.2	8.2	8.2	8.1	8.1	8.0	7.9	7.8															
SW 174 ST(8.0R)						FC125																													
2077581	8.068	9.705	C	2000		0213	CRACKING	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	5.5*	3.5*	1.0*	1.0*	1.0*	0.0*															
HUBBARD CONSTRUCTION COMPA(2002)							SPRIDE	7.8	7.7	7.3	7.3	7.3	7.3	7.2	7.3	7.2	7.1	6.8	6.9	6.9	6.5														
2076683	7.827	14.050	C	2025		0012																													
26070000	9.830	12.140	R	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0															
26			2	5.2	26000		RIDE	8.8	8.8	8.6	8.5	8.6	8.3	8.5	8.4	8.4	8.4	8.4	8.3	8.3															
CR 241(9.9R)						DGFC																													
2076681	9.602	12.164	C	1997		0213	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	2.5*															
WHITE CONSTRUCTION CO INC (2000)							S RIDE	8.3	8.2	7.8	7.9	7.8	8.1	8.1	8.0	8.0	8.0	7.9	8.0	7.9	7.5														
2076683	7.827	14.050	C	2025		0012																													
26070000	12.140	14.048	R	1	1	45	CRACKING	6.5	4.5*	2.0*	2.0*	2.0*	2.0*	10.0	10.0	10.0	10.0	9.5	9.5	9.5															
26			2	5.2	30500		RIDE	7.2	6.9	6.7	6.6	6.8	6.3	8.7	8.4	8.5	8.4	8.4	8.2	8.2															
NW 98TH ST(12.9C)						FC95M																													
2075943	12.317	14.048	C	2005		0012	CRACKING	9.5	9.5	9.5	8.0	8.0	8.0	8.0	7.0	7.0	6.5	6.5	6.2*	5.9*	2.5*															
V. E. WHITEHURST & SONS, I(2007)							RIDE	8.2	8.3	7.7	7.4	7.7	7.9	7.9	7.8	7.8	7.8	7.6	7.7	7.7	7.3														
2076683	7.827	14.050	C	2025		0012																													
26070000	14.048	15.800	R	1	1	35	CRACKING	10.0	10.0	10.0	9.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5															
26			3	1.6	52500		RIDE	8.6	8.7	8.2	7.7	7.5	6.8	6.9	7.1	7.0	6.9	6.8	6.7	6.8															
NW 80 BLVD(14.1R)						FC125M																													
4305421	14.589	15.649	R	2015		0012	CRACKING	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.7	6.5															
PREFERRED MATERIALS, INC. (2018)							SPRIDE	6.6	6.3	6.3		8.2	8.0	8.1	8.1	8.0	7.9	7.9	7.9	7.6	7.2														
26070000	15.800	16.973	R	1	1	45	CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	8.0	8.0	7.0	7.0															
26			2	1.6	24500		RIDE	7.7	7.6	7.3	7.6	7.4	7.6	6.8	7.2	7.5	7.9	7.9	7.7	7.6															
NW 52ND TER(15.8R)						FC125																													
4305421	15.800	16.973	R	2015		0012	CRACKING	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.9	8.7	6.5															
PREFERRED MATERIALS, INC. (2018)							SPRIDE	7.3	6.8	7.2	7.0	8.0	8.2	8.0	8.1	8.1	7.6	8.0	7.8	7.9	7.5														
26070000	16.973	17.601	R	1	1	35	CRACKING	9.0	9.0	9.0	8.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5															
26			2	1.6	19500		RIDE	7.7	6.6	5.9	6.4		7.2	7.1	7.0	6.7	6.6	6.7	6.5	6.5															
W 38TH ST(17.0R)						FC125																													
2078171	17.139	17.597	C	2004		0012	CRACKING	9.5	9.5	9.5	8.0	8.0	8.0	8.0	7.0	7.0	6.5	6.5	5.2*	4.6*	1.0*															
PREFERRED MATERIALS, INC. (2006)							SPRIDE	6.6	6.3	5.7	5.3*	5.5	5.9	5.9	5.9	6.0	5.7	6.1	5.9	5.9	5.5														
2078175	16.961	18.884	C	2027		0012																													
26070000	17.601	18.520	C	1	1	35	CRACKING	2.0*	2.0*	2.0*	2.0*	2.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5															
26			3	1.6	20500		RIDE	6.5	6.2	5.5	4.8*		8.0	7.6	7.5	7.4	7.6	7.6	7.5	7.4															
SW 32ND ST(17.7R)						FC125																													
2078171	17.597	18.453	C	2004		0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	6.0*	6.0*	6.0*	6.0*	5.7*	2.0*															
				(2006)			RIDE	7.3	6.8	6.8	7.0	6.9	7.0	6.8	7.0	6.9	6.9	6.4	6.9	6.7	6.3													
2078175	16.961	18.884	C	2027		0012																													
26070000	18.520	18.885	R	1	1	35	CRACKING	2.0*	2.0*	9.0	8.0	8.0	8.0		10.0	10.0	10.0	10.0	10.0	10.0															
26			1	1.6	20500		RIDE	6.5	6.2	7.3	7.1	6.6	6.5		6.5	6.7	6.7	6.7	6.8	6.8															
SR-26A/NW 21ST TER(18.7R)						FC125																													
2077901	18.462	18.890	C	2005		0005	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	6.0*	5.0*	4.5*	1.0*															
ANDERSON COLUMBIA CO., INC(2008)							SPRIDE	6.9	6.3	6.8	7.0	6.4	6.5	6.7	6.6	6.5				5.5	5.1*															
2078175	16.961	18.884	C	2027		0012																													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD / %T / FY-P / FY-F	AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26070000	18.885	19.522	R	1	1	25		CRACKING	10.0	10.0	9.0	8.0	8.0	8.0	8.0	7.0	6.5	6.5	10.0	10.0	10.0														
26			2	1.6			22000	RIDE	7.3	7.7	7.3	7.1	6.6	6.5	5.9	5.9	6.2	6.2	7.1	6.9	6.7														
FLETCHER DR(19.1R)							FC125M																												
2076652	18.890	20.012	R	2010			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	7.0	6.0*	7.0	4.0*													
PREFERRED MATERIALS, INC. (2011)								RIDE	6.7	6.4	6.3	6.2	6.1	6.2	6.0	6.0	5.8	5.9	5.5	5.7	5.6	5.2*													
4355582	18.875	21.167	C	2028			0012																												
26070000	19.522	19.960	R	1	1	30		CRACKING	10.0	10.0	9.0	8.0	8.0	8.0	8.0	7.0	6.5	2.0*	10.0	10.0	10.0														
24			2	1.6			17700	RIDE	8.1	7.7	7.3	7.1	6.6	6.5	5.9	5.9	6.2	5.1*	7.1	6.9	6.7														
TWELFTH ST(19.6C)							FC125M																												
2076652	18.890	20.012	R	2010			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	7.0	6.0*	3.5*	0.5*													
PREFERRED MATERIALS, INC. (2011)								RIDE	6.7	6.4	6.3	6.2	6.1	6.2	6.0	6.0	5.8	5.9	5.5	5.7	5.4*	5.0*													
4355582	18.875	21.167	C	2028			0012																												
26070000	19.960	21.167	R	1	1	30		CRACKING	9.5	9.5	9.5	9.5	9.5	8.0	8.0	8.0	8.0	5.5*	10.0	10.0	10.0														
20			2	1.6			19000	RIDE	7.6	7.3	7.2	6.6	6.4	6.0	5.6	6.2	5.7	5.8	7.1	6.9	6.7														
SW 7TH ST(20.0R)							FC125M																												
2076652	20.266	21.126	R	2010			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	7.0	6.0*	7.0	4.0*													
PREFERRED MATERIALS, INC. (2011)								RIDE	6.7	6.4	6.3	6.2	6.1	6.2	6.0	6.0	5.8	5.9	5.5	5.7	5.7	5.3*													
4355582	18.875	21.167	C	2028			0012																												
26070000	18.885	21.167	L	1	1	30		CRACKING	9.0	9.0	9.0	9.0	7.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0														
24			2	1.6			22000	RIDE	7.3	7.0	6.6	6.2	6.4	5.9	5.8	5.9	5.8	6.0	7.0	7.2	7.0														
NINETEENTH ST NW(19.0L)							FC125M																												
2076652	18.890	20.012	L	2010			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.0	4.0*													
PREFERRED MATERIALS, INC. (2011)								RIDE	7.0	7.1	6.0	5.7	5.9	5.8	5.8	5.7	5.7	5.4*	5.1*	5.3*	5.3*	4.9*													
4355582	18.875	21.167	C	2028			0012																												
26070000	18.520	18.885	L	1	1	35		CRACKING	2.0*	2.0*	10.0	10.0	9.5	8.0		10.0	8.0	10.0	10.0	10.0	10.0														
26			2	1.6			20500	RIDE	6.5	6.2	8.0	7.8	7.8	7.3		7.1	7.0	7.1	6.5	6.5	6.2														
NW 22ND ST(18.6L)							FC125																												
								CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	6.1*	5.7*	2.5*													
							(2010)	RIDE	6.2	6.3	6.1	5.8	5.9	6.0	6.0	6.0	5.7	5.3*	5.6	5.8	5.7	5.3*													
2078175	16.961	18.884	C	2027			0012																												
26070000	16.973	17.601	L	1	1	35		CRACKING	9.5	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
26			2	1.6			19500	RIDE	6.9	6.9	6.5	6.4	6.3	7.5	7.4	7.3	7.2	7.1	7.0	6.9	6.9														
MOVIE THEATER ENT(17.0L)							FC125																												
2078171	17.139	17.597	C	2004			0012	CRACKING	10.0	10.0	10.0	9.5	9.5	8.0	8.0	7.0	7.0	7.0	7.0	6.0*	4.0*	0.5*													
PREFERRED MATERIALS, INC. (2006)							SPR	RIDE	7.1	6.9	6.6	6.9	6.6	6.5	6.5	6.3	6.6	6.6	6.7	6.4	6.4	6.0													
2078175	16.961	18.884	C	2027			0012																												
26070000	15.800	16.973	L	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5														
26			2	1.6			24500	RIDE	8.8	8.7	8.5	8.1	7.9	8.0	7.5	8.0	7.6	8.0	7.6	7.8	7.6														
NW 48TH BLVD(16.1C)							FC125																												
4305421	15.800	16.973	L	2015			0012	CRACKING	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.9	7.0													
PREFERRED MATERIALS, INC. (2018)							SPR	RIDE	7.4	7.7	7.8	7.8	8.4	8.3	8.4	8.3	8.1	8.2	8.2	8.2	8.1	7.7													
26070000	14.048	15.800	L	1	1	35		CRACKING	10.0	10.0	9.0	9.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5														
26			3	1.6			52500	RIDE	8.2	8.0	7.8	7.6	7.6	7.2	6.8	7.1	7.1	7.0	7.2	6.9	6.7														
NEWBERRY CROSSING SHOPPI(14.3L)							FC125M																												
4305421	14.589	15.649	L	2015			0012	CRACKING	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	9.0	7.0													
PREFERRED MATERIALS, INC. (2018)							SPR	RIDE	6.6	6.7	6.3		8.4	8.5	8.3	8.1	8.2	8.2	7.9	8.2	8.2	7.8													
26070000	12.140	14.048	L	1	1	45		CRACKING	9.5	9.5	9.5	9.5	9.5	6.5	10.0	10.0	10.0	9.5	9.5	9.5	9.0														
26			2	5.2			30500	RIDE	8.2	8.3	8.1	7.5	7.4	7.3	8.7	7.5	8.5	8.5	8.4	8.2	8.0														
NW 109 DR(12.2L)							FC95M																												
2075943	12.317	14.048	C	2005			0012	CRACKING	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.0	7.0	6.5	6.5	6.5	6.5	3.0*													
V. E. WHITEHURST & SONS, I(2007)							S	RIDE	8.1	8.1	7.8	7.8	7.7	7.7	7.8	7.7	7.6	7.5	7.6	7.5	7.4	7.0													
2076683	7.827	14.050	C	2025			0012																												
26070000	9.830	12.140	L	1	1	50		CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5														
26			2	5.2			26000	RIDE	9.0	9.0	8.9	8.6	8.5	8.5	7.6	8.4	8.4	8.4	8.4	7.9	8.0														
NW CR-241(9.9L)							DGFC																												
2076681	9.602	12.164	C	1997			0213	CRACKING	9.5	9.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	2.5*													
WHITE CONSTRUCTION CO INC (2000)							S	RIDE	7.9	8.2	8.2	8.1	8.2	8.1	8.1	8.1	8.1	8.0	8.0	8.0	7.9	7.5													
2076683	7.827	14.050	C	2025			0012																												
26070000	7.827	9.830	L	1	1	50		CRACKING		10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	8.5	8.5	8.5														
26			2	5.2			23000	RIDE		8.7	8.6	8.3	8.3	8.3	8.3	8.2	8.2	8.2	8.1	8.1	8.0													
NW 175 ST(7.9L)							FC125																												
2077581	8.068	9.705	C	2000			0213	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.5	6.0*	6.0*	6.0*	4.0*	4.0*	2.2*	0.0*													
HUBBARD CONSTRUCTION COMPA(2002)							SPR	RIDE	8.0	8.1	7.4	7.7	7.7	7.6	7.6	7.6	7.5	7.4	7.4	7.4	7.3	6.9													
2076683	7.827	14.050	C	2025			0012																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / SURFTYPE / ASTYPE	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2031 (PMRS)
26070000	4.190	7.827	L	1	1	60	CRACKING	10.0	10.0	8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	
26			2	5.2	23000		RIDE	8.5	8.5	8.4	8.3	8.3	8.2	8.0	8.2	8.1	8.3	8.1	8.1	8.0	
SIDE ROAD(4.2C)							FC5M														
4412621	3.030	7.832	L	2021		0012	CRACKING	7.5	7.5	7.5	6.5	6.5	4.5*	3.5*	2.5*	10.0	10.0	10.0	9.4	10.0	8.0
PREFERRED MATERIALS, INC. (2022)							SPRIDE	8.0	7.9	8.0	8.0	7.9	8.0	8.1	8.1	9.2	9.1	9.1	9.1	8.9	8.7
26070000	3.030	4.190	L	1	1	50	CRACKING	10.0	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	10.0	
26			2	5.2	21500		RIDE	8.5	8.5		8.3	8.3	8.2	8.0	8.2	8.1	8.3	8.1	8.1	8.1	
SR 45(3.0C)							FC125M														
4412621	3.030	7.832	L	2021		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	10.0	10.0	10.0	10.0	10.0	8.5
PREFERRED MATERIALS, INC. (2022)							SPRIDE	8.2	8.2	7.7	7.8	7.8	7.7	7.7	7.8	8.6	8.5	8.5	8.4	8.4	8.0
2078502	0.000	4.031	C	2027		0213															
26070068	0.000	0.548	R	1	1	35	CRACKING	7.5	3.5*	3.5*	3.5*	1.0*	0.0*		10.0	10.0	10.0	10.0	10.0	10.0	
26A			1	1.8	14800		RIDE						4.4*		6.1	6.2	6.2	6.0	6.0	6.2	
SR 26(0.0C)							FC125														
2077901	0.000	1.813	C	2005		0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	8.0	7.0	7.0	3.5*
ANDERSON COLUMBIA CO., INC(2008)							SPRIDE	6.2	6.3	5.1*	5.5	5.6	5.3*	5.4*	5.4*	5.4*	5.5	5.7	5.6	5.4*	5.0*
2077902	0.000	1.691	C	2028		0012															
26070068	0.548	1.691	C	1	1	35	CRACKING	7.5	7.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	
26A			2	1.8	11900		RIDE	7.3	7.4	7.4	6.6	6.4	6.2		7.5	7.3	7.4	7.2	7.1	7.0	
SW 32ND ST(0.6L)							FC125														
2077901	0.000	1.813	C	2005		0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.5	7.0	7.0	6.7	6.5	3.0*
ANDERSON COLUMBIA CO., INC(2008)							SPRIDE	7.1	7.2	6.9	6.9	7.1	7.1	7.0	6.9	6.9	6.8	6.9	6.7	6.7	6.3
2077902	0.000	1.691	C	2028		0012															
26070068	0.000	0.548	L	1	1	35	CRACKING	7.5	3.5*	3.5*	3.5*	1.0*	0.0*		10.0	10.0	10.0	10.0	10.0	10.0	
26A			1	1.8	14800		RIDE						4.4*		6.4	6.3	6.3	6.2	6.2	6.3	
SR-26(0.0L)							FC125														
2077901	0.000	1.813	C	2005		0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	7.2	4.0*
ANDERSON COLUMBIA CO., INC(2008)							SPRIDE	6.2	6.3	5.3*	5.3*	5.0*	5.3*	5.4*	5.2*	5.3*	5.2*	5.2*	4.9*	5.0*	4.6*
2077902	0.000	1.691	C	2028		0012															
26070168	0.000	0.043	C	1	1	35	CRACKING								10.0	10.0	10.0	10.0	10.0	10.0	
26A			1	1.8	9300		RIDE														
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	9.4	9.5	6.0*
		(2008)					RIDE													5.0*	4.6*
26080000	0.000	0.256	R	1	1	35	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	5.5*	5.5*	10.0	10.0	10.0	
20			3	4.2	22500		RIDE	7.6	7.4	5.6	4.7*	4.8*	4.9*	4.8*	4.9*	4.4*	4.4*	7.4	6.8	6.5	
SR-331/WALDO RD(0.0R)							DGFC														
2073552	0.000	0.182	R	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.0	7.0	5.0*	2.0*
PREFERRED MATERIALS, INC. (2011)							SPRIDE	6.5	6.3	5.5	5.1*	5.1*	4.9*	5.1*	5.1*	5.2*	5.0*	5.2*	5.0*	5.1*	4.7*
2073553	0.000	0.256	C	2028		0012															
26080000	0.256	3.775	R	1	1	45	CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0	
20			2	4.2	13700		RIDE	7.6	7.4	8.3	7.9	8.0	7.9	7.9	7.9	7.9	7.9	7.8	7.7	7.8	
CR-2043/SE 15TH ST(0.3R)							FC125M														
4361761	0.257	4.219	C	2020		0012	CRACKING	8.0	8.0	8.0	7.0	7.0	6.0*	5.5*	5.5*	10.0	10.0	10.0	9.6	10.0	8.5
PREFERRED MATERIALS, INC. (2022)							SPRIDE	7.6	7.6	7.1	7.5	7.4	7.6	7.5	7.5	8.8	8.7	8.7	8.6	8.7	8.3
26080000	3.775	4.232	R	1	1	55	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	6.5	5.5*	5.5*	5.5*	10.0	
20			2	4.2	10500		RIDE	8.7	8.7	8.5	8.1	8.2	8.1	7.9	7.7	7.7	7.9	7.9	7.6	8.5	
							FC5M														
4244731	3.438	8.790	R	2012		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	9.0	9.4	5.0*
V. E. WHITEHURST & SONS, I(2013)							SPRIDE	8.4	8.7	8.6	8.6	8.8	8.7	8.9	8.8	8.9	8.9	8.9	8.7	8.7	8.5
26080000	4.232	5.000	R	1	1	55	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	6.5	5.5*	5.5*	5.5*	10.0	
20			2	4.2	10500		RIDE	8.7	8.7	8.5	8.1	8.2	8.1	7.9	7.7	7.7	7.9	7.9	7.6	8.5	
SE 60 TER(4.6R)							FC5														
4244731	3.438	8.790	R	2012		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	9.0	7.0	2.5*
V. E. WHITEHURST & SONS, I(2013)							SPRIDE	8.4	8.7	8.6	8.6	8.8	8.7	8.9	8.8	8.9	8.9	8.9	8.7	8.2	8.0
26080000	5.000	8.790	R	1	1	65	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	6.5	5.5*	5.5*	5.5*	10.0	
20			2	4.2	9300		RIDE	8.7	8.7	8.5	8.1	8.2	8.1	7.9	7.7	7.7	7.9	7.9	7.6	8.5	
CR 2092(5.4R)							FC5														
4244731	3.438	8.790	R	2012		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	9.0	9.3	5.0*
V. E. WHITEHURST & SONS, I(2013)							SPRIDE	8.4	8.7	8.6	8.6	8.8	8.7	8.9	8.8	8.9	8.9	8.9	8.7	8.9	8.7

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26080000	8.790	14.130	R	1	1	65	CRACKING	5.5*	5.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	10.0	9.0															
20			2	4.2	8600		RIDE	8.4	8.3	8.2	7.4			8.1	7.9	7.9	8.0	7.9	7.6	7.7															
SE 156 TER(10.8R)							FC5M																												
4432581	8.764	14.139	C	2022			0012	CRACKING	9.0	9.0	8.0	6.5	4.5*	4.5*	4.5*	3.5*	0.0*	10.0	10.0	9.8	10.0	8.5													
ANDERSON COLUMBIA CO., INC		(2023)					SPRIDE	7.4	7.5	7.7	7.7	7.7	7.7	7.7	7.6	7.4	8.6	8.6	8.6	8.6	8.4													
26080000	14.130	15.522	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0															
20			2	4.2	8600		RIDE	8.2	8.1	8.0	7.6			8.1	7.9	7.9	8.0	7.9	7.6	7.4															
SE 211TH ST(14.2C)							FC125																												
2077141	9.114	15.547	C	2002			0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.0	6.5	5.5*	3.6*	0.0*													
RUSSELL ENGINEERING, INC		(2007)					SPRIDE	7.4	7.5	6.9	6.7	7.1	7.0	6.8	7.2	7.0	7.0	6.9	6.9	7.0	6.6													
4432582	14.130	15.522	C	2029			0012																												
26080000	15.522	16.810	R	1	1	55	CRACKING	10.0	10.0	10.0	9.0	8.0	7.0	7.0	7.0	7.0	4.5*	4.5*	4.5*	4.5*															
20			2	4.2	8600		RIDE	8.7	8.7	8.4	8.3	8.3	8.2	8.0	7.8	7.9	7.4	7.7	7.4	7.5															
CHEROKEE DR(15.6R)							FC125M																												
2078182	15.529	16.801	C	2017			0213	CRACKING	10.0	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	10.0	8.5													
SEMA CONSTRUCTION, INC.		(2021)					SPRIDE	8.6	8.6	8.1	8.3	8.4			8.0	8.0	7.9	7.9	7.7	7.8	7.4													
26080000	15.522	16.810	L	1	1	55	CRACKING	10.0	10.0	10.0	9.0	8.0	7.0	7.0	7.0	7.0	4.5*	4.5*	4.5*	4.5*															
20			2	4.2	8600		RIDE	8.7	8.7	8.4	8.3	8.3	8.2	8.0	7.8	7.9	7.4	7.7	7.4	7.5															
							FC125M																												
2078182	15.529	16.801	C	2017			0213	CRACKING	10.0	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	9.5	8.0													
SEMA CONSTRUCTION, INC.		(2021)					SPRIDE	8.6	8.6	8.1	8.3	8.4			8.0	8.0	7.9	7.9	7.8	7.8	7.4													
26080000	14.130	15.522	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0															
20			2	4.2	8600		RIDE	8.2	8.1	8.0	7.6			7.9	7.8	7.8	8.0	7.9	7.8	7.5															
SE 211TH ST(14.2C)							FC125																												
2077141	9.114	15.547	C	2002			0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.0	6.0*	5.7*	5.3*	2.0*													
RUSSELL ENGINEERING, INC		(2007)					SPRIDE	7.5	7.7	6.3	6.7	7.0	6.5	6.6	6.9	6.9	6.8	6.7	6.8	6.8	6.4													
4432582	14.130	15.522	C	2029			0012																												
26080000	8.864	14.130	L	1	1	65	CRACKING	5.5*	5.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	10.0	9.0															
20			2	4.2	8600		RIDE	8.4	8.3	8.2	7.4			7.9	7.8	7.8	8.0	7.9	7.8	7.9															
CR 20A(10.5L)							FC5M																												
4432581	8.764	14.139	C	2022			0012	CRACKING	9.0	6.5	6.5	6.5	4.5*	3.5*	3.5*	3.5*	0.0*	10.0	10.0	9.8	10.0	8.5													
ANDERSON COLUMBIA CO., INC		(2023)					SPRIDE	7.7	7.6	7.8	7.8	7.7	7.6	7.4	7.8	7.6	8.6	8.6	8.5	8.5	8.3													
26080000	5.000	8.864	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	6.5	6.5	4.5*	4.5*	4.5*	10.0															
20			2	4.2	9300		RIDE	8.6	8.6	8.3	7.9	8.0	8.0	7.8	7.7	7.6	7.4	7.3	7.0	8.5															
CR 234(7.1C)							FC5																												
4244731	3.429	8.864	L	2012			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	9.2	9.4	5.0*													
V. E. WHITEHURST & SONS, I		(2013)					SPRIDE	8.4	8.5	8.5	8.6	8.7	8.6	8.7	8.7	8.8	8.7	8.7	8.6	8.7	8.5													
26080000	4.232	5.000	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	6.5	6.5	4.5*	4.5*	4.5*	10.0															
20			2	4.2	10500		RIDE	8.6	8.6	8.3	7.9	8.0	8.0	7.8	7.7	7.6	7.4	7.3	7.0	8.5															
							FC5																												
4244731	3.429	8.864	L	2012			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	9.2	7.8	3.5*													
V. E. WHITEHURST & SONS, I		(2013)					SPRIDE	8.4	8.5	8.5	8.6	8.7	8.6	8.7	8.7	8.8	8.7	8.7	8.6	8.3	8.1													
26080000	3.775	4.232	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	6.5	6.5	4.5*	4.5*	4.5*	10.0															
20			2	4.2	10500		RIDE	8.6	8.6	8.3	7.9	8.0	8.0	7.8	7.7	7.6	7.4	7.3	7.0	8.5															
							FC5M																												
4244731	3.429	8.864	L	2012			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	9.2	9.8	5.5*													
V. E. WHITEHURST & SONS, I		(2013)					SPRIDE	8.4	8.5	8.5	8.6	8.7	8.6	8.7	8.7	8.8	8.7	8.7	8.6	8.9	8.7													
26080000	0.256	3.775	L	1	1	45	CRACKING	8.0	8.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.0	7.5	7.5															
20			2	4.2	13700		RIDE	7.6	7.6	8.4	8.0	8.1	7.9	7.9	7.4	7.0	7.7	7.6	7.4	7.5															
CR 2043(0.3L)							FC125M																												
4361761	0.257	4.219	C	2020			0012	CRACKING	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	5.5*	10.0	10.0	10.0	9.7	10.0	8.5													
PREFERRED MATERIALS, INC.		(2022)					SPRIDE	7.2	7.2	7.4	7.5	7.4	7.6	7.5	7.6	8.8	8.7	8.7	8.6	8.6	8.2													
26080000	0.000	0.256	L	1	1	35	CRACKING	8.0	8.0	7.0	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0															
20			3	4.2	22500		RIDE	7.6	7.6	4.7*	4.9*	4.9*	4.5*	4.6*	5.3*	4.3*	5.9	8.1	7.8	7.9															
SR-24/WALDO RD(0.0L)							DGFC																												
2073552	0.000	0.182	L	2010			0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.0	4.0*													
PREFERRED MATERIALS, INC.		(2011)					SPRIDE	7.7	7.8	7.1	7.1	7.0	6.8	7.1	6.7	6.9	6.7	6.8	6.5	6.4	6.0													
2073553	0.000	0.256	C	2028			0012																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYS / %T / FY-P / FY-F	TYP SPD / AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
26080011 200	0.000	0.067	C 1 2 2.0	1	1 1000	CRACKING RIDE																												
						CRACKING RIDE																											5.2* 3.4*	
26090000 24 HAUL RD(0.1R)	0.000	2.762	C 1 2 11.0	1	55 8300 FC125M	CRACKING RIDE	9.5 8.7	9.5 8.7	9.5 8.5	8.0 8.1	8.0 8.2	7.0 7.6	6.0* 7.7	6.0* 7.6	4.5* 7.1	4.5* 7.3	4.0* 7.0	4.0* 6.6																
4233961 V. E. WHITEHURST & SONS, I(2014)	0.816	2.762	C 2012		0012 SPRIDE	CRACKING RIDE	10.0 8.6	10.0 8.6	10.0 8.0	10.0 8.2	10.0 8.4	8.5 8.2	8.5 8.3	8.5 8.3	8.5 8.3	7.5 8.2	7.5 8.3	6.7 8.2	7.0 8.2	4.5* 7.8														
26090000 24 SR 45(2.8C)	2.762	4.280	C 1 2 11.0	1	60 13000 FC125M	CRACKING RIDE	5.5* 6.3*	5.5* 6.3*	4.5* 6.1*	4.5* 5.1*	10.0 8.3	10.0 8.3	9.0 8.2	9.0 8.1	9.0 6.9	9.0 8.1	9.0 8.0	7.5 7.9	7.5 7.9														
4393441 V. E. WHITEHURST & SONS, I(2022)	2.977	6.088	C 2020		0012 SPRIDE	CRACKING RIDE	7.5 7.9	7.5 8.0	7.5 7.7	7.5 7.4	7.5 7.8	6.0* 7.7	6.0* 7.6	4.5* 7.6	10.0 8.6	10.0 8.4	10.0 8.4	9.5 8.3	9.5 8.1	8.0 7.7														
26090000 24 SW 143 ST(4.5R)	4.280	4.800	C 1 2 11.0	7	60 13000 FC125M	CRACKING RIDE	5.5* 6.3*	5.5* 6.3*	4.5* 6.1*	4.5* 5.1*	10.0 8.3	10.0 8.3	9.0 8.2	9.0 8.1	9.0 6.9	9.0 8.1	9.0 8.0	7.5 7.9	7.5 7.9														
				(2026)		CRACKING RIDE	7.5 7.9	7.5 8.0	7.5 7.7	7.5 7.4	7.5 7.8	6.0* 7.7	6.0* 7.6	4.5* 7.6	10.0 8.6	10.0 8.4	10.0 8.4	9.5 8.3	10.0 7.8	9.0 7.4												
26090000 24 SW 138 ST(5.0C)	4.800	6.915	C 1 2 11.0	1	60 22500 FC125M	CRACKING RIDE	5.5* 6.3*	5.5* 6.3*	4.5* 6.1*	4.5* 5.1*	10.0 8.3	10.0 8.3	9.0 8.2	9.0 8.1	9.0 6.9	9.0 8.1	9.0 8.0	7.5 7.9	7.5 7.9														
4393441 V. E. WHITEHURST & SONS, I(2022)	2.977	6.088	C 2020		0012 SPRIDE	CRACKING RIDE	7.5 7.9	7.5 8.0	7.5 7.7	7.5 7.4	7.5 7.8	6.0* 7.7	6.0* 7.6	4.5* 7.6	10.0 8.6	10.0 8.4	10.0 8.4	9.5 8.3	8.7 8.4	7.5 8.0												
26090000 24 SW 111 TER(7.2R)	6.915	7.435	C 1 2 11.0	7	60 22500 FC125M	CRACKING RIDE	5.5* 6.3*	5.5* 6.3*	4.5* 6.1*	4.5* 5.1*	10.0 8.3	10.0 8.3	9.0 8.2	9.0 8.1	9.0 6.9	9.0 8.1	9.0 8.0	7.5 7.9	7.5 7.9														
				(2026)		CRACKING RIDE	7.5 7.9	7.5 8.0	7.5 7.7	7.5 7.4	7.5 7.8	6.0* 7.7	6.0* 7.6	4.5* 7.6	10.0 8.6	10.0 8.4	10.0 8.4	9.5 8.3	10.0 8.3	9.0 7.9												
26090000 24 SW 107 ST(7.6R)	7.435	8.776	C 1 2 11.0	1	60 22500 FC125M	CRACKING RIDE	5.5* 6.3*	5.5* 6.3*	4.5* 6.1*	4.5* 5.1*	10.0 8.3	10.0 8.3	9.0 8.2	9.0 8.1	9.0 6.9	9.0 8.1	9.0 8.0	7.5 7.9	7.5 7.9														
4393441 V. E. WHITEHURST & SONS, I(2022)	7.845	8.530	C 2020		0012 SPRIDE	CRACKING RIDE	7.5 7.9	7.5 8.0	7.5 7.7	7.5 7.4	7.5 7.8	6.0* 7.7	6.0* 7.6	4.5* 7.6	10.0 8.6	10.0 8.4	10.0 8.4	9.5 8.3	10.0 7.8	8.5 7.4												
26090000 24 SW 88 ST(9.0R)	8.776	9.600	R 1 1 11.0	1	50 22500 FC125M	CRACKING RIDE	5.5* 8.0	5.5* 8.6	9.5 8.7		10.0 8.3	10.0 8.2	10.0 7.9	9.0 7.9	9.0 8.0	9.0 8.1	9.0 8.0	9.0 8.0	9.0 8.0														
4393441 V. E. WHITEHURST & SONS, I(2022)	8.530	9.632	R 2020		0012 SPRIDE	CRACKING RIDE	9.0 8.0	9.0 8.0	9.0 7.7	9.0 7.2	9.0 7.3	8.5 7.7	7.5 7.6	7.0 7.6	10.0 8.6	10.0 8.5	10.0 8.5	9.3 8.4	9.5 8.5	8.0 8.1												
26090000 24 SW 78 ST(9.7R)	9.600	12.100	R 1 2 11.0	1	45 29500 FC125	CRACKING RIDE	10.0 8.3	9.5 8.2	8.0 8.2	8.0 7.9	8.0 7.9	7.0 7.6	6.0* 7.0	4.5* 7.5	4.5* 7.2	2.0* 6.7	1.5* 6.8	1.5* 6.8	10.0 8.4														
2076693 PREFERRED MATERIALS, INC. (2013)	9.953	12.422	R 2012		0012 SPRIDE	CRACKING RIDE	10.0 8.3	10.0 8.3	10.0 7.8	10.0 8.0	10.0 8.1	10.0 8.0	10.0 7.9	8.5 7.9	7.5 8.0	7.5 7.8	7.5 7.9	6.9 7.8	7.0 7.7	4.5* 7.3												
26090000 24 SW 44 ST(12.3R)	12.100	14.848	R 1 3 5.3	1	45 43500 FC125M	CRACKING RIDE	10.0 8.3	10.0 8.3	9.5 8.2	9.5 7.9	9.5 7.9	8.0 7.7	8.0 7.0	8.0 7.6	8.0 7.5	7.0 7.6	7.0 7.6	7.0 7.5	7.0 7.5														
4343231 V. E. WHITEHURST & SONS, I(2020)	12.769	14.848	R 2017		0012 SPRIDE	CRACKING RIDE	7.0 7.5	7.0 7.5	7.0 7.1	6.0* 7.4	6.0* 7.2		10.0 8.2	10.0 7.9	10.0 7.9	10.0 7.7	10.0 7.8	10.0 7.7	9.6 7.8	8.0 7.4												
26090000 24 ARCHER RD(14.9R)	14.848	15.767	R 1 2 4.9	1	35 26500 FC125M	CRACKING RIDE	10.0 8.6	10.0 8.7	10.0 8.5	10.0 8.2	10.0 8.2	9.5 8.1	9.0 8.0	7.5 7.9	7.5 7.3	7.5 7.8	7.5 7.8	7.5 7.8	7.5 7.8														
				(2021)		CRACKING RIDE	7.5 7.8	7.5 7.8	7.0 7.3	7.0 7.6	7.0 7.9	7.0 7.6		10.0 7.7	10.0 7.7	10.0 7.6	10.0 7.6	9.6 7.7	9.0 7.7	7.5 7.3												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = ALACHUA

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	%T / LN / RW / FY-P / FY-F	AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26090000 SR 24 SPUR TO SR 25(15.9R)	15.767	15.916	R	1	1	35	5.3	23000 FC125M	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	10.0	10.0	10.0	10.0													
				2					RIDE																										
									CRACKING	10.0	10.0	10.0	10.0	10.0	10.0		8.5	7.5	7.5	7.0	7.0	5.7*	4.0*												
		(2021)							RIDE								4.0*	4.0*	4.1*	6.3		3.8*	3.4*												
26090000 SR 24 FROM MLK JR HWY(15.9L)	15.767	15.916	L	1	1	35	5.3	23000 DGFC	CRACKING	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0													
				2					RIDE						4.0*																				
									CRACKING	10.0	10.0	10.0	9.5	9.5	9.5		6.0*	6.0*	6.0*	6.0*	6.0*	5.5*	2.5*												
		(2010)							RIDE								3.7*	4.0*	3.8*	3.7*		3.5*	3.1*												
26090000 SR 24 GALE LEMERAND DR(15.1C)	14.890	15.767	L	1	1	35	4.9	26500 FC125M	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	7.0	7.0													
				2					RIDE	8.3	8.3	7.8	7.8	8.1	7.9	7.9	7.1	7.4	7.3	7.2	7.2	7.0													
									CRACKING	7.0	7.0	7.0	7.0	7.0	6.0*		10.0	10.0	10.0	10.0	9.0	9.1	7.5												
		(2021)							RIDE	7.0	7.1	6.6	6.6	7.3	7.1		7.3	7.6	7.4	7.8	7.4	7.3	6.9												
26090000 SR 24 FRED BEAR DR(12.4L)	12.290	14.890	L	1	1	45	5.3	43500 FC125M	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0													
				3					RIDE	8.4	8.5	8.4	8.1	8.2	8.0	8.0	7.9	7.9	7.8	7.8	7.6	7.7													
4343231 V. E. WHITEHURST & SONS,	12.769	14.848	L	2017		0012			CRACKING	7.0	7.0	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	9.6	9.5	8.0												
		I(2020)							SPRIDE	7.7	7.5	7.3	6.9	7.8		8.2	8.2	8.1	7.8	8.0	7.9	7.6	7.2												
26090000 SR 24 SW 75 TER(9.9C)	9.600	12.290	L	1	1	45	11.0	29500 FC125	CRACKING	10.0	10.0	10.0	9.0	8.0	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	10.0													
				2					RIDE	8.5	8.4	8.2	8.0	8.0	7.7	7.6	7.6	7.5	7.3	7.2	6.8	8.3													
2076693 V. E. WHITEHURST & SONS,	9.953	12.422	L	2012		0012			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	8.0	7.8	5.0*												
		I(2013)							SPRIDE	8.3	8.3	8.0	7.9	8.1	8.0	8.0	8.0	8.0	7.8	7.9	7.9	7.8	7.4												
26090000 SR 24 SW 91 TERR(8.8L)	8.776	9.600	L	1	1	50	11.0	22500 FC125M	CRACKING	5.5*	5.5*	9.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0													
				2					RIDE	8.0	8.6	8.7		8.3	8.2	8.2	8.0	8.1	8.1	8.0	8.0	8.0													
4393441 V. E. WHITEHURST & SONS,	8.530	9.632	L	2020		0012			CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	7.5	7.0	10.0	10.0	10.0	9.3	9.2	8.0												
		I(2022)							SPRIDE	8.0	8.0	7.7	7.2	7.3	7.7	7.6	7.6	8.6	8.5	8.5	8.4	8.5	8.1												
26100000 SR 121 GAINESVILLE CITY LIMITS(0.0C)	0.000	15.882	C	1	1	60	6.9	2700 FC125M	CRACKING	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0													
				2					RIDE	8.5	8.5	8.8	8.6	8.5	8.4	8.0	8.3	8.3	8.2	8.2	8.1	8.0													
4322631 V. E. WHITEHURST & SONS,	0.110	9.804	C	2016		0012			CRACKING	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	6.5												
		I(2018)							RIDE	8.0	8.1	7.6		8.8	8.6	8.4	8.3	8.3	8.4	8.3	8.4	8.4	8.0												
26110000 SR 235 UNSIGNED(0.1R)	0.069	1.040	C	1	2	30	15.6	11000 FC125	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0													
				2					RIDE	8.1	8.3	7.1	7.3	6.7	6.9	6.4	7.0	7.1	7.0	7.0	7.0	6.9													
2078241 WHITEHURST, VE AND SON INC(2000)	0.007	1.042	C	1999		0216			CRACKING	9.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	5.5*	0.0*	0.0*												
									SPRIDE	6.9	6.9	7.4	7.1	7.3	6.9	7.0	6.9	7.1	6.9	7.0	6.9	7.2	6.8												
26110000 SR 235 NW 134 DR(1.4L)	1.040	7.122	C	1	2	55	15.6	4000 FC125M	CRACKING	9.0	9.0	9.0	9.0	7.5	6.0*	5.5*	5.5*	5.5*	3.5*	3.5*	3.5*	10.0													
				2					RIDE	8.7	8.5	8.6	8.0	7.8	8.0	7.4	7.5	7.1	6.9	6.8	6.4*	8.8													
4233971 PREFERRED MATERIALS, INC.	2.638	13.739	C	2012		0012			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	6.5	3.5*	1.0*												
		(2013)							SPRIDE	8.7	8.7	8.5	7.9	8.4	8.3	8.2	8.3	8.2	8.1	8.1	8.0	8.0	7.6												
26110000 SR 235 NW 53 TER(7.5L)	7.402	11.089	C	1	1	55	15.6	1400 FC125M	CRACKING	10.0	9.5	9.5	9.5	7.5	7.0	7.0	7.0	7.0	5.5*	5.5*	5.5*	10.0												
				2					RIDE	8.9	8.8	8.7	8.2	8.0	7.9	7.3	7.5	7.3	7.3	7.1	7.1	8.8												
4233971 PREFERRED MATERIALS, INC.	2.638	13.739	C	2012		0012			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.5	5.0*												
		(2013)							SPRIDE	8.7	8.8	8.3	8.1	8.2	7.8	7.9	7.9	8.0	7.9	8.0	7.9	7.7	7.3												
26110000 SR 231 NW 214 LN(11.7L)	11.089	13.757	C	1	1	55	15.6	4100 FC125M	CRACKING	10.0	9.5	9.5	9.5	7.5	7.0	7.0	7.0	7.0	5.5*	5.5*	5.5*	10.0												
				2					RIDE	8.9	8.8	8.7	8.2	8.0	7.9	7.3	7.5	7.3	7.3	7.1	7.1	8.8												
4233971 PREFERRED MATERIALS, INC.	2.638	13.739	C	2012		0012			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.0	5.5*												
		(2013)							SPRIDE	8.7	8.8	8.3	8.1	8.2	7.8	7.9	7.9	8.0	7.9	8.0	7.9	8.1	7.7												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = ALACHUA

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	LN	%T	SPD	AADT	SURFTYPE	DISTRESS / RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26110101 235 NW 142 AVE(0.0C)	0.000	0.160	C	1	1	1	2.8	30	12600	FC125	CRACKING RIDE																								5.5* 6.9	4.5* 5.8	4.4* 5.6	4.5* 5.7	
26130000 26 SR-20(0.0R) 2075802 V. E. WHITEHURST & SONS, I(2010) 2075804	0.000 0.079 1.343	2.969 2.430 6.045	R R 2008 C 2028	1 0012	1	1	7.0	45	9200	FC125M SPRIDE	CRACKING RIDE CRACKING RIDE	9.5 7.7 10.0 7.6	9.5 7.8 10.0 7.6	9.5 7.4 10.0 7.0	9.5 7.3 10.0 7.2	9.5 7.3 10.0 7.5	8.0 7.2 9.0 7.3	6.0* 6.6 9.0 7.4	4.5* 6.9 8.5 7.3	4.5* 6.8 8.5 7.4	10.0 8.3 7.5 7.4	10.0 8.1 7.5 7.3	10.0 7.8 7.9 7.3	10.0 7.8 7.4 7.1	4.5* 6.7											
26130000 26 NFETC(3.5L) 2075802 V. E. WHITEHURST & SONS, I(2010) 2075804	2.969 2.818 1.343	6.045 6.045 6.045	C C 2008 C 2028	1 0012	1	1	7.0	60	5500	FC125M SPRIDE	CRACKING RIDE CRACKING RIDE	9.5 8.6 10.0 8.0	8.0 8.6 10.0 7.9	6.5 8.4 10.0 7.7	6.5 8.0 10.0 7.5	8.0 8.0 10.0 7.8	6.0* 7.8 9.0 7.7	6.0* 6.9 8.0 7.8	6.0* 7.5 7.0 7.6	4.5* 7.2 7.0 7.6	10.0 8.3 6.5 7.6	10.0 8.2 6.5 7.6	10.0 8.1 7.0 7.6	10.0 8.1 5.9* 7.5	3.0* 7.1											
26130000 26 HATCHETT CREEK LODGE RD(8.1L) 2075802 V. E. WHITEHURST & SONS, I(2010) 26130000 26	6.224 6.224 12.397	11.045 8.868 12.590	C C 2008 C	1 0012 1	1	1	7.0	60	11500	FC125M SPRIDE FC125M	CRACKING RIDE CRACKING RIDE CRACKING RIDE	9.5 8.6 10.0 8.3 10.0 8.2	8.0 8.6 10.0 8.3 10.0 8.2	6.5 8.4 10.0 7.9 10.0 7.6	6.5 8.0 10.0 7.7 10.0 7.2	8.0 8.0 10.0 8.0 10.0 7.5	6.0* 7.8 9.0 8.0 9.0 7.9	6.0* 6.9 8.5 8.0 9.5 7.8	6.0* 7.5 8.0 8.0 9.5 7.7	4.5* 7.2 7.0 7.9 9.5 6.7	10.0 8.3 7.0 7.8 8.5	10.0 8.2 8.0 7.9 7.5	10.0 8.2 7.4 7.8 7.8	10.0 8.3 7.5 7.8 7.0	4.5*											
2075802 V. E. WHITEHURST & SONS, I(2010) 26130000 26 CR 1469 NE(13.7C) 2078231 ANDERSON COLUMBIA CO., INC(2001)	6.224 12.590 11.757	8.868 17.271 17.256	C 2008 C C 1999	0012 1 0216	8	1	7.0	60	11000	SPRIDE FC125 CRACKING	CRACKING RIDE CRACKING RIDE CRACKING	10.0 8.3 10.0 8.2 7.0	10.0 8.3 10.0 8.2 7.0	10.0 7.9 10.0 8.0 7.0	10.0 7.7 10.0 7.6 7.0	10.0 8.0 10.0 8.0 7.0	9.0 8.0 10.0 7.9 7.0	8.5 8.0 9.5 7.8 6.0*	8.0 7.9 9.5 7.7 5.5*	7.0 8.0 9.5 6.7 5.5*	7.0 7.9 8.5 7.8 5.5*	8.0 7.8 7.5 7.7 5.5*	7.4 7.8 7.5 7.8 5.4*	7.5 7.8 7.0 7.8	4.5* 7.4											
26130000 26 E 14TH ST(0.0C) 2075802 V. E. WHITEHURST & SONS, I(2010) 2075804	0.000 0.079 1.343	2.969 2.430 6.045	L L 2008 C 2028	1 0012	1	1	7.0	45	9200	FC125M SPRIDE	CRACKING RIDE CRACKING RIDE	7.5 7.4 8.5 6.6	7.5 7.3 8.5 6.8	7.5 6.9 8.5 6.5	7.5 6.7 8.5 6.3	7.5 6.7 8.5 6.6	6.5 6.3 8.5 6.4	6.5 6.2 8.5 6.5	4.5* 5.9 8.5 6.3	4.5* 6.0 8.5 6.3	10.0 8.2 7.5 6.3	10.0 7.9 7.0 6.3	8.5 7.3 6.5 6.2	8.5 7.0 6.5 6.1	3.5* 5.7											
26130001 26 GORE AT SR 26 REALIG(0.0C)	0.000	1.347	C	1	1	1	7.0	60	11500	FC125M	CRACKING RIDE CRACKING RIDE	10.0 8.5	10.0 8.3	10.0 7.7	10.0 7.7	10.0 8.0	10.0 7.9	10.0 7.9	10.0 7.9	10.0 7.9	9.0 7.9	8.5 7.8	8.6 7.8	10.0 8.5 8.3 7.7	5.5* 7.3											
26130002 262	0.000	0.475	C	1	1	1	2.0		1000		CRACKING RIDE													6.5 5.8*											
26130002 262	0.475	0.976	C	1	1	1	2.0		1000		CRACKING RIDE													6.8 6.6											
26130100 26 BEG OF REALIGNMENT(0.0C)	0.000	0.084	C	1	6	1	7.0	50	3600		CRACKING RIDE CRACKING RIDE	10.0 8.5	10.0 8.3	10.0 7.7	10.0 7.7	10.0 8.0	10.0 7.9	10.0 7.9	10.0 7.9	10.0 7.9	10.0 7.9	8.5 7.8	10.0 7.8	10.0 9.5 7.7	8.5 7.3											

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	LN	%T	AADT / SURFTYPE / FY-P / FY-F	DISTRESS / RATINGS / WKMX-P / ASTYPE / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26220000	0.000	8.625	C				1		60	CRACKING	9.5	9.5	6.5	6.5	6.5	4.5*	1.0*	0.0*	0.0*	10.0	10.0	10.0	9.5												
121				2	5.8				11500	RIDE	8.3	8.2	7.9	7.4	7.4	7.0	6.7	6.4*	5.8*	8.7	8.6	8.5	8.5												
CR 346 SW(1.1L)										FC125																										
2077344	0.000	5.155	C	2009					0012	CRACKING	9.5	9.5	9.5	9.5	9.5	8.5	8.5	7.5	7.5	7.5	7.5	7.6	7.4	4.5*												
PREFERRED MATERIALS, INC.				(2010)						SPRIDE	8.5	8.5	7.9	8.1	8.1	8.0	8.0	8.0	7.9	8.0	7.9	7.9	7.8	7.4												
26220000	8.625	8.956	R				1		45	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5												
121				2	5.8				13500	RIDE	8.2	8.1	7.9	7.8	7.8	7.3	7.4	7.0	6.1	5.6	5.7	5.6	5.6												
SW 35 DR(8.7R)										FC125M																										
										CRACKING	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	8.5	6.5												
				(2018)						RIDE	5.8	5.9	6.0	6.2									7.5	7.1												
26220000	8.956	11.101	R				1		45	CRACKING	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.0												
331				2	5.8				30000	RIDE	7.0	6.5	5.9*	6.0*	5.8*	5.7	7.8	6.8	7.5	7.6	7.5	7.3	7.3												
SW 34TH ST(9.0R)										FC125M																										
4361661	8.956	11.101	C	2018					0012	CRACKING	8.0	8.0	8.0	6.5	6.5		10.0	10.0	10.0	10.0	10.0	9.5	9.1	7.5												
ANDERSON COLUMBIA CO., INC				(2020)						SPRIDE	7.3	6.9	6.5	6.4	6.4		8.4	8.5	8.4	8.3	8.4	8.4	8.2	7.8												
26220000	8.956	11.101	L				1		45	CRACKING	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.0												
331				2	5.8				30000	RIDE	7.3	7.3	7.1	6.7	6.7	6.6	7.7	7.6	7.5	7.7	7.5	7.4	7.3												
CR 23(9.0L)										FC125M																										
4361661	8.956	11.101	C	2018					0012	CRACKING	9.0	7.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	9.5	9.2	7.5												
ANDERSON COLUMBIA CO., INC				(2020)						SPRIDE	7.2	6.9	6.4	6.6	6.5		8.3	8.2	8.3	8.3	8.3	8.2	8.1	7.7												
26220000	8.625	8.956	L				1		45	CRACKING	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	8.0	7.5	7.5	7.5	6.5												
121				2	5.8				13500	RIDE	8.3	8.3	8.2	7.8	7.6	7.5	7.5	7.6	7.3	7.5	7.4	7.6	7.3												
BEAR DR(8.7L)										FC125M																										
										CRACKING	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.3	6.5												
				(2018)						RIDE	7.4	7.1	6.8	6.9									7.7	7.3												
26250000	0.000	1.623	R				1		45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0												
121				3	2.9				26806	RIDE	8.1	8.4	8.4	7.9	8.0	7.9	7.7	7.8	7.6	7.6	7.6	7.4	7.5												
SR-331/WILLISTON RD(0.0R)										FC3																										
2076631	0.000	1.591	C	1994					0213	CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.5	6.5	6.5	6.5	6.3*	6.0*	1.0*												
JOHN C. HIPP CONSTRUCTION				(1998)						S RIDE	7.5	7.5	7.3	7.5	7.4	7.4	7.6	7.3	7.4	7.1	7.5	7.4	7.0	6.6												
26250000	1.623	3.084	R				1		45	CRACKING	9.0	9.0	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0												
121				3	2.9				44500	RIDE	7.0	7.4	7.3	8.0	7.8	7.4	7.0	7.4	7.5	7.2	7.2	7.1	7.0												
REGENCY OAKS APTS(1.8R)										FC125M																										
4305471	1.623	3.285	R	2015					0012	CRACKING	8.0	7.0		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.7	8.3	6.0*												
PREFERRED MATERIALS, INC.				(2017)						SPRIDE	6.8	6.9		8.6	8.4	8.4	8.4	8.3	8.3	8.1	8.3	8.3	8.2	7.8												
2077126	1.621	3.433	R	2028					0012																											
26250000	3.084	3.551	R				1		35	CRACKING	9.0	9.0	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0												
121				2	2.9				22500	RIDE	7.0	7.4	6.8	8.0	7.8	7.4	7.0	7.4	7.5	7.2	7.2	7.1	7.0												
SR 26A(3.2C)										FC125M																										
										CRACKING	8.0	7.0		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.7	8.4	6.5												
				(2017)						RIDE	6.8	6.9		8.6	8.4	8.4	8.4	8.3	8.3	8.1	8.3	8.3	7.4	7.0												
2077126	1.621	3.433	R	2028					0012																											
26250000	3.551	4.345	R				1		35	CRACKING	7.5	7.5	7.5	7.5	7.5	6.5	5.5*	5.5*	3.5*	10.0	10.0	10.0	10.0												
121				1	2.9				19500	RIDE	6.9	7.1	7.1	6.6	6.4	5.8	5.8	5.6	5.3*	8.1	7.7	7.6	7.7												
CR 338(3.8C)										FC125M																										
2077123	3.540	4.406	R	2008					0012	CRACKING	7.5	7.5	7.5	7.5	7.5	7.0	7.0	6.5	6.5	6.5	6.5	6.1*	7.3	4.0*												
PREFERRED MATERIALS, INC.				(2010)						RIDE	6.8	7.0	6.2										7.3	6.9												
26250000	4.345	4.665	R				1		40	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5		10.0	10.0	10.0	10.0												
121				1	2.9				16000	RIDE	8.1	8.2	8.1	7.5	7.6	7.5	6.9	7.6		8.1	7.7	7.6	7.7												
CR 172(4.3C)										FC125M																										
										CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.0	7.0	7.0	7.0	7.0	9.6	8.5												
				(2026)						RIDE	7.6	7.8	6.7	7.4	7.3	7.2	7.2	7.1	7.1	7.5	7.6	7.5	7.8	7.4												
26250000	4.665	5.444	C				1		40	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5		10.0	10.0	10.0	10.0												
121				2	2.9				16500	RIDE	8.1	8.2	8.1	7.5	7.6	7.5	6.9	7.6		8.1	7.7	7.6	7.7												
NW 21ST PL(4.7L)										FC125M																										
2077123	4.406	5.652	C	2008					0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.0	7.0	7.0	7.0	7.0	8.4	5.5*												
PREFERRED MATERIALS, INC.				(2010)						RIDE	7.6	7.8	6.7	7.4	7.3	7.2	7.2	7.1	7.1	7.5	7.6	7.5	7.6	7.2												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = ALACHUA

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYS / %T / FY-P / FY-F	TYP SPD / AADT / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
26250000 121	5.444 5.677		R 1	1 2.9	40 16500 FC125M	CRACKING RIDE	10.0 8.1	9.5 8.2	9.5 8.1	9.5 7.5	9.5 7.6	9.5 7.5	9.5 6.9	9.5 7.6		10.0 8.1	10.0 7.7	10.0 7.6	10.0 7.7											
		(2026)				CRACKING RIDE	10.0 7.6	10.0 7.8	10.0 6.7	10.0 7.4	10.0 7.3	9.0 7.2	8.0 7.2	7.0 7.1	7.0 7.1	7.0 7.5	7.0 7.6	7.0 7.5	10.0 8.3	9.0 7.9											
26250000 121 CR 120/NW 31ST BLVD(5.7R) 2077123 PREFERRED MATERIALS, INC.	5.677 5.652	6.312 5.990	R 1 R	1 3.1 2008 (2010)	40 17500 FC125M 0012	CRACKING RIDE CRACKING RIDE	9.0 7.5 10.0 7.6	9.0 7.9 10.0 7.8	9.0 7.7 10.0 6.7	9.0 7.3 10.0 7.4	9.0 7.2 10.0 7.3	9.0 7.1 9.0 7.2	9.0 6.6 8.0 7.2	9.0 6.9 7.0 7.1	7.0 7.1	10.0 8.1 7.0 7.5	10.0 7.7 7.0 7.6	10.0 7.6 7.0 7.5	10.0 7.7 5.5* 6.9	2.5* 6.5											
26250000 121 NW 45TH AVE(6.4R)	6.312	6.919	R 1	1 3.1	40 17500 FC125M	CRACKING RIDE	9.0 7.5	9.0 7.9	9.0 7.7	9.0 7.3	9.0 7.2	9.0 7.1	9.0 6.6	9.0 6.9		10.0 8.1	10.0 7.7	10.0 7.6	10.0 7.7											
		(2026)				CRACKING RIDE	10.0 7.6	10.0 7.8	10.0 6.7	10.0 7.4	10.0 7.3	9.0 7.2	8.0 7.2	7.0 7.1	7.0 7.1	7.0 7.5	7.0 7.6	7.0 7.5	10.0 8.3	9.0 7.9											
26250000 121 NW 29TH ST(7.0R) 2077123 PREFERRED MATERIALS, INC.	6.919 7.019	7.206 7.258	R 1 R	1 3.1 2008 (2010)	40 17500 FC125M 0012	CRACKING RIDE CRACKING RIDE	9.0 7.5 10.0 7.6	9.0 7.9 10.0 7.8	9.0 7.7 10.0 6.7	9.0 7.3 10.0 7.4	9.0 7.2 10.0 7.3	9.0 7.1 9.0 7.2	9.0 6.6 8.0 7.2	9.0 6.9 7.0 7.1	7.0 7.1	10.0 8.1 7.0 7.5	10.0 7.7 7.0 7.6	10.0 7.6 7.0 7.5	10.0 7.7 5.5* 5.7	2.5* 5.3*											
26250000 121 NW 24TH TER(7.5R)	7.206	7.703	R 1	1 2.9	40 11000 FC125M	CRACKING RIDE	9.0 7.5	9.0 7.9	9.0 7.7	9.0 7.3	9.0 7.2	9.0 7.1	9.0 6.6	9.0 6.9		10.0 8.1	10.0 7.7	10.0 7.6	10.0 7.7											
		(2026)				CRACKING RIDE	10.0 7.6	10.0 7.8	10.0 6.7	10.0 7.4	10.0 7.3	9.0 7.2	8.0 7.2	7.0 7.1	7.0 7.1	7.0 7.5	7.0 7.6	7.0 7.5	10.0 8.4	9.0 8.0											
26250000 121 RAMP FROM SR 25(8.0R) 2077123 PREFERRED MATERIALS, INC.	7.703 7.258	8.043 7.933	R 1 C	1 2.9 2008 (2010)	40 11000 DGFC 0012	CRACKING RIDE CRACKING RIDE	9.0 7.5 10.0 7.6	9.0 7.9 10.0 7.8	9.0 7.7 10.0 6.7	9.0 7.3 10.0 7.4	9.0 7.2 10.0 7.3	9.0 7.1 9.0 7.2	9.0 6.6 8.0 7.2	9.0 6.9 7.0 7.1	7.0 7.1	10.0 8.1 7.0 7.5	10.0 7.7 7.0 7.6	10.0 7.6 7.0 7.5	10.0 7.7 7.5 6.7	4.5* 6.3											
26250000 121 NW 58TH AVE(7.8L) 2077123 PREFERRED MATERIALS, INC.	7.703 7.258	8.043 7.933	L 1 C	1 2.9 2008 (2010)	40 11000 FC125M 0012	CRACKING RIDE CRACKING RIDE	9.0 7.5 10.0 7.6	9.0 7.9 10.0 7.8	9.0 7.7 10.0 6.7	9.0 7.3 10.0 7.4	9.0 7.2 10.0 7.3	9.0 7.1 9.0 7.2	9.0 6.6 8.0 7.2	9.0 6.9 7.0 7.1	7.0 7.1	10.0 8.1 7.0 7.5	10.0 7.7 7.0 7.6	10.0 7.6 7.0 7.5	10.0 7.7 6.5 6.1	3.5* 5.7											
26250000 121 NW 54TH AVE(7.2L)	7.206	7.703	L 1	1 2.9	40 11000 FC125M	CRACKING RIDE	9.0 7.5	9.0 7.9	9.0 7.7	9.0 7.3	9.0 7.2	9.0 7.1	9.0 6.6	9.0 6.9		10.0 8.1	10.0 7.7	10.0 7.6	10.0 7.7											
		(2026)				CRACKING RIDE	10.0 7.6	10.0 7.8	10.0 6.7	10.0 7.4	10.0 7.3	9.0 7.2	8.0 7.2	7.0 7.1	7.0 7.1	7.0 7.5	7.0 7.6	7.0 7.5	10.0 8.1	9.0 7.7											
26250000 121 CR 232(7.1L) 2077123 PREFERRED MATERIALS, INC.	6.919 7.019	7.206 7.258	L 1 L	1 3.1 2008 (2010)	40 17500 FC125M 0012	CRACKING RIDE CRACKING RIDE	9.0 7.5 10.0 7.6	9.0 7.9 10.0 7.8	9.0 7.7 10.0 6.7	9.0 7.3 10.0 7.4	9.0 7.2 10.0 7.3	9.0 7.1 9.0 7.2	9.0 6.6 8.0 7.2	9.0 6.9 7.0 7.1	7.0 7.1	10.0 8.1 7.0 7.5	10.0 7.7 7.0 7.6	10.0 7.6 7.0 7.5	10.0 7.7 5.1* 6.6	2.0* 6.2											
26250000 121 NW 34TH ST(6.5L)	6.312	6.919	L 1	1 3.1	40 17500 FC125M	CRACKING RIDE	9.0 7.5	9.0 7.9	9.0 7.7	9.0 7.3	9.0 7.2	9.0 7.1	9.0 6.6	9.0 6.9		10.0 8.1	10.0 7.7	10.0 7.6	10.0 7.7											
		(2026)				CRACKING RIDE	10.0 7.6	10.0 7.8	10.0 6.7	10.0 7.4	10.0 7.3	9.0 7.2	8.0 7.2	7.0 7.1	7.0 7.1	7.0 7.5	7.0 7.6	7.0 7.5	10.0 8.4	9.0 8.0											
26250000 121 NW 37TH AVE(5.7L) 2077123 PREFERRED MATERIALS, INC.	5.677 5.652	6.312 5.990	L 1 L	1 3.1 2008 (2010)	40 17500 FC125M 0012	CRACKING RIDE CRACKING RIDE	9.0 7.5 10.0 7.6	9.0 7.9 10.0 7.8	9.0 7.7 10.0 6.7	9.0 7.3 10.0 7.4	9.0 7.2 10.0 7.3	9.0 7.1 9.0 7.2	9.0 6.6 8.0 7.2	9.0 6.9 7.0 7.1	7.0 7.1	10.0 8.1 7.0 7.5	10.0 7.7 7.0 7.6	10.0 7.6 7.0 7.5	10.0 7.7 7.2 7.1	4.0* 6.7											

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = ALACHUA

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	LN / RW / FY-P / FY-F	SYS / %T / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	TYP	SPD	AADT	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
26250000	5.444	5.677	L	1	1	40		CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5		10.0	10.0	10.0	10.0													
121			1	2.9			16500	RIDE	8.1	8.2	8.1	7.5	7.6	7.5	6.9	7.6		8.1	7.7	7.6	7.7													
NW 33RD LN(5.5L)							FC125M																												
								CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.0	9.0											
					(2026)			RIDE	7.6	7.8	6.7	7.4	7.3	7.2	7.2	7.1	7.1	7.5	7.6	7.5	8.3	7.9											
26250000	4.345	4.665	L	1	1	40		CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5		10.0	10.0	10.0	10.0													
121			1	2.9			16000	RIDE	8.1	8.2	8.1	7.5	7.6	7.5	6.9	7.6		8.1	7.7	7.6	7.7													
CR 172(4.3C)							FC125M																												
								CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	9.1	8.0											
					(2026)			RIDE	7.6	7.8	6.7	7.4	7.3	7.2	7.2	7.1	7.1	7.5	7.6	7.5	7.2	6.8											
26250000	3.847	4.345	L	1	1	35		CRACKING	7.5	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0													
121			1	2.9			19500	RIDE	6.9	7.1	7.1	6.6	6.4	6.6	6.6	5.9	5.8	8.1	7.7	7.6	7.7													
CR 338(3.8C)							FC125M																												
2077123	3.540	4.406	L	2008		0012		CRACKING	7.5	7.5	7.5	7.5	7.5	7.0	7.0	6.5	6.5	6.5	6.5	6.1*	5.9*	3.0*												
PREFERRED MATERIALS, INC.			(2010)					RIDE	6.8	7.0	6.2										6.2	5.8												
2077126	0.017	4.366	L	2028		0012																													
26250000	3.551	3.847	L	1	1	35		CRACKING	7.5	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0													
121			1	2.9			22500	RIDE	6.9	7.1	7.1	6.6	6.4	6.6	6.6	5.9	5.8	8.1	7.7	7.6	7.7													
NW 7TH AVE(3.7L)							FC125M																												
2077123	3.540	4.406	L	2008		0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.5	7.5	7.5	7.5	6.8	6.6	3.5*												
PREFERRED MATERIALS, INC.			(2010)					RIDE	7.9	7.8	7.0	7.4	7.6	7.4	7.5	7.4	7.3	7.3	7.4	7.2	7.2	6.8												
2077126	0.017	4.366	L	2028		0012																													
26250000	3.087	3.551	L	1	1	35		CRACKING	7.5	7.5	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0													
121			2	2.9			22500	RIDE	6.4*	6.1	5.0*	7.6	7.6	7.1	7.2	6.8	6.8	6.7	6.9	6.4	6.6													
SR 26A(3.2C)							FC125M																												
								CRACKING	8.0	7.0		10.0	10.0	10.0	9.5	9.0	9.0	9.0	9.0	8.2	8.4	6.5												
					(2017)			RIDE	6.6	6.7		8.3	8.4	8.0	8.0	8.0	7.9	7.7	7.8	7.9	6.6	6.2												
2077126	0.017	4.366	L	2028		0012																													
26250000	1.623	3.087	L	1	1	45		CRACKING	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0													
121			3	2.9			44500	RIDE	6.4*	6.1*	6.3*	7.6	7.6	7.1	7.2	6.8	6.8	6.7	6.9	6.4	6.6													
SIDE ROAD L(1.7L)							FC125M																												
4305471	1.623	3.285	L	2015		0012		CRACKING	8.0	7.0		10.0	10.0	10.0	9.5	9.0	9.0	9.0	9.0	8.2	7.5	5.5*												
PREFERRED MATERIALS, INC.			(2017)				SPR	RIDE	6.6	6.7		8.3	8.4	8.0	8.0	8.0	7.9	7.7	7.8	7.9	7.9	7.5												
2077126	0.017	4.366	L	2028		0012																													
26250000	0.000	1.623	L	1	1	45		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0	9.0	9.0	8.0													
121			3	2.9			26806	RIDE	8.2	8.4	8.3	7.9	8.0	7.9	7.7	7.0	7.7	7.6	7.4	7.5	7.5													
SR-121/WILLISTON RD(0.0L)							FC3																												
2076631	0.000	1.591	C	1994		0213		CRACKING	8.0	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.0*	1.0*												
JOHN C. HIPP CONSTRUCTION			(1998)				S	RIDE	7.5	7.3	7.3	7.6	7.6	7.5	7.6	7.6	7.6	7.4	7.5	7.4	7.3	6.9												
2077126	0.017	4.366	L	2028		0012																													
26260000	0.000	9.270	R	4	1	70		CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0													
93 I75	372.7	382.0	3	29.6		71500		RIDE	8.6	8.6	8.7	8.4	8.4	8.3	8.2	8.1	8.0	8.2	7.6	7.5	7.4													
							FC5M																												
4288051	0.000	9.271	C	2016		0012		CRACKING	9.0	9.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	8.5	6.5												
PREFERRED MATERIALS, INC.			(2018)				SPR	RIDE	7.3	7.4	7.8		9.1	9.1	9.1	9.1	9.0	9.0	9.0	9.0	9.0	8.9												
26260000	9.270	16.195	R	4	1	70		CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0													
93 I75	382.0	388.9	3	29.3		98500		RIDE	8.6	8.6	8.7	8.4	8.4	8.3	8.2	8.1	8.0	8.2	7.6	7.3	7.3													
							FC5M																												
4288041	9.270	15.813	C	2016		0012		CRACKING	8.5	8.5	8.5	7.5	7.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.4	6.5												
PREFERRED MATERIALS, INC.			(2019)				SPR	RIDE	7.1	7.4	7.7	7.8	8.5	9.0	8.9	8.7	8.7	8.7	8.7	8.7	8.7	8.6												
26260000	16.195	27.233	R	4	1	70		CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0													
93 I75	388.9	399.9	3	29.3		73000		RIDE	8.8	8.3	8.6	8.2	8.3	8.2	8.0	7.9	7.9	8.0	7.8	7.6	7.6													
							FC5M																												
4288031	15.811	27.232	C	2015		0012		CRACKING	9.0	9.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.9	7.0												
PREFERRED MATERIALS, INC.			(2018)				SPR	RIDE	7.5	7.6	7.9		9.1	9.1	9.1	9.1	9.0	9.0	9.0	8.9	8.9	8.8												
26260000	27.233	35.190	R	4	1	70		CRACKING	9.5	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0													
93 I75	399.9	407.9	3	29.3		47000		RIDE	8.6	8.6	8.6	8.2	8.3	8.2	8.0	7.9	7.9	8.0	7.3	7.0	7.2													
							FC5M																												
4288021	27.233	35.190	C	2015		0012		CRACKING	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.3	8.7	6.5												
ANDERSON COLUMBIA CO., INC			(2017)				SPR	RIDE	7.1	7.1	7.6	8.6	9.0	8.9	8.9	8.9	8.9	8.9	8.8	8.8	8.8	8.7												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 2 COUNTY = ALACHUA ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	LN	%T	AADT	SURFTYPE / ASTYPE / WKMX-P / WKMX-F	DISTRESS / RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	FUTURE 2031 (PMRS)
26260000	27.233	35.190	L	4	1	70					CRACKING	9.5	8.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	8.0	8.0	8.0														
93 I75	399.9	407.9	3	29.3		47000					RIDE	8.5	8.4	8.6	8.2	8.3	8.2	8.0	7.8	7.8	7.8	7.2	6.9	7.0														
										FC5M																												
4288021	27.233	35.190	C	2015		0012					CRACKING	8.0	8.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.1	8.5	6.5													
ANDERSON COLUMBIA CO., INC				(2017)						SPRIDE		6.7	7.1	7.4	8.6	8.9	8.8	8.8	9.0	8.9	8.9	8.9	8.9	8.9	8.8													
26260000	15.813	27.233	L	4	1	70					CRACKING	10.0	9.5	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	8.0	8.0	8.0														
93 I75	388.5	399.9	3	29.3		73000					RIDE	8.7	8.8	8.6	8.2	8.3	8.2	8.0	7.8	7.8	7.8	7.8	7.7	7.6														
										FC5M																												
4288031	15.811	27.232	C	2015		0012					CRACKING	8.0	8.0	8.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.8	7.0													
PREFERRED MATERIALS, INC.				(2018)						SPRIDE		7.4	7.6	7.8		9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.0													
26260000	9.270	15.813	L	4	1	70					CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	9.0	8.5	8.5														
93 I75	382.0	388.5	3	29.3		98500					RIDE	8.6	8.6	8.7	8.4	8.4	8.3	8.2	8.0	7.9	8.1	7.8	7.6	7.6														
										FC5M																												
4288041	9.270	15.813	C	2016		0012					CRACKING	8.5	8.5	8.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.7	7.0													
PREFERRED MATERIALS, INC.				(2019)						SPRIDE		7.3	7.6	7.9	8.0	8.4	9.1	8.9	8.8	8.8	8.8	8.8	8.7	8.7	8.6													
26260000	0.000	9.270	L	4	1	70					CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	8.5	8.5	8.5														
93 I75	372.7	382.0	3	29.6		71500					RIDE	8.6	8.6	8.7	8.4	8.4	8.3	8.2	8.0	7.9	8.1	7.6	7.4	7.3														
										FC5M																												
4288051	0.000	9.271	C	2016		0012					CRACKING	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	8.3	6.5													
PREFERRED MATERIALS, INC.				(2018)						SPRIDE		7.2	7.5	7.8		9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.0	9.0	8.9													
26260048	0.000	0.661	C	1	1	35					CRACKING																												
2221			2	2.0		400					RIDE																												
											CRACKING														8.2													
											RIDE														5.8													
26260048	0.661	0.791	C	1	1	35					CRACKING																												
2221			1	2.0		400					RIDE																												
											CRACKING														7.0													
											RIDE														3.8*													
26260058	0.000	1.550	C	1	1	25					CRACKING																												
253			2	12.0		1000					RIDE																												
										DGFC																												
				(2025)							CRACKING																										10.0	9.2	8.0
											RIDE																										7.9	7.8	7.4

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).