

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = BAKER																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT	AT (MP SIDE)																					
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P																	
CONTRACTOR	(AGE ONE YEAR)				ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																(PMRS)	
27010000	0.000	9.273	C	1	1 60	CRACKING		3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	6.5	6.5		
10 90			2	12.1	7200	RIDE		8.3	8.1	7.9	8.4	8.1	8.1	8.0	8.3	8.3	8.2	8.0	8.0	7.9		
FOX HOLLOW LN(0.6R)					FC125M																	
				(2016)		CRACKING		6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	6.9	5.0*	
						RIDE		7.9	7.8	7.6	8.3	8.3	8.3	8.3	8.2	8.2	8.1	8.0	7.9	8.0	7.6	
27010000	9.273	10.029	R	1	7 50	CRACKING		8.0	7.0	7.0	7.0	7.0	6.0*	6.0*	4.5*	4.5*	10.0	10.0	10.0	10.0		
10 90			2	12.1	7200	RIDE		8.5	8.3	8.4	8.3	7.8	7.7	7.6	7.5	7.7	8.2	8.2	8.0	8.0		
					DGFC																	
				(2025)		CRACKING		10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.5	6.0*	6.0*	6.0*	6.0*	10.0	9.0	
						RIDE		8.0	7.8	7.8	7.6	7.5	7.4	7.4	7.3	7.4	7.3	7.3	7.1	8.3	7.9	
27010000	10.029	11.890	C	1	1 50	CRACKING		6.5	6.5	6.5	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	6.5	6.5		
10 90			2	20.9	2300	RIDE		7.8	7.6	7.4	8.4	8.1	8.0	7.9	8.0	8.0	7.9	7.7	7.5	7.3		
NO NAME(10.5R)					FC125M																	
4305591	10.029	11.865	C	2015	0012	CRACKING		6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	7.4	5.5*	
ANDERSON COLUMBIA CO., INC(2016)					SPRIDE			7.2	7.2	6.9	8.4	8.4	8.3	8.3	8.2	8.2	8.0	7.8	7.7	7.8	7.4	
27010000	11.890	18.690	C	1	1 60	CRACKING		9.5	9.5	9.5	9.5	9.5	7.0	7.0	6.5	6.5	4.5*	4.5*		10.0		
10 90			2	20.9	5600	RIDE		8.9	8.9	8.8	8.7	8.3	8.2	8.1	8.2	8.1	7.9	7.7		8.6		
THOMAS SWEAT RD(11.9R)					FC125M																	
2079144	12.071	18.493	C	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	7.5	7.5	6.8	4.5*	
PREFERRED MATERIALS, INC. (2012)					SPRIDE			8.6	8.5	8.5	8.1	8.1	7.9	7.9	7.9	7.9	7.7	7.8	7.7	7.8	7.4	
27010000	18.690	20.378	R	1	1 45	CRACKING		10.0	10.0	10.0	10.0	10.0	7.5	7.5	4.5*	4.5*	3.5*	3.5*		10.0		
10 90			2	20.9	11200	RIDE		8.8	8.5	8.5	8.5	8.0	7.7	7.4	7.4	7.0	6.7	6.2		8.6		
N SHERMAN AVE(18.7C)					FC125M																	
2079144	18.623	20.274	R	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	7.5	6.5	4.0*	
PREFERRED MATERIALS, INC. (2012)					SPRIDE			8.6	8.5	8.5	8.3	8.3	8.3	8.2	8.1	8.1	7.9	8.0	8.0	7.7	7.3	
27010000	20.378	20.946	R	1	1 35	CRACKING		10.0	10.0	9.5	8.0	8.0	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0		
10 90			1	20.9	8300	RIDE		8.7	8.4	8.2	8.2	7.7	7.6	7.2	7.4	7.3	7.1	7.0	6.8	8.2		
S MLK JR DR(20.8R)					FC125M																	
2079144	20.274	20.942	R	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5	7.5	7.0	6.0*	5.8*	3.5*	
PREFERRED MATERIALS, INC. (2012)					SPRIDE			8.2	8.2	8.2	7.8	7.8	7.8	7.6	7.7	7.6	7.6	7.9	7.9	7.2	6.8	
27010000	20.946	25.448	C	1	1 60	CRACKING		9.5	9.5	9.5	9.5	8.0	7.0	7.0	6.5	6.5	4.5*	4.5*	4.5*	10.0		
10 90			2	16.2	5100	RIDE		9.1	9.0	8.9	8.9	8.3	8.1	8.2	8.2	8.1	8.0	7.9	7.5	8.2		
CR 228(21.0R)					FC125M																	
2079144	20.942	23.324	C	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5	7.5	7.0	6.8	4.5*		
PREFERRED MATERIALS, INC. (2012)					SPRIDE			8.2	8.2	8.2	7.8	7.8	7.8	7.6	7.7	7.6	7.6	7.5	7.5	7.4	7.0	
27010000	20.378	20.946	L	1	1 35	CRACKING		10.0	10.0	9.5	8.0	8.0	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0		
10 90			1	20.9	8300	RIDE		8.7	8.4	8.2	8.2	7.7	7.6	7.2	7.4	7.3	7.1	7.0	6.8	8.2		
BLAIR ST(20.5L)					FC125M																	
2079144	20.452	20.942	L	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5	7.5	7.0	7.0	7.0	4.5*	
PREFERRED MATERIALS, INC. (2012)					SPRIDE			8.2	8.2	8.2	7.8	7.8	7.8	7.6	7.7	7.6	7.6	7.8	7.8	7.6	7.2	
27010000	18.690	20.378	L	1	1 45	CRACKING		10.0	10.0	10.0	10.0	10.0	7.5	7.5	6.5	4.5*	3.5*	3.5*		10.0		
10 90			2	20.9	11200	RIDE		8.6	8.6	8.4	8.5	8.0	7.8	7.6	7.5	7.2	7.0	6.4		8.5		
N SHERMAN AVE(18.7C)					FC125M																	
2079144	18.686	20.452	L	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	8.0	7.0	7.0	7.0	4.5*	
PREFERRED MATERIALS, INC. (2012)					SPRIDE			8.4	8.4	8.4	8.2	8.2	8.1	8.0	8.1	7.9	7.8	7.8	7.8	7.6	7.2	
27010000	9.273	10.029	L	1	7 50	CRACKING		10.0	10.0	10.0	9.5	9.5	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0		
10 90			2	12.1	7200	RIDE		8.7	8.5	8.6	8.5	8.4	8.2	8.1	8.4	8.4	8.4	8.4	8.2	8.2		
					FC125																	
				(2025)		CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	7.5	7.5	10.0	9.0	
						RIDE		8.2	8.2	8.2	7.9	7.9	7.9	7.9	7.8	7.8	7.8	7.9	7.8	8.6	8.2	
27020000	0.000	14.702	C	1	1 60	CRACKING		10.0	10.0	10.0	9.5	9.5	9.5	9.5	7.0	6.5	6.5	6.5	6.5	6.5		
2			2	28.7	450	RIDE		8.4	8.3	8.6	8.6	8.1	7.8	7.7	7.9	7.7	7.4	7.8	7.7	7.8		
OSCEOLA WILDLIFE MA(0.2R)					FC125A																	
4233981	0.000	14.650	C	2015	0012	CRACKING		6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	7.8	6.0*	
ANDERSON COLUMBIA CO., INC(2016)					SPRIDE			7.9	7.7	7.7	8.4	8.4	8.4	8.2	8.1	7.9	7.6	7.5	7.4	7.4	7.0	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = BAKER

RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR												FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS		2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
INTERSECT AT (MP SIDE)																					
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P																
CONTRACTOR (AGE ONE YEAR)					ASTYPE																
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																
27030000	0.000	9.050	C	1	7 60	CRACKING	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	
121			2	13.4	7600	RIDE	8.3	8.1	8.8	8.7	8.5	8.4	8.4	8.6	8.6	8.6	8.6	8.5	8.4	8.4	
SAPP RD(0.4L)					FC125M																
4454361	0.000	9.027	C	2023	0012	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.0*	6.0*	10.0	9.0
PREFERRED MATERIALS, INC. (2025)					SPRIDE		8.3	8.2	8.3	8.2	8.2	8.2	8.2	8.1	8.2	8.0	8.0	8.0	8.0	8.6	8.2
27030000	9.050	9.223	C	1	1 45	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	
121			2	13.4	7600	RIDE	7.3	7.2	8.8	8.7	8.5	8.4	8.4	8.6	8.6	8.6	8.6	8.5	8.4	8.4	
CR 23A(9.1L)					FC125																
2079261	0.000	9.160	C	2001	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*	5.5*	5.5*	7.0	3.5*
ANDERSON COLUMBIA CO., INC(2002)					SPRIDE		8.3	8.2	8.3	7.2	7.2	7.2	7.2	7.0	7.1	7.0	6.9	7.0	7.0	6.2	5.8
27030000	9.223	10.150	R	1	1 45	CRACKING	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
121			2	20.9	11200	RIDE	7.3	7.2	6.3*		8.3	8.1	8.0	8.3	8.4	8.1	8.0	8.0	7.9	8.2	
INDUSTRIAL WAY(9.5R)					FC125																
2079111	9.223	10.783	C	2002	0213	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	7.5	7.0	6.0*	4.0*	4.0*	2.3*	0.0*
J.B. COXWELL CONTRACTING, I(2004)					SPRIDE		7.9	8.0	7.9	7.9	7.8	7.9	7.9	7.6	7.8	7.7	7.7	7.7	7.7	7.2	6.8
4460423	9.321	16.404	C	2028	0012																
27030000	10.150	10.796	R	1	1 30	CRACKING	7.0	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
121			1	20.9	11200	RIDE	7.9	7.8	7.0		8.1	7.9	7.6	7.8	7.8	7.4	7.1	7.3	7.1		
JONATHAN ST W(10.2R)					FC125																
2079111	9.223	10.783	C	2002	0213	CRACKING	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	5.5*	5.5*	5.5*	2.0*
J.B. COXWELL CONTRACTING, I(2004)					SPRIDE		7.2	7.0	6.8	6.9	7.0	7.1	6.9	6.5	6.4	6.3	6.5	6.7	5.9	5.5	
4460423	9.321	16.404	C	2028	0012																
27030000	10.796	11.823	C	1	1 40	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	
121			2	20.9	5100	RIDE	7.9	7.8	8.1	8.1	8.1	7.7	7.4	6.9	7.2	8.4	7.9	7.6	7.7	8.0	
MACCLENNY AVE(10.8C)					FC125																
2079113	10.824	11.890	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	6.0*	6.0*	5.9*	3.0*
ANDERSON COLUMBIA CO., INC(2008)					SPRIDE		8.1	7.9	8.0	7.7	7.7	7.6	7.5	7.7	7.4	7.1	7.5	7.3	7.4	7.0	
4460423	9.321	16.404	C	2028	0012																
27030000	11.823	16.404	C	1	1 60	CRACKING	9.5	9.5	8.5	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	
121			2	9.7	3031	RIDE	8.1	8.0	8.3	8.1	7.9	7.7	7.7	7.9	7.9	8.4	8.3	8.3	8.2	8.2	
CR 228(12.0R)					FC125M																
2079113	12.074	16.404	C	2007	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	7.0	7.0	7.0	4.0*	
ANDERSON COLUMBIA CO., INC(2008)					SPRIDE		8.1	8.0	8.1	7.8	7.8	7.8	7.8	7.8	7.6	7.5	7.6	7.5	7.5	7.5	
4460423	9.321	16.404	C	2028	0012																
27030000	10.150	10.796	L	1	1 30	CRACKING	7.0	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
121			1	20.9	11200	RIDE	7.9	7.8	7.0		8.1	7.9	7.6	7.8	7.8	7.4	7.1	7.3	7.1		
S SEVENTH ST(10.3L)					FC125																
2079111	9.223	10.783	C	2002	0213	CRACKING	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	3.0*	4.0*	4.2*	1.0*
J.B. COXWELL CONTRACTING, I(2004)					SPRIDE		7.2	7.0	6.8	6.9	7.0	7.1	6.9	6.5	6.4	6.3	5.7	5.6	5.7	5.3*	
4460423	9.321	16.404	C	2028	0012																
27030000	9.223	10.150	L	1	1 45	CRACKING	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
121			2	20.9	11200	RIDE	7.3	7.2	6.3*		8.2	7.9	7.3	8.1	8.2	8.1	8.0	7.9	8.0		
GEORGE HODGES RD(9.4L)					FC125																
2079111	9.223	10.783	C	2002	0213	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.0	6.0*	4.0*	4.0*	3.5*	0.0*
J.B. COXWELL CONTRACTING, I(2004)					SPRIDE		8.0	8.0	7.9	7.6	7.4	7.5	7.5	7.5	7.5	7.3	7.1	7.4	7.0	6.6	
4460423	9.321	16.404	C	2028	0012																
27070000	5.617	6.024	R	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0
228			2	2.6	13000	RIDE	7.9	7.7	8.0	7.7	7.4	6.7	7.2	7.7	7.4	7.0	6.8	7.1	6.7		
E M SPENCE RD(6.0C)					FC125M																
4376131	5.617	6.138	R	2019	0012	CRACKING	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	9.6	8.0
ANDERSON COLUMBIA CO., INC(2021)					SPRIDE		6.8	6.6	6.2	6.7	6.6	6.6	6.1	6.3	8.1	7.9	8.0	7.7	7.9	7.5	
27070000	6.024	7.544	C	1	1 30	CRACKING	4.0*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	
228			2	2.6	13000	RIDE	8.1	7.9	7.3	7.4		7.7	7.8	7.9	7.9	7.9	7.9	7.7	7.7	7.5	
BARBER RD(6.1L)					FC125																
4376131	6.138	7.544	C	2019	0012	CRACKING	7.5	7.5	7.0	6.5	6.5	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.5
ANDERSON COLUMBIA CO., INC(2021)					SPRIDE		7.6	7.6	7.4	7.4	7.4	7.5	7.4	7.3	8.1	8.1	8.0	8.1	7.8	7.4	
27070000	5.617	6.024	L	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	
228			2	2.6	13000	RIDE	8.1	7.6	7.9	8.0	7.9	7.2	7.3	7.7	7.7	7.5	7.5	7.3	7.1	7.1	
E M SPENCE RD(6.0C)					FC125M																
4376131	5.617	6.138	L	2019	0012	CRACKING	9.5	8.0	8.0	7.0	7.0	7.0	7.0	6.0*	6.0*	10.0	10.0	10.0	10.0	9.5	8.0
ANDERSON COLUMBIA CO., INC(2021)					SPRIDE		6.8	6.6	6.7	6.3						8.2	8.0	8.0	8.0	7.9	7.5

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = BAKER																								
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR											FUTURE		
INTERSECT	AT	(MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKMX-P	ASTYPE			2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
CONTRACTOR	(AGE ONE YEAR)										2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F	W_BMP	W_EMP																						
27090000	0.000	20.400	R	4	7 70	CRACKING					10.0	9.5	8.0	7.0	6.0*	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	
8	I10	314.4	334.8	2	29.2	23924	RIDE				9.0	8.9	8.9	8.8	8.1	7.6	7.2	6.5	7.4	8.4	8.1	8.5	8.4	
						FC5M																		
4434231	8.918	20.396	C	2022	0012	CRACKING					10.0	10.0	10.0	9.0	9.0	8.0	6.5	6.5	4.5*	4.5*	3.5*		10.0	9.0
ANDERSON	COLUMBIA CO., INC	(2025)				SPRIDE					8.3	8.2	8.0	8.3	8.2	8.5	8.2	8.4	8.3	8.0	7.6		8.7	8.6
27090000	20.400	25.462	R	4	1 70	CRACKING					10.0	9.5	8.0	7.0	6.0*	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	
8	I10	334.8	339.9	2	30.3	40000	RIDE				9.0	8.9	8.9	8.8	8.1	7.6	7.2	6.5	7.4	8.4	7.9	8.3	8.3	
						FC5M																		
2130034	20.398	25.462	C	2008	0012	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	6.5	6.5	6.0*	5.4*	2.5*
ANDERSON	COLUMBIA CO., INC	(2009)				RIDE					8.2	8.2	8.1	8.2	8.2	8.3	8.3	8.3	8.3	8.3	8.2	8.1	8.1	8.0
4460421	20.400	25.462	C	2024	0012																			
27090000	20.400	25.462	L	4	1 70	CRACKING					10.0	9.5	9.5	9.5	8.0	6.0*	6.0*	4.5*	4.5*	10.0	10.0	10.0	10.0	
8	I10	334.8	339.9	2	30.3	40000	RIDE				9.1	9.0	9.0	9.0	8.6	8.4	8.3	8.3	8.3	8.5	7.9	8.3	8.2	
						FC5M																		
2130034	20.398	25.462	C	2008	0012	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	6.5	6.5	6.5	6.5	3.5*
ANDERSON	COLUMBIA CO., INC	(2009)				RIDE					8.2	8.2	8.1	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.3	8.3	8.3	8.2
4460421	20.400	25.462	C	2024	0012																			
27090000	0.000	20.400	L	4	7 70	CRACKING					10.0	9.5	9.5	9.5	8.0	6.0*	6.0*	4.5*	4.5*	10.0	10.0	10.0	10.0	
8	I10	314.4	334.8	2	29.2	23924	RIDE				9.1	9.0	9.0	9.0	8.6	8.4	8.3	8.3	8.3	8.5	8.1	8.6	8.5	
						FC5M																		
4434231	8.918	20.396	C	2022	0012	CRACKING					10.0	10.0	10.0	10.0	10.0	8.0	8.0	8.0	7.0	5.5*	5.5*		10.0	9.0
ANDERSON	COLUMBIA CO., INC	(2025)				SPRIDE					8.5	8.4	8.4	8.6	8.5	8.6	8.6	8.6	8.6	8.6	8.4		8.7	8.6

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).