

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = BRADFORD -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)		W_BMP		W_EMP		RW		FY-P		WKMX-P		ASTYPE										2031
		(AGE_ONE YEAR)		YEAR																(PMRS)		
		W_BMP		W_EMP		RW		FY-F		WKMX-F												
28010000		0.000		5.291	R	1	7 65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	7.0	7.0		
200	301				2	20.8		27960	RIDE	8.8	8.9	8.9	8.5	8.4	8.4	8.6	8.6	8.5	8.4	8.4	8.4	8.3
CR 221 WYE (0.8R)																						
4472041		0.004		5.271	R	2024		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.7*	10.0
ANDERSON	COLUMBIA	CO.,	INC	(2026)					SPRIDE	8.4	8.3	8.5	8.4	8.6	8.6	8.7	8.5	8.5	8.5	8.6	8.6	9.0
28010000		6.038		6.923	R	1	7 55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	7.0	7.0		
200	301				2	4.8		10100	RIDE	8.8	8.9	8.9	8.5	8.4	8.4	8.6	8.6	8.5	8.4	8.4	8.4	8.3
COMMERCIAL DR L(6.1R)																						
4472041		6.038		6.921	R	2024		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	10.0
ANDERSON	COLUMBIA	CO.,	INC	(2026)					SPRIDE	8.4	8.3	8.5	8.4	8.6	8.5	8.6	8.4	8.4	8.5	8.4	8.4	8.7
28010000		6.923		8.044	R	1	1 35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	8.0	8.0	
200	301				2	4.8		10100	RIDE	8.8	8.9	8.9	8.0	7.9	7.8	8.1	8.0	7.7	7.7	7.8	7.5	7.7
ALEXANDER ST(7.0R)																						
4342981		6.923		8.044	C	2017		0012	CRACKING	7.0	7.0	7.0	6.5	6.5		10.0	10.0	10.0	10.0	10.0	9.5	9.1
ANDERSON	COLUMBIA	CO.,	INC	(2020)					SPRIDE	7.3	7.2	7.2	7.0	7.3		8.1	8.0	7.8	7.6	7.8	7.8	7.7
28010000		8.044		8.954	R	1	1 30	CRACKING	10.0	9.5	9.5	9.5	9.5	8.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0
200	301				2	4.8		19000	RIDE	7.4	7.2	7.2	7.1	6.7	6.5	8.2	8.1	7.9	7.8	7.6	7.3	7.3
MADISON ST(8.1C)																						
4361561		8.044		8.954	C	2017		0012	CRACKING	7.0	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	8.8	8.4
ANDERSON	COLUMBIA	CO.,	INC	(2020)					SPRIDE	7.2	6.4	6.8	6.4	6.6		7.7	7.7	7.7	7.7	7.7	7.7	7.6
28010000		8.954		9.875	R	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	7.0	6.0*	6.0*	
200	301				2	4.8		5500	RIDE	7.9	8.2	8.1	7.9	7.9	7.8	8.1	8.0	7.8	7.8	7.6	7.5	7.4
ANDREWS ST(9.0C)																						
4323091		8.954		14.320	C	2017		0012	CRACKING	6.0*	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	8.9	9.5
ANDERSON	COLUMBIA	CO.,	INC	(2020)					SPRIDE	7.2	6.8	7.2	6.9	7.1		8.5	8.5	8.5	8.5	8.4	8.5	8.4
28010000		9.875		11.362	R	1	1 55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	
200	301				2	4.8		5500	RIDE	8.7	8.9	8.8	8.3	8.3	8.3	8.5	8.5	8.4	8.3	8.3	8.3	8.2
UNSIGNED(10.1R)																						
4323091		8.954		14.320	C	2017		0012	CRACKING	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	9.1	9.7
ANDERSON	COLUMBIA	CO.,	INC	(2021)					SPRIDE	8.1	8.1	8.4	8.3	8.5		8.9	8.9	8.9	8.9	8.9	8.9	8.9
28010000		11.916		14.330	R	1	1 65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	
200	301				2	4.8		30500	RIDE	8.7	8.9	8.8	8.3	8.3	8.3	8.5	8.5	8.4	8.3	8.3	8.3	8.2
NE 196 TER(12.3R)																						
4323091		8.954		14.320	C	2017		0012	CRACKING	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	8.4	8.9
ANDERSON	COLUMBIA	CO.,	INC	(2021)					SPRIDE	8.1	8.1	8.4	8.3	8.5		9.1	9.0	9.1	9.0	9.0	9.1	9.0
28010000		14.330		15.052	R	1	1 55	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	7.0	7.0	6.5	6.5		
200	301				2	4.8		30500	RIDE	8.7	8.2	8.3	7.8	7.8	7.6	7.8	7.6	7.0	6.9	6.3*	6.2*	
FC5M																						
4286921		14.320		15.857	C	2014		0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	9.5	7.5	7.5	6.5	6.5	6.5	4.0*
ANDERSON	COLUMBIA	CO.,	INC	(2015)					SPRIDE	7.7	8.3	8.4	8.4	8.4	8.2	8.3	8.2	8.1	8.5	8.4	8.3	8.2
4286922		14.330		15.875	C	2026		0012														8.0
28010000		15.052		15.857	R	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	7.0	7.0	6.5	6.5	
200	301				2	4.8		30500	RIDE	8.1	8.2	8.3	7.8	7.8	7.6	7.8	7.6	7.0	6.9	6.3	6.2	
CR-225/LAKE ST(15.4R)																						
4286921		14.320		15.857	C	2014		0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	9.5	7.5	4.5*	4.5*	4.5*	4.3*	
ANDERSON	COLUMBIA	CO.,	INC	(2015)					SPRIDE	7.7	8.3	8.4	8.4	8.4	8.2	8.3	8.2	7.6	7.8	7.9	7.6	7.7
4286922		14.330		15.875	C	2026		0012														7.3
28010000		15.857		20.227	R	1	1 65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0	7.0	7.0	6.0*	
200	301				2	29.1		24000	RIDE	8.9	8.9	8.9	8.4	8.4	8.3	8.5	8.5	8.4	8.3	8.3	8.3	
CR 125(16.3C)																						
4323151		15.857		20.078	C	2017		0012	CRACKING	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	9.0
ANDERSON	COLUMBIA	CO.,	INC	(2019)					SPRIDE	8.2	8.2	8.5	8.4		8.9	8.9	8.9	8.8	8.8	8.9	8.8	8.9
28010000		15.857		20.227	L	1	1 65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0	7.0	7.0	6.0*	
200	301				2	29.1		24000	RIDE	8.9	8.9	8.8	8.4	8.3	8.4	8.5	8.5	8.4	8.3	8.3	8.3	
CR 125(16.3C)																						
4323151		15.857		20.078	C	2017		0012	CRACKING	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	8.9
ANDERSON	COLUMBIA	CO.,	INC	(2019)					SPRIDE	8.2	8.1	8.4	8.4		8.9	8.9	8.9	8.8	8.8	8.8	8.8	8.8

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 ** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = BRADFORD -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)	
28010000	15.052	15.857	L	1	1	45	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	8.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	
200 301			2	4.8		30500	RIDE	8.0	8.3	8.2	7.9	7.9	7.6	7.6	7.6	7.4	7.3	6.9	7.0	7.0		
CR 225(15.3L)						FC125M																
4286921	14.320	15.857	C	2014	0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	2.0*
ANDERSON COLUMBIA CO., INC(2015)						SPRIDE	7.0	8.3	8.4	8.3	8.4	8.1	8.2	8.1	7.2	7.5	7.7	7.7	7.6	7.6	7.2	
4286922	14.330	15.875	C	2026	0012																	
28010000	14.330	15.052	L	1	1	55	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	8.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	
200 301			2	4.8		30500	RIDE	8.8	8.3	8.2	7.9	7.9	7.6	7.6	7.6	7.4	7.3	6.9	7.0	7.0		
NW 219 ST(14.8L)						FC5M																
4286921	14.320	15.857	C	2014	0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	6.5	4.5*	5.1*	3.9*	0.0*	
ANDERSON COLUMBIA CO., INC(2015)						SPRIDE	7.0	8.3	8.4	8.3	8.4	8.1	8.2	8.1	8.1	8.4	8.4	8.2	8.0	8.0	7.8	
4286922	14.330	15.875	C	2026	0012																	
28010000	11.916	14.330	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0		
200 301			2	4.8		30500	RIDE	8.8	8.9	8.9	8.3	8.3	8.3	8.5	8.5	8.4	8.4	8.3	8.3	8.1		
NW 196 ST(12.3L)						FC5M																
4323091	8.954	14.320	C	2017	0012	CRACKING	7.0	7.0	7.0	7.0	7.0			10.0	10.0	10.0	9.0	8.7	8.8	6.5		
ANDERSON COLUMBIA CO., INC(2021)						SPRIDE	8.1	8.0	8.3	8.2	8.6			9.0	8.9	9.0	8.9	8.9	9.0	8.8		
28010000	9.875	11.362	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0		
200 301			2	4.8		5500	RIDE	8.8	8.9	8.9	8.3	8.3	8.3	8.5	8.5	8.4	8.4	8.3	8.3	8.1		
NW 36TH AVE(10.1L)						FC5M																
4323091	8.954	14.320	C	2017	0012	CRACKING	7.0	7.0	7.0	7.0	7.0			10.0	10.0	10.0	10.0	9.5	9.4	7.0		
ANDERSON COLUMBIA CO., INC(2021)						SPRIDE	8.1	8.0	8.3	8.2	8.6			8.8	8.6	8.7	8.7	8.7	8.7	8.5		
28010000	8.954	9.875	L	1	1	45	CRACKING	10.0	10.0	10.0	9.5	9.5	8.0	8.0	6.5	6.5	6.5	6.5	6.5	6.5		
200 301			2	4.8		5500	RIDE	8.0	8.3	8.1	7.9	7.8	7.5	7.6	7.4	6.9	7.0	6.8	7.3	7.4		
ANDREWS ST(9.0C)						FC125M																
4323091	8.954	14.320	C	2017	0012	CRACKING	6.5	6.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	8.9	9.5	8.0	
ANDERSON COLUMBIA CO., INC(2020)						SPRIDE	7.2	6.9	7.1	6.8	7.0			8.5	8.3	8.4	8.4	8.4	8.4	8.4		
28010000	8.044	8.954	L	1	1	30	CRACKING	10.0	9.5	9.5	7.0	6.0*	6.0*	10.0	10.0	10.0	10.0	8.0	7.0	7.0		
200 301			2	4.8		19000	RIDE	7.0	5.9	6.1	6.5	5.9	5.6	8.0	7.9	7.5	6.7	7.4	7.3	6.6		
MADISON ST(8.1C)						FC125M																
4361561	8.044	8.954	C	2017	0012	CRACKING	6.0*	5.5*	5.5*	5.5*	5.5*			10.0	10.0	10.0	10.0	10.0	8.9	9.3	7.5	
ANDERSON COLUMBIA CO., INC(2020)						SPRIDE	6.8	5.4*	6.6	6.3	6.5			7.9	7.8	7.8	7.9	7.9	7.8	7.4		
28010000	6.923	8.044	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.5	8.5	8.5		
200 301			2	4.8		10100	RIDE	8.8	8.9	8.9	7.4	7.2	7.1	7.7	7.5	7.0	7.2	7.2	6.9	6.8		
BRADFORD SQ(7.6L)						FC125M																
4342981	6.923	8.044	C	2017	0012	CRACKING	8.5	8.5	8.5	7.0	7.0			10.0	10.0	10.0	10.0	10.0	8.9	8.8	7.0	
ANDERSON COLUMBIA CO., INC(2020)						SPRIDE	6.8	6.6	7.1	7.2	7.2			8.2	8.1	7.8	7.6	7.8	7.8	7.8		
28010000	6.038	6.923	L	1	7	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.5	7.0		
200 301			2	4.8		10100	RIDE	8.8	8.9	8.9	8.4	8.4	8.4	8.6	8.6	8.4	8.4	8.4	8.3	8.3		
SHOPPING ENT(6.1L)						FC125M																
4472041	6.038	6.921	L	2024	0012	CRACKING	7.0	7.0	7.0	7.0	7.0			5.5*	3.5*	1.0*	1.0*	1.0*	1.0*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2026)						SPRIDE	8.3	8.0	8.3	8.3	8.5			8.3	8.4	8.3	8.2	8.2	8.3	8.6	8.2	
28010000	0.000	5.291	L	1	7	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	7.0		
200 301			2	20.8		27960	RIDE	8.8	8.9	8.9	8.4	8.4	8.4	8.6	8.6	8.4	8.4	8.4	8.3	8.3		
SW 85TH ST(0.2L)						FC5HP																
4472041	0.004	5.271	L	2024	0012	CRACKING	7.0	7.0	7.0	7.0	7.0			6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.2*	10.0	9.0
ANDERSON COLUMBIA CO., INC(2026)						SPRIDE	8.3	8.0	8.3	8.3	8.5			8.4	8.4	8.3	8.3	8.3	8.3	9.1	8.9	
28010001	0.000	0.447	R	1	1	45	CRACKING															
200 301			2	4.8		10100	RIDE															
US-301 S(0.0R)						DGFC																
(2021)						CRACKING RIDE									10.0	10.0	10.0	10.0	9.0	9.1	7.5	
																					7.4	7.0
28010001	0.000	0.447	L	1	1	45	CRACKING															
200 301			2	4.8		10100	RIDE															
US-301 N ALT(0.0L)						FC125M																
(2021)						CRACKING RIDE									10.0	10.0	10.0	10.0	9.1	8.8	7.0	
																					6.9	6.5

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = BRADFORD -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT	(MP)	(SIDE)					*****															
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR	(AGE_ONE	YEAR)																			(PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F																	
28010002	0.000	0.281	R	1	1	45	CRACKING															
200 301				2	4.8	5500	RIDE															
NE 187 ST(0.0C)							FC125M															
							CRACKING								10.0	10.0	10.0	10.0	10.0	9.6	8.0	
							RIDE													7.2	6.8	
							(2021)															
28010002	0.000	0.281	L	1	1	45	CRACKING															
200 301				2	4.8	5500	RIDE															
NE 187 ST(0.0C)							FC125M															
							CRACKING								10.0	10.0	10.0	10.0	9.6	9.5	8.0	
							RIDE													7.3	6.9	
							(2021)															
28020000	0.000	10.095	C	1	1	60	CRACKING	10.0	10.0	9.5	9.5	7.0	7.0	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0
100				2	9.6	7100	RIDE	8.7	8.7	8.5	7.9	7.9	7.9	7.9	7.7	7.6	7.3	8.2	8.2	8.1		
SE 3 AVE(0.2L)							FC125M															
2079566	4.035	10.168	C	2010		0012	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.0	7.0	7.0	6.0*	4.9*	4.1*	1.0*	
V. E. WHITEHURST & SONS,				I(2011)			RIDE	8.0	7.8	7.7	7.6	7.6	7.5	7.5	7.6	7.4	7.4	7.3	7.4	7.2	6.8	
4472042	0.000	10.100	C	2029		0012																
28020000	10.095	11.570	C	1	1	45	CRACKING	10.0	10.0	9.5	9.5	10.0		10.0	10.0	9.5	9.5	9.5	8.0	8.0		
100				2	7.8	8100	RIDE	8.7	8.7	8.5	7.9	7.9		8.2	8.0	8.1	7.8	7.9	7.8	7.7		
CR 100A(10.2R)							FC125M															
4323141	10.240	11.133	C	2017		0012	CRACKING	8.0	8.0	8.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.3	7.5	
V. E. WHITEHURST & SONS,				I(2019)			SPRIDE	7.7	7.6	7.7	7.6	7.7	8.1	7.9	8.0	7.3	6.9	7.9	7.9	7.7	7.3	
28020000	11.570	12.829	C	1	1	45	CRACKING	9.5	9.5	9.5	9.5	9.5		10.0	10.0	9.5	7.0	7.0	7.0	7.0		
100				2	16.7	8900	RIDE	8.2	8.3	8.2	7.7	7.7		7.5	7.8	7.3	7.0	7.0	6.8	6.7		
SR 200(11.6C)							FC125M															
4361791	11.622	12.496	C	2019		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	5.5*	5.5*		10.0	10.0	10.0	9.6	10.0	8.5	
PREFERRED MATERIALS, INC.				(2022)			SPRIDE	6.6	6.5	6.6	6.4	6.3	6.9	6.5		8.0	8.1	8.2	8.1	8.1	7.7	
28020000	12.829	13.680	C	1	1	45	CRACKING	6.0*	6.0*	6.0*	4.5*	4.5*		10.0	10.0	10.0	9.5	9.5	8.0	7.0		
100				2	19.2	6257	RIDE	8.2	8.3	8.0	7.5	7.5		8.3	8.3	8.3	8.2	8.1	8.0	8.0		
CR 100 A(13.5L)							FC125M															
4361791	12.858	13.404	C	2019		0012	CRACKING	6.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	
PREFERRED MATERIALS, INC.				(2021)			SPRIDE	7.9	7.8	7.7	7.6			8.1	7.9	7.9	7.7	7.8	7.7	7.7	7.3	
28020000	13.680	22.169	C	1	1	60	CRACKING	6.0*	6.0*	6.0*	4.5*	4.5*		10.0	10.0	10.0	9.5	9.5	8.0	7.0		
100				2	19.2	6257	RIDE	8.2	8.3	8.0	7.5	7.5		8.3	8.3	8.3	8.2	8.1	8.0	8.0		
CROSBY LAKE CEMETERY(13.9L)							FC125M															
4361791	16.174	20.162	C	2019		0012	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	9.5	9.6	8.0	
PREFERRED MATERIALS, INC.				(2021)			SPRIDE	7.9	7.8	7.7	7.6	7.7	7.5	6.9	8.7	8.7	8.7	8.7	8.7	8.7	8.3	
28030000	0.000	0.691	C	1	1	30	CRACKING	8.0	8.0	8.0	8.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
16				2	3.6	9900	RIDE	6.7	7.1	6.9	6.5	6.2	5.8	5.9	8.1	7.6	7.9	7.7	7.5	7.7		
SR 200(0.0C)							FC125M															
2080022	0.000	3.701	C	2007		0012	CRACKING	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.0	7.0	7.0	6.0*	4.4*	3.5*	0.0*	
PREFERRED MATERIALS, INC.				(2008)			RIDE	7.5	7.5	7.4	7.6	7.6	8.0	7.8	7.2	7.7	7.5	7.6	7.6	7.7	7.3	
2080206	0.000	3.701	C	2029		0012																
28030000	0.691	3.701	C	1	1	60	CRACKING	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
16				2	10.4	6900	RIDE	8.2	8.5	8.4	7.8	7.7	7.6	6.9	8.7	8.5	8.3	8.5	8.4	8.2		
FAXON LN(1.1L)							FC125M															
2080022	0.000	3.701	C	2007		0012	CRACKING	10.0	9.5	9.5	9.5	9.5	8.5	8.5	8.0	7.0	7.0	7.0	6.4*	6.3*	3.0*	
PREFERRED MATERIALS, INC.				(2008)			RIDE	8.2	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.0	8.0	7.9	7.9	7.8	7.4	
2080206	0.000	3.701	C	2029		0012																
28030001	0.000	3.860	C	1	1	55	CRACKING	1.5*	1.5*	1.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0		
16				2	3.6	3900	RIDE	8.2	8.0	7.7	8.3	8.2	8.3	7.4	8.3	8.2	8.0	8.1	8.1	7.9		
ENT TO FSP(0.3R)							FC125															
2080202	0.000	9.184	C	2002		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	3.5*	3.5*	3.5*	3.3*	3.1*	0.0*	
ANDERSON COLUMBIA CO., INC(2004)							SPRIDE	7.8	7.8	7.8	7.7	7.7	7.6	7.7	7.3	7.2	7.1	6.9	7.1	7.1	6.7	
2080205	0.000	9.163	C	2025		0012																
28030001	3.860	7.250	C	1	1	60	CRACKING	1.5*	1.5*	1.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0		
16				2	3.6	5100	RIDE	8.2	8.0	7.7	8.3	8.2	8.3	7.4	8.3	8.2	8.0	8.1	8.1	7.9		
NW 216TH ST(4.2L)							FC125															
2080202	0.000	9.184	C	2002		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	4.3*	
ANDERSON COLUMBIA CO., INC(2004)							SPRIDE	7.8	7.8	7.8	7.7	7.7	7.6	7.7	7.9	7.9	7.8	7.7	7.8	7.7	7.3	
2080205	0.000	9.163	C	2025		0012																

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 ** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = BRADFORD -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	#T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)								=====														
ITMSEG-P W_BMP W_EMP RW FY-P WKMX-P																						
CONTRACTOR (AGE_ONE YEAR) ASTYPE																						
ITMSEG-F W_BMP W_EMP RW FY-F WKMX-F																						
28030001		7.250	7.790	C	1	1 40	CRACKING	1.5*	1.5*	1.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	
16				2	3.6	5100	RIDE	8.2	8.0	7.7	8.3	8.2	8.3	7.4	8.3	8.2	8.0	8.1	8.1	7.9		
NW 177TH ST(7.3R)								FC125M														
						(2020)	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	9.0	9.0	9.0	8.6	8.8	7.0	
							RIDE	7.8	7.8	7.8	7.7	7.7	7.6	7.6	7.5	7.5	7.5	7.4	7.4	7.4	7.0	
2080205		0.000	9.163	C	2025	0012																
28030001		7.790	9.184	C	1	1 40	CRACKING	7.0	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5		
16				2	3.6	5900	RIDE	7.7	7.6	7.4	8.1	8.0	7.8	7.2	8.0	7.8	7.7	7.9	7.8	7.7		
HARLEY CIR(7.9R)								FC125														
2080202		0.000	9.184	C	2002	0012	CRACKING	9.5	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	5.5*	5.5*	3.5*	2.8*	2.4*	0.0*	
ANDERSON COLUMBIA CO., INC(2004)								SPRIDE														
2080205		0.000	9.163	C	2025	0012																
28040000		0.000	5.708	C	1	1 60	CRACKING	7.0	6.5	6.5	6.5	6.5	6.5	6.5	3.5*	10.0	10.0	10.0	10.0	8.5		
18				2	8.0	900	RIDE	8.2	8.2	7.8	7.6	7.8	7.6	7.7	7.8	8.6	8.2	8.3	8.0	7.7		
SW 206 AVE(1.8L)								FC125														
2079732		0.000	5.509	C	2007	0221	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	6.9	6.2*	3.0*	
ANDERSON COLUMBIA CO., INC(2009)								SPRIDE														
2079703		0.000	5.708	C	2028	0012														6.6	6.4*	6.0*
28050000		0.000	0.379	C	1	1 25	CRACKING	9.5	9.5	9.5	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5		
230				2	2.2	3600	RIDE	5.9*	5.4*	7.2	6.4	6.5	6.5	7.0	6.6	6.4	6.4	6.3	6.3	6.2		
SR 200(0.0C)								FC125														
						(2024)	CRACKING	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	9.0	
							RIDE	5.0*	4.7*	4.4*	4.4*	4.5*	4.3*	4.4*					4.2*	4.2*	3.8*	
28050000		0.379	3.843	C	1	1 55	CRACKING	10.0	9.5	9.5	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5		
230				2	6.7	1750	RIDE	8.2	8.7	8.7	8.2	8.1	8.0	8.1	7.9	7.8	7.3	7.4	7.1	6.8		
REDGRAVE ST(0.4R)								FC125R														
4244821		0.694	3.843	C	2013	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	3.5*	
V. E. WHITEHURST & SONS, I(2014)								SPRIDE														
4244823		0.379	3.843	C	2027	0012																
28060000		0.000	0.657	C	1	1 55	CRACKING	9.5	8.0	8.0	7.0	8.0	8.0	6.5	4.5*	10.0	10.0	10.0	10.0	10.0		
231				2	5.9	4200	RIDE	8.0	8.3	8.2	7.7	7.6	7.3	7.7	7.5	8.2	7.8	8.1	7.8	7.4		
SW 114 ST(0.3L)								FC125														
2079783		0.000	0.671	C	2007	0012	CRACKING	10.0	9.0	9.0	9.0	9.0	8.5	7.5	7.0	6.0*	6.0*	5.5*	4.2*	3.7*	0.5*	
ANDERSON COLUMBIA CO., INC(2009)								SPRIDE														
2079702		0.000	0.657	C	2028	0012																
28090000		0.000	3.560	C	1	1 55	CRACKING	4.5*	3.5*	2.5*	2.5*	2.5*		10.0	10.0	10.0	10.0	10.0	8.5	8.5		
21				2	7.9	9900	RIDE	7.5	7.3	5.8*	6.2*	6.1*		8.4	8.3	8.4	8.3	8.2	8.1	8.1		
SE 16TH ST(0.8L)								FC125M														
						(2022)	CRACKING	8.5	7.0	7.0	7.0	7.0	6.0*	6.0*	5.5*	10.0	10.0	10.0	10.0	10.0	8.5	
							RIDE	8.1	8.0	7.9	7.8	7.8	7.7	7.7	7.7	8.3	8.3	8.3	8.3	8.2	7.8	
28125000		0.000	0.240	R	1	1 55	CRACKING															
200 301				2	29.2	21900	RIDE															
N END BR #280061(0.0C)								FC5M														
2080014		0.000	2.661	C	2016	0002	CRACKING								10.0	10.0	10.0	10.0	10.0	7.9	5.5*	
SUPERIOR CONSTRUCTION COMP(2021)								SPRIDE														
															8.8	8.7	8.6	8.6	8.2	8.1	7.9	
28125000		0.240	0.550	R	1	1 55	CRACKING															
223 A301				2	29.2	21900	RIDE															
SR 200(0.4R)								FC125M														
2080014		0.000	2.661	C	2016	0002	CRACKING								10.0	10.0	10.0	10.0	9.5	10.0	8.5	
SUPERIOR CONSTRUCTION COMP(2021)								SPRIDE														
															8.8	8.7	8.6	8.6	7.9	7.8	7.4	
28125000		0.550	6.640	R	1	1 70	CRACKING															
223 A301				2	29.2	19500	RIDE															
(2021)								CRACKING RIDE														
															10.0	10.0	10.0	10.0	9.0	9.0	7.0	
															8.8	8.7	8.6	8.6	8.7	8.7	8.5	
28125000		6.640	6.996	R	1	1 55	CRACKING															
200 301				2	29.2	19500	RIDE															
SR 200(6.8R)								FC125M														
						(2021)	CRACKING								10.0	10.0	10.0	10.0	9.1	10.0	8.5	
							RIDE								8.8	8.7	8.6	8.6	8.2	8.2	7.8	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = BRADFORD -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT	AT	(MP	SIDE)				SURFTYPE	=====														
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	-P																
CONTRACTOR	(AGE_ONE	YEAR)		ASTYPE				2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	-F															(PMRS)	
28125000	6.996	7.166	R	1	1	55	CRACKING															
200 301				2	29.2	19500	RIDE															
CR 233(7.2C)						FC5M																
				(2021)			CRACKING								10.0	10.0	10.0	10.0	9.0	8.8	6.5	
							RIDE								8.8	8.7	8.6	8.6	8.6	8.6	8.4	
28125000	6.996	7.166	L	1	1	55	CRACKING															
200 301				2	29.2	19500	RIDE															
CR-233(7.2L)						FC5M																
				(2021)			CRACKING								10.0	10.0	10.0	10.0	9.0	9.0	7.0	
							RIDE								8.9	8.7	8.6	8.6	8.8	8.9	8.7	
28125000	6.651	6.996	L	1	1	55	CRACKING															
200 301				2	29.2	19500	RIDE															
						FC125M																
				(2021)			CRACKING								10.0	10.0	10.0	10.0	9.1	9.5	8.0	
							RIDE								8.9	8.7	8.6	8.6	8.3	8.2	7.8	
28125000	0.531	6.651	L	1	1	70	CRACKING															
223 A301				2	29.2	19500	RIDE															
						FC5M																
				(2021)			CRACKING								10.0	10.0	10.0	10.0	9.0	8.8	6.5	
							RIDE								8.9	8.7	8.6	8.6	8.7	8.6	8.4	
28125000	0.230	0.531	L	1	1	55	CRACKING															
200 301				2	29.2	21900	RIDE															
						FC125M																
2080014	0.000	2.661	C	2016	0002	CRACKING																
SUPERIOR CONSTRUCTION COMP(2021)						SPRIDE									10.0	10.0	10.0	10.0	10.0	8.5	7.0	
															8.9	8.7	8.6	8.6	8.1	8.1	7.7	
28125000	0.000	0.230	L	1	1	55	CRACKING															
200 301				2	29.2	21900	RIDE															
N END BR #280061(0.0C)						FC5M																
2080014	0.000	2.661	C	2016	0002	CRACKING																
SUPERIOR CONSTRUCTION COMP(2021)						SPRIDE									10.0	10.0	10.0	10.0	9.0	8.3	6.0*	
															8.9	8.7	8.6	8.6	8.1	7.9	7.7	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).