

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = COLUMBIA -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR US	G_BMP	G_EMP	LN	#T	AADT	RATINGS	*****	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****															(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F																	
ITMSEG-P																						
ITMSEG-F																						
29001000	0.000	0.363	C	1	1	45	CRACKING															
100A 441				2	17.8		6800 RIDE															
SR 25( 0.0C)							FC125M															
4432821	0.026	0.354	C	2022			0012 CRACKING					3.0*	3.0*	3.0*	3.0*	3.0*	10.0	10.0	9.1	10.0	8.5	
ANDERSON COLUMBIA CO., INC(2023)							SPRIDE					6.3	6.2	6.8	7.3	6.4	8.0	7.1	7.0	6.6	6.2	
29002000	0.000	3.471	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0
10A				2	7.6		17200 RIDE	8.3	8.5	8.5	8.0	7.9	7.7	7.3	7.6	7.7	7.1	7.0	7.0	7.0	6.9	
DUVAL ST( 0.0C)							FC125M															
4305561	0.959	3.471	R	2016			0012 CRACKING	7.0	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.4	6.5	4.5*	
ANDERSON COLUMBIA CO., INC(2017)							SPRIDE	7.4	6.6	7.0	8.0	7.8	7.5	7.6	7.6	7.4	7.4	7.1	7.1	7.1	6.7	
29002000	0.000	3.471	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	7.0	7.0
10A				2	7.6		17200 RIDE	8.5	8.4	8.4	7.8	7.5	7.1	6.8	7.2	7.2	7.1	7.0	7.0	6.9		
DUVAL ST( 0.0C)							FC125M															
4305561	0.959	3.471	L	2016			0012 CRACKING	7.0	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	6.5	4.5*	
ANDERSON COLUMBIA CO., INC(2017)							SPRIDE	7.4	6.6	7.0	8.0	7.8	7.5	7.6	7.6	6.9	6.8	6.6	6.6	6.5	6.1	
29010000	0.000	4.490	C	1	1	60	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.0	7.0	6.0*	6.0*	6.0*		
10 90				2	5.8		7754 RIDE	9.0	8.9	8.8	8.5	8.6	8.3	8.4	8.6	8.4	8.4	8.3	8.2	8.1		
BELL LAKE CT( 0.5L)							FC125M															
4244931	0.687	4.493	C	2013			0012 CRACKING	4.0*	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5	4.0*	
ANDERSON COLUMBIA CO., INC(2015)							SPRIDE	8.1	8.5	8.4	8.5	8.4	8.3	8.4	8.4	8.2	8.4	8.4	8.3	8.2	7.8	
29010000	4.490	5.957	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.0	7.0	6.0*	6.0*	6.0*		
10 90				2	5.8		24000 RIDE	9.0	8.9	8.8	8.5	8.6	8.3	8.4	8.1	8.1	7.9	7.9	7.9	7.6		
SW EXECUTIVE DR( 4.8R)							FC125M															
				(2018)			CRACKING RIDE	6.0*	6.0*			10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.5	6.5	
								7.7	7.7			7.9	7.6	7.7	7.6	7.7	7.5	7.6	7.5	7.6	7.2	
29010000	5.957	6.900	R	1	1	45	CRACKING	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	8.0		
10 90				2	5.8		30000 RIDE	7.4	6.4*	8.6	8.1	8.3	8.0	8.1	8.1	8.1	7.9	7.9	7.9	7.8		
CR 252B( 6.2R)							FC125M															
4433131	5.908	6.775	R	2022			0012 CRACKING	7.0	7.0	5.5*		6.0*	3.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2024)							SPRIDE	7.8	7.8	7.7		7.5	7.8	8.5	8.5	8.4		8.1	8.1	8.1	7.7	
29010000	6.900	9.137	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5		
10 90				2	5.8		29000 RIDE	8.6	8.4	8.4	8.0	8.1	8.0	7.8	8.2	8.2	7.7	7.6	7.7	7.8		
REAL RD( 7.3C)							FC125M															
4433131	6.775	9.065	R	2022			0012 CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.0	7.0		10.0	10.0	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2024)							SPRIDE	7.7	7.8	7.6	7.7	7.5	7.6	7.6	7.6	7.5		8.7	8.6	8.6	8.2	
29010000	9.137	9.208	R	1	1	45	CRACKING	3.5*	3.5*	1.0*	1.0*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0	8.5	8.5		
10 90				2	5.8		19900 RIDE	7.6	7.4	7.2	6.4*	6.3*	5.8	8.1	7.7	7.3	7.3	7.1	7.3	7.2		
BAYA AVE( 9.2R)							FC125M															
4433131	9.065	9.208	R	2022			0012 CRACKING	8.5	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	10.0		10.0	10.0	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2024)							SPRIDE	7.8	7.7	7.7	7.6	7.6	7.7	7.5	7.5	8.2				7.6	7.2	
29010000	9.208	11.191	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5		
10 90				2	5.8		14600 RIDE	8.5	8.4	8.4	7.7	7.9	7.5	7.7	7.4	7.8	7.6	7.7	7.5	7.2		
MCFARLANE AVE R( 9.4R)							FC125M															
4412581	9.208	11.997	C	2020			0012 CRACKING	8.5	7.5	7.0	5.5*	5.5*	5.5*	5.5*	4.0*	10.0	10.0	10.0	9.6	10.0	8.5	
ANDERSON COLUMBIA CO., INC(2022)							SPRIDE	7.3	6.9	7.1	6.9	7.1	7.3	7.3	7.3	8.2	8.1	8.1	8.1	8.0	7.6	
29010000	11.191	12.000	C	1	1	45	CRACKING	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
10 90				4	5.8		10000 RIDE	7.7	7.4	7.5	6.8	6.9	6.5	8.2	8.1	8.3	8.2	8.2	7.7	7.7		
MONTROSE AVE NE(11.2C)							FC125M															
4412581	9.208	11.997	C	2020			0012 CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	10.0	10.0	10.0	9.4	10.0	8.5	
ANDERSON COLUMBIA CO., INC(2022)							SPRIDE	7.8	7.6	7.7	7.6	7.3	7.4	7.2	7.4	8.2	8.1	8.1	8.0	8.0	7.6	
29010000	12.000	12.589	R	1	1	45	CRACKING	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	6.5	6.5	4.5*	10.0	10.0		
10 90				2	11.9		7200 RIDE	8.5	8.2	8.7	8.0	8.0	8.1	7.7	8.1	8.0	7.9	7.9	7.8	7.9		
LLEWELLYN AVE SE(12.0R)							FC125M															
2083663	12.069	14.321	R	2011			0226 CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	4.5*	4.1*	4.5*	1.5*	
ANDERSON COLUMBIA CO., INC(2012)							SPRIDE	8.1	7.9	8.2	8.1	8.1	8.2	8.1	8.3	8.2	8.1	8.1	8.0	6.8	6.4	
2083665	12.008	14.663	C	2027			0012															

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = COLUMBIA -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	W_YEAR	FY-P	WKM-X-P	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)
29010000	12.589	14.664	R	1	1	55	CRACKING	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	6.5	6.5	4.5*	10.0	10.0	
10 90				2	11.9		10700 RIDE	8.5	8.2	8.7	8.0	8.0	8.1	7.7	8.1	8.0	7.9	7.9	7.8	7.9	
DIVISION OF FORESTRY(12.6R) FC5																					
2083663	12.069	14.321	R	2011		0226	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	4.5*	4.1*	4.5*	0.0*
ANDERSON	COLUMBIA CO., INC(2012)						SPRIDE	8.1	7.9	8.2	8.1	8.1	8.2	8.1	8.3	8.2	8.1	8.1	8.0	8.2	8.0
2083665	12.008	14.663	C	2027		0012															
29010000	14.664	20.891	C	1	1	60	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	
10 90				2	11.9		7500 RIDE	8.7	8.5	8.6	7.7	7.7	7.3	7.3	8.6	8.5	8.4	8.4	8.1	8.0	
BILLY CRAIG CT NE(14.7L) FC125M																					
2083662	14.920	17.791	C	2007		0012	CRACKING	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	5.5*	5.5*	5.5*	3.5*	3.5*	3.5*	0.0*
ANDERSON	COLUMBIA CO., INC(2008)						RIDE	8.1	7.8	7.8	7.9	7.7	7.6	7.9	7.8	7.8	7.8	7.6	7.5	7.6	7.2
2083664	14.663	20.891	C	2027		0012															
29010000	12.589	14.664	L	1	1	55	CRACKING	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	6.5	6.5	6.0*	10.0	10.0	
10 90				2	11.9		10700 RIDE	8.8	8.5	8.5	8.2	8.2	8.0	8.2	8.2	8.1	8.0	7.9	8.2	8.1	
NE CR-245(12.7L) FC5																					
2083663	12.069	14.321	L	2011		0226	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.6*	3.0*	0.0*
ANDERSON	COLUMBIA CO., INC(2012)						SPRIDE	8.3	8.1	8.3	8.3	8.2	8.3	8.3	8.3	8.3	8.1	8.1	8.1	8.2	8.0
2083665	12.008	14.663	C	2027		0012															
29010000	12.000	12.589	L	1	1	45	CRACKING	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	6.5	6.5	6.0*	10.0	10.0	
10 90				2	11.9		7200 RIDE	8.8	8.5	8.5	8.2	8.2	8.0	8.2	8.2	8.1	8.0	7.9	8.2	8.1	
CR 100(12.1L) FC125M																					
2083663	12.069	14.321	L	2011		0226	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.6*	2.8*	0.0*
ANDERSON	COLUMBIA CO., INC(2012)						SPRIDE	8.3	8.1	8.3	8.3	8.2	8.3	8.3	8.3	8.3	8.3	8.1	8.1	8.1	7.2
2083665	12.008	14.663	C	2027		0012															
29010000	9.208	11.191	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	
10 90				2	5.8		14600 RIDE	8.6	8.0	8.4	7.8	8.0	7.7	7.7	7.8	7.9	7.9	7.7	7.5	7.4	
DUVAL ST W( 9.3L) FC125M																					
4412581	9.208	11.997	C	2020		0012	CRACKING	8.5	7.5	7.0	5.5*	5.5*	5.5*	5.5*	4.0*	10.0	10.0	10.0	9.7	10.0	8.5
ANDERSON	COLUMBIA CO., INC(2022)						SPRIDE	7.3	6.9	7.1	6.9	7.1	7.3	7.3	7.5	8.2	8.1	7.9	8.0	7.8	7.4
29010000	9.137	9.208	L	1	1	45	CRACKING	6.5	6.5	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	9.0	8.5	8.5	8.5	
10 90				2	5.8		19900 RIDE	7.3	7.1	7.0	6.0*	6.0*	5.3*	8.1	7.8	7.8	7.7	7.9	7.9	7.7	
EDISON WAY( 9.2L) FC125M																					
4433131	9.065	9.208	L	2022		0012	CRACKING	8.5	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	10.0		10.0	10.0	10.0	9.0
ANDERSON	COLUMBIA CO., INC(2024)						SPRIDE	7.8	7.7	7.7	7.6	7.6	7.7	7.5	7.3	8.2				7.7	7.3
29010000	6.884	9.137	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.5	8.5	
10 90				3	5.8		29000 RIDE	8.7	8.5	8.5	7.9	7.9	7.8	7.7	8.0	8.0	7.8	7.5	7.6	7.5	
BROOKSIDE AVE L( 7.0L) FC125M																					
4433131	6.775	9.065	L	2022		0012	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.0	7.0		10.0	10.0	10.0	9.0
ANDERSON	COLUMBIA CO., INC(2024)						SPRIDE	7.7	7.8	7.6	7.7	7.5	7.6	7.6	7.8	7.9		8.6	8.4	8.4	8.0
29010000	5.957	6.884	L	1	1	45	CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	
10 90				2	5.8		30000 RIDE	8.0	7.7	8.7	8.2	8.4	7.9	8.0	8.3	8.2	7.7	7.7	7.8	7.6	
NW HARVEY WAY( 6.2L) FC125M																					
4433131	5.908	6.775	L	2022		0012	CRACKING	7.0	7.0	5.5*		6.0*	3.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	9.0
ANDERSON	COLUMBIA CO., INC(2024)						SPRIDE	7.8	7.8	7.7		7.5	7.8	8.5	8.4	8.4		8.5	8.2	8.2	7.8
29010000	4.490	5.957	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5	7.0	6.0*	6.0*	6.0*	
10 90				2	5.8		24000 RIDE	9.0	8.9	8.8	8.5	8.6	8.3	8.4	8.2	8.1	7.9	7.8	7.9	7.6	
BROWN RD( 4.8L) FC125M																					
							CRACKING	6.0*	6.0*			10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	6.0*
					(2018)		RIDE	7.7	7.7			7.9	7.9	7.8	7.7	7.4	7.3	7.3	7.2	7.1	6.7
29020000	0.000	4.326	C	1	1	60	CRACKING	10.0	10.0	8.5	7.0	7.0	6.0*	5.5*	4.0*	4.0*	10.0	10.0	10.0	10.0	
47				2	7.3		2828 RIDE	8.7	8.8	8.7	7.9	8.0	7.8	7.4	7.1	7.0	8.6	8.6	8.5	8.5	
C-138( 0.3R) FC125																					
2084171	0.000	4.312	C	2009		0012	CRACKING	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	7.5	7.5	7.5	6.7	6.5	3.5*
ANDERSON	COLUMBIA CO., INC(2010)						SPRIDE	8.2	8.3	8.1	8.1	8.0	8.1	7.9	8.0	7.9	7.9	7.8	7.8	7.9	7.5
29020000	4.326	4.963	C	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.5	8.5	8.5	
47				2	6.1		5100 RIDE	8.3	8.5	8.6	7.9	8.3	8.1	8.1	8.3	7.9	8.0	7.9	7.8	7.7	
SW WELL ST( 4.4C) FC125M																					
							CRACKING	7.0	7.0	7.0	6.5	6.0*	5.5*	10.0	10.0	10.0	10.0	9.0	9.1	8.4	6.5
4454021	4.325	18.676	C	2023		0012	RIDE	7.7	7.6	7.6	7.6	7.5	7.6	8.3	8.2	8.1	7.9	7.7	7.7	7.4	7.0

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @\* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = COLUMBIA -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	=====	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013		
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)	
ITMSEG-P																						
ITMSEG-F																						
29020000	4.963	18.000	C	1	1	60	CRACKING	7.5	5.5*	5.0*	5.0*	10.0	10.0	9.5	9.5	9.5	9.5	8.5	8.5	8.5		
47			2	6.1		6300	RIDE	7.8	7.6	7.5	6.0*	8.3	8.1	8.1	8.1	7.9	8.0	7.9	7.8	7.7		
DEESE LN( 5.1L)						FC125M																
				(2025)			CRACKING	7.0	7.0	7.0	6.5	6.0*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	9.0	
							RIDE	7.7	7.6	7.6	7.6	7.5	7.6	7.4	7.5	7.4	7.3	7.3	8.4	8.3	7.9	
29020000	18.000	18.989	R	1	1	45	CRACKING	10.0	8.5	7.5	7.5	10.0	10.0	9.5	10.0	10.0	10.0	10.0	9.0	9.0		
47			2	6.1		14000	RIDE	8.4	8.3	8.1	7.4	8.3	8.1	8.1	8.0	7.8	7.8	7.9	7.7	7.5		
ARUID DR SW(18.2R)						FC125M																
				(2025)			CRACKING	9.0	9.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	5.5*	10.0	10.0	9.0	
							RIDE	7.7	7.5	7.1	7.0	7.3	7.3	7.3	7.4	7.2	7.4	7.3	8.0	8.0	7.6	
29020000	18.989	22.554	R	1	1	50	CRACKING	7.5	7.0	6.0*	6.0*	6.0*			10.0	10.0	10.0	10.0	10.0	10.0		
47			2	6.1		13000	RIDE	8.5	8.4	8.3	7.7	7.4			8.1	8.2	8.0	8.0	7.9	7.9		
CANNON CREEK PARK(19.1R)						FC125																
2083631	18.821	22.554	C	2004		0213	CRACKING	10.0	10.0	9.0	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	5.6*	5.0*	1.5*	
ANDERSON COLUMBIA CO., INC(2008)						SPRIDE		7.8	7.8	7.7	7.5	7.6	7.6	7.5	7.5	7.5	7.5	7.3	7.4	7.3	6.9	
4454022	18.676	22.550	C	2029		0012																
29020000	18.944	22.554	L	1	1	50	CRACKING	7.5	7.0	6.0*	6.0*	6.0*			10.0	10.0	10.0	10.0	10.0	10.0		
47			2	6.1		13000	RIDE	8.5	8.4	8.3	7.7	7.4			8.3	8.2	8.1	8.1	8.0	7.9		
SW RING CT(19.1L)						FC125																
2083631	18.821	22.554	C	2004		0213	CRACKING	10.0	9.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.0*	6.0*	5.1*	4.2*	1.0*	
ANDERSON COLUMBIA CO., INC(2008)						SPRIDE		7.9	7.8	7.5	7.6	7.4	7.4	7.3	7.4	7.3	7.4	7.3	7.3	7.3	6.9	
4454022	18.676	22.550	C	2029		0012																
29020000	18.000	18.944	L	1	1	55	CRACKING	10.0	8.5	7.5	7.5	10.0	10.0	9.5	10.0	10.0	10.0	10.0	10.0	10.0		
47			2	6.1		14000	RIDE	8.4	8.3	8.1	7.4	8.3	8.1	8.1	7.6	7.5	7.3	7.4	7.2	7.1		
RIDGE RD(18.3L)						FC125M																
				(2025)			CRACKING	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	9.0	
							RIDE	7.1	7.2	6.7	6.6	7.7	7.6	7.6	7.4	7.5	7.6	7.3	8.1	8.2	7.8	
29030000	0.000	9.664	C	1	1	60	CRACKING	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0		
25 41			2	9.6		5400	RIDE	8.4	8.2	8.1		8.1	7.9	8.0	7.9	7.9	7.9	7.9	7.8	7.7		
RIVERVIEW CIR SE( 0.2R)						FC125M																
				(2020)			CRACKING	6.5	6.5	4.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	9.0	7.0	
							RIDE	7.6	7.2	7.7	7.6	7.4			8.7	8.7	8.7	8.6	8.6	8.5	8.1	
29030000	9.664	10.377	R	1	1	45	CRACKING	10.0	10.0	8.5		8.5	9.0	9.0	10.0	7.0	6.5	6.5	6.5	10.0		
25 41			2	9.6		5400	RIDE	8.5	8.4	8.4		7.6	7.4	7.4	7.2	7.3	7.0	6.9	7.0	8.1		
SE SR 238(10.4R)						FC125M																
2083523	10.344	10.607	R	2022		0012	CRACKING	7.5	7.5	7.5	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*		10.0	9.0	
				(2026)			RIDE	8.0	7.7	7.9	7.9	7.9	7.7	7.7	7.8	7.7	7.7	7.7		8.1	7.7	
29030000	10.630	20.509	C	1	7	60	CRACKING	7.0	6.0*	6.0*	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	9.0		
25 41			2	7.5		6400	RIDE	9.0	8.9	8.8	8.1	7.7	7.8	7.8	8.5	8.5	8.4	8.4	8.1	8.1		
SW TABERNACLE GLN(10.9L)						FC125M																
2083523	10.607	17.100	C	2022		0012	CRACKING	7.5	7.5	7.5	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*		10.0	9.0	
				(2026)			RIDE	8.0	7.7	7.9	7.9	7.9	7.7	7.7	7.8	7.7	7.7	7.7		9.0	8.6	
29030000	20.509	20.837	R	1	7	45	CRACKING	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0		
25 41			1	7.5		10000	RIDE	7.8	8.3	8.3	7.9	7.8	7.9	7.3	8.5	8.5	8.3	8.2	8.0	7.9		
FINDERS PL SE(20.7R)						FC125M																
2083523	20.447	20.696	R	2022		0012	CRACKING	8.5	8.5	8.5	7.5	7.5	6.0*	6.0*	5.5*	5.5*	5.5*	5.5*		10.0	9.0	
				(2026)			RIDE	8.0	7.7	7.6	7.6	7.7	7.7	7.6	7.6	7.7	7.4	7.6		8.4	8.0	
29030000	20.837	22.458	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	6.0*	6.0*	6.0*		
25 41			2	5.5		10100	RIDE	8.8	8.7	8.8	8.2	8.3	8.0	8.1	8.0	8.0	7.9	7.9	7.8	7.7		
ALFRED MAR SE(20.9R)						FC125M																
4286931	20.837	22.478	C	2014		0012	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	6.5	4.3*	2.0*
ANDERSON COLUMBIA CO., INC(2015)						SPRIDE		7.7	8.7	8.3	8.2	8.1	8.1	8.0	8.0	8.1	8.0	8.0	8.0	7.9	7.5	

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = COLUMBIA -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	*****	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-X-P	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	(AGE_ONE YEAR)	W_EMP	RW	FY-F	WKM-X-F																(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F																
29030000	22.458	23.949	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	7.5	
25 41				2	7.5	19600	RIDE	8.2	8.2	8.1	7.7	7.7	7.7	7.3	7.5	7.3	7.4	7.7	7.3	7.3	
SHOPPING ENT(22.7R)																					
4305611	22.458	23.949	C	2015		0012	CRACKING	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.8	6.5
ANDERSON	COLUMBIA CO., INC	(2017)					SPRIDE	7.4	7.2	7.4	7.9	7.8	7.7	7.7	7.6	7.6	7.4	7.5	7.5	7.4	7.0
-----																					
29030000	22.458	23.949	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.5	7.5	7.5	
25 41				2	7.5	19600	RIDE	7.9	8.0	8.0	7.7	7.7	7.5	7.6	7.6	7.7	7.6	7.5	7.5	7.6	7.3
SR 47 NB(22.5L)																					
4305611	22.458	23.949	C	2015		0012	CRACKING	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.6	6.7	4.5*
ANDERSON	COLUMBIA CO., INC	(2017)					SPRIDE	7.4	7.3	7.4	8.0	8.0	7.8	7.9	7.8	7.7	7.6	7.6	7.5	7.5	7.1
-----																					
29030000	20.835	22.458	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	6.5	4.5*	4.5*	4.5*	
25 41				2	5.5	10100	RIDE	8.8	8.8	8.7	8.0	8.3	8.0	7.9	8.0	7.8	7.5	7.7	7.3	7.1	
UNSGIGNED(20.9L)																					
4286931	20.837	22.478	C	2014		0012	CRACKING	3.5*	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0	7.0	6.0*	5.4*	4.5*	2.0*
ANDERSON	COLUMBIA CO., INC	(2015)					SPRIDE	7.2	8.6	8.3	7.9	8.1	8.2	8.2	8.1	8.1	8.2	8.0	8.1	7.9	7.5
-----																					
29030000	20.509	20.835	L	1	7	45	CRACKING	8.5	8.5	8.5	10.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	
25 41				1	7.5	10000	RIDE	7.4	7.1	7.3	8.0	7.0	6.6	6.7	8.5	8.3	8.1	7.9	7.7	7.7	
2083523 20.447 20.696 L 2022 0012 CRACKING 8.5 8.5 7.5 7.5 7.0 5.5* 5.5* 5.5* 5.5* 5.5* 4.0* 10.0 9.0																					
(2026) RIDE 7.7 7.6 7.5 7.6 7.7 7.4 7.6 7.4 7.3 7.4 7.2 8.3 7.9																					
-----																					
29030000	10.377	10.630	L	1	7	45	CRACKING	7.0	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
25 41				1	7.5	6900	RIDE	9.0	8.9	8.8		7.9	7.6	7.9	8.5	8.5	8.4	8.4	8.1	8.1	
2083523 10.344 10.607 L 2022 0012 CRACKING 7.5 7.5 7.5 7.0 7.0 5.5* 5.5* 5.5* 5.5* 5.5* 5.5* 10.0 9.0																					
(2026) RIDE 8.0 7.7 7.9 7.9 7.9 7.7 7.7 7.8 7.7 7.7 7.7 8.1 7.7																					
-----																					
29030000	9.664	10.377	L	1	1	45	CRACKING	10.0	10.0	10.0		8.5	8.5	8.5	9.5	8.5	8.5	7.5	7.5	10.0	
25 41				2	9.6	5400	RIDE	8.1	7.6	8.3		7.5	7.2	7.4	7.6	7.2	7.1	7.1	7.0	8.0	
HOWELL ST SW( 9.9L)																					
							CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.5	7.5	6.0*	5.5*	3.5*
							RIDE	8.1	8.0	7.8	7.8	7.7	7.6	7.7	7.6	7.5	7.4	7.2	7.1	7.0	6.6
(2013)																					
-----																					
29030002	0.000	0.924	C	1	1		CRACKING														4.9*
25F				2	2.0	500	RIDE														7.5
CRACKING RIDE																					
-----																					
29040000	0.000	0.720	R	1	1	45	CRACKING	7.0	5.5*	3.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
25 41				2	13.8	11200	RIDE	7.3	7.1	7.0		7.8	7.9	7.5	7.7	7.9	7.8	7.8	7.8	7.7	
DUVAL ST( 0.0C)																					
4361781	0.031	1.261	R	2021		0012	CRACKING	8.5	8.5	7.5	5.5*	5.5*	4.0*	4.0*	4.0*	4.0*	10.0	10.0	10.0	10.0	8.5
ANDERSON	COLUMBIA CO., INC	(2023)					SPRIDE	7.6	7.7	7.5	7.5	7.5	7.4	7.6	7.6	7.3	8.1	7.2	7.3	7.2	6.8
-----																					
29040000	0.720	1.934	R	1	1	45	CRACKING	8.5	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	
25 41				1	13.8	10300	RIDE	7.8	7.8	7.7		8.5	8.2	8.1	8.3	8.3	8.2	8.2	8.0	7.9	
LONG ST NW( 0.7C)																					
							CRACKING	7.5	7.5	7.0	5.5*	5.5*	4.0*	4.0*	4.0*	4.0*	10.0	10.0	10.0	10.0	8.5
							RIDE	7.8	7.3	7.8	7.7	7.6	7.6	7.9	7.8	7.8	8.1	8.1	8.0	8.1	7.7
(2023)																					
-----																					
29040000	1.934	4.149	C	1	1	60	CRACKING	7.5	7.0	5.5*		10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	
25 41				2	13.8	8700	RIDE	8.5	8.3	8.2		8.4	8.3	8.4	8.5	8.4	8.4	8.3	8.3	8.1	
MOORE RD NW( 3.0C)																					
							CRACKING	7.0	7.0	7.0	5.5*	6.5	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	8.5
							RIDE	8.0	8.0	7.9	7.8	7.9	7.8	7.9	7.9	7.8	8.6	8.4	8.4	8.3	7.9
(2023)																					
-----																					
29040000	4.149	4.788	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	10.0	
25 41				2	13.8	8700	RIDE	8.9	8.8	8.9	8.4	8.5	8.2	8.1	8.1	8.0	7.9	7.9	7.9	8.2	
CR 25A NW( 4.3R)																					
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5	6.5	5.5*	3.7*	1.0*
							RIDE	8.3	8.2	8.0	7.9	7.9	7.7	7.7	7.6	7.7	7.5	7.4	7.4	7.3	6.9
(2013)																					

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

															DISTRICT = 2		COUNTY = COLUMBIA																
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR		2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE													
SR US	G_BMP	G_EMP	LN	#T	ADT	RATINGS		2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013													
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031												
ITMSEG-P	(AGE_ONE YEAR)																				(PMRS)												
CONTRACTOR																																	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F																												
29040000	4.788	11.480	C	1	1 60	CRACKING	7.5	7.5	7.0	5.0*	3.0*	3.0*	3.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
25 41				2	13.8	5800 RIDE	8.4	8.1	8.0	7.2	7.0	6.6	6.4*	8.6	8.5	8.4	8.5	8.4	8.3														
FLAMINGO GLEN NW( 5.0L) FC95M																																	
2083893	4.788	11.480	C	2007	0012	CRACKING	8.5	8.5	8.5	8.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.1*	4.3*	1.0*													
ANDERSON	COLUMBIA CO., INC(2008)					RIDE	8.3	8.2	8.1	8.1	8.1	8.0	8.0	8.0	7.9	7.8	7.8	7.7	7.3														
2083895	4.837	11.480	C	2027	0012																												
-----																																	
29040000	4.149	4.788	L	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0													
25 41				2	13.8	8700 RIDE	8.5	8.3	8.3	7.6	7.8	7.7	7.7	7.8	7.8	7.8	7.7	7.8	8.1														
FC125M																																	
						CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.0	7.0	7.0	6.5	5.5*	3.5*	1.0*													
						RIDE	8.2	8.1	7.9	7.8	7.8	7.6	7.8	7.6	7.6	7.4	7.3	7.3	7.2	6.8													
(2013)																																	
-----																																	
29040000	0.000	1.934	L	1	1 45	CRACKING	7.0	7.0	3.0*		10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5														
25 41				2	13.8	11200 RIDE	6.2*	7.0	7.0		8.3	7.8	8.1	8.0	8.4	7.7	8.1	7.6	7.9														
DUVAL ST( 0.0C) FC125M																																	
4361781	0.031	1.261	L	2021	0012	CRACKING	8.5	8.5	8.5	7.5	6.0*	6.0*	6.0*	5.5*	5.5*	10.0	10.0	10.0	10.0	8.5													
ANDERSON	COLUMBIA CO., INC(2023)					SPRIDE	7.6	7.8	7.6	7.9	7.7	7.7	7.8	7.8	7.7	8.0	7.7	7.6	7.7	7.3													
-----																																	
29050000	0.000	7.219	C	1	7 60	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0													
20 27				2	7.3	6800 RIDE	8.5	8.8	8.8	8.4	8.6	8.4	8.4	8.5	8.5	8.5	8.4	8.4	8.4														
RIVER RISE STATE PK( 0.3R) FC125M																																	
2084183	3.954	11.839	C	2022	0012	CRACKING	8.5	8.5	8.5	8.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	3.5*		10.0	9.0													
						RIDE	8.4	8.3	8.0	8.0	8.1	8.1	8.0	8.1	8.0	8.0	8.0		8.3	7.9													
(2026)																																	
-----																																	
29050000	7.219	7.968	C	1	7 30	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5													
20 27				2	7.3	6200 RIDE	7.6	8.5	8.4	7.9	8.1	8.0	8.0	8.1	7.7	7.8	7.8	7.7	7.8														
CR-18( 7.3R) FC125M																																	
2084183	3.954	11.839	C	2022	0012	CRACKING	8.5	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*		10.0	9.0													
						RIDE	7.8	7.7	7.4	7.6	7.6	7.5	7.4	7.5	7.4	7.3	7.4		8.2	7.8													
(2026)																																	
-----																																	
29050000	7.968	12.590	C	1	7 60	CRACKING	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5													
20 27				2	7.3	6200 RIDE	8.6	8.8	8.8	8.5	8.6	8.4	8.5	8.6	8.5	8.6	8.5	8.4	8.4														
CENTERVILLE AVE SW( 8.5R) FC125M																																	
2084183	3.954	11.839	C	2022	0012	CRACKING	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*		10.0	9.0													
						RIDE	8.5	8.3	8.0	8.0	8.0	8.0	7.9	7.9	8.0	7.9	7.8		8.2	7.8													
(2026)																																	
-----																																	
29060000	0.000	7.350	C	1	1 60	CRACKING	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.5	8.5	7.0														
100				2	13.0	4600 RIDE	7.9	7.4	8.9	8.4	8.7	8.6	8.6	8.7	8.7	8.7	8.6	8.4	8.4														
CR 242 SE( 1.2C) FC125M																																	
4342971	0.000	7.350	C	2019	0012	CRACKING	7.0	5.5*	5.5*	3.5*	3.5*	3.0*		10.0	10.0	10.0	10.0	9.7	10.0	8.5													
PREferred	MATERIALS, INC. (2021)					SPRIDE	8.4	8.2	8.2	8.1	8.1	8.0		8.8	8.9	8.9	8.9	8.8	8.8	8.8	8.4												
-----																																	
29060000	7.350	9.989	C	1	1 60	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.5														
100				2	13.0	4600 RIDE	8.7	8.7	8.7	7.9	8.0	8.1	8.0	8.1	8.2	8.2	8.1	8.0	8.0														
ACADEMIC AVE SE( 7.5R) FC125A																																	
4286941	7.354	9.915	C	2015	0012	CRACKING	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.0	6.0*													
ANDERSON	COLUMBIA COMPANY (2017)					SPRIDE	8.0	7.9	7.8	8.5	8.5	8.3	8.4	8.4	8.3	8.4	8.4	8.3	8.3	7.9													
-----																																	
29070000	0.061	0.569	R	1	1 45	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	5.5*	5.5*	10.0	10.0	10.0	10.0														
25A 441				1	7.6	5200 RIDE	7.9	7.9	7.7	7.4	7.2	7.3	7.2	7.0	7.2	8.4	8.3	7.8	7.9														
SR 25( 0.1C) FC125																																	
2084024	0.248	0.544	R	2009	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	7.0	6.2*	7.0	4.0*													
						RIDE	7.7	7.3	7.7	7.7	7.6	7.5	7.5	7.3	7.3	7.3	7.2	7.2	7.1	6.7													
(2010)																																	
-----																																	
29070000	0.569	1.045	C	1	1 45	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	6.0*	10.0	10.0	10.0	10.0														
25A 441				2	7.6	5200 RIDE	7.9	7.9	7.7	7.4	7.2	7.3	7.2	8.1	8.1	8.4	8.3	7.8	7.9														
CORONADO ST SW( 0.6L) FC125																																	
2084024	0.544	1.086	C	2009	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	7.0	6.2*	7.0	4.0*													
						RIDE	7.7	7.3	7.7	7.7	7.6	7.5	7.5	7.3	7.3	7.3	7.2	7.2	7.4	7.0													
(2010)																																	
-----																																	
29070000	1.045	2.652	R	1	1 45	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	10.0	10.0	10.0	10.0														
25A 441				1	7.6	6300 RIDE	7.9	7.9	7.7	7.4	7.2	7.3	7.2	7.2	7.2	8.4	8.3	7.8	7.9														
BUTLER BLVD SE( 1.3R) FC125																																	
2084024	1.086	2.653	R	2009	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	7.0	6.2*	7.5	4.5*													
						RIDE	7.7	7.3	7.7	7.7	7.6	7.5	7.5	7.3	7.3	7.3	7.2	7.2	7.0	6.6													
(2010)																																	

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @# INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = COLUMBIA -----																							
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE			
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031		
INTERSECT AT (MP SIDE)		W_BMP		W_EMP		RW		FY-P		WKM-F		ASTYPE											
		(AGE_ONE YEAR)		YEAR		RW		FY-F		WKM-F													
29070000	2.652	3.031	C	1	4	30	CRACKING	1.4*	3.2*	3.0*	2.3*	0.9*	0.5*	1.0*	0.0*	2.4*	2.0*	2.2*	1.2*	0.8*			
25A 441				2	7.6	4800	RIDE	7.2	6.9	7.1	5.8	5.7	5.2*	5.6	5.6	5.9	6.3	6.1	5.7	6.0			
SE CAMP ST( 2.7R)																							
2083861	2.524	3.005	C	1992		0217	CRACKING	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.1*	0.6*	0.0*	0.0*		
ANDERSON	COLUMBIA	CO., INC	(1997)				RIDE	6.1	5.6	6.5	6.4	6.4	6.6	6.2	6.0	5.9	6.0	5.9	5.9	6.0	5.9		
29070000	4.000	6.513	R	1	7	45	CRACKING	9.0	9.0	9.0	9.0	9.0	7.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		
47 441				2	7.6	6300	RIDE	6.7	6.7	7.6	6.8	6.9	6.4	8.1	8.2	8.1	8.1	8.1	7.9	7.6			
BASCOM NORRIS DR( 4.0R)																							
4454341	4.000	6.490	R	2024		0012	CRACKING	8.0	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	10.0	9.0		
ANDERSON	COLUMBIA	CO., INC	(2026)				SPRIDE	7.6	7.2	7.6	7.5	7.4	7.7	7.6	7.5	7.3	7.1	7.0	6.9	8.4	8.0		
29070000	6.513	6.912	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	10.0			
47 441				1	13.2	3200	RIDE	8.3	8.3	8.3	7.7	7.7	7.6	7.6	7.6	7.5	7.6	7.5	7.4	8.4			
FC125M																							
							CRACKING	10.0	10.0	10.0	10.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.0	6.5	5.8*	3.0*	
							RIDE	8.4	8.2	7.7	7.7	7.6	7.5	7.5	7.5	7.5	7.5	7.4	7.4	7.2	6.8		
2130745	6.490	6.881	C	2029		0012																	
29070000	6.912	15.991	C	1	7	60	CRACKING	10.0	10.0	7.0	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0			
47 441				2	13.2	3200	RIDE	8.6	8.5	8.5	7.7	7.8	7.5	7.4	7.4	8.5	8.4	8.4	8.2	8.0			
FRASER GREEN RD( 7.0R)																							
2084026	6.881	15.971	C	2023		0012	CRACKING	7.0	7.0	7.0	7.0	6.5	5.5*	5.5*	5.5*	5.5*	3.5*	3.5*	3.5*	10.0	9.0		
ANDERSON	COLUMBIA	CO., INC	(2026)				RIDE	8.0	7.6	7.8	7.7	7.8	7.8	7.6	7.5	7.5	7.4	7.2	7.2	8.5	8.1		
29070000	15.991	32.016	C	1	1	60	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.0			
47 441				2	13.2	950	RIDE	8.7	8.7	8.7	8.2	8.2	8.0	7.9	8.0	7.8	7.8	7.7	7.5	7.4			
NE REGISTER LN(16.2R)																							
4244921	15.991	32.016	C	2013		0012	CRACKING	10.0	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	6.5	6.0*	5.5*	4.7*	2.0*		
ANDERSON	COLUMBIA	CO., INC	(2014)				SPRIDE	8.9	8.3	8.3	8.2	8.1	8.1	8.0	7.8	7.9	8.0	7.9	7.8	7.6	7.2		
2083897	15.990	32.016	C	2029		0012																	
29070000	6.513	6.912	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	10.0			
47 441				2	13.2	3200	RIDE	8.1	8.2	8.0	7.6	7.8	7.7	7.6	7.6	7.7	7.6	7.5	7.4	8.4			
FC125M																							
							CRACKING	10.0	10.0	10.0	10.0	7.5	7.5	7.5	7.5	7.0	7.0	7.0	6.5	5.5*	3.0*		
							RIDE	8.4	8.2	7.7	7.7	7.6	7.5	7.5	7.6	6.9	7.1	6.9	6.8	6.6	6.2		
2130745	6.490	6.881	C	2029		0012																	
29070000	4.000	6.513	L	1	7	45	CRACKING	9.0	9.0	9.0	9.0	7.5	6.5	10.0	10.0	10.0	9.0	9.0	9.0	9.0			
47 441				2	7.6	6300	RIDE	7.8	7.7	7.6	7.1	7.0	6.8	8.3	8.4	8.4	8.1	8.1	7.9	7.6			
US-441/SR-100A( 4.0L)																							
4454341	4.000	6.490	L	2024		0012	CRACKING	8.0	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	10.0	9.0		
ANDERSON	COLUMBIA	CO., INC	(2026)				SPRIDE	7.6	7.2	7.6	7.5	7.4	7.7	7.6	7.5	7.6	7.6	7.4	7.5	8.4	8.0		
29080000	0.000	1.473	C	1	1	55	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.5	10.0	10.0	10.0		
238				2	8.8	4400	RIDE	8.5	8.2	8.5	7.8	7.6	7.6	7.4	7.5	7.6	7.0	8.7	8.5	8.3			
SR 25 US 41 US 441( 0.0C)																							
2083932	0.000	1.472	C	2010		0226	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	6.5	3.5*		
ANDERSON	COLUMBIA	CO., INC	(2011)				RIDE	8.4	8.2	8.2	8.1	8.1	7.9	8.1	8.1	8.0	7.9	7.8	7.8	7.7	7.3		
29090000	0.000	10.245	C	1	1	60	CRACKING	9.0	7.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0			
247				2	15.4	5200	RIDE	8.1	8.1	8.4	7.8	7.4	7.4	6.6	8.3	8.3	8.0	8.0	7.7	7.7			
RAMP FROM MARKET RD( 0.2L)																							
2084115	0.000	5.580	C	2007		0012	CRACKING	8.5	8.5	8.5	8.5	7.5	7.0	7.0	7.0	3.5*	3.5*	3.5*	3.5*	3.5*	0.0*		
ANDERSON	COLUMBIA	CO., INC	(2008)				RIDE	7.9	7.7	7.5	7.3	7.4	7.4	7.4	7.3	7.4	7.4	7.2	7.2	7.2	6.8		
2084119	0.000	10.074	C	2027		0012																	
29090000	10.245	11.348	R	1	1	45	CRACKING	9.0		10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.0	8.0			
247				1	4.4	13500	RIDE	8.4		8.2	7.7	7.8	7.6	7.5	7.5	6.9	7.2	7.3	7.5				
LEISURE DR SW(10.4R)																							
							CRACKING	8.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	5.5*	3.7*	0.0*		
							RIDE	7.5	7.3	7.0	6.9	6.8	6.9	6.8	6.8	6.7	6.6	6.6	6.5	6.5	6.1		
4454351	10.074	11.348	C	2027		0012																	
29090000	10.245	11.348	L	1	1	45	CRACKING	9.0		10.0	10.0	10.0	8.5	9.0	8.5	8.5	8.5	8.5	8.0	8.0			
247				1	4.4	13500	RIDE	8.4		8.2	7.7	7.8	7.6	7.5	7.7	6.9	7.2	7.2	7.3	7.5			
REAL TERR SW(10.4L)																							
							CRACKING	8.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	5.5*	4.4*	0.5*		
							RIDE	7.5	7.3	7.0	6.9	6.8	6.9	6.8	6.7	6.5	6.5	6.5	6.4	6.5	6.1		
4454351	10.074	11.348	C	2027		0012																	

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @\* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = COLUMBIA -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT	AT	(MP		SIDE)	SURFTYPE	=====															
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR	(AGE	ONE	YEAR)																		(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F																
29110000	0.000	0.837	C	1	1	60	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	7.5	7.5	7.5	
2				2	28.8	400	RIDE	8.4	8.6	8.5	7.7	8.1	7.9	7.5	8.0	7.8	7.9	8.0	7.9	7.9	
						FC125A															
4244841	0.000	0.837	C	2015	0012		CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.1	6.5	4.0*
ANDERSON	COLUMBIA	CO.,	INC	(2016)			RIDE	7.9	7.8	8.4	8.4	8.4	8.3	8.1	7.9	7.7	7.4	7.1	6.7	6.3*	
29160000	0.000	2.243	C	1	1	55	CRACKING	6.0*	3.5*	0.0*	0.0*	0.0*	0.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
136				2	12.1	2600	RIDE	8.0	7.9	7.8	6.2*	6.1*	6.1*	8.4	8.4	8.4	8.4	8.4	8.4	8.2	
						FC125															
NULL DR NW(	0.9L)																				
2083712	0.000	2.243	C	2006	0012		CRACKING	9.0	9.0	9.0	7.5	7.5	7.0	7.0	6.0*	6.0*	5.5*	3.5*	3.5*	3.1*	0.0*
ANDERSON	COLUMBIA	CO.,	INC	(2007)			RIDE	8.2	8.0	8.0	8.0	8.0	7.8	7.8	7.7	7.6	7.6	7.6	7.4	7.6	7.2
29170000	0.000	0.323	R	4	7	70	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	6.5	6.0*	6.0*	10.0	
8	I10	293.8	294.1	2	27.7	29000	RIDE	9.1	9.0	9.0	8.4	8.5	8.2	8.3	8.1	8.0	7.9	7.7	7.4	8.4	
						FC5M															
					(2026)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.3	10.0	9.0
							RIDE	8.5	8.4	8.7	8.7	8.6	8.7	8.7	8.9	8.9	8.9	8.8	8.7	8.4	8.3
29170000	0.323	6.455	R	4	1	70	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	6.5	6.0*	6.0*	10.0	
8	I10	294.1	300.2	2	28.3	24000	RIDE	9.1	9.0	9.0	8.4	8.5	8.2	8.3	8.1	8.0	7.9	7.7	7.4	8.4	
						FC2															
2130743	0.000	9.522	C	2011	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.3	7.8	5.0*
ANDERSON	COLUMBIA	CO.,	INC	(2013)			SPRIDE	8.5	8.4	8.7	8.7	8.6	8.7	8.7	8.9	8.9	8.9	8.8	8.7	8.7	8.6
29170000	6.455	16.297	R	4	1	70	CRACKING	10.0	9.0	6.5	4.5*	4.5*	3.5*	8.0		10.0	10.0	10.0	10.0	10.0	
8	I10	300.2	310.1	2	27.3	25957	RIDE	9.1	8.9	8.6	7.5	6.7	6.5	7.4		8.1	8.2	8.2	8.0	8.0	
						FC5M															
4326411	5.125	16.154	C	2013	0012		CRACKING	10.0		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.3	7.8	5.5*
				(2016)			RIDE	8.1		8.7	8.7	8.7	8.7	8.7	8.9	8.9	8.8	8.7	8.5	8.7	8.6
2130745	6.455	16.323	C	2029	0012																
29170000	16.297	20.690	R	4	1	70	CRACKING	10.0	9.0	6.5	4.5*	4.5*	3.5*	8.0		10.0	10.0	10.0	10.0	10.0	
8	I10	310.1	314.4	2	27.3	25957	RIDE	9.1	8.9	8.6	7.5	6.7	6.5	7.4		8.1	8.2	8.2	8.0	8.0	
						FC5M															
4434211	16.323	20.690	C	2022	0012		CRACKING	10.0	9.0	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.0
ANDERSON	COLUMBIA	CO.,	INC	(2025)			SPRIDE	8.1	7.7	8.3	8.3	8.2	8.3	8.4	8.5	8.4	8.2	8.0	8.7	8.8	8.7
29170000	16.297	20.690	L	4	1	70	CRACKING	10.0	10.0	9.0	6.5	6.5	4.5*	3.5*		10.0	10.0	10.0	10.0	10.0	
8	I10	310.1	314.4	2	27.3	25957	RIDE	8.9	8.7	8.7	8.0	7.4	7.1	6.9		8.1	8.2	8.2	8.2	8.1	
						FC5M															
4434211	16.323	20.690	C	2022	0012		CRACKING	10.0	10.0	9.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.0
ANDERSON	COLUMBIA	CO.,	INC	(2025)			SPRIDE	8.2	8.0	8.5	8.4	8.4	8.5	8.5	8.6	8.5	8.4	8.2	8.9	9.1	9.0
29170000	6.455	16.297	L	4	1	70	CRACKING	10.0	10.0	9.0	6.5	6.5	4.5*	3.5*		10.0	10.0	10.0	10.0	10.0	
8	I10	300.2	310.1	2	27.3	25957	RIDE	8.9	8.7	8.7	8.0	7.4	7.1	6.9		8.1	8.2	8.2	8.2	8.1	
						FC5M															
4326411	5.125	16.154	C	2013	0012		CRACKING	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.6	8.3	6.0*
				(2016)			RIDE	8.2		8.8	8.7	8.7	8.8	8.8	8.9	8.9	8.9	8.8	8.8	8.8	8.7
2130745	6.455	16.323	C	2029	0012																
29170000	0.323	6.455	L	4	1	70	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	6.5	6.5	10.0	
8	I10	294.1	300.2	2	28.3	24000	RIDE	9.2	9.2	9.1	8.6	8.5	8.4	8.3	8.2	8.2	8.1	7.8	7.7	8.4	
						FC5															
2130743	0.000	9.522	C	2011	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	7.5	7.5	5.0*
ANDERSON	COLUMBIA	CO.,	INC	(2013)			SPRIDE	8.5	8.4	8.7	8.7	8.7	8.8	8.8	8.9	8.9	8.8	8.8	8.8	8.8	8.7
29170000	0.000	0.323	L	4	7	70	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	6.5	6.5	10.0	
8	I10	293.8	294.1	2	27.7	29000	RIDE	9.2	9.2	9.1	8.6	8.5	8.4	8.3	8.2	8.2	8.1	7.8	7.7	8.4	
						FC5M															
					(2026)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0		10.0	9.0
							RIDE	8.5	8.4	8.7	8.7	8.7	8.8	8.8	8.9	8.9	8.8	8.8		8.6	8.5
29180000	0.000	9.790	R	4	1	70	CRACKING	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.5	6.5	6.0*	6.0*		10.0	
93	I75	407.9	417.7	3	30.8	58000	RIDE	9.0	9.0	9.0	8.4	7.9	7.6	8.1	7.9	7.7	7.4	6.8		8.2	
						FC5M															
2130713	0.000	9.802	C	2011	0012		CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	6.9	6.5	4.0*
V. E. WHITEHURST & SONS,				I	(2013)		SPRIDE	8.3	8.2	8.6	8.6	8.6	8.7	8.8	8.9	8.9	8.8	8.8	8.7	8.7	8.6

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = COLUMBIA -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT	AT	(MP		SIDE)			SURFTYPE	=====													
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	P	ASTYPE														
CONTRACTOR	(AGE	ONE	YEAR)					2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F															(PMRS)
29180000	9.790	15.304	R	4	1	70	CRACKING	10.0	10.0	9.0	9.0	9.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0
93 I75	417.7	423.2	3	30.8	53000	RIDE		8.9	8.9	8.8	8.2	8.0	7.9	7.9	7.9	8.3	8.3	8.2	8.1	7.9	
							FC5M														
4455471	9.802	15.318	C	2023	0012	CRACKING	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	6.5	6.5	6.5	10.0	10.0	10.0	9.0
ANDERSON	COLUMBIA	CO.,	INC(2025)		SPRIDE			8.1	7.9	8.4	8.4	8.3	8.4	8.5	8.6	8.6	8.5	8.5	9.0	8.9	8.8
29180000	15.304	19.008	R	4	1	70	CRACKING	10.0	10.0	9.0	9.0	9.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
93 I75	423.2	426.9	3	30.8	53000	RIDE		8.9	8.9	8.8	8.2	8.0	7.9	7.9	8.1	8.2	8.2	8.1	8.1	7.8	
							FC5M														
4425811	15.318	19.002	C	2021	0012	CRACKING	10.0	10.0	9.0	9.0	7.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.7	10.0	8.5	
ANDERSON	COLUMBIA	CO.,	INC(2023)		SPRIDE			7.9	7.7	8.1	8.1	8.1	8.3	8.3	8.4	8.2	9.1	9.1	9.0	9.0	8.9
29180000	19.008	27.352	R	4	1	70	CRACKING	10.0	8.5	7.0	6.0*		10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	
93 I75	426.9	435.2	3	31.7	48915	RIDE		9.0	8.7	8.5	8.3		8.3	8.3	8.2	8.1	7.9	7.8	7.8	7.4	
							FC5M														
4327331	19.008	27.379	C	2016	0012	CRACKING	7.0	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.0
ANDERSON	COLUMBIA	CO.,	INC(2018)		SPRIDE			7.2	6.8	7.5		8.9	8.9	8.8	8.9	8.9	8.9	8.9	8.8	8.8	8.7
29180000	27.352	30.447	R	4	1	70	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	10.0	10.0	10.0	
93 I75	435.2	438.3	3	30.8	48000	RIDE		8.9	9.0	8.9	8.5	8.3	8.2	8.2	8.0	7.9	7.8	8.3	8.4	8.4	
							FC5M														
4460451	27.379	30.447	C	2023	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	6.5	6.5	10.0	10.0	9.0
ANDERSON	COLUMBIA	CO.,	INC(2025)		SPRIDE			8.4	8.2	8.5	8.5	8.4	8.6	8.6	8.7	8.6	8.5	8.5	9.0	8.9	8.8
29180000	27.352	30.447	L	4	1	70	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	10.0	10.0	10.0	
93 I75	435.2	438.3	3	30.8	48000	RIDE		9.0	9.0	8.9	8.4	8.2	8.2	8.1	7.9	7.7	7.1	8.2	8.3	8.3	
							FC5M														
4460451	27.379	30.447	C	2023	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	10.0	10.0	9.0
ANDERSON	COLUMBIA	CO.,	INC(2025)		SPRIDE			8.3	8.2	8.5	8.5	8.5	8.7	8.7	8.8	8.7	8.7	8.6	8.8	9.0	8.9
29180000	19.008	27.352	L	4	1	70	CRACKING	10.0	8.5	7.0	6.0*		10.0	10.0	9.0	9.0	9.0	8.5	8.5	8.5	
93 I75	426.9	435.2	3	31.7	48915	RIDE		9.0	8.9	8.8	8.1		8.3	8.3	8.2	8.2	8.0	7.9	7.7	7.6	
							FC5M														
4327331	19.008	27.379	C	2016	0012	CRACKING	7.0	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.7	9.0	7.0	
ANDERSON	COLUMBIA	CO.,	INC(2018)		SPRIDE			7.4	7.2	7.8		8.8	8.8	8.8	8.9	8.9	8.9	8.9	8.9	8.9	8.8
29180000	15.315	19.008	L	4	1	70	CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	7.5	6.5	10.0	10.0	10.0	10.0	10.0	
93 I75	423.2	426.9	3	30.8	53000	RIDE		9.0	8.5	8.8	8.2	8.1	7.9	7.8	8.2	8.1	8.1	8.1	8.1	7.9	
							FC5M														
4425811	15.318	19.002	C	2021	0012	CRACKING	9.0	9.0	9.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	8.5
ANDERSON	COLUMBIA	CO.,	INC(2023)		SPRIDE			7.8	7.5	8.1	8.1	8.0	8.3	8.3	8.3	8.1	9.1	9.1	9.1	9.1	9.0
29180000	9.790	15.315	L	4	1	70	CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	
93 I75	417.7	423.2	3	30.8	53000	RIDE		9.0	8.5	8.8	8.2	8.1	7.9	7.8	7.8	8.2	8.3	8.2	7.9	7.8	
							FC5M														
4455471	9.802	15.318	C	2023	0012	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	6.5	4.5*	4.5*	10.0	10.0	9.0
ANDERSON	COLUMBIA	CO.,	INC(2025)		SPRIDE			7.9	7.7	8.3	8.3	8.3	8.3	8.3	8.6	8.5	8.4	8.4	9.1	9.0	8.9
29180000	0.000	9.790	L	4	1	70	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	6.0*	6.0*	6.0*		10.0	
93 I75	407.9	417.7	3	30.8	58000	RIDE		9.1	9.0	8.9	8.4	8.2	8.2	7.8	7.8	7.5	7.0	7.1		8.3	
							FC5M														
2130713	0.000	9.802	C	2011	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.8	7.3	4.5*
V. E. WHITEHURST & SONS, I(2013)					SPRIDE			8.3	8.2	8.5	8.5	8.5	8.6	8.6	8.6	8.7	8.6	8.6	8.5	8.5	8.4

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 "@@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).