

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = GILCHRIST																								
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE				
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012				
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKMX-P	SURFTYPE	=====																	
ITMSEG-P	(AGE ONE YEAR)				ASTYPE																			
CONTRACTOR	W BMP	W EMP	RW	FY-F	WKMX-F			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025		2030 (PMRS)		
31010000	0.000	7.822	C	1	7 60	CRACKING		7.0	6.5	6.5	6.0*	3.5*	3.5*	10.0	10.0	10.0	9.5	9.5	9.5	9.5				
26			2	6.4	6900	RIDE		8.4	8.2	8.2	7.5	7.0	6.8	8.5	8.6	8.5	8.4	8.2	8.2	8.2				
FANNING SPRINGS CITY LIM(0.0C)					FC125M																			
4412591	0.000	7.653	C	2023	0012	CRACKING		9.5	7.0	7.0	7.0	6.5	6.5	6.5	6.5	5.5*	4.0*	4.0*			10.0	9.0		
V. E. WHITEHURST & SONS, I(2025)					SPRIDE			8.1	8.1	8.0	7.9	7.8	7.9	7.7	7.8	7.7	7.7	7.7			8.1	7.7		
31010000	7.822	17.730	C	1	1 60	CRACKING		9.0	7.0	7.0	5.5*	3.5*	3.0*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0				
26			2	6.4	10100	RIDE		8.3	8.1	7.9	7.4	6.9	6.8	7.2	6.3*	8.4	8.3	8.2	8.2	8.2				
SE 1ST ST(7.8R)					FC125																			
2097372	10.511	15.482	C	2007	0012	CRACKING		10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	6.0*	6.0*	3.0*			
ANDERSON COLUMBIA CO., INC(2008)					RIDE			8.0	8.0	7.8	7.8	7.7	7.8	7.6	7.7	7.5	7.3	7.4	7.1	7.2	6.8			
2097906	7.818	17.530	C	2025	0012																			
31030000	0.000	2.767	C	1	1 60	CRACKING		3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0				
49 129			2	6.4	6000	RIDE		8.2	7.9	8.8	8.7	8.4	8.4	8.5	8.6	8.5	8.5	8.4	8.4	8.3				
SW 103 ST(0.2R)					FC125M																			
4376201	0.000	1.394	C	2019	0012	CRACKING		9.0	7.5	7.5	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	9.2	8.0			
V. E. WHITEHURST & SONS, I(2021)					SPRIDE			8.3	8.2	7.9	8.1	8.0	8.0	7.8		8.3	8.2	8.1	8.1	8.0	7.6			
31030000	2.767	12.804	C	1	1 60	CRACKING		3.5*		10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5				
49 129			2	7.4	4800	RIDE		6.8		8.9	8.8	8.6	8.6	8.5	8.5	8.3	8.3	8.2	8.2	8.1				
PIEDMONT DAIRY RD(4.5R)					FC125M																			
(2022)					CRACKING			7.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	9.5	8.5			
					RIDE			7.9	7.9	7.8	7.8	7.8	7.6	7.7			8.6	8.6	8.5	8.5	8.1			
31030000	12.804	23.488	C	1	1 60	CRACKING		10.0	7.5	7.5	4.5*	4.5*	3.5*	1.0*	0.0*	0.0*	10.0	10.0	10.0	10.0				
49 129			2	7.4	5100	RIDE		8.7	8.6	8.5	8.1	7.1	6.9	6.5	6.4*	6.1*	8.6	8.4	8.3	8.3				
RODEO RD(12.9L)					FC125M																			
2097692	12.804	23.488	C	2007	0012	CRACKING		10.0	8.5	8.5	7.5	6.0*	6.0*	6.0*	6.0*	3.5*	3.5*	3.5*	3.5*	3.5*	0.5*			
ANDERSON COLUMBIA CO., INC(2009)					SPRIDE			8.1	8.0	7.9	7.9	7.9	7.8	7.5	7.6	7.5	7.4	7.3	7.1	7.1	6.7			
4470361	12.752	23.488	C	2024	0012																			
31040000	0.000	0.612	R	1	7 35	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.0	7.0				
55 19			2	17.7	14300	RIDE			8.2	8.2	8.0	8.0	7.9	7.9	8.0	7.9	7.9	7.8	7.8	7.7				
SIDE ROAD(0.0C)					FC125M																			
(2025)					CRACKING			7.0	6.0*	6.0*	6.0*	4.0*	10.0	10.0	10.0	10.0	10.0	8.5	8.5	10.0	9.0			
					RIDE			7.6	7.5	7.3	7.3	7.2	8.1	8.0	7.9	7.9	7.8	7.8	7.5	8.4	8.0			
31040000	0.000	0.612	L	1	7 35	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.0	7.0	7.0				
55 19			2	17.7	14300	RIDE			8.3	8.2	8.0	7.9	7.8	7.9	7.9	7.9	7.9	7.8	7.8	7.7				
SIDE ROAD(0.0C)					FC125M																			
(2025)					CRACKING			7.0	6.0*	6.0*	6.0*	4.0*	10.0	10.0	10.0	10.0	10.0	8.5	8.5	10.0	9.0			
					RIDE			7.6	7.5	7.1	7.2	7.1	8.2	8.1	8.1	8.0	7.8	7.8	7.6	8.3	7.9			
31050000	0.000	18.364	C	1	7 60	CRACKING		3.0*	3.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0				
47			2	21.5	2500	RIDE		7.9	7.6	8.7	8.6	8.4	8.4	8.3	8.5	8.4	8.4	8.3	8.3	8.3				
SR 49(0.0C)					FC125M																			
4453551	0.000	8.379	C	2023	0012	CRACKING		10.0	8.5	8.5	8.0	7.0	7.0	6.0*	6.0*	4.0*	4.0*	4.0*	4.0*	10.0	9.0			
PREFERRED MATERIALS, INC. (2025)					SPRIDE			8.2	8.2	8.1	7.9	7.9	7.9	7.7	7.9	7.8	7.6	7.7	7.6	8.7	8.3			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).