

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	#T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	W_KMX-P	ASTYPE	=====															(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	W_KMX-F																	
ITMSEG-P	ITMSEG-F																					
36001000	0.000	8.656	R	1	1	65	CRACKING	7.5	6.5	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
25 301				2	18.6		29000 RIDE	8.9	8.6	8.6	8.0	7.7	8.0	8.2	8.2	8.2	8.2	8.1	8.0	7.9		
CR 25A( 0.0C)							FC5HP															
4411361	0.000	8.656	C	2021		0012	CRACKING	10.0	9.0	7.0	6.0*	6.0*	6.0*	6.0*	4.5*	4.5*		10.0	10.0	9.7	8.5	
ANDERSON COLUMBIA CO., INC(2024)							SPRIDE	7.8	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0		8.5	8.5	8.5	8.5	8.3
36001000	8.656	14.221	R	1	1	65	CRACKING	0.0*	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0		
25 441				2	21.3		7700 RIDE	8.6	8.6	8.5	8.0	8.0	7.8	7.9	7.8	7.8	7.7	7.7	7.5	7.5		
NW140 ST( 9.7R)							FC5M															
4272801	8.911	13.788	C	2016		0012	CRACKING	7.0	7.0	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.4	9.7	7.5	
ANDERSON COLUMBIA CO., INC(2018)							SPRIDE	7.3	7.2	7.7		8.6	8.6	8.5	8.4	8.3	8.2	8.3	8.2	8.2	8.0	8.0
36001000	8.656	14.221	L	1	1	65	CRACKING	0.0*	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	6.5	6.5	6.5	6.5		
25 441				2	21.3		7700 RIDE	8.5	8.5	8.5	8.0	8.0	7.9	7.9	7.8	7.8	7.7	7.7	7.5	7.5		
NW 142 PL(10.0L)							FC5M															
4272801	8.911	13.788	C	2016		0012	CRACKING	6.5	6.0*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.3	10.0	8.0	
ANDERSON COLUMBIA CO., INC(2018)							SPRIDE	7.4	7.2	7.8		8.6	8.5	8.5	8.4	8.2	8.3	8.3	8.2	8.2	8.0	8.0
36001000	0.000	8.656	L	1	1	65	CRACKING	6.5	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
25 301				2	18.6		29000 RIDE	8.8	8.6	8.5	7.7	7.3	8.3	8.4	8.3	8.4	8.4	7.7	8.0	8.2		
CR 25A( 0.0C)							FC5HP															
4411361	0.000	8.656	C	2021		0012	CRACKING	10.0	10.0	8.5	7.0	7.0	6.5	6.5	3.5*	3.5*		10.0	10.0	9.8	8.5	
ANDERSON COLUMBIA CO., INC(2024)							SPRIDE	8.1	8.0	8.2	8.1	8.1	8.2	8.2	8.1	8.1		8.4	8.4	8.4	8.2	8.2
36002000	0.000	4.727	R	1	1	60	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	7.5	6.5	6.5		
200 301				2	25.0		17400 RIDE	8.9	8.9	8.7	8.3	8.2	8.1	7.9	8.0	7.9	7.9	8.0	7.8	7.7		
SR 25( 0.0C)							FC5M															
4272491	0.000	4.774	C	2013		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.7	7.4	4.5*	
(2014)							RIDE	8.0	8.0	8.4	8.4	8.4	8.5	8.5	8.4	8.5	8.5	8.5	8.5	8.5	8.5	8.3
36002000	0.000	4.727	L	1	1	60	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	6.5	7.5	6.5	6.5		
200 301				2	25.0		17400 RIDE	8.7	8.7	8.6	8.2	8.1	8.1	8.0	7.9	7.8	7.8	7.6	7.5	7.4		
US-441/SR-25( 0.0L)							FC5M															
4272491	0.000	4.774	C	2013		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.9	7.2	4.5*	
(2014)							RIDE	8.2	8.3	8.5	8.5	8.5	8.6	8.6	8.6	8.6	8.6	8.6	8.5	8.5	8.5	8.3
36004000	0.000	0.633	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5		
464				2	15.1		32000 RIDE	8.3	8.5	7.7	7.3	7.1	7.2	6.8	7.3	7.8	8.0	7.7	7.7	7.1		
COLLEGE RD SW( 0.0C)							FC3															
2386731	0.000	1.228	C	1993		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.0	7.0	7.0	7.0	7.0	7.0	6.8	6.6	3.0*	
CRRAGS CONSTRUCTION COMPAN(1994)							S RIDE	6.9	7.1	7.0	7.0	7.1	6.9	7.1	7.1	7.8	7.2	7.2	7.1	7.0	6.7	
4526341	0.017	1.210	C	2029		0226																
36004000	0.633	1.332	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	10.0	10.0	10.0	10.0	10.0		
464				2	15.1		32000 RIDE	8.3	8.5	7.7	7.3	7.1	7.2	6.8	7.3	7.8	6.9	6.9	6.9	6.7		
SW 12 AVE( 0.7C)							FC95															
4526341	0.017	1.210	C	2029		0226	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	6.0*	
(2010)							RIDE	6.9	7.0	6.9	6.8	6.4	6.5	6.4	6.4	6.8	7.0	6.7	6.7	6.3	6.0	
36004000	1.332	7.213	R	1	8	50	CRACKING	8.0	8.0	6.5	4.5*	4.5*	3.5*	3.5*		10.0	10.0	9.0	9.0	8.5		
464				2	3.8		34532 RIDE	8.5	8.4	8.0	7.6	7.3	7.0	7.0		8.0	8.0	8.0	7.9	7.8		
FIRST AVE SW( 1.4C)							FC5															
4155231	1.242	7.213	C	2007		0012	CRACKING	8.5	8.5	8.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	3.7*			
ANDERSON COLUMBIA CO., INC(2009)							SPRIDE	7.8	7.7	7.8	7.7	7.6	7.6	7.7	7.7	7.6	7.6	7.1	7.0			
4411411	1.335	7.213	C	2023		0012																
36004000	1.332	7.213	L	1	8	50	CRACKING	9.0	9.0	6.5	4.5*	4.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	8.5		
464				2	3.8		34532 RIDE	8.6	8.4	8.3	7.8	7.6	7.2	7.1		8.0	7.9	7.6	7.5	7.5		
FIRST AVE SW( 1.4C)							FC5															
4155231	1.242	7.213	C	2007		0012	CRACKING	8.5	8.5	8.5	7.0	7.0	7.0	4.5*	4.5*	4.5*	4.5*	3.5*				
ANDERSON COLUMBIA CO., INC(2009)							SPRIDE	7.4	7.4	7.7	7.6	7.6	7.4	7.5	7.5	7.1	6.9	6.5				
4411411	1.335	7.213	C	2023		0012																
36004000	0.633	1.332	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
464				2	15.1		32000 RIDE	7.6	7.8	7.9	7.5	7.2	7.5	7.2	7.2	7.3	7.0	7.0	7.0	7.2	7.0	
SW 12 AVE( 0.7C)							FC95															
2386731	0.000	1.228	C	1993		0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	7.0	7.0	8.0	8.0	8.4	5.0*	
CRRAGS CONSTRUCTION COMPAN(1994)							S RIDE	6.9	6.8	6.8	6.7	6.4	6.1	6.5	6.4	6.9	6.8	6.5	6.4	6.2	5.9	
4526341	0.017	1.210	C	2029		0226																

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @\* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-M	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
ITMSEG-P	(AGE_ONE YEAR)	W_EMP	RW	FY-F	WKM-M	ASTYPE	=====														(PMRS)	
CONTRACTOR																						
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-M	ASTYPE																
36004000	0.000	0.633	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	
464				2	15.1	32000	RIDE	7.6	7.8	7.9	7.5	7.2	7.5	7.2	7.2	7.3	7.5	7.3	7.2	7.4		
COLLEGE RD SW( 0.0C)																						
2386731	0.000	1.228	C	1993		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.0	7.0	7.0	7.0	7.0	7.0	6.1*	7.0	3.5*	
CRAGGS CONSTRUCTION COMPAN(1994)																						
4526341	0.017	1.210	C	2029		0226	RIDE	7.1	7.4	7.5	7.9	8.0	8.0	7.5	7.7	8.0	7.8	7.5	7.6	7.5	7.2	
-----																						
36004001	0.000	0.216	C	1	1		CRACKING															
464				2	3.8	300	RIDE															
CRACKING																						
RIDE																						
-----																						
36004002	0.000	0.237	C	1	1		CRACKING															
464				2	3.8	600	RIDE															
CRACKING																						
RIDE																						
(2026)																						
-----																						
36004003	0.000	0.309	C	1	1		CRACKING															
464				2	3.8	450	RIDE															
CRACKING																						
RIDE																						
-----																						
36008000	0.000	3.737	R	1	1	45	CRACKING	6.5	6.5	3.5*	3.5*	3.5*	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5		
492				2	23.3	17000	RIDE	7.5	7.4	6.8	6.0*	5.5*	7.6	7.4	7.8	7.7	7.3	7.5	7.4	7.3		
PINE AVE N( 0.0C)																						
4306551	0.000	3.719	C	2018		0012	CRACKING	8.5	8.5	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	8.7	8.5	7.0	
ANDERSON COLUMBIA CO., INC(2020)																						
4306551	0.000	3.719	C	2018		0012	CRACKING	7.5	7.3	7.2	7.1	6.9		8.0	8.0	7.8	7.8	7.7	7.7	7.7	7.4	
ANDERSON COLUMBIA CO., INC(2020)																						
36008000	0.000	3.737	L	1	1	45	CRACKING	6.5	6.5	3.5*	3.5*	3.5*	10.0	10.0	10.0	9.0	8.5	7.0	7.0	7.0		
492				2	23.3	17000	RIDE	7.6	7.5	7.2	6.2*	5.7*	7.8	7.8	7.9	7.8	7.5	7.6	7.1	7.1		
PINE AVE N( 0.0C)																						
4306551	0.000	3.719	C	2018		0012	CRACKING	7.0	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	8.5	8.1	7.6	6.0*	
ANDERSON COLUMBIA CO., INC(2020)																						
4306551	0.000	3.719	C	2018		0012	CRACKING	7.0	7.0	6.6	6.7	6.6		7.9	7.9	7.7	7.6	7.7	7.6	7.6	7.3	
ANDERSON COLUMBIA CO., INC(2020)																						
36009000	0.000	1.486	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	
35				2	17.3	15000	RIDE	8.4	8.3	8.2	7.8	7.8	7.5	7.7	7.7	7.6	7.9	7.8	7.7	7.3		
CR-25/SE 110 ST( 0.0R)																						
4248851	0.000	1.570	C	2013		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.3	7.8	6.0*	
D.A.B. CONSTRUCTORS, INC (2014)																						
4248851	0.000	1.570	C	2013		0012	CRACKING	8.2	8.3	8.2	8.2	8.0	8.0	8.1	8.2	8.1	8.2	8.0	8.0	8.0	7.8	7.5
D.A.B. CONSTRUCTORS, INC (2014)																						
36009000	1.486	5.269	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	6.5	6.5	6.5	6.5		
35				2	10.2	28500	RIDE	8.4	8.3	8.2	7.8	7.8	7.5	7.7	7.9	7.4	7.9	7.8	7.8	7.7		
SE 96 PL RD( 1.5R)																						
2386931	1.486	5.244	C	2015		0213	CRACKING	6.5	6.0*	6.0*				10.0	10.0	10.0	10.0	10.0	9.6	9.2	8.0	
(2020)																						
2386931	1.486	5.244	C	2015		0213	CRACKING	7.5	7.3	7.3				7.3	7.3	7.2	7.1	7.2	7.1	7.1	6.8	
(2020)																						
36009000	5.269	10.843	R	1	1	45	CRACKING	8.5	8.5	7.0	6.0*	3.5*	3.5*	3.5*		4.5*	4.5*			10.0		
35				2	15.7	22000	RIDE	8.6	8.3	7.8	7.1	6.6	6.2	5.7		5.9	6.4			8.3		
CR-464( 5.5R)																						
2386771	5.123	10.827	C	2010		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	7.5	5.5*	3.5*	
(2013)																						
4542111	5.264	10.829	C	2029		0012	RIDE	8.2	8.4	8.2	8.2	8.1	8.0	8.0	8.1	8.0	7.8	7.8	7.6	7.7	7.4	
-----																						
36009000	5.269	10.843	L	1	1	45	CRACKING	8.5	8.5	7.0	6.0*	3.5*	3.5*	3.5*		4.5*	4.5*			10.0		
35				2	15.7	22000	RIDE	8.6	8.3	7.8	7.1	6.6	6.2	5.7		5.9	6.4			8.2		
CR 464( 5.5L)																						
2386771	5.123	10.827	C	2010		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	5.0*	3.0*	
(2013)																						
4542111	5.264	10.829	C	2029		0012	RIDE	8.3	8.3	8.2	8.2	8.2	8.1	8.1	8.1	8.1	8.0	8.0	7.9	7.9	7.6	
-----																						
36009000	1.486	5.269	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	6.5	6.5	6.5	6.5		
35				2	10.2	28500	RIDE	8.4	8.3	8.2	7.8	7.8	7.5	7.7	7.9	7.4	7.9	7.8	7.8	7.8	7.7	
SE 92 PL RD( 1.8L)																						
2386931	1.486	5.244	C	2015		0213	CRACKING	6.5	6.0*	6.0*				10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.0	
(2020)																						
2386931	1.486	5.244	C	2015		0213	CRACKING	7.5	7.3	7.3				7.7	7.7	7.6	7.6	7.6	7.5	7.6	7.3	
(2020)																						

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @\* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKMXP	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKMXP	F															(PMRS)
ITMSEG-P																					
ITMSEG-F																					
36010000	14.347	14.711	R	1	1	35	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5		10.0	9.5	9.5	9.5	9.5	
25 27				2	3.8	13200	RIDE	7.3	7.5	7.2	7.0	7.1	6.9	6.1		7.3	6.9	6.9	6.9	6.1	
BASELINE RD(14.3R)																					
4392381	14.347	14.711	C	2020		0012	CRACKING	9.5	8.5	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	9.0
WESTERN SURETY COMPANY (2024) SPRIDE 7.0 6.8 5.9 6.0 5.8 5.6 5.6 5.7 5.7 5.3* 7.1 6.0 5.7																					
36010000	14.711	23.895	R	1	1	55	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	
25 27				2	20.5	30000	RIDE	8.6	8.6	8.4	8.2	8.2	8.0	8.1	8.1	8.1	8.1	8.1	8.1	7.9	
OAK RD(14.8R)																					
4392381	14.711	23.868	C	2020		0012	CRACKING	9.0	8.0	8.0	6.5	6.5	6.5	6.5	4.5*	4.5*		10.0	10.0	10.0	8.5
WESTERN SURETY COMPANY (2024) SPRIDE 8.0 7.7 8.1 8.0 8.0 8.1 8.1 8.1 8.1 8.0 8.2 8.2 8.2 8.0																					
36010000	23.895	24.959	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
25 27				3	3.8	32000	RIDE	8.3	8.3	7.9	7.7	7.5	7.2	7.8	7.7	7.8	8.0	7.7	7.6	7.4	
SE 22 PL(24.0R)																					
4392381	23.868	24.959	C	2020		0012	CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.0
WESTERN SURETY COMPANY (2024) SPRIDE 7.6 7.3 7.2 7.1 7.1 7.0 6.9 7.0 6.7 6.4 6.8 6.8 6.9 6.6																					
36010000	23.895	24.959	L	1	1	35	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
25 27				3	3.8	32000	RIDE	8.1	8.2	8.0	7.7	7.5	7.4	7.4	7.5	7.4	7.5	7.5	7.3	7.3	
SE 1ST AVE(24.0L)																					
4392381	23.868	24.959	C	2020		0012	CRACKING	10.0	8.5	7.0	6.5	6.5	6.5	6.5	4.5*	3.5*	3.5*	10.0	10.0	10.0	9.0
WESTERN SURETY COMPANY (2024) SPRIDE 7.2 7.2 7.1 7.2 7.0 6.8 7.0 7.1 6.6 6.5 7.8 7.8 7.8 7.5																					
36010000	14.711	23.895	L	1	1	55	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	
25 27				2	20.5	30000	RIDE	8.6	8.6	8.3	8.2	8.1	7.9	8.2	8.2	8.1	8.1	8.2	8.1	8.1	
SE 57 AVE(14.9C)																					
4392381	14.711	23.868	C	2020		0012	CRACKING	9.0	7.0	6.5	6.5	6.5	5.5*	5.5*	3.5*	3.5*		10.0	10.0	10.0	8.5
WESTERN SURETY COMPANY (2024) SPRIDE 8.0 7.9 8.0 7.9 7.9 7.9 7.9 7.9 7.9 7.8 8.1 8.1 8.1 7.9																					
36010000	14.347	14.711	L	1	1	35	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5		10.0	9.5	9.5	9.5	9.5	
25 27				2	3.8	13200	RIDE	7.3	7.5	7.2	7.0	7.1	6.9	6.1		7.3	6.9	6.9	6.9	6.1	
SE 62ND AVE(14.4L)																					
4392381	14.347	14.711	C	2020		0012	CRACKING	9.5	8.5	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	9.0
WESTERN SURETY COMPANY (2024) SPRIDE 7.0 6.8 5.9 6.0 5.8 5.6 5.6 5.7 5.7 5.3* 6.0 5.8 5.5																					
36030000	0.000	0.292	R	1	1	35	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	
25 27				3	13.4	41500	RIDE	7.4	8.1	7.6	6.1	6.8	6.8	5.0*	6.8	6.6	7.9	7.9	7.8	7.8	
OCALA CITY LIMITS( 0.0C)																					
4195851	0.000	2.699	C	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	6.0*	6.0*		3.6*	1.5*
THE MIDDLESEX CORPORATION (2010) RIDE 7.7 7.6 7.5 7.5 7.4 6.9 7.1 7.1 7.0 7.1 6.4 6.5 6.2																					
4526351	0.012	0.296	C	2027		0226															
36030000	0.292	0.652	R	1	7	35	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	
25 27				3	13.4	41500	RIDE	7.4	8.1	7.6	6.1	6.8	6.8	5.0*	6.8	6.6	7.9	7.9	7.8	7.8	
SW 3 ST( 0.3C)																					
				(2026)			CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	6.0*	6.0*		10.0	9.0
RIDE 7.7 7.6 7.5 7.5 7.4 6.9 7.1 7.1 7.0 7.1 6.4 5.8 5.5																					
36030000	0.652	1.805	R	1	1	45	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	
25 27				2	12.2	32500	RIDE	9.0	9.0	8.7	8.6	8.4	8.1	8.2	8.2	8.2	8.6	8.6	8.6	8.5	
NW 3 ST( 0.7R)																					
4195851	0.000	2.699	C	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	7.0	7.1	6.8	4.5*
THE MIDDLESEX CORPORATION (2010) RIDE 8.5 8.4 8.3 8.2 8.2 7.9 8.0 8.0 7.9 7.8 7.7 7.8 7.5																					
4542141	0.692	1.809	C	2028		0012															
36030000	1.805	2.606	R	1	1	45	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	
25 301				2	22.7	19500	RIDE	9.0	9.0	8.7	8.6	8.4	8.1	8.2	8.2	8.2	8.6	8.6	8.6	8.5	
CR 200A( 1.9R)																					
				(2024)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	10.0	10.0	10.0	9.0
RIDE 8.5 8.4 8.3 8.2 8.2 7.9 8.0 8.0 8.0 7.9 8.2 8.1 8.2 7.9																					
36030000	16.463	19.635	R	1	1	60	CRACKING	10.0	9.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	
25 441				2	11.6	8800	RIDE	8.8	8.7	8.5	7.8	7.5	7.3	7.1	6.9	8.1	8.0	8.0	8.0	7.9	
NW 177 PL(16.8R)																					
4171621	16.399	22.764	C	2007		0012	CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	7.5	4.5*	4.5*	4.5*	4.5*	3.3*	2.4*	0.0*
ANDERSON COLUMBIA CO., INC(2009) SPRIDE 7.9 7.8 8.2 8.3 8.2 8.3 8.2 8.2 8.2 8.1 8.0 7.9 7.6 7.4																					
4486351	16.399	19.572	C	2025		0012															

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @\* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	W_YEAR	FY-P	WKM-F	WKM-F	ASTYPE	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	W_BMP	W_EMP	W_YEAR	FY-F	WKM-F	WKM-F	ASTYPE														(PMRS)
ITMSEG-F	W_BMP	W_EMP	W_YEAR	FY-F	WKM-F	WKM-F	ASTYPE														
36030000	19.635	20.075	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
25 441				4	19.6	8200	RIDE	8.3	8.3	7.8	7.6	7.5	7.2	7.4	7.4	7.9	7.7	7.8	7.8	7.7	
AVE H(19.7C)																					
4171621	16.399	22.764	C	2007	0012	CRACKING	10.0	8.5	8.5	7.5	7.5	7.5	7.5	7.5	6.5	6.0*	6.0*	6.0*	5.5*	6.3*	4.0*
ANDERSON	COLUMBIA CO., INC	(2009)					SPRIDE	7.7	7.6	7.6	7.6	7.6	7.5	7.5	7.5	7.4	7.4	7.2	7.4	7.1	6.8
4452181	19.572	22.718	C	2025	0012																
36030000	20.075	22.831	R	1	1	65	CRACKING	10.0	10.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0
25 441				2	19.6	8200	RIDE	8.7	8.6	8.4	7.4	7.0	6.7	6.8	6.4*	8.2	8.2	8.1	8.0	7.7	
AVE C(20.1C)																					
4171621	16.399	22.764	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	4.5*	4.5*	4.5*	4.3*	3.9*	0.0*
ANDERSON	COLUMBIA CO., INC	(2009)					SPRIDE	7.4	7.7	8.1	8.1	8.2	8.2	8.3	8.3	8.1	8.2	8.2	8.0	7.8	7.6
4452181	19.572	22.718	C	2025	0012																
36030000	20.075	22.831	L	1	1	65	CRACKING	9.0	10.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0
25 441				2	19.6	8200	RIDE	8.6	8.2	8.2	7.3	7.2	7.0	6.7	6.4*	8.0	7.9	7.9	7.9	7.8	
AVE C(20.1C)																					
4171621	16.399	22.764	C	2007	0012	CRACKING	10.0	9.5	9.5	9.0	9.0	7.5	7.5	7.5	4.5*	4.5*	4.5*	4.5*	3.6*	3.1*	0.0*
ANDERSON	COLUMBIA CO., INC	(2009)					SPRIDE	7.8	7.7	8.2	8.2	8.1	8.1	8.2	8.2	8.1	8.1	8.1	8.0	7.8	7.6
4452181	19.572	22.718	C	2025	0012																
36030000	19.635	20.075	L	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	10.0	10.0	10.0	10.0	10.0
25 441				2	19.6	8200	RIDE	8.3	8.3	7.8	7.6	7.5	7.2	7.4	7.4	7.9	7.7	7.8	7.8	7.7	
AVE H(19.7C)																					
4171621	16.399	22.764	C	2007	0012	CRACKING	10.0	8.5	8.5	7.5	7.5	7.5	7.5	7.5	6.5	6.0*	6.0*	6.0*	5.5*	5.3*	3.0*
ANDERSON	COLUMBIA CO., INC	(2009)					SPRIDE	7.7	7.6	7.6	7.6	7.6	7.5	7.5	7.5	7.4	7.4	7.2	7.4	6.7	6.4
4452181	19.572	22.718	C	2025	0012																
36030000	16.463	19.635	L	1	1	60	CRACKING	9.0	6.5	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0
25 441				2	11.6	8800	RIDE	8.6	8.6	8.2	7.9	7.4	6.9	6.9	6.5	8.2	8.2	8.1	8.2	8.1	
NW 177 LN(16.8L)																					
4171621	16.399	22.764	C	2007	0012	CRACKING	10.0	8.5	8.5	8.5	8.5	8.5	7.0	7.0	4.5*	4.5*	4.5*	4.5*	4.4*	4.0*	0.5*
ANDERSON	COLUMBIA CO., INC	(2009)					SPRIDE	8.0	8.0	8.3	8.3	8.2	8.4	8.3	8.3	8.2	8.2	8.1	8.0	7.7	7.5
4486351	16.399	19.572	C	2025	0012																
36030000	1.805	2.606	L	1	1	45	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	6.0*	10.0	10.0	10.0	10.0	10.0
25 301				2	22.7	19500	RIDE	8.5	8.8	8.7	8.4	8.3	8.0	8.0	7.9	7.6	8.6	8.6	8.6	8.5	
NW 22 ST( 2.1C)																					
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	10.0	10.0	10.0
							RIDE	8.5	8.5	8.3	8.2	8.2	7.9	8.1	8.1	8.1	8.0	8.4	8.2	8.3	8.0
36030000	0.652	1.805	L	1	1	45	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	6.0*	10.0	10.0	10.0	10.0	10.0
25 27				2	12.2	32500	RIDE	8.5	8.8	8.7	8.4	8.3	8.0	8.0	7.9	7.6	8.6	8.6	8.6	8.5	
EIGHTH ST NW( 1.0C)																					
4195851	0.000	2.699	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.5	7.5	7.0	5.0*
THE MIDDLESEX CORPORATION			(2010)				RIDE	8.5	8.5	8.3	8.2	8.2	7.9	8.1	8.1	8.0	7.9	7.9	7.7	8.0	7.7
4542141	0.692	1.809	C	2028	0012																
36030000	0.292	0.652	L	1	7	35	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	7.0	10.0	10.0	10.0	10.0	10.0
25 27				2	13.4	41500	RIDE	8.5	8.3	8.1	7.8	7.8	7.6	7.1	7.0	6.7	7.8	7.8	7.6	7.6	
SW 3 ST( 0.3C)																					
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.0	8.0	7.0	7.0		10.0	9.0
							RIDE	7.5	7.5	7.3	7.3	7.2	7.3	7.3	7.4	7.2	7.3	7.1		7.5	7.2
36030000	0.000	0.292	L	1	1	35	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	6.5	6.5	7.0	10.0	10.0	10.0	10.0	10.0
25 27				3	13.4	41500	RIDE	8.5	8.3	8.1	7.8	7.8	7.6	7.1	7.0	6.7	7.8	7.8	7.6	7.6	
OCALA CITY LIMITS( 0.0C)																					
4195851	0.000	2.699	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.0	8.0	7.0	7.0		5.0*	3.0*
THE MIDDLESEX CORPORATION			(2010)				RIDE	7.5	7.5	7.3	7.3	7.2	7.3	7.3	7.4	7.2	7.3	7.1		7.3	7.0
4526351	0.012	0.296	C	2027	0226																
36040000	14.143	14.310	R	1	1	55	CRACKING	9.0	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
200 301				2	16.2	14800	RIDE	8.7	8.5	8.1	7.4	7.2	6.9	7.6	7.8	7.8	7.7	7.6	7.7		
FROM CR-200A(14.2R)																					
4155111	14.161	16.652	C	2006	0012	CRACKING	10.0	10.0	9.0	9.0	8.0	7.0	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	8.3	8.3	4.5*
ANDERSON	COLUMBIA CO., INC	(2007)					SPRIDE	7.7	7.7	7.8	7.7	7.7	7.7	7.7	7.7	7.6	7.9	7.9	8.3	8.3	8.1
36040000	14.310	15.026	R	1	1	45	CRACKING	9.0	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
200 301				2	16.2	14800	RIDE	8.7	8.5	8.1	7.4	7.2	6.9	7.6	7.8	7.8	7.7	7.6	7.7		
NE 175 ST(14.5C)																					
4452121	14.290	15.007	R	2023	0012	CRACKING	10.0	10.0	9.0	9.0	8.0	7.0	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.0
							RIDE	7.7	7.7	7.8	7.7	7.7	7.7	7.7	7.7	7.6	7.9	7.9	8.2	8.3	8.1

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @\* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR US	G_BMP	G_EMP	LN	#T	ADT	RATINGS	*****	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013		
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	*****															(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	*****															
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	*****															
36040000	15.026	15.632	R	1	1	45	CRACKING	9.0	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
200 301				2	16.2	14800	RIDE	8.7	8.5	8.1	7.4	7.2	6.9	7.6	7.8	7.8	7.8	7.7	7.6	7.7		
NE 180 ST(15.0C)						FC125M																
4452121	15.007	15.605	R	2023	0012		CRACKING	10.0	10.0	9.0	9.0	8.0	7.0	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.0	
				(2025)			RIDE	7.7	7.7	7.8	7.7	7.7	7.7	7.7	7.7	7.6	7.9	7.9	7.6	7.6	7.6	7.3
36040000	15.632	16.652	R	1	1	55	CRACKING	9.0	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
200 301				2	16.2	14800	RIDE	8.7	8.5	8.1	7.4	7.2	6.9	7.6	7.8	7.8	7.8	7.7	7.6	7.7		
NE 189 LN(16.0R)						FC5M																
4452121	15.605	16.652	R	2023	0012		CRACKING	10.0	10.0	9.0	9.0	8.0	7.0	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.0	
				(2025)			RIDE	7.7	7.7	7.8	7.7	7.7	7.7	7.7	7.7	7.6	7.9	7.9	8.5	8.5	8.5	8.3
36040000	15.589	16.652	L	1	1	55	CRACKING	9.0	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
200 301				2	16.2	14800	RIDE	8.7	8.6	8.1	7.9	7.5	7.3	7.7	7.8	7.8	7.7	7.8	7.7	7.7		
NE 189 LN(16.0L)						FC5M																
4452121	15.605	16.652	L	2023	0012		CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	9.0	
				(2025)			RIDE	7.6	7.6	7.7	7.6	7.6	7.6	7.6	7.6	7.5	7.8	7.8	8.5	8.5	8.5	8.3
36040000	14.957	15.589	L	1	1	45	CRACKING	9.0	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
200 301				2	16.2	14800	RIDE	8.7	8.6	8.1	7.9	7.5	7.3	7.7	7.8	7.8	7.7	7.8	7.7	7.7		
NE 180 ST(15.0C)						FC125M																
4452121	15.007	15.605	L	2023	0012		CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	9.0	
				(2025)			RIDE	7.6	7.6	7.7	7.6	7.6	7.6	7.6	7.6	7.5	7.8	7.8	7.9	7.9	7.9	7.6
36040000	14.300	14.957	L	1	1	45	CRACKING	9.0	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
200 301				2	16.2	14800	RIDE	8.7	8.6	8.1	7.9	7.5	7.3	7.7	7.8	7.8	7.7	7.8	7.7	7.7		
NE 175 ST(14.5C)						FC5																
4452121	14.290	15.007	L	2023	0012		CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	9.0	
V. E. WHITEHURST & SONS,				(2025)			SPRIDE	7.6	7.6	7.7	7.6	7.6	7.6	7.6	7.6	7.5	7.8	7.8	8.6	8.6	8.6	8.4
36040000	14.143	14.300	L	1	1	55	CRACKING	9.0	6.5	4.5*	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
200 301				2	16.2	14800	RIDE	8.7	8.6	8.1	7.9	7.5	7.3	7.7	7.8	7.8	7.7	7.8	7.7	7.7		
FROM CR 200A(14.2L)						FC5																
				(2025)			CRACKING	10.0	10.0	9.0	9.0	9.0	7.5	4.5*	4.5*	3.5*	3.5*	3.5*	9.0	8.5	7.5	
							RIDE	7.6	7.6	7.7	7.6	7.6	7.6	7.6	7.6	7.5	7.8	7.8	8.2	8.2	8.0	8.0
36050000	0.000	1.500	R	1	1	55	CRACKING	8.5	8.5	7.0	6.5	4.5*		3.5*	3.5*	3.5*			10.0	10.0		
35 301				2	3.8	30500	RIDE	8.5	8.1	8.3	7.9	7.9		7.7	7.8	7.5			8.4	7.7		
						FC5																
4112563	0.000	1.404	C	2010	0213		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5	7.8	4.5*
D.A.B. CONSTRUCTORS, INC				(2012)			SPRIDE	8.3	8.4	8.3	8.3	8.3	8.0	8.0	8.0	8.0	8.0	8.0	7.9	8.0	8.0	7.8
4526941	0.000	1.540	C	2029	0226																	
36050000	1.500	1.900	R	1	7	55	CRACKING	8.5	8.5	7.0	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
35 301				2	20.3	16200	RIDE	8.5	8.1	8.3	7.9	7.9		7.5	7.6	7.5	7.6	7.6	7.4	6.9		
CR 42( 1.5C)						FC125M																
4453021	1.540	1.904	R	2024	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	10.0	9.0	
C. W. ROBERTS CONTRACTING,				(2026)			SPRIDE	7.3	7.4	7.3	7.1	7.2	8.0	8.0	8.0	8.0	8.0	8.0	7.9	8.2	7.9	7.9
36050000	1.900	3.235	C	1	7	55	CRACKING	8.5	8.5	7.0	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	
35 301				2	20.3	16200	RIDE	8.5	8.1	8.3	7.9	7.9	7.1	7.5	7.5		8.4	8.4	8.3	7.8		
SE 151 ST( 2.9L)						FC125M																
4453021	1.904	2.526	C	2024	0012		CRACKING	10.0	9.5	8.5	8.5	8.5	7.0	6.5	6.5	6.5	6.5	6.5	5.9*	10.0	9.0	
C. W. ROBERTS CONTRACTING,				(2026)			SPRIDE	8.2	8.0	7.9	7.6	7.4	7.1	7.2	7.1	6.9	7.5	7.3	7.1	8.3	8.0	8.0
36050000	3.235	3.744	R	1	7	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5		10.0	10.0	10.0	10.0	10.0	
35 301				2	20.3	16200	RIDE	8.7	8.8	8.5	8.4	8.2	7.8	7.9	8.0		8.4	8.4	8.3	7.8		
SE 147 ST( 3.4C)						FC125M																
4453021	3.278	3.747	R	2024	0012		CRACKING	10.0	9.5	8.5	8.5	8.5	7.0	6.5	6.5	6.5	6.5	6.5	5.9*	10.0	9.0	
C. W. ROBERTS CONTRACTING,				(2026)			SPRIDE	8.2	8.0	7.9	7.6	7.4	7.1	7.2	7.1	6.9	7.5	7.3	7.1	7.3	7.0	7.0
36050000	3.744	6.866	R	1	1	55	CRACKING	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	
35 301				2	20.3	16200	RIDE	8.9	8.7	8.5	8.3	8.3	8.1	8.2	8.2		8.4	8.4	8.3	7.9		
SE 139 ST( 4.2R)						FC5																
4195571	1.904	6.866	C	2008	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	6.9	6.5	3.0*	
C. W. ROBERTS CONTRACTING,				(2010)			SPRIDE	8.3	8.4	8.5	8.4	8.4	8.5	8.5	8.5	8.5	8.5	8.5	8.4	8.5	8.4	8.2
4542151	3.747	6.866	C	2029	0012																	

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	*****	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	*****														(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	*****														
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	*****														
36050000	3.744	6.866	L	1	1	55	CRACKING	8.5	8.5	7.0	7.0	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	
35 301				2	20.3		16200 RIDE	8.6	8.5	8.2	8.0	7.9	7.8	7.8	7.7		8.5	8.5	8.4	8.1	
SE 142 PL( 3.9L)							FC125														
4195571	1.904	6.866	C	2008		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	6.7	5.9*	3.5*
C. W. ROBERTS CONTRACTING, (2010)							SPRIDE	8.4	8.4	8.5	8.5	8.4	8.5	8.5	8.5	8.5	8.4	8.4	8.4	8.3	8.0
4542151	3.747	6.866	C	2029		0012															
36050000	3.235	3.744	L	1	7	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	9.5		10.0	10.0	10.0	10.0	
35 301				2	20.3		16200 RIDE	8.7	8.8	8.5	8.4	8.2	7.8	7.9	7.6		8.4	8.4	8.3	7.8	
SE 147 ST( 3.4C)							FC125														
4453021	3.278	3.747	L	2024		0012	CRACKING	10.0	9.5	8.5	8.5	8.5	7.0	6.5	6.5	6.5	6.5	6.5	5.9*	10.0	9.0
C. W. ROBERTS CONTRACTING, (2026)							SPRIDE	8.2	8.0	7.9	7.6	7.4	7.1	7.2	7.1	6.9	7.5	7.3	7.1	7.0	6.7
36050000	1.500	1.900	L	1	7	55	CRACKING	8.5	8.5	7.0	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	
35 301				2	20.3		16200 RIDE	8.5	8.1	8.3	7.9	7.9		7.7	7.8	7.7	7.9	7.9	7.6	6.9	
CR 42( 1.5C)							FC5														
4453021	1.540	1.904	L	2024		0012	CRACKING	10.0	9.5	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	10.0	9.0
C. W. ROBERTS CONTRACTING, (2026)							SPRIDE	7.5	7.6	7.3	7.0	7.2	7.9	7.8	7.9	7.8	7.9	7.9	7.8	8.3	8.1
36050000	0.000	1.500	L	1	1	55	CRACKING	8.5	8.5	7.0	6.5	4.5*		3.5*	3.5*	3.5*			10.0	10.0	
35 301				2	3.8		30500 RIDE	8.5	8.1	8.3	7.9	7.9		7.7	7.8	7.5			8.3	7.9	
SE 177 PL( 0.3L)							FC5														
4112563	0.000	1.404	C	2010		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	8.2	5.0*
D.A.B. CONSTRUCTORS, INC (2012)							SPRIDE	8.3	8.2	8.2	8.2	8.2	7.9	7.8	7.9	7.8	7.9	7.9	7.8	7.9	7.7
4526941	0.000	1.540	C	2029		0226															
36060000	0.000	0.619	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0	8.5	
45 41				2	25.1		22500 RIDE	8.2	7.7	8.0	7.5	7.6	7.4	7.1	7.5	7.4	7.4	7.2	7.3	7.1	
CR-484/PENN AVE( 0.3R)							FC3														
2386571	0.000	0.735	C	1998		0012	CRACKING	8.5	8.5	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	3.0*
D.A.B. CONSTRUCTORS, INC (2000)							S RIDE	7.1	7.0	7.5	7.6	7.5	7.4	7.3	7.4	7.4	7.4	7.4	7.3	7.3	7.0
4485261	0.100	1.410	R	2025		0012															
36060000	0.619	1.532	R	1	1	35	CRACKING	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
45 41				2	8.5		23500 RIDE	8.0	7.8	8.1		7.7	7.5	7.6	7.8	7.8	7.7	7.8	7.8	7.7	
E MCKINNEY AVE( 0.6R)							FC125														
2387401	0.619	1.662	C	2003		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.5	7.1	4.5*
D.A.B. CONSTRUCTORS, INC (2005)							SPRIDE	7.5	7.5	7.3	7.3	7.3	7.1	7.0	7.1	6.9	7.0	6.8	6.9	5.9	5.6
4485261	0.100	1.410	R	2025		0012															
36060000	1.532	4.939	C	1	1	55	CRACKING	7.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0	
45 41				2	8.5		23500 RIDE	8.0	7.8	8.1	8.0	7.9	7.8	7.8	7.7	7.7	7.8	7.7	8.0	7.8	
SW 108 PL( 1.6R)							FC125R														
4195841	1.621	4.939	C	2011		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	7.0	7.0	4.3*	3.5*	1.5*
V. E. WHITEHURST & SONS, I(2012)							RIDE	7.6	7.5	7.3	7.3	7.3	7.2	7.1	7.1	7.1	7.1	6.9	6.9	6.9	6.6
2386481	1.438	5.556	C	2030		0213															
36060000	4.939	11.928	C	1	1	60	CRACKING	9.0	9.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	
45 41				2	13.4		5900 RIDE	8.6	8.6	8.5	8.3	8.2	8.1	8.1	8.2	8.7	8.6	8.5	8.4	8.5	
SW 61 ST( 5.8R)							FC95														
4171791	4.939	11.928	C	2008		0012	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.6	7.1	5.0*
STEVEN COUNTS, INC. (2009)							RIDE	8.4	8.4	8.3	8.2	8.3	8.2	8.1	8.1	8.1	8.2	8.0	8.0	8.0	7.7
36060000	0.619	1.532	L	1	1	35	CRACKING	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
45 41				2	8.5		23500 RIDE	8.0	7.8	8.1		7.5	6.9	7.4	7.8	7.7	7.8	7.9	7.7	7.7	
MAGNOLIA AVE( 0.6L)							FC125														
2387401	0.619	1.662	C	2003		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	7.0	7.0	7.4	7.0	4.5*
D.A.B. CONSTRUCTORS, INC (2005)							SPRIDE	7.7	7.7	7.3	7.3	7.4	7.1	7.3	7.3	7.2	7.1	7.1	7.3	7.2	6.9
4485261	0.175	1.431	L	2025		0012															
36060000	0.000	0.619	L	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	
45 41				2	25.1		22500 RIDE	8.2	8.8	8.6	8.2	8.1	8.2	8.1	7.9	8.0	8.1	7.6	7.6	7.7	
RIVER DR( 0.1L)							FC3														
2386571	0.000	0.735	C	1998		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	7.3	7.1	4.0*
D.A.B. CONSTRUCTORS, INC (2000)							S RIDE	8.1	8.2	7.8	7.8	7.8	7.7	7.7	7.7	7.7	7.7	7.7	7.6	7.6	7.3
4485261	0.175	1.431	L	2025		0012															
36070000	0.000	6.672	R	1	1	65	CRACKING	4.5*	3.5*			10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.0	9.0	
500 27				2	19.9		10700 RIDE	8.3	8.1			8.3	8.2	8.2	8.0	8.2	8.3	8.2	8.1	8.1	
NW 160 AVE( 1.7C)							FC5M														
4373391	0.000	6.672	C	2019		0012	CRACKING	7.0	7.0	6.0*	6.0*	6.0*	4.5*		10.0	10.0	10.0	10.0	8.9	8.1	6.5
V. E. WHITEHURST &amp																					

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																								
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE				
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031			
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM	X-P	*****																	
ITMSEG-P	(AGE_ONE YEAR)	ASTYPE																						
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM	X-F																		
ITMSEG-F																								
36070000	6.672	14.305	R	1	1	65	CRACKING				10.0	10.0	10.0	10.0	10.0	8.5	7.0	6.5	6.5	6.5				
500 27				2	19.9	10700	RIDE				8.2	8.2	8.1	8.1	8.1	7.9	7.8	7.7	7.4	7.2				
CR 326( 6.8C)						FC5M																		
4290531	6.683	14.305	C	2015	0012	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.3	8.3	5.5*			
ANDERSON COLUMBIA CO., INC(2016)						RIDE	7.1	6.8	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.5	8.4	8.4	8.4	8.2			
36070000	14.305	17.912	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	7.5				
500 27				2	25.2	21000	RIDE	8.6	8.7	8.5	8.1	8.1	8.0	8.1	7.9	8.0	8.0	7.9	7.8	7.8				
CR 225A(14.5C)						FC5M																		
4290831	14.305	17.912	C	2015	0012	CRACKING	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.9	8.2	6.0*			
ANDERSON COLUMBIA CO., INC(2017)						RIDE	7.7	7.6		8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.3	8.3	8.4	8.2			
36070000	17.912	20.700	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.0	7.0	7.0	7.0				
500 27				2	17.1	22000	RIDE	8.7	8.7	8.5	8.3	8.2	8.1	8.1	8.4	8.1	8.1	8.0	7.8	7.8				
NW 35 AVE RD(18.2C)						FC125M																		
4290831	17.912	20.700	C	2015	0012	CRACKING	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.5	6.0*			
ANDERSON COLUMBIA CO., INC(2017)						RIDE	7.6	7.6		8.0	8.0	7.8	7.8	7.9	7.8	7.8	7.8	7.8	7.8	7.8	7.5			
36070000	17.912	20.700	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	7.5	7.0	7.0	7.0				
500 27				2	17.1	22000	RIDE	8.4	8.5	8.3	7.9	8.0	7.8	7.9	8.3	7.7	7.9	7.8	7.8	7.6				
FROM NW 35 AVE RD(18.1L)						FC125M																		
4290831	17.912	20.700	C	2015	0012	CRACKING	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.9	7.5	6.0*			
ANDERSON COLUMBIA CO., INC(2017)						RIDE	7.5	7.5		8.0	7.9	7.6	7.8	7.9	7.8	7.8	7.8	7.8	7.8	7.8	7.5			
36070000	14.305	17.912	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0				
500 27				2	25.2	21000	RIDE	8.8	8.7	8.6	8.3	8.2	8.2	8.2	8.3	8.1	8.1	8.0	7.9	7.8				
CR 225A(14.5C)						FC5M																		
4290831	14.305	17.912	C	2015	0012	CRACKING	7.0	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.3	8.3	6.0*			
ANDERSON COLUMBIA CO., INC(2017)						RIDE	7.3	7.5		8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.2	8.2	8.3	8.1			
36070000	6.672	14.305	L	1	1	65	CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	8.5	7.5	7.5	7.5				
500 27				2	19.9	10700	RIDE				8.3	8.2	8.1	8.2	8.1	8.1	8.1	8.0	7.8	7.8				
NW 131 CT( 6.7L)						FC5M																		
4290531	6.683	14.305	C	2015	0012	CRACKING	6.5	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.9	8.3	5.5*			
ANDERSON COLUMBIA CO., INC(2016)						RIDE	7.3	7.4	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.2	8.2	8.2	8.2	8.2	8.0			
36070000	0.000	6.672	L	1	1	65	CRACKING	4.5*	3.5*		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	8.0				
500 27				2	19.9	10700	RIDE	8.3	8.1		8.3	8.2	8.2	8.2	8.2	8.1	8.1	8.1	8.0	8.0				
COUNTY ROAD 316( 0.1L)						FC5M																		
4373391	0.000	6.672	C	2019	0012	CRACKING	7.0	6.5	6.0*	6.0*	6.0*	5.0*		10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.0			
V. E. WHITEHURST & SONS, I(2021)						RIDE	7.8	7.5	7.9	7.9	7.7	7.8		8.9	8.7	8.6	8.4	8.4	8.4	8.5	8.3			
36080000	0.000	6.494	R	1	1	45	CRACKING	7.0	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0				
40				2	6.8	21825	RIDE	7.3	7.2	6.9	6.2*	5.9*		7.7	7.7	7.8	7.8	7.7	7.7	7.7				
OCALA CITY LIMITS( 0.0C)						FC125																		
4135701	0.000	6.499	C	2005	0012	CRACKING	10.0	10.0	8.5	8.5	8.5	8.0	8.0	7.0	7.0	7.0	7.0	6.9	6.6	4.0*				
STEVEN COUNTS, INC. (2007)						SPRIDE	7.7	7.7	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.3	7.4	7.3	7.3	7.4	7.1			
4509511	2.356	6.494@	C	2026	0226																			
36080000	6.494	9.640	C	1	1	55	CRACKING	10.0	9.0	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	9.0	9.0	9.0				
40				2	11.3	18700	RIDE	8.6	8.5	8.3	7.6	7.6	7.3	7.2	6.8	6.2*	8.5	8.4	8.3	8.2				
SR 326( 7.2L)						FC95																		
4171601	6.494	9.617	C	2007	0012	CRACKING	9.0	9.0	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.0	6.8	4.5*			
ANDERSON COLUMBIA CO., INC(2010)						SPRIDE	8.2	8.2	7.9	7.9	7.8	7.7	7.7	7.7	7.7	7.7	7.8	7.7	7.7	7.7	7.4			
4106742	6.146	11.473	C	2030	0213																			
36080000	10.157	12.615	C	1	1	55	CRACKING	9.0	9.0	6.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0				
40				2	6.7	14000	RIDE	8.0	8.2	7.9		8.2	8.2	8.2	8.4	8.4	8.4	8.4	8.3	8.3				
COLBY WOODS CAMPGROUNDS(10.4L)						FC125																		
4116601	10.157	14.112	C	2003	0012	CRACKING	9.0	9.0	8.5	8.5	8.5	7.5	7.5	7.0	6.0*	6.0*	6.0*	5.7*	5.4*	2.5*				
ANDERSON COLUMBIA CO., INC(2005)						SPRIDE	8.3	8.2	8.1	8.1	8.1	8.0	8.0	8.0	8.0	7.9	7.9	7.9	7.9	7.9	7.6			
4509481	10.148	20.643	C	2026	0012																			
36080000	12.615	13.360	C	1	1	55	CRACKING	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0				
40				3	6.7	14000	RIDE	7.3	7.6	6.3*		8.3	8.1	8.2	8.3	8.2	8.4	8.3	8.1	8.2				
NE 130 TER(13.3R)						FC4																		
4116601	10.157	14.112	C	2003	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.0	7.0	7.0	6.6	7.0	4.5*			
ANDERSON COLUMBIA CO., INC(2005)						SPRIDE	8.2	8.1	8.0	8.0	8.0	7.8	7.8	7.9	7.8	7.9	7.8	7.7	7.7	7.7	7.4			
4509481	10.148	20.643	C	2026	0012																			

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR		2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE	
SR US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	*****	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-X-P	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)
ITMSEG-P																					
ITMSEG-F																					
36080000	13.360	14.260	C	1	1	50	CRACKING	4.5*	4.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
40				2	6.7	14000	RIDE	7.8	7.5	6.4*		8.3	8.2	8.3	8.3	8.2	8.3	8.2	8.2	8.1	
NE 134 TER(13.7R)																					
4116601	10.157	14.112	C	2003		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.0	6.0*	6.0*	6.0*	6.1*	3.5*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.1	8.2	7.9	7.8	7.8	7.7	7.7	7.8	7.7	7.7	7.7	7.6	7.6	7.3
4509481	10.148	20.643	C	2026		0012															
36080000	14.260	15.470	C	1	1	50	CRACKING	10.0	10.0	10.0		10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	7.5	7.5
40				2	6.7	14000	RIDE	8.3	8.5	8.6		8.3	8.2	8.3	8.1	8.3	8.4	8.4	8.3	8.2	8.2
NE 14 ST RD(14.5L)																					
4344081	14.260	15.120	C	2018		0012	CRACKING	7.5	7.5	7.5	7.0	7.0	10.0	10.0	9.0	7.0	7.0	7.0	7.0	7.3	6.0*
D.A.B. CONSTRUCTORS, INC	(2019)						RIDE	8.2	8.2	8.1	8.2	8.1	8.0	8.0	8.0	7.9	8.0	8.0	8.0	7.9	7.6
4509481	10.148	20.643	C	2026		0012															
36080000	15.470	16.220	C	1	1	55	CRACKING	4.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5
40				3	6.7	14000	RIDE	7.8	7.9	6.9		8.3	8.3	8.4	8.5	8.4	8.4	8.4	8.3	8.3	
FC125																					
4116611	14.923	23.528	C	2003		0012	CRACKING	9.0	9.0	9.0	8.0	8.0	8.0	7.5	7.0	6.0*	6.0*	6.0*	5.8*	5.5*	3.0*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.3	8.3	8.0	8.0	8.0	7.9	7.9	8.0	7.9	7.9	7.9	7.9	7.9	7.6
4509481	10.148	20.643	C	2026		0012															
36080000	16.220	17.440	C	1	1	45	CRACKING	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
40				2	6.8	8200	RIDE	7.5	7.7	6.9		8.1	8.1	8.1	8.2	8.3	8.3	8.2	8.0	8.2	
CR 314A(16.6C)																					
4116611	14.923	23.528	C	2003		0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	6.0*	5.7*	5.4*	2.5*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.2	8.2	7.6	7.9	7.8	7.6	7.7	7.8	7.7	7.7	7.5	7.5	7.3	7.0
4509481	10.148	20.643	C	2026		0012															
36080000	17.440	21.237	C	1	1	55	CRACKING	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0
40				2	7.1	5600	RIDE	9.0	9.0	8.5		8.3	8.2	8.3	8.2	8.4	8.4	8.3	8.2	8.3	
SE 167 CT RD(17.7L)																					
4116611	14.923	23.528	C	2003		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	8.5	7.0	6.0*	6.0*	6.0*	6.0*	5.6*	3.0*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.2	8.2	8.0	8.0	8.0	7.9	7.9	7.9	7.8	7.8	7.8	7.7	7.7	7.4
4509481	10.148	20.643	C	2026		0012															
36080000	21.237	22.297	C	1	1	55	CRACKING	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
40				3	7.1	5600	RIDE	8.5	8.2	7.5		8.4	8.3	8.3	8.4	8.4	8.4	8.5	8.4	8.3	
FC4																					
4116611	14.923	23.528	C	2003		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	6.0*	6.0*	4.9*	4.4*	1.5*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.2	8.2	8.1	8.1	8.0	7.8	7.9	7.9	7.8	7.9	7.8	7.8	7.7	7.4
4509482	20.643	32.206	C	2028		0226															
36080000	22.297	22.563	C	1	1	55	CRACKING	7.0	7.0	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
40				2	7.1	5600	RIDE	9.1	9.0	9.0		8.3	8.3	8.3	8.4	8.4	8.4	8.4	7.8	8.3	
FC4																					
4116611	14.923	23.528	C	2003		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	6.0*	6.0*	6.0*	6.0*	6.4*	3.5*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.3	8.2	8.1	8.1	8.2	8.1	8.0	8.0	7.9	8.0	7.9	7.9	7.5	7.2
4509482	20.643	32.206	C	2028		0226															
36080000	22.563	23.528	C	1	1	55	CRACKING	7.0	6.0*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
40				3	7.1	5600	RIDE	7.7	6.8	5.7*		8.5	8.4	8.5	8.5	8.5	8.6	8.6	8.5	8.3	
FOREST ROAD #97(23.4C)																					
4116611	14.923	23.528	C	2003		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	6.0*	6.0*	6.0*	6.1*	3.5*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.4	8.3	8.2	8.2	8.3	8.2	8.2	8.3	8.2	8.2	8.2	8.1	8.2	7.9
4509482	20.643	32.206	C	2028		0226															
36080000	23.528	26.540	C	1	1	55	CRACKING	7.0	7.0	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
40				2	7.1	5600	RIDE	8.4	7.9	7.0		8.4	8.4	8.5	8.5	8.5	8.5	8.5	8.5	8.4	
FOREST ROAD #11(24.2L)																					
4116621	23.528	32.206	C	2003		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	7.0	6.0*	6.0*	6.0*	5.9*	3.0*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.4	8.4	8.2	8.2	8.2	8.1	8.1	8.2	8.1	8.1	8.0	8.0	7.9	7.6
4509482	20.643	32.206	C	2028		0226															
36080000	26.540	27.540	C	1	1	55	CRACKING	7.0	7.0	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
40				3	7.1	5600	RIDE	8.9	8.6	7.9		8.5	8.5	8.5	8.6	8.6	8.6	8.6	8.5	8.5	
FOREST RD #33(26.7L)																					
4116621	23.528	32.206	C	2003		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	6.0*	6.0*	5.8*	5.3*	2.5*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.4	8.4	8.3	8.3	8.3	8.1	8.1	8.2	8.0	8.1	8.0	8.0	7.9	7.6
4509482	20.643	32.206	C	2028		0226															
36080000	27.540	28.623	C	1	1	55	CRACKING	7.0	7.0	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
40				2	7.1	5600	RIDE	8.6	7.9	7.8		8.4	8.4	8.4	8.5	8.5	8.5	8.4	8.3	8.4	
JUNIPER SPRINGS(27.6L)																					
4116621	23.528	32.206	C	2003		0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.0	6.0*	6.0*	6.0*	4.8*	4.5*	2.0*
ANDERSON	COLUMBIA CO., INC	(2005)					SPRIDE	8.3	8.3	8.2	8.2	8.1	8.0	8.0	8.1	7.9	7.8	7.8	7.7	7.7	7.4
4509482	20.643	32.206	C	2028		0226															

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR											FUTURE			
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	WKM-F	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F	WKM-F	*****														(PMRS)	
36080000	28.623	29.627	C	1	1	55	CRACKING	7.0	7.0	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
40				3	7.1		5600 RIDE	7.9	7.6	6.4*		8.5	8.3	8.4	8.4	8.4	8.4	8.4	8.4	8.3	8.1	
4116621	23.528	32.206	C	2003		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	6.0*	6.0*	6.0*	4.7*	4.3*	1.5*	
ANDERSON COLUMBIA CO., INC (2005)							SPRIDE	8.2	8.0	7.9	8.1	8.0	7.7	7.9	7.9	7.8	7.8	7.7	7.7	7.6	7.3	
4509482	20.643	32.206	C	2028		0226																
36080000	29.627	32.206	C	1	1	55	CRACKING	6.5	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
40				2	7.1		5600 RIDE	8.4	8.0	7.7		8.3	8.3	8.3	8.2	8.2	8.2	8.2	8.2	8.1	8.0	
SR 19(32.1C)							FC4															
4116621	23.528	32.206	C	2003		0012	CRACKING	10.0	9.0	9.0	8.5	8.5	8.0	8.0	6.5	6.0*	6.0*	6.0*	5.3*	4.9*	2.0*	
ANDERSON COLUMBIA CO., INC (2005)							SPRIDE	8.0	7.9	7.7	7.7	7.6	7.6	7.6	7.6	7.4	7.5	7.4	7.4	7.4	7.1	
4509482	20.643	32.206	C	2028		0226																
36080000	0.000	6.494	L	1	1	45	CRACKING	6.5	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	
40				2	6.8		21825 RIDE	7.8	7.5	7.2	6.7	6.6		7.8	8.1	8.1	8.0	7.9	7.9	7.9	7.9	
OCALA CITY LIMITS( 0.0C)							FC125															
4135701	0.000	6.499	C	2005		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.0	8.0	7.0	7.0	7.0	7.0	7.0	6.8	6.5	4.0*
STEVEN COUNTS, INC. (2007)							SPRIDE	7.9	7.9	7.7	7.6	7.5	7.3	7.5	7.6	7.5	7.4	7.5	7.4	7.4	7.1	
4509511	2.356	6.494@	C	2026		0226																
36090000	0.000	3.057	C	1	1	55	CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	
19				2	15.5		2050 RIDE	8.1		8.6	8.2	8.3	8.2	8.3	8.2	8.0	7.9	7.8	7.5	7.4		
SR 40( 0.2C)							FC125															
2387701	0.000	15.808	C	2001		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.3	8.1	5.5*	
THE MIDDLESEX CORPORATION (2003)							SPRIDE	7.3	7.2	7.4	7.4	7.3	7.1	7.3	7.3	7.2	7.2	7.2	7.2	7.2	6.9	
36090000	3.868	15.780	C	1	1	55	CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	
40				2	22.7		2200 RIDE	8.1		8.6	8.2	8.3	8.2	8.3	8.2	8.0	7.9	7.8	7.6	7.5		
THE YEARLING TR( 6.1L)							FC125															
2387701	0.000	15.808	C	2001		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	8.5	8.4	5.5*
THE MIDDLESEX CORPORATION (2003)							SPRIDE	7.4	7.3	7.4	7.4	7.4	7.3	7.3	7.4	7.3	7.2	7.3	7.3	7.2	6.9	
36090000	15.780	17.448	C	1	1	55	CRACKING	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	
19				2	9.4		4900 RIDE	8.1	7.6	7.7	7.3	7.1	6.9	6.9	7.1	8.4	8.3	8.3	8.2	8.2		
NE 133 PL(15.8L)							FC125M															
4195831	15.780	17.448	C	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.7	7.3	5.0*	
P & S PAVING, INC. (2009)							RIDE	8.2	8.1	7.6	7.6	7.6	7.4	7.5	7.5	7.4	7.4	7.4	7.4	7.4	7.1	
36090100	0.000	0.811	C	1	1	55	CRACKING										10.0	10.0	10.0			
19				2	15.5		2050 RIDE										8.1	8.2	8.0			
3331 FT S/BR 360067( 0.0C)							FC125															
(2011)							CRACKING RIDE	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.3	6.8	4.5*	
								7.8	7.6	7.4	7.5	7.4	7.1	7.0	7.1	7.0	6.9	6.9	6.7	6.8	6.6	
36100000	0.000	3.113	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.0	6.5	6.5			
200				2	10.7		18100 RIDE	8.9	8.9	8.7	8.2	8.1	8.0	8.0	8.1	7.6	7.7	7.4	7.1			
SW 137 CT( 0.2R)							FC125M															
4286871	0.000	5.815	C	2013		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.0	7.0	7.0	7.0	5.0*	
C. W. ROBERTS CONTRACTING, (2014)							RIDE	8.8	8.7	8.6	8.6	8.6	8.5	8.5	8.6	8.5	8.5	8.5	8.5	8.5	8.2	
36100000	3.113	3.672	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	6.5	7.5	7.0	6.5	6.5			
200				2	10.7		18100 RIDE	8.9	8.9	8.7	8.2	8.1	8.0	8.0	7.2	7.6	7.7	7.4	7.1			
SW 136 PL( 3.2R)							FC125M															
4286871	0.000	5.815	C	2013		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.0	7.0	7.0	7.3	5.5*	
C. W. ROBERTS CONTRACTING, (2014)							RIDE	8.8	8.7	8.6	8.6	8.6	8.5	8.5	8.6	8.5	8.5	8.5	8.5	8.1	7.8	
36100000	3.672	5.795	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.0	6.5	6.5			
200				2	10.7		18100 RIDE	8.9	8.9	8.7	8.2	8.1	8.0	8.0	7.7	7.6	7.7	7.4	7.1			
ROSS PRAIRIE TR( 4.4R)							FC125M															
4286871	0.000	5.815	C	2013		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.0	7.0	7.0	7.1	5.0*	
C. W. ROBERTS CONTRACTING, (2014)							RIDE	8.8	8.7	8.6	8.6	8.6	8.5	8.5	8.6	8.5	8.5	8.5	8.5	8.6	8.3	
36100000	5.795	11.983	R	1	1	50	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0		
200				3	12.6		38000 RIDE			8.7	8.3	8.4	8.2	8.2	8.3	8.2	8.1	7.6	7.9	7.8		
CR 484( 6.0C)							FC5M															
4368791	5.981	11.983	C	2019		0012	CRACKING	8.0	7.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	9.6	9.4	7.5	
ANDERSON COLUMBIA CO., INC (2021)							RIDE	7.5	7.4	7.8	7.7	7.6	7.6		8.7	8.6	8.7	8.6	8.6	8.6	8.4	

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @# INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	*****														(PMRS)
ITMSEG-P																					
ITMSEG-F																					
36100000	11.983	14.635	R	1	1	50	CRACKING	10.0	10.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0
200				3	3.6	44005	RIDE	8.6	8.6	8.2		8.0	7.9	8.0	8.0	8.0	7.9	7.9	7.7	7.7	
SW 66 ST(12.2R)																					
4373441	11.983	14.750	C	2018		0012	CRACKING	8.0	6.5	4.5*	4.5*	4.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	8.0
D.A.B. CONSTRUCTORS, INC (2021)																					
36100000	14.635	15.040	R	1	1	45	CRACKING	10.0	10.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0
200				3	3.6	44005	RIDE	8.6	8.6	8.2		8.0	7.9	8.0	8.0	8.0	7.9	7.9	7.7	7.7	
SW 38 CT(14.7C)																					
							CRACKING	8.0	6.5	4.5*	4.5*	4.5*	3.5*		10.0	10.0	10.0	10.0	9.0	9.5	8.0
							RIDE	7.3	7.1	7.6	7.5	7.3	7.3		7.3	7.4	7.3	7.4	7.3	7.4	7.1
(2022)																					
36100000	15.040	17.870	R	1	8	45	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	8.0	
200				3	5.9	35500	RIDE	7.6	7.6	7.5	7.0	6.9	6.3	7.1	7.6	7.5	7.5	7.4	7.3	7.2	
SW 36 AVE(15.1R)																					
4135831	15.074	18.427	C	2005		0012	CRACKING	8.0	7.5	7.0	7.0	7.0	6.5	6.5	6.5	6.0*	6.0*	6.0*	4.6*		
ANDERSON COLUMBIA CO., INC(2007)																					
36100000	17.870	18.405	R	1	8	45	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.5	9.5	9.0	9.0	
200				2	15.6	28000	RIDE	7.6	7.6	7.5	7.0	6.9	6.3	7.1	6.6	7.8	7.8	7.8	7.4	7.5	
SW 7 RD(18.0R)																					
4135831	15.074	18.427	C	2005		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	6.5	6.5	5.4*	
ANDERSON COLUMBIA CO., INC(2007)																					
36100000	17.870	18.405	R	1	8	45	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.5	9.5	9.0	9.0	
200				2	15.6	28000	RIDE	7.6	7.6	7.5	7.0	6.9	6.3	7.1	6.6	7.8	7.8	7.8	7.4	7.5	
SW 7 RD(18.0R)																					
4135831	15.074	18.427	C	2005		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	6.5	6.5	5.4*	
ANDERSON COLUMBIA CO., INC(2007)																					
36100000	17.870	18.405	L	1	8	45	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.0	9.0	8.5	7.5	
200				2	15.6	28000	RIDE	7.7	7.8	7.0	7.0	7.0	6.6	7.6	6.7	6.6	6.8	6.8	6.8	6.8	
SW 10 AVE(18.0L)																					
4135831	15.074	18.427	C	2005		0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	6.5	6.5	4.8*	
ANDERSON COLUMBIA CO., INC(2007)																					
4392341	15.070	18.391	L	2024		0012	RIDE	6.7	6.6	6.8	7.4	7.0	6.8	7.1	6.7	6.6	6.9	6.5	6.3		
36100000	15.060	17.870	L	1	8	45	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.0	9.0	8.5	7.5	
200				3	5.9	35500	RIDE	7.7	7.8	7.0	7.0	7.0	6.6	7.6	7.7	7.7	7.7	7.6	7.6	7.5	
SW 36 TER(15.1L)																					
4135831	15.074	18.427	C	2005		0012	CRACKING	7.5	7.5	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.8*	
ANDERSON COLUMBIA CO., INC(2007)																					
4392341	15.070	18.391	L	2024		0012	RIDE	7.5	7.4	7.2	7.1	7.2	6.9	6.9	6.9	6.9	7.0	6.9	6.8		
36100000	14.635	15.060	L	1	1	45	CRACKING	10.0	10.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	
200				3	3.6	44005	RIDE	8.6	8.6	8.3		8.2	7.8	7.9	7.8	7.8	7.8	7.7	7.6	7.7	
SW 38 CT(14.7C)																					
							CRACKING	7.5	4.5*	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	8.8	8.6	7.0
							RIDE	7.5	7.3	7.6	7.6	7.2	7.3		7.1	7.1	7.1	7.1	7.2	6.8	6.6
(2022)																					
36100000	11.983	14.635	L	1	1	50	CRACKING	10.0	10.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	
200				3	3.6	44005	RIDE	8.6	8.6	8.3		8.2	7.8	7.9	7.8	7.8	7.8	7.7	7.6	7.7	
SW 58 CT(12.2L)																					
4373441	11.983	14.750	C	2018		0012	CRACKING	7.5	4.5*	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	9.0	8.9	7.0
D.A.B. CONSTRUCTORS, INC (2021)																					
							RIDE	7.5	7.3	7.6	7.6	7.2	7.3		8.5	8.4	8.4	8.4	8.3	8.4	8.2
36100000	5.795	11.983	L	1	1	50	CRACKING			10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.5	
200				3	12.6	38000	RIDE			8.7	8.4	8.3	8.2	8.3	8.2	8.1	8.0	8.0	7.8	7.7	
CR 484( 6.0C)																					
4368791	5.981	11.983	C	2019		0012	CRACKING	6.5	6.5	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	9.7	10.0	8.0
ANDERSON COLUMBIA CO., INC(2021)																					
							RIDE	7.6	7.4	7.7	7.6	7.5	7.4		8.8	8.7	8.7	8.6	8.6	8.7	8.5
36110000	6.600	8.053	C	1	1	55	CRACKING	7.5	7.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	
40				2	24.0	8900	RIDE	8.1	7.9	7.9	7.4	7.2	6.8	6.6	6.5		8.1	8.1	8.0	8.0	
SR 45( 6.6C)																					
4171821	6.643	19.588	C	2007		0012	CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.0	7.0	7.0	7.0	6.6	5.4*	3.0*
ANDERSON COLUMBIA CO., INC(2010)																					
4526361	6.632	15.750	C	2027		0012	SPRIDE	7.8	7.9	7.8	7.7	7.7	7.5	7.5	7.6	7.5	7.5	7.4	7.4	6.8	6.5
36110000	8.053	8.649	R	1	1	55	CRACKING	7.5	7.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	
40				2	24.0	8900	RIDE	8.1	7.9	7.9	7.4	7.2	6.8	6.6	6.5		8.1	8.1	8.0	8.0	
SW 185 AVE RD( 8.1R)																					
4171821	6.643	19.588	C	2007		0012	CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.0	7.0	7.0	7.0	6.6	7.3	5.0*
ANDERSON COLUMBIA CO., INC(2010)																					
4526361	6.632	15.750	C	2027		0012	SPRIDE	7.8	7.9	7.8	7.7	7.7	7.5	7.5	7.6	7.5	7.5	7.4	7.4	7.2	6.9

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	#T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	W_YEAR	FY-P	W_KMX-P	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	W_KMX-F																(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	W_KMX-F																
36110000	8.649	15.847	C	1	1	55	CRACKING	7.5	7.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	
40				2	24.0		8900 RIDE	8.1	7.9	7.9	7.4	7.2	6.8	6.6	6.5		8.1	8.1	8.0	8.0	
SW 178 TER( 8.7L)							FC95														
4171821	6.643	19.588	C	2007		0012	CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.0	7.0	7.0	7.0	6.6	5.5*	3.5*
ANDERSON COLUMBIA CO., INC(2010)							SPRIDE	7.8	7.9	7.8	7.7	7.7	7.5	7.5	7.6	7.5	7.5	7.4	7.4	7.5	7.2
4526361	6.632	15.750	C	2027		0012															
36110000	15.847	19.589	R	1	1	55	CRACKING	7.5	7.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	
40				2	7.3		18500 RIDE	8.1	7.9	7.9	7.4	7.2	6.8	6.6	6.5		8.1	8.1	8.0	8.0	
SW 119 AVE(15.9R)							FC5M														
2387191	15.847	19.589	C	2014		0213	CRACKING	10.0	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	8.2	6.0*
D.A.B. CONSTRUCTORS, INC (2017)							SPRIDE	7.8	7.9		8.3	8.3	8.3	8.3	8.3	8.2	8.2	8.2	8.2	8.2	8.0
36110000	19.589	22.747	R	1	1	55	CRACKING	7.5	7.5	6.5	6.5	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	
40				2	3.3		24500 RIDE	8.1	7.9	7.9	7.4	7.2	6.8		8.1	8.1	8.1	8.1	8.1	8.1	
SW 80 AVE(19.9R)							FC5														
2387621	19.588	22.805	C	2006		0213	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	6.5	6.5	6.5	5.0*	4.5*	0.5*
ANDERSON COLUMBIA CO., INC(2008)							SPRIDE	8.0	7.9	8.2	8.1	8.1	8.1	8.1	8.2	8.0	8.1	8.0	8.0	8.0	7.8
4506651	19.572	22.776	C	2028		0226															
36110000	22.747	23.800	R	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	
40				2	15.6		29500 RIDE	8.6	8.5	8.5	8.3	8.2	8.0	8.2	8.4	8.1	8.3	8.3	8.2	8.1	
SW 49 AVE(23.0R)							FC125M														
4306561	22.747	24.138	C	2016		0012	CRACKING	9.0	9.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	5.5*
MASCI GENERAL CONTRACTORS (2017)							RIDE	8.2	7.9	7.9	8.7	8.7	8.6	8.6	8.5	8.5	8.5	8.4	8.4	8.3	8.0
36110000	23.800	26.311	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
40				2	15.1		22500 RIDE	8.3	8.2	8.1	7.5	7.5	7.4	7.7	7.5	7.5	7.5	7.7	7.8	7.7	
HOLIDAY TRAVEL PARK(23.8R)							FC95														
2387571	23.719	26.705	C	1999		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.3	7.0	4.0*
ANDERSON COLUMBIA CO., INC(2001)							SPRIDE	7.6	7.5	7.5	7.5	7.3	7.3	7.4	7.4	7.3	7.3	7.2	7.2	7.2	6.9
36110000	23.800	26.311	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	7.0	7.0	10.0	9.5	9.5	9.5	9.5	9.5	
40				2	15.1		22500 RIDE	8.2	8.1	7.8	7.3	7.3	7.1	7.1	7.3	7.5	7.5	7.5	7.3	7.0	
OAK TREE DR W(24.4L)							FC95														
4137191	23.808	26.705	C	2005		0216	CRACKING	9.5	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	7.7	7.5	5.0*
STEVEN COUNTS, INC. (2008)							SPRIDE	7.4	7.4	7.2	7.1	7.2	7.1	7.1	7.1	6.9	6.9	6.9	6.9	6.9	6.6
36110000	22.747	23.800	L	1	1	50	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	7.0	
40				2	15.6		29500 RIDE	8.6	8.6	8.4	7.8	7.9	7.8	8.3	8.2	8.2	8.0	8.0	7.9	7.8	
NW 49 AVE(23.0L)							FC125M														
4306561	22.747	24.138	C	2016		0012	CRACKING	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.2	8.5	7.0
MASCI GENERAL CONTRACTORS (2017)							RIDE	7.6	7.4	7.7	8.5	8.6	8.5	8.5	8.5	8.4	8.3	8.2	8.3	8.2	7.9
36110000	19.589	22.747	L	1	1	55	CRACKING	7.5	7.5	6.5	6.5	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	
40				2	3.3		24500 RIDE	8.1	7.9	7.9	7.4	7.2	6.8		8.1	8.1	8.1	8.1	8.1	8.1	
NW 82 CT(19.7L)							FC5														
2387621	19.588	22.805	C	2006		0213	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	6.5	6.5	6.5	6.5	6.5	2.5*
ANDERSON COLUMBIA CO., INC(2008)							SPRIDE	8.1	8.0	8.1	8.2	8.1	8.1	8.1	8.2	8.1	8.1	8.0	8.0	8.0	7.8
4506651	19.572	22.776	C	2028		0226															
36110000	15.847	19.589	L	1	1	55	CRACKING	7.5	7.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	
40				2	7.3		18500 RIDE	8.1	7.9	7.9	7.4	7.2	6.8	6.6	6.5		8.1	8.1	8.0	8.0	
CR 328(16.3L)							FC5M														
2387191	15.847	19.589	C	2014		0213	CRACKING	10.0	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.7	6.5
D.A.B. CONSTRUCTORS, INC (2017)							SPRIDE	7.8	7.9		8.3	8.3	8.4	8.3	8.4	8.3	8.3	8.3	8.3	8.3	8.1
36110500	0.000	0.358	R	1	1	30	CRACKING								3.5*	10.0	10.0	10.0	10.0	10.0	
40				2	3.8		22200 RIDE								5.0*	5.7	5.4*	6.1			
SW BROADWAY( 0.0R)							FC95														
(2009)							CRACKING RIDE	10.0	9.0	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.5	5.7*	3.5*
																					5.7
36110500	0.000	0.358	L	1	1	30	CRACKING								3.5*	10.0	10.0	10.0	10.0	10.0	
40				2	3.8		22200 RIDE								5.0*	7.7	7.7	7.6			
BROADWAY AVE W( 0.0C)							FC95														
(2009)							CRACKING RIDE	9.0	9.0	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.5	7.5	6.5	5.3*	3.0*
																					5.9

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	*T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013		
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM	P	ASTYPE	=====														2031
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM	F		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	(PMRS)	
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	WKM	F																
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F																
36180000	12.560	14.003	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	10.0	10.0	10.0	10.0	10.0		
326				2	6.8	26500	RIDE	8.3	8.0	8.1	7.8	7.5	7.5	7.5	7.7	8.1	8.0	8.1	8.0	7.9		
NW 42ND AVE RD(13.2R)																						
4170051	12.827	14.003	C	2007		0216	CRACKING	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.5	4.0*	
ANDERSON	COLUMBIA CO., INC	(2009)					RIDE	8.0	7.9	7.5	7.4	7.5	7.3	7.5	7.3	7.3	7.3	7.3	7.4	7.4	7.1	
4542161	12.560	14.003	C	2029		0012																
-----																						
36180000	12.560	14.003	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	10.0	10.0	10.0	10.0	10.0	8.5	
326				2	6.8	26500	RIDE	7.7	8.0	7.7	7.4	7.3	7.3	7.0	7.2	7.9	7.8	7.8	7.5	7.6		
NW 47 AVE(12.7L)																						
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	4.5*	
							RIDE	8.1	8.1	7.7	7.8	7.4	7.4	7.7	7.6	7.4	7.4	7.4	7.1	7.1	6.8	
4542161	12.560	14.003	C	2029		0012																
-----																						
36180001	0.000	1.674	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	6.5	6.0*	10.0	10.0	10.0		
326				2	12.2	11900	RIDE	8.7	8.6	8.6	8.2	7.9	8.1	8.0	8.1	7.9	7.7	7.9	8.0	8.0		
36180 MEDIAN GORE( 0.0C)																						
4233481	0.000	1.674	C	2010		0226	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.3	7.0	3.5*	
ANDERSON	COLUMBIA CO., INC	(2011)					RIDE	8.1	8.0	8.4	8.4	8.4	8.4	8.5	8.5	8.4	8.5	8.5	8.5	8.5	8.3	
-----																						
36180001	0.000	1.674	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	6.0*	6.0*	10.0	10.0	10.0		
326				2	12.2	11900	RIDE	8.4	8.5	8.4	7.9	7.8	7.7	7.6	7.4	7.1	6.8	7.8	7.9	7.8		
36180 MEDIAN GORE( 0.0C)																						
4233481	0.000	1.674	C	2010		0226	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.0	7.0	3.5*	
ANDERSON	COLUMBIA CO., INC	(2011)					RIDE	7.9	7.8	8.3	8.2	8.2	8.2	8.3	8.3	8.2	8.3	8.2	8.1	8.2	8.0	
-----																						
36210000	0.000	13.905	R	4	1	70	CRACKING	9.0	9.0	7.5	7.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0		
93	I75	334.4	3	26.4	140500	RIDE	8.9	8.9	8.7	8.1	7.8	7.8	7.6	7.5	8.0	8.3	8.3	8.3	8.2	8.1		
4431701																						
ANDERSON	COLUMBIA CO., INC	(2025)				0012	CRACKING	10.0	10.0	9.0	7.5	7.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*	10.0	10.0	9.0	
							SPRIDE	8.0	7.9	8.4	8.3	8.2	8.4	8.4	8.4	8.4	8.1	8.0	8.7	8.8	8.7	
-----																						
36210000	13.905	18.482	R	4	1	70	CRACKING	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0		
93	I75	348.3	3	26.4	100500	RIDE	9.0	8.7	8.9	8.4	8.1	8.0	7.9	7.8	7.5	8.2	8.2	8.2	8.2	8.2		
4194371																						
ANDERSON	COLUMBIA CO., INC	(2009)				0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	5.5*	4.5*	4.3*	1.5*	
ANDERSON	COLUMBIA CO., INC	(2010)					SPRIDE	8.1	8.1	8.4	8.4	8.4	8.6	8.6	8.6	8.6	8.5	8.4	8.3	8.3	8.2	
4520741	13.991	22.000	C	2025		0548																
-----																						
36210000	18.482	38.282	R	4	1	70	CRACKING	10.0	7.5	4.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5		
93	I75	352.9	3	29.7	71000	RIDE	8.6	8.6	8.0	7.3	6.9	7.9	8.0	7.9	7.9	7.8	7.7	7.5	7.5			
ALACHUA CO LINE(38.3C)																						
4306431	18.482	38.282	C	2015		0012	CRACKING	7.5	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.6	8.3	6.5	
ANDERSON	COLUMBIA CO., INC	(2018)					SPRIDE	7.3	6.8	7.6		8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	
-----																						
36210000	18.482	38.282	L	4	1	70	CRACKING	9.0	7.5	6.5	4.5*	1.0*	10.0	10.0	10.0	9.0	8.0	7.5	7.5	6.5		
93	I75	352.9	3	29.7	71000	RIDE	8.8	8.6	8.2	7.5	7.1	8.0	7.9	7.9	7.9	7.6	7.8	7.6	7.4	7.3		
ALACHUA CO LINE(38.3C)																						
4306431	18.482	38.282	C	2015		0012	CRACKING	6.5	4.5*	4.5*		10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.4	7.2	5.0*	
ANDERSON	COLUMBIA CO., INC	(2018)					SPRIDE	6.8	6.2*	7.3		8.6	8.7	8.6	8.6	8.6	8.6	8.6	8.5	8.5	8.4	
-----																						
36210000	13.905	18.482	L	4	1	70	CRACKING	9.0	9.0	9.0	8.0	7.0	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0		
93	I75	348.3	3	26.4	100500	RIDE	8.6	8.9	8.7	8.2	7.9	7.8	7.6	7.6	7.6	7.6	8.2	8.3	8.2	8.2		
4194371																						
ANDERSON	COLUMBIA CO., INC	(2010)				0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	6.5	4.5*	4.5*	4.5*	1.5*	
ANDERSON	COLUMBIA CO., INC	(2010)					SPRIDE	8.2	8.1	8.5	8.4	8.3	8.5	8.5	8.6	8.5	8.4	8.4	8.1	8.0	7.9	
4520741	13.991	22.000	C	2025		0548																
-----																						
36210000	0.000	13.905	L	4	1	70	CRACKING	9.0	9.0	9.0	7.5	6.5	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0		
93	I75	334.4	3	26.4	140500	RIDE	8.9	8.8	8.5	8.0	7.8	7.6	7.5			8.3	8.3	8.3	8.3	8.1		
4431701																						
ANDERSON	COLUMBIA CO., INC	(2025)				0012	CRACKING	10.0	10.0	9.0	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.0	
							SPRIDE	8.1	7.9	8.3	8.2	8.2	8.4	8.4	8.4	8.3	8.1	7.9	8.6	8.6	8.5	
-----																						
36220000	0.000	8.760	R	1	1	55	CRACKING	9.0	9.0	7.0	6.5	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0		
500	27			2	20.3	19100	RIDE	9.0	8.9	8.6	8.2	8.0	7.8	7.7	7.6	8.2	8.3	8.3	8.2	7.7		
SE 178 PL( 0.2C)																						
4155241	0.000	8.760	C	2007		0012	CRACKING	10.0	10.0	10.0	10.0	9.5	9.0	9.0	7.5	6.5	4.5*	4.5*	4.5*	4.5*	1.0*	
ANDERSON	COLUMBIA CO., INC	(2009)					SPRIDE	8.2	8.2	8.3	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.3	8.3	8.3	8.1	
4506371	0.228	8.430	C	2026		0226																

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 5 COUNTY = MARION -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP   SIDE)		SURFTYPE		=====																		
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-M-P																2031	
CONTRACTOR	(AGE_ONE	YEAR)	ASTYPE																		(PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-M-F																	
36220000	0.000	8.760	L	1	1	55	CRACKING	9.0	9.0	7.0	6.5	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0		
500 27				2	20.3	19100	RIDE	9.0	8.9	8.7	8.3	8.1	7.8	7.6	7.6	8.3	8.3	8.3	8.3	8.3	7.9	
SE 178 PL( 0.2C)																						
4155241	0.000	8.760	C	2007		0012	CRACKING	10.0	10.0	10.0	10.0	9.5	9.0	8.5	6.5	6.5	4.5*	4.5*	4.5*	4.4*	0.5*	
ANDERSON COLUMBIA CO., INC(2009)						SPRIDE		8.3	8.2	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.3	8.2	8.3	8.1	
4506371	0.228	8.430	C	2026		0226																
-----																						
36518000	0.000	0.288	R	1	7	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	10.0	10.0	10.0		
326				2	0.0	12200	RIDE	8.0	8.0	7.4	7.4	7.6	6.8	6.2	6.5	6.5	6.4	7.3	7.1	7.1		
SR 200( 0.0C)																						
4452171	0.024	0.288	R	2023		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	6.5	6.3*	10.0	9.0	
C. W. ROBERTS CONTRACTING,(2026)						SPRIDE		7.1	7.1	7.6	7.7	7.4	7.4	7.5	7.5	7.6	7.9	7.4	7.1	8.2	7.9	
-----																						
36518000	0.288	8.460	C	1	7	55	CRACKING	0.0*	0.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0	8.5		
326				2	6.8	12900	RIDE	6.8	6.2*	8.3	8.3	8.2	8.1	8.1	8.2	8.1	8.1	8.1	8.0	8.0		
NW 8 AVE( 0.5R)						FC125M																
						CRACKING		8.5	8.5	7.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	3.5*		10.0	9.0	
				(2026)		RIDE		7.9	7.9	7.7	7.6	7.6	7.6	7.6	7.6	7.4	7.4	7.4		8.2	7.9	
-----																						
36518000	0.000	0.288	L	1	7	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.5	10.0	10.0	10.0		
326				2	0.0	12200	RIDE	7.8	8.1	7.7	6.6	6.8	6.5	7.4	6.5	7.2	6.8	6.9	7.0	6.7		
SR 200( 0.0C)																						
4452171	0.024	0.288	L	2023		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	6.5	6.5	5.5*	10.0	9.0	
C. W. ROBERTS CONTRACTING,(2026)						SPRIDE		6.8	6.9	7.2	7.3	6.9	6.8	6.7	7.1	7.3	6.7	6.7	6.3	7.8	7.5	

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 "@@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).