

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

### PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = TAYLOR -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	#T	AADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	=====															(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F																	
ITMSEG-P	ITMSEG-F																					
38010000	0.000	7.831	R	1	1	65	CRACKING	8.5	8.5	7.0	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
55 19				2	13.0		5700 RIDE	8.9	8.4	8.9	8.4	8.4		8.6	8.3	8.5	8.4	8.3	8.2	8.1		
SR 51( 0.2C)							FC5M															
4376181	0.000	7.831	C	2019		0012	CRACKING	10.0	9.0	9.0	7.5	7.5	4.5*		10.0	10.0	10.0	10.0	9.6	9.7	7.5	
ANDERSON COLUMBIA CO., INC(2021)							SPRIDE	8.1	7.9	8.1	7.9	8.0	8.0		8.9	8.9	8.9	8.7	8.7	8.6	8.4	
38010000	7.831	24.844	R	1	1	65	CRACKING	6.5	4.5*	4.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	
55 19				2	13.0		5700 RIDE	8.7	8.6	8.5	7.8	7.8	7.6		8.3	8.4	8.4	8.3	8.3	8.2		
JOSH MCCALL( 8.8R)							FC5HP															
4410591	7.831	24.844	R	2021		0012	CRACKING	10.0	10.0	9.0	7.5	7.5	4.5*	4.5*	4.5*		10.0	10.0	9.7	10.0	8.5	
ANDERSON COLUMBIA CO., INC(2023)							SPRIDE	8.1	7.9	8.1	8.1	8.3	8.2	8.1	8.0		8.9	8.9	8.8	8.8	8.6	
38010000	24.844	27.458	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0		
55 19				2	13.0		9600 RIDE	8.3	8.3	8.4	8.2	8.2	7.8	8.0	8.1	8.1	8.0	7.9	7.8	7.8		
CARLTON CEMETERY RD(24.9R)							FC125M															
4361651	24.832	27.395	C	2018		0012	CRACKING	6.0*	6.0*	6.0*	6.0*	6.0*	5.5*	10.0	10.0	10.0	10.0	10.0	9.0	9.5	8.0	
CAPITAL ASPHALT INC				(2020)			SPRIDE	7.7	7.7	7.7	7.7	7.9	7.7	8.5	8.5	8.4	8.4	8.4	8.3	8.2	7.8	
38010000	24.844	27.458	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*		
55 19				2	13.0		9600 RIDE	8.3	8.5	8.4	8.1	8.0	7.8	7.9	8.1	8.2	8.0	8.0	7.9	7.8		
UNSIGN(24.9L)							FC125M															
4361651	24.832	27.395	C	2018		0012	CRACKING	6.0*	6.0*	6.0*	6.0*	6.0*	5.5*	10.0	10.0	10.0	10.0	10.0	8.7	9.5	8.0	
CAPITAL ASPHALT INC				(2020)			SPRIDE	7.8	7.7	7.8	7.7	7.9	7.7	8.5	8.4	8.4	8.4	8.3	8.2	8.2	7.8	
38010000	7.831	24.844	L	1	1	65	CRACKING	6.5	6.5	4.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0		
55 19				2	13.0		5700 RIDE	8.7	8.9	8.8	8.3	8.2	8.0		8.3	8.4	8.4	8.4	8.3	8.3		
FISH CREEK RD( 9.4L)							FC5HP															
4410591	7.831	24.844	L	2021		0012	CRACKING	10.0	9.0	9.0	8.0	8.0	7.5	6.5	4.5*	10.0	10.0	10.0	9.8	8.9	7.0	
ANDERSON COLUMBIA CO., INC(2022)							SPRIDE	8.2	8.1	8.4	8.4	8.6	8.5	8.5	8.4	9.0	8.9	8.9	8.9	8.9	8.7	
38010000	0.000	7.831	L	1	1	65	CRACKING	8.5	8.5	7.0	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0		
55 19				2	13.0		5700 RIDE	8.8	8.5	8.8	8.3	8.2		8.6	8.2	8.6	8.6	8.5	8.5	8.4		
SR 51( 0.2C)							FC5M															
4376181	0.000	7.831	C	2019		0012	CRACKING	10.0	10.0	9.0	9.0	9.0	7.5		10.0	10.0	10.0	10.0	9.7	9.5	7.5	
ANDERSON COLUMBIA CO., INC(2021)							SPRIDE	8.4	8.3	8.4	8.4	8.4	8.3		8.8	8.8	8.8	8.7	8.7	8.7	8.5	
38020000	0.000	1.784	R	1	1	40	CRACKING	7.5	7.5	5.5*	5.5*	3.0*	3.0*	3.0*	10.0	10.0	10.0	10.0	10.0	10.0		
30 19				2	10.2		11500 RIDE	8.0	8.0	7.7	7.0	7.2	6.5	6.5	8.4	8.3	8.3	8.0	8.0	7.9		
US-221/SR-55/JEFFER( 0.0R)							FC125M															
2108782	0.000	1.784	C	2007		0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	8.5	7.0	7.0	7.0	6.0*	4.9*	4.4*	1.0*	
ANDERSON COLUMBIA CO., INC(2008)							SPRIDE	7.9	7.9	7.9	7.8	7.9	7.8	7.7	7.7	7.6	7.6	7.6	7.5	7.5	7.1	
2108784	0.000	1.784	C	2028		0012																
38020000	1.784	2.005	R	1	1	45	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0		
20 19				2	10.2		11300 RIDE	8.9	8.8	8.8	8.4	8.3	8.1	8.1	7.9	7.7	7.5	8.5	8.5	8.5		
CR 356( 2.0C)							FC125M															
2108783	1.784	17.387	R	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.1	6.5	3.5*	
ANDERSON COLUMBIA CO., INC(2011)							SPRIDE	8.5	8.5	8.7	8.7	8.8	8.7	8.7	8.7	8.7	8.7	8.6	8.6	7.6	7.2	
38020000	2.005	17.387	R	1	2	65	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0		
20 19				2	10.2		5800 RIDE	8.9	8.8	8.8	8.4	8.3	8.1	8.1	7.9	7.7	7.5	8.5	8.5	8.5		
ASH RD W( 2.3C)							FC5M															
2108783	1.784	17.387	R	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.1	7.0	2.0*	
ANDERSON COLUMBIA CO., INC(2011)							SPRIDE	8.5	8.5	8.7	8.7	8.8	8.7	8.7	8.7	8.7	8.7	8.6	8.6	8.6	8.4	
38020000	4.657	17.387	L	1	1	65	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	3.5*	6.0*	6.0*	6.0*	10.0	10.0	10.0		
20 19				2	10.2		5800 RIDE	8.8	8.8	8.8	8.3	8.3	8.0	7.9	8.3	8.2	7.9	8.6	8.6	8.5		
PISGAH CHURCH RD( 5.3L)							FC5M															
2108783	1.784	17.387	L	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.0	6.9	2.0*	
ANDERSON COLUMBIA CO., INC(2011)							SPRIDE	8.6	8.5	8.8	8.8	8.9	8.9	8.8	8.9	8.8	8.8	8.8	8.7	8.7	8.5	
38020000	2.855	4.657	L	1	8	55	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0		
20 19				2	10.2		8600 RIDE	8.8	8.8	8.8	8.3	8.3	8.0	7.9	7.3	7.1	7.0	8.6	8.6	8.5		
ANDREW REAMS RD( 3.1L)							FC5M															
2108783	1.784	17.387	L	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.0	7.0		
ANDERSON COLUMBIA CO., INC(2011)							SPRIDE	8.6	8.5	8.8	8.8	8.9	8.9	8.8	8.9	8.8	8.8	8.8	8.8	8.7		

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

**PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = TAYLOR -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	%T	ADT	RATINGS		2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM-X-P	ASTYPE	=====														
ITMSEG-P (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F			2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)
38020000	2.005	2.855	L	1	1	55	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	
20 19				2	10.2		8600 RIDE	8.8	8.8	8.8	8.3	8.3	8.0	7.9	7.3	7.1	7.0	8.6	8.6	8.5	
ASH RD W( 2.3C)							FC5M														
2108783	1.784	17.387	L	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.0	6.5	1.5*
ANDERSON COLUMBIA CO., INC(2011)							SPRIDE	8.6	8.5	8.8	8.8	8.9	8.9	8.8	8.9	8.8	8.8	8.8	8.7	8.6	8.4
38020000	1.784	2.005	L	1	1	45	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	
20 19				2	10.2		11300 RIDE	8.8	8.8	8.8	8.3	8.3	8.0	7.9	7.3	7.1	7.0	8.6	8.6	8.5	
CR 356( 2.0C)							FC125M														
2108783	1.784	17.387	L	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.0	6.5	3.5*
ANDERSON COLUMBIA CO., INC(2011)							SPRIDE	8.6	8.5	8.8	8.8	8.9	8.9	8.8	8.9	8.8	8.8	8.8	8.7	7.8	7.4
38020000	0.000	1.784	L	1	1	40	CRACKING	7.5	7.5	5.5*	5.0*	3.0*	3.0*	3.0*	10.0	10.0	10.0	10.0	10.0	10.0	
30 19				2	10.2		11500 RIDE	8.3	8.0	7.7	7.0	6.6	6.4	6.1	8.2	8.1	8.1	8.1	7.8	7.8	
CR-361A PUCKETT RD( 0.0L)							FC125M														
2108782	0.000	1.784	C	2007		0012	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.0*	6.0*	6.0*	5.5*	4.4*	3.9*	0.5*
ANDERSON COLUMBIA CO., INC(2008)							SPRIDE	7.8	7.9	7.6	7.7	7.7	7.6	7.6	7.5	7.4	7.4	7.4	7.1	7.3	6.9
2108784	0.000	1.784	C	2028		0012															
38030000	0.000	0.334	C	1	1	30	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	
20 27				2	7.1		5100 RIDE	7.0	7.5	7.3	6.8	6.6	6.3	6.4	6.3	6.4	6.5	5.8	5.6	5.6	
US-19/27A/98/SR-30( 0.0R)							FC125M														
4305491	0.020	0.683	C	2015		0012	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	6.5	4.0*
ROBERTS AND ROBERTS, INC. (2016)							SPRIDE	6.0	6.0	7.6	7.6	7.4	7.1	6.8	7.0	7.0	6.9	6.6	6.5	6.4	6.0
38030000	0.334	0.686	R	1	1	30	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	
20 27				1	7.1		5200 RIDE	7.0	7.5	7.3	6.8	6.6	6.3	6.4	6.3	6.4	6.5	5.8	5.6	5.6	
QUINCY ST S( 0.4C)							FC125M														
4305491	0.020	0.683	C	2015		0012	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	6.5	4.0*
ROBERTS AND ROBERTS, INC. (2016)							SPRIDE	6.0	6.0	7.6	7.6	7.4	7.1	6.8	7.0	7.0	6.9	6.6	6.5	6.3	5.9
38030000	0.686	1.104	R	1	1	40	CRACKING	7.0	7.0	7.0	6.0*	6.0*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
20 27				1	7.1		3700 RIDE	7.6	7.6	7.2	6.8	6.7	6.5	8.5	8.5	8.6	8.6	8.5	8.4	8.4	
MAPLE AVE( 0.7C)							FC125M														
2108652	0.686	6.704	C	2006		0012	CRACKING	8.5	8.5	7.5	7.5	7.5	7.0	7.0	6.5	6.0*	6.0*	4.0*	3.5*	2.3*	0.0*
ANDERSON COLUMBIA CO., INC(2007)							SPRIDE	8.1	8.2	8.1	8.1	8.1	8.0	8.0	8.0	7.7	7.9	7.7	7.7	7.5	7.1
2108656	0.686	3.979	C	2027		0012															
38030000	1.104	3.756	C	1	1	50	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	
20 27				4	7.1		3900 RIDE	8.0	7.9	7.8	7.3	7.2	6.9	8.5	8.5	8.6	8.6	8.5	8.4	8.4	
BISHOP BLVD( 1.4L)							FC125M														
2108652	0.686	6.704	C	2006		0012	CRACKING	8.5	8.5	7.5	7.5	7.5	7.0	7.0	6.5	6.0*	6.0*	4.0*	3.5*	3.1*	0.0*
ANDERSON COLUMBIA CO., INC(2007)							SPRIDE	8.1	8.2	8.1	8.1	8.1	8.0	8.0	8.0	7.7	7.9	7.7	7.7	7.8	7.4
2108656	0.686	3.979	C	2027		0012															
38030000	3.756	4.040	C	1	1	50	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
20 27				4	7.1		2400 RIDE	8.0	7.9	7.8	7.3	7.2	6.9	8.5	8.5	8.6	8.6	8.5	8.4	8.4	
WELDON POPPELL RD( 3.8L)							DGFC														
2108656	0.686	3.979	C	2027		0012	CRACKING RIDE	8.5 8.1	8.5 8.2	7.5 8.1	7.5 8.1	7.5 8.1	7.0 8.0	7.0 8.0	6.5 8.0	6.0* 7.7	6.0* 7.9	4.0* 7.7	3.5* 7.7	3.1* 7.8	0.0* 7.4
38030000	4.040	4.625	C	1	7	50	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
20 27				2	7.1		2400 RIDE	7.6	7.7	7.7	7.1	6.9	6.7	8.2	8.2	8.2	8.1	7.9	7.5	7.6	
CONNEL RD( 4.0L)							FC125M														
2108655	4.036	4.613	C	2024		0012	CRACKING	8.5	8.5	8.5	7.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*	5.5*	3.5*	10.0	9.0
ANDERSON COLUMBIA CO., INC(2026)							SPRIDE	7.7	7.7	7.8	7.7	7.4	7.8	7.7	7.7	7.6	7.7	7.6	7.6	8.5	8.1
38030000	4.625	4.983	R	1	7	50	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	
20 27				1	7.1		3500 RIDE	8.7	8.7	8.6	8.1	7.9	7.8	8.4	8.4	8.4	8.5	8.4	8.2	8.1	
CR 30( 4.7R)							FC125M														
2108655	4.613	4.979	R	2024		0012	CRACKING	9.0	9.0	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	5.5*	3.5*	10.0	9.0
ANDERSON COLUMBIA CO., INC(2026)							SPRIDE	8.0	8.0	8.1	8.1	8.2	8.0	8.0	8.0	8.0	8.1	8.0	8.0	8.3	7.9
38030000	4.983	6.660	C	1	7	60	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	
20 27				2	7.1		3500 RIDE	8.8	8.8	8.8	8.0	7.9	7.7	8.5	8.6	8.5	8.5	8.4	8.2	8.1	
CR 356( 5.5L)							FC125M														
2108655	4.979	6.649	C	2024		0012	CRACKING	9.0	9.0	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	5.5*	3.5*	10.0	9.0
ANDERSON COLUMBIA CO., INC(2026)							SPRIDE	8.0	8.0	8.1	8.1	8.2	8.0	8.0	8.0	8.0	8.1	8.0	8.0	8.6	8.2

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).

# FLORIDA DEPARTMENT OF TRANSPORTATION

## ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = TAYLOR -----																								
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE				
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031			
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM	P	*****																	
ITMSEG-P	(AGE_ONE_YEAR)	ASTYPE																						
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F																		
38030000	6.660	14.697	C	1	1	60	CRACKING	9.0	9.0	7.0	6.5	6.5	6.5	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0			
20 27			2	7.1		3500	RIDE	9.0	8.9	8.9	8.1	7.9	7.5	7.2	7.2	8.8	8.8	8.7	8.6	8.4				
SIDE ROAD( 7.1C)								FC125M																
2108653	6.704	14.697	C	2008	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.0	7.0	7.0	7.0	7.0	6.5	6.5	3.5*			
ANDERSON COLUMBIA CO., INC(2009)						SPRIDE	8.5	8.4	8.4	8.3	8.3	8.1	8.2	8.2	8.1	8.1	8.1	8.1	8.0	8.0	7.6			
2108657	6.704	14.697	C	2029	0012																			
-----																								
38040000	0.000	0.358	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	5.5*	10.0	10.0				
55 221			2	2.1		9700	RIDE	8.1	7.7	7.6	7.1	7.1	7.1	7.4	7.6	7.4	7.1	6.9	8.1	7.3				
CR 361A( 0.0C)						FC3																		
						(2012)	CRACKING	10.0	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	6.0*	5.5*	5.5*	4.9*	4.6*	2.0*			
							RIDE	7.6	7.0	7.0	6.5	6.9	6.6	6.8	7.2	6.5	6.5	6.1	6.5	5.9	5.5			
-----																								
38040000	0.358	0.933	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	5.5*	7.0	5.5*					
55 221			2	2.1		9300	RIDE	8.1	7.7	7.6	7.1	7.1	7.1	7.4	7.6	7.4	7.1	6.9	6.2	6.2				
E JONES ST( 0.4R)								FC125M																
4323101	0.351	0.872	R	2018	0012	CRACKING	5.5*	5.0*	3.5*	3.0*	3.0*	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	6.0*				
PREFERRED MATERIALS, INC. (2019)						SPRIDE	5.7	6.5	6.6	6.4	6.6	8.5	8.0	8.3	8.1	7.8	7.8	7.6	7.7	7.3				
-----																								
38040000	3.210	14.620	C	1	1	60	CRACKING	6.0*	6.0*	5.5*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0				
55 221			2	11.3		3000	RIDE	8.5	8.2	8.0	7.2		8.6	8.5	8.4	8.4	8.4	8.4	8.2	8.1				
CR 359A( 3.4L)						FC125H																		
4410581	3.447	13.387	C	2023	0012	CRACKING	8.5	8.5	7.5	7.0	7.0	6.0*	6.0*	5.5*	5.5*	5.5*		10.0	10.0	9.0				
ANDERSON COLUMBIA CO., INC(2025)						SPRIDE	7.9	7.9	7.9	7.7	7.9	7.7	7.7	7.7	7.6	7.5		8.4	8.3	7.9				
-----																								
38070000	0.346	1.940	C	1	1	30	CRACKING	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5				
51			2	8.7		1100	RIDE	7.2	7.2	7.0	6.4	8.1	7.9	7.8	7.7	7.8	7.6	7.4	7.3	7.2				
FIRST AVE S( 0.3L)								FC95																
4088671	0.000	1.906	C	2004	0012	CRACKING	7.0	7.0	7.0	7.0	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	0.0*			
ANDERSON COLUMBIA CO., INC(2005)						RIDE	7.0	6.9	6.9	6.8	6.8	6.6	6.5	6.4	6.4	6.2	6.2	6.2	6.3	6.0	5.6			
4088672	0.336	1.933	C	2027	0012																			
-----																								
38070000	1.940	11.853	C	1	7	60	CRACKING	7.0	7.0	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	8.5				
51			2	8.7		1100	RIDE	8.1	8.0	8.0	7.1	7.1	6.7	6.8	6.5	8.5	8.4	8.3	7.9	7.8				
1ST AVE S( 2.0R)								FC125M																
4470761	1.933	11.853	C	2023	0012	CRACKING	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	9.0			
						(2026)	RIDE	7.5	7.3	7.6	7.4	7.4	7.3	7.2	7.1	7.0	7.0	7.0	6.9	8.5	8.1			
-----																								
38090000	0.259	11.687	C	1	1	60	CRACKING	10.0	8.5	8.5	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	10.0				
30 98			2	28.6		2329	RIDE	8.8	8.8	8.8	8.4	8.2	8.0	7.9	7.9	7.7	7.5	8.6	8.6	8.5				
AUCILLA LANDING RD( 0.3L)								FC125M																
2108832	0.000	11.861	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	7.0	7.0	7.3	7.0	4.0*				
ANDERSON COLUMBIA CO., INC(2011)						RIDE	8.5	8.5	8.4	8.3	8.3	8.2	8.2	8.1	8.1	8.1	8.0	8.0	8.0	7.6				
2108833	0.000	11.861	C	2029	0012																			
-----																								
38090000	11.687	24.698	C	1	1	60	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0				
30 98			2	2.1		2200	RIDE		8.8	8.8	8.5	8.4	8.3	8.2	8.0	8.2	8.4	8.3	8.1	8.2				
CABBAGE GROVE(12.3L)								FC125M																
4433111	11.825	24.682	C	2022	0012	CRACKING	8.5	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*		10.0	10.0	10.0	9.0				
ANDERSON COLUMBIA CO., INC(2024)						SPRIDE	8.1	8.1	7.9	7.9	7.9	7.8	7.7	7.6	7.6		8.5	8.4	8.3	7.9				
-----																								
38501000	0.000	1.346	C	1	1	45	CRACKING																	
359A 221			2	2.1		1400	RIDE																	
DGFC																								
4410581	0.000	1.346	C	2023	0012	CRACKING							8.5	8.5	8.5	8.5	8.5	10.0	10.0	9.0				
ANDERSON COLUMBIA CO., INC(2025)						SPRIDE							7.6	7.2	7.2	7.2	7.3	8.3	8.3	7.9				

\*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.  
 \*\*\* INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.  
 @\* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.  
 2031 FORECASTED BY PAVEMARS (PMRS).