

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = UNION -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE
SR	US	G_BMP	G_EMP	LN	WT	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F																
39010000	0.000	3.423	C	1	1	60	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	7.0	
100				2	14.1		6100 RIDE	8.1	8.6	8.6	8.4	8.3	8.3	8.5	8.5	8.3	8.3	8.3	8.3	8.3	8.2
SE 206 PL(0.3L)																					
4342951	0.000	3.399	C	2017	0012	CRACKING	7.0	7.0	6.0*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0
V. E. WHITEHURST & SONS, I(2018) SPRIDE																					
39010000	3.423	3.765	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	6.0*	5.5*	5.5*	
100				1	14.1		6100 RIDE	7.6	7.9	6.8	7.2	6.9	6.9	6.9	6.9	7.2	6.8	6.0*	5.5*	5.5*	
RAMP TO SR 121(3.5R)																					
							FC125M														
							CRACKING	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	5.5*
(2016) RIDE																					
							RIDE	6.2	6.4		7.0	7.4	8.0	8.0	7.9	7.9	7.8	7.9	7.9	7.1	6.7
39010000	3.765	4.265	R	1	1	40	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	
100				1	14.1		6100 RIDE	8.0	8.4	8.2	7.8	7.8	7.7	7.9	7.8	7.7	7.7	7.4	7.3	7.3	
EPPERSON ST(4.0R)																					
4234271	3.782	14.012	C	2016	0012	CRACKING	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.7	6.5
ANDERSON COLUMBIA CO., INC(2017) SPRIDE																					
39010000	4.265	4.573	C	1	1	30	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	
100				2	14.1		7000 RIDE	8.0	8.4	8.2	7.8	7.8	7.7	7.9	7.8	7.7	7.7	7.4	7.3	7.3	
NE 1ST AVE/ CHURCH S(4.3R)																					
4234271	3.782	14.012	C	2016	0012	CRACKING	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.5
ANDERSON COLUMBIA CO., INC(2017) SPRIDE																					
39010000	4.573	5.048	R	1	1	30	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	
100				1	14.1		5000 RIDE	8.0	8.4	8.2	7.8	7.8	7.7	7.9	7.8	7.7	7.7	7.4	7.3	7.3	
NW 4TH AVE/DEKLE ST(4.6R)																					
4234271	3.782	14.012	C	2016	0012	CRACKING	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.4	5.5*
ANDERSON COLUMBIA CO., INC(2017) SPRIDE																					
39010000	5.048	5.338	C	1	1	40	CRACKING	3.0*	3.0*	3.0*		10.0	10.0	10.0	10.0	9.5	9.5	7.5	7.5	7.5	
100				2	14.1		5000 RIDE	7.6	7.0	6.5		8.5	8.4	8.6	8.6	8.4	8.4	8.3	8.3	8.1	
NINTH AVE SW(5.1L)																					
4234271	3.782	14.012	C	2016	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.2	6.0*
ANDERSON COLUMBIA CO., INC(2017) SPRIDE																					
39010000	5.338	14.012	C	1	1	60	CRACKING	3.0*	3.0*	3.0*		10.0	10.0	10.0	10.0	9.5	9.5	7.5	7.5	7.5	
100				2	13.0		3800 RIDE	7.6	7.0	6.5		8.5	8.4	8.6	8.6	8.4	8.4	8.3	8.3	8.1	
CR 231(5.6R)																					
4234271	3.782	14.012	C	2016	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	6.5
ANDERSON COLUMBIA CO., INC(2017) SPRIDE																					
39020000	0.029	0.874	C	1	1	35	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	6.0*	6.0*	
121				2	15.5		7000 RIDE	7.4	7.0	6.9	8.2	8.0	8.1	8.3	8.3	8.1	8.1	8.0	7.9	7.8	
SW 33 TRL(0.3R)																					
4323071	0.029	8.600	C	2016	0012	CRACKING	6.0*	6.0*	4.5*	10.0	10.0	10.0	10.0	9.5	9.5	9.0	9.0	9.0	8.3	7.8	5.5*
V. E. WHITEHURST & SONS, I(2017) SPRIDE																					
39020000	0.874	2.300	C	1	1	50	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	6.0*	6.0*	
121				2	15.5		7000 RIDE	7.4	7.0	6.9	8.2	8.0	8.1	8.3	8.3	8.1	8.1	8.0	7.9	7.8	
LITTLE SPRINGS RD(1.1R)																					
4323071	0.029	8.600	C	2016	0012	CRACKING	6.0*	6.0*	4.5*	10.0	10.0	10.0	10.0	9.5	9.5	9.0	9.0	8.3	7.4	5.5*	
V. E. WHITEHURST & SONS, I(2017) SPRIDE																					
39020000	2.300	8.600	C	1	1	60	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	6.0*	6.0*	
121				2	15.5		7000 RIDE	7.4	7.0	6.9	8.2	8.0	8.1	8.3	8.3	8.1	8.1	8.0	7.9	7.8	
SW 50 ST(2.4R)																					
4323071	0.029	8.600	C	2016	0012	CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.4	8.0	6.0*	
V. E. WHITEHURST & SONS, I(2017) SPRIDE																					
39020000	8.600	10.367	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	6.0*	6.0*	6.0*	
121				1	15.5		7700 RIDE	8.2	8.3	8.1	7.8	7.4	7.4	7.4	7.1	7.0	6.8	6.7	6.7	6.7	
SR 231(8.9C)																					
4305581	8.613	10.356	R	2015	0012	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.0	7.0	4.5*
PRPREFERRED MATERIALS, INC. (2016) SPRIDE																					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = UNION -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	=====															
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	WKM-X-F	ASTYPE		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F	ASTYPE																
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F	ASTYPE																
39020000	10.367	23.410	C	1	1	60	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	
121				2	17.4		6600 RIDE		8.8	8.8	8.6	8.6	8.3	8.7	8.7	8.6	8.6	8.5	8.5	8.5		
SB OFF(10.4L)																						
4305581	10.356	16.560	C	2015		0012	CRACKING	8.5	8.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.0	7.5	5.0*	
PREFERRED MATERIALS, INC. (2016) SPRIDE																						
39040000	0.000	2.605	C	1	1	45	CRACKING	6.0*	5.5*	5.5*	5.5*	3.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	9.0		
16				2	9.7		2900 RIDE	8.0	8.0	7.4	6.6	6.1*	5.9	6.0	8.4	8.2	8.1	8.2	8.0	8.0		
S.R. 121(0.0C)																						
2109492	0.000	1.770	C	2007		0012	CRACKING	9.0	8.0	8.0	8.0	8.0	7.5	7.5	7.5	6.5	4.5*	4.5*	4.6*	4.3*	1.0*	
ANDERSON COLUMBIA CO., INC(2008) RIDE																						
4382122	0.000	2.605	C	2029		0012		8.0	7.9	7.8	7.7	7.8	7.7	7.6	7.6	7.5	7.5	7.3	7.2	7.2	6.8	
31ST LN SW(0.2R)																						
2109553	0.000	13.887	C	2010		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.0	6.5	6.0*	6.0*	4.8*	4.3*	1.5*	
ANDERSON COLUMBIA CO., INC(2011) RIDE																						
2109554	0.000	13.983	C	2029		0012		8.0	7.7	7.7	7.4	7.6	7.5	7.5	7.4	7.3	7.2	7.2	7.1	6.7		
39050000	13.850	13.986	C	1	1	35	CRACKING	10.0	10.0	10.0	9.5	8.0	8.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0		
238				2	10.3		6000 RIDE	5.9*	5.7	6.1	5.4*	4.3*	4.8*	4.9*	4.6*	3.9*	7.0					
SR 231(13.9R)																						
							UNKW															
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	6.5	6.5	6.5	3.5*	
(2010) RIDE																						
2109554	0.000	13.983	C	2029		0012		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	6.1	
39070000	0.000	0.892	C	1	1	40	CRACKING	5.5*	5.5*	5.5*	5.5*	3.5*	3.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0		
18				2	8.0		900 RIDE	7.2	6.8	6.1	6.1	6.5	6.3	6.4	6.5	8.0	8.0	8.0	7.6	7.8		
SR 121(0.0C)																						
2109622	0.000	0.892	C	2007		0221	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	7.5	7.2	6.8	3.5*	
ANDERSON COLUMBIA CO., INC(2009) SPRIDE																						
7.5	7.2	7.4	7.0	6.6	6.9	6.7	6.3	6.2	6.1	6.3	6.1	6.3	6.1	6.2	6.1	6.2	6.1	6.2	6.2	5.8		
39090000	0.000	2.739	C	1	1	55	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	6.5	3.5*	3.5*	10.0	10.0	10.0	10.0		
231				2	2.8		4200 RIDE	8.5	8.5	8.4	8.1	7.8	7.8	8.0	7.8	7.7	8.0	8.0	7.7	7.6		
SW 73 ST(0.0L)																						
2109522	0.000	2.739	C	2008		0012	CRACKING	10.0	9.0	9.0	8.5	8.5	8.0	8.0	7.0	6.5	6.0*	6.0*	5.0*	4.6*	1.5*	
V. E. WHITEHURST & SONS, I(2010) RIDE																						
7.5	7.4	7.1	6.9	6.9	6.3*	6.3*	6.2*	6.0*	5.7*	5.8*	5.7*	5.9*	5.5*									
2109555	0.000	2.739	C	2028		0012																

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).