FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 3 COUNTY = HOLMES ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
52002000	0.000	8.370	R	4	1	70	CRACKING	4.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.0															
8 I10	94.5	102.8	2	37.6	20500		RIDE	5.4*		8.9	8.4	8.2	8.2	8.3	8.3	8.2	7.7	7.9	7.8															
							FC5																											
4252772	0.000	8.370	C	2012		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	4.0*														
ANDERSON COLUMBIA CO., INC(2014)							SPRIDE	8.2	8.2	8.5	8.5	8.7	8.6	8.5	8.7	8.6	8.5	8.4	8.4	8.4	8.3													
4252773	0.000	8.370	C	2025		0012																												
52002000	14.195	16.683	R	4	1	70	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	6.5	6.5														
8 I10	108.7	111.2	2	33.0	19600		RIDE		9.0	8.8	8.4	8.3	8.3	7.9	8.3	8.2	8.1	8.0	7.7	7.6														
							FC5M																											
4327382	14.195	16.683	C	2016		0012	CRACKING	6.5	6.5	6.5		10.0	10.0	10.0	9.5	9.5	9.0	9.0	8.9	7.9	6.0*														
OLDCASTLE MATERIALS SOUTHE(2018)							SPRIDE	7.5	7.4	8.0		8.9	8.9	9.0	9.1	9.0	9.0	9.0	9.0	8.9	8.8													
52002000	16.683	21.276	R	4	1	70	CRACKING	9.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	7.0	7.0	7.0														
8 I10	111.2	115.7	2	34.1	20400		RIDE	8.2	8.8	8.8	8.3	8.2	8.2	8.1	8.2	8.1	7.9	7.7	7.6	7.3														
							FC5M																											
4289381	17.243	19.448	C	2014		0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.8	5.5*														
				(2015)			RIDE	7.3	8.5	8.8	8.8	8.9	8.8	8.9	8.9	8.9	8.8	8.7	8.7	8.7	8.6													
52002000	16.683	21.276	L	4	1	70	CRACKING	9.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	7.0	6.5	6.5	6.5														
8 I10	111.2	115.7	2	34.1	20400		RIDE	8.3	8.9	8.8	8.3	8.2	8.1	8.2	8.1	7.9	7.8	7.7	7.5	7.2														
							FC5M																											
4289381	17.243	19.448	C	2014		0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.8	7.8	5.5*														
				(2015)			RIDE	6.9	8.5	8.8	8.7	8.9	8.9	8.8	9.0	8.9	8.8	8.7	8.8	8.7	8.6													
52002000	14.195	16.683	L	4	1	70	CRACKING	4.3*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	6.5	6.5														
8 I10	108.7	111.2	2	33.0	19600		RIDE	6.0*	8.9	8.8	8.5	8.4	8.4	8.6	8.4	8.3	8.2	8.0	7.8	7.6														
							FC5M																											
4327382	14.195	16.683	C	2016		0012	CRACKING	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.9	6.0*														
OLDCASTLE MATERIALS SOUTHE(2018)							SPRIDE	7.3	7.2	7.9	7.7	8.8	8.7	8.8	8.9	8.9	8.8	8.8	8.8	8.8	8.7													
52002000	0.000	8.370	L	4	1	70	CRACKING	5.3*		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.0	7.0															
8 I10	94.5	102.8	2	37.6	20500		RIDE	6.0*		8.9	8.4	8.3	8.2	8.3	8.2	8.1	7.8	7.6	7.6															
							FC5																											
4252772	0.000	8.370	C	2012		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	4.0*														
ANDERSON COLUMBIA CO., INC(2014)							SPRIDE	8.3	8.4	8.6	8.6	8.8	8.6	8.6	8.8	8.7	8.6	8.6	8.5	8.5	8.4													
4252773	0.000	8.370	C	2025		0012																												
52010000	0.000	7.463	C	1	1	55	CRACKING	3.0*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	7.0	7.0	7.0														
10 90			2	15.5	3100		RIDE	8.2	8.6	8.5	8.3	8.3	8.1	8.3	8.2	8.0	8.0	7.9	7.8	7.5														
MORROW RD(3.8R)							FC125M																											
4377601	0.000	6.621	C	2024		0012	CRACKING	7.0	7.0	6.5	6.5	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	10.0	10.0	8.5														
ANDERSON COLUMBIA CO., INC(2025)							SPRIDE	7.7	7.6	7.6	7.7	7.7	7.6	7.6	7.6	7.4	7.4	7.4	8.0	8.0	7.6													
52010000	7.463	14.030	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	7.0	7.0	7.0	7.0														
10 90			2	14.9	1850		RIDE	8.3	8.9	8.8	8.4	8.4	8.3	8.4	8.3	8.2	8.0	8.0	7.9	7.7														
E MAIN ST(7.5R)							FC95MR																											
							CRACKING	7.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5	7.0	6.8	6.5	4.5*													
				(2015)			RIDE	7.6	8.8	8.4	8.3	8.1	7.9	7.7	7.7	7.5	7.4	7.6	7.3	7.3	6.9													
4570281	7.463	14.030	C	2029		0012																												
52010000	19.069	21.824	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	7.0														
10 90			2	12.2	3300		RIDE	8.2	8.8	8.8	8.4	8.4	8.3	8.5	8.5	8.4	8.4	8.3	8.2	8.2														
END 61010000(19.1C)							FC125M																											
4362691	19.069	21.824	C	2018		0012	CRACKING	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.6	7.0													
ANDERSON COLUMBIA CO., INC(2019)							RIDE	8.1	8.0	8.0	8.0	8.0	8.3	8.3	8.1	7.9	7.9	7.8	7.8	7.7	7.3													
52010000	21.824	23.214	R	1	1	45	CRACKING	9.5	9.5	9.5	8.0	7.0	6.0*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0														
10 90			2	8.1	5700		RIDE	8.4	8.4	8.4	8.0	7.9	7.7	7.9	8.0	7.7	8.7	8.7	8.6	8.1														
SIEG LN(22.2R)							FC95M																											
4169321	21.814	23.130	C	2009		0012	CRACKING	10.0	10.0	9.5	9.5	9.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	5.7*	3.5*													
PREFERRED MATERIALS, INC. (2010)							SPRIDE	8.5	8.4	8.3	8.3	8.2	8.1	8.0	7.9	7.7	7.7	7.6	7.4	7.3	6.9													
4362692	21.824	23.790	C	2025		0012																												
52010000	23.214	23.813	R	1	1	45	CRACKING	9.5	9.5	9.5	9.5	7.0	7.0	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0														
10 90			2	11.8	6000		RIDE	7.4	7.1	7.2	7.1	7.1	7.0	6.9	6.7	6.0	7.9	7.5	7.8	7.6														
DEPOT ST(23.3C)							FC95M																											
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	6.1*	5.6*	3.5*													
				(2010)			RIDE	7.5	7.4	7.5	7.4	7.4	7.4	7.3	7.0	6.8	6.9	6.6	6.6	6.9	6.5													
4362692	21.824	23.790	C	2025		0012																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 3 COUNTY = HOLMES ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYS / %T / FY-P / ASTYPE / FY-F	TYP / SURFTYPE / WKMX-P / WKMX-F	SPD / AADT	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
52010000	23.813	27.250	C	1	1	55	CRACKING	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	7.0															
10	90		2	11.8		6000	RIDE	7.0	6.0*		8.2	8.1	8.2	8.3	8.4	8.3	8.3	8.3	8.2	8.1															
MAGNOLIA ST(23.8L)						FC125M																													
4436441	25.462	27.216	C	2022		0012	CRACKING	7.0	7.0	6.5	6.5	6.5	6.0*	6.0*	5.5*	5.5*	3.5*	10.0	9.0	10.0	8.5															
ANDERSON COLUMBIA CO., INC			(2024)				SPRIDE	8.0	7.9	7.7	7.8	7.8	7.6	7.6	7.5	7.6	7.4	8.4	8.2	8.3	7.9													
52010000	27.250	27.386	C	1	8	55	CRACKING	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	7.0															
10	90		2	8.0		4165	RIDE	7.0	6.0*		8.2	8.1	8.2	8.3	8.4	8.3	8.3	8.3	8.2	8.1															
						FC125																													
							CRACKING	7.0	7.0	6.5	6.5	6.5	6.0*	6.0*	5.5*	5.5*	3.5*	10.0	9.0															
			(2024)				RIDE	8.0	7.9	7.7	7.8	7.8	7.6	7.6	7.5	7.6	7.4	8.4	8.2															
52010000	23.214	23.813	L	1	1	45	CRACKING	9.5	9.5	8.0	7.0	6.0*	6.0*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0															
10	90		2	11.8		6000	RIDE	7.1	6.9	7.0	6.4*	6.3*	6.3	6.2	6.3	6.0	8.0	7.9	7.7	7.3															
DEPOT ST(23.3C)						FC95M																													
							CRACKING	10.0	10.0	9.5	9.5	9.5	8.0	9.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	4.0*													
			(2010)				RIDE	7.2	7.4	7.4	7.3	7.3	7.0	7.3	6.8	6.7	6.7	6.3	6.4	6.5	6.1													
4362692	21.824	23.790	C	2025		0012																													
52010000	21.824	23.214	L	1	1	45	CRACKING	9.5	9.5	8.0	7.0	7.0	7.0	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0															
10	90		2	8.1		5700	RIDE	8.5	8.5	8.4	7.9	7.8	7.8	7.9	7.8	7.6	8.7	8.6	8.5	8.5															
DYKES RD(22.5L)						FC95M																													
4169321	21.814	23.130	C	2009		0012	CRACKING	10.0	10.0	9.5	9.5	9.5	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.1*	4.7*	2.5*													
PREFERRED MATERIALS, INC.			(2010)				SPRIDE	8.4	8.1	8.3	8.1	8.1	7.8	7.9	7.8	7.4	7.4	7.2	7.1	7.0	6.6													
4362692	21.824	23.790	C	2025		0012																													
52030000	0.958	1.380	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	7.0	7.0															
79			2	9.5		12000	RIDE	8.2	8.8	8.8	8.5	8.6	8.6	8.7	8.7	8.4	8.4	8.2	8.2	8.1															
CR 3 R(1.0R)						FC95MR																													
4269361	0.954	1.386	C	2015		0012	CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.6	8.4	6.5													
C. W. ROBERTS CONTRACTING,			(2016)				SPRIDE	7.9	7.9	8.4	8.4	8.4	8.3	8.3	8.3	8.2	8.1	8.1	8.0	8.1	7.7													
52030000	1.380	3.054	R	1	1	45	CRACKING	6.0*	6.0*	6.0*	5.5*	3.5*	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0															
79			1	8.0		13400	RIDE	7.7	8.0	7.9	7.0	6.6	8.0	8.2	8.2	8.1	8.1	8.1	8.0	7.9															
SON IN LAW RD(1.5R)						FC125M																													
4373671	1.632	3.054	R	2019		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	9.3	8.7	7.0													
C. W. ROBERTS CONTRACTING,			(2021)				SPRIDE	7.7	7.3	7.4	7.4	7.3	7.1	7.1	7.7	7.7	7.7	7.7	7.7	7.7	7.3													
52030000	3.054	4.115	R	1	2	25	CRACKING	7.0	6.0*	5.5*	3.5*	3.5*	3.5*	1.0*	10.0	10.0	8.5	8.5	8.5	8.5															
79			2	9.5		11500	RIDE	6.2*	6.1	5.7	5.2*	5.0*	4.5*	4.9*	7.5	7.2	7.4	7.3	7.3	7.4															
SR 10(3.1C)						FC125M																													
2191652	3.272	4.070	C	2007		0012	CRACKING	8.5	8.5	8.5	8.0	8.0	8.0	8.0	7.0	6.0*	6.0*	6.0*	6.0*	5.8*	3.5*													
PREFERRED MATERIALS, INC.			(2008)				SPRIDE	7.2	6.9	6.9	6.7	6.8	6.4	6.8	6.2	6.7	6.5	6.4	6.3	6.1	5.7													
2191653	3.054	5.617	C	2025		0012																													
52030000	4.115	5.313	C	1	1	55	CRACKING	5.5*	5.5*	3.5*		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0															
79			2	14.8		7400	RIDE	7.7	7.3	7.0		8.7	8.7	8.7	8.6	8.6	8.5	8.5	8.5	8.5															
NIMES DR(4.3L)						FC125																													
2191651	4.500	17.767	C	2003		0012	CRACKING	9.0	9.0	8.5	7.5	7.5	7.5	7.5	6.5	6.0*	6.0*	6.0*	5.2*	4.3*	2.0*													
APAC-FLORIDA INC			(2005)				SPRIDE	8.4	8.4	8.3	8.3	8.3	8.1	8.0	8.1	8.0	8.1	8.0	8.0	8.1	7.7													
2191653	3.054	5.617	C	2025		0012																													
52030000	5.313	5.617	C	1	1	55	CRACKING	5.5*	5.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
79			2	14.8		7400	RIDE	7.7	7.3	7.0		8.7	8.7	8.3	8.2	8.2	8.2	8.2	8.1	8.1															
CR 177(5.5L)						FC125																													
2191651	4.500	17.767	C	2003		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	7.5	7.5	6.5	6.0*	6.0*	6.0*	5.2*	7.9	6.0*													
APAC-FLORIDA INC			(2007)				SPRIDE	8.0	8.0	7.8	7.6	7.8	8.1	8.0	8.1	8.0	8.1	8.0	8.0	7.5	7.1													
2191653	3.054	5.617	C	2025		0012																													
52030000	5.617	17.674	C	1	1	55	CRACKING	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5															
79			2	14.8		4400	RIDE	8.0	7.9	7.7		8.7	8.7	8.7	8.8	8.7	8.7	8.6	8.5	8.4															
MT OLIVE RD(7.2L)						FC95MR																													
4377521	5.594	17.673	C	2019		0012	CRACKING	7.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
C. W. ROBERTS CONTRACTING,			(2021)				SPRIDE	8.5	8.3	8.3	8.2	8.3	8.2	8.2	8.6	8.6	8.6	8.6	8.6	8.6	8.2													
52030000	1.380	3.054	L	1	1	45	CRACKING	6.0*	6.0*	6.0*	5.5*	3.5*	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0															
79			1	8.0		13400	RIDE	7.7	8.0	7.9	7.0	6.6	8.0	8.2	8.2	8.1	8.1	8.1	8.0	7.9															
ST JOHNS RD(1.5L)						FC125M																													
4373671	1.632	3.054	L	2019		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	9.0	8.3	7.7	6.0*													
C. W. ROBERTS CONTRACTING,			(2021)				SPRIDE	7.7	7.3	7.4	7.4	7.3	7.1	7.1	7.9	7.9	7.8	7.7	7.7	7.9	7.5													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 3 COUNTY = HOLMES ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS / %T / FY-P / FY-F	TYP SPD / AADT / SURFTYPE / WKMX-P / WKMX-F	DISTRESS RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
52030000	0.958	1.380	L	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5																	
79			2	9.5	12000	RIDE	8.2	8.7	8.7	8.4	8.2	8.5	8.4	8.6	8.5	8.4	8.2	8.0	8.2																	
UNSIGNED(1.0L)					FC95MR																														
4269361	0.954	1.386	C	2015	0012	CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0																
C. W. ROBERTS CONTRACTING,(2016)					SPRIDE		7.9	8.0	8.3	8.2	8.2	8.1	8.1	8.1	8.1	8.0	8.0	7.8	7.9	7.5															
52040000	0.000	0.435	C	1	1 45	CRACKING	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5																	
81			2	13.0	2700	RIDE	7.7		8.4	8.0	7.9	7.8	8.2	8.2	8.2	8.2	8.1	8.0	7.9																	
HOGANS DR(0.0L)					FC95MR																														
4325371	0.000	0.406	C	2016	0012	CRACKING	9.5	8.0	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.6	8.4	6.5																
C. W. ROBERTS CONTRACTING,(2018)					SPRIDE		7.9	7.8	7.7		8.7	8.7	8.7	8.6	8.5	8.5	8.5	8.5	8.5	8.1															
52040000	0.435	1.006	R	1	1 45	CRACKING	9.5		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	7.0	7.0	7.0																	
81			1	13.0	2700	RIDE	8.0		8.3	8.1	8.0	8.0	8.2	8.2	8.0	8.0	7.9	7.8	7.6																	
					FC95MR																														
4325371	0.406	1.006	C	2016	0012	CRACKING	7.0	7.0	6.5		10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.0	5.5*																
C. W. ROBERTS CONTRACTING,(2018)					SPRIDE		7.5	7.5	7.3		8.0	7.9	7.9	7.9	7.9	7.8	7.7	7.7	7.6	7.2															
52040000	1.006	1.747	C	1	1 45	CRACKING	4.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	8.0																	
81			2	11.2	4200	RIDE	6.6		8.1	7.7	7.6	7.6	7.7	7.8	7.4	7.4	7.4	6.8	6.6																	
JOE MANNING LN(1.0R)					FC95MR																														
						CRACKING	8.0	8.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0	6.5															
				(2017)		RIDE	6.2	7.1	6.5	8.9	8.8	8.8	8.8	8.7	8.7	8.7	8.6	8.6	6.0	5.6															
52040000	1.747	21.576	C	1	1 55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	7.0	7.0																	
81			2	12.0	2050	RIDE	8.3	8.9	8.9	8.5	8.5	8.5	8.6	8.5	8.4	8.3	8.4	8.0	8.1																	
BLUE CREEK DR(1.8R)					FC95MR																														
4325371	7.325	21.576	C	2016	0012	CRACKING	6.5	6.5	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	9.1	7.5																
C. W. ROBERTS CONTRACTING,(2017)					SPRIDE		7.9	7.7	7.9	8.9	8.8	8.8	8.8	8.7	8.7	8.7	8.6	8.6	8.6	8.2															
52040000	0.435	1.006	L	1	1 45	CRACKING	7.0		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	7.0																	
81			1	13.0	2700	RIDE	7.7		8.4	8.2	8.1	7.7	8.2	8.0	7.8	7.7	7.6	7.5	7.2																	
NB TO WB SR 9(0.8L)					FC95MR																														
4325371	0.406	1.006	C	2016	0012	CRACKING	7.0	7.0	7.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.7	7.4	5.5*																
C. W. ROBERTS CONTRACTING,(2017)					SPRIDE		7.0	7.0	7.0	8.1	8.1	8.1	8.0	7.9	7.9	7.8	7.8	7.7	7.7	7.3															
52050000	6.711	14.318	C	1	1 60	CRACKING	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0																	
2			2	27.9	1050	RIDE	7.5		8.8	8.4	8.4	8.3	8.6	8.5	8.4	8.3	8.3	7.7	8.1																	
MYRTLE RD(8.3R)					FC95MR																														
4362671	6.714	13.916	C	2018	0012	CRACKING	7.0	7.0	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.0																
C. W. ROBERTS CONTRACTING,(2020)					SPRIDE		8.1	8.0	7.9	7.9	7.9	7.8	8.7	8.6	8.6	8.6	8.5	8.5	8.5	8.1															
52050000	14.802	20.872	C	1	1 55	CRACKING	7.0	7.0	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.0																	
2			2	27.9	1900	RIDE	8.5	8.5	8.4	7.9	7.8	7.6	8.9	8.8	8.7	8.6	8.5	8.3	8.2																	
CHOCTAWHATCHEE LN(14.9R)					FC125M																														
4455371	14.802	20.835	C	2023	0012	CRACKING	8.5	7.5	7.5	7.5	6.5	6.0*	5.5*	3.5*	3.5*	3.0*	3.0*	10.0	10.0	8.5																
C. W. ROBERTS CONTRACTING,(2025)					SPRIDE		8.0	7.8	8.0	8.0	7.9	7.9	7.8	7.6	7.5	7.4	7.3	8.6	8.7	8.3															
52050000	20.872	24.837	C	1	1 55	CRACKING	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	7.0																	
2			2	20.7	1700	RIDE	7.5	7.5	8.4	8.2	8.1	8.1	8.2	8.2	8.1	8.1	8.0	7.6	7.7																	
NEW BAYVIEW CHURCH(21.3L)					FC125M																														
4325561	20.872	24.795	C	2017	0012	CRACKING	6.5	6.5	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.1	6.5																
C. W. ROBERTS CONTRACTING,(2018)					RIDE		7.6	7.4	7.3	7.1	8.4	8.3	8.3	8.3	8.3	8.2	8.2	8.2	8.1	7.7															
52050000	24.837	33.915	C	1	1 55	CRACKING	8.0	7.0	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	9.0																	
2			2	16.2	2074	RIDE	8.6	8.8	8.7	8.2	7.9	7.9		8.6	8.6	8.5	8.4	8.2	8.2																	
TEN MILE RD(25.0L)					FC125M																														
4455391	29.310	33.915	C	2023	0012	CRACKING	9.0	9.0	9.0	9.0	6.0*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	8.5																
C. W. ROBERTS CONTRACTING,(2025)					SPRIDE		8.1	8.0	7.9	7.9	7.9	7.7	7.7	7.6	7.4	7.3	7.1	8.0	7.9	7.5															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).