

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = CLAY

RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS		2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)							=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
CONTRACTOR (AGE ONE YEAR)					ASTYPE																(PMRS)	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																	
71010000	0.000	4.728	R	1	1 60	CRACKING		7.0	6.0*	4.0*	4.0*	3.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0		
15 17			2	23.5	10000	RIDE		8.7	8.1	8.1	7.6	6.1*	6.7	5.6*	6.6	8.4	8.3	8.2	8.2	8.1		
CR 214(1.0R)					FC5M																	
2081772	0.000	5.000	C	2007	0012	CRACKING		10.0	10.0	9.5	9.5	9.5	9.0	7.5	6.5	5.5*	3.5*	3.5*	3.5*	2.5*	0.0*	
HUBBARD CONSTRUCTION COMPA(2008)						RIDE		8.0	7.9	7.9	8.2	8.2	8.3	8.2	8.3	8.2	8.1	8.0	7.9	7.7	7.5	
2081773	0.000	4.720	C	2025	0012																	
71010000	4.728	7.887	R	1	1 60	CRACKING		5.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5		
15 17			2	23.5	10000	RIDE		8.2	7.7	7.8	7.4	8.0	7.6	8.0	8.2	8.2	8.2	8.0	7.9	7.7		
AIRPARK RD(4.8R)					FC5M																	
4322691	4.728	10.489	C	2017	0012	CRACKING		6.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	9.0	9.0	9.8	7.0	
ANDERSON COLUMBIA CO., INC(2019)						SPRIDE		7.7	7.4	7.3	7.8	7.8		8.8	8.8	8.8	8.8	8.9	8.9	8.9	8.7	
71010000	7.887	8.573	R	1	7 60	CRACKING		5.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5		
15 17			2	23.5	10500	RIDE		8.2	7.7	7.8	7.4	8.0	7.6	8.0	8.2	8.2	8.2	8.0	7.9	7.7		
JP HALL BLVD(7.9R)					FC2																	
						CRACKING		6.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0				10.0	9.0	
(2025)						RIDE		7.7	7.4	7.3	7.8	7.8		8.8	8.8	8.8				8.0	7.8	
71010000	8.573	10.489	R	1	1 60	CRACKING		5.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5		
15 17			2	12.7	15300	RIDE		8.2	7.7	7.8	7.4	8.0	7.6	8.0	8.2	8.2	8.2	8.0	7.9	7.7		
CR 209(9.0R)					FC5M																	
4322691	4.728	10.489	C	2017	0012	CRACKING		6.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	9.0	9.0	8.9	6.0*	
ANDERSON COLUMBIA CO., INC(2019)						SPRIDE		7.7	7.4	7.3	7.8	7.8		8.8	8.8	8.8	8.5	8.5	8.5	8.5	8.3	
71010000	10.489	11.277	R	1	1 45	CRACKING		10.0	10.0	10.0	10.0	10.0	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0		
15 17			2	23.5	19500	RIDE		7.9	8.0	8.4	8.3	7.8	7.7	7.6	8.2	8.2	8.1	8.1	7.9	8.0		
COVE PLAZA ENT(10.6R)					FC125M																	
2080852	10.647	11.277	C	2006	0012	CRACKING		9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.0	7.0	7.0	6.0*	6.0*	5.4*	2.5*	
J.B. COXWELL CONTRACTING, I(2007)						SPRIDE		8.0	7.9	7.7	7.6	7.4	7.3	7.3	7.4	7.5	7.2	6.6	6.9	6.9	6.5	
71010000	10.489	11.277	L	1	1 45	CRACKING		10.0	10.0	10.0	10.0	9.5	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0		
15 17			2	23.5	19500	RIDE		8.6	8.3	8.4	8.5	7.8	7.5	7.7	7.4	7.4	7.3	7.4	7.3	7.3		
COOKS LN W(10.6L)					FC125M																	
2080852	10.647	11.277	C	2006	0012	CRACKING		9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.0	7.0	6.5	6.5	6.5	3.5*	
J.B. COXWELL CONTRACTING, I(2007)						SPRIDE		7.3	7.2	7.2	6.5	6.4	6.5	6.3	6.9	6.7	6.8	6.3	6.6	6.2	5.8	
71010000	8.573	10.489	L	1	1 60	CRACKING		9.5	9.5	7.0	7.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	6.5		
15 17			2	12.7	15300	RIDE		9.0	8.8	8.7	8.6	7.7	7.8	7.8	8.0	8.0	8.0	7.8	7.8	7.8		
CLEAR HALL LN(9.2L)					FC5M																	
4322691	4.728	10.489	C	2017	0012	CRACKING		6.5	6.5	6.5	5.5*	5.5*		10.0	10.0	10.0	10.0	9.0	9.0	8.9	6.0*	
ANDERSON COLUMBIA CO., INC(2019)						SPRIDE		7.6	7.5	7.3	7.8	7.8		8.7	8.8	8.6	8.5	8.5	8.4	8.4	8.2	
71010000	7.887	8.573	L	1	7 60	CRACKING		9.5	9.5	7.0	7.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	6.5		
15 17			2	23.5	10500	RIDE		9.0	8.8	8.7	8.6	7.7	7.8	7.8	8.0	8.0	8.0	7.8	7.8	7.8		
					FC2																	
(2025)						CRACKING		6.5	6.5	6.5	5.5*	5.5*		10.0	10.0	10.0				10.0	9.0	
						RIDE		7.6	7.5	7.3	7.8	7.8		8.7	8.8	8.6				7.7	7.5	
71010000	4.728	7.887	L	1	1 60	CRACKING		9.5	9.5	7.0	7.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	6.5		
15 17			2	23.5	10000	RIDE		9.0	8.8	8.7	8.6	7.7	7.8	7.8	8.0	8.0	8.0	7.8	7.8	7.8		
AIR PARK RD(4.8L)					FC5M																	
4322691	4.728	10.489	C	2017	0012	CRACKING		6.5	6.5	6.5	5.5*	5.5*		10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	
ANDERSON COLUMBIA CO., INC(2019)						SPRIDE		7.6	7.5	7.3	7.8	7.8		8.7	8.8	8.6	8.9	8.9	8.9	8.8	8.6	
71010000	0.000	4.728	L	1	1 60	CRACKING		8.0	7.0	5.0*	4.0*	3.5*	1.0*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0		
15 17			2	23.5	10000	RIDE		9.0	8.6	8.1	7.9	6.4*	5.7*	7.0	7.1	8.4	8.3	8.2	8.1	8.1		
LOVERS LN(0.3L)					FC5M																	
2081772	0.000	5.000	C	2007	0012	CRACKING		10.0	9.5	9.5	9.0	9.0	9.0	7.5	6.5	5.5*	3.5*	2.5*	2.5*	1.4*	0.0*	
HUBBARD CONSTRUCTION COMPA(2008)						RIDE		8.1	7.9	7.9	8.2	8.2	8.3	8.2	8.2	8.2	8.1	8.0	7.9	7.6	7.4	
2081773	0.000	4.720	C	2025	0012																	
71020000	0.000	1.239	R	1	1 35	CRACKING		9.5	8.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0		
15 17			2	9.4	22500	RIDE		7.2	6.8	6.5	6.3	6.1	5.9	5.9	7.3	7.3	7.1	7.0	6.9	6.9		
FERRIS ST(0.0R)					FC125M																	
2080852	0.000	1.239	C	2006	0012	CRACKING		9.0	8.5	8.5	8.5	8.5	8.5	8.5	7.5	6.5	6.0*	6.0*	3.5*	3.0*	0.0*	
J.B. COXWELL CONTRACTING, I(2007)						SPRIDE		6.9	6.8	6.7	5.8	5.7	5.9	5.5	5.4*	5.3*	5.3*	5.2*	5.0*	4.9*	4.5*	
2082025	0.000	3.921	C	2025	0012																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = CLAY																									
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR																	FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012					
INTERSECT AT (MP SIDE)	W BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE																			
CONTRACTOR (AGE ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025					2030 (PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F																				
71020000 15 17	1.239	1.865	R 2	1 9.4	1 40 29500	CRACKING RIDE		10.0 8.8	10.0 8.3	10.0 8.6	10.0 8.6	10.0 8.2	9.5 7.8	9.5 8.0	9.5 8.3		10.0 8.1	10.0 8.0	10.0 7.9	10.0 8.0					
SHERIFFS OFFICE(1.4R)					FC125M																				
2080853	1.239	6.563	C 2007	0012	CRACKING		10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	6.0*	4.5*	4.5*	4.5*	4.5*	1.5*				
HUBBARD CONSTRUCTION COMPA(2009)					SPRIDE		7.9	7.8	7.9	7.7	7.7	7.6	7.4	7.4	7.4	7.4	7.4	7.2	7.2	7.1	6.7				
2082025	0.000	3.921	C 2025	0012																					
71020000 15 17	1.865	3.921	R 2	1 9.4	1 55 29500	CRACKING RIDE		9.5 9.0	8.0 8.8	8.0 8.6	7.0 8.4	7.0 7.2	4.5* 6.4*	4.5* 6.1*	4.5* 5.9*		10.0 8.4	10.0 8.2	10.0 8.3	10.0 8.2					
HICKORY KNOLLS DR(2.2R)					FC5																				
2080853	1.239	6.563	C 2007	0012	CRACKING		10.0	10.0	9.5	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	4.5*	4.5*	4.3*	0.0*				
HUBBARD CONSTRUCTION COMPA(2009)					SPRIDE		8.2	8.1	8.1	8.4	8.4	8.5	8.6	8.6	8.5	8.5	8.4	8.4	8.3	8.3	8.1				
2082025	0.000	3.921	C 2025	0012																					
71020000 15 17	4.198	4.944	R 2	1 9.4	1 55 34500	CRACKING RIDE		9.5 8.8	8.0 8.5	8.0 8.6	7.0 8.4	7.0 7.2	4.5* 6.4*	4.5* 6.1*	4.5* 5.9*		10.0 8.4	10.0 8.2	10.0 8.3	10.0 8.2					
4393461	4.198	4.725	R 2019	0012	CRACKING		10.0	10.0	9.5	9.0	9.0	9.0	9.0	9.0		10.0	10.0	10.0	10.0	9.6	7.5				
HUBBARD CONSTRUCTION COMPA(2021)					SPRIDE		8.2	8.1	8.1	8.4	8.4	8.4	8.5	8.5		8.9	8.8	8.8	8.8	8.8	8.6				
71020000 15 17	4.944	6.623	R 3	1 9.4	1 55 34500	CRACKING RIDE		9.5 8.8	8.0 8.5	8.0 8.6	7.0 8.4	7.0 7.2		10.0 8.4	10.0 8.5	10.0 8.4	10.0 8.4	10.0 8.3	9.0 8.2	9.0 8.1					
MARGARETS WALK RD(5.0R)					FC5M																				
4393461	4.956	6.603	R 2019	0012	CRACKING		7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	8.0				
HUBBARD CONSTRUCTION COMPA(2021)					SPRIDE		8.0	7.9	7.7	7.5	7.4	7.4	7.4	7.3		8.4	8.3	8.3	8.4	8.4	8.2				
71020000 15 17	6.623	8.241	R 3	1 6.4	8 55 44210	CRACKING RIDE			10.0 8.1	10.0 8.5	10.0 8.4	10.0 8.3	10.0 7.6	10.0 8.3	10.0 8.4	10.0 8.4	9.5 8.3	9.5 8.3	8.0 8.1	8.0 8.1					
WATER OAK LN(6.7R)					FC5M																				
4233991	6.563	8.241	R 2013	0012	CRACKING		8.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	7.5	6.5	6.5						
HUBBARD CONSTRUCTION COMPA(2014)					SPRIDE		8.1	8.5	8.5	8.4	8.8	8.7	8.4	8.5	8.4	8.4	8.4	8.3	8.2						
4433021	6.598	8.630	C 2024	0012																					
71020000 15 17	8.241	11.321	R 3	1 9.4	8 50 58000	CRACKING RIDE		10.0 9.1	9.5 8.9	9.5 8.9	8.0 8.8	8.0 8.1	7.5 7.5	6.5 7.5	6.5 7.1	3.5* 6.8	3.5* 6.5	10.0 8.4	10.0 8.5	10.0 8.4					
CR-15A(8.3R)					FC5M																				
2082073	8.261	10.899	R 2009	0012	CRACKING		10.0	10.0	10.0	10.0	8.5	8.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*							
HUBBARD CONSTRUCTION COMPA(2010)					SPRIDE		8.4	8.3	8.3	8.6	8.7	8.8	8.0	8.1	8.0	7.6	7.3	6.9							
4471801	8.594	11.321	C 2023	0012																					
71020000 15 17	11.676	12.480	R 3	1 9.4	1 45 51000	CRACKING RIDE		6.0* 8.2	5.5* 8.1	3.5* 7.6	3.5* 7.7	3.0* 6.6	0.0* 6.0*	0.0* 5.8	0.0* 6.0	0.0* 6.0				10.0 8.3					
HOLLY POINT RD(11.8R)					FC125M																				
2082071	11.682	12.192	C 2007	0213	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.4	6.0*				
ARCHER WESTERN CONTRACTORS(2012)					SPRIDE		8.2	8.3	8.2	8.1	8.1	8.1	7.9	8.0	8.0	8.0	8.0	8.0	7.9	7.7	7.3				
2082283	11.321	13.806	C 2026	0012																					
71020000 15 17	12.480	13.808	R 3	1 9.4	1 40 58500	CRACKING RIDE		4.0* 8.5	3.5* 8.3	3.5* 7.9	3.5* 8.0	3.5* 6.0	10.0 7.9	10.0 7.7	10.0 7.8	10.0 7.7	10.0 7.7	9.0 7.5	9.0 7.4	9.0 7.4					
STOWE AVE(12.5C)					FC125																				
2082281	12.762	14.365	C 2003	0012	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	7.0	7.0	7.0	5.5*	4.2*	1.0*				
HUBBARD CONSTRUCTION COMPA(2005)					RIDE		7.7	7.4	7.8	7.7	7.6	7.7	7.5	7.5	7.4	7.5	7.3	7.3	7.2	6.8					
2082283	11.321	13.806	C 2026	0012																					
71020000 15 17	13.808	14.365	R 4	1 9.4	8 40 89000	CRACKING RIDE		6.0* 7.8	6.0* 7.6	6.0* 7.4	6.0* 7.3	6.0* 6.2	10.0 7.9	10.0 7.7	10.0 7.8	10.0 7.7	10.0 7.7	9.0 7.5	9.0 7.4	9.0 7.4					
JOHNSON AVE(14.0C)					FC125M																				
(2016)					CRACKING		9.0	9.0		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	6.8						
					RIDE		7.7	7.4		7.7	7.6	7.5	7.4	7.4	7.4	7.3	7.4	7.4	6.8						
71020000 15 17	13.808	14.365	L 3	1 9.4	8 40 89000	CRACKING RIDE		5.5* 7.9	3.5* 7.7	3.5* 7.3	3.5* 7.6	3.5* 5.0*	10.0 8.0	10.0 7.8	10.0 8.0	10.0 8.0	10.0 8.0	10.0 7.9	10.0 7.9	10.0 7.8					
JOHNSON AVE(14.0C)					FC125M																				
(2016)					CRACKING		10.0	9.5		10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	8.5							
					RIDE		7.8	7.8		7.7	7.8	7.8	7.8	7.6	7.6	7.7	7.4	7.7	7.3						
71020000 15 17	12.480	13.808	L 3	1 9.4	1 40 58500	CRACKING RIDE		4.0* 8.2	4.0* 8.1	3.5* 7.9	3.5* 7.9	3.5* 5.4*	10.0 7.6	10.0 7.4	10.0 7.7	10.0 7.6	10.0 7.6	9.5 7.4	9.5 7.3	9.5 7.3					
STOWE AVE(12.5C)					FC125																				
2082281	12.762	14.365	C 2003	0012	CRACKING		9.5	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	5.5*	5.5*	3.5*	0.0*					
HUBBARD CONSTRUCTION COMPA(2005)					RIDE		7.2	7.3	7.1	7.5	7.3	7.4	7.3	7.3	7.2	7.1	7.0	6.5	6.7	6.3					
2082283	11.321	13.806	C 2026	0012																					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

ROWID	BMP										SURVEYED YEAR										FUTURE			
	SR	US	G_BMP	G_EMP	RW	LN	SYS	TYP	SPD	DISTRESS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009		2010	2011	2012
	INTERSECT	AT	(MP)	SIDE			%T	ADT	RATINGS	=====														
	ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P	ASTYPE																	
CONTRACTOR	(AGE)	ONE	YEAR																					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																		(PMRS)	
71020000	11.676	12.480	L	1	1	45	CRACKING	6.0*	6.0*	5.5*	5.5*	3.5*	1.0*	1.0*	0.0*	0.0*							10.0	
15 17			3	9.4	51000	RIDE		8.4	8.2	8.1	7.9	6.9	6.6	6.9	6.8	6.7							8.1	
HOLLY PT W(11.8L) FC125M																								
2082071	11.682	12.192	C	2007	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.0	5.5*
ARCHER WESTERN CONTRACTORS(2012)						SPRIDE		8.1	7.9	8.1	8.2	8.2	8.2	7.9	8.1	8.1	8.1	8.0	8.1	8.1	7.9	8.0	7.6	
2082283	11.321	13.806	C	2026	0012																			
71020000	8.241	11.321	L	1	8	50	CRACKING	10.0	10.0	9.5	9.5	8.0	7.5	6.5	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0		10.0	
15 17			3	9.4	58000	RIDE		9.1	8.9	8.8	8.7	8.1	7.7	7.8	7.7	7.6	7.5	7.5	8.0	8.5	8.5	8.4	8.4	
BALD EAGLE RD(8.3L) FC5M																								
2082073	8.261	10.899	L	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	4.5*	4.5*	3.5*					
HUBBARD CONSTRUCTION COMPA(2010)						SPRIDE		8.4	8.3	8.3	8.6	8.6	8.6	8.5	8.6	8.3	8.2	8.1	7.8					
4471801	8.594	11.321	C	2023	0012																			
71020000	6.563	8.241	L	1	1	55	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5		9.5	
15 17			3	6.4	44210	RIDE			8.2	8.5	8.5	8.3	8.0	8.3	8.4	8.3	8.4	8.3	8.1	8.1		8.1		
VILLAGE SQUARE PKWY(6.7L) FC5M																								
4233991	6.563	8.241	L	2013	0012	CRACKING	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	6.5	6.5	5.5*	1.5*			
HUBBARD CONSTRUCTION COMPA(2014)						SPRIDE		7.7	8.4	8.4	8.5	8.6	8.6	8.5	8.6	8.6	8.4	8.4	8.2	8.1	8.1	7.9		
4433021	6.598	8.630	C	2024	0012																			
71020000	4.735	6.563	L	1	1	55	CRACKING	10.0	9.5	8.0	8.0	7.5		10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0			
15 17			3	9.4	34500	RIDE		8.9	8.5	8.5	8.4	7.7		8.3	8.3	8.4	8.2	8.2	8.1	8.0				
TOWN CENTER BLVD(5.0L) FC5M																								
4393461	4.956	6.603	L	2019	0012	CRACKING	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	8.0	8.0		
HUBBARD CONSTRUCTION COMPA(2021)						SPRIDE		7.7	7															

```

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = CLAY																								
RDWYID	SR	US	BMP	G	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR												FUTURE
INTERSECT	AT	(MP)	SIDE							=====														
ITMSEG-P	W	BMP	W	EMP	RW	FY-P	W	KMX-P																
CONTRACTOR	(AGE	ONE	YEAR)					ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
ITMSEG-F	W	BMP	W	EMP	RW	FY-F	W	KMX-F																(PMRS)
71030000			3.195		5.540	L	1	1	65	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	
200	301					2	29.7	27000		RIDE		8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	
								FC5M																
						(2025)				CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0		8.9	8.0
										RIDE	8.0	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9		9.0	8.8
71030000			2.910		3.195	L	1	7	55	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	
200	301					2	29.7	27000		RIDE		8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	
UNSIGNED(	3.1L)							FC5M																
						(2025)				CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0		10.0	9.0
										RIDE	8.0	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9		8.0	7.8
71030000			2.765		2.910	L	1	1	65	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	
200	301					2	34.3	19800		RIDE		8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	
								FC5M																
						(2025)				CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0		9.3	8.5
										RIDE	8.0	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9		8.6	8.4
71030000			0.500		2.765	L	1	7	65	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	
200	301					2	34.3	19800		RIDE		8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	
								FC5M																
						(2025)				CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0		10.0	9.0
										RIDE	8.0	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9		8.7	8.5
71030000			0.000		0.500	L	1	1	65	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	
200	301					2	34.3	19800		RIDE		8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	
								FC5M																
						(2025)				CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0		9.0	8.0
										RIDE	8.0	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9		8.8	8.6
71040000			0.000		2.882	R	1	1	50	CRACKING	9.5	9.5	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	
100						1	5.2	12100		RIDE	8.6	8.0	8.2	8.2	7.3	7.5	7.3	7.7	7.4	7.4	7.2	6.9	8.5	
SE 1 AVE(	0.0R)							FC125M																
						(2012)				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	5.0*
										RIDE	8.3	8.3	8.3	8.1	8.1	8.1	8.0	8.0	8.0	7.9	7.9	7.9	7.8	7.4
71040000			2.882		5.304	C	1	1	60	CRACKING	10.0	9.5	9.5	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	10.0	
100						2	8.4	7200		RIDE	8.7	8.3	8.6	8.5	8.1	8.0	8.0	8.2	8.0	7.9	7.6	7.3	8.5	
3RD ST(	3.0R)							FC125M																
2081872			2.882		5.304	C	2011	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	7.5	7.0	4.5*
PREFERRED	MATERIALS, INC.	(2012)						SPRIDE			8.3	8.3	8.3	8.1	8.1	8.1	8.0	8.0	8.0	8.1	8.1	8.0	8.0	7.6
71040000			0.000		2.882	L	1	1	50	CRACKING	9.5	9.5	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	
100						1	5.2	12100		RIDE	8.6	8.0	8.2	8.2	7.3	7.5	7.3	7.7	7.4	7.4	7.2	6.9	8.5	
KINGS ST(	0.3L)							FC125M																
						(2012)				CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	5.0*
										RIDE	8.3	8.3	8.3	8.1	8.1	8.1	8.0	8.0	8.0	8.0	8.0	7.8	7.9	7.5
71050000			0.000		2.148	C	1	1	60	CRACKING	9.5	9.5	8.5	7.0	6.5	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	
16						2	9.8	7000		RIDE	8.5	8.0	8.3	8.2	7.9	7.6	7.6	7.7	8.6	8.7	8.6	8.4	8.4	
LIGHTNING	STRIKE RD(	0.8C)						FC125M																
2082032			0.000		1.939	C	2007	0012		CRACKING	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.1	4.0*
PREFERRED	MATERIALS, INC.	(2008)						RIDE			8.2	8.1	8.0	8.1	8.2	8.0	8.1	8.1	8.0	8.0	8.0	7.9	7.8	7.4
71050000			2.148		4.357	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	
16						2	9.0	8000		RIDE	8.9	8.4	8.8	8.7	8.4	8.3	8.1	8.5	8.4	8.3	8.2	8.0	8.0	
MARY DOT	LN(	2.5R)						FC3																
4343191			2.148		4.357	C	2017	0012		CRACKING	8.0	8.0	7.0	7.0	7.0			10.0	10.0	10.0	10.0	10.0	9.2	7.5
ANDERSON	COLUMBIA CO., INC	(2019)						SPRIDE			7.9	7.7	7.6	7.9	8.0			8.6	8.6	8.5	8.5	8.5	8.4	8.0
71050000			4.357		10.175	R	1	1	65	CRACKING	5.5*	3.5*	3.0*	3.0*	3.0*			10.0	10.0	10.0	9.5	9.0	7.5	7.5
16						2	9.0	4100		RIDE	7.0	6.8	6.5	6.4*	5.4*			8.1	8.2	8.1	8.2	8.0	7.8	7.5
CR 16A(	4.4R)							FC5A																
4343191			4.357		10.175	R	2017	0012		CRACKING	7.5	6.5	4.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	10.0	7.5
ANDERSON	COLUMBIA CO., INC	(2019)						SPRIDE			7.3	6.7	6.2*	6.8	6.7			9.0	8.9	8.8	8.8	8.9	8.8	8.5

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = CLAY

RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR														FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS		2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKM-X-P	ASTYPE	=====	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
ITMSEG-P	W BMP	W EMP	RW	FY-F	WKM-X-F																(PMRS)		
CONTRACTOR (AGE ONE YEAR)	W BMP	W EMP	RW	FY-F	WKM-X-F																		
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																		
71050000	10.175	10.528	R	1	45	CRACKING	5.5*	3.5*	3.0*	3.0*	3.0*				10.0	10.0	10.0	10.0	10.0	8.5			
16			2	12.8	8000	RIDE	7.0	6.8	6.5	6.4*	5.4*				7.9	7.7	7.8	7.7	7.6	7.7			
SR 16(10.3C)						DGFC																	
4411291	10.130	10.489	R	2021	0012	CRACKING	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*		10.0	10.0	9.4	8.5		
DUVAL ASPHALT PRODUCTS, IN(2023)						SPRIDE	7.6	7.5	7.5	6.7	6.9	6.8	6.8	6.8	6.8	6.7		7.9	7.8	7.6	7.2		
71050000	10.528	18.140	C	1	60	CRACKING	7.0	7.0	6.5	7.0	6.5	5.5*			10.0	10.0	10.0	10.0	9.5	9.5			
16			2	12.8	8000	RIDE	8.4	7.9	7.9	7.8	7.1	6.9			8.1	8.0	8.1	8.1	8.0	7.9			
SEAMARK RANCH RD(12.7L)						FC125M																	
2082002	10.520	19.433	C	2005	0012	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	5.5*	5.5*	4.4*	1.5*		
PREFERRED MATERIALS, INC. (2007)						SPRIDE	7.9	7.8	7.8	7.6	7.6	7.5	7.5	7.5	7.5	7.4	7.4	7.3	7.2	7.1	6.7		
2082005	10.489	18.206	C	2026	0012																		
71050000	18.140	19.538	C	1	8	55	CRACKING	7.0	6.0*	5.5*	5.5*	5.5*	3.5*		10.0	10.0	10.0	10.0	9.5	9.5			
16			2	8.3	12500	RIDE	7.9	7.6	7.6	7.5	6.2*	5.9*			8.1	8.0	8.1	8.1	8.0	7.9			
GARY RD(18.4R)						DGFC																	
2082002	10.520	19.433	C	2005	0012	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0								
PREFERRED MATERIALS, INC. (2007)						SPRIDE	7.9	7.8	7.8	7.6	7.6	7.5	7.5	7.5	7.5								
71050000	19.538	20.185	C	1	55	CRACKING	7.0	6.0*	5.5*	5.5*	5.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5			
16			2	8.3	12500	RIDE	7.9	7.6	7.6	7.5	6.2*	5.9*	8.2	8.2	8.0	7.9	7.9	8.0	7.8	7.7			
CHESSER RD(19.9L)						FC1																	
2082002	19.433	20.047	C	2005	0012	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	6.0*	6.0*	5.5*	5.5*	4.3*	1.0*			
PREFERRED MATERIALS, INC. (2006)						SPRIDE	7.7	7.7	7.7	7.5	7.7	7.6	7.5	7.3	7.3	7.4	7.2	7.1	7.0	7.0	6.6		
2082005	19.086	23.614	C	2026	0012																		
71050000	20.185	21.708	C	1	55	CRACKING	7.0	6.0*	5.5*	5.5*	5.5*	3.5*			10.0	10.0	10.0	9.5	9.5	9.5			
16			2	8.3	13700	RIDE	7.9	7.6	7.6	7.5	6.2*	5.9*			8.2	7.7	8.1	8.0	8.0	7.9			
CR 315(20.4L)						FC125M																	
2082002	20.047	21.430	C	2005	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	5.5*	5.0*	5.0*	4.0*	1.0*			
PREFERRED MATERIALS, INC. (2007)						SPRIDE	7.8	7.8	7.7	7.3	7.4	7.3	7.1	7.1	7.0	7.0	6.9	6.9	6.8	6.4*			
2082005	19.086	23.614	C	2026	0012																		
71050000	21.708	22.563	R	1	45	CRACKING	3.0*	3.0*	3.0*	3.0*	2.0*	0.0*			10.0	10.0	10.0	10.0	10.0	9.5			
16			1	8.3	13700	RIDE	7.9	7.5	7.2	6.8	5.1*	5.1*			7.9	7.4	7.7	7.6	7.5	7.5			
CR 16A(21.9C)						FC125M																	
2082002	21.708	22.461	C	2005	0012	CRACKING	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	5.5*	5.5*	3.5*	2.1*	0.0*			
PREFERRED MATERIALS, INC. (2007)						SPRIDE	7.3	7.2	7.0	6.5	6.3	6.1	6.1	5.5	5.8	5.5	5.5	5.3*	5.2*	4.8*			
2082005	19.086	23.614	C	2026	0012																		
71050000	22.563	23.614	R	1	35	CRACKING	7.0	6.0*	4.0*	4.0*	3.5*	3.5*			10.0	10.0	10.0	10.0	10.0	10.0			
16			2	8.3	12500	RIDE	7.8	7.5	7.1	7.0	6.4	6.0			6.8	5.7	6.4	6.8	6.3	5.5			
HIGHLAND AVE(22.6C)						FC125M																	
2082002	22.690	23.621	C	2005	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	7.0	6.0*	6.0*	6.0*	5.5*	5.0*	2.0*		
PREFERRED MATERIALS, INC. (2007)						SPRIDE	6.1	6.1	6.0	5.5	5.5	5.6	5.3*	5.3*	4.8*	4.8*	5.1*	4.9*	4.7*	4.6*	2.2*		
2082005	19.086	23.614	C	2026	0012																		
71050000	22.563	23.614	L	1	35	CRACKING	7.0	6.0*	5.5*	5.5*	3.5*	3.5*			10.0	10.0	10.0	10.0	10.0	10.0			
16			2	8.3	12500	RIDE	7.8	7.6	7.6	7.1	6.0	5.7			8.1	7.2	7.7	7.5	7.5	7.5			
HIGHLAND AVE(22.6C)						FC125M																	
2082002	22.690	23.621	C	2005	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	7.5	7.0	7.0	6.0*	5.5*	5.2*	2.0*		
PREFERRED MATERIALS, INC. (2007)						SPRIDE	7.6	7.3	6.8	6.4	6.7	6.7	6.5	6.3	5.8	5.5	6.3	6.0	5.9	5.5			
2082005	19.086	23.614	C	2026	0012																		
71050000	21.708	22.563	L	1	45	CRACKING	3.0*	3.0*	3.0*	3.0*	2.0*	0.0*			10.0	10.0	10.0	10.0	10.0	9.5			
16			1	8.3	13700	RIDE	7.9	7.5	7.2	6.8	5.1*	5.1*			7.9	7.4	7.7	7.6	7.5	7.5			
CR 16A(21.9C)						FC125M																	
2082002	21.708	22.461	C	2005	0012	CRACKING	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	6.5	4.5*	4.5*	3.1*	0.0*			
PREFERRED MATERIALS, INC. (2007)						SPRIDE	7.3	7.2	7.0	6.5	6.3	6.1	6.1	5.5	5.8	5.9	5.7	5.7	5.7	5.3*			
2082005	19.086	23.614	C	2026	0012																		
71050000	10.175	10.528	L	1	45	CRACKING	5.5*	3.5*	3.0*	3.0*	3.0*				10.0	10.0	10.0	10.0	10.0	9.5			
16			2	12.8	8000	RIDE	7.8	7.5	7.4	7.3	6.1*				8.1	7.9	7.9	7.8	7.9	7.6			
SR 16(10.3C)						FC125M																	
4411291	10.130	10.489	L	2021	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	7.0	6.0*		10.0	10.0	9.5	8.5		
DUVAL ASPHALT PRODUCTS, IN(2023)						SPRIDE	7.6	7.4	7.4	7.1	6.6	6.8	6.8	6.8	6.6	6.6		8.2	7.8	8.1	7.7		
71050000	4.357	10.175	L	1	65	CRACKING	5.5*	3.5*	3.0*	3.0*	3.0*				10.0	10.0	10.0	9.5	9.0	7.5	6.5		
16			2	9.0	4100	RIDE	7.8	7.5	7.4	7.3	6.1*				8.0	8.3	8.1	8.2	8.0	7.9	7.5		
BARKER RD(5.2L)						FC5A																	
4343191	4.357	10.175	L	2017	0012	CRACKING	6.5	4.5*	4.5*	4.5*	4.5*				10.0	10.0	10.0	10.0	10.0	9.7	7.0		
ANDERSON COLUMBIA CO., INC(2019)						SPRIDE	7.3	6.7	6.2*	7.2	7.1				8.9	8.9	8.9	8.8	8.8	8.8	8.6		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

										DISTRICT = 2 COUNTY = CLAY																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED			YEAR																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = CLAY

RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS		2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)						SURFTYPE	=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
CONTRACTOR (AGE ONE YEAR)					ASTYPE																(PMRS)	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																	
71070000	5.677	7.314	L	1	1 45	CRACKING		3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	6.5	6.5		
21			3	6.4	48000	RIDE		8.4	8.2	8.6	8.6	8.1	7.6	8.1	8.2	8.2	8.2	8.0	8.0	7.9		
BRANAN FIELD RD(5.8L)					FC125M																	
2082117	5.677	7.124	L	2015	0213	CRACKING		6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	
HUBBARD CONSTRUCTION COMPAN(2018)					SPRIDE			7.8	7.5	7.0			8.1	7.9	7.7	7.9	7.7	7.8	7.7	7.5	7.1	
71070000	4.870	5.677	L	1	1 45	CRACKING		3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	6.5	6.5		
21			3	6.4	48000	RIDE		8.4	8.2	8.6	8.6	8.1	7.6	8.1	8.2	8.2	8.2	8.0	8.0	7.9		
ALLIE MURRAY RD(5.0L)					FC125M																	
2082119	4.824	5.677	C	2014	0213	CRACKING		6.5	6.5	6.5				10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	
(2019)					RIDE			7.8	7.5	7.0				8.3	8.3	8.3	8.3	8.3	8.2	8.1	7.7	
71070000	1.886	4.870	L	1	1 45	CRACKING		7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
21			3	6.4	35500	RIDE		8.6	8.1	8.6	8.6	8.1	7.6	8.1	8.3	8.2	8.0	8.0	7.9	7.9		
CARLSEE LN(2.2L)					FC125M																	
2082118	3.038	4.817	C	2019	0213	CRACKING		10.0	10.0	9.0	9.0	8.5	7.5	7.5					10.0	9.6	8.5	
REEVES CONSTRUCTION COMPAN(2024)					SPRIDE			7.9	7.9	7.9	7.6	7.6	7.6	7.4					8.1	8.0	7.6	
71070000	1.470	1.886	L	1	7 45	CRACKING		6.0*	5.5*	3.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0		
21			2	9.4	19699	RIDE		8.6	8.3	8.0	7.7	6.3*	5.7*		8.4	8.2	8.0	8.0	7.9	7.9		
SHOPPING CENTER(1.6L)					FC125																	
4471761	0.000	1.772	C	2023	0012	CRACKING		10.0	10.0	9.0	9.0	8.5	7.5	7.5	7.0	6.0*	6.0*	6.0*	3.5*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)					SPRIDE			7.9	7.9	7.9	7.6	7.6	7.6	7.4	7.4	7.0	6.9	6.8	6.3	7.6	7.2	
71070000	0.000	1.470	L	1	7 55	CRACKING		6.0*	5.5*	3.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0		
21			2	9.4	19699	RIDE		8.6	8.3	8.0	7.7	6.3*	5.7*		8.4	8.3	8.3	8.1	8.1	8.1		
END OF 71110000(0.0C)					FC5M																	
4471761	0.000	1.772	C	2023	0012	CRACKING		10.0	10.0	9.5	9.5	9.0	9.0	7.5	4.5*	4.5*	4.5*	1.0*	1.0*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)					SPRIDE			8.0	7.9	7.8	8.0	8.0	8.1	7.9	8.0	7.8	7.4	6.9	6.6	8.9	8.7	
71080000	0.000	2.238	C	1	1 55	CRACKING		10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	7.0	7.0	7.0	7.0	7.0		
230			2	8.1	1950	RIDE		8.8	8.3	8.7	8.5	8.0	8.0	7.9	8.0	7.8	7.9	7.8	7.4	7.2		
LIGHTENING STRIKE RD(0.7C)					FC3																	
2081901	0.000	2.238	C	1994	0225	CRACKING		7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	6.1*	1.5*	
ANDERSON COLUMBIA CO., INC(1995)					S	RIDE		7.4	7.3	7.2	7.5	7.6	7.4	7.4	7.5	7.5	7.4	7.3	7.2	7.2	6.8	
2082033	0.000	3.518	C	2027	0012																	
71080000	2.238	3.518	C	1	1 55	CRACKING																
230			2	8.1	1950	RIDE																
SCOTT AVE(2.8R)					FC3																	
						CRACKING																
						RIDE																
2082033	0.000	3.518	C	2027	0012																	
71100000	0.000	0.809	C	1	1 45	CRACKING		10.0	10.0	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	10.0		
16			2	9.1	20500	RIDE		8.5	8.1	8.0	8.1	7.7	7.5	7.5	7.5	7.8	7.9	7.8		8.5		
US-17 S/SR-15(0.0R)					FC95MR																	
2081833	0.039	0.761	C	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	7.5	6.5	5.5*	4.5*	2.0*	
PREFERRED MATERIALS, INC. (2012)					RIDE			8.2	8.1	8.3	8.0	8.0	8.0	7.9	7.5	7.5	7.5	7.1	7.0	6.9	6.5	
2081836	0.030	1.825	C	2028	0012																	
71100000	0.809	1.740	R	1	1 45	CRACKING		10.0	10.0	10.0	9.5	8.0	8.0	7.0	7.0	6.5	6.5	6.5		10.0		
16			2	9.1	20500	RIDE		8.8	8.3	8.5	8.5	7.9	7.7	7.5	7.4	7.1	7.0	6.8		8.5		
MAIN GATE ENT(1.2C)					FC95MR																	
2081833	0.910	1.586	R	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	4.5*	4.0*	4.0*	3.5*	1.0*	
PREFERRED MATERIALS, INC. (2012)					RIDE			8.5	8.5	8.4	8.2	8.1	8.1	7.9	7.8	7.7	7.5	6.9	6.7	6.5	6.1	
2081836	0.030	1.825	C	2028	0012																	
71100000	1.740	3.001	C	1	2 45	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	7.0		10.0		
16			2	9.1	20500	RIDE		8.4	8.1	8.2	8.2	8.0	7.8	7.9	8.0	7.9	7.9	7.8		8.8		
KELSEY RD(2.0L)					FC95MR																	
2081833	1.706	3.001	C	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	6.5	6.0*	3.5*	
PREFERRED MATERIALS, INC. (2012)					RIDE			8.8	8.8	8.7	8.4	8.3	8.2	8.1	8.0	8.0	7.9	7.8	7.7	7.5	7.1	
71100000	0.809	1.740	L	1	1 45	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5		10.0		
16			2	9.1	20500	RIDE		8.5	8.1	8.3	8.4	7.9	7.8	7.9	7.9	8.1	8.1	8.0	7.9		8.5	
MAIN GATE ENT(1.2C)					FC95MR																	
2081833	0.910	1.706	L	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.0	6.0*	6.0*	3.5*	
PREFERRED MATERIALS, INC. (2012)					RIDE			8.4	8.3	8.1	8.1	8.0	8.0	7.9	7.9	7.9	7.8	7.6	7.7	7.6	7.2	
2081836	0.030	1.825	C	2028	0012																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

ALL SYSTEM PAVEMENT CONDITION FORECAST

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

```

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```

ALL SYSTEM PAVEMENT CONDITION FORECAST

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

.....

```

**" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
**" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```