

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = CLAY -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	#T	ADT	RATINGS		2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM	P	ASTYPE	=====													
ITMSEG-P	(AGE_ONE YEAR)							2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR																					(PMRS)
ITMSEG-F																					
71010000	0.000	4.728	R	1	8	60	CRACKING	6.0*	4.0*	4.0*	3.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0
15 17				2	21.0	10600	RIDE	8.1	8.1	7.6	6.1*	6.7	5.6*	6.6	8.4	8.3	8.2	8.2	8.1	8.0	
CR 214(1.0R)						FC5M															
2081772	0.000	5.000	C	2007	0012		CRACKING	10.0	9.5	9.5	9.5	9.0	7.5	6.5	5.5*	3.5*	3.5*	3.5*	2.5*		
HUBBARD CONSTRUCTION COMPA(2008)							RIDE	7.9	7.9	8.2	8.2	8.3	8.2	8.3	8.2	8.1	8.0	7.9	7.7		
2081773	0.000	4.720	C	2025	0012																
71010000	4.728	7.887	R	1	1	60	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5	6.5	
15 17				2	21.0	10600	RIDE	7.7	7.8	7.4	8.0	7.6	8.0	8.2	8.2	8.2	8.0	7.9	7.7	7.7	
AIRPARK RD(4.8R)						FC5M															
4322691	4.728	10.489	C	2017	0012		CRACKING	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	9.0	9.0	9.8	9.7	7.0
ANDERSON COLUMBIA CO., INC(2019)							SPRIDE	7.4	7.3	7.8	7.8		8.8	8.8	8.8	8.8	8.9	8.9	8.9	8.8	8.6
71010000	7.887	8.660	R	1	1	60	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5	6.5	
15 17				2	21.0	10600	RIDE	7.7	7.8	7.4	8.0	7.6	8.0	8.2	8.2	8.2	8.0	7.9	7.7	7.7	
JP HALL BLVD(7.9R)						FC5M															
				(2025)			CRACKING	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0				10.0	10.0	9.0
							RIDE	7.4	7.3	7.8	7.8		8.8	8.8	8.8				8.0	7.6	7.4
71010000	8.660	10.282	R	1	1	60	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5	6.5	
15 17				2	13.0	15400	RIDE	7.7	7.8	7.4	8.0	7.6	8.0	8.2	8.2	8.2	8.0	7.9	7.7	7.7	
CR 209(9.0R)						FC5M															
4322691	4.728	10.489	C	2017	0012		CRACKING	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	9.0	9.0	8.9	9.0	6.0*
ANDERSON COLUMBIA CO., INC(2019)							SPRIDE	7.4	7.3	7.8	7.8		8.8	8.8	8.8	8.5	8.5	8.5	8.5	8.5	8.3
71010000	10.282	10.489	R	1	1	55	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5	6.5	
15 17				2	13.0	15400	RIDE	7.7	7.8	7.4	8.0	7.6	8.0	8.2	8.2	8.2	8.0	7.9	7.7	7.7	
						FC125M															
4322691	4.728	10.489	C	2017	0012		CRACKING	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	9.0	9.0	8.9	6.5	4.5*
ANDERSON COLUMBIA CO., INC(2019)							SPRIDE	7.4	7.3	7.8	7.8		8.8	8.8	8.8	8.5	8.5	8.5	8.5	7.9	7.5
71010000	10.489	10.900	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	
15 17				2	21.0	22500	RIDE	8.0	8.4	8.3	7.8	7.7	7.6	8.2	8.2	8.1	8.1	7.9	8.0	8.0	
COVE PLAZA ENT(10.6R)						FC125M															
				(2026)			CRACKING	9.0	8.5	8.5	8.5	8.5	8.5	8.0	7.0	7.0	6.0*	6.0*	5.4*	8.6	7.5
							RIDE	7.9	7.7	7.6	7.4	7.3	7.3	7.4	7.5	7.2	6.6	6.9	6.9	7.4	7.0
71010000	10.900	11.277	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	
15 17				2	21.0	22500	RIDE	8.1	8.4	8.3	7.8	7.7	7.6	8.2	8.2	8.1	8.1	7.9	8.0	8.0	
MAGNOLIA AVE(11.1C)						FC125M															
2080852	10.647	11.277	C	2006	0012		CRACKING	9.0	8.5	8.5	8.5	8.5	8.5	8.0	7.0	7.0	6.0*	6.0*	5.4*	4.5*	1.0*
J.B. COXWELL CONTRACTING,I(2007)							SPRIDE	7.9	7.7	7.6	7.4	7.3	7.3	7.4	7.5	7.2	6.6	6.9	6.9	6.7	6.3
2082025	10.905	11.277	C	2025	0012																
71010000	10.900	11.277	L	1	1	35	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	
15 17				2	21.0	22500	RIDE	7.5	7.0	7.2	7.8	7.5	7.7	7.4	7.4	7.3	7.4	7.3	7.3	7.3	
MAGNOLIA AVE(11.1C)						FC125M															
2080852	10.647	11.277	C	2006	0012		CRACKING	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.0	7.0	6.5	6.5	6.5	3.5*	0.0*
J.B. COXWELL CONTRACTING,I(2007)							SPRIDE	7.2	7.2	6.5	6.4	6.5	6.3	6.9	6.7	6.8	6.3	6.6	6.2	5.8	5.4*
2082025	10.905	11.277	C	2025	0012																
71010000	10.489	10.900	L	1	1	45	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	
15 17				2	21.0	22500	RIDE	8.3	8.4	8.5	7.8	7.5	7.7	7.4	7.4	7.3	7.4	7.3	7.3	7.3	
COOKS LN W(10.6L)						FC125M															
				(2026)			CRACKING	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.0	7.0	6.5	6.5	6.5	8.8	8.0
							RIDE	7.2	7.2	6.5	6.4	6.5	6.3	6.9	6.7	6.8	6.3	6.6	6.2	7.3	6.9
71010000	10.282	10.489	L	1	1	55	CRACKING	9.5	7.0	7.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	6.5	6.5	
15 17				2	13.0	15400	RIDE	8.8	8.7	8.6	7.7	7.8	7.8	8.0	8.0	7.8	7.8	7.8	7.8	7.6	
ENERGY COVE CT(10.3L)						FC125M															
4322691	4.728	10.489	C	2017	0012		CRACKING	6.5	6.5	5.5*	5.5*		10.0	10.0	10.0	10.0	9.0	9.0	8.9	7.0	5.0*
ANDERSON COLUMBIA CO., INC(2019)							SPRIDE	7.5	7.3	7.8	7.8		8.7	8.8	8.6	8.5	8.5	8.4	8.4	7.7	7.3
71010000	8.660	10.282	L	1	1	60	CRACKING	9.5	7.0	7.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	6.5	6.5	
15 17				2	13.0	15400	RIDE	8.8	8.7	8.6	7.7	7.8	7.8	8.0	8.0	7.8	7.8	7.8	7.8	7.6	
CLEAR HALL LN(9.2L)						FC5M															
4322691	4.728	10.489	C	2017	0012		CRACKING	6.5	6.5	5.5*	5.5*		10.0	10.0	10.0	10.0	9.0	9.0	8.9	8.7	6.0*
ANDERSON COLUMBIA CO., INC(2019)							SPRIDE	7.5	7.3	7.8	7.8		8.7	8.8	8.6	8.5	8.5	8.4	8.4	8.5	8.3

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = CLAY -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	WKM-F	ASTYPE	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	WKM-F	WKM-F	ASTYPE														(PMRS)
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F	WKM-F	ASTYPE														
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F	WKM-F	ASTYPE														
71020000	12.480	13.808	R	1	1	40	CRACKING	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	
15 17				3	7.8	60000	RIDE	8.3	7.9	8.0	6.0	7.9	7.7	7.8	7.7	7.7	7.5	7.4	7.4	7.7	
STOWE AVE(12.5C)																					
2082281	12.762	14.365	C	2003	0012		CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	8.0	7.0	7.0	7.0	5.5*	4.2*	3.9*	0.0*
HUBBARD CONSTRUCTION COMPA(2005)																					
2082283	11.321	13.817	C	2026	0012		RIDE	7.4	7.8	7.7	7.6	7.7	7.5	7.5	7.4	7.5	7.3	7.3	7.2	7.3	6.9
FC125M																					
71020000	13.808	14.365	R	1	7	40	CRACKING	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	
15 17				5	7.8	89500	RIDE	7.6	7.4	7.3	6.2	7.9	7.7	7.8	7.7	7.7	7.5	7.4	7.4	7.7	
JOHNSON AVE(14.0C)																					
							CRACKING	9.0		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5		10.0	9.0
							RIDE	7.4		7.7	7.6	7.5	7.4	7.4	7.4	7.3	7.4	6.8		8.3	7.9
(2026)																					
71020000	13.808	14.365	L	1	7	40	CRACKING	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
15 17				4	7.8	89500	RIDE	7.7	7.3	7.6	5.0*	8.0	7.8	8.0	8.0	8.0	7.9	7.9	7.8	7.8	
JOHNSON AVE(14.0C)																					
							CRACKING	9.5		10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5		10.0	9.0
							RIDE	7.8		7.7	7.8	7.8	7.6	7.6	7.7	7.4	7.7	7.3		8.4	8.0
(2026)																					
71020000	12.480	13.808	L	1	1	40	CRACKING	4.0*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	
15 17				3	7.8	60000	RIDE	8.1	7.9	7.9	5.4*	7.6	7.4	7.7	7.6	7.6	7.4	7.3	7.3	7.2	
STOWE AVE(12.5C)																					
2082281	12.762	14.365	C	2003	0012		CRACKING	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	5.5*	5.5*	3.5*	2.6*	0.0*
HUBBARD CONSTRUCTION COMPA(2005)																					
2082283	11.321	13.817	C	2026	0012		RIDE	7.3	7.1	7.5	7.3	7.4	7.3	7.3	7.2	7.1	7.0	6.5	6.7	6.9	6.5
FC125M																					
71020000	11.676	12.480	L	1	1	45	CRACKING	6.0*	5.5*	5.5*	3.5*	1.0*	1.0*	0.0*	0.0*					10.0	10.0
15 17				3	7.8	48500	RIDE	8.2	8.1	7.9	6.9	6.6	6.9	6.8	6.7					8.1	8.1
HOLLY PT W(11.8L)																					
2082071	11.682	12.192	C	2007	0213		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.0	8.0
ARCHER WESTERN CONTRACTORS(2012)																					
2082283	11.321	13.817	C	2026	0012		SPRIDE	7.9	8.1	8.2	8.2	8.2	7.9	8.1	8.1	8.0	8.1	7.9	8.0	8.0	5.0*
FC125M																					
71020000	8.650	11.321	L	1	7	50	CRACKING	10.0	9.5	9.5	8.0	7.5	6.5	6.5	3.5*	3.5*	10.0	10.0	10.0	10.0	
15 17				3	7.8	57500	RIDE	8.9	8.8	8.7	8.1	7.7	7.8	7.7	7.6	7.5	8.4	8.5	8.4	8.4	
DENMARK DR(8.7L)																					
4471801	8.594	11.321	C	2023	0012		CRACKING	10.0	10.0	10.0	10.0	9.5	9.0	7.5	6.5	4.5*	4.5*	3.5*		10.0	9.0
DUVAL ASPHALT PRODUCTS, IN(2026)																					
							SPRIDE	8.3	8.3	8.6	8.6	8.6	8.5	8.6	8.3	8.2	8.1	7.8		8.8	8.6
71020000	6.623	8.650	L	1	8	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.0
15 17				3	6.4	43163	RIDE	8.2	8.5	8.5	8.3	8.0	8.3	8.4	8.3	8.4	8.3	8.1	8.1	7.7	
VILLAGE SQUARE PKWY(6.7L)																					
4233991	6.563	8.241	L	2013	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	6.5	6.5	5.5*		
HUBBARD CONSTRUCTION COMPA(2014)																					
4433021	6.598	8.630	C	2024	0012		SPRIDE	8.4	8.4	8.5	8.6	8.6	8.5	8.6	8.6	8.4	8.4	8.2	8.1		
FC5M																					
71020000	4.735	6.623	L	1	1	55	CRACKING	9.5	8.0	8.0	7.5		10.0	10.0	10.0	9.5	9.5	9.5	8.0	7.5	
15 17				3	7.8	40000	RIDE	8.5	8.5	8.4	7.7		8.3	8.3	8.4	8.2	8.2	8.1	8.0	7.7	
TOWN CENTER BLVD(5.0L)																					
4393461	4.956	6.603	L	2019	0012		CRACKING	7.5	7.5	7.5	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	8.0
HUBBARD CONSTRUCTION COMPA(2021)																					
							SPRIDE	7.5	7.6	7.6	7.7	7.7	7.5		8.7	8.6	8.6	8.7	8.7	8.6	8.4
71020000	4.198	4.735	L	1	1	55	CRACKING	9.5	8.0	8.0	7.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	
15 17				2	7.8	40000	RIDE	8.5	8.5	8.4	7.7	7.1	6.8	6.6		8.3	8.2	8.2	8.2	8.2	
BLACK CREEK TL(4.5L)																					
4393461	4.198	4.725	L	2019	0012		CRACKING	10.0	9.5	9.0	9.0	9.0	9.0		10.0	10.0	10.0	10.0	9.1	9.1	7.0
HUBBARD CONSTRUCTION COMPA(2021)																					
							SPRIDE	8.2	8.1	8.3	8.5	8.6	8.6		8.9	8.9	8.8	8.6	8.7	8.7	8.5
71020000	1.783	3.921	L	1	1	55	CRACKING	9.5	9.5	8.0	7.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	
15 17				2	7.8	30500	RIDE	9.0	8.9	8.7	7.7	7.1	6.8	6.6		8.3	8.2	8.2	8.2	8.2	
SHEDD RD(2.3L)																					
2080853	1.239	6.563	C	2007	0012		CRACKING	10.0	9.5	9.0	9.0	9.0	6.5	5.5*	5.5*	4.5*	3.5*	3.5*	3.5*	1.0*	0.0*
HUBBARD CONSTRUCTION COMPA(2009)																					
2082025	0.000	3.921	C	2025	0012		SPRIDE	8.2	8.1	8.3	8.5	8.6	8.4	8.5	8.4	8.3	8.0	8.1	7.9	7.9	7.7
FC5M																					
71020000	1.239	1.783	L	1	1	40	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5		10.0	10.0	10.0	10.0	10.0	
15 17				2	7.8	30500	RIDE	8.5	8.6	8.6	8.3	8.1	8.1	8.4		8.1	7.9	7.5	7.6	7.9	
HARBOR RD(1.6L)																					
2080853	1.239	6.563	C	2007	0012		CRACKING	10.0	9.0	9.0	9.0	9.0	8.5	7.0	6.0*	4.5*	4.5*	4.5*	4.0*	2.7*	0.0*
HUBBARD CONSTRUCTION COMPA(2009)																					
2082025	0.000	3.921	C	2025	0012		SPRIDE	7.8	7.7	7.4	7.2	7.6	7.3	7.2	7.5	7.2	6.9	7.0	6.9	6.8	6.4

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = CLAY -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	=====	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-M	P	ASTYPE	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-M	F	ASTYPE														(PMRS)
ITMSEG-P	ITMSEG-F																				
71020000	0.000	1.239	L	1	1	35	CRACKING	8.0	7.0	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	
15 17				2	7.8	26000	RIDE	6.7	6.3	6.6	6.2	6.0	5.7	7.2	7.1	7.0	6.8	6.6	6.7	6.4	
FERRIS ST/SR-16(0.0L)																					
						FC125M															
2080852	0.000	1.239	C	2006	0012	CRACKING	9.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	5.5*	5.5*	5.0*	3.1*	0.0*
J.B. COXWELL CONTRACTING, I (2007)																					
						SPRIDE	6.5	6.5	5.8	5.7	5.6	5.3*	5.2*	5.2*	5.3*	4.9*	5.1*	5.2*	5.0*	4.6*	
2082025	0.000	3.921	C	2025	0012																

71030000	0.000	0.564	R	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	8.0	8.0	
200 301				2	29.1	24000	RIDE	9.0	9.0	8.9	8.4	8.3	8.3	8.5	8.5	8.5	8.3	8.3	8.2	7.9	
RICHARD MOSLEY RD(0.2R)																					
						LDG+TG															
4303522	0.000	5.523	C	2015	0012	CRACKING	7.0	7.0	10.0	10.0			10.0	10.0	9.0	9.0	9.0	9.0	8.3	8.1	7.5
ANDERSON COLUMBIA CO., INC(2019)																					
						RIDE	8.0	7.8	8.8	8.9			8.9	9.0	9.0	8.8	8.7	7.7	7.7	7.7	7.6

71030000	0.564	3.033	R	1	4	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	8.0	8.0	
200 301				2	29.1	24000	RIDE	9.0	9.0	8.9	8.4	8.3	8.3	8.5	8.5	8.5	8.3	8.3	8.2	7.9	
NGCS																					
						CRACKING	7.0	7.0	10.0	10.0			10.0	10.0	9.0	9.0	9.0	9.4	9.2	8.6	8.0
						RIDE	8.0	7.8	8.8	8.9			8.9	9.0	9.0	8.8	8.7	8.9	8.6	8.5	8.4
						(2024)															

71030000	3.033	3.182	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	8.0	8.0	
200 301				2	31.1	25500	RIDE	9.0	9.0	8.9	8.4	8.3	8.3	8.5	8.5	8.5	8.3	8.3	8.2	7.9	
CR 218(3.1R)																					
						FC5M															
4303521	0.116	3.510	C	2016	9924	CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	10.0	6.5	
SUPERIOR CONSTRUCTION COMP(2016)																					
						SPRIDE	8.0	7.8	8.8	8.9	9.1	8.9	9.0	9.0	8.8	8.7	8.8	8.7	7.1	6.9	

71030000	3.182	5.540	R	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	8.0	8.0	
200 301				2	31.1	25500	RIDE	9.0	9.0	8.9	8.4	8.3	8.3	8.5	8.5	8.5	8.3	8.3	8.2	7.9	
FC5M																					
						CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.2	4.5*	
						RIDE	8.0	7.8	8.8	8.9	9.1	8.9	9.0	9.0	8.8	8.7	8.8	8.7	8.9	8.9	8.7
ANDERSON COLUMBIA CO., INC(2016)																					

71030000	3.195	5.540	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0
200 301				2	31.1	25500	RIDE	8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	8.0	
FC5M																					
						CRACKING	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0			8.9	8.0	7.0
						RIDE	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9			9.0	8.9	8.7
						(2025)															

71030000	2.910	3.195	L	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	7.0	
200 301				2	31.1	25500	RIDE	8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	8.0	
FC5M																					
						CRACKING	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0			10.0	10.0	9.0
						RIDE	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9			8.0	8.1	7.9
						(2025)															

71030000	2.765	2.910	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	7.0	
200 301				2	29.1	24000	RIDE	8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	8.0	
FC5M																					
						CRACKING	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0			9.3	9.1	8.0
						RIDE	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9			8.6	8.5	8.3
						(2025)															

71030000	2.571	2.765	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	7.0	
200 301				2	29.1	24000	RIDE	8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	8.0	
FCQ																					
						CRACKING	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0			10.0	10.0	9.0
						RIDE	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9			8.7	8.5	8.3
						(2025)															

71030000	0.500	2.571	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	7.0	
200 301				2	29.1	24000	RIDE	8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	8.0	
FC5M																					
						CRACKING	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0			10.0	10.0	9.0
						RIDE	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9			8.7	8.7	8.5
						(2025)															

71030000	0.000	0.500	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	7.0	7.0	
200 301				2	29.1	24000	RIDE	8.9	8.9	8.9	8.3	8.2	8.3	8.4	8.4	8.4	8.2	8.2	8.2	8.0	
FC5M																					
						CRACKING	7.0	6.5	10.0	10.0	10.0	10.0	10.0	8.5	9.0	9.0			9.0	8.8	7.5
						RIDE	7.9	7.7	8.9	8.9	9.0	9.0	9.0	9.0	8.9	8.9			8.8	8.8	8.6
						(2025)															

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = CLAY -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	#T	AADT	RATINGS	*****	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	(AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F	*****														(PMRS)
CONTRACTOR																					
ITMSEG-F																					
71040000	0.000	0.642	R	1	1	45	CRACKING	9.5	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	
100				1	9.8	11500	RIDE	8.0	8.2	8.2	7.3	7.5	7.3	7.7	7.4	7.4	7.2	6.9	8.5	8.3	
SE 1 AVE(0.0R)						FC125M															
2081872	0.223	0.638	R	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	6.5	3.5*
PREFERRED MATERIALS, INC. (2012)						SPRIDE	8.3	8.3	8.1	8.1	8.1	8.1	8.0	8.0	8.0	7.9	7.9	7.9	7.8	7.9	7.5
71040000	0.642	0.843	R	1	1	45	CRACKING	9.5	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	
100				1	9.8	11500	RIDE	8.0	8.2	8.2	7.3	7.5	7.3	7.7	7.4	7.4	7.2	6.9	8.5	8.3	
						FC125M															
2081872	0.638	1.041	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	8.5	5.5*
PREFERRED MATERIALS, INC. (2012)						SPRIDE	8.3	8.3	8.1	8.1	8.1	8.1	8.0	8.0	8.0	7.9	7.9	7.9	7.8	7.1	6.7
71040000	0.843	2.882	R	1	1	50	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	
100				1	5.4	12500	RIDE	8.3	8.6	8.5	8.1	8.0	8.0	8.2	8.0	7.9	7.6	7.3	8.5	8.3	
CITRUS AVE(1.0R)						FC125M															
						CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	6.5	3.5*
(2012)						RIDE	8.3	8.3	8.1	8.1	8.1	8.1	8.0	8.0	8.0	7.9	7.9	7.9	7.8	7.8	7.4
71040000	2.882	5.304	C	1	1	60	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	
100				2	9.8	7200	RIDE	8.3	8.6	8.5	8.1	8.0	8.0	8.2	8.0	7.9	7.6	7.3	8.5	8.3	
3RD ST(3.0R)						FC125M															
2081872	2.882	5.304	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	7.5	7.0	5.2*	2.5*
PREFERRED MATERIALS, INC. (2012)						SPRIDE	8.3	8.3	8.1	8.1	8.1	8.1	8.0	8.0	8.0	8.1	8.1	8.0	8.0	8.0	7.6
71040000	0.843	2.882	L	1	1	50	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	
100				1	5.4	12500	RIDE	8.3	8.6	8.5	8.1	8.0	8.0	8.2	8.0	7.9	7.6	7.3	8.5	8.3	
BEREA AVE NW(0.9L)						FC125M															
						CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	6.5	3.5*
(2012)						RIDE	8.3	8.3	8.1	8.1	8.1	8.1	8.0	8.0	8.0	8.0	8.0	7.8	7.9	8.0	7.6
71040000	0.642	0.843	L	1	1	45	CRACKING	9.5	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	
100				1	9.8	11500	RIDE	8.0	8.2	8.2	7.3	7.5	7.3	7.7	7.4	7.4	7.2	6.9	8.5	8.3	
						FC125M															
2081872	0.638	1.041	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	8.5	5.5*
PREFERRED MATERIALS, INC. (2012)						SPRIDE	8.3	8.3	8.1	8.1	8.1	8.1	8.0	8.0	8.0	8.0	8.0	7.8	7.9	7.2	6.8
71040000	0.000	0.642	L	1	1	45	CRACKING	9.5	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	
100				1	9.8	11500	RIDE	8.0	8.2	8.2	7.3	7.5	7.3	7.7	7.4	7.4	7.2	6.9	8.5	8.3	
KINGS ST(0.3L)						FC125M															
2081872	0.223	0.638	L	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	6.5	3.5*
PREFERRED MATERIALS, INC. (2012)						SPRIDE	8.3	8.3	8.1	8.1	8.1	8.1	8.0	8.0	8.0	8.0	8.0	7.8	7.9	8.0	7.6
71050000	0.000	2.148	C	1	1	60	CRACKING	9.5	8.5	7.0	6.5	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	
16				2	10.4	6900	RIDE	8.0	8.3	8.2	7.9	7.6	7.6	7.7	8.6	8.7	8.6	8.4	8.4	8.2	
LIGHTNING STRIKE RD(0.8C)						FC125M															
2082032	0.000	1.939	C	2007	0012	CRACKING	10.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.1	6.5	3.0*
PREFERRED MATERIALS, INC. (2008)						RIDE	8.1	8.0	8.1	8.2	8.0	8.1	8.1	8.1	8.0	8.0	8.0	7.9	7.8	7.8	7.4
71050000	2.148	4.249	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	
16				2	8.5	7800	RIDE	8.4	8.8	8.7	8.4	8.3	8.1	8.5	8.4	8.3	8.2	8.0	8.0	7.9	
MARY DOT LN(2.5R)						FC3															
4343191	2.148	4.357	C	2017	0012	CRACKING	8.0	7.0	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.3	6.5
ANDERSON COLUMBIA CO., INC(2019)						SPRIDE	7.7	7.6	7.9	8.0			8.6	8.6	8.5	8.5	8.5	8.5	8.4	8.4	8.0
71050000	4.249	4.466	R	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	
16				2	8.5	8800	RIDE	8.4	8.8	8.7	8.4	8.3	8.1	8.5	8.4	8.3	8.2	8.0	8.0	7.9	
CR 16A(4.4R)						FC3															
4343191	4.357	10.175	R	2017	0012	CRACKING	8.0	7.0	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.3	6.5
ANDERSON COLUMBIA CO., INC(2019)						SPRIDE	7.7	7.6	7.9	8.0			9.0	8.9	8.8	8.8	8.9	8.8	8.7	8.2	7.8
71050000	4.466	10.175	R	1	1	65	CRACKING	3.5*	3.0*	3.0*	3.0*			10.0	10.0	10.0	9.5	9.0	7.5	7.5	7.5
16				2	8.5	4600	RIDE	6.8	6.5	6.4*	5.4*			8.1	8.2	8.1	8.2	8.0	7.8	7.5	7.3
AVE D(6.4R)						FC5A															
4343191	4.357	10.175	R	2017	0012	CRACKING	6.5	4.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0
ANDERSON COLUMBIA CO., INC(2019)						SPRIDE	6.7	6.2*	6.8	6.7			9.0	8.9	8.8	8.8	8.9	8.8	8.7	8.8	8.6

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = CLAY -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT	AT	(MP	SIDE)				*****															
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	-P																
CONTRACTOR	(AGE	ONE	YEAR)		AST	TYPE																
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	-F																(PMRS)
71050000	10.175	10.528	R	1	1	45	CRACKING	3.5*	3.0*	3.0*	3.0*			10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	
16				2	9.6	7300	RIDE	6.8	6.5	6.4*	5.4*			7.9	7.7	7.8	7.7	7.6	7.7	7.6		
SR 16(10.3C)																						
4411291	10.130	10.489	R	2021		0012	CRACKING	8.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*		10.0	10.0	9.4	10.0	8.5	
DUVAL ASPHALT PRODUCTS, IN(2023) DGFC SPRIDE																						
71050000	10.528	18.140	C	1	1	60	CRACKING	7.0	6.5	7.0	6.5	5.5*		10.0	10.0	10.0	10.0	9.5	9.5	9.5		
16				2	9.6	7300	RIDE	7.9	7.9	7.8	7.1	6.9		8.1	8.0	8.1	8.1	8.0	7.9	7.9		
SEAMARK RANCH RD(12.7L) FC125M																						
2082002	10.520	19.433	C	2005		0012	CRACKING	9.5	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	5.5*	5.5*	4.4*	4.0*	0.5*	
PREFERRED MATERIALS, INC. (2007) SPRIDE																						
2082005	10.489	18.206	C	2026		0012		7.8	7.8	7.6	7.6	7.5	7.5	7.5	7.4	7.4	7.3	7.2	7.1	7.1	6.7	
2082005 10.489 18.206 C 2026 0012																						
71050000	18.140	19.538	C	1	8	55	CRACKING	6.0*	5.5*	5.5*	5.5*	3.5*		10.0	10.0	10.0	10.0	9.5	9.5	9.5		
16				2	9.4	13000	RIDE	7.6	7.6	7.5	6.2*	5.9*		8.1	8.0	8.1	8.1	8.0	7.9	7.9		
GARY RD(18.4R) DGFC																						
2082002	10.520	19.433	C	2005		0012	CRACKING	9.5	8.0	8.0	8.0	8.0	7.0	7.0								
PREFERRED MATERIALS, INC. (2007) SPRIDE																						
2082005	10.489	18.206	C	2026		0012		7.8	7.8	7.6	7.6	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5		
2082005 10.489 18.206 C 2026 0012																						
71050000	19.538	20.185	R	1	1	55	CRACKING	6.0*	5.5*	5.5*	5.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5		
16				2	9.4	13000	RIDE	7.6	7.6	7.5	6.2*	5.9*	8.2	8.2	8.0	7.9	8.0	7.8	7.7	7.7		
CR 315(19.9R) FC1																						
2082002	19.433	20.047	C	2005		0012	CRACKING	9.5	8.0	8.0	8.0	8.0	8.0	7.0	6.0*	6.0*	5.5*	5.5*	4.3*	4.2*	0.5*	
PREFERRED MATERIALS, INC. (2006) SPRIDE																						
2082005	19.086	23.614	C	2026		0012		7.7	7.7	7.5	7.7	7.6	7.5	7.3	7.3	7.4	7.2	7.1	7.0	6.9	6.5	
2082005 19.086 23.614 C 2026 0012																						
71050000	20.185	20.520	R	1	1	55	CRACKING	6.0*	5.5*	5.5*	5.5*	3.5*		10.0	10.0	10.0	9.5	9.5	9.5	8.0		
16				2	9.4	14800	RIDE	7.6	7.6	7.5	6.2*	5.9*		8.2	7.7	8.1	8.0	8.0	7.9	7.8		
FC125M																						
2082002	20.047	21.430	C	2005		0012	CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	5.5*	5.0*	5.0*	4.0*	2.6*	0.0*	
PREFERRED MATERIALS, INC. (2007) SPRIDE																						
2082005	19.086	23.614	C	2026		0012		7.8	7.7	7.3	7.4	7.3	7.1	7.1	7.0	7.0	6.9	6.9	6.8	5.8*	5.4*	
2082005 19.086 23.614 C 2026 0012																						
71050000	20.520	21.209	C	1	1	55	CRACKING	6.0*	5.5*	5.5*	5.5*	3.5*		10.0	10.0	10.0	9.5	9.5	9.5	8.0		
16				2	9.4	14800	RIDE	7.6	7.6	7.5	6.2*	5.9*		8.2	7.7	8.1	8.0	8.0	7.9	7.8		
CR 315A(21.1L) FC125M																						
2082002	20.047	21.430	C	2005		0012	CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	5.5*	5.0*	5.0*	4.0*	2.1*	0.0*	
PREFERRED MATERIALS, INC. (2007) SPRIDE																						
2082005	19.086	23.614	C	2026		0012		7.8	7.7	7.3	7.4	7.3	7.1	7.1	7.0	7.0	6.9	6.9	6.8	7.0	6.6	
2082005 19.086 23.614 C 2026 0012																						
71050000	21.209	22.563	R	1	1	45	CRACKING	3.0*	3.0*	3.0*	2.0*	0.0*		10.0	10.0	10.0	10.0	10.0	9.5	9.5		
16				1	9.4	14800	RIDE	7.5	7.2	6.8	5.1*	5.1*		7.9	7.4	7.7	7.6	7.5	7.5	7.3		
CR 16A(21.2R) FC125M																						
2082002	21.708	22.461	C	2005		0012	CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	5.5*	5.5*	3.5*	2.1*	3.5*	0.0*	
PREFERRED MATERIALS, INC. (2007) SPRIDE																						
2082005	19.086	23.614	C	2026		0012		7.2	7.0	6.5	6.3	6.1	6.1	5.5	5.8	5.5	5.5	5.3*	5.2*	5.8	5.4*	
2082005 19.086 23.614 C 2026 0012																						
71050000	22.563	23.614	R	1	1	35	CRACKING	6.0*	4.0*	4.0*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0		
16				2	9.4	13000	RIDE	7.5	7.1	7.0	6.4	6.0		6.8	5.7	6.4	6.8	6.3	5.5	6.1		
HIGHLAND AVE(22.6C) FC125M																						
2082002	22.690	23.621	C	2005		0012	CRACKING	10.0	9.0	9.0	9.0	9.0	8.5	7.0	6.0*	6.0*	6.0*	5.5*	5.0*	4.0*	0.5*	
PREFERRED MATERIALS, INC. (2007) SPRIDE																						
2082005	19.086	23.614	C	2026		0012		6.1	6.0	5.5	5.5	5.6	5.3*	5.3*	4.8*	5.1*	4.9*	4.7*	4.6*	4.6*	4.2*	
2082005 19.086 23.614 C 2026 0012																						
71050000	22.563	23.614	L	1	1	35	CRACKING	6.0*	5.5*	5.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0		
16				2	9.4	13000	RIDE	7.6	7.6	7.1	6.0	5.7		8.1	7.2	7.7	7.5	7.5	7.5	7.6		
HIGHLAND AVE(22.6C) FC125M																						
2082002	22.690	23.621	C	2005		0012	CRACKING	10.0	9.0	9.0	9.0	9.0	8.5	7.5	7.0	7.0	6.0*	5.5*	5.2*	4.9*	1.5*	
PREFERRED MATERIALS, INC. (2007) SPRIDE																						
2082005	19.086	23.614	C	2026		0012		7.3	6.8	6.4	6.7	6.7	6.5	6.3	5.8	5.5	6.3	6.0	5.9	6.0	5.6	
2082005 19.086 23.614 C 2026 0012																						
71050000	21.708	22.563	L	1	1	45	CRACKING	3.0*	3.0*	3.0*	2.0*	0.0*		10.0	10.0	10.0	10.0	10.0	9.5	9.5		
16				1	9.4	14800	RIDE	7.5	7.2	6.8	5.1*	5.1*		7.9	7.4	7.7	7.6	7.5	7.5	7.3		
CR 16A(21.9C) FC125M																						
2082002	21.708	22.461	C	2005		0012	CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	6.5	4.5*	4.5*	3.1*	2.8*	0.0*	
PREFERRED MATERIALS, INC. (2007) SPRIDE																						
2082005	19.086	23.614	C	2026		0012		7.2	7.0	6.5	6.3	6.1	6.1	5.5	5.8	5.9	5.7	5.7	5.7	5.4*	5.0*	
2082005 19.086 23.614 C 2026 0012																						
71050000	10.175	10.528	L	1	1	45	CRACKING	3.5*	3.0*	3.0*	3.0*			10.0	10.0	10.0	10.0	9.5	9.5			
16				2	9.6	7300	RIDE	7.5	7.4	7.3	6.1*			8.1	7.9	7.9	7.8	7.9	7.6	7.6		
SR 16(10.3C) FC125M																						
4411291	10.130	10.489	L	2021		0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	7.0	6.0*		10.0	10.0	9.5	10.0	8.5	
DUVAL ASPHALT PRODUCTS, IN(2023) SPRIDE																						
4411291	10.130	10.489	L	2021		0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	7.0	6.0*		10.0	10.0	9.5	10.0	8.5	
DUVAL ASPHALT PRODUCTS, IN(2023) SPRIDE																						

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = CLAY -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-X-F																(PMRS)	
ITMSEG-P																						
ITMSEG-F																						
71050000	4.249	10.175	L	1	1	65	CRACKING	3.5*	3.0*	3.0*	3.0*		10.0	10.0	10.0	9.5	9.0	7.5	6.5	6.5		
16				2	8.5	4600	RIDE	7.5	7.4	7.3	6.1*		8.0	8.3	8.1	8.2	8.0	7.9	7.5	7.3		
BARKER RD(5.2L) FC5A																						
4343191	4.357	10.175	L	2017		0012	CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.7	9.6	7.0	
ANDERSON	COLUMBIA CO.,	INC(2019)					SPRIDE	6.7	6.2*	7.2	7.1		8.9	8.9	8.9	8.8	8.8	8.8	8.8	8.7	8.5	
71070000	0.000	1.470	R	1	1	55	CRACKING	4.0*	3.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
21				2	7.8	25206	RIDE	8.4	8.3	8.1	7.0	6.5		8.1	8.1	8.1	8.0	8.0	8.0	7.8	8.0	
END OF 71110000(0.0C) FC5M																						
4471761	0.000	1.772	C	2023		0012	CRACKING	10.0	9.5	9.5	9.0	9.0	7.5	4.5*	4.5*	4.5*	3.5*	1.0*	10.0	10.0	9.0	
ANDERSON	COLUMBIA CO.,	INC(2025)					SPRIDE	8.0	7.8	7.9	7.8	7.9	7.7	7.7	7.6	7.3	7.1	6.7	8.6	8.6	8.4	
71070000	1.470	1.886	R	1	1	45	CRACKING	4.0*	3.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
21				2	7.8	25206	RIDE	8.4	8.3	8.1	7.0	6.5		8.2	8.2	8.1	8.0	7.9	7.9	7.9	7.9	
BUDDINGTONS LANDING CT(1.6R) FC125																						
4471761	0.000	1.772	C	2023		0012	CRACKING	9.0	9.0	9.0	8.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*	3.5*	10.0	10.0	9.0	
ANDERSON	COLUMBIA CO.,	INC(2025)					SPRIDE	7.9	7.8	7.4	7.3	7.3	7.1	6.9	7.1	7.2	7.0	6.7	7.9	7.9	7.5	
71070000	1.886	4.870	R	1	1	45	CRACKING	6.0*	8.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
21				3	5.6	43500	RIDE	7.3	7.8	7.8	7.3	6.8		8.2	8.2	8.1	8.0	7.9	7.9	7.9	7.9	
PARSONAGE ST(2.1R) FC125M																						
2082118	3.038	4.817	C	2019		0213	CRACKING	9.0	9.0	9.0	8.5	7.5	6.0*	6.0*				10.0	9.5	10.0	9.0	
REEVES	CONSTRUCTION	COMPAN(2024)					SPRIDE	7.9	7.8	7.4	7.3	7.3	7.1	6.9				8.1	8.0	7.9	7.5	
71070000	4.870	5.090	R	1	1	45	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	7.5	6.5	6.5		
21				3	5.6	49000	RIDE	8.1	8.6	8.6	8.1	7.5	8.1	8.3	8.3	8.3	8.1	8.0	7.7	7.8	7.8	
FC125M																						
2082119	4.824	5.677	C	2014		0213	CRACKING	6.5	6.5				10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	6.0*	
(2019)							RIDE	7.5	7.5				8.3	8.0	8.0	8.2	8.2	8.1	7.8	8.2	7.8	
71070000	5.090	5.578	R	1	7	45	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	7.5	6.5	6.5		
21				3	5.6	49000	RIDE	8.1	8.6	8.6	8.1	7.5	8.1	8.3	8.3	8.3	8.1	8.0	7.7	7.8	7.8	
FC125M																						
(2026)							CRACKING	6.5	6.5				10.0	10.0	10.0	10.0	10.0	10.0	8.5	10.0	9.0	
							RIDE	7.5	7.5				8.3	8.0	8.0	8.2	8.2	8.1	7.8	8.6	8.2	
71070000	5.578	7.314	R	1	1	45	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	7.5	6.5	6.5		
21				3	5.6	49000	RIDE	8.1	8.6	8.6	8.1	7.5	8.1	8.3	8.3	8.3	8.1	8.0	7.7	7.8	7.8	
BAXLEY RD(5.8R) FC125M																						
2082117	5.677	7.124	R	2015		0213	CRACKING	6.5	6.5			10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.3	8.6	6.5	
HUBBARD	CONSTRUCTION	COMPAN(2018)					SPRIDE	7.5	7.5			8.1	7.7	7.7	7.6	7.8	7.7	7.6	7.4	7.6	7.2	
71070000	7.314	8.175	R	1	1	55	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5		10.0	10.0		
21				3	5.6	49000	RIDE	8.1	8.6	8.6	8.1	7.5	8.1	8.3	8.3	8.3	8.1		8.5	8.4		
KINGFISHER BLVD(7.7R) FC125M																						
2082112	7.137	8.071	R	2009		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	5.9*	3.0*	
RUSSELL	ENGINEERING,	INC	(2012)				SPRIDE	8.3	8.2	8.4	8.4	8.3	8.2	8.2	8.2	8.1	8.0	7.9	8.0	7.9	7.5	
71070000	8.175	12.726	R	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0		
21				3	5.6	62000	RIDE	8.2	8.2	8.3	8.0	7.6	7.9	8.0	8.0	7.9	7.9	7.8	7.8	7.8	7.8	
RAMP TO CR 220B(8.3R) FC125M																						
4286981	8.175	12.726	C	2014		0012	CRACKING	8.0		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.5	7.2	5.0*	
HUBBARD	CONSTRUCTION	COMPAN(2016)					SPRIDE	7.7		8.2	8.2	8.2	7.9	8.1	8.1	8.1	8.0	7.8	8.0	7.8	7.4	
71070000	12.726	14.498	R	1	1	45	CRACKING	9.5	9.5	9.5	9.5	9.5	8.5	7.0	6.5	6.5	6.5	10.0	10.0	10.0		
21				3	5.6	59000	RIDE	8.3	8.3	8.3	7.6	7.2	7.4	7.7	7.6	7.7	7.3	8.5	8.5	8.5		
BLAIRMORE BLVD(13.1C) FC125M																						
2082301	12.260	14.498	R	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.5	8.6	8.2	5.0*
HUBBARD	CONSTRUCTION	COMPAN(2011)					SPRIDE	8.3	8.2	8.3	8.4	8.5	8.3	8.2	8.4	8.1	8.2	8.2	8.0	8.1	7.7	
71070000	12.726	14.498	L	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	8.0	6.5	6.5	6.5	10.0	10.0	10.0		
21				3	5.6	59000	RIDE	8.3	8.4	8.4	7.7	7.6	7.7	7.7	7.8	7.7	7.4	8.6	8.5	8.5		
SPENCER RD(12.7L) FC125M																						
2082301	12.260	14.498	L	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.4	8.0	5.0*	
HUBBARD	CONSTRUCTION	COMPAN(2011)					SPRIDE	8.3	8.3	8.3	8.5	8.4	8.4	8.4	8.5	8.3	8.3	8.3	8.0	8.3	7.9	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = CLAY -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	#T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	=====															
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	=====															
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	=====															
71070000	8.175	12.726	L	1	1	45	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	8.0	8.0	8.0	8.0	
21				3	5.6		62000 RIDE	8.4	8.5	8.5	8.2	7.8	7.9	8.1	8.0	8.1	8.0	7.9	7.9	7.9		
OAK LN(8.3L)																						
4286981	8.175	12.726	C	2014		0012	CRACKING	7.0		10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	7.4	6.6	4.5*	
HUBBARD CONSTRUCTION							SPRIDE	7.9		8.1	8.2	8.2	8.0	8.1	8.1	8.0	8.0	7.8	7.9	7.8	7.4	
FC125M																						
71070000	7.314	8.175	L	1	1	55	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0		10.0	10.0		
21				3	5.6		49000 RIDE	8.2	8.6	8.6	8.1	7.6	8.1	8.2	8.2	8.2	8.0		8.6	8.5		
BEAR RUN BLVD(8.0L)																						
2082112	7.137	8.071	L	2009		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	6.5	6.5	6.5	5.4*	2.5*	
RUSSELL ENGINEERING, INC							SPRIDE	8.4	8.3	8.4	8.4	8.3	8.2	8.3	8.2	8.2	8.1	8.1	7.9	7.8	7.4	
FC125M																						
71070000	5.677	7.314	L	1	1	45	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	6.5	6.5	6.5		
21				3	5.6		49000 RIDE	8.2	8.6	8.6	8.1	7.6	8.1	8.2	8.2	8.2	8.0	8.0	7.9	7.8		
BRANAN FIELD RD(5.8L)																						
2082117	5.677	7.124	L	2015		0213	CRACKING	6.5	6.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	6.5	
HUBBARD CONSTRUCTION							SPRIDE	7.5	7.0			8.1	7.9	7.7	7.9	7.7	7.8	7.7	7.5	7.6	7.2	
FC125M																						
71070000	4.870	5.677	L	1	7	45	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	6.5	6.5	6.5		
21				3	5.6		49000 RIDE	8.2	8.6	8.6	8.1	7.6	8.1	8.2	8.2	8.2	8.0	8.0	7.9	7.8		
ALLIE MURRAY RD(5.0L)																						
							CRACKING	6.5	6.5				10.0	10.0	10.0	10.0	10.0	10.0	8.5	10.0	9.0	
							RIDE	7.5	7.0				8.3	8.3	8.3	8.3	8.3	8.2	8.1	8.4	8.0	
(2026)																						
71070000	1.886	4.870	L	1	1	45	CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
21				3	5.6		43500 RIDE	8.1	8.6	8.6	8.1	7.6	8.1	8.3	8.2	8.0	8.0	7.9	7.9	7.9		
CARLSEE LN(2.2L)																						
2082118	3.038	4.817	C	2019		0213	CRACKING	10.0	9.0	9.0	8.5	7.5	7.5					10.0	9.6	10.0	9.0	
REEVES CONSTRUCTION							SPRIDE	7.9	7.9	7.6	7.6	7.6	7.4					8.1	8.0	7.9	7.5	
FC125M																						
71070000	1.470	1.886	L	1	1	45	CRACKING	5.5*	3.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
21				2	7.8		25206 RIDE	8.3	8.0	7.7	6.3*	5.7*		8.4	8.2	8.0	8.0	7.9	7.9	7.9		
SHOPPING CENTER(1.6L)																						
4471761	0.000	1.772	C	2023		0012	CRACKING	10.0	9.0	9.0	8.5	7.5	7.5	7.0	6.0*	6.0*	6.0*	3.5*	10.0	10.0	9.0	
ANDERSON COLUMBIA CO., INC							SPRIDE	7.9	7.9	7.6	7.6	7.6	7.4	7.4	7.0	6.9	6.8	6.3	7.6	7.9	7.5	
FC125M																						
71070000	0.000	1.470	L	1	1	55	CRACKING	5.5*	3.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
21				2	7.8		25206 RIDE	8.3	8.0	7.7	6.3*	5.7*		8.4	8.3	8.3	8.1	8.1	8.1	8.1	8.0	
END OF 71110000(0.0C)																						
4471761	0.000	1.772	C	2023		0012	CRACKING	10.0	9.5	9.5	9.0	9.0	7.5	7.5	4.5*	4.5*	4.5*	1.0*	1.0*	10.0	10.0	9.0
ANDERSON COLUMBIA CO., INC							SPRIDE	7.9	7.8	8.0	8.0	8.1	7.9	7.9	8.0	7.8	7.4	6.9	6.6	8.9	8.8	8.6
FC5M																						
71080000	0.000	2.238	C	1	1	55	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	
230				2	6.7		1750 RIDE	8.3	8.7	8.5	8.0	8.0	7.9	8.0	7.8	7.9	7.8	7.4	7.2	7.4		
LIGHTENING STRIKE RD(0.7C)																						
2081901	0.000	2.238	C	1994		0225	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	6.1*	5.9*	0.5*	
ANDERSON COLUMBIA CO., INC							S RIDE	7.3	7.2	7.5	7.6	7.4	7.4	7.5	7.5	7.4	7.3	7.2	7.2	7.1	6.7	
2082033	0.000	3.518	C	2027		0012																
FC3																						
71080000	2.238	3.518	C	1	1	55	CRACKING															
230				2	6.7		1750 RIDE															
SCOTT AVE(2.8R)																						
							CRACKING					7.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	6.0*	5.6*		
							RIDE					7.6	7.5	7.4	7.5	7.4	7.3	7.4	7.3	7.2		
2082033																						
71080001	0.000	0.212	C	1	1		CRACKING															
230				2	21.0		RIDE															
FC3																						
							CRACKING															5.0*
							RIDE															5.7*

71100000	0.000	0.314	R	1	1	45	CRACKING	10.0	9.5	9.5	8.0	8.0	8.0	8.0	7.0	7.0	7.0		10.0	10.0		
16				2	8.6		20500 RIDE	8.1	8.0	8.1	7.7	7.5	6.8	7.5	7.8	7.9	7.8		8.5	8.2		
US-17 S/SR-15(0.0R)																						
2081833	0.039	0.761	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	7.5	6.5	5.5*	4.5*	8.3	5.5*	
PREFERRED MATERIALS, INC.							RIDE	8.1	8.3	8.0	8.0	8.0	7.9	7.5	7.5	7.5	7.1	7.0	6.9	6.4	6.0	
2081836	0.030	1.825	C	2028		0012																
FC125M																						

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = CLAY -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	*****	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-M	P	ASTYPE	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-P	(AGE_ONE YEAR)																				(PMRS)
CONTRACTOR																					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-M	F															
71100000	0.314	0.809	C	1	1	45	CRACKING	10.0	9.5	9.5	8.0	8.0	8.0	8.0	7.0	7.0	7.0		10.0	10.0	
16			2	8.6		20500	RIDE	8.1	8.0	8.1	7.7	7.5	6.8	7.5	7.8	7.9	7.8		8.5	8.2	
RIO VISTA CIR(0.7L) FC95MR																					
2081833	0.039	0.761	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	7.5	6.5	5.5*	4.5*	1.2*	0.0*
PREFERRED MATERIALS, INC. (2012)																					
2081836	0.030	1.825	C	2028		0012	RIDE	8.1	8.3	8.0	8.0	8.0	7.9	7.5	7.5	7.5	7.1	7.0	6.9	7.3	6.9
71100000	0.809	1.840	R	1	1	45	CRACKING	10.0	10.0	9.5	8.0	8.0	7.0	7.0	6.5	6.5	6.5		10.0	10.0	
16			2	8.6		20500	RIDE	8.3	8.5	8.5	7.9	7.7	7.5	7.4	7.1	7.0	6.8		8.5	8.5	
MAIN GATE ENT(1.2C) FC95MR																					
2081833	0.910	1.586	R	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	4.5*	4.0*	4.0*	3.5*	0.5*	0.0*
PREFERRED MATERIALS, INC. (2012)																					
2081836	0.030	1.825	C	2028		0012	RIDE	8.5	8.4	8.2	8.1	8.1	7.9	7.8	7.7	7.5	6.9	6.7	6.5	6.2	5.8
71100000	1.840	2.406	C	1	8	45	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	7.0		10.0	10.0	
16			2	8.6		20500	RIDE	8.1	8.2	8.2	8.0	7.8	7.9	8.0	7.9	7.9	7.8		8.8	8.8	
KELSEY RD(2.0L) FC95MR																					
2081833	1.706	3.001	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	6.5	6.0*		
PREFERRED MATERIALS, INC. (2012)																					
2081836	0.030	1.825	C	2028		0012	RIDE	8.8	8.7	8.4	8.3	8.2	8.1	8.0	8.0	7.9	7.8	7.7	7.5		
71100000	2.406	3.001	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	7.0		10.0	10.0	
16			2	8.6		19500	RIDE	8.1	8.2	8.2	8.0	7.8	7.9	8.0	7.9	7.9	7.8		8.8	8.8	
SUSAN DR(2.9L) FC95MR																					
2081833	1.706	3.001	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	6.5	6.0*	5.5*	2.5*
PREFERRED MATERIALS, INC. (2012)																					
2081836	0.030	1.825	C	2028		0012	RIDE	8.8	8.7	8.4	8.3	8.2	8.1	8.0	8.0	7.9	7.8	7.7	7.5	7.8	7.4
71100000	0.809	1.840	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5		10.0	10.0	
16			2	8.6		20500	RIDE	8.1	8.3	8.4	7.9	7.8	7.9	8.1	8.1	8.0	7.9		8.5	8.4	
MAIN GATE ENT(1.2C) FC95MR																					
2081833	0.910	1.706	L	2010		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.0	6.0*	6.0*	2.6*	0.0*
PREFERRED MATERIALS, INC. (2012)																					
2081836	0.030	1.825	C	2028		0012	RIDE	8.3	8.1	8.1	8.0	8.0	7.9	7.9	7.9	7.8	7.6	7.7	7.6	7.5	7.1
71110000	0.000	0.833	C	1	1	55	CRACKING	5.5*	5.5*	5.5*	5.5*	5.5*		10.0	9.5	9.5	9.5	9.5	7.5	7.0	
21			2	7.9		9900	RIDE	6.9	6.7	6.8	6.1*	6.1*		8.5	8.5	8.4	8.3	8.2	8.2	7.8	
LAKEVIEW DR(0.2L) FC125M																					
				(2022)			CRACKING	7.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	5.5*	10.0	10.0	10.0	10.0	10.0	8.5
							RIDE	7.8	7.9	7.9	7.9	7.7	7.7	7.8	7.8	8.4	8.4	8.3	8.3	8.3	7.9
71110000	4.393	6.440	C	1	1	35	CRACKING	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	9.5	9.5	8.0	8.0	
21			2	9.1		7000	RIDE	7.5	7.4	7.5	6.9	6.6		7.3	7.2	7.4	7.3	7.2	7.4	7.4	
ORCHID AVE(4.6L) FC125M																					
				(2022)			CRACKING	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	10.0	10.0	10.0	9.6	10.0	8.5
							RIDE	7.4	7.4	7.2	7.1	7.2	7.1	7.1	7.1	8.0	7.9	8.0	7.9	7.9	7.5
71110000	6.440	20.070	C	1	1	60	CRACKING	3.5*	2.5*	1.0*	1.0*		10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	
21			2	9.1		9900	RIDE	7.2	6.7	6.4*	4.8*		8.0	8.6	8.6	8.5	8.4	8.3	8.3	8.3	
WOODLAND DR(6.6L) FC125M																					
4433051	6.434	15.072	C	2022		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*		10.0	9.5	10.0	9.0
ANDERSON COLUMBIA CO., INC(2024)																					
2081836	0.030	1.825	C	2028		0012	SPRIDE	8.2	8.1	8.0	8.0	8.0	8.0	7.9	7.8	7.8		8.7	8.6	8.6	8.2
71110000	20.070	20.794	C	1	1	60	CRACKING	2.5*	2.5*	1.0*	1.0*		10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	
21			2	9.1		9900	RIDE	6.8	6.5	6.2*	5.1*		8.0	8.6	8.6	8.5	8.4	8.3	8.3	8.3	
FC125M																					
				(2020)			CRACKING	7.0	7.0	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5
							RIDE	8.2	8.1	8.0	8.0	8.0	8.0	7.5	7.5	7.5	7.3	7.4	7.5	7.4	7.0
71110000	20.794	22.698	C	1	1	60	CRACKING	2.5*	2.5*	1.0*	1.0*		10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	
21			2	9.1		9900	RIDE	6.8	6.5	6.2*	5.1*		8.0	8.6	8.6	8.5	8.4	8.3	8.3	8.3	
WEEKS RD(21.3R) FC125M																					
4433051	20.720	22.639	C	2022		0012	CRACKING	7.0	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*		10.0	9.6	10.0	9.0
ANDERSON COLUMBIA CO., INC(2024)																					
2081836	0.030	1.825	C	2028		0012	SPRIDE	8.2	8.1	8.0	8.0	8.0	8.0	8.0	7.9	7.8	7.8		8.6	8.5	8.6
71110000	22.698	26.790	C	1	1	60	CRACKING	4.0*	4.0*	4.0*	4.0*	2.0*		10.0	10.0	10.0	10.0	9.5	8.0	7.0	
21			2	9.1		8400	RIDE	8.2	8.1	7.9	6.8	6.3*		8.3	8.3	8.3	8.2	8.1	8.1	8.0	
SR 16(22.8C) FC125M																					
4411291	23.004	25.910	C	2021		0012	CRACKING	7.0	6.5	6.5	6.5	6.5	4.5*	3.5*	3.5*		10.0	10.0	9.6	10.0	8.5
DUVAL ASPHALT PRODUCTS, IN(2023)																					
2081836	0.030	1.825	C	2028		0012	SPRIDE	7.8	7.6	7.8	7.8	7.9	7.5	7.3	7.1		8.2	8.1	8.1	8.0	7.6

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

