

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = PUTNAM -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	%T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)								=====													
ITMSEG-P W_BMP W_EMP RW FY-P WKMX-P																					
CONTRACTOR (AGE_ONE YEAR) ASTYPE																					
ITMSEG-F W_BMP W_EMP RW FY-F WKMX-F																					
76010000	0.000	3.788	C	1	1	60	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	7.0	6.5	
15 17			2	4.9		6400	RIDE		8.4	8.4	8.0	7.9	7.9	7.8	7.6	7.8	7.4	7.3	7.2	7.0	
SILVER POND RD(0.4L)								FC125A													
4305511	0.000	3.788	C	2015	0012	CRACKING		6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	8.1	6.0*
HALIFAX PAVING, INC.								(2016) SPRIDE 6.8 6.4* 7.8 7.5 8.0 7.9 7.9 7.8 7.8 7.8 7.8 7.8 7.8 7.8 7.8 7.8 7.8 7.6 7.6 7.2													
76010000	3.788	4.131	R	1	1	45	CRACKING	9.5	9.5	9.5	9.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	
15 17			1	8.6		7400	RIDE	7.9	7.8	7.7	6.9	6.6	6.6	6.5	6.3	6.6	6.5	6.5	6.4	8.5	
S PROSPECT ST(3.9R)								FC125M													
(2013)								CRACKING 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 9.0 9.0 7.5 7.4 7.2 4.5* RIDE 8.4 8.4 7.9 7.9 7.9 7.9 7.9 7.7 7.7 7.9 7.4 7.6 7.7 7.6 7.3 6.9													
76010000	4.131	5.125	R	1	1	35	CRACKING	9.5	9.5	9.5	9.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	
15 17			2	8.6		7400	RIDE	7.9	7.8	7.7	6.9	6.6	6.6	6.5	6.3	6.6	6.5	6.5	6.4	7.6	
LEMON AVE(4.2C)								FC125M													
(2013)								CRACKING 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 9.0 9.0 8.5 9.0 8.9 6.0* RIDE 7.6 7.5 7.3 7.3 7.3 7.3 7.2 7.0 7.3 7.0 6.8 6.8 6.8 6.6 6.8 6.4													
76010000	5.125	5.910	R	1	1	45	CRACKING	8.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	10.0	
15 17			2	8.6		7500	RIDE	7.3	7.1	7.0	7.7	7.5	7.2	7.0	7.0	5.9	5.5	5.5	5.3*	8.0	
LAKE VIEW AVE(5.2R)								FC125M													
(2013)								CRACKING 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 9.0 9.0 8.5 9.0 8.6 6.0* RIDE 8.1 8.2 7.6 7.6 7.8 7.7 7.6 7.7 7.6 7.7 7.6 7.7 7.7 7.6 7.5 7.1													
76010000	5.910	6.358	C	1	1	60	CRACKING	8.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	10.0	
15 17			2	8.6		6600	RIDE	7.3	7.1	7.0	7.7	7.5	7.2	7.0	7.0	5.9*	5.5*	5.5*	5.3*	8.0	
MONICA LN(6.3R)								FC125M													
(2013)								CRACKING 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 9.0 9.0 8.5 9.0 8.2 5.5* RIDE 8.1 8.2 7.6 7.6 7.8 7.7 7.6 7.7 7.6 7.7 7.6 7.7 7.7 7.6 7.7 7.3													
76010000	6.358	12.380	C	1	1	60	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	8.0	9.0	9.0	9.0	9.0	9.0	9.0	
15 17			2	8.6		5900	RIDE	7.6	7.6	7.6	7.1	7.1	7.0	7.0	8.1	8.3	8.2	8.2	8.1	8.0	
R A BILL LN(6.4R)								FC125M													
2100212	8.353	12.398	C	2007	0012	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.0	6.0*	2.5*
P & S PAVING, INC.								(2008) RIDE 8.0 7.6 7.8 7.6 7.8 7.7 7.7 7.7 7.7 7.7 7.6 7.6 7.6 7.5 7.4 7.0													
76010000	12.380	17.496	C	1	1	60	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	8.5	8.0	7.0	7.0	7.0	
15 17			2	8.6		6400	RIDE	8.8	8.7	8.8	8.2	8.2	8.1	8.0	7.2	8.0	7.7	7.6	7.6	7.4	
FEAGLE AVE(12.4R)								FC125													
4305521	12.380	17.496	L	2016	0012	CRACKING		7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.3	6.5
HALIFAX PAVING, INC.								(2018) SPRIDE 7.3 6.6 7.3 8.5 8.3 8.2 8.1 8.2 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 8.0 7.9 7.5													
76010000	17.496	19.548	C	1	1	45	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	
15 17			2	8.6		12000	RIDE	7.7	7.7	7.6	7.0	7.3	6.9	7.1	6.9	7.2	6.8	7.9	7.8	7.8	
LAKE MYRA LN(17.5R)								FC125M													
2099583	18.357	19.648	C	2009	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.1	8.0	5.0*
ANDERSON COLUMBIA CO., INC								(2011) SPRIDE 7.8 7.2 7.4 7.6 7.6 7.4 7.4 7.4 7.4 7.4 7.4 7.3 7.3 7.1 7.3 7.3 6.9													
76010000	19.548	20.048	R	1	1	45	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	
15 17			2	8.6		12000	RIDE	7.7	7.7	7.6	7.0	7.3	6.9	7.1	6.9	7.2	6.8	7.9	7.8	7.8	
HOOT OWL RD(19.7R)								FC5M													
(2011)								CRACKING 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 9.0 9.0 8.5 8.3 8.5 3.5* RIDE 7.8 7.2 7.4 7.6 7.6 7.4 7.4 7.4 7.4 7.4 7.4 7.3 7.3 7.3 7.3 7.3 7.3 7.3 7.3 7.3 7.1													
76010000	20.560	21.916	R	1	1	45	CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	10.0	10.0	10.0	
15 17			2	8.6		12000	RIDE	7.5	7.4	8.4	7.7	8.2	8.1	8.0	7.4	7.4	7.0	8.2	8.1	8.1	
SAN MATEO RD(20.7R)								FC5M													
4354441	19.826	21.682	C	2018	0213	CRACKING		10.0	10.0	10.0							10.0	10.0	9.4	8.6	7.0
GLF CONSTRUCTION CORPORATI								(2023) SPRIDE 8.1 7.7 7.9 8.1 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.4 7.2													
76010000	21.916	23.667	R	1	1	55	CRACKING	9.5	9.5	9.5	9.5	8.0	8.0	8.0	7.0	7.0	7.0	10.0	10.0	10.0	
15 17			2	8.6		16500	RIDE	7.5	7.4	7.9	7.6	7.3	6.8	7.1	6.7	6.8	7.0	8.2	8.1	8.1	
TROPIC AVE(22.0R)								FC5A													
(2019)								CRACKING 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 9.3 10.0 7.0 RIDE 8.1 7.7 7.9 8.5 8.3 8.1 8.1 8.1 8.5 8.5 8.4 8.5 8.3 8.5 8.3													

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN - 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = PUTNAM -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT	AT	(MP		SIDE)			SURFTYPE	=====														
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	P	ASTYPE															
CONTRACTOR	(AGE_ONE	YEAR)						2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F																
76010000	23.667	26.336	R	1	1	55	CRACKING	9.5	8.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	
15 17			2	12.4		20673	RIDE	8.7	8.6	8.5	7.6	7.5	7.1	8.0	7.6	8.0	7.8	7.8	7.7	7.6		
BOUNDARY RD N R(23.7R)																						
4391151	23.667	26.313	C	2023		0012	CRACKING	9.0	9.0	7.0	7.0	6.5	4.5*	4.5*	4.5*	3.5*	3.5*	1.0*	10.0	10.0	9.0	
HALIFAX PAVING, INC.				(2025)			SPRIDE	7.4	7.3	7.9	7.8	8.1	7.9	8.0	7.9	7.8	7.5	7.3	8.5	8.3	8.1	
76010000	26.336	27.821	R	1	1	40	CRACKING	9.5	8.0	9.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	10.0		
15 17			2	8.6		38000	RIDE	8.7	8.6	8.7	7.6	7.5	7.1	8.1	7.2	7.9	7.7	7.8	7.7	7.8		
RAMP TO SR 207(26.5R)																						
4269591	26.621	27.821	R	2012		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.1	8.0	5.5*	
HALIFAX PAVING, INC.				(2013)			SPRIDE	7.7	7.4	7.0	7.0	7.0	6.9	6.8	6.9	6.8	6.8	6.8	6.8	6.8	6.8	6.4
76010000	28.583	29.284	R	1	1	35	CRACKING	9.0	9.0	6.0*	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
15 17			2	8.6		38000	RIDE	7.6	7.3	7.4	6.5	6.3	5.8	5.9	6.5	7.5	7.4	7.3	7.2	7.1		
FIRST ST(28.6R)																						
2099492	28.672	30.366	C	2006		0012	CRACKING	9.5	9.5	9.5	9.5	9.5	8.0	7.0	6.0*	6.0*	6.0*	5.5*	4.6*	1.0*	0.0*	
P & S PAVING, INC.				(2008)			RIDE	7.1	6.6	7.0	7.1	7.2	7.0	7.0	6.9	6.8	6.7	6.7	6.5	6.1	5.7	
2100262	28.601	30.366	C	2026		0012																
76010000	29.284	30.366	R	1	1	35	CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
15 17			2	8.6		27000	RIDE	7.0	6.6	6.7	7.1	7.3	6.4	6.4	6.5	7.5	7.4	7.3	7.2	7.1		
11TH ST(29.3C)																						
2099492	28.672	30.366	C	2006		0012	CRACKING	9.5	9.5	9.5	9.5	9.5	8.0	7.0	6.0*	6.0*	6.0*	5.5*	4.6*	4.7*	1.5*	
P & S PAVING, INC.				(2008)			RIDE	7.1	6.6	7.0	7.1	7.2	7.0	7.0	6.9	6.8	6.7	6.7	6.5	6.4	6.0	
2100262	28.601	30.366	C	2026		0012																
76010000	28.583	30.366	L	1	1	35	CRACKING	4.5*	1.0*	1.0*	10.0	10.0	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
15 17			2	8.6		27000	RIDE	6.6	6.6	6.4	7.5	7.3	6.7	6.3	7.5	7.3	7.3	7.3	7.2	7.2		
FIRST ST L(28.6L)																						
2099492	28.672	30.366	C	2006		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.0	6.0*	6.0*	6.0*	5.7*	5.0*	1.5*	
P & S PAVING, INC.				(2008)			RIDE	7.2	6.5	6.9	6.6	7.0	7.0	6.9	6.9	6.9	6.8	6.6	6.5	6.4	6.0	
2100262	28.601	30.366	C	2026		0012																
76010000	26.336	27.821	L	1	1	40	CRACKING	9.0	7.5	9.5	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0		
15 17			2	8.6		38000	RIDE	8.4	8.3	8.7	7.8	7.7	7.6	7.8	7.7	7.8	7.5	7.4	7.2	7.8		
BROWNING LN(26.8L)																						
4269591	26.621	27.821	L	2012		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.6	8.2	5.5*	
HALIFAX PAVING, INC.				(2013)			SPRIDE	7.8	7.8	7.2	7.2	7.1	7.0	6.9	6.9	6.8	6.8	6.8	6.8	6.7	6.3	
76010000	23.667	26.336	L	1	1	55	CRACKING	9.0	7.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.0		
15 17			2	12.4		20673	RIDE	8.4	8.3	8.0	7.8	7.7	7.6	7.9	7.7	8.0	7.6	7.7	7.5	7.6		
CEDAR ST(23.8L)																						
4391151	23.667	26.313	C	2023		0012	CRACKING	9.0	9.0	7.0	7.0	6.5	4.5*	4.5*	4.5*	3.5*	3.5*	1.0*	10.0	10.0	9.0	
HALIFAX PAVING, INC.				(2025)			SPRIDE	7.3	7.1	7.8	7.8	8.0	7.8	7.9	7.8	7.5	7.3	7.0	8.7	8.4	8.2	
76010000	21.682	23.667	L	1	1	55	CRACKING	9.5	9.5	9.5	9.5	8.0	8.0	8.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	
15 17			2	8.6		16500	RIDE	7.5	7.4	7.9	7.6	7.3	6.8	7.1	6.7	6.8	7.0	8.2	8.1	8.1		
WHITE OAKS TR(21.7L)																						
				(2019)			CRACKING	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	5.5*
							RIDE	8.1	7.7	7.9			8.4	8.4	8.4	8.4	8.3	8.3	8.3	8.2	8.0	
76010000	20.560	21.682	L	1	1	45	CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	
15 17			2	8.6		12000	RIDE	7.5	7.4	8.4	7.7	8.2	8.1	8.0	7.4	7.4	7.0	8.2	8.1	8.1		
DUNNS CREEK RD(20.7L)																						
4354441	19.826	21.682	C	2018		0213	CRACKING	10.0	10.0	10.0							10.0	10.0	9.0	9.0	7.5	
GLF CONSTRUCTION CORPORATI				(2023)			SPRIDE	8.1	7.7	7.9							7.9	7.9	7.8	7.8	7.6	
76010000	19.548	20.048	L	1	1	45	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0		
15 17			2	8.6		12000	RIDE	7.7	7.7	7.6	7.0	7.3	6.9	7.1	6.9	7.2	6.8	7.9	7.8	7.8		
DUNNS CREEK RD S(19.9L)																						
				(2011)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.3	8.5	3.5*	
							RIDE	7.8	7.2	7.4	7.6	7.6	7.4	7.4	7.4	7.4	7.3	7.3	7.3	7.4	7.2	
76010000	4.131	5.125	L	1	1	35	CRACKING	9.5	9.5	9.5	9.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	10.0		
15 17			2	8.6		7400	RIDE	7.9	7.8	7.7	6.9	6.6	6.6	6.5	6.3	6.6	6.5	6.5	6.4	7.9		
LEMON AVE(4.2C)																						
				(2013)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.8	8.6	6.0*	
							RIDE	7.8	7.6	7.3	6.7	7.4	7.2	7.0	7.2	6.9	6.8	6.8	6.6	6.6	6.2	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = PUTNAM -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	*****	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F	ASTYPE	*****														(PMRS)	
ITMSEG-P	ITMSEG-F																					
76010000	3.788	4.131	L	1	1	45	CRACKING	9.5	9.5	9.5	9.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	10.0		
15 17				1	8.6	7400	RIDE	7.9	7.8	7.7	6.9	6.6	6.6	6.5	6.3	6.6	6.5	6.5	6.4	8.5		
CRESCENT CITY CITY LIMIT(3.9L) FC125M																						
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.4	7.8	5.0*
							RIDE	8.4	8.4	7.9	7.9	7.9	7.7	7.7	7.9	7.9	7.4	7.6	7.7	7.6	7.4	7.0

76020000	0.000	7.324	C	1	1	60	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	
19			2	20.4	4000	RIDE	9.0	9.0	9.0	8.5	8.5	8.5	8.6	8.4	8.1	8.1	8.1	8.1	7.8	7.5	7.6	
FOREST RD #62(2.1R) FC125A																						
							CRACKING	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.6	6.5	
							SPRIDE	7.3	6.7	7.5		8.5	8.4	8.3	8.2	8.0	7.8	7.7	7.6	7.6	7.2	

76020000	7.587	11.123	C	1	1	60	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	
19			2	9.1	4200	RIDE	9.1	9.0	8.9	8.7	8.5	8.5	8.4	8.1	8.0	8.0	8.0	7.7	7.4	7.2		
CARAVELLE WMA(10.2R) FC125M																						
							CRACKING	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.5	6.5	
							SPRIDE	7.2	7.1	7.3		8.5	8.4	8.2	8.1	8.0	7.9	7.9	7.9	7.9	7.5	

76020000	11.630	18.885	C	1	7	60	CRACKING	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0		
19			2	9.1	4200	RIDE	7.6	7.6	8.8	8.4	8.3	8.2	8.2	8.2	8.2	8.1	8.0	7.9	7.8			
TO CR 310(11.7L) FC125M																						
							CRACKING	9.0	9.0	9.0	9.0	9.0	8.0	8.0	6.5	4.0*	4.0*	4.0*	4.0*	10.0	9.0	
							SPRIDE	7.7	7.3	7.2	7.4	7.7	7.6	7.6	7.6	7.4	7.3	7.3	7.3	8.4	8.0	

76020000	18.885	19.725	R	1	7	55	CRACKING	9.0	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0		
19			1	9.1	10400	RIDE	7.9	7.6	8.8	8.4	8.3	8.2	8.2	8.2	8.2	8.1	8.0	8.0	7.9	7.8		
HORSEMAN CLUB RD(19.0C) FC125M																						
							CRACKING	9.0	9.0	9.0	9.0	9.0	8.0	8.0	6.5	4.0*	4.0*	4.0*	4.0*	10.0	9.0	
							SPRIDE	7.7	7.3	7.2	7.4	7.7	7.6	7.6	7.6	7.4	7.3	7.3	7.3	8.3	7.9	

76020000	19.725	20.695	R	1	1	45	CRACKING	9.0	7.5	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	7.0		
19			2	9.1	10400	RIDE	7.9	7.6	8.8	7.5	7.4	7.1	7.3	6.9	7.0	6.7	6.8	6.6	6.3			
RELLIM DR(19.9R) FC125M																						
							CRACKING	7.0	7.0	6.5	6.5	5.0*		10.0	10.0	10.0	10.0	10.0	9.7	10.0	8.5	
							SPRIDE	6.3	6.2	5.3*	5.5	5.7		7.9	7.9	7.8	7.6	7.6	7.5	7.7	7.3	

76020000	20.695	22.028	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	8.5	8.0	6.5		
19			3	9.1	21500	RIDE	8.0	7.9	7.9	7.9	7.7	7.6	7.6	7.6	7.6	7.5	7.5	7.2	7.1	7.1		
FROM CRILL AVE(20.7R) FC125M																						
							CRACKING	6.5	6.5	6.5	5.5*	5.5*		10.0	10.0	10.0	10.0	10.0	9.1	10.0	8.5	
							SPRIDE	7.1	7.1	7.0	7.0	7.0	8.0	8.0	7.9	7.8	7.8	7.8	7.8	7.8	7.4	

76020000	22.028	22.964	R	1	1	45	CRACKING	8.0	7.0	7.0	7.0	6.5	3.5*	3.5*	1.0*	1.0*	1.0*	10.0	10.0	10.0		
19			2	9.1	8500	RIDE	8.5	8.1	8.3	7.7	7.4	7.4	7.6	7.3	6.9	7.2	7.2	7.8	7.7	7.7		
TOWLES RD W(22.3R) FC125M																						
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	8.0	8.0	8.0	7.0	5.8*	3.0*	
							RIDE	7.7	7.4	7.3	7.3	7.6	7.5	7.4	7.5	7.3	7.3	7.1	7.0	7.3	6.9	

76020000	22.028	22.964	L	1	1	45	CRACKING	9.5	8.0	8.0	7.0	6.5	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0		
19			2	9.1	8500	RIDE	8.1	8.2	8.0	7.5	7.0	7.0	7.0	7.2	7.4	7.3	7.2	8.1	7.9	7.9		
ORIE GRIFFIN BLVD(22.8L) FC125M																						
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.9	7.5	4.5*	
							RIDE	7.9	7.1	7.4	6.9	7.8	7.8	7.7	7.7	7.6	7.3	7.5	7.4	7.4	7.0	

76020000	20.584	22.028	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0		
19			3	9.1	21500	RIDE	7.7	8.0	8.1	7.6	7.3	7.3	7.2	7.4	7.6	7.5	7.2	7.2	7.2	7.0		
SR-20/CRILL AVE(20.7C) FC125M																						
							CRACKING	8.0	8.0	7.0	6.5	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	
							SPRIDE	7.3	7.1	6.9	6.4	7.2		7.9	7.8	7.8	7.7	7.7	7.7	7.6	7.2	

76020000	19.725	20.584	L	1	1	45	CRACKING	9.0	7.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	8.0		
19			2	9.1	10400	RIDE	7.9	7.6	8.8	7.7	7.6	7.6	7.6	7.3	7.5	7.4	7.6	7.6	7.0	7.3		
NICOLE DR(19.8L) FC125M																						
							CRACKING	8.0	8.0	8.0	8.0	8.0		10.0	10.0	10.0	10.0	10.0	9.3	10.0	8.5	
							SPRIDE	7.3	7.0	7.0	6.5	7.0		8.0	8.0	7.9	8.0	7.9	7.9	7.9	7.5	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = PUTNAM -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE	
SR	US	G_BMP	G_EMP	LN	WT	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	
INTERSECT AT (MP SIDE)							*****														
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	P		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
CONTRACTOR (AGE_ONE YEAR)					ASTYPE																(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	F															
76030000	0.000	1.234	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
15 17				2	13.4		8800 RIDE	8.0	7.8	7.8	7.1	6.8	6.3	6.2	8.1	8.0	7.5	7.5	7.3	7.0	
PALATKA CITY LIMITS(0.0C) FC125M																					
2100204	0.000	1.298	C	2006	0012		CRACKING	10.0	10.0	9.0	8.5	8.5	7.5	7.5	7.5	7.5	7.5	6.5	6.5	4.5*	1.0*
P & S PAVING, INC. (2008) RIDE																					
2100262	0.000	1.214	C	2026	0012			7.2	7.0	7.2	7.3	7.0	7.2	7.1	7.1	7.1	6.9	6.7	6.7	6.6	6.2
76030000 1.234 3.020 R 1 1 60 CRACKING 10.0 10.0 10.0 9.5 9.5 8.0 7.5 7.5 7.5 7.5 7.5 10.0 10.0 10.0																					
15 17 2 13.4 13000 RIDE 8.6 8.6 8.4 8.1 8.0 7.9 7.9 7.6 7.5 7.5 8.0 8.0 7.9																					
COMFORT RD(1.5R) FC5M																					
2100205	1.298	4.540	R	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	7.5	6.5	5.5*	0.5*
ANDERSON COLUMBIA CO., INC(2011) RIDE 8.0 8.1 8.2 8.2 8.4 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.2 8.0																					
76030000 3.391 4.525 R 1 1 60 CRACKING 10.0 10.0 10.0 10.0 10.0 9.0 9.0 9.0 7.5 7.5 10.0 10.0 10.0																					
15 17 2 13.4 14300 RIDE 8.6 8.6 8.5 8.1 8.1 8.0 8.0 7.7 7.7 7.6 8.0 8.0 8.0																					
CR-209/W RIVER RD(4.4R) FC5M																					
2100205	1.298	4.540	R	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	7.5	7.8	7.1	2.0*
ANDERSON COLUMBIA CO., INC(2011) RIDE 8.1 7.8 8.3 8.2 8.4 8.3 8.3 8.3 8.3 8.3 8.4 8.3 8.3 8.3 8.4 8.3 8.3 8.3 8.3 8.3 8.1																					
76030000 4.525 13.427 R 1 1 60 CRACKING 9.5 8.0 8.0 7.5 7.5 5.5* 5.5* 10.0 10.0 10.0 10.0 10.0 10.0																					
15 17 2 13.4 10900 RIDE 8.8 8.7 8.6 8.0 7.9 7.8 7.6 8.3 8.4 8.3 8.2 8.1 8.1																					
SEMINOLE ELEC(6.7R) FC5M																					
4432721	4.510	13.427	C	2022	0012		CRACKING	9.5	9.5	8.0	8.0	7.5	6.5	4.5*	4.5*	1.0*	1.0*	10.0	10.0	10.0	8.5
DUVAL ASPHALT PRODUCTS, IN(2024) SPRIDE 8.1 7.8 8.2 8.1 8.4 8.3 8.2 8.2 7.9 7.6 9.1 9.1 9.0 9.0 8.8																					
76030000 4.525 13.427 L 1 1 60 CRACKING 5.5* 4.5* 4.5* 4.5* 4.5* 4.5* 3.5* 10.0 10.0 10.0 10.0 10.0 9.5																					
15 17 2 13.4 10900 RIDE 8.8 8.7 8.5 7.6 7.4 7.2 7.1 8.2 8.4 8.2 8.2 8.0 8.0																					
GORDON WILKINSON RD(5.0L) FC5M																					
4432721	4.510	13.427	C	2022	0012		CRACKING	8.0	8.0	7.0	7.0	6.5	4.5*	4.5*	3.5*	0.0*	0.0*	10.0	10.0	10.0	8.5
DUVAL ASPHALT PRODUCTS, IN(2024) SPRIDE 7.9 7.6 8.1 7.9 8.1 7.8 7.7 7.4 6.7 6.4* 9.1 9.0 8.8 8.6																					
76030000 3.391 4.525 L 1 1 60 CRACKING 10.0 10.0 9.5 9.0 9.0 8.0 8.0 8.0 7.5 7.5 10.0 10.0 10.0																					
15 17 2 13.4 14300 RIDE 7.7 8.5 8.5 8.0 8.1 7.8 7.8 7.3 7.2 7.2 8.1 8.1 8.1																					
POOR FARM RD(3.5L) FC5M																					
2100205	1.298	4.540	L	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	6.5	6.5	6.5	6.5	6.5	1.5*
ANDERSON COLUMBIA CO., INC(2011) RIDE 8.1 8.0 8.2 8.2 8.4 8.3 8.4 8.3 8.1 8.3 8.4 8.3 8.3 8.3 8.4 8.3 8.3 8.3 8.2 8.0																					
76030000 1.234 3.020 L 1 1 60 CRACKING 10.0 10.0 10.0 10.0 9.5 8.0 7.5 5.5* 5.5* 5.5* 10.0 10.0 10.0																					
15 17 2 13.4 13000 RIDE 7.7 7.9 7.7 7.4 7.5 7.4 7.1 7.3 7.4 6.7 8.1 8.0 8.0																					
DOOR LITE RD(2.0L) FC5M																					
2100205	1.298	4.540	L	2010	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	6.5	6.5	6.5	1.5*
ANDERSON COLUMBIA CO., INC(2011) RIDE 7.9 7.9 8.2 8.2 8.4 8.3 8.3 8.4 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.3 8.2 8.0																					
76030000 0.000 1.234 L 1 1 45 CRACKING 10.0 10.0 10.0 10.0 9.5 8.0 7.5 10.0 10.0 10.0 10.0 10.0																					
15 17 2 13.4 8800 RIDE 7.7 7.9 7.7 7.4 7.5 7.4 7.1 7.8 7.9 7.4 7.4 7.2 7.0																					
MISSING DESCRIPTION I(0.0L) FC125M																					
2100204	0.000	1.298	C	2006	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	7.5	7.5	6.9	7.0	3.5*
P & S PAVING, INC. (2008) RIDE 7.2 6.5 7.2 7.1 7.1 7.1 7.1 7.0 6.8 6.8 6.6 6.4 6.0																					
2100262 0.000 1.214 C 2026 0012																					
76040000 0.000 6.093 C 1 1 60 CRACKING 0.0* 10.0 10.0 10.0 10.0 10.0 10.0 9.0 9.0 9.0 9.0 9.0 8.0																					
20 2 12.3 6000 RIDE 7.5 8.3 8.3 7.8 7.9 7.9 7.8 7.6 7.9 7.7 7.6 7.5 7.3																					
SR 15(0.0C) FC125M																					
4454191	0.872	6.093	C	2024	0012		CRACKING	8.0	8.0	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	10.0	9.0
P & S PAVING, INC. (2025) SPRIDE 7.6 6.9 7.3 7.4 7.3 7.1 7.1 7.2 6.9 6.8 6.7 8.5 8.3 7.9																					
76050000 0.000 5.929 R 1 1 50 CRACKING 9.0 9.0 9.0 6.5 6.5 6.5 6.5 6.0* 5.5* 5.5* 5.5* 5.5* 3.5*																					
20 2 4.2 8900 RIDE 7.7 7.5 7.4 7.1 6.9 6.7 6.6 6.4* 6.4* 5.9* 6.0* 5.8* 5.7*																					
SE 65 LN(0.0R) FC125M																					
2100244	2.181	7.325	C	2020	0213		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	7.5				10.0	9.2	10.0	9.0
(2024) RIDE 8.7 7.9 8.0 7.7 8.1 8.0 8.0																					
76050000 7.111 7.516 R 1 1 50 CRACKING 9.0 9.0 9.0 6.5 6.5 6.5 6.5 6.0* 5.5* 5.5* 5.5* 5.5* 3.5*																					
20 2 4.2 8900 RIDE 7.7 7.5 7.4 7.1 6.9 6.7 6.6 6.4* 6.4* 5.9* 6.0* 5.8* 5.7*																					
MARTHA DR(7.4R) FC125M																					
2100244	2.181	7.325	C	2020	0213		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	7.5				10.0	10.0	10.0	9.0
(2024) RIDE 8.7 7.9 8.0 7.7 8.1 8.0 8.0																					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = PUTNAM -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	FW	FY-P	WKM	WKM	*****														
ITMSEG-P	(AGE_ONE	YEAR)	ASTYPE																		
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM	WKM	*****	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-F																					
76050000	7.516	11.038	R	1	1	50	CRACKING	7.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*
20				2	4.2	8900	RIDE	7.3	6.6	6.7	6.8	6.8	6.7	6.6	6.3*	6.6	6.1*	6.4*	6.1*	5.4*	
LADY SLIPPER LAKE RD(7.7R)							FC125M														
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5
							RIDE	8.7	7.9	8.0	7.7	8.1	8.0	8.0			7.6	7.6	7.6	7.5	7.1
							(2023)														
76050000	11.038	15.892	R	1	1	50	CRACKING	2.0*	2.0*	2.0*	10.0	9.0	9.0	8.0				10.0	10.0	10.0	
20				2	8.7	13264	RIDE	7.4	7.7	7.6	7.9	7.8	7.6	7.5				8.6	8.6	8.5	
WILLIAMS DR(11.2R)							FC125														
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.0	8.5	5.5*
							RIDE	8.5	7.7	7.3	7.6	8.0	7.9	7.9	7.9	7.8	7.9	7.8	7.8	7.8	7.4
							(2011)														
76050000	15.892	20.430	R	1	1	65	CRACKING	2.0*	2.0*	2.0*	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
20				2	8.7	13264	RIDE	7.4	7.7	7.6	7.9		8.1	8.2	8.0	8.1	8.2	8.2	8.1	8.1	
DIV OF FORESTRY(16.4R)							FC5														
2099991	15.896	20.308	C	2003	0213	CRACKING	9.5	9.5	9.5	9.5	8.0	8.0	8.0	8.0	4.5*	4.5*	4.5*	4.5*	3.5*	0.0*	
ANDERSON COLUMBIA CO., INC(2006)							SPRIDE	8.1	7.9	7.8	7.8	7.9	7.9	7.9	7.8	7.8	7.8	7.8	7.7	7.5	
76050000	20.430	23.740	R	1	1	50	CRACKING	5.5*	5.5*	5.5*			10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	
20				2	4.2	20300	RIDE	7.8	7.7	7.5			8.1	7.9	7.8	8.1	7.8	7.8	7.7		
RADCLIFF RD(20.6R)							FC125M														
2100041	19.977	23.746	C	2002	0213	CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	6.0*	6.0*	5.5*	4.7*	4.2*	0.5*	
ANDERSON COLUMBIA CO., INC(2006)							RIDE	7.7	7.3	7.3	7.3	7.4	7.3	7.3	7.3	7.2	7.2	7.1	7.1	7.0	
76050000	23.740	24.600	R	1	1	45	CRACKING	5.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
20				2	4.2	19700	RIDE	6.2*	6.5	6.4*	5.9*	5.8*	7.7	7.7	7.9	7.7	7.9	8.0	7.9	7.8	
FLORIDA DR(23.8R)							FC95														
2100044	23.758	24.554	C	2004	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	8.0	8.0	8.0	7.0	7.0	5.9*	6.5	3.0*	
ANDERSON COLUMBIA CO., INC(2006)							RIDE	7.7	7.4	7.0	6.8	7.1	6.8	7.0	6.7	6.5	6.4	6.4	6.8	6.7	
2100047	23.735	24.503	R	2027	0012																
76050000	24.600	25.771	R	1	1	35	CRACKING	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	
20				1	4.2	19700	RIDE	5.7*	5.7	5.6	5.1*	5.1*	7.6	7.0	6.8	7.2	6.9	6.3	6.2	6.5	
SIDE ROAD ()(24.8C)							FC125M														
4390801	24.786	25.734	R	2020	0012	CRACKING	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	9.4	9.0	7.5	
HALIFAX PAVING, INC.							SPRIDE	6.0	5.9	5.7	5.3*	5.7	5.6	5.3*	6.6	6.3	6.3	6.3	6.2	6.3	
76050000	25.771	26.320	C	1	1	25	CRACKING	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	
20				2	4.2	15500	RIDE	5.7*	5.7	5.6	5.1*	5.1*	7.6	7.0	6.8	7.2	6.9	6.3	6.2	6.5	
OSCEOLA ST(25.9R)							FC95														
							CRACKING	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	9.4	10.0	
							RIDE	6.0	5.9	5.7	5.3*	5.7	5.6	5.3*	6.6	6.3	6.3	6.3	6.2	5.3*	
							(2021)														
76050000	23.740	24.600	L	1	1	45	CRACKING	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	
20				2	4.2	19700	RIDE	6.7	6.8	7.2	6.2*	6.2*	7.6	7.2	7.5	7.4	7.8	7.5	7.7	7.6	
CENTRAL AVE L(23.9L)							FC95														
2100044	23.758	24.554	C	2004	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.0	9.0	8.5	7.0	7.0	7.0	6.7	7.0	3.5*	
ANDERSON COLUMBIA CO., INC(2006)							RIDE	7.7	7.1	6.1	6.2	6.6	6.8	6.4	6.7	6.5	6.7	6.6	6.3	6.6	
2100047	15.956	24.503	L	2027	0012																
76050000	20.430	23.740	L	1	1	50	CRACKING	5.5*	5.5*	5.5*			10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	
20				2	4.2	20300	RIDE	7.8	7.7	7.5			8.0	8.0	7.9	7.9	7.8	7.8	7.7	7.6	
MOTES RD(20.6L)							FC125M														
2100041	19.977	23.746	C	2002	0213	CRACKING	9.5	9.5	9.5	9.5	9.5	9.0	9.0	8.5	7.0	7.0	7.0	6.7	7.0	3.5*	
ANDERSON COLUMBIA CO., INC(2006)							RIDE	7.6	7.1	7.4	7.1	7.4	7.3	7.3	7.3	7.2	7.2	7.2	7.1	7.2	
2100047	15.956	24.503	L	2027	0012																
76050000	16.390	20.430	L	1	1	65	CRACKING	2.0*	2.0*	0.0*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
20				2	8.7	13264	RIDE	7.4	6.3*	5.9*	7.6		8.0	8.1	8.0	8.0	8.2	8.2	8.2	8.1	
MOTES RD(20.3L)							FC5														
2099991	15.896	20.308	C	2003	0213	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	4.5*	4.5*	4.5*	3.6*	2.5*	0.0*	
ANDERSON COLUMBIA CO., INC(2006)							SPRIDE	8.0	7.8	8.1	8.0	8.2	8.1	8.1	8.1	8.1	7.9	7.9	7.6	7.4	
2100047	15.956	24.503	L	2027	0012																
76050000	10.775	16.390	L	1	1	50	CRACKING	2.0*	2.0*	2.0*	10.0	9.0	9.0	8.0				10.0	10.0	10.0	
20				2	8.7	13264	RIDE	7.4	7.7	7.6	7.9	7.8	7.6	7.5				8.6	8.7	8.5	
CR 315(10.8C)							FC125														
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.6	
							RIDE	8.5	8.0	7.6	7.3	8.1	8.0	8.0	8.0	7.9	7.9	7.9	7.9	7.9	
							(2011)														

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026-2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = PUTNAM -----																								
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE				
SR	US	G_BMP	G_EMP	LN	*T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031			
INTERSECT	AT	(MP		SIDE)	SURF	TYPE	=====																	
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P	ASTYPE		2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031			
CONTRACTOR	(AGE_ONE	YEAR)		FY-F	WKMX-F																			
ITMSEG-F	W_BMP	W_EMP	RW																					
76050000	7.516	10.775	L	1	1	50	CRACKING	7.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*			
20			2	4.2		8900	RIDE	7.3	6.6	6.7	6.8	6.8	6.7	6.6	6.3*	6.6	6.1*	6.4*	6.1*	5.4*				
KITTY LN(7.6L)							FC125M																	
				(2023)			CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	7.5		10.0	10.0	10.0	10.0	8.5				
							RIDE	8.7	7.9	8.0	7.7	8.1	8.0	8.0						7.9	7.5			
76050001	0.000	1.219	R	1	1	50	CRACKING																	
20			2	4.2		8900	RIDE																	
				(2025)			CRACKING													10.0	10.0	9.0		
							RIDE													8.2	8.2	7.8		
76050001	0.000	1.219	L	1	1	50	CRACKING																	
20			2	4.2		8900	RIDE																	
				(2025)			CRACKING													10.0	10.0	9.0		
							RIDE													8.0	8.0	7.6		
76060000	0.000	1.222	R	1	1	55	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
207			2	7.3		19300	RIDE			8.6	8.2	8.0	7.7	7.8	7.9	8.0	8.2	8.0	8.0	8.0	7.6			
SR 100(0.0C)							FC125																	
2099651	0.100	4.210	C	1999		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	6.6	6.9	3.0*			
APAC-FLORIDA INC (2003)							SPRIDE	7.8	7.4	7.4	7.3	7.5	7.6	7.4	7.6	7.4	7.4	7.3	7.3	7.2	6.8			
2099872	0.011	1.222	C	2028		0012																		
76060000	1.222	6.668	R	1	1	55	CRACKING	8.0		10.0	10.0	10.0	9.0	7.5	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*			
207			2	7.3		19300	RIDE	8.8		8.8	8.1	7.9	7.6	7.6	7.0	7.2	7.9	7.8	7.7	7.7	7.8			
E CRACKER SWAMP RD(1.4R)							FC5A																	
4287121	1.222	6.668	C	2014		0012	CRACKING	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.5	7.5	6.5	4.5*	1.0*			
PREFERRED MATERIALS, INC. (2016)							SPRIDE	7.6	7.7	8.4	8.4	8.7	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.5	8.3		
76060000	1.222	6.668	L	1	1	55	CRACKING	8.0		10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.5	7.5	7.5	7.5			
207			2	7.3		19300	RIDE	8.8		8.8	8.1	8.1	8.1	8.0	7.8	7.9	7.5	7.7	8.1	8.1				
CRACKER SWAMP RD E(1.4L)							FC5A																	
4287121	1.222	6.668	C	2014		0012	CRACKING	7.5	7.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	6.5	5.3*	4.2*	0.5*			
PREFERRED MATERIALS, INC. (2016)							SPRIDE	8.0	7.7	8.5	8.5	8.7	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.4	
76060000	0.000	1.222	L	1	1	55	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
207			2	7.3		19300	RIDE			8.6	8.2	8.0	7.8	8.0	8.1	8.1	8.0	7.9	7.7	7.9				
SR 100(0.0C)							FC125																	
2099651	0.100	4.210	C	1999		0213	CRACKING	10.0	10.0	9.5	9.5	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	6.6	2.5*			
APAC-FLORIDA INC (2003)							SPRIDE	7.7	7.2	6.8	7.2	7.3	7.1	7.0	6.7	6.9	7.0	6.9	6.9	6.9	6.9	6.5		
2099872	0.011	1.222	C	2028		0012																		
76070000	0.000	7.781	C	1	1	55	CRACKING	8.0	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0			
21			2	5.5		2600	RIDE	8.3	8.5	8.4	7.8	7.7	7.5	7.4	6.9	8.5	8.6	8.5	8.4	8.3				
SR 20(0.0C)							FC125																	
2098802	1.630	7.181	C	2008		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	6.0*	3.0*			
PREFERRED MATERIALS, INC. (2009)							RIDE	8.3	8.0	7.7	7.7	8.1	8.0	8.0	8.0	7.7	7.8	7.6	7.6	7.6	7.5	7.1		
76080000	0.000	0.357	C	1	8	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
26			2	7.0		11000	RIDE	8.4	8.5	8.6	7.9	8.2	8.0	8.2	7.1	8.4	8.1	7.9	7.8	8.0				
ALACHUA CO LINE(0.0C)							FC125																	
2099202	0.000	0.320	C	2008		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	9.4					
V. E. WHITEHURST & SONS, I (2009)							RIDE	8.4	8.0	8.0	8.0	8.0	7.9	7.8	7.3	7.2	7.7	7.4	7.7					
76080000	0.357	5.702	C	1	1	55	CRACKING	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0			
26			2	10.8		4000	RIDE	8.0	8.1	8.0	7.4	7.2	7.1	6.9	6.2*	8.2	8.2	8.0	7.9	7.9				
SR 21(0.4C)							FC125																	
2099202	1.252	5.702	C	2008		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.0	6.0*	6.0*	6.0*	6.0*	5.4*	2.0*			
V. E. WHITEHURST & SONS, I (2009)							RIDE	8.0	7.7	7.7	8.0	7.9	7.9	7.8	7.9	7.7	7.7	7.7	7.7	7.6	7.6	7.6	7.2	
4453492	0.360	5.702	C	2029		0012																		
76110000	0.000	8.488	C	1	1	60	CRACKING	10.0	9.5	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0				
100			2	14.1		8000	RIDE	9.0	8.9	8.9	8.2	8.0	7.9	7.6	7.1	7.4	7.2	7.1	8.4	8.4				
FOREST HILLS RD(0.7L)							FC125M																	
2100142	1.395	8.459	C	2010		0012	CRACKING	10.0	10.0	10.0	10.0	9.5	9.0	9.0	8.5	6.0*	6.0*	6.0*	6.0*	5.9*	3.0*			
ANDERSON COLUMBIA CO., INC (2012)							SPRIDE	8.3	8.1	8.0	7.8	8.3	8.2	8.2	8.2	8.1	8.1	8.1	8.1	8.1	8.1	7.9	7.5	
2100143	0.000	18.824	C	2027		0012																		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 2 COUNTY = PUTNAM -----																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE		
SR	US	G_BMP	G_EMP	LN	#T	ADT	RATINGS	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2031	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	W_YEAR	FY-P	W_KMX-P	ASTYPE	=====	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031	
ITMSEG-P	W_BMP	W_EMP	RW	FY-F	W_KMX-F																(PMRS)	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	W_KMX-F																	
76110000	8.488	9.070	R	1	1	60	CRACKING	10.0	9.5	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0		
100				1	14.1		7400 RIDE	9.0	8.9	8.9	8.2	8.0	7.9	7.6	7.1	7.4	7.2	7.1	8.4	8.4		
SCHOOL ENT(8.7R)							FC125M															
2100142	8.459	9.040	R	2010			0012 CRACKING	10.0	10.0	10.0	10.0	9.5	9.0	9.0	8.5	6.0*	6.0*	6.0*	6.0*	5.9*	3.0*	
ANDERSON COLUMBIA CO., INC(2012)							SPRIDE	8.3	8.1	8.0	7.8	8.3	8.2	8.2	8.2	8.1	8.1	8.1	8.1	8.1	8.2	7.8
2100143	0.000	18.824	C	2027			0012															
76110000	9.070	17.423	C	1	1	60	CRACKING	10.0	9.5	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0		
100				2	14.1		7400 RIDE	9.0	8.9	8.9	8.2	8.0	7.9	7.6	7.1	7.4	7.2	7.1	8.4	8.4		
SIDE ROAD(10.3C)							FC125M															
2100142	9.040	17.611	C	2010			0012 CRACKING	10.0	10.0	10.0	10.0	9.5	9.0	9.0	8.5	6.0*	6.0*	6.0*	6.0*	5.5*	2.5*	
ANDERSON COLUMBIA CO., INC(2012)							SPRIDE	8.3	8.1	8.0	7.8	8.3	8.2	8.2	8.2	8.1	8.1	8.1	8.1	8.1	8.1	7.7
2100143	0.000	18.824	C	2027			0012															
76110000	17.423	17.755	C	1	1	60	CRACKING	10.0	9.5	7.5	7.5	7.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	
100				2	14.1		10000 RIDE	9.0	8.9	8.9	8.2	8.0	7.9	7.6	7.1	8.4	8.4	8.3	8.4	8.4	8.4	
SPRINGSIDE RD(17.5L)							FC125															
2100142	9.040	17.611	C	2010			0012 CRACKING	10.0	10.0	10.0	10.0	9.5	9.0	9.0	8.5	6.0*	6.0*	6.0*	6.0*	4.5*	1.5*	
ANDERSON COLUMBIA CO., INC(2012)							SPRIDE	8.3	8.1	8.0	7.8	8.3	8.2	8.2	8.2	8.1	8.1	8.1	8.1	8.1	6.5	6.1*
2100143	0.000	18.824	C	2027			0012															
76110000	17.755	18.840	C	1	1	60	CRACKING	10.0	9.5	7.5	7.5	7.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	
100				2	14.1		10000 RIDE	9.0	8.9	8.9	8.2	8.0	7.9	7.6	7.1	8.4	8.4	8.3	8.3	8.3	8.3	
							FC125															
2100312	17.511	19.352	C	2006			0012 CRACKING	10.0	10.0	10.0	10.0	9.5	8.0	8.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	2.0*	
ANDERSON COLUMBIA CO., INC(2008)							RIDE	8.2	7.7	7.7	7.7	7.9	7.9	7.8	7.8	7.7	7.7	8.0	7.8	7.8	7.4	
2100143	0.000	18.824	C	2027			0012															
76110000	18.840	19.406	C	1	1	50	CRACKING	10.0	9.5	7.5	7.5	7.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	
100				2	14.1		10000 RIDE	9.0	8.9	8.9	8.2	8.0	7.9	7.6	7.1	8.4	8.4	8.3	8.3	8.3	8.3	
AIRPORT RD(19.3R)							FC125M															
4432741	19.121	19.441	C	2022			0012 CRACKING	10.0	10.0	10.0	10.0	9.5	8.0	8.0	7.0	7.0	5.5*	5.5*	10.0	10.0	9.0	
HALIFAX PAVING, INC.							SPRIDE	8.2	7.7	7.7	7.7	7.9	7.9	7.8	7.8	7.7	7.7	8.0	8.2	8.2	7.8	
76110000	19.406	21.165	R	1	1	45	CRACKING	0.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0		
100				2	14.1		10900 RIDE	7.5		8.4	8.0	7.9	7.8	7.8	6.9	7.8	7.7	7.6	7.4	7.4		
MOODY RD(19.9R)							FC125M															
4432741	19.441	20.560	R	2022			0012 CRACKING	9.0	9.0	9.0	9.0	8.0	7.0	7.0	7.0			10.0	9.6	10.0	9.0	
HALIFAX PAVING, INC.							SPRIDE	7.5	7.3	7.1	7.3	7.5	7.4	7.4	7.3	7.4		8.1	8.0	7.9	7.5	
76110000	21.165	21.361	R	1	1	40	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0		
100				2	14.1		17700 RIDE	7.0		8.4	8.0	7.9	7.8	7.8	6.9	7.8	7.7	7.6	7.4	7.4		
IDA ST(21.2R)							FC125M															
4432741	21.236	21.361	R	2022			0012 CRACKING	9.0	9.0	9.0	9.0	8.0	7.0	7.0	7.0	6.0*	4.5*	10.0	10.0	10.0	9.0	
HALIFAX PAVING, INC.							SPRIDE	7.5	7.3	7.1	7.3	7.5	7.4	7.4	7.3	7.0	7.7	7.9	7.9	7.8	7.4	
76110000	21.165	21.361	L	1	1	40	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0		
100				2	14.1		17700 RIDE	7.0		7.8	7.6	7.5	7.4	7.7	6.9	7.6	7.4	7.1	7.2	7.1		
PALATKA CITY LIMITS(21.4L)							FC125M															
4432741	20.560	21.361	L	2022			0012 CRACKING	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	9.0	
HALIFAX PAVING, INC.							SPRIDE	7.5	7.1	7.3	6.8	7.3	7.4	7.3	7.4	7.2	6.3		6.5	6.4	6.0	
76110000	19.406	21.165	L	1	1	45	CRACKING	2.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0		
100				2	14.1		10900 RIDE	7.3		7.8	7.6	7.5	7.4	7.7	6.9	7.6	7.4	7.1	7.2	7.1		
CR 216A(19.6L)							FC125M															
4432741	19.441	20.560	L	2022			0012 CRACKING	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	4.5*		10.0	10.0	10.0	9.0	
HALIFAX PAVING, INC.							SPRIDE	7.5	7.1	7.3	6.8	7.3	7.4	7.3	7.4	7.2		8.2	8.2	8.1	7.7	
76110001	0.000	0.031	R	1	1	40	CRACKING														10.0	
100				1	14.1		17700 RIDE															
GORE TO US-17(0.0C)																						
							CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	7.0	7.0	8.0	10.0	10.0	9.0
							RIDE														5.5	5.1*
76110001	0.000	0.031	L	1	1	40	CRACKING															10.0
100				2	14.1		17700 RIDE															
GORE TO US-17(0.0C)																						
							CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	7.0	7.0	8.0	10.0	10.0	9.0
							RIDE														2.4*	2.0*

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @* INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2031 FORECASTED BY PAVEMARS (PMRS).