

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																								
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR														FUTURE	
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012				
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKMX-P																			
ITMSEG-P	(AGE_ONE YEAR)	ASTYPE						2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030			
CONTRACTOR	W BMP	W EMP	RW	FY-F	WKMX-F																(PMRS)			
ITMSEG-F																								
86003000	0.000	0.240	R	1	1 35	CRACKING		4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
844			2	4.1	21000	RIDE		7.0	6.9	6.5		6.0	6.1	6.2	6.0	6.6	7.0	6.9	7.0	7.0	7.0			
FEDERAL HWY(0.0C)					DGFC																			
					(2004)	CRACKING		9.5	9.5	9.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	7.5	6.0*		
						RIDE		6.8	6.4	6.0	6.2	6.2	6.5	6.4	5.9	5.9	5.9	6.1	5.9	6.3	5.9			
86003000	0.240	0.902	R	1	1 35	CRACKING		4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0				
844			2	2.1	16000	RIDE		7.0	6.9	6.5	6.5	6.0	5.8	4.8*	4.7*		7.4	7.2	7.1	7.0				
NE 27 AVE(0.3R)					FC95																			
2279541	0.240	0.902	C	2007	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.7	7.5			
COMMUNITY ASPHALT CORP.					(2009) SPRIDE			7.1	6.9	6.9	6.1	6.2	6.4	5.8	5.7	5.9	5.5	5.7	5.6	5.3*	4.9*			
86003000	0.240	0.902	L	1	1 35	CRACKING		4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0				
844			2	2.1	16000	RIDE		7.1	6.8	6.8	6.5	5.7	5.6	5.3*	5.4*		7.2	7.1	7.2	7.1				
NE 27 AVE(0.3L)					FC95																			
2279541	0.240	0.902	C	2007	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.6	7.5			
COMMUNITY ASPHALT CORP.					(2009) SPRIDE			7.1	7.1	7.2	6.4	6.3	6.3	6.1	5.9	6.0	5.9	5.9	5.8	5.7	5.3*			
4476721	0.000	0.894	L	2025	0012																			
86003000	0.000	0.240	L	1	6 35	CRACKING		4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
844			3	4.1	21000	RIDE		7.1	6.8	6.8		6.9	6.6	6.4	5.9	6.6	7.4	7.3	7.4	7.3				
FEDERAL HWY(0.0C)					DGFC																			
					(2004)	CRACKING		10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.1	5.5*			
						RIDE		7.2	7.2	7.0	7.0	5.5	5.1*	5.0*	4.4*									
4476721	0.000	0.894	L	2025	0012																			
86005000	0.000	0.187	R	1	6 35	CRACKING		10.0	10.0	9.0	6.5	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0				
838			3	3.5	40000	RIDE		6.0*	5.9*	6.2	5.4*	6.7	6.4	5.8	6.0	6.0	6.6	6.6	6.5	6.3				
NE 18 AV(0.0R)					FC125																			
					(2004)	CRACKING		9.0	7.5	7.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	6.7	5.0*			
						RIDE		6.1	6.5	6.4	6.0	6.3	6.6											
4419551	0.000	0.200	C	2030	0213																			
86005000	0.187	0.323	R	1	6 35	CRACKING		10.0	10.0	9.0	6.5	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0				
838			3	3.5	40000	RIDE		6.0*	5.9*	6.2	5.4*	6.7	6.4	5.8	6.0	6.0	6.6	6.6	6.5	6.3				
					DGFC																			
					(2018)	CRACKING		9.0	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.6	7.5			
						RIDE		6.1	6.5	6.4	6.0													
86005000	0.323	0.820	R	1	2 35	CRACKING		10.0	9.0	9.0	6.5	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0				
838			3	8.3	27000	RIDE		7.0	7.0	6.9	7.2	6.7	6.4	5.8	6.0	6.0	6.6	6.6	6.5	6.3				
MIDDLE RIVER DR(0.3R)					FC125																			
2279501	0.394	0.760	C	2001	0012	CRACKING		9.0	7.5	7.5	7.5	7.5	7.0	7.0	6.5	6.5	6.5	6.5	6.5	5.5*	5.5*			
					(2004) SPRIDE			6.1	6.5	6.4	6.0	5.7	5.9	5.8	5.7	5.8	5.5	5.5	5.5	5.4*	5.3*			
4461811	0.361	0.827	C	2025	0012																			
86005000	0.820	1.191	R	1	6 35	CRACKING		10.0	9.0	9.0	6.5	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0				
838			3	6.2	23000	RIDE		7.0	7.0	6.9	7.2	4.0*	5.7	5.6	5.7	5.7	5.7	6.0	5.6	5.8				
BREAKERS AVE(1.1R)					FC95A																			
					(2018)	CRACKING		6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0			
						RIDE		5.3*	5.5	5.5	5.1*	5.1*												
86005000	0.820	1.191	L	1	6 35	CRACKING		9.0	9.0	6.5	6.5	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0				
838			3	6.2	23000	RIDE		7.3	6.6	6.7	7.1	5.3*	5.4*	5.2*	4.9*	5.7	6.0	6.0	5.8	6.0				
FIRE STATION(0.9L)					FC95A																			
					(2018)	CRACKING		7.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0			
						RIDE		5.7	5.9	5.6	5.0*	5.1*												
86005000	0.384	0.820	L	1	1 35	CRACKING		9.0	9.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5				
838			3	8.3	27000	RIDE		7.3	6.6	6.7	7.1	6.6	6.2	6.3	5.9	6.1	6.7	6.8	6.6	6.5				
BAYVIEW DR(0.5C)					FC125																			
2279501	0.394	0.760	C	2001	0012	CRACKING		9.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.9*	4.5*			
					(2004) SPRIDE			6.5	6.3	5.8	5.1*	4.9*	5.0*	5.3*	5.1*	5.1*	4.9*	5.0*	5.1*	4.8*	4.4*			
4461811	0.361	0.827	C	2025	0012																			
86005000	0.083	0.384	L	1	6 35	CRACKING		10.0	10.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5				
838			3	3.5	40000	RIDE		6.7	6.6	5.9	6.6	6.6	6.2	6.3	5.9	6.1	6.7	6.8	6.6	6.5				
SPUR(0.1L)					DGFC																			
					(2018)	CRACKING		9.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0			
						RIDE		6.5	6.3	5.8	5.1*													

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

										DISTRICT = 4 COUNTY = BROWARD																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
RDWYID	SR	US	BMP	G BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKM-X-P	ASTYPE															
CONTRACTOR (AGE ONE YEAR)	W BMP	W EMP	RW	FY-F	WKM-X-F																
ITMSEG-F																					2030 (PMRS)
86006000	2.090	2.958	L 1	1 45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		10.0	10.0	10.0	10.0	
842			3 2.7	44000	RIDE	6.2*	6.1*	6.8	6.8	6.0*	5.9*	5.0*	4.5*				6.8	7.0	6.9	6.6	
NW 48 AVE(2.4L)				FC4																	
			(2009)		CRACKING	10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.0	8.0	8.0	8.0	8.1	7.0	5.1*
					RIDE	6.6	6.5	6.5	6.1	5.9	6.1	5.9	5.7	5.9	5.7	5.9	5.8	5.6	5.5	5.1*	
86006000	0.000	2.090	L 1	7 45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		10.0	10.0	10.0	10.0	
842			3 5.4	51500	RIDE	5.9*	6.0*	5.8*	6.2*	5.7*	5.8*	5.3*	5.2*				7.2	6.8	6.8	6.6	
PLANTATION CITY LIMITS(0.0C)				FC125																	
4442651	0.143	2.098	L 2022	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	9.5
WEEKLEY ASPHALT PAVING, IN(2025)					RIDE	6.7	6.4	6.7	6.9	6.9	6.6	6.4	6.3	6.4	6.3	6.4	6.3	6.3		6.6	6.2
86010000	0.000	0.838	R 1	1 45	CRACKING	4.5*	4.5*	4.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	10.0	10.0	10.0	
5			3 6.3	59000	RIDE	7.2	7.5	7.0	7.1	6.4*				6.9	6.6	7.0	6.9	6.5	6.4	6.3	
VIA DA FORTUNA(0.1R)				FC125																	
4035851	0.000	0.780	C 2003	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.9	7.5	
COMMUNITY ASPHALT CORP.			(2006)	S	RIDE	6.9	6.2	6.1	6.2	6.4	6.3	5.9	5.9	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.4*
4476741	0.000	1.538	C 2025	0012																	
86010000	0.838	2.476	R 1	2 35	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
5			2 2.4	30283	RIDE	6.7	6.5	6.4	6.5	5.9	5.5	6.3	6.0	6.0	6.0	6.2	5.8	5.9	5.8		
FIRST CT NE(0.9R)				FC125																	
2280341	0.777	2.426	C 2003	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.7	7.0	
COMMUNITY ASPHALT CORP.			(2006)	SPRIDE		5.9	5.8	5.7	5.3*	5.1*	5.0*	4.9*	4.8*	5.0*	5.0*	5.0*	4.9*	4.6*	5.0*	4.6*	
86010000	2.476	2.713	C 1	6 25	CRACKING	7.0	7.0	9.0	9.0	9.0	9.0	9.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	
5			3 7.8	15000	RIDE	5.9*	6.0*	5.8	5.1*	5.2*	4.5*	4.6*			4.5*	4.7*	5.8	5.1*	4.8*		
S YOUNG CIRCLE(2.5L)				FC95																	
4137931	2.476	2.713	C 2005	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.4	7.0	
			(2008)		RIDE	4.8*	5.2*	4.7*	4.2*	3.9*	3.9*	3.9*	3.8*	3.9*	3.6*	3.6*	3.6*	3.7*			
86010000	2.713	4.117	R 1	2 35	CRACKING	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	6.5	6.0*	6.0*	10.0	10.0	10.0	10.0	
5			2 7.8	31000	RIDE	6.6	6.5	6.3	6.3	5.5	5.6	5.3*	5.2*	5.4*	5.2*	5.2*	7.3	7.2			
ALLEY(2.7R)				FC95																	
			(2021)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	3.5*	3.5*	8.5	8.5	8.5	8.5	8.5	7.5	
					RIDE	7.0	6.9	7.0	6.9	7.0	7.0	7.0	5.2*	6.3	6.2	6.0	6.1	5.9	6.6	6.2	
86010000	4.117	5.948	R 1	1 35	CRACKING	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	
5			2 4.7	35000	RIDE	7.3	7.5	7.5	7.3	6.7	6.3	6.5	6.0	6.1	6.6	7.5	7.2	7.3			
SHERIDAN ST(4.1C)				DGFC																	
4138291	4.094	5.806	R 2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.1	7.0	
WEEKLEY ASPHALT PAVING, IN(2010)				SPRIDE		7.0	7.3	7.1	7.2	7.1	7.0	6.9	6.7	6.7	6.7	6.6	6.6	6.4	6.6	6.2	
4498151	4.117	5.917	C 2028	0012																	
86010000	8.286	8.814	R 1	1 40	CRACKING	9.0	9.0	9.0	9.0	9.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	
5			3 8.9	58000	RIDE	7.8	7.7	7.4	7.3	6.9	6.7	6.5	6.4	6.5	6.2	6.4	6.2	6.7			
FORT LAUDERDALE CITY LIM(8.3C)				DGFC																	
			(2013)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	
					RIDE	7.9	7.8	7.9	7.7	8.0	8.0	7.7	7.8	7.8	7.8	7.6	7.8	7.6	7.6	7.2	
86010000	8.814	10.330	R 1	1 40	CRACKING	9.0	9.0	9.0	9.0	9.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	
5			3 3.1	36000	RIDE	7.8	7.7	7.4	7.3	6.9	6.7	6.5	6.4	6.5	6.2	6.4	6.2	6.7			
SE 16 CT(8.9R)				FC125																	
			(2014)		CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.7	7.5	
					RIDE	6.7	7.5	7.6	7.4	7.2	7.5	7.6	7.0	7.2	7.5	6.9	6.9	6.6	6.6	6.2	
86010000	8.814	10.330	L 1	1 40	CRACKING	9.0	7.5	7.5	7.5	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	
5			3 3.1	36000	RIDE	7.5	7.3	7.4	7.3	6.4	6.5	6.5	6.0	6.1	6.4	6.3	6.2	6.7			
SE 16 CT(8.9L)				FC125																	
			(2014)		CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	
					RIDE	6.3	7.3	7.4	7.4	7.1	7.3	7.1	7.1	7.0	7.1	6.7	6.6	6.6	6.6	6.2	
86010000	8.286	8.814	L 1	1 40	CRACKING	9.0	7.5	7.5	7.5	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	
5			3 8.9	58000	RIDE	7.5	7.3	7.4	7.3	6.4	6.5	6.5	6.0	6.1	6.4	6.3	6.2	6.7			
FORT LAUDERDALE CITY LIM(8.3C)				DGFC																	
			(2013)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.6	8.5	
					RIDE	7.9	7.8	7.8	7.9	7.7	8.0	7.5	7.7	7.8	7.7	7.9	7.8	7.9	7.9	7.5	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

ALL SYSTEM PAVEMENT CONDITION FORECAST

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																								
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR														FUTURE	
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012				
INTERSECT AT (MP SIDE)																								
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P																			
CONTRACTOR (AGE ONE YEAR)					ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030			
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																	(PMRS)		
86012000	0.312	1.330	R	1	1 45	CRACKING		9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0			
869			2	4.3	46500	RIDE		6.3*	6.2*	6.1*	6.0*	5.9*	5.7*	5.9	5.3*	5.7	5.6	5.7	5.8	5.4*				
SW 30 AVE(0.5R)					FC95																			
4246651	0.163	1.445	R	2012	0012	CRACKING		8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5		
COMMUNITY ASPHALT CORP.				(2014)	SPRIDE			5.5	7.8	7.8	7.2	7.2	7.2	6.8	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.5		
86012000	1.330	1.820	R	1	1 40	CRACKING		9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5			
869			3	4.8	50000	RIDE		7.5	7.0	7.4	7.4	6.7	6.1	6.9	6.9	6.5	6.1	6.5	7.0	7.0	6.9			
CR 809(1.4C)					FC95																			
4246651	1.445	1.829	R	2012	0012	CRACKING		6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.4	8.5		
COMMUNITY ASPHALT CORP.				(2014)	SPRIDE			6.9	8.4	8.4	7.6	7.6	7.7	7.0	7.5	7.6	7.3	7.3	7.3	7.3	7.5	7.1		
86012000	1.820	2.152	R	1	6 40	CRACKING		9.0	9.0	9.0	9.0	9.0	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0			
869			3	4.8	50000	RIDE		7.5	7.0	7.4	7.4	6.7	6.1	6.9		8.1	7.3	8.2	8.4	8.2				
E NEWPORT CENTER DR(1.8R)					DGFC																			
				(2008)				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.9	7.5			
						CRACKING		8.3	8.3	8.3	7.6	7.7	7.3	6.9	7.0	6.8								
						RIDE																		
86012000	1.820	2.152	L	1	1 40	CRACKING		9.0	9.0	9.0	9.0	9.0	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0			
869			3	4.8	50000	RIDE		6.7	6.7	6.9	7.1	6.8	6.3	6.5		8.3	7.9	7.5	7.6	7.9				
NEWPORT CENTER DR E(1.8L)					DGFC																			
				(2008)				10.0	10.0	9.0	9.0	9.0	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.5	8.4	7.0		
						CRACKING		8.4	8.2	8.4	8.1	8.2	8.2	8.2	8.0	8.0	8.2	8.0	7.8	7.8	7.8	7.4		
						RIDE																		
86012000	1.557	1.820	L	1	1 40	CRACKING		9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5			
869			3	4.8	50000	RIDE		6.7	6.7	6.9	7.1	6.8	6.3	6.5	6.1	7.0	7.1	7.2	7.5	7.5	6.7			
					FC95																			
4246651	1.653	1.829	L	2012	0012	CRACKING		6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.6	7.5			
COMMUNITY ASPHALT CORP.				(2014)	SPRIDE			6.7	7.8	8.3	8.1	7.6	8.0	7.9	7.8	7.7	7.8	7.6	7.4	7.4	7.0			
86012000	0.312	1.557	L	1	1 45	CRACKING		8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.5	6.5				
869			2	4.3	46500	RIDE		7.4	7.3	7.5	7.3	6.9	6.9	6.8	6.7	6.9	6.8	6.8	6.3	6.6				
CR 809(1.4C)					FC95																			
4246651	0.312	1.653	L	2012	0012	CRACKING		6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5			
COMMUNITY ASPHALT CORP.				(2014)	SPRIDE			6.6	8.0	7.9	7.4	7.6	7.3	7.4	7.4	7.3	7.1	7.4	7.2	7.3	6.9			
86012000	0.000	0.312	L	1	1 45	CRACKING		9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*				
869			3	4.3	46500	RIDE		7.4	8.1	7.9	8.2	7.5	7.1	7.1	7.2	6.7	6.5	6.9	6.5	6.4				
POWERLINE RD(0.0C)					FC95																			
4246651	0.012	0.312	L	2012	0012	CRACKING		4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5			
COMMUNITY ASPHALT CORP.				(2014)	SPRIDE			6.2	7.8	7.4	7.3	7.3	7.4	7.0	7.1	7.1	7.0	6.8	6.5	7.0	6.6			
86014000	0.000	0.803	R	1	1 45	CRACKING		10.0	10.0	9.0	9.0	9.0	9.0	8.5	7.0	6.5	6.5	6.5	6.5	4.5*	4.5*			
870			3	3.4	54000	RIDE		8.1	7.9	8.0	7.9	7.2	7.3	7.3	7.2	6.8	6.8	6.9	6.9	6.7				
SR 817(0.0C)					FC95																			
4246661	0.017	0.814	C	2012	0012	CRACKING		4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0			
WEEKLEY ASPHALT PAVING, IN(2014)					SPRIDE			6.5	7.9	8.1	7.5	7.7	7.6	7.4	7.5	7.3	7.5	7.6	7.2	7.1	6.7			
86014000	0.803	1.180	R	1	1 45	CRACKING		10.0	10.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
870			3	3.4	54000	RIDE		8.1	7.9	8.0	7.9	7.2	7.2	7.0	7.0	7.2	7.0	7.2	7.1	7.2				
NW 64 AVE(1.0C)					FC125																			
				(2005)				10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.3	7.0			
						CRACKING		7.0	7.1	7.2	6.8	6.7	6.6	6.4	6.4	6.5	6.4	6.4	6.4	6.4	6.0			
						RIDE																		
86014000	1.180	2.330	R	1	1 45	CRACKING		10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	4.5*	4.5*				
870			3	5.4	50500	RIDE		8.1	7.9	8.0	7.9	7.2	6.8	6.6	6.1	6.4	6.4	6.5	6.2	6.8				
WHITE OAK LA(1.2R)					FC125M																			
4270041	1.180	2.330	C	2014	0012	CRACKING		4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5			
GENERAL ASPHALT CO., INC. (2016)						RIDE		6.3	6.0	6.1	7.7	7.7	7.9	7.9	7.4	7.7	7.7	7.7	7.6	7.5	7.1			
86014000	2.330	2.795	R	1	6 45	CRACKING		10.0	10.0	9.0	9.0	9.0	10.0	10.0	10.0				10.0	10.0				
870			3	4.0	72500	RIDE		8.1	7.9	8.0	7.9	7.2	7.3	7.1	6.8				7.5	7.3				
					UNKW																			
				(2011)				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.6	8.5		
						CRACKING		7.4	7.3	7.5	6.6	6.2	6.3	5.8	5.8									
						RIDE																		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

ALL SYSTEM PAVEMENT CONDITION FORECAST

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKMX-P	ASTYPE	=====														
ITMSEG-P (AGE ONE YEAR)	W BMP	W EMP	RW	FY-F	WKMX-F			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F																					
86014000	2.795	4.228	L	1	1 45	CRACKING		9.0	9.0	9.0	9.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
870			3	5.5	55500	RIDE		6.8	7.2	6.9	6.9	6.2*	6.7	6.6	6.4	6.7	6.7	6.9	6.5	6.3	
NW 47 TER(2.8C)					FC125																
				(2005)		CRACKING		10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.3	7.0
						RIDE		6.5	6.4	6.6	6.3	6.4	6.3	6.2	6.4	6.3	6.3	6.4	6.2	6.3	5.9
86014000	2.330	2.795	L	1	1 45	CRACKING		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0				10.0	10.0	
870			3	4.0	72500	RIDE		8.0	8.1	8.0	7.8	6.9	7.7	7.6	7.4				7.8	7.5	
CENTRAL PARK(2.4L)					UNKW																
				(2011)		CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.2	7.0
						RIDE		7.6	7.5	7.7	7.4	7.3	7.2	7.3	7.0	6.9	6.8	6.8	6.8	6.6	6.2
86014000	1.180	2.330	L	1	1 45	CRACKING		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	4.5*	4.5*	
870			3	5.4	50500	RIDE		8.0	8.1	8.0	7.8	6.9	7.7	7.6	7.4	7.7	7.4	7.6	7.5	7.4	
SAFEGUARD(1.2L)					FC125M																
4270041	1.180	2.330	C	2014	0012	CRACKING		4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.7	8.5
GENERAL ASPHALT CO., INC.				(2016)		RIDE		7.4	7.3	7.4	7.8	7.8	7.8	7.8	7.6	7.7	7.5	7.7	7.4	7.6	7.2
86014000	0.803	1.180	L	1	1 45	CRACKING		10.0	10.0	10.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
870			3	3.4	54000	RIDE		8.0	8.1	8.0	7.8	6.9	7.3	7.3	7.2	7.2	7.0	7.0	7.0	6.3	
NW 64 AVE(1.0C)					FC125																
				(2005)		CRACKING		10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.3	6.0*
						RIDE		6.9	6.6	6.9	7.0	7.0	7.0	7.0	6.6	6.9	6.7	6.9	6.6	6.9	6.5
86014000	0.000	0.803	L	1	1 45	CRACKING		10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	
870			3	3.4	54000	RIDE		8.0	8.1	8.0	7.8	6.9	6.5	6.6	6.1	6.5	6.0	6.5	5.8	6.2	
SR 817(0.0C)					FC95																
4246661	0.017	0.814	C	2012	0012	CRACKING		4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.1	8.0
WEEKLEY ASPHALT PAVING, INC.				(2014)		SPRIDE		6.2	8.0	8.0	7.8	7.9	7.9	7.3	7.7	7.6	7.6	7.6	7.4	7.4	7.0
86015000	0.000	2.497	R	1	8 45	CRACKING		7.0	6.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	10.0	
818			3	5.4	28500	RIDE		7.9	7.8	7.7	7.6	7.1			7.9	7.7	7.6	7.6	7.4	7.5	
COOPER CITY LIMITS(0.0C)					FC125M																
2274621	0.200	2.424	C	2003	0213	CRACKING		10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5		
RUSSELL ENGINEERING, INC				(2007)		SPRIDE		7.5	7.4	7.4	7.0	6.9	6.9	6.7	6.9	6.6	6.7	6.6	6.6		
4463711	0.000	2.507	C	2024	0012																
86015000	2.497	3.924	R	1	1 45	CRACKING		7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
818			3	3.4	31500	RIDE		7.9	7.8	7.7	7.6	7.8	7.7	7.6	7.7	7.7	7.7	7.7	7.6	7.6	
SW 90 AVE(2.6R)					FC125																
2278821	2.424	3.906	C	2001	0213	CRACKING		10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.0	7.0	7.0	7.0	5.5*
RUSSELL ENGINEERING, INC				(2004)		SPRIDE		7.6	7.5	7.6	6.8	6.6	6.6	6.5	6.5	6.5	6.5	6.4	6.2	6.4	6.0
4483991	2.491	3.958	C	2031	0012																
86015000	3.924	6.124	R	1	1 45	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
818			3	4.6	29163	RIDE					8.3	7.9	8.2	7.9	7.9	7.8	7.6	7.7	7.6	7.5	
SUNDANCE WAY(3.9R)					FC3																
2277061	3.877	6.525	C	1998	0213	CRACKING		10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	5.5*
TRIPLE R PAVING INC				(2003)		S RIDE		7.4	7.4	7.4	7.4	7.3	7.4	7.4	7.4	6.9	6.9	6.9	6.9	6.9	6.5
4498161	3.924	6.124	C	2029	0012																
86015000	6.519	10.738	R	1	1 45	CRACKING		9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	
818			3	4.4	37500	RIDE		7.3	7.3	7.3	7.2	6.6	6.7	6.5	6.3	6.4		8.3	7.9	7.8	
DAVIE CITY LIMITS(6.7C)					FC95																
4138321	6.691	10.587	R	2008	0012	CRACKING		10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.9	7.5
THE DE MOYA GROUP INC.				(2010)		SPRIDE		7.7	7.8	7.8	7.6	7.6	7.4	7.3	7.3	7.1	7.0	7.0	6.9	6.8	6.4
86015000	6.519	10.738	L	1	1 45	CRACKING		7.0	7.0	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*		10.0	10.0	10.0	
818			3	4.4	37500	RIDE		7.3	6.7	6.6	6.6	5.9*	6.0*	5.9	5.8	5.8		8.3	8.2	7.9	
SW 46 TERR(6.6L)					FC95																
4138321	6.691	10.729	L	2008	0012	CRACKING		10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.8	7.5
THE DE MOYA GROUP INC.				(2010)		SPRIDE		8.1	7.8	7.8	7.6	7.3	7.3	7.2	7.2	6.9	7.0	6.8	6.8	6.8	6.4
86015000	3.924	6.124	L	1	1 45	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
818			3	4.6	29163	RIDE					8.8	8.2	8.2	8.0	8.3	8.2	8.0	7.9	7.9	8.0	
ACCESS RD TO ORANGE(4.7L)					FC3																
2277061	3.877	6.525	C	1998	0213	CRACKING		10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	7.0	5.5*
TRIPLE R PAVING INC				(2003)		S RIDE		7.8	7.8	7.8	7.8	7.6	7.9	7.8	7.8	7.7	7.7	7.7	7.6	7.6	7.2
4498161	3.924	6.124	C	2029	0012																

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD

RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)							=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-F	ASTYPE																
CONTRACTOR (AGE ONE YEAR)								2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F																(PMRS)	
86015000	2.497	3.924	L	1	1 45	CRACKING		7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
818			3	3.4	31500	RIDE		7.9	7.8	7.7	7.6	7.9	7.9	7.8	7.7	7.7	7.8	7.8	7.7	7.6		
ACCESS RD TO ORANGE(3.0L)					FC125																	
2278821	2.424	3.906	C	2001	0213	CRACKING		10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	5.5*	
RUSSELL ENGINEERING, INC				(2004)	SPRIDE			7.6	7.5	7.5	6.9	6.8	6.8	6.6	6.7	6.5	6.4	6.5	6.4	6.4	6.0	
4483991	2.491	3.958	C	2031	0012																	
86015000	0.000	2.497	L	1	8 45	CRACKING		7.0	6.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	10.0		
818			3	5.4	28500	RIDE		7.9	7.8	7.7	7.6	7.1			7.9	7.5	7.6	7.5	7.3	7.2		
COOPER CITY LIMITS(0.0C)					FC125M																	
2274621	0.200	2.424	C	2003	0213	CRACKING		10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5			
RUSSELL ENGINEERING, INC				(2007)	SPRIDE			7.3	7.2	7.2	6.5	6.5	6.4	6.2	6.3	5.9	6.0	6.0	6.0			
4463711	0.000	2.507	C	2024	0012																	
86015009	0.000	0.369	R	1	1 45	CRACKING																
818			3	5.7	37500	RIDE																
DRIFTWOOD ACRES / SW(0.3R)					FC3																	
(2019)						CRACKING									10.0	10.0	10.0	10.0	10.0	8.5	7.5	
						RIDE									7.2	7.2	7.3	7.0	7.0	6.9	6.5	
86015009	0.000	0.369	L	1	1 45	CRACKING																
818			3	5.7	37500	RIDE																
SW 48 AVE(0.3L)					FC3																	
(2019)						CRACKING									10.0	10.0	10.0	10.0	10.0	9.5	8.5	
						RIDE									7.3	7.6	7.4	7.3	7.0	7.5	7.1	
86016000	0.000	2.786	R	1	1 45	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0		
848			3	2.8	33000	RIDE		7.5	7.4	7.2	7.3	6.7	6.6	6.7	6.6	6.6	6.6	6.6	6.7	6.4		
CARRIAGE HILLS DR(0.0C)					FC95M																	
4287251	0.018	2.786	C	2017	0012	CRACKING		8.0	8.0	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.7	9.0	
WEEKLEY ASPHALT PAVING, IN				(2019)	RIDE			6.5	6.5	5.7	5.7	5.5	5.5	7.0	6.9	6.9	6.9	6.9	7.0	6.9	6.5	
86016000	2.786	6.726	R	1	1 45	CRACKING		9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0		
848			3	3.1	39500	RIDE		6.5	6.6	6.4*	6.3*	6.0*	5.9*	6.0	5.6	5.8	7.9	7.5	7.4	7.3		
N 58 AVE(2.9R)					FC95																	
4114381	2.727	6.650	R	2006	0012	CRACKING		10.0	10.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	5.5*	
PAVEX CORPORATION				(2009)	SPRIDE			7.2	7.0	7.0	6.9	6.9	6.8	6.9	6.6	6.4	6.4	6.3	6.1	6.3	5.9	
86016000	5.363	6.726	L	1	1 45	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0		
848			3	3.1	20600	RIDE		6.5	6.3*	6.6	6.1*	5.7*	4.8*	6.0	5.5	5.8	7.8	7.6	7.5	7.4		
SW 19 CT(5.4L)					FC95																	
4114381	2.727	6.693	L	2006	0012	CRACKING		9.5	9.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	5.5*		
PAVEX CORPORATION				(2009)	SPRIDE			7.3	7.3	7.2	7.0	6.1	5.9	5.6	5.5	5.3*	5.4*	5.3*	5.1*	5.3*	4.9*	
4463701	2.767	6.726	L	2024	0012																	
86016000	4.498	5.363	L	1	1 45	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0		
848			3	3.7	47500	RIDE		6.5	6.3*	6.6	6.1*	5.7*	4.8*	6.0	5.5	5.8	7.8	7.6	7.5	7.4		
LAKE SHORE DR(4.5L)					FC95																	
4114381	2.727	6.693	L	2006	0012	CRACKING		9.5	9.5	8.5	8.5		6.5	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	2.0*	
PAVEX CORPORATION				(2009)	SPRIDE			7.3	7.3	7.2	7.0		5.6	6.9	6.8	6.5	6.5	6.3	6.3	6.6	6.2	
4463701	2.767	6.726	L	2024	0012																	
86016000	2.786	4.498	L	1	1 45	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0		
848			3	3.1	39500	RIDE		6.5	6.3*	6.6	6.1*	5.7*	4.8*	6.0	5.5	5.8	7.8	7.6	7.5	7.4		
SW 40 AVE(3.2L)					FC95																	
4114381	2.727	6.693	L	2006	0012	CRACKING		9.5	9.5	8.5	8.5	8.5	6.5	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	2.0*	
PAVEX CORPORATION				(2009)	SPRIDE			7.3	7.3	7.2	7.0	7.4	6.8	7.2	7.2	7.1	7.1	7.0	6.7	6.7	6.3	
4463701	2.767	6.726	L	2024	0012																	
86016000	0.000	2.786	L	1	1 45	CRACKING		10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5		
848			3	2.8	33000	RIDE		6.9	6.7	6.7	6.7	6.3*	6.1*	6.3	5.9	6.0	6.0	6.1	6.0	6.0		
CARRIAGE HILLS DR(0.0C)					FC95M																	
4287251	0.018	2.786	C	2017	0012	CRACKING		6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5	
WEEKLEY ASPHALT PAVING, IN				(2019)	RIDE			6.0	5.7	5.8	5.3*	5.3*	5.2*	7.0	6.9	6.8	6.9	6.9	6.8	6.8	6.4	
86018000	0.000	0.285	R	1	2 45	CRACKING		9.0	9.0	9.0	9.0	9.0			10.0	10.0	10.0	10.0	10.0	10.0		
824			3	3.1	42500	RIDE		6.8	6.9	6.7	6.9	6.6			7.8	7.4	7.3	7.3	6.8	7.1		
MIRAMAR CITY LIMITS(0.0C)					FC125																	
4062781	0.000	0.257	C	2003	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.3	7.0	
PAVEX CORPORATION				(2006)	SPRIDE			7.3	7.0	7.1	7.3	7.3	7.1	6.8	6.9	7.0	6.9	6.4	6.5	6.6	6.2	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD

RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)																						
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P																	
CONTRACTOR (AGE ONE YEAR)					ASTYPE																	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																2030 (PMRS)	
86018000	0.285	1.150	R	1	1 45	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0		
824			3	3.1	42500	RIDE		6.8	6.9	6.7	6.9	6.6	6.9	6.5	6.5	5.4*	8.0	7.9	7.9	7.8		
OLEANDER DR(0.3R)					FC125																	
4114391	0.285	1.150	R	2006	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.8	7.5	
GENERAL ASPHALT CO., INC. (2009)					SPRIDE			7.9	7.7	7.8	7.6	7.6	7.4	7.3	7.3	7.2	7.1	7.2	7.1	7.3	6.9	
4463721	0.364	2.335	C	2027	0012																	
86018000	1.150	2.335	R	1	1 40	CRACKING		7.5	7.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0		
824			2	7.6	45500	RIDE		6.4*	6.4*	6.2	6.0	5.6	5.6	5.3*	5.7	5.6	7.3	7.0	6.9	7.1		
ALCAZAR DR(1.1R)					FC125																	
4114391	1.150	2.267	R	2006	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	5.5*	
GENERAL ASPHALT CO., INC. (2009)					SPRIDE			7.1	6.8	7.0	7.1	6.9	7.0	7.1	7.0	6.8	6.7	6.7	6.5	6.9	6.5	
4463721	0.364	2.335	C	2027	0012																	
86018000	2.335	4.910	R	1	1 40	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
824			3	10.9	51000	RIDE		7.8	7.8	7.7	7.5	7.2	7.1	7.0	6.9	6.9	7.2	7.1	7.0	7.0		
SW 60 TER(2.5R)					FC3																	
2274531	2.282	4.898	C	1994	0213	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.6	7.0	
THE DE MOYA GROUP INC. (1998)					S RIDE			6.9	6.6	5.9	6.5	6.6	6.9	6.0	6.3	6.3	6.2	6.2	6.2	6.2	5.8	
4484001	2.455	4.856	C	2029	0012																	
86018000	4.910	5.220	R	1	6 35	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
824			3	10.9	51000	RIDE		7.5	7.6	7.6	8.0	6.7	6.4	6.8	6.8	6.9	7.0	6.6	6.8	7.0		
SW 31 AVE(4.9R)					FC3																	
2316221	5.029	5.200	C	1995	0213	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.0	
COMMUNITY ASPHALT CORP. (1997)					S RIDE			6.9	6.5	6.8	6.1											
86018000	5.220	6.547	R	1	1 35	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0		
824			2	3.7	34000	RIDE		7.0	7.0	7.1	6.8	6.5	6.4	6.6	6.2	6.4	6.3	6.4	6.3	6.0		
NW 10 AVE(5.3R)					FC95A																	
4305901	5.172	6.150	R	2016	0012	CRACKING		7.0	7.0	7.0	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0	
GENERAL ASPHALT CO., INC. (2018)					SPRIDE			5.9	6.0	5.9	6.1	6.4	7.6	7.3	7.4	7.4	7.2	7.1	7.2	7.2	6.8	
86018000	5.220	6.547	L	1	1 35	CRACKING		10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	9.5	7.5	7.0	7.0		
824			2	3.7	34000	RIDE		7.6	7.5	7.6	7.6	7.0	6.6	7.0	6.4	6.8	6.8	6.8	7.0	6.9		
S 28 AVE(5.3L)					FC95A																	
4305901	5.219	6.150	L	2016	0012	CRACKING		7.0	7.0	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.8	8.0	
GENERAL ASPHALT CO., INC. (2018)					SPRIDE			6.7	6.3	4.7*	6.4	6.2	7.7	7.6	7.2	7.3	6.7	7.0	7.0	7.0	6.6	
86018000	4.910	5.220	L	1	1 35	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5		
824			3	10.9	51000	RIDE		7.1	6.7	7.1	7.2	6.8	6.5	6.6	6.3	6.4	6.5	6.3	6.6	6.4		
S 30 AVE(5.0L)					FC3																	
2316221	5.029	5.200	C	1995	0213	CRACKING		8.5	8.5	8.5	8.5	8.5	9.0	9.0	9.0	9.0	9.0	7.5	7.5	8.3	6.5	
COMMUNITY ASPHALT CORP. (1997)					S RIDE			6.4	6.2	6.6	6.2	6.0	6.6	6.6	6.5	6.4	6.5	6.0	6.5	6.5	6.1	
86018000	2.335	4.910	L	1	1 40	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0		
824			3	10.9	51000	RIDE		8.3	8.3	8.2	8.2	7.7	7.6	7.4	7.2	7.4	7.5	7.4	7.4	7.2		
S 61 AVE(2.4L)					FC3																	
2274531	2.282	4.898	C	1994	0213	CRACKING		9.0	9.0	9.0	9.0	8.0	8.0	8.0	7.5	7.5	7.5	7.5	7.5	8.4	6.5	
THE DE MOYA GROUP INC. (1998)					S RIDE			6.5	7.0	7.0	7.0	6.9	6.7	6.6	6.7	6.7	6.7	6.6	6.5	6.6	6.2	
4484001	2.455	4.856	C	2029	0012																	
86018000	1.528	2.335	L	1	1 40	CRACKING		9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0		
824			2	7.6	45500	RIDE		6.6	6.5	6.5	6.4	5.6	6.3	6.1	5.8	5.9	7.3	7.3	7.2	7.1		
S 66 AVE(1.7L)					FC125																	
4114391	1.528	2.334	L	2006	0012	CRACKING		10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	
GENERAL ASPHALT CO., INC. (2009)					SPRIDE			7.1	6.8	7.1	7.4	7.4	7.2	7.2	7.3	7.3	7.3	7.2	7.3	7.3	6.9	
4463721	0.364	2.335	C	2027	0012																	
86018000	0.285	1.528	L	1	1 45	CRACKING		9.0	9.0	7.5	7.5	7.5	7.5	7.5	6.5	6.5	10.0	10.0	10.0	10.0		
824			3	3.1	42500	RIDE		6.5	6.5	6.7	6.4*	6.2*	6.4*	6.3	6.3	6.4	7.6	7.6	7.4	7.2		
UNSIGNED(0.3L)					FC125																	
4114391	0.285	1.528	L	2006	0012	CRACKING		9.5	9.5	9.5	9.0	8.5	8.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	
GENERAL ASPHALT CO., INC. (2009)					SPRIDE			7.6	7.4	7.2	7.2	7.2	7.0	6.9	7.1	6.8	6.9	6.8	6.8	6.8	6.4	
4463721	0.364	2.335	C	2027	0012																	
86018000	0.000	0.285	L	1	2 45	CRACKING		9.0	9.0	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0		
824			3	3.1	42500	RIDE		6.5	6.5	6.7	6.4*	6.2*		7.7	7.4	7.4	6.9	7.0	6.6	6.9		
MIRAMAR CITY LIMITS(0.0C)					FC125																	
4062781	0.000	0.257	C	2003	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	8.0	7.5	6.0*	
PAVEX CORPORATION (2006)					SPRIDE			6.9	6.7	6.7	6.6	6.5	6.2	5.8	5.7	5.6	6.4	5.7	5.7	6.3	5.9	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

											DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	SR	US	BMP	G	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR											FUTURE										
INTERSECT	AT	(MP)	(SIDE)							=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012									
ITMSEG-P	W	BMP	W	EMP	RW	FY-P	W	KMX-P																								
CONTRACTOR	(AGE	ONE	YEAR)					ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030								
ITMSEG-F	W	BMP	W	EMP	RW	FY-F	W	KMX-F															(PMRS)									
86020000	5	1	0.000	1.813	R	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	6.5	6.5									
BROWARD BLVD(0.0C)					3	2.1	40500	RIDE	8.3	7.8	8.0	7.6	7.2	7.1	6.8	6.5	7.1	6.9	7.1	7.0	7.0	6.9										
4287261	0.012	1.813	C	2015	0012	CRACKING	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0								
COMMUNITY ASPHALT CORP.			(2017)			SPRIDE	6.6	6.3	6.4	6.5	7.3	7.6	7.4	6.8	6.9	7.3	6.9	6.4	6.1	5.7												
86020000	5	1	1.813	4.200	R	1	1	45	CRACKING	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0									
VICTORIA PK RD(1.9R)					3	2.8	47500	RIDE	6.7	6.4*	6.4*	6.4*	6.0*	6.0*	5.8	5.7	5.4*	7.9	7.8	7.7	7.8											
4114401	1.834	4.200	C	2006	0012	CRACKING	9.0	9.0	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*									
PAVEX CORPORATION			(2009)			SPRIDE	7.6	7.6	7.7	7.1	7.1	7.1	6.9	6.9	6.9	6.9	6.8	6.6	6.6	6.5	6.1											
4461851	1.818	4.307	C	2023	0012																											
86020000	5	1	4.200	5.736	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0									
NE 33 CT(4.3R)					3	5.2	50000	RIDE	8.3	8.3	8.3	8.3	7.5	7.5	7.4	7.2	7.5	7.6	7.6	7.4	7.3											
4360971	4.200	5.740	R	2018	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0									
COMMUNITY ASPHALT CORP.			(2020)			SPRIDE	7.4	7.4	7.4	7.1	7.3	7.1	7.1	8.0	7.9	7.8	8.0	7.9	7.9	7.9	7.9	7.5										
86020000	5	1	5.736	8.254	R	1	8	45	CRACKING	9.0	9.0	7.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0									
COMMERCIAL BLVD(5.7C)					3	2.3	49000	RIDE	7.1	7.0	7.1	7.0	6.7	6.6	7.3	6.9	7.3	7.1	7.1	7.1	7.1	7.1										
2280931	6.831	8.050	C	2004	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5										
COMMUNITY ASPHALT CORP.			(2006)			SPRIDE	7.0	6.9	7.0	6.7	6.6	6.6	6.4	6.3	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.4										
4461881	5.751	8.254	R	2023	0012																											
86020000	5	1	8.254	8.756	R	1	1	45	CRACKING	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	6.5									
SE 7 ST(8.3R)					3	4.0	50500	RIDE	6.7	6.7	6.7	6.6	6.6	6.3*	6.4	6.2	6.3	6.3	6.3	6.3	6.2	6.2	6.2									
4229981	8.274	8.769	C	2012	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.6	8.5								
WEEKLEY ASPHALT PAVING, IN(2013)						RIDE	7.4	7.4	7.5	7.0	7.2	7.0	6.9	6.8	6.7	6.9	6.7	6.6	6.6	6.7	6.7	6.7	6.3									
86020000	5	1	8.756	11.863	R	1	1	45	CRACKING	9.0	9.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5									
ATLANTIC BLVD(8.8C)					3	4.9	50500	RIDE	7.4	7.4			7.6	7.7	7.4	7.0	7.4	7.1	7.2	6.8	7.2											
			(2004)			CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*									
4484011	8.756	11.789	C	2029	0012									6.6	6.5	6.3	6.3	6.3	6.3	6.3	6.3	6.2	5.8									
86020000	5	1	11.863	15.314	R	1	1	45	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0									
NE 39 ST(12.1C)					3	5.8	41000	RIDE	6.9	6.8	6.8	6.7	6.2*	6.2*	6.0	6.9	6.8	6.9	6.8	6.7	6.8	6.8	6.8									
			(2022)			CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	9.0									
						RIDE	6.6	6.5	6.5	6.5	6.4	6.4	6.3	6.3	6.3	6.3	6.3	5.9	8.0	8.0	8.0	7.9	7.5									
86020000	5	1	11.863	15.314	L	1	1	45	CRACKING	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0									
NE 39 ST(12.1C)					3	5.8	41000	RIDE	7.7	7.4	7.5	7.3	6.6	6.6	6.3	7.2	7.4	7.3	7.3	7.2	7.2	7.2	7.2									
			(2022)			CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	9.0									
						RIDE	7.2	7.1	6.8	6.3	6.3	6.3	6.2	6.2	6.2	6.0	5.4*	7.8	7.7	7.7	7.6	7.2										
86020000	5	1	8.756	11.863	L	1	1	45	CRACKING	9.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0									
ATLANTIC BLVD(8.8C)					3	4.9	50500	RIDE	7.5	7.8			7.7	7.7	7.6	7.2	7.6	7.4	7.4	7.6	7.3											
			(2004)			CRACKING	9.0	9.0	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*									
4484011	8.756	11.789	C	2029	0012									6.9	6.8	6.8	6.7	6.7	6.7	6.5	6.6	6.2										
86020000	5	1	8.254	8.756	L	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0									
FIFTH CT SE(8.5L)					3	4.0	50500	RIDE	7.5	7.4	7.4	7.3	6.6	6.6	6.5	6.7	6.8	6.9	6.5	6.5	6.5	6.5	6.5									
4229981	8.274	8.769	C	2012	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5									
WEEKLEY ASPHALT PAVING, IN(2013)						RIDE	8.4	8.2	8.0	7.8	7.8	7.7	7.6	7.6	7.6	7.6	7.6	7.6	7.5	7.2	7.5	7.5	7.1									
86020000	5	1	5.736	8.254	L	1	8	45	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0									
COMMERCIAL BLVD(5.7C)					3	2.3	49000	RIDE	5.4*	5.6*	5.5*	5.4*	5.0*	5.1*	6.7	6.2	6.6	6.4	6.5	6.3	6.3	6.3										
2280931	6.831	8.050	C	2004	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5										
COMMUNITY ASPHALT CORP.			(2006)			SPRIDE	6.1	6.0	6.0	5.9	5.7	5.9	6.2	5.5	5.6	5.6	5.6	5.6	5.6	5.6	5.4*											
4461881	5.740	8.254	L	2023	0012																											

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKM-M	P	=====															
ITMSEG-P	(AGE ONE YEAR)				ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F																	
86020000	4.200	5.736	L	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0		
5 1			3	5.2	50000	RIDE	7.9	7.8	7.8	7.7	6.9	7.1	6.8	6.2	6.7	7.1	7.1	6.9	6.8			
NE 33 CT(4.3L)					FC125M																	
4360971	4.200	5.740	L	2018	0012	CRACKING	8.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.7	9.0	
COMMUNITY ASPHALT CORP.				(2020)	SPRIDE		6.8	6.8	6.8	6.6	6.6	6.4	6.5	6.5	7.7	7.6	7.5	7.6	7.6	7.3	6.9	
86020000	1.813	4.200	L	1	1 45	CRACKING	9.0	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0		
5 1			3	2.8	47500	RIDE	6.5	6.4*	6.6	6.4*	5.9*	6.1*	5.8	5.9	5.8	7.5	7.5	7.5	7.5	7.4		
VICTORIA PARK RD(1.9L)					FC125M																	
4114401	1.834	4.200	C	2006	0012	CRACKING	9.0	9.0	8.5	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	6.0*	
PAVEX CORPORATION				(2009)	SPRIDE		7.3	7.3	7.3	6.9	6.9	6.7	6.4	6.7	6.6	6.6	6.4	6.4	6.3	5.9		
4461851	1.818	4.307	C	2023	0012																	
86020000	1.080	1.813	L	1	1 35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	6.5	6.5	6.5		
5 1			3	2.5	63000	RIDE	8.4	8.0	7.6	7.3	6.8	6.8	6.4	6.4	7.0	6.9	6.9	6.5	6.5	6.4		
EIGHTH AVE NE(1.1L)					FC125A																	
4287261	0.012	1.813	C	2015	0012	CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.3	8.5	
COMMUNITY ASPHALT CORP.				(2018)	SPRIDE		6.3	6.5	6.6	6.3		7.9	7.9	7.7	7.7	7.4	7.6	6.9	7.4	7.0		
86020000	0.000	1.080	L	1	1 35	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	6.5	6.5	6.5		
5 1			3	2.1	40500	RIDE	8.4	8.0	7.6	7.3	6.8	6.8	6.4	6.4	7.0	6.9	6.9	6.5	6.5	6.4		
BROWARD BLVD(0.0C)					FC125A																	
4287261	0.012	1.813	C	2015	0012	CRACKING	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.9	8.0	
COMMUNITY ASPHALT CORP.				(2017)	SPRIDE		6.3	6.5	6.6	6.3	7.4	7.0	7.0	6.8	7.0	7.3	7.0	6.7	6.6	6.2		
86028000	0.000	1.428	R	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5		
834			3	3.7	32000	RIDE	7.6	7.7	7.4	7.5	6.8	7.0	6.8	6.2	6.6	6.6	6.6	6.7	6.5	6.4		
CORAL SPRINGS CITY LIMIT(0.0C)					FC125																	
2280371	0.000	1.684	C	1998	0012	CRACKING	9.0	9.0	9.0	8.0	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	5.0*		
COMMUNITY ASPHALT CORP.				(2000)	S RIDE		6.3	6.3	6.3	6.5	6.5	6.5	6.4	6.0	6.2	6.1	6.2	6.1	6.1	6.1	5.7	
4461941	0.011	1.451	C	2024	0012																	
86028000	1.428	3.221	R	1	1 45	CRACKING	10.0	10.0	9.0	7.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0		
834			3	4.2	38000	RIDE	7.8	7.7	7.9	7.6	7.1	7.1	6.9	6.8	6.7	6.5	6.4	8.1	8.0			
BELMONTE BLVD(1.5R)					FC95																	
4138381	1.428	3.236	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	
HUBBARD CONSTRUCTION COMPA(2011)					SPRIDE		7.9	7.9	8.0	7.8	7.7	7.7	7.6	7.6	7.6	7.6	7.4	7.5	7.3	6.9		
86028000	3.221	4.763	R	1	1 45	CRACKING	10.0	10.0	10.0	8.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*		
834			3	2.9	42500	RIDE	7.8	7.6	7.8	7.6	7.1	7.2	7.0	6.9	7.1	6.9	7.0	6.9	6.9	6.8		
NW 54 AVE(3.3C)					FC95																	
4216561	3.221	4.763	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5	
GENERAL ASPHALT CO., INC. (2013)					SPRIDE		8.3	8.2	8.2	7.8	7.9	7.7	7.7	7.7	7.7	7.7	7.7	7.6	7.6	7.2		
86028000	4.763	5.805	R	1	1 45	CRACKING	6.5	9.0	6.5	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
834			3	9.6	54500	RIDE	6.9	7.5	7.4	7.4	6.6	6.8	6.7	6.7	6.9	6.9	6.9	6.8	6.7			
FESTIVAL FLEA MARKET(5.4R)					UNKW																	
2280721	4.754	7.558	C	2003	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.5	7.5	8.1	6.5	
APAC-FLORIDA INC				(2005)	SPRIDE		6.5	6.8	6.8	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.2	6.0	6.1	6.1	5.7	
86028000	5.805	7.070	R	1	1 45	CRACKING	6.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0		
834			3	9.2	39525	RIDE	6.9			7.5	6.6	6.5	6.6	6.9	7.0	7.0	6.5	6.5	5.9			
CROSSROADS SHOPPING CENT(5.9C)					FC125																	
2280721	4.754	7.558	C	2003	0012	CRACKING	9.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.0*	6.0*	4.5*	4.5*	3.0*		
APAC-FLORIDA INC				(2003)	SPRIDE		6.3	6.5	6.5	6.4	6.6	6.8	6.7	6.6	6.3	6.5	6.1	6.1	6.1	5.7		
4461951	6.078	7.139	C	2024	0012																	
86028000	7.070	7.187	R	1	6 35	CRACKING	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0		
834			3	4.1	57500	RIDE	6.9	6.0*	5.3*	5.4*	6.6	6.5	6.6	6.9	7.0	7.0	6.5	6.5	5.9			
ANDREWS AVE(7.1R)					UNKW																	
2280721	4.754	7.558	C	2003	0012	CRACKING	9.0	7.0	7.0	7.0		6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.0*		
APAC-FLORIDA INC				(2004)	SPRIDE		6.3	6.5	6.5	6.4												
4461951	6.078	7.139	C	2024	0012																	
86028000	7.187	7.586	R	1	1 35	CRACKING	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
834			4	4.1	57500	RIDE	6.9	6.0*	5.3*	5.4*	4.4*	7.1	7.1	7.1	6.7	6.5	6.6	6.7	6.5			
NW 8 AVE(7.3R)					UNKW																	
				(2024)	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	6.5	6.5	9.0	9.0	8.5	
					RIDE		6.5												5.5	5.1*		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD

RDWYID	SR	US	BMP	G_BMP	EMP	G_EMP	RW	SYS	TYP	SPD	AADT	DISTRESS	RATINGS	SURVEYED YEAR										FUTURE			
INTERSECT AT (MP SIDE)	AT	MP	(MP SIDE)					%	ADT			=====		2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	CONTRACTOR	(AGE ONE YEAR)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE						2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F			W_BMP	W_EMP	RW	FY-F	WKM-F																				
86028000	834	NE 2 AVE(8.1R)	7.586	8.122	R	1	7	45	CRACKING	10.0	10.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0		10.0	10.0	10.0	9.0	
					3	4.1	57500	FC95	RIDE	6.9	6.2*	6.9	7.4	6.2*	5.5*	5.8	5.3*					7.4	7.2	7.3	7.2		
		(2025)							CRACKING	8.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.9	9.0	10.0	9.5
									RIDE	7.2	7.0	7.0	6.6	6.6	6.2	6.3	6.2	6.3	6.3	6.3	6.2	6.3	6.1	6.9	7.1	6.7	
86028000	834	NE 3 AVE(8.1C)	8.122	9.491	R	1	45	CRACKING	5.5*	5.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	9.0		
					3	3.6	39000	FC125M	RIDE	6.2*	6.7	5.8*	5.9*	5.6*	5.7*	5.7	5.1*					7.4	7.2	7.3	7.2		
		ASPHALT GROUP, INC.			C	2021	0012	CRACKING	8.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	9.6	9.0	
		(2023)							SPRIDE	7.2	7.0	7.0	6.6	6.6	6.2	6.3	6.2	6.3	6.2	6.3	6.2	6.3	6.1	7.2	7.1	7.0	6.6
86028000	834	NE 3 AVE(8.1C)	8.122	9.491	L	1	45	CRACKING	7.0	7.0	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*					10.0	10.0	10.0	10.0		
					3	3.6	39000	FC125M	RIDE	6.4*	6.7	6.9	6.6	6.1*	6.2*	6.1	5.8					7.3	6.7	7.0	7.0		
		ASPHALT GROUP, INC.			C	2021	0012	CRACKING	10.0	10.0	10.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	9.0	
		(2023)							SPRIDE	7.0	6.8	6.5	6.4	6.3	6.0	6.2	6.1	6.1	6.1	6.0	6.0	7.3	7.1	7.1	7.1	6.7	
86028000	834		7.586	8.122	L	1	7	45	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		10.0	10.0	10.0	10.0		
					3	4.1	57500	FC95	RIDE	7.4	7.5	7.6	7.5	6.7	7.0	7.0	6.6					7.3	6.7	7.0	7.0		
		(2025)							CRACKING	10.0	10.0	10.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	9.0	9.0	10.0	9.5	
									RIDE	7.0	6.8	6.5	6.4	6.3	6.0	6.2	6.1	6.1	6.1	6.0	6.0	6.8	6.4	7.4	7.0	7.0	
86028000	834	FRONTAGE ROAD(7.3L)	7.118	7.586	L	1	35	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		
					3	4.1	57500	UNKW	RIDE	6.7	5.7*	5.8	5.8	5.2*	6.4	6.3	6.2	6.2	6.2	6.2	6.2	6.2	6.2	5.9	6.0		
		(1986)							CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.8	6.5	
									RIDE	6.0	5.9	6.0	5.1*	5.4*	5.2*	5.5	5.3*	5.0*	5.2*	5.1*	4.9*	5.5	5.1*	5.5	5.1*		
86028000	834	CROSSROADS SHOPPING CENT(5.9C)	5.805	7.118	L	1	45	CRACKING	9.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
					3	9.2	39525	FC125	RIDE	6.7			8.0	7.3	7.5	7.5	7.3	7.4	7.4	7.4	7.4	7.4	7.5	7.3	7.3		
		APAC-FLORIDA INC			C	2003	0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.7	5.0*	
		(2003)							SPRIDE	7.4	7.3	7.3	7.1	7.1	7.1	6.9	7.0	6.7	6.8	6.7	6.8	6.7	6.5	6.6	6.2		
		4461951			C	2024	0012																				
86028000	834	LAND FILL(5.4L)	4.763	5.805	L	1	45	CRACKING	9.0	9.0	9.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5		
					3	9.6	54500	UNKW	RIDE	6.7	7.3	7.2	6.8	6.2*	7.0	6.8	6.8	6.9	7.0	7.0	7.0	7.0	6.9	6.8			
		APAC-FLORIDA INC			C	2003	0012	CRACKING	9.5	9.5	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	7.0	7.0	5.5*		
		(2005)							SPRIDE	6.9	6.5	6.6	5.9	6.0	6.1	5.9	5.9	5.8	6.0	5.8	5.7	5.8	5.7	5.8	5.4*		
86028000	834	NW 54 AVE(3.3C)	3.221	4.763	L	1	45	CRACKING	10.0	10.0	10.0	8.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*		
					3	2.9	42500	FC95	RIDE	7.7	7.6	7.9	7.5	7.3	7.3	7.1	6.3	7.0	7.0	7.0	7.0	7.0	7.1	6.8	6.5		
		4216561			C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
		(2013)							SPRIDE	8.2	8.2	7.5	7.8	7.8	7.8	7.7	7.7	7.7	7.7	7.5	7.7	7.5	7.7	7.6	7.6	7.2	
86028000	834	SHOPPING CENTER ENT(1.6L)	1.428	3.221	L	1	45	CRACKING	8.5	8.5	7.0	6.5	6.5	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0		
					3	4.2	38000	FC95	RIDE	8.1	8.0	8.1	7.7	6.8	7.0	6.8	6.6	6.8	6.4	6.6	6.4	6.6	6.4	8.1	8.0		
		4138381			C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	8.7	7.5		
		(2011)							SPRIDE	7.8	7.8	7.7	7.7	7.7	7.7	7.6	7.5	7.4	7.4	7.4	7.4	7.4	7.4	7.3	7.3	6.9	
86028000	834	CORAL SPRINGS CITY LIMIT(0.0C)	0.000	1.428	L	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5		
					3	3.7	32000	FC125	RIDE	8.0	7.9	7.7	7.7	6.7	6.6	6.5	6.2	6.2	6.2	6.2	6.2	6.2	6.4	5.8	5.9		
		2280371			C	1998	0012	CRACKING	7.5	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.8	5.0*	
		COMMUNITY ASPHALT CORP.			(2000)				S	5.9	5.8	5.9	6.3	6.2	6.0	5.9	5.6	5.7	5.6	5.7	5.6	5.5	5.5	5.5	5.5	5.1*	
		4461941			C	2024	0012																				
86030000	A1A	OCEAN DR(0.2R)	0.000	0.879	R	1	35	CRACKING						9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5		
					3	1.6	26000	FC95A	RIDE					5.8	6.0	5.3*	4.9*	5.7	4.4*	3.7*	3.1*	4.1*					
		4287271			R	2014	0012	CRACKING	7.5	6.5	4.5*			10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.7	7.5	
		WEEKLEY ASPHALT PAVING, IN			(2017)				RIDE	4.0*	3.8*	4.8*		6.9	6.2	6.4	6.3	6.3	6.3	6.1	5.9	6.0	6.0	6.0	5.6		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

										DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	SR	US	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE									
INTERSECT AT (MP SIDE)	W BMP	W_EMP	W BMP	W_EMP	RW	FY-P	WKMX-P	ADT	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012									
CONTRACTOR (AGE ONE YEAR)	W_BMP	W_EMP			RW	FY-F	WKMX-F	ASTYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)								
86030000 A1A OCEAN CREST CLUB(	0.879	2.282		1.3R)	R	1	1	35	CRACKING	6.5	6.5	6.5		6.5	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*										
4168691 GENERAL ASPHALT CO., INC.	1.242	2.011		2.011	R	2010	0012	28000	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.0	8.0	7.0	7.0	6.5	6.5	6.5	5.5*								
4461991	0.905	2.288			C	2025	0012	FC95M	SPRIDE	6.3	5.8	6.6	6.1	6.0	6.6	5.8	5.7	5.2*	5.2*	5.1*	4.8*	4.9*	4.5*								
86030000 A1A MONROE ST(	2.282	2.497		2.3R)	R	1	1	35	CRACKING	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5									
4323231	2.288	2.547		2.288	R	2017	0012	28000	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	9.1	8.5								
COMMUNITY ASPHALT CORP.						(2021)		FC95M	RIDE	5.5	5.5	5.4*	5.0*	4.8*	4.7*	4.4*		6.8	6.4	6.7	6.0	5.7	5.3*								
86030000 A1A HOLLYWOOD BLVD(	2.497	4.104		2.6R)	R	1	1	35	CRACKING	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5									
4323231	2.547	4.104		2.547	R	2017	0012	25500	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	9.0	8.0								
COMMUNITY ASPHALT CORP.						(2021)		FC95M	RIDE	5.5	5.5	5.4*	5.0*	4.8*	4.7*			6.2	6.0	6.0	5.9	5.8	5.4*								
86030000 A1A FOREST ST(	4.104	5.351		4.4R)	C	1	1	35	CRACKING	6.5	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0									
4114321	4.122	5.193		4.122	C	2007	0012	11700	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*	4.5*								
COMMUNITY ASPHALT CORP.						(2010)		FC95	SPRIDE	6.1	6.2	6.0	5.8	5.5	5.6	5.3*	5.4*	5.1*	5.0*	4.9*	5.0*	4.8*	4.4*								
4484021	4.104	5.351			C	2028	0012																								
86030000 A1A CAMBRIDGE ST(	5.351	5.783		5.4R)	C	1	1	30	CRACKING	9.0	9.0	9.0	9.0	9.0	7.0	9.0	7.0	9.0		10.0	10.0	10.0									
						4	6.0	14600	RIDE	6.3*	6.2*	6.3	6.6	6.2	6.5	6.0	6.0	5.9		7.0	5.9										
						(2018)		FC95	CRACKING	10.0	10.0	10.0	10.0		10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.2*	7.0								
									RIDE						5.9	5.9	5.9	5.6	5.9	5.5	5.5	5.2*	4.8*								
86030000 A1A GULF STREAM RD	5.783	6.683		6.7R)	R	1	1	40	CRACKING	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0									
						2	6.0	14600	RIDE	7.0	7.3	6.9	7.1	6.4	6.5	6.4	6.0	6.2		7.8	7.6	7.5									
						(2021)		FC125M	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0								
									RIDE	7.5	7.6	7.7	7.4	7.5	7.5	7.4	7.4	7.7	7.7	7.7	7.7	7.6	7.2								
86030000 A1A NE 2 CT(	6.683	7.449		7.3R)	R	1	1	40	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0									
						3	2.5	23000	RIDE	5.9*	5.5*	6.0	5.5	4.7*	5.2*	4.8*	5.2*	5.2*		7.2	6.7	7.1									
						(2010)		FC95	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.4	7.0								
4461981	6.683	7.449			C	2024	0012		RIDE	7.1	7.1	7.2	7.1	6.9	7.1	7.0	6.8	6.7	6.7	6.7	6.4	6.4	6.0								
86030000 A1A FIFTH AVE SE	6.683	7.449		6.9L)	L	1	1	40	CRACKING	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0									
						3	2.5	23000	RIDE	5.2*	4.8*	4.9*	5.0*	4.3*	4.5*	4.5*	4.4*	4.8*		6.9	6.7	7.2									
						(2010)		FC95	CRACKING	10.0	10.0	9.0	8.5	8.5	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*								
4461981	6.683	7.449			C	2024	0012		RIDE	6.9	6.7	6.7	6.6	6.6	6.6	6.0	6.4	6.4	6.6	6.4	6.1	5.9	5.5								
86030000 A1A BILLY'S STONE CRAB(	6.360	6.683		2.7L)	L	1	1	40	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		10.0	10.0	10.0									
						2	6.0	14600	RIDE	7.1	7.1	6.9	6.6	6.2	6.1	6.0	6.0	5.9		7.5	7.5	7.4									
						(2021)		FC125M	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.4	8.5								
									RIDE	7.5	7.4	7.5	6.8	7.4	7.2	7.3	7.3	7.7	7.6	7.6	7.6	7.3	6.9								
86030000 A1A BILLY'S STONE CRAB(	5.783	6.360		2.7L)	L	1	1	40	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		10.0	10.0	10.0									
						2	6.0	14600	RIDE	7.1	7.1	6.9	6.6	6.2	6.1	6.0	6.0	5.9		7.5	7.5	7.4									
						(2021)		FC125M	CRACKING	10.0	10.0	10.0	10.0		9.5	9.5	9.5	10.0	10.0	10.0	10.0	9.3	8.5								
									RIDE	7.5	7.4	7.5	6.8		6.5	6.4	6.3	6.8	6.8	6.7	6.6	6.6	6.2								
86030000 A1A BILLY'S STONE CRAB(	2.497	4.104		2.7L)	L	1	1	35	CRACKING	3.5*		10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5									
						2	1.2	25500	RIDE	4.6*		7.8	7.6	6.8	6.6	6.2	5.7	5.8	5.9	5.4*	5.5	6.1									
								FC95M																							
4323231	2.497	4.104		2.497	L	2017	0012	28000	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	8.7	8.0								
COMMUNITY ASPHALT CORP.						(2021)		FC95M	RIDE	6.0	5.9	5.9	4.9*	4.9*	4.7*	4.4*		5.9	5.8	5.6	5.4*	5.5	5.1*								

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR														FUTURE
SR	US	G BMP	G EMP	LN	%T	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT	AT	(MP)	(SIDE)			SURFTYPE	=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P	ASTYPE																
CONTRACTOR	(AGE ONE YEAR)							2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																(PMRS)	
86030000	2.282	2.497	L	1	1	35	CRACKING	6.5		10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5		
A1A			3	1.6	28000	RIDE	6.0*			8.0	7.6	6.8	6.6	6.2	5.7	5.8	5.9	5.4*	5.5	6.1		
4323231	2.362	2.497	L	2017	0012	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	9.0	
COMMUNITY ASPHALT CORP.			(2021)			RIDE	6.0	5.9	5.9	4.9*	4.9*	4.7*	5.4*			6.6	6.5	6.3	6.3	6.3	5.9	
86030000	0.879	2.282	L	1	1	35	CRACKING	10.0	8.5	8.5		6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		
A1A			3	1.6	28000	RIDE	7.4	7.4	6.6			5.8	5.8	5.6	5.3*	5.4*	5.8	5.1*	5.6			
SEACREST PKWY(0.9L)							FC95															
4168691	1.242	2.011	L	2010	0012	CRACKING	10.0	10.0	10.0	9.5	9.5	8.5	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	5.5*	
GENERAL ASPHALT CO., INC.			(2013)			SPRIDE	7.4	7.2	7.2	7.2	7.0	6.9	6.9	6.8	6.3	6.3	6.3	6.2	6.3	6.3	5.9	
4461991	0.905	2.288	C	2025	0012																	
86030000	0.000	0.879	L	1	1	35	CRACKING					9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5		
A1A			3	1.6	26000	RIDE						6.4	6.8	6.6	6.1	6.4	6.9	6.7	6.3	5.5		
HEMISPHERES(0.3C)							FC95A															
4287271	0.124	0.774	L	2014	0012	CRACKING	6.5	6.5	4.5*		10.0	10.0	9.5	9.5	9.5	9.5	8.5	8.5	8.3	7.5		
WEEKLEY ASPHALT PAVING, IN(2017)						RIDE	5.9	6.1	5.4*		7.4	7.3	7.2	7.1	7.0	6.8	6.7	6.8	6.3	5.9		
86039000	0.000	2.482	R	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	6.0*	4.5*	4.5*		
814			3	3.1	54500	RIDE	6.9	6.9	6.7	6.5	6.2*	6.1*	6.1	5.8	6.1	6.0	6.0	6.0	5.7	5.9		
MARGATE CITY LIMITS(0.0C)							FC125															
4230021	0.484	1.786	R	2011	0012	CRACKING	4.5*	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	
RANGER CONSTRUCTION INDUST(2014)						SPRIDE	5.7	8.0	8.1	7.7	7.6	7.7	7.6	7.8	7.4	7.4	7.4	7.3	7.3	7.3	6.9	
86039000	0.000	2.482	L	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	7.0	7.0		
814			3	3.1	54500	RIDE	6.9	6.9	7.0	6.8	6.3*	6.5	6.4	6.2	7.3	7.2	7.3	7.3	7.1	7.2		
MARGATE CITY LIMITS(0.0C)							FC125															
4230021	0.484	1.786	L	2011	0012	CRACKING	7.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.9	8.0	
RANGER CONSTRUCTION INDUST(2014)						SPRIDE	6.9	7.9	8.0	7.7	7.7	7.8	7.7	7.4	7.5	7.6	7.4	7.4	7.4	7.3	6.9	
86040000	0.000	1.365	R	1	1	45	CRACKING	9.0	9.0	9.0	9.0	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*		
820			2	5.3	9900	RIDE	7.7	7.7	7.5	7.8	7.2	7.3	6.8	7.2	7.4	7.2	7.1	7.0	7.0			
PEMBROKE PINES CITY LIM(0.0C)							DGFC															
4216571	0.009	1.365	R	2011	0012	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	8.0	8.0	7.0	7.0	7.2	6.0*		
WEEKLEY ASPHALT PAVING, IN(2013)						SPRIDE	8.0	7.9	7.9	7.8	7.7	7.6	7.7	7.3	7.6	7.5	7.4	7.4	7.5	7.1		
86040000	1.365	1.667	R	1	1	45	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	6.5	6.5	
820			3	4.6	30000	RIDE	8.2	8.2	8.1	8.0	7.5	7.5	7.4	7.3	7.5	7.3	7.3	7.3	7.3	7.2		
SW 196 AVE(1.5R)							DGFC															
4216571	1.365	1.660	R	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.4	7.0	
WEEKLEY ASPHALT PAVING, IN(2013)						SPRIDE	8.2	7.9	8.0	7.8	7.8	7.8	7.8	7.6	7.5	7.3	7.0	7.1	6.9	6.9	6.5	
86040000	1.667	5.087	R	1	1	45	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	6.5	6.5	
820			3	4.5	41500	RIDE	8.2	8.2	8.1	8.0	7.5	7.5	7.4	7.3	7.5	7.3	7.3	7.3	7.3	7.2		
SW 186 AVE(2.2R)							FC95															
4270061	1.667	3.623	R	2013	0012	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.6	8.5	
COMMUNITY ASPHALT CORP.			(2015)			SPRIDE	7.1	7.2	8.7	8.3	8.4	8.4	8.3	8.3	8.2	8.2	8.2	8.1	8.1	8.1	7.7	
86040000	5.087	6.320	R	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	10.0	10.0		
820			3	4.7	50500	RIDE	7.8	7.6	7.9	7.5	7.2	7.3	7.0	6.7	6.9	6.8	6.5	7.7	7.8			
SW 149 AVE(5.3R)							OGFC															
			(2011)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.1	4.5*		
						RIDE	7.7	7.7	7.7	7.6	7.8	7.8	7.7	7.6	7.7	7.7	7.7	7.6	7.8	7.6		
86040000	6.320	7.870	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0		
820			4	2.1	59500	RIDE	8.1	8.0	7.5	7.9	7.3	7.3	7.0	7.8	7.8	7.9	7.7	7.8	7.7			
SW 136 AVE(6.5R)							DGFC															
			(2007)			CRACKING	9.0	9.0	8.5	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	5.0*		
						RIDE	7.6	7.5	7.5	7.7	7.7	7.9	7.8	7.7	7.6	7.6	7.7	7.6	7.7	7.3		
4462001	6.170	7.870	R	2024	0012																	
86040000	7.870	9.664	R	1	1	45	CRACKING	9.0	9.0	7.5	6.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0		
820			4	6.6	51000	RIDE	7.7	7.9	7.8	7.9	7.3	7.3	7.1	7.0		7.7	7.7	7.8	7.7			
SW 114 AVE(8.2R)							DGFC															
4168701	8.490	9.516	R	2008	0012	CRACKING	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	9.5	8.0	
			(2009)			RIDE	7.7	7.7	7.7	7.3	7.3	7.3	7.2	7.1	7.1	7.1	7.1	7.1	7.1	7.1	6.7	
4484031	7.870	9.664	C	2030	0012																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE	
SR US	G BMP	G_EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT	AT (MP)	(SIDE)			SURFTYPE		=====															
ITMSEG-P	W BMP	W_EMP	RW	FY-P	WKMX-P																	
CONTRACTOR	(AGE)	ONE YEAR			ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																(PMRS)	
86040000	9.664	10.489	R	3	1	45	CRACKING	9.0	9.0	7.5	6.5	6.5	4.5*	4.5*	4.5*	7.0		10.0	10.0	10.0		
820						52000	RIDE	7.7	7.9	7.8	7.9	7.3	7.3	7.1	7.0	7.3		7.8	7.8	7.7		
TANGLEDWOOD PLAZA(9.8R)																						
4168701	9.516	10.509	R	2008	0012		CRACKING	10.0	9.0	9.0	9.0	9.0	8.5	7.5	7.5	7.5	7.5	7.5	7.5	8.7	7.5	
				(2010)			RIDE	7.7	7.7	7.8	7.5	7.4	7.4	7.3	7.3	7.3	7.2	7.3	7.2	7.2	6.8	
86040000	10.489	13.410	R	3	1	40	CRACKING	10.0	10.0	10.0	10.0	8.5	7.0	7.0	6.0*	6.0*	4.5*	4.5*	4.5*	4.5*		
820						47500	RIDE	8.3	8.0	8.4	8.3	7.2	7.4	7.0	7.2	6.6	6.6	6.7	6.6	6.2		
DOUGLAS RD/NW 89 AVE(10.5R)																						
4216591	10.489	13.432	C	2011	0012		CRACKING	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	7.5	7.5	7.5	7.5	8.0	7.0	
COMMUNITY	ASPHALT	CORP.		(2013)			SPRIDE	8.1	8.0	8.1	8.0	8.0	8.1	7.9	7.8	7.8	7.8	7.8	7.8	7.8	7.4	
86040000	13.410	13.840	R	3	1	6	CRACKING	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		
820						48500	RIDE	6.4*	6.5	5.9	6.4	5.2*	5.8	5.1*	5.0*	4.5*	4.7*	4.7*	4.3*	4.3*		
SW 63 TER(13.6R)																						
4270071	13.432	13.860	C	2013	0012		CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	
GENERAL	ASPHALT	CO., INC.		(2015)			RIDE	4.0*	4.3*	6.5												
86040000	13.840	14.038	R	3	1	6	CRACKING	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		
820						48500	RIDE	6.4*	6.5	5.9	6.4	5.2*	5.8	5.1*	5.0*	4.5*	4.7*	4.7*	4.3*	4.3*		
SR 7(14.0C)																						
				(2020)			CRACKING	6.5	6.5	6.5					10.0	10.0	10.0	10.0	10.0	9.1	8.0	
							RIDE	4.0*	4.3*	3.4*					6.2							
86040000	14.038	15.241	R	3	1	1	CRACKING	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	6.5	6.5		
820						45000	RIDE	6.6	6.6	6.6	6.6	5.8	6.0	5.9	5.8	5.7	5.6	5.6	5.5	5.3*		
WALMART(14.2R)																						
4216592	14.038	15.241	C	2011	0012		CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.7	7.5	
COMMUNITY	ASPHALT	CORP.		(2015)			SPRIDE		8.5	7.7	7.8	7.7	7.8	7.9	7.7	7.4	7.5	7.5	7.5	7.5	7.1	
86040000	15.241	15.402	R	3	1	1	CRACKING	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	6.5	6.5		
820						45000	RIDE	6.6	6.6	6.6	6.6	5.8	6.0	5.9	5.8	5.7	5.6	5.6	5.5	5.3*		
S CIRCLE DR(15.3R)																						
				(2015)			CRACKING		10.0	10.0	9.0	9.0	9.0			7.0	7.0	7.0	7.0	7.0	6.0*	
4484041	15.233	16.521	C	2029	0012		RIDE		7.7	6.9	6.9	7.3	6.9			6.6	6.8	6.8	6.4	6.3	5.9	
86040000	15.402	15.625	C	1	6	30	CRACKING	10.0	10.0	10.0	9.0	8.5	7.0	7.5	7.0	7.5	7.0	10.0	10.0	10.0		
820						18500	RIDE	7.3	7.1	7.2	6.6	6.3	6.3	5.9	6.3	5.7	6.2	7.5				
PRESIDENTIAL CIR(15.5L)																						
2281601	15.402	15.625	C	2008	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.4	7.0	
COMMUNITY	ASPHALT	CORP.		(2010)			SPRIDE															
4484041	15.233	16.521	C	2029	0012																	
86040000	15.625	16.431	R	3	1	1	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0		
820						49500	RIDE	4.9*	5.1*	5.0*	5.1*	4.5*	4.3*	4.3*	4.2*	4.6*	4.5*		7.4	7.0		
ALLEY(15.7C)																						
2281601	15.625	16.431	R	2008	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.5	7.5	7.9	6.5	
COMMUNITY	ASPHALT	CORP.		(2011)			SPRIDE	6.5	6.7	6.5	6.9	6.9	7.0	6.8	6.7	5.9	5.9	6.0	5.9	5.7	5.3*	
4484041	15.233	16.521	C	2029	0012																	
86040000	16.431	16.826	R	3	1	6	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0		
820						49500	RIDE	4.9*	5.1*	5.0*	5.1*	4.5*	4.3*	4.3*	4.2*	4.6*	4.5*		5.4*	4.9*		
CALLE LARGO(16.4R)																						
				(2011)			CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.5	
							RIDE	5.0*	5.1*	5.9	4.3*											
86040000	18.394	19.956	R	2	1	1	CRACKING	10.0	7.0	6.0*	5.5*	3.5*	3.5*	3.5*	1.0*	1.0*	1.0*	1.0*		10.0		
820						15772	RIDE	6.6	7.1	7.7	7.7	6.9	6.8	6.3	6.2	6.4	6.1	5.7		7.4		
S 16 AVE(18.5R)																						
4138351	18.394	19.764	C	2009	0012		CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.3	6.0*	
WEEKLEY	ASPHALT	PAVING,		(2012)			SPRIDE	6.9	7.1	7.3	6.8	6.7	6.6	6.5	6.7	6.5	6.3	6.0	5.9	5.8	5.4*	
4476541	18.394	19.956	C	2024	0012																	
86040000	18.394	19.956	L	2	1	1	CRACKING	8.5	7.0	6.0*	5.5*	3.5*	3.5*	3.5*	1.0*	1.0*	1.0*	1.0*	10.0	10.0		
820						15772	RIDE	6.6	6.7	7.6	7.4	6.2	6.3	6.3	5.8	5.7	5.5	5.6	8.0	7.6		
HARRISON ST(18.4L)																						
4138351	18.394	19.764	C	2009	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	7.5	7.5	7.0	7.0	7.0	5.5*	
WEEKLEY	ASPHALT	PAVING,		(2011)			SPRIDE	7.1	7.0	7.1	7.0	6.7	6.7	6.5	6.5	6.0	6.3	5.9	5.9	5.9	5.5	
4476541	18.394	19.956	C	2024	0012																	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)					SURFTYPE																	
ITMSEG-P	W BMP	W_EMP	RW	FY-P	WKMX-P																	
CONTRACTOR (AGE ONE YEAR)					ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																	
86040000	16.431	16.826	L	1	1 35	CRACKING		6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	10.0		
820			3	2.2	49500	RIDE		5.8*	5.9*	6.1	5.8	5.9	5.4*	5.2*	5.0*	5.1*	5.3*		6.3	6.1		
N 31 AVE(16.4L)					FC95																	
				(2011)		CRACKING		8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	4.5*	
						RIDE		5.8	5.5	6.4	5.5	5.7	5.8	6.0	5.6	5.3*	4.9*	4.6*	4.8*	5.3*	4.9*	
86040000	15.625	16.431	L	1	1 35	CRACKING		6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	10.0		
820			3	4.6	49500	RIDE		5.8*	5.9*	6.1	5.8	5.9	5.4*	5.2*	5.0*	5.1*	5.3*		7.4	7.3		
TO 86040215(15.6L)					FC95																	
2281601	15.625	16.431	L	2008	0012	CRACKING		10.0	10.0	10.0	8.5	8.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	5.0*	
COMMUNITY ASPHALT CORP.				(2011)	SPRIDE			6.8	6.8	6.8	5.7	5.9	5.8	5.9	6.0	5.9	5.4*	5.5	5.3*	5.5	5.1*	
4484041	15.233	16.521	C	2029	0012																	
86040000	15.241	15.402	L	1	6 35	CRACKING		10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0		
820			3	7.2	45000	RIDE		7.3	7.1	7.2	7.1	6.3	6.3	6.2	6.3	6.3	6.2	6.3	6.4	6.4		
CIRCLE DR N(15.3L)					FC95																	
				(2015)		CRACKING				10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	7.5	
						RIDE				5.7												
4484041	15.233	16.521	C	2029	0012																	
86040000	14.038	15.241	L	1	1 35	CRACKING		10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0		
820			3	7.2	45000	RIDE		7.3	7.1	7.2	7.1	6.3	6.3	6.2	6.3	6.3	6.2	6.3	6.4	6.4		
N 59 AVE(14.1L)					FC95																	
4216592	14.038	15.241	C	2011	0012	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.7	7.5	
COMMUNITY ASPHALT CORP.				(2015)	SPRIDE			8.5	7.7	7.8	7.7	7.6	7.7	7.6	7.7	7.5	7.4	7.5	7.5	7.6	7.2	
86040000	13.840	14.038	L	1	6 35	CRACKING		10.0	10.0	10.0	9.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5		
820			3	4.2	48500	RIDE		7.3	6.5	7.2	7.1	6.0	6.9	6.5	5.3*	5.3*	5.7	5.5	5.5	5.6	5.5*	
SR 7(14.0C)					DGFC																	
				(2020)		CRACKING		6.5	6.5	6.5	3.5*			10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
						RIDE		5.5	5.2*	5.4*	5.0*			4.3*	6.3	5.8	5.8	5.9	5.7			
86040000	13.410	13.840	L	1	1 35	CRACKING		10.0	10.0	10.0	9.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5		
820			3	4.2	48500	RIDE		7.3	6.5	7.2	7.1	6.0	6.9	5.3*	5.3*	5.7	5.5	5.5	5.6	5.2*		
NW 64 AVE(13.5L)					FC125																	
4270071	13.432	13.860	C	2013	0012	CRACKING		6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.8	7.5	
GENERAL ASPHALT CO., INC.				(2015)	RIDE			5.5	5.2*	7.5	6.9	6.5	6.6	6.9	6.4	6.4	6.1	6.4	6.1	5.7	5.3*	
86040000	10.489	13.410	L	1	1 40	CRACKING		10.0	10.0	10.0	10.0	9.0	7.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*		
820			3	3.7	47500	RIDE		8.7	8.6	8.6	8.5	7.7	7.9	7.7	7.7	7.4	7.3	7.3	7.1	6.9		
DOUGLAS RD(10.5L)					DGFC																	
4216591	10.489	13.432	C	2011	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.6	8.5	
COMMUNITY ASPHALT CORP.				(2013)	SPRIDE			8.3	8.3	8.4	8.1	8.1	8.2	8.0	7.9	7.9	8.0	8.0	7.8	7.9	7.5	
86040000	9.664	10.489	L	1	1 45	CRACKING		10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5		10.0	10.0	10.0		
820			3	3.4	52000	RIDE		8.2	8.3	8.3	8.2	7.7	7.5	7.2	7.1	7.2		7.9	7.8	7.8		
NW 98 AVE(9.8L)					DGFC																	
4168701	8.490	10.509	L	2008	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5	
				(2010)	RIDE			7.7	7.8	7.8	7.6	7.5	7.7	7.6	7.4	7.5	7.3	7.4	7.4	7.4	7.0	
86040000	7.870	9.664	L	1	1 45	CRACKING		10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5		10.0	10.0	10.0	10.0		
820			3	6.6	51000	RIDE		8.2	8.3	8.3	8.2	7.7	7.5	7.2	7.1		7.5	7.6	7.6	7.4		
NW 114 AVE(8.2L)					DGFC																	
4168701	8.490	10.509	L	2008	0012	CRACKING		10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	6.0*	
				(2009)	RIDE			7.4	7.3	7.3	7.1	7.1	7.0	7.0	7.1	7.0	6.9	7.1	7.0	7.2	6.8	
4484031	7.870	9.664	C	2030	0012																	
86040000	6.320	7.870	L	1	1 45	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
820			4	2.1	59500	RIDE		8.5	8.2	8.2	8.1	7.5	7.6	7.6	8.0	8.0	7.9	7.9	8.1	8.0		
CENTURY VILLAGE(6.5L)					DGFC																	
				(2007)		CRACKING		10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	5.0*	
						RIDE		8.0	7.9	8.1	7.8	7.8	7.9	7.8	7.9	7.9	7.9	7.8	7.9	7.9	7.5	
4462001	5.861	7.870	L	2024	0012																	
86040000	5.087	6.320	L	1	1 45	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	10.0	10.0		
820			3	4.7	50500	RIDE		8.2	7.7	7.7	7.7	7.5	7.5	7.3	7.5	7.4	7.4	7.5	7.6	7.7		
NW 142 AVE(6.2L)					OGFC																	
				(2011)		CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.2	5.0*	
						RIDE		7.4	7.5	7.5	7.5	7.5	7.3	7.5	7.4	7.6	7.3	7.4	7.3	7.6	7.4	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																							
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR															FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKM-F	ASTYPE	=====																
ITMSEG-P	(AGE ONE YEAR)							2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)		
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM-F																		
ITMSEG-F																							
86040000	1.667	5.087	L	1	1 45	CRACKING		10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5			
820			3	4.5	41500	RIDE		8.3	8.3	8.3	8.3	7.6	7.5	7.4	7.4	7.4	7.3	7.3	7.3	7.2			
NW 186 AVE(2.2L)					FC95																		
4270061	1.667	5.087	L	2013	0012	CRACKING		4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.6	8.5		
COMMUNITY ASPHALT CORP.				(2015)	SPRIDE			7.2	7.2	8.7	8.4	8.4	8.4	8.3	8.4	8.3	8.3	8.3	8.2	8.3	7.9		
86040000	0.000	1.667	L	1	1 45	CRACKING		10.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5			
820			2	5.3	9900	RIDE		8.3	8.2	8.1	8.2	7.5	7.4	7.3	7.0	6.9	6.5	6.5	6.6	6.8			
PEMBROKE PINES CITY LIMITS(0.0C)					DGFC																		
4216571	0.009	1.660	L	2011	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0		
WEEKLEY ASPHALT PAVING, INC				(2013)	SPRIDE			8.1	7.9	7.8	7.7	7.6	7.8	7.7	7.7	7.7	7.7	7.7	7.6	7.6	7.2		
86040005	0.000	0.289	C	1	6 25	CRACKING				9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0			
820			2	2.6	7100	RIDE				7.3	7.2												
HOLLYWOOD CITY LIMITS(0.0C)					FC95MR																		
						CRACKING		7.0	7.0	7.0	6.5	6.5	6.5	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	2.0*		
4476541	0.000	0.289	C	2024	0012	RIDE																	
86040215	0.000	0.277	C	1	1 25	CRACKING						8.5	9.0	9.0	9.0	9.0	7.5	10.0	10.0	10.0			
820			3	2.2	25000	RIDE										5.9	5.7	7.2	8.2	8.2			
EB HOLLYWOOD CIR(0.0C)					DGFC																		
				(2010)		CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	8.0	6.5		
						RIDE		8.1	8.0	8.0	7.3	7.2	7.2	7.1	7.1	6.7	6.8	6.7	6.7	6.5	6.1		
86050000	2.039	2.497	C	1	6 30	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	4.5*	4.5*		
A1A			2	23.6	16000	RIDE		7.1	7.1	7.1	6.7	6.0	5.9	5.9	6.0	5.3*	5.5	5.4*	5.3*	5.5			
POINSETTIA DR(2.2L)					FC95A																		
4306011	2.040	2.497	C	2016	0012	CRACKING		4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
WEEKLEY ASPHALT PAVING, INC				(2018)	RIDE			5.6	5.4*	5.4*	5.7	5.7	7.3										
86050000	2.497	3.334	R	1	1 30	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0			
A1A			2	4.1	33500	RIDE		6.5	6.6	6.4	6.2	5.6	5.9	7.6	7.4	5.3*	5.3*	5.6	5.5	5.1*			
					FC95A																		
4306011	2.497	3.320	R	2016	0012	CRACKING		9.0	7.5	7.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0		
WEEKLEY ASPHALT PAVING, INC				(2018)	RIDE			5.3*	5.6	5.4*	5.9	5.9	6.6	6.4	6.3	6.6	6.5	6.7	6.3	6.3	5.9		
86050000	3.334	4.322	R	1	6 30	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0			
A1A			1	3.8	18800	RIDE		7.8	7.8	7.8	7.8	7.1	6.9	7.0	6.7	6.9	6.6	6.4	6.6	6.2			
PED CROSSWALK(3.5C)					FC125A																		
4336884	3.334	4.322	C	2014	0005	CRACKING		9.0		8.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
RUSSELL ENGINEERING, INC				(2017)	SPRIDE			5.9	6.4				5.6	5.6									
86050000	4.322	5.363	R	1	1 35	CRACKING		7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	6.5	10.0	10.0			
A1A			2	7.8	20200	RIDE		6.5	6.3*	6.4	6.4	6.1	6.1	5.5	5.6	5.6	5.5	5.9	7.8	7.6			
ATLANTIC BLVD N(4.5R)					FC95M																		
4168721	4.310	5.365	C	2009	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.8	7.5		
GENERAL ASPHALT CO., INC.				(2011)	SPRIDE			7.5	7.5	7.6	7.2	7.2	6.6	6.6	6.4	6.6	6.5	6.5	6.4	6.5	6.1		
86050000	5.363	6.434	R	1	1 35	CRACKING		10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	4.5*	4.5*			
A1A			2	1.9	22000	RIDE		7.5	7.5	7.0	7.0	6.4	6.6	6.3	6.3	6.4	6.3	6.1	6.1	6.0			
OAKLAND PARK BLVD(5.4C)					FC95M																		
				(2019)		CRACKING		4.5*	10.0	10.0	10.0			10.0	10.0	9.0	9.0	9.0	9.0	10.0	9.0		
						RIDE		5.8	7.8	7.9	7.7			7.5	7.3	7.3	7.3	7.4	7.3	7.4	7.0		
86050000	6.434	7.443	R	1	1 30	CRACKING		6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
A1A			2	4.4	21500	RIDE		5.5*	5.3*	5.3*	6.3	5.4*	5.4*	5.1*	4.9*	4.7*	4.7*	4.9*	4.9*	4.7*			
PALM AVE(6.5R)					FC125																		
2279511	6.656	7.443	C	2000	0012	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	7.0	5.5*		
WEEKLEY ASPHALT PAVING, INC				(2003)	SPRIDE			4.9*	4.8*	5.0*	4.4*	4.6*	4.6*	4.5*	4.6*	4.5*	4.6*	4.6*	4.4*	4.4*	4.0*		
4484051	6.428	7.443	C	2026	0012																		
86050000	7.443	8.703	R	1	1 35	CRACKING		9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
A1A			1	2.8	17700	RIDE		5.5*	5.7*	5.5	5.4*	6.2	6.4	6.1	6.0	5.9	6.2	6.0	5.9	5.6			
PINE AVE(7.5C)					FC125M																		
4416281	7.461	8.678	R	2021	0012	CRACKING		9.0	8.0	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	9.5		
H&R PAVING INC				(2025)	RIDE			5.5	5.6	5.8	5.7	5.8	5.6	5.5	5.4*	5.4*	5.1*	5.9	5.8	6.7	6.3		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR														FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)																						
ITMSEG-P	W BMP	W_EMP	RW	FY-P	WKM-X-P																	
CONTRACTOR (AGE ONE YEAR)					ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																(PMRS)	
86050000	8.703	9.792	R	1	1 35	CRACKING		9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
A1A			1	2.8	17700	RIDE		5.5*	5.7*	5.5	5.4*	6.2	6.4	6.1	6.0	5.9	6.2	6.0	5.9	5.6		
SE 12 ST(9.2R)					FC125																	
2281141	7.443	9.267	C	2002	0012	CRACKING		9.0	8.0	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	7.4	6.0*	
APAC-FLORIDA INC				(2004)		RIDE		5.5	5.6	5.8	5.7	5.8	5.6	5.5	5.4*	5.4*	5.1*	5.9	5.8	5.0*	4.6*	
4416282	8.678	9.792	C	2021	0012																	
86050000	9.792	10.443	R	1	1 35	CRACKING		6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
A1A			2	3.3	13302	RIDE		4.9*	4.9*	5.1*	4.9*	7.3	7.0	6.8	6.8	6.6	6.0	6.2	6.3	5.9		
ATLANTIC BLVD(9.9C)					FC125																	
				(2018)		CRACKING		10.0	10.0	9.0	9.0		9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.1	7.0	
						RIDE		5.9	5.9	5.6	5.6		5.2*	5.3*	5.7	5.8	5.6	5.5	5.7	5.8	5.4*	
86050000	10.443	12.108	R	1	1 35	CRACKING		8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5		
A1A			1	4.5	8100	RIDE		6.8	7.4	7.3	7.1	6.8	6.7	6.3	6.5	6.3	6.2	6.3	6.4	6.2		
NE 10 ST(10.9C)					FC125																	
2281151	10.429	12.109	C	1999	0012	CRACKING		8.5	7.5	7.5	7.5	7.5	7.0	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	5.5*	4.0*	
WEEKLEY ASPHALT PAVING INC(2001)					SPRIDE			6.2	6.0	6.2	5.8	5.7	5.6	5.2*	5.2*	5.2*	5.2*	5.1*	5.0*	5.0*	4.6*	
4476551	10.430	12.047	C	2024	0012																	
86050000	12.108	15.622	C	1	7 35	CRACKING		9.0	9.0	7.5	7.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	9.0		
A1A			2	4.5	8100	RIDE		7.0	6.8	6.8	6.5	6.7	6.7	6.6	6.6	6.7	6.6	6.6	6.5	6.4		
DEERFIELD BEACH CITY LIM(15.2C)					DGFC																	
				(2025)		CRACKING		9.0	8.0	8.0	7.5	7.5	6.5	6.5		10.0	10.0	9.0		10.0	9.5	
						RIDE		6.4	6.2	6.3	5.9	5.9	5.9	5.7		6.0	6.0	5.9		5.5	5.1*	
86050000	15.622	16.327	C	1	1 30	CRACKING		9.0	9.0	7.5	7.5	9.0	9.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5		
A1A			2	2.9	10600	RIDE		7.0	6.8	6.8	6.5	6.7	6.6	6.6	6.3	7.0	6.6	6.1	6.4	6.2		
SE 3 ST(15.6C)					FC95M																	
				(2018)		CRACKING		6.5	6.5	6.5	6.5	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.0	
						RIDE		5.8	5.9	5.9	5.7	5.1*	7.1	7.0	6.8	6.8	6.8	6.6	6.8	6.7	6.3	
86050000	10.443	12.108	L	1	1 35	CRACKING		8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5		
A1A			1	4.5	8100	RIDE		6.8	7.4	7.3	7.1	6.8	6.7	6.3	6.5	6.3	6.2	6.3	6.4	6.2		
FIFTH ST NE(10.5L)					FC125																	
2281151	10.429	12.109	C	1999	0012	CRACKING		8.5	7.5	7.5	7.5	7.5	7.0	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	2.0*	
WEEKLEY ASPHALT PAVING INC(2001)					SPRIDE			6.2	6.0	6.2	5.8	5.7	5.6	5.2*	5.2*	5.2*	5.2*	5.1*	4.3*	4.1*	3.7*	
4476551	10.430	12.047	C	2024	0012																	
86050000	9.792	10.443	L	1	1 35	CRACKING		7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
A1A			2	3.3	13302	RIDE		4.9*	4.9*	5.1*	4.8*	7.0	6.9	6.8	6.6	6.5	6.4	6.2	6.3	5.9		
FIRST ST SE(9.8L)					FC125																	
				(2018)		CRACKING		10.0	10.0	9.0	9.0		9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.3	7.5	
						RIDE		5.9	5.9	5.6	5.6		5.2*	5.3*	5.7	5.8	5.6	5.5	6.0	6.5	6.1	
86050000	8.703	9.792	L	1	1 35	CRACKING		9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	9.5	10.0	10.0	10.0		
A1A			1	2.8	17700	RIDE		5.5*	5.7*	5.5	5.4*	6.2	6.4	6.1	6.0	5.9	6.5	6.0	5.9	5.6		
TERRA MAR DR(8.8L)					FC125																	
2281141	7.443	9.267	C	2002	0012	CRACKING		9.0	8.0	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	8.3	6.5	
APAC-FLORIDA INC				(2004)		RIDE		5.5	5.6	5.8	5.7	5.8	5.6	5.5	5.4*	5.4*	5.1*	5.9	6.0	5.3*	4.9*	
4416282	8.678	9.792	C	2021	0012																	
86050000	7.443	8.703	L	1	1 35	CRACKING		9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	9.5	10.0	10.0	10.0		
A1A			1	2.8	17700	RIDE		5.5*	5.7*	5.5	5.4*	6.2	6.4	6.1	6.0	5.9	6.5	6.0	5.9	5.6		
PINE AVE(7.5C)					FC125M																	
4416281	7.461	8.678	L	2021	0012	CRACKING		9.0	8.0	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	9.5	
H&R PAVING INC				(2025)		RIDE		5.5	5.6	5.8	5.7	5.8	5.6	5.5	5.4*	5.4*	5.1*	5.9	6.0	6.7	6.3	
86050000	6.434	7.443	L	1	1 30	CRACKING		6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
A1A			1	4.4	21500	RIDE		5.5*	5.3*	5.3*	6.3	5.4*	5.4*	5.1*	4.9*	4.7*	4.7*	4.9*	4.9*	4.7*		
CODRINGTON DR(6.4L)					FC125																	
2279511	6.656	7.443	C	2000	0012	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	7.1	5.5*	
WEEKLEY ASPHALT PAVING, IN(2003)					SPRIDE			4.9*	4.8*	5.0*	4.4*	4.6*	4.6*	4.5*	4.6*	4.5*	4.6*	4.6*	4.3*	4.4*	4.0*	
4484051	6.428	7.443	C	2026	0012																	
86050000	5.363	6.434	L	1	1 35	CRACKING		10.0	10.0	10.0	10.0	9.0	7.0	7.0	6.5	6.5	6.5	6.5	4.5*	4.5*		
A1A			2	1.9	22000	RIDE		7.3	7.5	7.6	7.6	7.2	7.1	6.4	6.6	7.1	7.1	7.0	7.0	6.8		
OAKLAND PARK BLVD(5.4C)					FC95M																	
				(2019)		CRACKING		4.5*	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
						RIDE		6.6	8.0	8.1	7.9			7.4	7.3	7.3	7.2	7.3	7.4	7.1	6.7	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR														FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)	W BMP	W_EMP	RW	FY-P	WKM-X-P		=====															
CONTRACTOR (AGE ONE YEAR)					ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F																	
86050000	4.322	5.363	L 2	1 7.8	35 20200	CRACKING RIDE		10.0 7.0	9.0 7.2	9.0 7.2	9.0 7.2	9.0 6.3	7.0 6.5	6.0* 6.2	6.0* 6.1	6.0* 6.2	6.0* 6.2	6.0* 6.0	10.0 7.3	10.0 7.0		
A1A					FC95M																	
NE 21 ST(4.5L)					0012	CRACKING		10.0 7.0	10.0 6.9	10.0 6.7	10.0 6.6	10.0 6.7	10.0 6.6	10.0 6.4	10.0 6.3	9.0 6.1	9.0 6.2	9.0 6.1	9.0 6.0	8.8 5.9	7.5 5.5	
GENERAL ASPHALT CO., INC.			(2011)		SPRIDE																	
86050000	3.334	4.322	L 1	1 3.8	6 18800	CRACKING RIDE		10.0 7.8	10.0 7.8	10.0 7.8	10.0 7.8	10.0 7.1	10.0 6.9	10.0 7.0	10.0 6.7	9.0 6.9	9.0 6.6	9.0 6.4	9.0 6.6	9.0 6.2		
A1A					FC125A																	
SR 838(3.3L)					0005	CRACKING		9.0 5.9		8.5 6.4		10.0	10.0 5.9	10.0 5.9	10.0	10.0	10.0	10.0	10.0	9.6 8.5		
4336884	3.334	4.322	C 2014			SPRIDE																
RUSSELL ENGINEERING, INC			(2017)																			
86050000	2.497	3.334	L 2	1 4.1	6 33500	CRACKING RIDE		10.0 6.4*	10.0 6.3*	10.0 6.3	10.0 6.1	10.0 5.3*	10.0 5.2*	9.0 4.9*	9.0 5.3*	9.0 4.9*	9.0 4.8*	9.0 4.3*	6.5 4.9*	6.5 4.6*		
A1A					FC95A																	
SEVILLE ST(2.5L)					0012	CRACKING		6.5 4.7*	6.5 4.9*	4.5* 4.7*		6.5 5.0*	10.0 5.9	10.0 5.9	10.0 5.8	10.0 6.0	10.0 5.6	10.0 5.7	10.0	9.1 8.0		
4306011	2.497	3.320	L 2016			RIDE																
WEEKLEY ASPHALT PAVING, IN			(2018)																			
86050100	0.000	0.926	C 2	1 5.9	1 14000	CRACKING RIDE		10.0 6.8	10.0 6.6	10.0 6.3	10.0 6.2	9.0 5.6	9.0 5.3*	9.0 5.1*	9.0 5.8	9.0 5.5	9.0 5.6	9.0 5.5	6.5 5.5	6.5 5.4*		
A1A					FC95A																	
SEVILLE ST(0.0R)					0012	CRACKING		6.5 5.2*	6.5 5.4*	6.5 5.1*	6.5 5.1*	6.5 5.2*	10.0 6.9	10.0 6.7	10.0 6.4	10.0 5.9	10.0 6.1	10.0 5.6	10.0 5.8	8.5 5.5	7.5 5.1*	
4306011	0.000	0.926	C 2016			RIDE																
WEEKLEY ASPHALT PAVING, IN			(2018)																			
86060000	0.000	7.190	R 2	1 19.9	1 20500	CRACKING RIDE		6.5 8.0	4.5* 8.1	4.5* 8.0	4.5* 7.9	10.0 8.0	10.0 8.0	10.0 7.9	10.0 7.9	10.0 7.8	8.5 7.8	7.5 7.7	7.0 7.7	7.0 7.7		
25 27					FC5M																	
MIRAMAR CITY LIMITS(2.5R)					0012	CRACKING		7.0 7.6	7.0 7.5	7.0 7.5	6.5 7.7	6.5 7.6	3.5* 7.6		10.0 8.5	10.0 8.6	10.0 8.6	10.0 8.6	9.1 8.5	7.5 8.3		
4306031	0.000	7.190	R 2017			SPRIDE																
RANGER CONSTRUCTION INDUST			(2020)																			
86060000	7.190	27.627	R 2	1 27.1	1 10300	CRACKING RIDE		10.0 8.9	9.0 9.1	9.0 8.9	7.5 8.8	7.5 8.5	7.5 8.5	6.5 8.3	6.5 8.2	6.5 8.2	6.0* 8.1		10.0 8.2	10.0 8.2		
25 27					FC5																	
CIRCLE K TRUCK STOP(7.3R)					0012	CRACKING		10.0 8.2	10.0 8.2	9.0 8.3	9.0 8.5	9.0 8.5	9.0 8.5	9.0 8.4	9.0 8.4	9.0 8.5	6.5 8.6	6.5 8.5	6.5 8.6	7.0 8.5	4.5* 8.3	
4162421	7.192	27.678	C 2009			RIDE																
COMMUNITY ASPHALT CORP.			(2011)																			
4401431	15.250	27.627@	C 2021			9924																
86060000	7.190	27.627	L 2	1 27.1	1 10300	CRACKING RIDE		10.0 8.9	10.0 8.9	10.0 8.9	9.0 8.8	7.5 8.3	6.5 8.3	4.5* 8.1	4.5* 7.9	3.5* 7.8	3.5* 7.8	3.5* 7.6	10.0 7.8	10.0 7.9		
25 27					FC5																	
FRONTAGE RD(11.9C)					0012	CRACKING		10.0 7.9	10.0 7.8	9.0 7.9	9.0 8.2	9.0 8.2	6.5 8.1	4.5* 8.0	4.5* 8.0	4.5* 8.3	4.5* 8.3	4.5* 8.3	4.5* 8.3	5.5* 8.2	3.0* 8.0	
4162421	7.192	27.678	C 2009			RIDE																
COMMUNITY ASPHALT CORP.			(2011)																			
4401431	15.250	27.627@	C 2021			9924																
86060000	0.000	7.190	L 2	1 19.9	1 20500	CRACKING RIDE		10.0 8.6	10.0 8.7	10.0 8.7	7.5 8.6	10.0 8.1	10.0 8.1	10.0 8.1	10.0 8.0	10.0 8.0	8.5 7.9	7.5 7.9	7.0 7.7	7.0 7.6		
25 27					FC5M																	
JOHNSON ST(4.0C)					0012	CRACKING		7.0 7.6	7.0 7.5	6.5 7.5	6.5 7.8	6.5 7.7	3.5* 7.7		10.0 8.3	10.0 8.5	10.0 8.4	10.0 8.4	10.0 8.4	9.0 8.4	7.5 8.2	
4306031	0.000	7.190	L 2017			SPRIDE																
RANGER CONSTRUCTION INDUST			(2020)																			
86065000	0.000	1.800	R 2	1 7.3	1 22000	CRACKING RIDE		10.0 8.1	10.0 8.0	10.0 8.1	10.0 8.0	10.0 7.2	10.0 7.1	9.0 7.1	9.0 6.9	9.0 7.9	9.0 7.7	9.0 7.6	7.5 7.5	7.0 7.3		
845					FC125A																	
FORT LAUDERDALE CITY LIM			(0.0C)		0012	CRACKING		7.0 7.6	6.5 6.9	6.5 7.0	6.5 7.3	4.5* 7.3	10.0 8.5	10.0 8.3	10.0 8.2	10.0 8.2	10.0 8.2	10.0 8.1	10.0 8.1	9.2 8.0	8.0 7.6	
4306041	0.000	1.230	R 2017			RIDE																
COMMUNITY ASPHALT CORP.			(2018)																			
86065000	1.800	2.025	R 3	1 6.1	6 25500	CRACKING RIDE		9.0 4.3*	9.0 4.0*	9.0 5.5	9.0 5.6	9.0 4.7*	9.0 5.0*	9.0 3.8*	9.0 3.5*	10.0 5.9	10.0 5.6	10.0 5.3*	10.0 5.7	10.0 5.7		
845					FC95																	
NW 29 CT(1.8R)																						
(2022)																						
86065000	2.025	2.920	R 2	1 5.7	1 26500	CRACKING RIDE		10.0 8.5	10.0 8.4	9.0 8.3	9.0 8.3	9.0 7.7	6.5 7.7	6.5 7.5	6.5 7.4	6.5 6.4	4.5* 6.8	4.5* 7.1	10.0 7.1	10.0 7.0		
845					FC95M																	
OAKLAND PARK BLVD(2.0C)					0012	CRACKING		10.0 6.2	10.0 6.5	10.0 6.0	10.0 6.8	10.0 6.7	10.0 6.7	10.0 7.0	10.0 6.5	10.0 6.6	10.0 6.3	9.0 7.4	9.0 7.3	9.6 7.4	8.5 7.0	
4168731	2.065	2.890	C 2009			SPRIDE																
WEEKLEY ASPHALT PAVING, IN			(2011)																			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
INTERSECT AT (MP SIDE)	W BMP	W_EMP	RW	FY-P	WKMX-P		=====														
ITMSEG-P	(AGE ONE YEAR)				ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																
86065000	2.920	3.273	R	1	1 40	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
845			2	6.0	29000	RIDE		7.6	7.3	6.0	7.1	6.9	6.8	6.8	6.7	7.1	6.5	6.6	6.6	6.3	
PROSPECT RD(3.1C)					FC95M																
2281091	3.008	4.329	C	1998	0012	CRACKING		10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.5	8.0	8.0	9.1	7.5
PAN AMERICAN CONSTRUCTION (2000)					S	RIDE		6.5	6.6	6.7	5.5	5.6	5.5	5.3*	5.6	5.9	5.3*	6.8	6.3	6.3	5.9
86065000	3.273	4.527	R	1	1 40	CRACKING		8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	
845			3	4.5	35000	RIDE		6.4*	8.4	7.7	7.7	7.5	7.2	7.2	6.9	7.3	7.0	7.1	6.7	6.9	
COMMERCIAL BLVD(3.6C)					FC95																
2281091	3.008	4.329	C	1998	0012	CRACKING		8.5	8.0	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	5.0*
PAN AMERICAN CONSTRUCTION (2001)					S	RIDE		6.2	6.4	6.4	6.9	6.7	6.8	6.6	6.5	6.7	6.5	6.5	6.3	6.4	6.0
4461961	3.558	5.627	C	2024	0012																
86065000	4.527	6.519	R	1	1 45	CRACKING		8.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	
845			3	6.5	40500	RIDE		6.4*	6.2*	6.4*	6.2*	5.7*	5.6*	5.4*	5.1*	5.5	5.3*	7.9	7.7	7.7	
CYPRESS CREEK RD(4.6C)					FC95																
2280751	4.527	6.519	C	2008	0012	CRACKING		10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.0	8.0	8.0	8.0	8.0	8.4	7.0
PAVEX CORPORATION (2010)					SPRIDE			7.4	7.6	7.5	7.4	7.4	7.4	7.1	6.9	7.0	6.9	6.8	7.0	6.8	6.4
4461961	3.558	5.627	C	2024	0012																
86065000	6.519	9.142	R	1	1 45	CRACKING		7.0	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	
845			3	6.7	31500	RIDE		6.4*	6.4*	6.3*	6.4*	5.6*	5.7*		7.4	7.6	7.7	7.5	7.6	7.5	
NW 2 ST/REV E GRAHAM(6.7R)					FC125																
2281101	6.519	9.424	C	2004	0012	CRACKING		9.0	9.0	8.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.6	6.0*
PAVEX CORPORATION (2007)					SPRIDE			7.5	7.4	7.5	7.1	7.0	7.1	6.8	6.9	6.8	6.6	6.6	6.6	6.7	6.3
4484061	6.519	9.142	C	2028	0012																
86065000	9.142	11.424	R	1	7 45	CRACKING		9.0	9.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
845			3	8.4	40000	RIDE		5.8*	5.7*	5.5*			7.5	7.5	7.3	7.5	7.4	7.4	7.0	7.1	
NW 30 PL(9.2R)					FC125M																
4460961	9.142	11.412	C	2023	0012	CRACKING		10.0	10.0	9.0	9.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	10.0	9.5
WEEKLEY ASPHALT PAVING, IN(2025)					SPRIDE			7.0	7.0	7.0	6.7	6.6	6.6	6.5	6.5	6.5	6.3	6.2	6.1	6.8	6.4
86065000	11.424	11.941	R	1	1 45	CRACKING		9.0	9.0	9.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
845			3	7.2	42000	RIDE		6.5	6.4*	6.0*			7.5	7.5	7.3	7.5	7.4	7.4	7.0	7.1	
AMERICAN WAY(11.6R)					FC125																
2279001	9.612	11.848	C	2001	0213	CRACKING		10.0	10.0	9.0	9.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	7.9	6.5
LANZO CONSTRUCTION CO FLOR(2005)					SPRIDE			7.0	7.0	7.0	6.7	6.6	6.6	6.5	6.5	6.5	6.3	6.2	6.1	6.6	6.2
86065000	11.941	13.295	R	1	1 45	CRACKING		10.0	10.0	10.0			9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	
845			2	1.8	37500	RIDE		7.2	7.2	7.2			6.2*	6.0	5.7	6.0	5.9	5.9	6.0	5.7	
NEST DR(12.0C)					FC95A																
4306051	11.941	13.301	R	2015	0012	CRACKING		6.5	6.5	5.5*			10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.0
WEEKLEY ASPHALT PAVING, IN(2017)					SPRIDE			5.4*	5.6	5.6			7.5	7.5	7.3	7.4	7.3	7.3	7.3	7.3	6.9
86065000	11.941	13.295	L	1	1 45	CRACKING		10.0	10.0	10.0			9.0	9.0	9.0	9.0	7.0	6.5	6.5	6.5	
845			3	1.8	37500	RIDE		6.7	6.9	6.7			6.4*	6.1	6.2	6.4	6.2	6.1	6.2	6.2	
SPUR(12.0L)					FC95A																
(2017)						CRACKING		6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5
						RIDE		6.1	6.1	6.0			7.7	7.4	7.5	7.6	7.5	7.6	7.5	7.3	6.9
86065000	11.424	11.941	L	1	1 45	CRACKING		9.0	9.0	9.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
845			3	7.2	42000	RIDE		7.4	6.4*	6.1*			7.5	7.8	7.4	7.7	7.6	7.5	7.5	7.4	
AMERICAN WAY(11.5L)					FC125																
2279001	9.612	11.848	C	2001	0213	CRACKING		9.0	9.0	9.0	8.0	7.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	6.0*	8.2	6.5
LANZO CONSTRUCTION CO FLOR(2005)					SPRIDE			7.4	7.2	7.3	6.7	6.6	6.5	6.4	6.2	6.3	6.0	6.0	6.0	6.2	5.8
86065000	9.142	11.424	L	1	7 45	CRACKING		9.0	9.0	9.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
845			3	8.4	40000	RIDE		7.3	7.4	7.0			7.5	7.8	7.4	7.7	7.6	7.5	7.5	7.4	
NW 30 PL(9.2L)					FC125M																
4460961	9.142	11.412	C	2023	0012	CRACKING		9.0	9.0	9.0	8.0	7.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	6.0*	10.0	9.5
WEEKLEY ASPHALT PAVING, IN(2025)					SPRIDE			7.4	7.2	7.3	6.7	6.6	6.5	6.4	6.2	6.3	6.0	6.0	6.0	6.3	5.9
86065000	6.519	9.142	L	1	1 45	CRACKING		9.0	9.0	7.5	7.5	7.5	7.0		10.0	10.0	10.0	9.0	9.0	9.0	
845			3	6.7	31500	RIDE		6.4*	6.4*	6.3*	6.2*	5.6*	5.6*		7.1	6.9	6.7	6.8	6.5	6.5	
NW 2 ST(6.7L)					FC125																
2281101	6.519	9.424	C	2004	0012	CRACKING		8.5	8.5	8.5	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.4	6.0*
PAVEX CORPORATION (2007)					SPRIDE			6.5	6.4	6.3	6.4	6.2	6.3	6.1	6.0	5.9	5.8	5.7	5.8	5.7	5.3*
4484061	6.519	9.142	C	2028	0012																

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.

2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

										DISTRICT = 4 COUNTY = BROWARD																			
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR															FUTURE			
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	W_BMP	W_EMP	RW	FY-P	%T	AADT	ASTYPE	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012						
ITMSEG-P	CONTRACTOR (AGE ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKMX-F					2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)					
86065000	845	CYPRESS CREEK RD(4.6C)	4.527	6.519	L 3	1 6.5	1 40500	FC95	CRACKING RIDE	9.0 6.2*	9.0 6.6	9.0 6.4*	9.0 6.1*	9.0 6.0*	9.0 5.7*	9.0 5.5	7.0 5.3*	7.0 5.6	7.0 5.6	7.0 5.6	10.0 8.2	10.0 8.1	10.0 7.3						
2280751	PAVEX CORPORATION	4.527	6.519	C 2008	(2010)	0012	SPRIDE		CRACKING	10.0 7.5	10.0 7.3	10.0 7.7	8.5 7.7	7.5 7.6	7.5 7.6	7.5 7.4	7.0 7.4	7.0 7.4	7.0 7.3	7.0 7.2	7.0 7.0	7.0 6.9	5.5* 6.5						
86065000	845	NW 47 ST(3.3L)	3.273	4.527	L 3	1 4.5	1 35000	FC95	CRACKING RIDE	9.0 6.2*	10.0 8.1	10.0 7.8	10.0 7.6	10.0 7.2	10.0 7.1	10.0 6.9	10.0 6.8	10.0 7.1	9.5 6.8	9.5 6.7	9.0 6.7	9.0 6.5							
2281091	PAN AMERICAN CONSTRUCTION	3.008	4.329	C 1998	(2001)	0012	S		CRACKING	8.5 6.4	8.5 6.3	8.0 6.3	7.0 6.4	7.0 6.3	7.0 6.3	7.0 6.2	6.5 6.1	6.5 5.9	6.5 5.7	6.5 6.0	6.5 5.8	6.5 5.9	5.0* 5.5						
86065000	845	PROSPECT RD(3.1C)	2.920	3.273	L 2	1 6.0	1 29000	FC95M	CRACKING RIDE	10.0 6.0*	10.0 5.7*	10.0 5.6	10.0 5.4*	10.0 5.0*	10.0 4.2*	10.0 5.0*	10.0 4.9*	10.0 5.4*	10.0 4.8*	9.5 4.8*	9.5 4.9*	9.5 5.1*							
					(2024)				CRACKING RIDE	9.5 4.9*	9.5 4.7*	9.5 5.0*	8.5 4.1*	7.0 4.0*	7.0 4.0*	7.0 4.2*	7.0 3.8*	7.0 3.8*	7.0 3.9*	6.5 6.3	9.0 6.0	10.0 5.9	9.5 5.5						
86065000	845	OAKLAND PARK BLVD(2.0C)	2.025	2.920	L 2	1 5.7	2 26500	FC95	CRACKING RIDE	10.0 8.3	10.0 8.0	7.5 7.3	7.5 7.4	7.5 7.1	7.5 7.1	6.5 6.9	4.5* 6.5	4.5* 5.2*	4.5* 5.7	4.5* 5.9	10.0 7.3	10.0 7.0							
4168731	WEEKLEY ASPHALT PAVING, INC	2.065	2.890	C 2009	(2011)	0012	SPRIDE		CRACKING	10.0 7.1	10.0 7.4	10.0 7.2	10.0 7.3	10.0 6.8	10.0 7.2	10.0 7.3	10.0 6.9	10.0 6.9	10.0 7.0	9.0 6.5	9.0 6.7	9.5 6.5	8.0 6.1						
86065000	845	NW 30 CT(2.0L)	1.800	2.025	L 3	1 6.1	6 25500	FC95	CRACKING RIDE	9.0 4.8*	7.0 3.3*	6.5 4.2*	4.5* 4.4*	4.5* 2.8*	4.5* 2.9*	4.5* 3.4*	4.5* 3.3*	10.0 6.9	10.0 6.7	10.0 6.6	10.0 7.0	10.0 6.6							
					(2022)				CRACKING RIDE	10.0 6.5	10.0 7.4	10.0 5.4*	9.0	8.0	8.0	8.0	8.0	8.0	8.0	10.0	10.0	9.5	8.5						
86065000	845	FORT LAUDERDALE CITY LIM(0.0C)	0.000	1.800	L 2	1 7.3	1 22000	FC125A	CRACKING RIDE	10.0 8.3	10.0 8.3	9.0 8.3	9.0 8.2	9.0 7.2	9.0 6.9	9.0 6.6	9.0 6.5	9.0 6.0	9.0 6.3	9.0 5.8	7.5 5.2*	7.5 5.5							
4306041	COMMUNITY ASPHALT CORP.	0.000	1.230	L 2017	(2018)	0012			CRACKING	7.5 5.2*	7.5 5.3*	7.5 5.5	6.5 5.3*	4.5* 5.1*	10.0 8.0	10.0 7.7	10.0 7.7	10.0 7.7	10.0 7.6	10.0 7.6	10.0 7.5	9.6 7.5	8.5 7.1						
86070000	9 I95	COUNTY LINE RD(0.0C)	0.000	0.755	R 4	4 9.2	1 224000	FC5M	CRACKING RIDE	6.5 8.5	6.5 8.5	6.5 8.4	4.5* 8.3	4.5* 7.6		10.0 7.7	10.0 7.6	10.0 7.7	10.0 7.8	9.0 7.8	9.0 7.8	9.0 7.7							
					(2017)				CRACKING RIDE	9.0 7.6				10.0 8.5	10.0 8.6	10.0 8.1	10.0 8.4	10.0 8.2	10.0 8.2	9.0 8.2	9.0 8.2	8.7 8.2	6.5 8.1						
86070000	9 I95		0.755	5.190	R 4	4 9.2	8 250000	FC5M	CRACKING RIDE	6.5 8.5	6.5 8.5	6.5 8.4	4.5* 8.3	4.5* 7.6		10.0 7.7	10.0 7.6	10.0 7.7	10.0 7.8	9.0 7.8	9.0 7.8	9.0 7.7							
					(2017)				CRACKING RIDE	9.0 7.6				10.0 8.4	10.0 8.5	10.0 8.2	10.0 8.3	10.0 8.4	9.0 8.4	9.0 8.2	9.0 8.2								
86070000	9 I95		5.190	6.156	R 5	4 9.2	8 220000	FC5M	CRACKING RIDE	6.5 8.5	6.5 8.5	6.5 8.4	4.5* 8.3	4.5* 7.6		10.0 7.7	10.0 7.6	10.0 7.7	10.0 7.8	9.0 7.8	9.0 7.8	9.0 7.7							
					(2017)				CRACKING RIDE	9.0 7.6				10.0 8.4	10.0 8.5	10.0 8.2	10.0 8.3	10.0 8.4	9.0 8.4										
86070000	9 I95		6.156	6.432	R 5	4 9.2	8 221000	FC5M	CRACKING RIDE	6.5 8.5	6.5 8.5	6.5 8.4	4.5* 8.3	4.5* 7.6		10.0 7.7	10.0 7.6	10.0 7.7	10.0 7.8	9.0 7.8	9.0 7.8	9.0 7.7							
					(2017)				CRACKING RIDE	9.0 7.6				10.0 8.3	10.0 8.2	10.0 7.7	10.0 8.2	9.0 8.4	9.0 8.4	9.0 8.1	9.0 8.3								
86070000	9 I95		6.432	7.100	R 5	4 9.2	8 221000	FC5	CRACKING RIDE	7.5 8.3	6.5 8.3	4.5* 8.2	4.5* 8.3	4.5* 7.6	6.5 7.2	6.5 7.3			10.0 7.8	10.0 7.8	10.0 7.7	10.0 7.7							
2317321	PAVEX CORPORATION	6.569	6.932	R 2005	(2009)	0012	SPRIDE		CRACKING	10.0 7.6				7.5 7.8	6.5 7.8	3.5* 7.5	3.5* 7.6	3.5* 7.8	3.5* 7.9	3.5* 7.8	3.5* 7.8	3.5* 7.7							

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 4 COUNTY = BROWARD -----																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR												FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
INTERSECT AT (MP SIDE)																					
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P																
CONTRACTOR (AGE_ONE YEAR)					ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																(PMRS)
86070000	7.100	7.700	R	4	8 65	CRACKING		7.5	6.5	4.5*	4.5*	4.5*	6.5	6.5			10.0	10.0	10.0	10.0	
9 I95	24.3	24.9	5	9.2	221000	RIDE		8.3	8.3	8.2	8.3	7.6	7.2	7.3			7.8	7.8	7.7	7.7	
					FC5																
2317321	6.932	7.614	R	2005	0012	CRACKING		10.0				7.5	6.5	3.5*	3.5*	3.5*	3.5*				
PAVEX CORPORATION				(2009)	SPRIDE			7.6				7.8	7.8	7.5	7.6	7.8	7.9				
86070000	7.700	8.382	R	4	8 65	CRACKING		9.0	9.0	9.0	6.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	
9 I95	24.9	25.6	4	9.2	196500	RIDE		8.4	8.4	8.3	8.2	7.6	7.2	7.3			7.8	7.8	7.7	7.7	
					FC5																
2317321	7.614	8.382	R	2005	0012	CRACKING		10.0	9.0	9.0	7.5	7.5	6.5	3.5*	3.5*						
PAVEX CORPORATION				(2009)	SPRIDE			7.6	7.5	7.4	7.8	7.7	7.6	7.6	7.4						
86070000	8.750	9.737	R	4	8 65	CRACKING		10.0	10.0	10.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	
9 I95	25.9	26.9	5	9.2	316000	RIDE		8.3	8.3	8.2	8.2	7.3	7.4	7.2	7.2	7.0	7.1	6.7		7.5	
					FC5																
2317331	8.763	9.677	R	2010	0012	CRACKING		10.0	10.0	10.0	10.0	10.0		3.5*	3.5*						
				(2012)	RIDE			7.4	7.4	7.4	7.5	7.5		7.8	7.7						
86070000	9.737	14.240	R	4	1 65	CRACKING		7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	
9 I95	26.9	31.4	5	9.2	247000	RIDE		8.6	8.4	8.2	8.3	7.6	7.4	7.7	7.4	7.2	7.5	7.6	7.6	7.6	
					FC5M																
				(2024)	CRACKING			10.0	9.0	9.0	9.0	9.0							10.0	10.0	9.0
					RIDE			7.6	7.5	7.5	8.0	7.9							7.9	8.1	8.0
86070000	14.240	15.806	R	4	1 65	CRACKING		7.5	7.5	7.5	7.5	6.5	6.5	6.5		4.5*	10.0	10.0	10.0	10.0	
9 I95	31.4	33.0	4	3.3	279000	RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.7		7.6	7.6	7.7	7.6	7.6	
					FC5M																
				(2024)	CRACKING			10.0	9.0	9.0	9.0	9.0							10.0	10.0	9.0
					RIDE			7.6	7.6	7.5	7.6	7.5							7.9	7.7	7.6
86070000	15.806	17.700	R	4	1 65	CRACKING		7.5	7.5	7.5	7.5	6.5	6.5	6.5		4.5*	10.0	10.0	10.0	10.0	
9 I95	33.0	34.9	4	3.3	247000	RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.7		7.6	7.6	7.7	7.6	7.6	
					FC5M																
				(2021)	CRACKING			10.0	9.0	9.0	9.0	9.0				10.0	10.0	10.0	10.0	8.8	7.5
					RIDE			7.6	7.6	7.5	7.6	7.5				8.1	8.1	7.9	8.0	7.9	7.8
86070000	17.700	19.867	R	4	1 65	CRACKING		7.5	7.5	7.5	7.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	
9 I95	34.9	37.1	3	6.5	181000	RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.7			8.0	8.0	8.0	8.0	
					FC5M																
				(2021)	CRACKING			10.0	9.0	9.0	6.5	6.5				10.0	10.0	10.0	10.0	9.0	7.5
					RIDE			7.9	7.9	7.8	8.1	8.1				8.1	8.1	8.1	8.1	8.1	8.0
86070000	19.867	21.043	R	4	1 65	CRACKING		7.5	7.5	7.5	7.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	
9 I95	37.1	38.2	3	3.3	209500	RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.7			8.0	8.0	8.0	8.0	
					FC5M																
				(2024)	CRACKING			10.0	9.0	9.0	6.5	6.5				10.0	10.0	10.0	10.0	10.0	9.0
					RIDE			7.9	7.9	7.8	8.1	8.1				8.1	8.1	8.1	8.1	8.1	8.0
86070000	21.043	22.890	R	4	1 65	CRACKING		7.5	7.5	7.5	7.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	
9 I95	38.2	40.1	3	9.2	210000	RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.7			7.7	7.7	7.7	7.7	
					FC5M																
				(2021)	CRACKING			10.0	10.0	9.0	9.0	9.0				10.0	10.0	10.0	10.0	8.8	7.5
					RIDE			7.7	7.6	7.5	7.9	7.9				8.1	8.1	8.1	8.1	8.1	8.0
86070000	22.890	24.690	R	4	1 65	CRACKING		7.5	7.5	7.5	7.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	
9 I95	40.1	41.9	3	3.3	230000	RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.7			7.7	7.7	7.7	7.7	
					FC5M																
				(2022)	CRACKING			10.0	10.0	9.0	9.0	9.0		3.5*			10.0	10.0	10.0	9.1	7.5
					RIDE			7.7	7.6	7.5	7.9	7.9		7.7			8.5	8.5	8.5	8.4	8.3
86070000	24.690	25.334	R	4	1 65	CRACKING		7.5	7.5	7.5	7.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	
9 I95	41.9	42.5	3	9.9	237000	RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.7			7.7	7.7	7.7	7.7	
					FC5M																
				(2023)	CRACKING			10.0	10.0	9.0	9.0	9.0		3.5*				10.0	10.0	10.0	9.0
					RIDE			7.7	7.6	7.5	7.9	7.9		7.7				8.2	8.2	8.2	8.1

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE
INTERSECT	AT (MP)	SIDE)																			
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P																
CONTRACTOR	(AGE ONE YEAR)				ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																(PMRS)
86070000	24.343	25.334	L	4	1	65	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0	7.5	7.5	9.0	
9 I95	41.5	42.5	3	9.9	237000	FC5M	RIDE	8.6	8.5	8.6	8.5	7.6	7.6	7.6		7.7	7.7	7.7	7.7	7.7	
				(2023)			CRACKING	9.0	7.5	6.5	4.5*	4.5*					10.0	10.0	10.0	9.0	
							RIDE	7.5	7.4	7.4	7.8	7.7					8.5	8.5	8.5	8.4	
86070000	23.790	24.343	L	4	1	65	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0	7.5	7.5	9.0	
9 I95	41.0	41.5	3	3.3	230000	FC5M	RIDE	8.6	8.5	8.6	8.5	7.6	7.6	7.6		7.7	7.7	7.7	7.7	7.7	
				(2023)			CRACKING	9.0	7.5	6.5	4.5*						10.0	10.0	10.0	9.0	
							RIDE	7.5	7.4	7.4	7.8						8.1	8.2	8.1	8.0	
86070000	21.045	23.790	L	4	1	65	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0	7.5	7.5	9.0	
9 I95	38.2	41.0	4	9.2	210000	FC5M	RIDE	8.6	8.5	8.6	8.5	7.6	7.6	7.6		7.7	7.7	7.7	7.7	7.7	
				(2021)			CRACKING	9.0	7.5	6.5	4.5*	4.5*				10.0	10.0	10.0	10.0	8.7	7.0
							RIDE	7.5	7.4	7.4	7.8	7.9				8.1	8.1	8.1	8.4	8.2	8.1
86070000	19.786	21.045	L	4	1	65	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*			10.0	10.0	9.0	9.0	
9 I95	37.0	38.2	3	6.5	181000	FC5M	RIDE	8.6	8.5	8.6	8.5	7.6	7.6	7.6			7.9	8.0	7.9	7.9	
				(2024)			CRACKING	9.0	9.0	7.5	4.5*	4.5*				10.0	10.0	10.0	10.0	10.0	9.0
							RIDE	7.8	7.8	7.7	8.0	8.0				8.1	8.1	8.1	8.3	7.7	7.6
86070000	17.261	19.786	L	4	1	65	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*			10.0	10.0	9.0	9.0	
9 I95	34.5	37.0	3	3.3	247000	FC5M	RIDE	8.6	8.5	8.6	8.5	7.6	7.6	7.6			7.9	8.0	7.9	7.9	
				(2021)			CRACKING	9.0	9.0	7.5	4.5*	4.5*				10.0	10.0	10.0	10.0	8.7	7.0
							RIDE	7.8	7.8	7.7	8.0	8.0				8.1	8.1	8.1	8.1	8.1	8.0
86070000	15.720	17.261	L	4	2	65	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*		6.5	10.0	10.0	9.0	9.0	
9 I95	32.9	34.5	5	3.3	247000	FC5M	RIDE	8.6	8.5	8.6	8.5	7.6	7.6	7.6		7.5	7.6	7.6	7.6	7.5	
				(2021)			CRACKING	9.0	9.0	9.0	7.5	7.5				10.0	10.0	10.0	10.0	10.0	8.5
							RIDE	7.4	7.4	7.2	7.4	7.4				8.1	8.1	7.8	7.7	7.8	7.7
86070000	15.537	15.720	L	4	2	65	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*		6.5	10.0	10.0	9.0	9.0	
9 I95	32.7	32.9	4	3.3	252000	FC5M	RIDE	8.6	8.5	8.6	8.5	7.6	7.6	7.6		7.5	7.6	7.6	7.6	7.5	
				(2024)			CRACKING	9.0	9.0	9.0	7.5	7.5							10.0	10.0	9.0
							RIDE	7.4	7.4	7.2	7.4	7.4							8.2	8.0	7.9
86070000	14.200	15.537	L	4	2	65	CRACKING	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*		6.5	10.0	10.0	9.0	9.0	
9 I95	31.4	32.7	4	3.3	279000	FC5M	RIDE	8.6	8.5	8.6	8.5	7.6	7.6	7.6		7.5	7.6	7.6	7.6	7.5	
				(2024)			CRACKING	9.0	9.0	9.0	7.5	7.5	7.5						10.0	10.0	9.0
							RIDE	7.4	7.4	7.2	7.4	7.4	7.3						8.2	7.7	7.6
86070000	9.677	14.200	L	4	2	65	CRACKING	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	
9 I95	26.9	31.4	5	9.2	247000	FC5	RIDE	8.4	8.1	8.4	8.2	7.4	7.3	7.4	7.3	7.3	7.5	7.6	7.6	7.6	
				(2024)			CRACKING	10.0	9.0	9.0	6.5	6.5	3.5*						10.0	10.0	9.0
							RIDE	7.6	7.6	7.3	7.9	7.9	7.8						8.2	7.7	7.6
86070000	8.750	9.677	L	4	8	65	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5		10.0	
9 I95	25.9	26.9	4	9.2	196500	FC5	RIDE	8.5	8.4	8.4	8.3	7.5	7.5	7.3	7.2	7.1	7.2	7.2		7.6	
2317331	8.763	9.801	L	2010	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	6.5								
WEEKLEY ASPHALT PAVING, IN(2012)					SPRIDE			7.7	7.7	7.6	7.6	7.6	7.6								
86070000	7.700	8.382	L	4	8	65	CRACKING	7.5	7.5	7.5	7.5	7.5	7.5	7.5			10.0	10.0	10.0	10.0	
9 I95	24.9	25.6	4	9.2	196500	FC5	RIDE	8.5	8.5	8.4	8.4	7.5	7.4	7.5			8.1	8.1	8.1	8.0	
2317321	7.614	8.382	L	2005	0012	CRACKING	10.0	9.0	9.0	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*					
PAVEX CORPORATION				(2009)	SPRIDE			8.0	7.8	7.9	8.1	8.1	8.1	8.0	7.9	8.2	8.2				

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

										DISTRICT = 4				COUNTY = BROWARD															
RDWYID	SR	US	BMP	G_EMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR												FUTURE					
INTERSECT	AT	(MP)	SIDE)		LN	%T	AADT			RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012						
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	W_KMX-P					=====																			
CONTRACTOR	(AGE	ONE	YEAR)		ASTYPE						2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																		(PMRS)						
86070000	6.444	7.700	L	4	8	65	CRACKING				9.0	9.0	7.5	7.5	7.5	7.5				10.0	10.0	10.0	10.0						
9 I95	23.6	24.9	5	9.2	221000	RIDE	8.4	8.5	8.4	8.3	8.4	8.5	8.4	8.3	7.4	7.5	7.4			8.1	8.1	8.1	8.0						
					FC5																								
2317321	6.932	7.614	L	2005	0012	CRACKING	10.0				10.0				7.5	7.5	4.5*	4.5*	4.5*	4.5*									
PAVEX CORPORATION			(2009)		SPRIDE		8.0				8.0				8.0	7.9	7.9	7.8	8.1	8.0									
86070000	6.156	6.444	L	4	8	65	CRACKING				9.0	9.0	7.5	4.5*	4.5*		10.0	10.0	10.0	8.5	8.5	7.5	7.5						
9 I95	23.4	23.6	5	9.2	221000	RIDE	8.7	8.7	8.6	8.4	8.7	8.7	8.6	8.4	7.7		7.6	7.6	7.7	7.7	7.6	7.6	7.5						
					FC5M																								
			(2017)			CRACKING	7.0				7.4				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0							
						RIDE									8.5	8.4	8.4	8.4	8.5	8.5	8.5	8.4							
86070000	5.080	6.156	L	4	8	65	CRACKING				9.0	9.0	7.5	4.5*	4.5*		10.0	10.0	10.0	8.5	8.5	7.5	7.5						
9 I95	22.3	23.4	4	9.2	220000	RIDE	8.7	8.7	8.6	8.4	8.7	8.7	8.6	8.4	7.7		7.6	7.6	7.7	7.7	7.6	7.6	7.5						
					FC5M																								
			(2017)			CRACKING	7.0				7.4				10.0	10.0	10.0	10.0	10.0	10.0	9.0								
						RIDE									8.4	8.4	8.4	8.1	8.3	8.3	8.3								
86070000	0.755	5.080	L	4	1	65	CRACKING				7.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	8.5	8.5	7.5	7.5						
9 I95	18.0	22.3	5	9.2	250000	RIDE	8.2	8.6	8.4	8.4	8.2	8.6	8.4	8.4	7.7		7.6	7.6	7.7	7.7	7.6	7.6	7.5						
					FC5M																								
			(2017)			CRACKING	7.0				7.4				10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.2	6.0*					
						RIDE									8.4	8.4	8.4	8.1	8.3	8.3	8.5	8.4	8.3	8.2					
86070000	0.000	0.755	L	4	1	65	CRACKING				7.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0	8.5	8.5	7.5	7.5						
9 I95	17.2	18.0	4	9.2	224000	RIDE	8.2	8.6	8.4	8.4	8.2	8.6	8.4	8.4	7.7		7.6	7.6	7.7	7.7	7.6	7.6	7.5						
COUNTY LINE RD(0.0C)					FC5M																								
			(2017)			CRACKING	7.0				7.4				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.6	6.5					
						RIDE									8.7	8.7	8.6	8.2	8.4	8.5	8.6	8.7	8.5	8.4					
86070901	0.000	0.969	C	4	1		CRACKING																						
9 I95			1	9.2	11500	RIDE																							
			(2020)			CRACKING																							
						RIDE																							
86070901	0.969	4.868	C	4	1		CRACKING																						
9 I95			2	9.2	21500	RIDE																							
			(2020)			CRACKING																							
						RIDE																							
86070901	4.868	7.989	C	4	8		CRACKING																						
9 I95			1	9.2	17250	RIDE																							
			(2020)			CRACKING																							
						RIDE																							
86070902	17.416	20.527	C	4	8		CRACKING																						
9 I95			1	9.2	17250	RIDE																							
			(2020)			CRACKING																							
						RIDE																							
86070902	20.527	24.462	C	4	1		CRACKING																						
9 I95			2	9.2	21500	RIDE																							
			(2020)			CRACKING																							
						RIDE																							
86070902	24.462	25.412	C	4	1		CRACKING																						
9 I95			1	9.2	14500	RIDE																							
			(2020)			CRACKING																							
						RIDE																							

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

										DISTRICT = 4				COUNTY = BROWARD													
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR														FUTURE					
SR US	G_BMP	G_EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012							
INTERSECT	AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKMX-P	ASTYPE																				
ITMSEG-P	(AGE ONE YEAR)							2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)						
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																						
860709039	I95	0.000	9.785	C 2	4 1.1	7 59500	CRACKING RIDE																				
				(2025)			CRACKING RIDE													10.0 8.2	9.0 8.1						
860709049	I95	0.000	8.190	C 1	4 1.1	7 28500	CRACKING RIDE																				
				(2025)			CRACKING RIDE													10.0 8.0	9.0 7.9						
8607500093	I75	0.000 5.5	1.960 7.4	R 4	4 7.1	1 70 205825 FC5M	CRACKING RIDE	9.0 8.8	9.0 8.8	9.0 8.8	8.0 8.7	8.0 8.2	7.0 8.1	7.0 7.8		10.0 7.4	10.0 7.5	10.0 7.7	10.0 7.7	10.0 7.6							
4378321	HALLEY ENGINEERING	0.000	6.000	R 2019	CONTRAC(2021)	0012	CRACKING SPRIDE	10.0 7.5	10.0 7.6	9.0 7.6	10.0 8.3	10.0 8.4			6.5 8.1	10.0 8.6	10.0 8.7	10.0 8.6	10.0 8.6	10.0 8.6	8.5 8.5						
8607500093	I75	1.960 7.4	2.437 7.9	R 4	4 12.6	1 70 164000 FC5M	CRACKING RIDE	9.0 8.8	9.0 8.8	9.0 8.8	8.0 8.7	8.0 8.2	7.0 8.1	7.0 7.8		10.0 7.4	10.0 7.5	10.0 7.7	10.0 7.7	10.0 7.6							
4378321	HALLEY ENGINEERING	0.000	6.000	R 2019	CONTRAC(2020)	0012	CRACKING SPRIDE	10.0 7.5	10.0 7.6	9.0 7.6	4.5* 7.7	4.5* 7.6			10.0 8.4	10.0 8.6	10.0 8.5	10.0 8.6	10.0 8.5	9.5 8.5	8.0 8.4						
8607500093	I75	2.437 7.9	5.104 10.6	R 4	4 9.1	1 70 170500 FC5M	CRACKING RIDE	9.0 8.8	9.0 8.8	9.0 8.8	8.0 8.7	8.0 8.2	7.0 8.1	7.0 7.8		10.0 7.4	10.0 7.5	10.0 7.7	10.0 7.7	10.0 7.6							
4378321	HALLEY ENGINEERING	0.000	6.000	R 2019	CONTRAC(2021)	0012	CRACKING SPRIDE	10.0 7.5	10.0 7.6	9.0 7.6	4.5* 7.7	4.5* 7.6			3.5* 7.2	10.0 8.9	10.0 8.9	10.0 8.8	10.0 8.9	10.0 8.8	8.5 8.7						
8607500093	I75	5.104 10.6	6.000 11.5	R 4	4 9.1	1 70 170500 FC5M	CRACKING RIDE	9.0 8.8	9.0 8.8	9.0 8.8	8.0 8.7	8.0 8.2	7.0 8.1	7.0 7.8		10.0 7.4	10.0 7.5	10.0 7.7	10.0 7.7	10.0 7.6							
4378321	HALLEY ENGINEERING	0.000	6.000	R 2019	CONTRAC(2020)	0012	CRACKING SPRIDE	10.0 7.5	10.0 7.6	9.0 7.6	4.5* 7.7	4.5* 7.6			10.0 8.1	10.0 8.3	10.0 8.4	10.0 8.3	10.0 8.3	9.5 8.4	8.0 8.3						
8607500093	I75	6.000 11.5	8.120 13.6	R 4	4 9.1	1 70 170500 FC5M	CRACKING RIDE	9.0 8.8	9.0 8.8	9.0 8.8	8.0 8.7	8.0 8.2	7.0 8.1	7.0 7.8	7.0 7.9		10.0 8.1	10.0 7.8	10.0 7.8	10.0 7.7							
4378322	OHLA USA, INC.	5.966	9.451	R 2021	(2023)	0012	CRACKING SPRIDE	10.0 7.8	10.0 7.8	10.0 7.8	10.0 8.2	10.0 8.2	10.0 8.1	9.0 8.1	9.0 8.1	10.0 8.4	9.0 8.3	10.0 8.7	10.0 8.6	9.7 8.6	8.5 8.5						
8607500093	I75	8.120 13.6	10.700 16.2	R 4	4 9.1	1 70 169000 FC5M	CRACKING RIDE	9.0 8.8	9.0 8.8	9.0 8.8	8.0 8.7	8.0 8.2	7.0 8.1	7.0 7.8	7.0 7.9			10.0 7.8	10.0 7.9	10.0 7.8							
4378322	OHLA USA, INC.	5.966	9.451	R 2021	(2023)	0012	CRACKING SPRIDE	10.0 7.8	10.0 7.8	10.0 7.8	10.0 8.0	10.0 8.1	10.0 8.1	9.0 8.0	9.0 8.0	9.0 8.2	9.0 8.2	10.0 8.9	10.0 8.8	9.7 8.7	8.5 8.6						
8607500093	I75	10.700 16.2	11.610 17.1	R 4	4 11.1	1 70 169000 FC5M	CRACKING RIDE	6.5 8.7	6.5 8.7	4.5* 8.7	4.5* 8.6	4.5* 7.8	4.5* 7.8	4.5* 7.6	4.5* 7.8			10.0 7.8	10.0 7.9	10.0 7.8							
4113221	COMMUNITY ASPHALT CORP.	5.917	11.153	R 2006	(2010)	0012	CRACKING RIDE	10.0 7.8	10.0 7.8	10.0 7.8	10.0 8.0	10.0 8.1	10.0 8.1	9.0 8.0	9.0 8.0	9.0 8.2	9.0 8.2	9.0 8.1	9.0 8.0	8.9 8.0	6.0* 7.9						
8607500093	I75	11.610 17.1	12.650 18.1	R 4	4 15.4	1 70 69000 FC5M	CRACKING RIDE	6.5 8.7	6.5 8.7	4.5* 8.7	4.5* 8.6	4.5* 7.8	4.5* 7.8	4.5* 7.6	10.0 7.9	10.0 8.0	10.0 8.1	9.0 8.1	9.0 8.1	9.0 8.0							
4416681	OHLA USA, INC.	11.605	17.199	R 2021	(2024)	0012	CRACKING SPRIDE	9.0 8.0	9.0 8.0	9.0 8.0	9.0 8.0	9.0 8.0	9.0 8.0	7.5 8.0	7.5 7.9	7.5 8.1	7.5 8.1		10.0 8.9	10.0 8.7	9.0 8.6						
8607500093	I75	12.650 18.1	13.800 19.3	R 4	4 15.4	1 70 69000 FC5M	CRACKING RIDE	6.5 8.7	6.5 8.7	4.5* 8.7	4.5* 8.6	4.5* 7.8	4.5* 7.8	4.5* 7.6	10.0 7.9	10.0 8.0	10.0 8.1	9.0 8.1	9.0 8.1	9.0 8.0							
4416681	OHLA USA, INC.	11.605	17.199	R 2021	(2024)	0012	CRACKING SPRIDE	9.0 8.0	9.0 8.0	9.0 8.0	9.0 8.0	9.0 8.0	9.0 8.0	7.5 8.0	7.5 7.9	7.5 8.1	7.5 8.1		10.0 8.7	10.0 8.7	9.0 8.6						

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																									
RDWYID	SR	US	BMP	G BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
INTERSECT	AT	(MP)	(SIDE)			LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
ITMSEG-P	W BMP	W BMP	W_EMP	RW	FY-P	WKMX-P																			
CONTRACTOR	(AGE ONE YEAR)					ASTYPE					2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W_EMP		RW	FY-F	WKMX-F																		(PMRS)	
86075000	13.800	17.500		R	4	1 70			CRACKING		6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.0	9.0	9.0		
93 I75	19.3	23.0		3	19.5	40500			RIDE		8.7	8.7	8.7	8.6	7.8	7.8	7.6	7.9	8.0	8.1	8.1	8.1	8.0		
4416681	11.605	17.199		R	2021	0012			CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5		10.0	10.0	9.0	
OHLA USA, INC.				(2024)		SPRIDE					8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.9	8.1	8.1		8.6	8.6	8.5	
86075000	17.500	18.900		R	4	1 70			CRACKING		7.0	7.0	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0		
93 I75	23.0	24.4		2	13.5	33335			RIDE		8.7	8.7	8.7	8.6	7.7	7.8	7.5	7.8	8.0	8.1	8.1	8.1	8.0	8.0	
4416681	17.199	18.932		R	2021	0012			CRACKING		10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		10.0	10.0	9.0	
OHLA USA, INC.				(2024)		SPRIDE					8.1	8.0	8.1	8.1	8.1	8.1	8.0	8.0	8.2	8.2		8.5	8.4	8.3	
86075000	18.900	30.054		R	4	1 70			CRACKING		9.0	9.0	9.0	8.0	8.0	7.0	7.0	7.0	7.8	6.5	6.5	4.5*		10.0	
93 I75	24.4	35.5		2	13.5	33335			RIDE		8.8	8.8	8.5	8.6	8.2	8.1	8.0	7.8	7.8	7.8	7.8		8.1		
4153941	18.870	30.054		C	2009	0012			CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	6.8	4.0*	
ASPHALT GROUP, INC.				(2012)		RIDE					8.1	8.1	8.1	8.2	8.2	8.2	8.1	8.1	8.1	8.3	8.3	8.3	8.2	8.1	
4441221	18.873	31.261		C	2025	0012																			
86075000	30.054	34.870		R	4	1 70			CRACKING		9.0	9.0	9.0	6.5	6.5	7.0	7.0	7.0	7.8	6.5	6.0*		10.0		
93 I75	35.5	40.3		2	13.5	33335			RIDE		8.6	8.7	8.5	8.5	7.8	8.1	8.0	7.8	7.9	7.9	7.8		8.0		
4153972	30.054	35.000		C	2009	0012			CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	5.0*	
ASPHALT GROUP, INC.				(2012)		RIDE					8.1	8.0	8.1	8.2	8.2	8.2	8.1	8.1	8.3	8.3	8.2	8.3	8.2	8.1	
4441224	31.261	45.341		C	2024	0012																			
86075000	34.870	45.367		R	4	1 70			CRACKING		9.0	9.0	9.0	6.5	6.5	6.5	3.5*	3.5*	3.5*		10.0	10.0	10.0		
93 I75	40.3	50.8		2	13.5	33335			RIDE		8.6	8.7	8.5	8.5	7.8	7.7	7.5	7.0	7.2		8.0	8.0	7.9		
4153971	35.000	45.410		C	2007	0012			CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	3.5*	
COMMUNITY ASPHALT CORP.				(2010)		RIDE					7.9	7.8	7.9	8.2	8.2	8.2	8.1	8.0	8.4	8.3	8.3	8.3	8.2	8.1	
4441224	31.261	45.341		C	2024	0012																			
86075000	35.000	45.367		L	4	1 70			CRACKING		9.0	9.0	7.5	6.5	6.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	10.0		
93 I75	40.5	50.8		2	13.5	33335			RIDE		8.7	8.6	8.6	8.8	7.8	7.6	7.5	7.2	7.2		7.9	7.9	7.8		
4153971	35.000	45.410		C	2007	0012			CRACKING		10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	4.5*	
COMMUNITY ASPHALT CORP.				(2010)		RIDE					7.7	7.6	7.7	7.9	7.9	7.9	7.8	7.8	8.0	8.0	8.0	8.0	7.9	7.8	
4441224	31.261	45.341		C	2024	0012																			
86075000	30.050	35.000		L	4	1 70			CRACKING		9.0	9.0	7.5	6.5	6.5	6.5	4.5*	7.0	6.5	5.5*	5.5*		10.0		
93 I75	35.5	40.5		2	13.5	33335			RIDE		8.7	8.6	8.6	8.8	7.8	7.6	7.5	7.8	7.9	7.8	7.8		8.0		
4153972	30.054	35.000		C	2009	0012			CRACKING		10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.3	5.5*	
ASPHALT GROUP, INC.				(2012)		RIDE					8.0	8.0	8.0	8.1	8.1	8.1	8.0	8.0	8.2	8.2	8.2	8.2	8.1	8.0	
4441224	31.261	45.341		C	2024	0012																			
86075000	18.870	30.050		L	4	1 70			CRACKING		9.0	9.0	9.0	8.0	8.0	7.0	7.0	7.0	7.0	6.0*	5.5*		10.0		
93 I75	24.3	35.5		2	13.5	33335			RIDE		8.7	8.6	8.6	8.5	7.8	7.8	7.7	7.2	7.2	7.2	7.3	7.2		8.0	
4153941	18.870	30.054		C	2009	0012			CRACKING		10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	5.0*	
ASPHALT GROUP, INC.				(2012)		RIDE					8.1	8.0	8.1	8.1	8.1	8.1	8.1	8.0	8.3	8.3	8.3	8.2	8.2	8.1	
4441221	18.873	31.261		C	2025	0012																			
86075000	17.680	18.870		L	4	7 70			CRACKING		9.0	9.0	7.5	7.5	7.5	6.5	4.5*	10.0	10.0	9.5	9.5	8.0	8.0		
93 I75	23.1	24.3		2	13.5	33335			RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.6	7.7	7.9	7.9	7.9	7.9	7.8		
4416681	17.690	18.932		L	2021	0012			CRACKING		8.0	8.0	8.0	8.0	8.0	7.5	7.5	7.5	7.5	7.5		10.0	9.0		
OHLA USA, INC.				(2025)		SPRIDE					7.9	7.8	7.9	8.0	8.0	8.0	7.9	7.9	8.1	8.1		8.8	8.7		
86075000	11.540	17.680		L	4	7 70			CRACKING		9.0	9.0	7.5	7.5	7.5	6.5	4.5*	10.0	10.0	9.5	9.5	8.0	8.0		
93 I75	17.0	23.1		3	15.4	69000			RIDE		8.7	8.6	8.6	8.5	7.8	7.7	7.6	7.7	7.9	7.9	7.9	7.9	7.8		
4416681	11.459	17.690		L	2021	0012			CRACKING		8.0	8.0	8.0	8.0	8.0	7.5	7.5	7.5	7.5	7.5		10.0	9.0		
OHLA USA, INC.				(2025)		SPRIDE					7.9	7.8	7.9	8.0	8.0	8.0	7.9	7.9	8.1	8.1		8.8	8.7		
86075000	10.784	11.540		L	4	7 70			CRACKING		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		
93 I75	16.2	17.0		6	11.1	169000			RIDE		8.9	9.0	8.9	8.9	8.3	8.3	8.1	7.8	7.8	8.1	7.8	7.7	7.7		
RAMP 86075047(11.3L)																									
4378322	10.342	11.340		L	2021	0012			CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		10.0	9.0		
OHLA USA, INC.				(2025)		SPRIDE					7.8	7.8	7.9	8.0	8.0	8.0	7.9	7.9	8.1	8.1		8.3	8.2		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4											COUNTY = BROWARD														
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
INTERSECT	AT	(MP)	(SIDE)																						
ITMSEG-P	W_BMP	W_EMP	W_EMP	RW	FY-P	W_KMX-P	ASTYPE																		
CONTRACTOR	(AGE)	ONE	YEAR																						
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	W_KMX-F																				(PMRS)
86075000	7.366	10.784	L	4	7	70	CRACKING	8.5	7.0	7.0	6.5	4.5*	4.5*	4.5*	3.5*						10.0	10.0	10.0		
93 I75	12.8	16.2	4	9.1	169000	RIDE	8.7	8.7	8.6	8.6	7.9	7.8	7.5	7.3							7.9	7.9	7.9		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

										DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE										
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012												
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKM-X-P	=====																									
ITMSEG-P	(AGE ONE YEAR)				ASTYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)											
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKMX-F																										
86080000 84	16.171	16.260	R 2	1 5.8	6 50 41500	CRACKING RIDE	10.0 7.5	10.0 7.5	10.0 7.7	9.0 7.8	9.0 6.6	9.0 7.1	9.0 6.9	6.5 7.3	6.5 7.0	6.5 7.1	6.5 7.2	4.5* 7.0	4.5* 6.9												
4230041 ASPHALT GROUP, INC.	16.080	16.803	R (2015)	2012	0012 DGFC	CRACKING SPRIDE	4.5* 6.5	4.5* 6.5	10.0 8.3	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5											
86080000 84	16.260	16.796	R 2	1 5.8	1 45 41500	CRACKING RIDE	10.0 7.5	10.0 7.5	10.0 7.7	9.0 7.8	9.0 6.6	9.0 7.1	9.0 6.9	6.5 7.3	6.5 7.0	6.5 7.1	6.5 7.2	4.5* 7.0	4.5* 6.9												
FRONTAGE ROAD(16.4R)	16.080	16.803	R (2014)	2012	0012 FC5	CRACKING SPRIDE	4.5* 6.5	10.0 7.8	10.0 7.5	10.0 7.7	10.0 7.6	10.0 7.6	10.0 7.4	7.5 7.4	6.5 7.4	6.5 7.4	6.5 7.4	6.5 7.2	6.5 7.2	4.5* 7.0											
4498271	16.271	17.207	C 2027		0012																										
86080000 84	16.796	17.137	R 4	1 9.0	1 45 38500	CRACKING RIDE	9.0 7.8	9.0 7.8	9.0 7.6	9.0 7.7	9.0 7.1	6.5 7.2	6.5 6.9	6.5 6.7	4.5* 6.6	4.5* 6.6	4.5* 6.7	4.5* 6.4	4.5* 6.2												
SW 29 AVE(16.9R)	16.803	16.975	R (2014)	2012	0012 FC5	CRACKING SPRIDE	4.5* 6.2	10.0 7.6	10.0 7.6	10.0 7.4	10.0 7.0	10.0 7.6	10.0 7.1	9.0 6.6	7.5 7.0	7.5 6.9	7.5 6.7	7.5 6.7	7.1 6.8	5.0* 6.6											
4498271	16.271	17.207	C 2027		0012																										
86080000 84	17.137	17.514	R 3	1 9.0	1 45 38500	CRACKING RIDE	9.0 8.2	6.5 8.2	6.5 8.5	6.5 8.2	6.5 7.8	6.5 7.5	6.5 7.2	4.5* 7.1	4.5* 7.2		10.0 7.4	10.0 7.1	10.0 7.6												
SW 26 TER(17.2R)					FC95	CRACKING RIDE	10.0 7.7	10.0 7.5	10.0 7.5	10.0 7.1	10.0 7.1	10.0 7.4	10.0 6.9	10.0 7.0	10.0 7.0	10.0 6.9		10.0 8.0	9.0 7.8	8.5 7.4											
(2024)																															
86080000 84	17.514	17.980	C 3	1 9.0	6 45 19250	CRACKING RIDE	9.0 8.2	6.5 8.2	6.5 8.5	6.5 8.2	6.5 7.8	6.5 7.5	6.5 7.2	4.5* 7.1	4.5* 7.2		10.0 7.4	10.0 7.1	10.0												
ACCESS RD(17.9L)					FC95	CRACKING RIDE	10.0 7.1	10.0 7.1	10.0 7.0	10.0 6.6	10.0 6.6	10.0 6.3	10.0 6.5	10.0 6.3	10.0 6.3			10.0 5.7	8.5 5.6	8.0 5.6											
(2024)																		10.0 5.7	8.5 5.6	8.0 5.2*											
86080000 84	17.980	19.776	R 3	1 7.3	1 40 58500	CRACKING RIDE	9.0 6.0*	9.0 5.9*	9.0 6.6	9.0 6.6	9.0 5.9	9.0 5.8	9.0 5.8	9.0 5.9	6.5 5.6		10.0 7.4	10.0 7.1	10.0 7.1												
ACCESS RD 86080002(18.0R)	16.698	19.570	C (2010)	2007	0012 FC95	CRACKING SPRIDE	10.0 7.0	10.0 7.0	10.0 7.0	9.5 6.6	8.5 6.6	8.5 6.3	8.5 6.5	8.5 6.3	7.0 6.3	7.0 6.1	7.0 5.7	7.0 5.6	8.0 5.6	6.5 5.2*											
WEEKLEY ASPHALT PAVING, IN																															
86080000 84	17.980	19.776	L 4	1 7.3	1 40 58500	CRACKING RIDE	9.0 6.9	9.0 6.5	9.0 6.6	9.0 6.5	9.0 5.9	9.0 5.9	9.0 5.5	9.0 5.2*	6.5 5.6		10.0 7.4	10.0 7.3	10.0 7.1												
ACCESS RD(18.0L)	18.698	19.570	C (2010)	2007	0012 FC95	CRACKING SPRIDE	10.0 7.1	10.0 7.1	10.0 7.0	10.0 6.7	10.0 6.5	10.0 6.7	10.0 6.7	10.0 6.6	10.0 6.6	9.0 6.3	9.0 5.9	9.0 5.7	9.0 5.9	7.5 5.5											
2282431	18.698	19.570																													
WEEKLEY ASPHALT PAVING, IN																															
86080000 84	17.187	17.514	L 4	1 9.0	1 45 38500	CRACKING RIDE	9.0 7.9	9.0 8.0	9.0 8.0	6.5 7.9	6.5 7.3	6.5 7.4	6.5 7.1	6.5 7.0	6.5 7.3		10.0 7.4	10.0 7.3	10.0 7.4												
SW 25 TER(17.3L)					FC95	CRACKING RIDE	10.0 7.6	10.0 7.5	10.0 7.5	10.0 7.5	10.0 7.3	10.0 7.3	10.0 7.3	9.0 7.2	9.0 7.3		10.0 7.2	10.0 7.4	8.7 7.4	8.0 7.0											
(2023)																															
86080000 84	16.260	17.187	L 2	1 5.8	1 45 41500	CRACKING RIDE	10.0 7.9	10.0 7.1	10.0 7.9	9.0 7.0	9.0 7.5	9.0 7.5	9.0 7.3	6.5 7.2	4.5* 7.2	4.5* 7.0	4.5* 6.8	4.5* 6.6	4.5* 6.5												
FRONTAGE ROAD(16.4L)	16.080	17.137	L (2014)	2012	0012 FC5	CRACKING SPRIDE	4.5* 6.1	10.0 7.4	10.0 7.4	10.0 7.0	10.0 7.0	10.0 7.2	10.0 7.0	9.0 6.9	7.5 6.9	6.5 6.9	6.5 6.8	6.5 6.8	6.5 6.7	4.5* 6.5											
4498271	16.271	17.207	C 2027		0012																										
86080000 84	16.171	16.260	L 2	1 5.8	6 50 41500	CRACKING RIDE	10.0 8.2	10.0 8.2	10.0 8.2	10.0 8.1	10.0 7.5	10.0 7.6	10.0 7.3	8.5 7.2	8.5 7.4	7.0 7.4	6.5 7.4	6.5 7.3	6.5 7.3												
CANAL DR(16.2L)	16.080	17.137	L (2015)	2012	0012 DGFC	CRACKING SPRIDE	6.5 7.2	6.5 7.2	10.0 8.2	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.0											
ASPHALT GROUP, INC.																															
86080100 84	0.000	2.252	C 2	1 6.6	1 45 13500	CRACKING RIDE																									
CANAL DRIVE(0.0R)					DGFC	CRACKING RIDE				10.0 8.3	10.0 8.3	10.0 8.3	10.0 8.2	9.0 8.0	9.0 8.0	9.0 8.0	9.0 7.8	9.0 7.9	8.7 7.8	7.5 7.4											
(2016)																															

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4											COUNTY = BROWARD														
RDWYID	SR	US	BMP	G	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE	
INTERSECT	AT	(MP)	SIDE							=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P																				
CONTRACTOR	(AGE ONE YEAR)				ASTYPE						2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																				
86080500	0.000	3.810	C	1	1	55	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	10.0		
84			2	2.8	6500	RIDE					8.5	8.4	8.5	8.5	7.8	7.7	7.7	7.5	7.7	7.6	7.7	7.5	8.3		
ARVIDA PKWY(0.0C)					FC5M																				
			(2024)				CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		10.0	10.0	9.0	
							RIDE				8.3	8.1	7.9	8.1	8.0	8.0	7.9	7.8	7.8	7.7		8.4	8.4	8.2	
86080500	3.810	5.443	C	1	1	55	CRACKING				9.0	9.0	9.0	9.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	10.0		
84			2	1.4	6700	RIDE					8.6	8.7	8.6	8.4	8.0	8.0	7.8	7.9	7.6	7.8	7.8	8.0	8.2		
SPUR FROM WESTON RD(3.8R)					FC5																				
			(2023)				CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0	9.0	
							RIDE				8.0	7.6	8.3	8.3	8.3	8.2	8.2	8.1	8.2		8.1	8.0	8.0	7.8	
86080500	5.443	10.434	C	1	1	50	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	6.5	6.0*			
84			2	5.8	17500	RIDE					8.4	8.4	8.4	8.3	7.6	7.7	7.6	7.6	7.6	7.6	7.6	7.5			
POINCIANA WAY(5.6R)					DGFC																				
			(2015)				CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
							RIDE					7.7	7.4	7.3	7.4	7.3	7.2	7.2	7.2	7.2	7.2	7.3	7.2	7.2	6.8
86080500	10.434	12.460	C	1	1	50	CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5			
84			2	10.3	11500	RIDE					8.2	8.3	7.9	8.0	7.8	7.7	7.5	7.4	7.5	7.4	7.6	7.3			
SW 81 AVENUE(10.6R)					DGFC																				
			(2015)				CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
							RIDE					7.7	7.1	7.1	7.0	6.9	6.9	6.8	6.9	6.9	6.9	6.7	6.8	6.4*	
86080500	12.460	14.188	C	1	1	45	CRACKING																		
84			2	5.4	26000	RIDE																			
SPUR(12.5R)					DGFC																				
			(2016)				CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
							RIDE					7.4	7.4	7.5	7.4	7.3	7.2	7.3	7.2	7.3	7.2	7.3	7.2	6.8	
86080500	14.188	14.750	C	1	1	45	CRACKING																		
84			2	3.9	8200	RIDE																			
CANAL DR(14.8L)					DGFC																				
			(2016)				CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	8.0	
							RIDE					7.4	7.3	7.3	7.4	7.3	7.2	7.1	7.1	7.1	7.1	7.2	7.1	6.7	
86080550	0.000	1.350	C	1	1	50	CRACKING				10.0	10.0	7.5	7.5	7.5	6.5	6.5	3.5*	3.5*	3.5*	3.5*	3.5*			
84			3	9.2	32500	RIDE					8.6	8.5	7.7	8.2	7.3	7.4	7.5	7.3	7.3	7.2	7.2	7.2			
DAVIE RD(0.0L)					DGFC																				
			(2015)				CRACKING					10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	
							RIDE					8.4	8.2	8.1	8.1	8.1	8.1	7.9	7.9	7.9	7.9	7.9	7.9	7.4	
86080550	1.350	2.003	C	1	1	50	CRACKING				10.0	10.0	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*			
84			2	2.4	21000	RIDE					8.6	8.5	7.3	7.9	6.8	6.6	6.4*	6.2*	6.6	6.4*	6.0*	5.8*			
TURN AROUND(1.5L)					DGFC																				
			(2015)				CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
							RIDE					7.4	7.6	7.7	7.6	7.5	7.5	7.4	7.3	7.4	7.3	7.3	7.3	6.9	
86080550	2.003	6.545	C	1	1	50	CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.0	6.5	6.5	6.5			
84			2	3.4	18500	RIDE					8.6	8.5	8.4	8.3	7.8	7.8	7.5	7.5	7.5	7.6	7.5	7.4			
TURN AROUND(2.5L)					DGFC																				
			(2015)				CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0	
							RIDE					7.8	7.6	7.6	7.6	7.5	7.5	7.4	7.4	7.4	7.4	7.4	7.3	6.9	
86080550	6.545	8.686	C	1	1	55	CRACKING				10.0	10.0	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0		
84			2	3.6	8200	RIDE					8.5	8.5	8.2	8.1	7.5	7.5	7.4	7.3	7.2	7.0	6.9	8.3	8.1		
TURN AROUND(6.6L)					FC5																				
4153231	6.545	8.710	C	2010	0012	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.4	6.0*	
COMMUNITY ASPHALT CORP.			(2011)		SPRIDE						8.1	7.8	7.7	7.8	7.7	7.7	7.6	7.5	7.4	7.1	7.1	7.0	6.9	6.7	
86080550	8.686	12.387	C	1	1	55	CRACKING				10.0	9.0	9.0	9.0	9.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	10.0		
84			2	9.5	6400	RIDE					7.7	8.1	8.5	8.4	7.7	7.8	7.7	7.6	7.4	7.5	7.5	7.2	8.4		
TURN AROUND(9.1L)					FC5M																				
			(2024)				CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
							RIDE				8.2	7.8	7.9	7.9	7.9	7.8	7.7	7.6	7.6	7.4	7.6	8.5	8.4	8.2	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

											DISTRICT = 4				COUNTY = BROWARD														
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE						
INTERSECT	AT	(MP SIDE)	W_BMP	W_EMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012						
ITMSEG-P	CONTRACTOR	(AGE ONE YEAR)	W_BMP	W_EMP	W_EMP	RW	FY-F	WKM-X-F			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)					
86081000	84	SW 18 TER(	0.000	0.1R)	0.591	C	1	1	45	CRACKING													10.0						
						3	7.3	17000		RIDE													7.4						
										DGFC																			
										(2024)	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		9.0	10.0	10.0	9.5					
										RIDE		7.5	7.5	7.3	7.4	7.4	7.3	7.2	7.4	7.3		7.0	7.4	7.0					
86090000	816	SR 817(	0.000	0.0C)	0.910	R	1	1	45	CRACKING	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0						
						3	3.7	36500		RIDE	6.9	7.4	7.3	7.3	6.4*	6.3*	6.2	6.4	7.1	7.3	7.3	7.1	7.0						
										FC125																			
										0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.2	7.0					
										SPRIDE		7.1	7.0	7.0	6.6	6.3	6.7	6.5	6.3	6.2	6.5	6.3	6.0	5.7					
86090000	816	DENTISTRY(	0.910	1.0R)	2.102	R	1	1	45	CRACKING	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0						
						3	2.1	50500		RIDE	6.9	7.4	7.3	7.3	6.4*	6.3*	6.2	6.4	6.9	6.8	6.6	6.5	6.4						
										FC125																			
										0012	CRACKING	10.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5	8.4	7.0					
										SPRIDE		6.2	6.0	5.6	6.1	6.0	5.9	6.0	5.9	5.7	5.8	5.7	5.8	5.4*					
86090000	816	NW 49 AVE(	2.102	2.5R)	3.329	R	1	1	45	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0						
						3	5.1	51000		RIDE	7.1	7.0	6.9	7.0	6.2*	6.1*	6.8	6.7	6.7	6.7	6.7	6.6	6.3						
										FC125																			
										(2006)	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.3	7.0					
										RIDE		6.5	6.5	6.1	6.3	6.3	5.9	6.0	6.0	6.0	5.9	5.5	5.5	5.7					
4476751	816		2.102	4.407	4.407	C	2027	0012																					
86090000	816	NW 36 TER(	3.329	3.6C)	4.400	R	1	1	45	CRACKING	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*		10.0	10.0						
						3	3.9	58000		RIDE	6.7	7.0	6.8	6.8	6.1*	6.3*	6.0	6.1	5.9	5.5		7.4	7.6						
										FC95																			
										0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	8.5	7.5	7.5	8.5	7.0					
										SPRIDE		7.2	6.4	7.2	7.0	6.9	6.8	6.5	6.5	6.1	5.9	6.1	6.1	5.6					
86090000	816	COMMUNITY ASPHALT	2.102	4.407	4.407	C	2027	0012																					
86090000	816	NW 30 AVE(	4.400	4.5R)	6.230	R	1	1	45	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	6.5	6.5						
						3	2.8	55000		RIDE	7.8	7.6	7.9	7.6	6.8	6.9	6.7	6.5	6.8	6.7	6.5	6.4	6.4						
										FC95A																			
										0012	CRACKING	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.0					
										SPRIDE		6.5	4.2*	6.4	5.8	5.5	7.8	7.5	7.6	7.4	7.3	7.3	6.9	7.1					
86090000	816	COMMUNITY ASPHALT	6.230	9.201	9.201	R	1	1	35	CRACKING	7.5	7.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*		10.0	10.0						
						3	3.7	35000		RIDE	7.4	7.3	7.3	7.0	6.5	6.4	6.6	6.1	6.1	6.1		7.2	6.8						
										FC95																			
										0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	7.0	7.0	8.0	6.5					
										SPRIDE		6.9	7.0	7.1	6.7	6.6	6.5	6.2	6.1	6.0	6.2	7.0	5.7	5.5					
86090000	816	ACCESS ROAD(	9.201	9.3R)	9.720	R	1	6	35	CRACKING	8.5	8.5	8.5	8.5	8.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5						
						2	6.1	26500		RIDE	5.6*	5.8*	5.8	6.0	5.2*	6.5	6.4	6.4	5.3*	6.5	6.5	5.1*	6.2						
										FC125																			
										0012	CRACKING	8.5	8.5	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	7.0	5.5*					
										SPRIDE		5.7	5.8	5.5	5.4*	5.2*	5.1*	5.1*											
86090000	816	WEEKLEY ASPHALT PAVING,	9.201	9.720	9.720	L	1	1	35	CRACKING	8.5	8.5	8.5	8.5	8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0						
						2	6.1	26500		RIDE	5.4*	5.7*	5.5	6.1	5.6	6.8	6.4	6.3	5.0*	6.6	5.8	5.4*	5.6						
										FC125																			
										0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	7.0	5.5*					
										SPRIDE		5.4*	6.1	5.9	4.8*	5.1*	4.3*	4.5*	4.4*	4.5*	4.5*	4.4*	4.2*	4.2*					
86090000	816	WEEKLEY ASPHALT PAVING,	6.230	9.201	9.201	L	1	1	35	CRACKING	7.5	7.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*		10.0					
						3	3.7	35000		RIDE	7.5	7.1	6.7	6.6	6.4	6.3	6.2	5.8	5.5	5.9		7.2	7.0						
										FC95																			
										0012	CRACKING	10.0	10.0	10.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	5.5*					
										SPRIDE		6.9	6.8	6.8	6.3	6.0	6.1	5.8	5.7	5.7	5.7	5.5	5.4*	5.5					
86090000	816	THE SHOPPES OF OAK(	4.400	4.5L)	6.230	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	9.0	9.0	7.5						
						3	2.8	55000		RIDE	7.7	7.6	7.5	7.5	6.5	6.6	6.4	6.3	6.2	6.4	6.8	6.8	6.0						
										FC95A																			
										0012	CRACKING	7.5	7.5	7.0	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0					
										SPRIDE		6.0	5.8	6.2	6.3	6.0	8.1	8.0	7.8	7.8	7.7	7.7	7.4	7.0					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD

RDWYID	SR	US	BMP	G BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	RATINGS	SURVEYED YEAR												FUTURE		
INTERSECT	AT	(MP)	(SIDE)			LN	%T	AADT		=====		2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P	ASTYPE																				
CONTRACTOR	(AGE)	ONE	YEAR									2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																				(PMRS)	
86090000	3.329	4.400	L	1	1	45	CRACKING	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*		10.0	10.0			
816			3	3.9	58000	RIDE	6.5	7.0	6.7	6.6	5.9*	6.1*	6.1	5.9	5.8	5.3*						7.4	7.4			
NW 36 TER(	3.6C)				FC95																					
4138861	3.329	4.429	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.0*		
COMMUNITY ASPHALT CORP.	(2011)				SPRIDE																					
4476751	2.102	4.407	C	2027	0012																					
86090000	2.102	3.329	L	1	1	45	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5			
816			3	5.1	51000	RIDE	6.1*	6.3*	6.3*	6.0*	5.9*	6.1*	6.1	6.9	6.5	6.7	6.5	6.7	6.5	6.5	6.5	6.5	6.5	6.6		
ROCK ISLAND RD(	2.1L)				FC125																					
					(2006)																					
4476751	2.102	4.407	C	2027	0012	CRACKING	9.5	9.5	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.0*		
					RIDE																					
					6.5	6.4	6.5	5.9	5.6	5.7	5.6	5.4*	5.6	4.6*	5.0*	5.3*	5.1*	4.7*								
86090000	0.910	2.102	L	1	1	45	CRACKING	6.5	6.5	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0		
816			3	2.1	50500	RIDE	7.1	7.1	6.9	7.0	6.1*	6.1*	6.0	5.9	6.9	7.0	6.6	6.9	6.9	6.9	6.9	6.9	6.9	6.9		
LANDINGS DR(	1.1C)				FC125																					
2281571	0.000	2.332	L	2005	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.4	7.0	
PREFERRED MATERIALS, INC.	(2008)				SPRIDE																					
					6.9	6.9	6.9	6.2	6.1	6.1	5.9	6.0	5.8	5.8	5.8	5.9	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.4*	
86090000	0.000	0.910	L	1	1	45	CRACKING	6.5	6.5	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0		
816			3	3.7	36500	RIDE	7.1	7.1	6.9	7.0	6.1*	6.1*	6.0	5.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.9	6.8		
SR 817(	0.0C)				FC125																					
2281571	0.000	2.332	L	2005	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.6	7.0	
PREFERRED MATERIALS, INC.	(2008)				SPRIDE																					
					6.8	6.8	6.9	6.3	6.4	6.4	6.0	6.3	5.9	6.1	6.1	6.1	6.1	6.1	6.1	6.1	6.1	6.1	6.0	5.6		

86095000	0.000	0.592	R	4	1	65	CRACKING	7.5	7.5	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	9.0	9.0			
862 I595	0.0	0.6	5	8.5	129500	RIDE	8.5	8.4	8.4	8.4	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.7		
					FC5M																					
					(2015)																					
					CRACKING																					
					RIDE																					
					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	6.5	4.5*
					8.0	8.1	8.1	8.1	8.0	8.0	8.0	8.0	8.0	8.0	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	7.9	7.8	7.7	
86095000	0.592	5.820	R	4	1	65	CRACKING	7.5	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	9.0	9.0			
862 I595	0.6	5.8	3	8.5	129500	RIDE	8.5	8.4	8.4	8.4	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.7			
SR 84 EB(	4.7R)				FC5M																					
4208093	0.920	5.820	R	2011	0213	CRACKING																				
I 595 EXPRESS, LLC	(2015)				RIDE																					
4208098	0.592	10.407	C	2025	0012																					
					8.0	8.2	8.1	8.1	8.0	8.0	7.9	8.1	8.0	7.9	8.1	8.1	8.0	8.0	8.0	8.0	8.0	8.0	7.9	7.8		
86095000	5.820	7.720	R	4	1	65	CRACKING	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
862 I595	5.8	7.7	4	7.3	151408	RIDE	8.5	8.5	8.5	8.4	7.8	7.7	7.7	7.7	7.7	7.7	7.5	7.9	7.9	7.9	7.9	7.9	7.9	7.9		
SR-84 EB 86080500(	6.9R)				FC5M																					
4208093	5.820	7.720	R	2011	0213	CRACKING																				
I 595 EXPRESS, LLC	(2015)				RIDE																					
4208098	0.592	10.407	C	2025	0012																					
					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
					8.0	8.4	8.3	8.3	8.2	8.2	8.2	8.2	8.2	8.4	7.5	8.4	7.5	8.3	6.5	8.3	6.2*	4.0*				
					8.0	8.1	8.0	8.0	7.9	7.9	8.0	7.9	7.9	8.0	7.9	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.6		
86095000	7.720	9.056	R	4	1	65	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
862 I595	7.7	9.1	4	7.3	220500	RIDE	8.3	8.3	8.2	8.2	7.1	7.5	7.5	7.2	7.4	7.9	7.8	8.0								
					FC5M																					
4208093	7.720	10.407	R	2011	0213	CRACKING																				
I 595 EXPRESS, LLC	(2015)				RIDE																					
4208098	0.592	10.407	C	2025	0012																					
					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
					7.9	7.4	7.8	8.0	8.0	8.0	7.9	7.9	8.1	8.1	8.0	8.1	8.0									
86095000	9.960	10.407	R	4	8	65	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0			
862 I595	10.0	10.4	3	7.3	79500	RIDE	8.5	8.5	8.5	8.2	8.0	7.6	7.6	7.												

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4											COUNTY = BROWARD													
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR												FUTURE
INTERSECT	AT	(MP)	(SIDE)							=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-X-P																			
CONTRACTOR	(AGE)	ONE	YEAR		ASTYPE						2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-X-F																			
86095000	12.263	12.860	L	4	1 65	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	
862 I595	12.3	12.9	3	34.4	7400	RIDE	7.7	7.6	7.7	7.8	7.1	6.8	7.0	6.8	7.1	6.8	6.9	6.9	6.9	6.9	6.9	6.9	6.5	
					OGFC																			
				(2016)		CRACKING	4.5*			10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.0	5.0*	
						RIDE	6.4*			6.8	7.0	6.8	7.1	7.2	6.8	7.1	7.1	7.1	7.1	6.9	6.9	6.9	6.8	
86095000	9.960	11.156	L	4	2 65	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0		
862 I595	10.0	11.2	2	7.3	79500	RIDE	8.7	8.4	8.4	8.3	7.6	7.7	7.7	7.5	7.7	7.1	7.2	7.2	7.4	7.6	7.6	7.6		
					FC5M																			
				(2010)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.9	5.0*	
						RIDE	7.6	7.6	7.6	7.7	7.7	7.7	7.6	7.6	7.8	7.8	7.8	7.7	7.8	7.2	7.1			
86095000	6.825	9.056	L	4	1 65	CRACKING	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0			
862 I595	6.8	9.1	4	7.3	220500	RIDE	8.4	8.4	8.3	8.2	7.6	7.2	7.5	7.6	7.6	7.8	7.9	7.9	7.9	7.9				
SR 84 WB(6.9L)					FC5M																			
4208093	6.825	9.525	L	2011	0213	CRACKING				10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	7.5	6.6	4.5*			
I 595 EXPRESS, LLC				(2016)		RIDE				8.2	8.2	8.2	8.1	8.0	8.2	8.2	8.1	8.1	8.1	8.0	7.9			
4208098	0.592	10.407	C	2025	0012																			
86095000	0.592	6.825	L	4	1 65	CRACKING	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0				
862 I595	0.6	6.8	4	8.5	129500	RIDE	8.7	8.6	8.6	8.5	7.9	7.8	7.7	7.7	8.0	7.7	7.7	7.7	7.6					
SR 84 WB(1.6L)					FC5M																			
4208093	0.592	6.825	L	2011	0213	CRACKING				10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	5.5*		
I 595 EXPRESS, LLC				(2015)		RIDE				8.2	8.3	8.3	8.3	8.2	8.2	8.3	8.3	8.3	8.3	8.3	8.2	8.1		
4208098	0.592	10.407	C	2025	0012																			
86095000	0.000	0.592	L	4	1 65	CRACKING	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0			
862 I595	0.0	0.6	5	8.5	129500	RIDE	8.7	8.6	8.6	8.5	7.9	7.8	7.7	7.7	8.0	7.7	7.7	7.7	7.6	7.4				
					FC5M																			
				(2015)		CRACKING	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.6	5.5*	
						RIDE	7.1		8.1	8.3	8.3	8.2	8.1	8.2	8.3	8.4	8.2	8.3	8.3	8.3	8.3	8.2		
86095900	0.000	0.595	C	4	1 70	CRACKING																		
862 I595			1	7.3	18000	RIDE																		
				(2020)		CRACKING											10.0	10.0	10.0	10.0	10.0	10.0	8.9	7.5
						RIDE											7.6	7.4	7.4	7.3	7.3	7.2	7.1	
86095900	0.595	1.659	C	4	1 70	CRACKING																		
862 I595			2	7.3	18000	RIDE																		
				(2020)		CRACKING											10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.0
						RIDE											7.8	7.7	7.7	7.6	7.7	7.4	7.3	
86095900	1.659	6.725	C	4	1 70	CRACKING																		
862 I595			3	7.3	18000	RIDE																		
				(2020)		CRACKING											10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0
						RIDE											8.0	8.1	8.1	8.0	8.1	8.0	7.9	
86095900	6.725	8.796	C	4	1 70	CRACKING																		
862 I595			2	2.9	10637	RIDE																		
				(2020)		CRACKING											10.0	10.0	10.0	10.0	10.0	9.0	7.5	
						RIDE											8.0	8.1	8.0	8.0	8.1	8.1	8.0	
86100000	0.000	0.900	R	1	1 40	CRACKING	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*							10.0	
7 441			3	5.2	50000	RIDE	6.7	6.8	6.8	6.7	6.5	6.8	6.4	6.3	6.3								7.2	
NW 215 ST/COUNTY LIN(0.0R)					FC125																			
2277731	0.000	1.050	C	2007	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.4	7.0	
RUSSELL ENGINEERING, INC				(2012)	SPRIDE		7.5	7.4	7.5	6.8	6.7	6.5	6.3	6.8	6.8	6.8	6.8	6.8	6.8	6.6	6.7	6.7	6.3	
86100000	0.900	4.957	R	1	1 40	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*			
7 441			3	3.7	53500	RIDE	7.4	7.3	7.3	7.2	6.5	6.7	6.4	6.3	6.3	6.3	6.3	6.3	6.3	6.6	6.5	6.3		
SW 26 ST(1.0R)					FC125M																			
				(2020)		CRACKING	4.5*	4.5*	4.5*	4.5*							10.0	10.0	10.0	10.0	10.0	10.0	9.0	
						RIDE	6.2	5.9	5.9	6.4							7.3	7.2	7.2	7.2	7.1	7.0	6.6	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD

RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	RATINGS	SURVEYED	YEAR	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE
INTERSECT	AT	(MP)	(SIDE)																								
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE																					
CONTRACTOR	(AGE)	ONE	YEAR																								
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F																						
86100000	4.957	5.741	R	1	1 45	CRACKING	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	
7 441			3	4.5	58000	RIDE	7.8	7.5	7.7	7.8	7.3	7.5	7.4	6.8	7.4	7.0	7.3	7.2	7.1								
OAK ST(5.0R)						DGFC																					
2277762	4.968	5.568	C	2003	0213	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	
				(2005)		RIDE	7.2	6.9	7.3	6.5	6.6	7.2	7.1	7.8	7.7	7.8	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	
4476761	4.957	6.664	C	2025	0012																						
86100000	5.741	6.573	R	1	1 45	CRACKING	6.5		10.0	10.0	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
7 441			3	4.5	58000	RIDE	7.7		6.3*	8.6	8.1	8.1	8.1	7.9	7.7	7.9	7.4	7.7	7.4	7.0	7.4	7.0	7.4	7.0	7.4	7.4	
AUTO AUCTION(5.8R)						DGFC																					
				(2003)																							
4476761	4.957	6.664	C	2025	0012																						
86100000	6.573	7.401	R	1	1 45	CRACKING	6.5	9.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	
7 441			3	5.9	50500	RIDE	7.7	8.3	8.2	8.1	7.4	7.4	7.4	7.2	6.9	7.1	7.1	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	
AT&T(6.7R)					FC125																						
4168761	6.479	7.400	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
COMMUNITY ASPHALT CORP.				(2013)		SPRIDE	8.4	8.2	8.3	7.9	7.9	7.9	7.9	7.4	7.8	7.7	7.4	7.7	7.4	7.7	7.4	7.7	7.4	7.7	7.4	7.7	
86100000	7.401	8.349	R	1	1 45	CRACKING	6.5	9.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	
7 441			3	4.3	58000	RIDE	7.7	8.3	8.2	8.1	7.4	7.4	7.4	7.2	6.9	7.1	7.1	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	
				(2015)																							
						CRACKING	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
						RIDE	6.6	6.1	8.3	8.1	8.0	8.1	8.0	8.1	7.9	8.0	7.9	7.8	7.9	7.8	7.9	7.8	7.9	7.8	7.9	7.8	
86100000	8.349	10.461	R	1	1 45	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
7 441			3	5.8	39500	RIDE			8.0	7.9	7.3	7.1	6.9	6.5	7.0	7.1	6.6	6.4	6.0								
RIVERLAND RD(8.5R)					FC3																						
2277041	8.500	10.300	C	1998	0213	CRACKING	10.0	10.0	10.0	8.5	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	
TRIPLE R PAVING INC				(2002)		RIDE	6.4	6.3	6.4	6.5	6.6	6.3	6.3	6.3	6.3	6.3	6.2	6.1	6.2	6.1	6.2	6.1	6.2	6.1	6.2	6.1	
4476771	8.349	10.461	C	2025	0012																						
86100000	10.461	12.986	R	1	1 40	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	
7 441			3	5.2	48500	RIDE	7.4	5.6*	7.0	6.9	6.3	6.5	6.1	5.9	8.2	8.1	7.8	7.9	7.1								
HOSPITAL DR N(10.6R)					FC95																						
2281881	10.461	12.986	C	2006	0012	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	
PAVEX CORPORATION				(2008)		SPRIDE	7.1	6.8	6.9	7.1	7.0	6.9	6.9	6.4	6.5	6.3	6.3	6.2	6.3	6.2	6.3	6.2	6.3	6.2	6.3	6.2	
4484101	10.461	12.986	C	2031	0012																						
86100000	12.986	14.791	R	1	1 40	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	
7 441			3	2.5	54000	RIDE	8.0	8.0	7.6	8.0	7.0	7.2	7.1	6.9	5.3*	7.5	7.4	7.2	7.3								
NW 29 ST(13.1R)					FC95																						
2281891	12.985	14.791	C	2007	0012	CRACKING	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	
COMMUNITY ASPHALT CORP.				(2009)		SPRIDE	7.2	7.3	7.3	6.9	7.0	6.6	6.6	6.6	6.6	6.2	5.9	7.5	6.4	7.5	6.1	6.2	6.2	6.2	6.2	6.2	
86100000	14.791	15.796	R	1	7 45	CRACKING	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
7 441			3	3.8	44500	RIDE	7.2	7.4	7.4	6.8	7.2	7.0	7.0	6.7	6.3	6.7	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	
COMMERCIAL BLVD(14.8C)					FC125M																						
4438451	14.791	15.796	R	2022	0012	CRACKING	10.0	10.0	9.5	9.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	
WEEKLEY ASPHALT PAVING, IN				(2025)		RIDE	6.6	6.7	6.5	6.3	6.4	6.1	6.3	6.1	6.0	5.9	6.1	5.8	6.1	5.8	6.1	5.8	6.1	5.8	6.1	5.8	
86100000	15.796	16.500	R	1	1 45	CRACKING	6.5	6.5	6.5	6.5	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	
7 441			3	3.4	43500	RIDE	7.2	7.4	7.4	6.8	7.6	7.7	7.3	7.2	7.4	7.4	7.5	7.4	7.5	7.4	7.5	7.4	7.5	7.4	7.5	7.4	
RAMP TO MCNAB RD(16.1R)					FC125																						
4168771	15.796	16.389	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	
COMMUNITY ASPHALT CORP.				(2012)		SPRIDE	8.0	7.7	7.5	7.3	7.3	7.2	6.8	6.5	6.8	6.7	6.6	6.8	6.7	6.6	6.8	6.7	6.6	6.8	6.7	6.6	
86100000	16.500	17.900	R	1	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
7 441			3	2.7	49500	RIDE	8.4	8.4	8.3	8.4	7.6	7.7	7.3	7.2	7.4	7.4	7.5	7.4	7.5	7.4	7.5	7.4	7.5	7.4	7.5	7.4	
SW 13 ST(16.5R)					DGFC																						

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKM-F	ASTYPE	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
ITMSEG-P	CONTRACTOR (AGE ONE YEAR)	W BMP	W EMP	RW	FY-F	WKM-F														(PMRS)		
86100000	20.865	23.290	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0		
7 441			3	4.1	57000	RIDE	8.2	8.2	8.1	8.2	7.7	7.7	7.6	7.5	7.7	7.7	7.5	7.5	7.3			
CULLUM RD(21.4R)																						
4216621	20.941	23.359	C	2011	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0	
GENERAL ASPHALT CO., INC. (2014)																						
86100000	23.290	24.597	R	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0		
7 441			3	4.6	55000	RIDE	8.2	8.5	8.3	8.4	7.4	7.9	7.7	7.5	7.8	7.7	7.8	7.7	7.5	7.3		
JOHNSON RD(23.5R)																						
4270101	23.290	24.591	C	2013	0012	CRACKING	9.0	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
COMMUNITY ASPHALT CORP. (2015)																						
86100000	23.290	24.597	L	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5			
7 441			3	4.6	55000	RIDE	8.4	8.4	8.4	8.5	7.7	7.7	7.5	7.5	7.8	7.7	7.6	7.5	7.3			
HOLMBERG RD(23.5L)																						
4270101	23.290	24.591	C	2013	0012	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.6	8.5		
COMMUNITY ASPHALT CORP. (2015)																						
86100000	20.865	23.290	L	1	1	45	CRACKING	9.0	9.0	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*		
7 441			3	4.1	57000	RIDE	8.1	8.1	8.0	8.0	7.5	7.4	7.3	7.1	7.2	7.2	7.1	6.8	6.8			
CREEKSIDE DR(21.4L)																						
4216621	20.941	23.359	C	2011	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.0	
GENERAL ASPHALT CO., INC. (2014)																						
86100000	17.900	20.865	L	1	1	45	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	6.5	6.5	6.5			
7 441			3	3.0	51500	RIDE	8.4	8.2	8.1	8.0	7.6	7.5	7.4	7.2	7.4	7.3	7.1	7.0				
NW 3RD ST(18.0L)																						
4168781	17.900	20.865	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.3	7.0		
RANGER CONSTRUCTION INDUST(2013)																						
86100000	16.500	17.900	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
7 441			3	2.7	49500	RIDE	8.6	8.6	8.4	8.6	8.2	8.1	7.8	7.6	8.1	8.1	8.0	7.9	8.0			
KIMBERLY BLVD(16.8L)																						
2277721	16.374	17.850	C	1995	0213	CRACKING	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	7.5	7.5	8.1	6.5		
WALSH GROUP ARCHER-WESTER(1999)																						
86100000	15.796	16.500	L	1	1	45	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0			
7 441			3	3.4	43500	RIDE	6.8	7.3	7.0	6.9	6.4*	6.4*	6.2	6.1	5.7	5.7	6.0	5.9	8.1			
BROADVIEW BLVD/SW 17(16.1L)																						
4168771	15.796	16.389	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.5	7.5	8.2	7.0		
COMMUNITY ASPHALT CORP. (2012)																						
86100000	14.791	15.796	L	1	7	45	CRACKING	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5			
7 441			3	3.8	44500	RIDE	6.8	6.8	7.1	7.1	7.2	7.2	7.2	7.0	7.1	7.0	7.0	7.2	7.1			
COMMERCIAL BLVD(14.8C)																						
4438451	14.791	15.796	L	2022	0012	CRACKING	9.5	9.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	9.5		
WEEKLEY ASPHALT PAVING, IN(2025)																						
86100000	12.986	14.791	L	1	1	40	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0			
7 441			3	2.5	54000	RIDE	7.1	6.8	7.1	7.1	6.2	6.5	6.3	6.1	5.5	7.6	7.4	7.3	7.5			
WALMART(13.1L)																						
2281891	12.985	14.791	C	2007	0012	CRACKING	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	8.0	6.5		
COMMUNITY ASPHALT CORP. (2009)																						
86100000	10.461	12.986	L	1	1	40	CRACKING	7.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0			
7 441			3	5.2	48500	RIDE	7.3	7.3	7.1	7.3	6.8	6.7	6.5	6.2	7.6	7.4	7.3	6.9	7.3			
HOSPITAL DR S(10.6L)																						
2281881	10.461	12.986	C	2006	0012	CRACKING	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*		
PAVEX CORPORATION (2008)																						
4484101	10.461	12.986	C	2031	0012															6.4		
86100000	9.065	10.461	L	1	1	45	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
7 441			3	5.8	39500	RIDE		8.0	8.0	7.7	7.7	7.6	7.1	7.1	7.5	7.0	7.3	7.0				
DAVIE BLVD(9.1L)																						
2277041	8.500	10.300	C	1998	0213	CRACKING	10.0	10.0	10.0	9.0	7.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	5.5*		
TRIPLE R PAVING INC (2002)																						
4476771	8.349	10.461	C	2025	0012															6.3		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

										DISTRICT = 4 COUNTY = BROWARD																			
RDWYID	SR	US	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE					
INTERSECT	AT	(MP)	(SIDE)	LN	%T	AADT	SURFTYPE		=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012							
ITMSEG-P	W_BMP	W_EMP	W_RW	FY-P	W_KMX-P	ASTYPE																							
CONTRACTOR	(AGE ONE YEAR)									2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)						
ITMSEG-F	W_BMP	W_EMP	W_RW	FY-F	W_KMX-F																								
86100000	8.370	9.065	L	1	1	45	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0							
7 441			3	4.3	58000	RIDE				8.6	8.5	8.6	7.8	7.9	7.4	7.4	7.7	7.8	7.2	7.3	7.5								
SW 21 ST(8.4L)					FC3																								
2277041	8.500	10.300	C	1998	0213	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0							
TRIPLE R PAVING INC				(2001)	S	RIDE	7.6	7.6	6.2	7.1	7.1	6.9	6.9	6.8	6.9	6.9	6.9	6.9	6.9	6.9	6.8	6.4							
4476771	8.349	10.461	C	2025	0012																								
86100000	7.401	8.370	L	1	1	45	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5							
7 441			3	4.3	58000	RIDE	7.9	8.1	8.0	8.1	7.6	7.7	7.5	7.4	7.4	7.4	7.4	7.4	7.4	7.3	7.6								
					DGFC																								
				(2015)				6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0							
								7.0	6.6	8.6	8.2	8.2	8.2	8.1	8.1	8.1	8.1	8.1	8.0	8.0	8.0	7.6							
86100000	6.640	7.401	L	1	2	45	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5							
7 441			3	5.9	50500	RIDE	7.9	8.1	8.0	8.1	7.6	7.7	7.5	7.4	7.4	7.4	7.4	7.4	7.4	7.3	7.6								
U-PULL-IT(6.7L)					FC125																								
4168761	6.479	7.400	C	2010	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	9.0	8.0							
COMMUNITY ASPHALT CORP.				(2013)	SPRIDE		8.3	8.3	8.3	8.0	7.9	8.0	7.8	8.0	7.9	7.8	7.9	7.8	7.8	7.9	7.5	7.1							
86100000	5.741	6.640	L	1	1	45	CRACKING	4.5*			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5								
7 441			3	4.5	58000	RIDE	8.0				7.6	6.9	7.1	6.8	6.2	6.7	7.1	7.3	7.3	7.1									
MANHEIM(5.8L)					DGFC																								
				(2003)				9.5	9.5	9.0	9.0	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	5.5*							
4476761	4.957	6.664	C	2025	0012			7.0	7.0	7.1	7.1	7.2	7.0	6.9	6.9	6.9	6.8	6.6	6.5	6.8	6.4								
86100000	4.957	5.741	L	3	1	45	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0								
7 441			3	4.5	58000	RIDE	8.0	8.0	7.7	7.8	6.7	7.5	7.1	7.0	7.1	7.2	7.2	7.2	6.9	7.0									
HOLLYWOOD CITY LIMITS(5.1C)					DGFC																								
2277762	4.968	5.568	C	2003	0213	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.9	7.5							
				(2005)			7.1	7.1	6.8	5.9	5.9	6.3	6.5	6.2	7.1	6.7	6.8	6.6	6.6	6.6	6.2								
4476761	4.957	6.664	C	2025	0012																								
86100000	0.900	4.957	L	1	1	40	CRACKING	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	4.5*	4.5*								
7 441			3	3.7	53500	RIDE	7.6	7.4	7.3	7.3	7.0	6.8	6.5	6.3	6.6	6.7	6.5	6.5	6.5	6.5	6.3								
SW 26 ST(1.0L)					FC125M																								
				(2020)				4.5*	4.5*	4.5*	4.5*					10.0	10.0	10.0	10.0	10.0	10.0	9.0							
								6.3	6.3	5.6	6.5					7.3	7.2	7.1	7.2	7.1	7.1	6.7							
86100000	0.000	0.900	L	1	1	40	CRACKING	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*				10.0							
7 441			3	5.2	50000	RIDE	7.3	7.6	7.6	7.4	6.4	6.7	6.4	6.1	6.2						7.5								
SR-852/NW 215 ST(0.0L)					FC125																								
2277731	0.000	1.050	C	2007	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.8	7.5						
RUSSELL ENGINEERING, INC				(2012)	SPRIDE		7.4	6.7	7.5	6.7	6.8	6.7	6.5	6.9	6.7	6.8	6.6	6.6	6.6	6.6	6.7	6.3							
86110000	0.000	2.706	R	1	1	45	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0								
838			3	4.7	29500	RIDE	6.5	6.3*	5.4*	8.2	7.8	7.5	7.7	7.3	7.5	7.3	7.5	7.3	7.5	7.4	7.3								
PLANTATION CITY LIMITS(0.0C)					FC125																								
2281171	0.000	3.156	C	2000	0012	CRACKING	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	8.2	6.5							
COMMUNITY ASPHALT CORP.				(2003)	SPRIDE		7.3	7.2	7.2	7.1	7.2	6.9	6.9	6.8	6.7	6.6	6.6	6.6	6.6	6.6	6.5	6.1							
86110000	2.706	3.371	R	1	1	45	CRACKING	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	8.5	8.5	8.5							
838			3	4.8	53500	RIDE	7.3	7.5	7.4	7.2	6.3*	6.4*	6.1	6.2	7.1	7.1	7.2	6.8	7.1										
					FC125M																								
				(2021)				8.5	8.5	8.5	8.5					10.0	10.0	10.0	10.0	10.0	10.0	9.0							
								7.0	7.0	7.1	6.4					7.1	7.1	7.0	7.0	6.9	6.5								
86110000	3.371	3.565	R	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5							
838			3	1.5	58000	RIDE	8.1	8.2	8.0	8.0	7.7	7.6	7.6	7.4	7.1	7.1	7.2	6.8	7.1										
NW 47 AVE(3.4C)					FC3																								
				(2000)				8.5	8.5	8.5	8.5																		
4498211	3.371	5.879	C	2028	0012			7.0	7.0	7.1	6.4					7.0	7.0	7.0	7.0	5.6	5.2*								
86110000	3.565	4.443	R	1	1	45	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5								
838			3	1.5	58000	RIDE			8.0	8.0	7.4	7.5	7.2	7.1	7.3	7.3	7.3	7.3	7.0	7.2									
					FC3																								
				(2002)				8.5	8.5	8.5	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*							
4498211	3.371	5.879	C	2028	0012			7.2	7.3	7.3	7.0	7.0	7.0	6.9	6.8	6.8	6.8	6.8	6.6	6.5	6.5	6.1							

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																									
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR																	FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012					
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKM-F	ASTYPE																			
CONTRACTOR (AGE ONE YEAR)	W BMP	W EMP	RW	FY-F	WKM-F			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030				(PMRS)
ITMSEG-F																									
86110000	4.443	6.190	R	1	1 45	CRACKING		5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0					
838			3	5.3	46000	RIDE		5.9*	5.5*	7.7	7.7	7.1	6.9	6.7	6.7	6.7	6.8	6.8	6.5	6.8					
M L KING AVE(5.0C)					FC3																				
2280761	4.238	6.159	C	2000	0012	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.7	6.0*				
WEEKLEY ASPHALT PAVING, IN(2002)					S	RIDE		6.7	6.6	6.7	6.5	6.3	6.3	6.3	6.6	6.3	6.1	6.0	6.2	6.0	5.6				
4498211	3.371	5.879	C	2028	0012																				
86110000	6.190	8.161	R	1	1 40	CRACKING		7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5					
838			3	3.8	63500	RIDE		7.0	6.6	6.3		7.7	7.4	7.2	7.1	7.5	7.4	7.2	7.1	6.9					
NW 17 AVE(6.3R)					FC3																				
						CRACKING		8.5	8.5	8.5	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.0*				
						RIDE		7.1	7.0	6.9	6.9	6.8	6.6	6.8	6.8	6.6	6.4	6.4	6.3	6.3	5.9				
4476781	6.337	8.040	R	(2004) 2025	0012																				
86110000	6.190	8.161	L	1	1 40	CRACKING		9.0	9.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0					
838			3	3.8	63500	RIDE		7.3	7.3	7.2		7.4	7.3	7.1	7.2	7.2	7.0	7.0	6.7	6.6					
NW 15 AVE(6.5L)					FC3																				
						CRACKING		9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.0	6.5	6.5	6.5	6.5	5.0*				
						RIDE		6.7	6.4	6.6	6.4	6.4	6.4	6.3	6.3	6.2	6.0	5.9	5.8	5.5	5.1*				
4476781	6.330	8.157	L	(2004) 2025	0012																				
86110000	4.443	6.190	L	1	1 45	CRACKING		6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5					
838			3	5.3	46000	RIDE		6.3*	6.2*	8.0	7.7	7.1	7.2	7.0	6.9	6.7	6.8	6.6	6.5	6.3					
M L KING AVE(5.0C)					FC3																				
2280761	4.238	6.159	C	2000	0012	CRACKING		8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.4	6.0*				
WEEKLEY ASPHALT PAVING, IN(2002)					S	RIDE		6.3	6.5	6.5	6.4	6.3	6.3	6.3	6.3	6.3	6.3	6.2	6.1	6.2	5.8				
4498211	3.371	5.879	C	2028	0012																				
86110000	3.565	4.443	L	1	1 45	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5					
838			3	1.5	58000	RIDE				8.0	7.9	7.5	7.6	7.4	7.3	7.5	7.5	7.5	7.5	7.4					
NW 45 AVE(3.6L)					FC3																				
						CRACKING		8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.6	5.0*				
						RIDE		7.5	7.4	7.4	6.6	6.7	6.7	6.6	6.5	6.6	6.3	6.4	6.3	6.0	5.8				
4498211	3.371	5.879	C	(2002) 2028	0012																				
86110000	3.371	3.565	L	1	1 45	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5					
838			3	1.5	58000	RIDE		8.0	8.2	8.1	8.1	7.5	7.7	7.8	7.4	7.5	7.5	7.4	7.7	7.4					
NW 47 AVE(3.4C)					FC3																				
						CRACKING		9.5	9.5	9.5	9.5					7.0	7.0	7.0	7.0	7.2	5.5*				
						RIDE		7.5	7.3	7.5	6.9					6.4	6.0	6.2	5.8	6.0	5.6				
4498211	3.371	5.879	C	(2000) 2028	0012																				
86110000	2.707	3.371	L	1	1 45	CRACKING		7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	9.5					
838			3	4.8	53500	RIDE		8.0	7.9	7.9	7.8	7.1	7.2	7.1	6.9	7.5	7.5	7.4	7.7	7.4					
NW 55 AVE(2.8L)					FC125M																				
						CRACKING		9.5	9.5	9.5	9.5					10.0	10.0	10.0	10.0	9.7	9.0				
						RIDE		7.5	7.3	7.5	6.9					7.8	7.7	7.7	7.5	7.3	6.9				
4498211	3.371	5.879	C	(2021) 2028	0012																				
86110000	0.000	2.707	L	1	1 45	CRACKING		6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0					
838			3	4.7	29500	RIDE		6.2*	6.5	5.0*	8.0	7.5	7.4	7.2	7.1	6.8	7.0	7.1	7.1	7.0					
PLANTATION CITY LIMITS(0.0C)					FC125																				
2281171	0.000	3.156	C	2000	0012	CRACKING		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	8.3	6.5				
COMMUNITY ASPHALT CORP. (2003)					SPRIDE			6.8	7.0	6.8	6.7	6.6	6.5	6.4	6.3	6.2	6.2	6.0	5.9	5.9	5.5				
4498211	3.371	5.879	C	(2003) 2028	0012																				
86120000	0.000	3.080	R	1	1 45	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0					
810			3	3.0	41000	RIDE		8.2	7.9	8.0	8.0	7.4	7.6	7.3	7.3	7.5	7.3	7.4	7.3	7.4					
COCONUT CREEK CITY LIMIT(0.0C)					FC3																				
2274671	0.014	3.084	C	1995	0213	CRACKING		9.0	9.0	9.0	9.0	9.0	8.0	8.0	7.5	7.5	7.0	7.0	7.0	7.0	5.0*				
ODEBRECHT CONTRACTORS OF F(1999)					S	RIDE		7.3	7.1	7.3	6.9	7.1	7.1	6.9	6.9	6.9	6.8	6.8	6.6	6.7	6.3				
4476791	0.000	3.038	C	2024	0012																				
86120000	3.080	4.644	R	1	1 45	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0					
810			3	5.7	43000	RIDE			8.1	8.2	8.1	7.6	7.6	7.5	7.3	7.5	7.4	7.6	7.4	7.4					
POWERLINE RD(3.1C)					FC3																				
2280771	3.108	4.614	C	1998	0012	CRACKING		8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.5	7.0	7.0	8.0	6.5				
PAVEX CORPORATION (2001)					S	RIDE		7.4	7.4	7.4	7.4	7.6	7.5	7.7	7.5	7.2	7.3	7.3	7.4	7.4	7.0				
4498231	3.079	4.631	C	2029	0012																				
86120																									

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKMX-P		=====														
ITMSEG-P	(AGE ONE YEAR)				ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKMX-F																
86120000	5.169	6.100	R	1	1 40	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	6.5	6.5	
810			3	4.9	56000	RIDE		8.4	8.2	8.1	8.2	7.3	7.5	7.4	7.3	7.4	7.2	7.2	7.0	7.1	
NATURA BLVD(5.7R)					FC95M																
			(2020)			CRACKING		4.5*	4.5*	4.5*	4.5*	4.5*			10.0	10.0	9.0	9.0	9.0	10.0	9.0
						RIDE		7.1	7.2	7.2	7.0	7.0			7.5	7.6	7.3	7.5	7.3	7.3	6.9
86120000	6.100	6.897	R	1	1 35	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	6.5	6.5	
810			3	3.6	27500	RIDE		8.4	8.2	8.1	8.2	7.3	7.5	7.4	7.3	7.4	7.2	7.2	7.0	7.1	
SW 1 TER(6.1R)					FC95M																
4306021	5.752	6.897	R	2016	0012	CRACKING		4.5*	4.5*	4.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	10.0	9.0
GENERAL ASPHALT CO., INC.			(2020)			RIDE		7.1	7.2	7.2	7.0	7.0			6.8	6.8	6.8	6.8	6.5	6.8	6.4
86120000	6.897	7.584	R	1	1 35	CRACKING		6.5	6.5	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*			
810			2	5.7	26500	RIDE		6.8	6.3*	6.4	6.2	5.8	5.5	5.3*	5.1*	5.2*	5.3*				
FEDERAL HWY(7.0C)					DGFC																
			(2013)			CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.9	7.5
						RIDE		6.8	7.0	6.9	6.3	5.9	6.2	5.9	5.9	5.9	6.0	6.0	5.9	5.9	5.5
86120000	7.584	7.823	C	1	6 35	CRACKING		10.0	10.0	10.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5				
810			4	5.7	26500	RIDE		6.4*	7.0	6.5	6.3	5.8	4.9*								
NE 19 TER(7.8L)					DGFC																
			(2013)			CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.4	6.0*
						RIDE		7.6	7.2	7.5	6.7	6.5	6.7	6.2	6.5	6.0	6.2				
86120000	6.897	7.584	L	1	1 35	CRACKING		4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*			
810			2	5.7	26500	RIDE		6.7	5.6*	6.5	6.8	5.2*	5.1*	5.4*	4.9*	4.8*	4.4*				
FEDERAL HWY(7.0C)					DGFC																
			(2013)			CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0
						RIDE		7.3	6.7	6.8	6.4	6.2	6.6	6.3	6.0	5.9	5.8	5.9	5.7	5.7	5.3*
86120000	6.383	6.897	L	1	1 35	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	
810			3	3.6	27500	RIDE		8.2	8.1	8.1	7.8	7.3	7.3	7.0	6.5	7.4	7.3	7.1	7.0	6.9	
NE 3 AVE(6.4L)					FC95M																
4306021	5.752	6.897	L	2016	0012	CRACKING		4.5*	4.5*	4.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	10.0	9.0
GENERAL ASPHALT CO., INC.			(2020)			RIDE		6.8	6.9	6.8	6.4	6.3			7.4	7.2	7.4	7.2	7.3	7.4	7.0
86120000	4.644	6.383	L	1	1 40	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	
810			3	4.9	56000	RIDE		8.2	8.1	8.1	7.8	7.3	7.3	7.0	6.5	7.4	7.3	7.1	7.0	6.9	
LOCK RD(4.8L)					FC95M																
			(2020)			CRACKING		4.5*	4.5*	4.5*	4.5*	4.5*			10.0	10.0	10.0	10.0	9.0	8.7	8.0
						RIDE		6.8	6.9	6.8	6.4	6.3			7.3	7.2	7.2	7.1	6.7	7.2	6.8
86120000	4.218	4.644	L	1	1 40	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	
810			3	5.7	43000	RIDE			8.0	8.1	8.0	7.5	7.6	7.6	7.5	7.3	7.3	7.3	7.6	7.4	
CENTURY BLVD(4.5C)					FC3																
			(2018)			CRACKING		8.5	8.5	8.5	8.5		8.5	8.5	7.0	7.0	6.0*	6.0*	7.0	7.2	6.0*
4498231	3.079	4.631	C	2029	0012	RIDE		7.3	7.4	7.4	7.4		7.1	7.3	7.2	7.1	7.1	7.2	7.1	7.0	6.6
86120000	3.038	4.218	L	1	1 45	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	
810			3	5.7	43000	RIDE			8.0	8.1	8.0	7.5	7.6	7.6	7.5	7.3	7.3	7.3	7.6	7.4	
POWERLINE RD(3.1C)					FC3																
2280771	3.108	4.614	C	1998	0012	CRACKING		8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	4.5*
PAVEX CORPORATION			(2001)		S	RIDE		7.3	7.4	7.4	7.4	7.4	7.4	7.3	7.3	7.2	7.1	7.0	7.0	7.1	6.7
4498231	3.079	4.631	C	2029	0012																
86120000	0.000	3.038	L	1	1 45	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
810			3	3.0	41000	RIDE		8.0	8.3	8.2	8.0	7.6	7.6	7.6	7.5	7.6	7.5	7.5	7.6	7.5	
COCONUT CREEK CITY LIMIT(0.0C)					FC3																
2274671	0.014	3.084	C	1995	0213	CRACKING		10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	5.5*
ODEBRECHT CONTRACTORS OF			F(1999)		S	RIDE		7.5	7.5	7.5	7.3	7.3	7.1	7.1	7.1	6.9	6.9	7.1	6.9	6.9	6.5
4476791	0.000	3.038	C	2024	0012																
86130000	2.271	3.228	R	1	1 40	CRACKING		9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*	
849			2	8.1	13100	RIDE		8.4	8.3	8.3	8.2	7.5	7.6	7.3	7.0	7.3	7.4	7.6	7.4	7.2	
MISSING DESCRIPTION I(2.9R)					FC95																
4230061	2.278	3.175	R	2011	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.9	7.5
WEEKLEY ASPHALT PAVING, IN(2013)					SPRIDE			7.8	7.8	7.9	7.1	6.8	6.6	6.5	6.2	6.6	6.3	6.1	6.3	6.1	5.7

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																								
RDWYID	SR	US	BMP	G	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE
INTERSECT AT (MP SIDE)	AT	(MP SIDE)	W_BMP	W	EMP	RW	FY-P	W_KMX-P	ASTYPE	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
CONTRACTOR (AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	W_BMP	W	EMP	RW	FY-F	W_KMX-F			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F	ITMSEG-F		W_BMP	W	EMP	RW	FY-F	W_KMX-F																
86130000	814		3.228	3.591	R	1	7.4	45	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.0	3.5*	3.5*	7.0	6.0*	6.0*	6.0*		
					3			50000	RIDE	7.3	7.2	7.1	6.8	6.4*	6.3*	6.2	6.2	5.9	6.8	7.2	6.7	6.5		
4230021			3.228	3.525	R	2011	0012	CRACKING	6.0*	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.7	7.5	
RANGER CONSTRUCTION		INDUST(2014)						SPRIDE	6.3	7.7	7.5	7.8	7.8	7.8	7.6	7.6	7.4	7.5	7.5	7.3	7.3	7.2	6.8	
86130000	814		3.591	4.591	R	1	7.4	45	CRACKING	7.5	6.5	6.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0		
					3			50000	RIDE	7.0	7.2	7.3	7.2	6.4*	6.2*	6.3	6.2	5.9	7.7	7.4	7.3	7.4		
SW 27 AVE(3.6R)								FC95																
4035771			3.591	4.591	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.5	7.5	8.5	7.0	
COMMUNITY ASPHALT		CORP.				(2009)	SPRIDE		7.4	7.3	7.4	7.2	7.2	7.1	7.2	7.2	7.0	6.8	7.0	6.6	6.6	6.2		
4476811			3.821	4.662	R	2025	0012																	
86130000	814		4.591	4.816	R	1	7.4	45	CRACKING	7.5	6.5	6.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*	7.0	10.0	10.0	10.0		
					3			50000	RIDE	7.0	7.2	7.3	7.2	6.4*	6.2*	6.3	6.2	5.9	5.4*	8.3	8.0	7.6		
ANDREWS AVE(4.8C)								DGFC																
						(2010)	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	
								RIDE	7.4	7.0	6.7	7.3	7.1	7.0	6.4	6.4								
86130000	814		4.816	5.421	R	1	8.4	45	CRACKING	7.5	6.5	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
					3			55000	RIDE	7.0	7.2	7.3	7.2	6.4*	6.2*	7.2	7.0	7.0	6.9	7.1	6.8	6.9		
						(2006)	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.0	
								RIDE	7.2	7.2	6.8	6.7	6.9	6.8	6.8	7.2	7.1	7.2	7.1	6.8	7.1	6.7		
86130000	814		4.816	5.421	L	1	8.4	45	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
					3			55000	RIDE	7.3	7.6	7.3	7.1	6.4*	6.2*	7.7	7.4	7.6	7.5	7.5	7.6	7.6		
NW 7 AVE(5.4L)								DGFC																
						(2006)	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.2	7.5	
								RIDE	7.6	7.4	7.4	6.8	7.1	7.1	6.9	7.3	7.3	7.0	7.1	7.3	7.1	6.7		
86130000	814		4.591	4.816	L	1	7.4	45	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	7.0	10.0	10.0	10.0		
					3			50000	RIDE	7.3	7.6	7.3	7.1	6.4*	6.2*	6.0	5.6	6.4	6.6	8.3	8.2	7.8		
SIDE ROAD(4.7L)								DGFC																
						(2010)	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.4	8.0		
								RIDE	7.8	7.6	7.7	7.4	7.4	7.3	7.3	6.6	6.9	7.1	6.4	6.3	6.4	6.0		
86130000	814		3.591	4.591	L	1	7.4	45	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0		
					3			50000	RIDE	7.3	7.6	7.3	7.1	6.4*	6.2*	6.0	5.6	6.4	7.7	7.5	7.6	7.5		
NW 27 AVE(3.6L)								FC95																
4035771			3.591	4.591	C	2007	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	7.5	7.5	7.5	6.0*	
COMMUNITY ASPHALT		CORP.				(2009)	SPRIDE		7.2	7.1	7.2	6.6	6.6	6.7	6.3	6.4	6.4	6.5	6.4	6.3	6.4	6.5	6.1	
4476811			3.591	4.662	L	2025	0012																	
86130000	814		3.228	3.591	L	1	7.4	45	CRACKING	9.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*		
					3			50000	RIDE	7.5	6.9	6.6	6.7	6.1*	5.9*	6.1	5.7	5.1*	6.8	6.9	6.4	6.0		
NW 30 AVE(3.4L)								FC125																
4230021			3.228	3.525	L	2011	0012	CRACKING	6.0*	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.5	8.5	
RANGER CONSTRUCTION		INDUST(2014)						SPRIDE	5.7	7.9	8.1	7.5	7.5	7.5	7.5	7.7	7.6	7.4	6.8	6.5	6.9	7.1	6.7	
86130000	849		2.271	3.228	L	1	8.1	40	CRACKING	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*		
					2			13100	RIDE	7.8	7.9	7.9	7.7	7.3	7.3	7.5	7.3	7.7	7.4	7.3	7.3	7.4		
CR 912(2.3L)								FC95																
4230061			2.278	3.175	L	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	7.5		
WEEKLEY ASPHALT PAVING, IN(2013)								SPRIDE	7.8	7.6	7.8	7.4	7.3	7.4	7.1	7.1	7.1	7.3	6.7	7.1	7.0	6.7	6.3	
86170000	811		0.000	0.981	R	1	11.9	30	CRACKING	8.0	8.0	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0		
					1		0.0C	23500	RIDE	6.1*	5.6*	5.7	5.3*	5.3*	5.0*	4.5*	4.7*	5.0*	6.0	6.3	6.1	6.0		
FORT LAUDERDALE CITY LIM(0.0C)								FC95M																
						(2021)	CRACKING	8.5	8.5	8.5	8.0	8.0	8.0	8.0	8.0	8.0	7.0	10.0	10.0	10.0	10.0	9.2	8.5	
								RIDE	5.8	5.7	5.0*	4.9*	4.8*	4.8*	4.7*	4.4*	6.6	6.7	6.4	6.3	6.2	5.8		
86170000	811		0.981	1.800	R	1	4.2	30	CRACKING	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0		
					1			13100	RIDE	7.8		7.1	7.0	6.0	6.5	6.0	5.9	6.4	6.1	6.1	6.0	5.9		
NE 19 ST(1.0R)								FC95M																
						(2021)	CRACKING	9.0	9.0	9.0	8.0	8.0	7.0	3.5*				10.0	10.0	10.0	10.0	9.5	8.5	
								RIDE	5.8	5.7	5.7	5.4*	5.3*	5.1*	4.5*			7.3	7.3	7.1	7.1	6.8	6.4	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)	W BMP	W_EMP	RW	FY-P	WKMX-P	ASTYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)	
ITMSEG-P	CONTRACTOR (AGE ONE YEAR)	W BMP	W_EMP	RW	FY-F	WKMX-F																
86170000	1.800	2.771	R	1	1 35	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5		
811			2	2.8	19300	RIDE	7.6	7.5	7.3	7.1	6.8	6.8	6.4	6.5	6.6	6.4	6.0	6.3	6.3			
SPUR TO DIXIE HWY(1.8R)					FC125																	
4246711	1.800	2.858	C	2013	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	7.6	6.5	
COMMUNITY ASPHALT CORP.				(2016)		RIDE	6.2	6.0	5.9	6.2	6.1	5.9	5.9	5.8	5.9	5.8	5.7	5.3*	5.7	5.3*		
86170000	2.771	2.976	R	1	6 35	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	9.5	7.0	6.5	6.5		
811			2	2.3	22000	RIDE	7.6	7.5	7.3	7.1	6.8	6.8	6.4	6.5	6.6	6.9	6.8	6.6	6.6			
PARK LN E(2.8C)					FC2																	
				(2009)		CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	7.5	7.5	8.3	5.5*	
						RIDE	6.8	6.7	6.4													
86170000	2.976	5.144	R	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	8.0	7.5	6.5	6.5	6.5		
811			2	3.2	21000	RIDE	8.3	8.3	8.0	7.9	7.5	7.3	7.1	7.1	7.0	7.1	6.8	7.0	6.9			
NE 40 CT(3.0R)					FC125																	
4246711	2.864	5.440	R	2013	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.9	7.0	
COMMUNITY ASPHALT CORP.				(2016)		RIDE	6.8	6.8	6.7	7.2	6.9	6.9	6.8	6.8	6.8	6.8	6.8	6.7	6.6	6.7	6.3	
86170000	10.021	12.100	R	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0		
811			2	7.4	22500	RIDE	8.4	8.3	8.3	8.2	8.0	8.0	7.9	7.7	7.7	7.7	7.6	7.5	7.3			
SAMPLE RD(10.0C)					FC3																	
2281001	8.971	13.011	C	1995	0213	CRACKING	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.0	8.0	8.0	8.0	8.0	8.8	7.0		
TRIPLE R PAVING INC				(1999)		S RIDE	7.4	7.2	7.1	7.1	7.4	7.2	7.1	7.3	7.3	7.3	7.3	7.2	7.3	6.9		
4481742	10.057	12.112	R	2028	9924																	
86170000	12.100	13.120	R	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
811			2	5.0	13400	RIDE	8.4	8.5	8.3	8.3	7.8	7.9	7.2	7.6	7.8	7.2	7.8	7.4	7.0			
SW 10 ST(12.1C)					FC3																	
2281001	8.971	13.011	C	1995	0213	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	9.0	7.5	
TRIPLE R PAVING INC				(2000)		S RIDE	7.3	7.4	7.1	7.4	7.1	6.9	7.1	7.0	7.2	7.2	7.0	6.9	6.6	6.2		
86170000	12.100	13.120	L	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
811			2	5.0	13400	RIDE	7.6	7.9	6.9	7.7	7.3	7.3	7.1	6.8	7.0	6.6	7.8	7.4	7.0			
SW 10 ST(12.1C)					FC3																	
2281001	8.971	13.011	C	1995	0213	CRACKING	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	5.5*		
TRIPLE R PAVING INC				(2000)		S RIDE	7.3	7.4	7.1	7.4	7.1	6.9	7.1	7.0	7.2	6.3	6.1	6.4	5.9	5.5		
86170000	10.021	12.100	L	1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0		
811			2	7.4	22500	RIDE	8.4	8.4	8.3	8.2	7.7	7.5	7.7	7.1	7.4	7.0	7.6	7.5	7.3			
SAMPLE RD(10.0C)					FC3																	
2281001	8.971	13.011	C	1995	0213	CRACKING	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.0	8.0	7.0	7.0	7.0	7.0	5.0*		
TRIPLE R PAVING INC				(1999)		S RIDE	7.4	7.2	7.1	7.1	7.4	7.2	7.2	7.1	7.3	6.9	6.9	7.1	6.9	6.5		
86170000	2.976	5.144	L	1	1 40	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5		
811			2	3.2	21000	RIDE	7.6	7.6	7.6	7.2	6.9	6.9	6.7	6.4	6.9	6.8	6.8	6.8	7.0	6.9		
NE 39 DR(3.0L)					FC125																	
4246711	2.864	5.440	L	2013	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.2	7.0	
COMMUNITY ASPHALT CORP.				(2016)		RIDE	6.8	6.8	6.7	7.2	6.9	6.9	6.8	6.8	6.8	6.8	6.5	6.5	6.3	6.4	6.0	
86170000	2.771	2.976	L	1	1 35	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	9.5	7.0	6.5	6.5		
811			2	2.3	22000	RIDE	7.2	7.3	7.0	6.9	6.4	6.2	6.1	6.0	6.6	6.9	6.8	6.6	6.6			
NE 37 ST(2.8L)					DGFC																	
				(2022)		CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	9.0	9.0	9.0	8.8	8.0	
						RIDE	6.8	6.7	6.4								4.6*	4.4*	4.7*	4.8*	4.4*	
86170000	1.800	2.771	L	1	1 35	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5		
811			2	2.8	19300	RIDE	7.2	7.3	7.0	6.9	6.4	6.2	6.1	6.0	6.6	6.4	6.0	6.3	6.3			
WILTON DR/NE 26 ST(1.8C)					FC125																	
4246711	1.800	2.858	C	2013	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.0	
COMMUNITY ASPHALT CORP.				(2016)		RIDE	6.2	6.0	5.9	6.2	6.1	5.9	5.9	5.8	5.9	5.9	5.9	5.9	5.6	5.9	5.5	
86170000	0.981	1.800	L	1	1 30	CRACKING	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0		
811			1	4.2	13100	RIDE	7.4		7.1	7.0	6.5	6.4	6.3	6.1	6.7	6.3	6.1	6.0	5.9			
NE 20 ST(1.1L)					FC95M																	
				(2021)		CRACKING	9.0	9.0	9.0	8.0	8.0	7.0	3.5*		10.0	10.0	10.0	10.0	9.1	8.5		
						RIDE	5.8	5.7	5.7	5.4*	5.3*	5.1*	4.5*		7.3	7.0	6.9	6.7	6.6	6.2		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

							DISTRICT = 4				COUNTY = BROWARD														
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR															FUTURE		
SR US	G_BMP	G_EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012					
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-X-P	ASTYPE	=====																		
ITMSEG-P	(AGE ONE YEAR)							2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)				
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKM-X-F																				
86170000	0.000	0.981	L 1	1 30	CRACKING			9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0					
811			1 11.9	23500	RIDE			5.6*	5.8*	5.8	5.6	5.3*	5.3*	5.0*	5.0*	4.6*	6.0	6.3	6.1	6.0					
FORT LAUDERDALE CITY LIM(0.0C)				FC95M																					
			(2021)		CRACKING			8.5	8.5	8.5	8.0	8.0	8.0	8.0	7.0	10.0	10.0	10.0	10.0	9.2	8.5				
					RIDE			5.8	5.7	5.0*	4.9*	4.8*	4.8*	4.7*	4.4*	6.6	6.9	6.5	6.8	6.8	6.4				
86180000	0.000	0.336	R 1	1 35	CRACKING			9.5	9.5	9.5	9.5	8.5	7.0	6.5	4.5*	10.0	10.0	10.0	10.0	10.0					
A1A			3 4.6	44000	RIDE			7.1	7.2	6.9	6.6	6.1	6.6	6.1	6.0	7.1	6.9	6.9	6.6	6.7					
FEDERAL HWY(0.0C)				DGFC																					
			(2008)		CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	6.0*				
			C 2031	0012	RIDE			6.8	6.9	6.7	5.7	5.6	6.0	5.3*	5.2*	5.5	5.4*	5.7	5.2*	5.1*	4.7*				
4498251	0.000	1.636	C 2031	0012																					
86180000	0.336	0.754	R 1	1 35	CRACKING			9.5	9.5	9.5	9.5	8.5	7.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*					
A1A			3 4.6	44000	RIDE			7.1	7.2	6.9	6.6	6.1	6.6	6.1	6.0	6.0	6.1	6.1	6.1	5.8					
HARBOR SHOPS(0.4R)				FC95																					
4230071	0.330	0.678	C 2012	0012	CRACKING			4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.5				
WEEKLEY ASPHALT PAVING, IN(2014)				SPRIDE				6.0	7.5	7.4	7.1	6.9	7.3	6.7	6.7	6.5	6.6	6.5	6.2	6.4	6.0				
4498251	0.000	1.636	C 2031	0012																					
86180000	0.754	0.912	R 1	6 35	CRACKING						9.5	8.5	7.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*					
A1A			3 3.5	33500	RIDE						6.6	6.1	6.6	6.1	6.0	6.0	6.1	6.1	6.1	5.8					
EISENHOWER BLVD(0.8C)				DGFC																					
			(2014)		CRACKING			4.5*	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	6.5	6.5	6.5	5.8*	4.5*				
			C 2031	0012	RIDE			6.0																	
4498251	0.000	1.636	C 2031	0012																					
86180000	1.290	1.535	R 1	6 35	CRACKING						10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5					
A1A			2 3.5	33500	RIDE						7.0	6.5	6.4	6.3	6.3	6.2	6.3	6.4	6.6	6.6					
HARBOUR INLET(1.4C)				FC125																					
			(2003)		CRACKING			9.0	7.5	7.5	7.5	7.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	7.0	5.5*				
			C 2031	0012	RIDE			6.4	6.6	6.4	5.5	5.5	5.1*	5.4*	5.3*	5.3*	4.8*	4.4*							
4498251	0.000	1.636	C 2031	0012																					
86180000	1.535	2.535	R 1	1 30	CRACKING			3.5*	3.5*	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5					
A1A			2 3.5	33500	RIDE			6.1*	5.6*	6.7	6.8	6.2	6.1	4.1*	5.4*	5.2*	5.3*	5.4*	5.4*	5.1*					
SPUR(1.6R)				FC95A																					
4306011	1.501	2.360	R 2016	0012	CRACKING			8.5	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.5				
WEEKLEY ASPHALT PAVING, IN(2018)					RIDE			5.1*	5.1*	5.1*	4.4*	4.6*	7.1	7.0	6.7	6.8	6.7	6.7	6.5	6.5	6.1				
86180000	2.535	2.964	C 1	1 30	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0					
A1A			2 2.0	13500	RIDE			6.0*	6.4*	6.5	6.8	5.9	6.1	4.1*	5.8	5.7	6.1	5.7	5.4*	5.5					
BAHIA MAR(2.5L)				FC2																					
4306011	2.535	2.960	C 2016	0012	CRACKING			9.0	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5				
WEEKLEY ASPHALT PAVING, IN(2018)					RIDE			5.6	5.5	5.5	5.7	5.5	6.9	6.3	6.2	6.3	6.7	6.2	6.6	6.6	6.4				
86180000	1.535	2.535	L 1	1 30	CRACKING			3.5*	3.5*	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.0	7.0					
A1A			2 3.5	33500	RIDE			5.9*	6.0*	7.2	7.1	6.5	6.5	6.3	6.4	6.1	6.2	6.2	6.0	6.0					
HASKINS AVE(1.6L)				FC95A																					
4306011	1.501	2.360	L 2016	0012	CRACKING			7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.0				
WEEKLEY ASPHALT PAVING, IN(2018)					RIDE			5.8	6.1	5.8	5.4*	5.2*	7.4	7.1	6.9	6.9	6.4	6.5	6.6	6.1	5.7				
86180000	1.290	1.535	L 1	2 35	CRACKING						10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0					
A1A			2 3.5	33500	RIDE						8.0	6.9	7.0	6.9	6.6	7.1	6.8	7.2	7.3	7.2					
HARBOUR INLET(1.4C)				FC125																					
			(2003)		CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	7.4	6.0*				
			C 2031	0012	RIDE			7.1	7.0	7.1	6.1	6.2	6.1	6.3	5.7	6.3	5.5	5.1*	5.2*	4.6*	4.2*				
4498251	0.000	1.636	C 2031	0012																					
86180000	0.754	0.912	L 1	6 35	CRACKING						9.5	8.5	7.0	7.0	6.5	6.5	6.5	6.5	4.5*	4.5*					
A1A			3 3.5	33500	RIDE						7.0	6.6	6.6	6.4	6.0	6.3	6.3	7.0	5.8	6.0					
EISENHOWER BLVD(0.8C)				DGFC																					
			(2014)		CRACKING			4.5*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.1*	5.0*				
			C 2031	0012	RIDE			5.2*																	
4498251	0.000	1.636	C 2031	0012																					
86180000	0.336	0.754	L 1	1 35	CRACKING			9.5	9.5	9.5	9.5	8.5	7.0	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*					
A1A			3 4.6	44000	RIDE			7.5	7.5	6.6	7.0	6.6	6.6	6.4	6.0	6.3	6.3	6.3	7.0	5.8	6.0				
CORDOVA RD(0.4L)				FC95																					
4230071	0.330	0.678	C 2012	0012	CRACKING			4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.5	7.5	7.5	7.5	6.5				
WEEKLEY ASPHALT PAVING, IN(2014)				SPRIDE				5.2*	7.3	6.5	6.5	6.7	6.0	5.9	5.8	5.8	5.7	5.7	5.6	5.7	5.3*				
4498251	0.000	1.636	C 2031	0012																					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																									
RDWYID	SR	US	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR															FUTURE
INTERSECT AT (MP SIDE)	AT	MP SIDE)	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P	ASTYPE				2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)		
CONTRACTOR (AGE ONE YEAR)	W BMP	W EMP	RW	FY-F	WKM-X-F																				
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																				
86180000	0.000	0.336	L	1	6 35	CRACKING				9.5	9.5	9.5	9.5	8.5	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0			
A1A			3	4.6	44000	RIDE				7.5	7.5	6.6	7.0	6.6	6.6	6.4	6.0	7.6	7.2	7.5	7.2	6.8			
FEDERAL HWY(0.0C)					DGFC																				
				(2008)		CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0	5.5*		
4498251	0.000	1.636	C	2031	0012	RIDE				7.3	7.3	7.0													
86190000	2.384	3.700	R	1	1 45	CRACKING				9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0			
823			3	3.8	51000	RIDE				8.2	8.2	8.2	8.1	7.3	7.4	7.1	7.3	7.4	7.2	7.7	7.7	7.7			
MIRAMAR CITY LIMITS(2.5C)					FC95																				
4138341	2.384	3.669	R	2008	0012	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.5	9.0	7.5		
WEEKLEY ASPHALT PAVING, IN(2010)					SPRIDE					7.7	7.6	7.7	7.4	7.5	7.5	7.4	7.3	7.3	7.2	7.3	7.3	7.1	6.7		
4476801	2.385	3.502	R	2025	0012																				
86190000	3.700	7.599	R	1	1 45	CRACKING				9.0	9.0	9.0	9.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	4.5*			
823			3	3.1	38500	RIDE				8.5	8.5	8.4	8.3	7.7	7.7	7.6	7.5	7.5	7.5	7.5	7.4				
TAFT ST(4.5C)					FC95																				
4216701	3.700	7.599	C	2011	0012	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0		
WEEKLEY ASPHALT PAVING, IN(2013)					SPRIDE					8.1	8.1	8.2	8.0	7.9	8.0	7.9	7.9	7.9	7.9	7.9	7.8	7.8	7.4		
86190000	7.599	10.897	R	1	1 50	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	6.5	6.5	6.5			
823			3	2.6	32500	RIDE				8.7	8.7	8.5	8.5	8.0	8.0	8.0	7.8	7.8	7.7	7.9	7.8	7.6			
DAYSTAR(7.9R)					FC95A																				
4270121	7.599	10.833	R	2016	0012	CRACKING				6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
COMMUNITY ASPHALT CORP. (2018)					SPRIDE					7.5	7.4	7.8	7.9	7.9	8.7	8.6	8.6	8.6	8.6	8.6	8.5	8.5	8.1		
86190000	7.599	10.897	L	1	1 50	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	6.5	6.5			
823			3	2.6	32500	RIDE				8.7	8.7	8.5	8.4	8.1	8.1	8.0	7.9	7.7	7.8	7.9	7.8	7.7			
SW 38 ST(7.9L)					FC95A																				
4270121	7.599	10.833	L	2016	0012	CRACKING				6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
COMMUNITY ASPHALT CORP. (2018)					SPRIDE					7.5	7.4	7.8	7.8	7.8	8.5	8.4	8.4	8.4	8.3	8.4	8.3	8.3	7.9		
86190000	3.700	7.599	L	1	1 45	CRACKING				9.0	9.0	9.0	9.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	4.5*			
823			3	3.1	38500	RIDE				8.5	8.5	8.4	8.4	7.7	7.7	7.6	7.5	7.5	7.4	7.4	7.3				
TAFT ST(4.5C)					FC95																				
4216701	3.700	7.599	C	2011	0012	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0		
WEEKLEY ASPHALT PAVING, IN(2013)					SPRIDE					8.0	8.0	8.1	7.9	7.9	7.9	7.9	7.9	7.8	7.9	7.9	7.8	7.8	7.4		
86190000	2.384	3.700	L	1	1 45	CRACKING				10.0	10.0	7.5	6.5	6.5	6.5	6.5	7.0	6.5	6.5	10.0	10.0	10.0			
823			3	3.8	51000	RIDE				8.1	8.1	8.1	8.0	7.3	7.5	7.1	7.1	7.2	7.2	7.5	7.5	7.5			
MIRAMAR CITY LIMITS(2.5C)					FC95																				
4138341	2.384	3.669	L	2008	0012	CRACKING				10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	5.5*		
WEEKLEY ASPHALT PAVING, IN(2010)					SPRIDE					7.5	7.4	7.5	7.4	7.3	7.4	7.4	7.3	7.3	7.3	7.3	7.2	7.4	7.0		
86190500	0.000	1.925	R	1	1 45	CRACKING				6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0			
823			3	5.0	40500	RIDE				8.6	8.4	8.5	8.4	7.7	7.6	7.5	7.4	7.1	8.4	8.6	8.5	8.4			
DADE CO LINE/BR# 550(0.0C)					FC95																				
4138371	0.000	2.032	C	2008	0012	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0		
COMMUNITY ASPHALT CORP. (2009)					SPRIDE					8.4	8.4	8.4	7.9	7.8	7.9	7.8	7.9	7.7	7.8	7.7	7.6	7.6	7.2		
86190500	0.000	1.925	L	1	1 45	CRACKING				6.5	6.5	6.5	6.5	6.5	6.5	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0			
823			3	5.0	40500	RIDE				8.5	8.4	8.5	8.2	7.5	7.5	7.4	7.3	7.1	8.6	8.2	8.2	8.1			
DADE CO LINE/BR# 550(0.0C)					FC95																				
4138371	0.000	2.032	C	2008	0012	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.7	8.5		
COMMUNITY ASPHALT CORP. (2009)					SPRIDE					8.2	8.1	8.1	7.7	7.6	7.6	7.6	7.6	7.3	7.2	7.2	7.3	7.1	6.7		
86200000	0.000	2.166	R	1	1 40	CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	6.5			
858			2	8.3	42500	RIDE				8.1	8.2	8.1	7.7	7.0	6.6	7.1	6.8	6.9	7.0	6.5	6.9	6.8			
SR 7(0.0C)					FC125M																				
4287331	0.220	2.166	C	2017	0012	CRACKING				6.5	6.5	6.5	6.5	6.5	3.5*		10.0	10.0	10.0	10.0	10.0	9.3	8.5		
COMMUNITY ASPHALT CORP. (2020)					SPRIDE					6.6	6.9	6.6	7.1	6.9	6.7		6.7	6.8	6.7	6.8	6.6	6.6	6.2		
86200000	2.166	3.707	R	1	1 40	CRACKING				9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0			
858			3	2.8	56918	RIDE				6.1*	6.1*	6.3	6.0	5.4*	5.2*	5.3*	4.9*	5.6	5.4*	7.0	6.9	6.5			
HOLIDAY PARK(2.2C)					FC95																				
4137911	2.407	3.707	R	2008	0012	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.7	7.5		
WEEKLEY ASPHALT PAVING, IN(2010)					SPRIDE					6.7	6.5	6.7	6.3	6.2	6.2	6.1	6.0	5.9	5.7	5.7	5.4*	5.7	5.3*		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKM-F	ASTYPE	=====	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-P	W BMP	W EMP	RW	FY-F	WKM-F	ASTYPE	=====														
CONTRACTOR (AGE ONE YEAR)	W BMP	W EMP	RW	FY-F	WKM-F	ASTYPE	=====														
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F	ASTYPE	=====														
86200000 858 SE 2 AVE(3.7R)	3.707	5.000	R 1	1 35	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	
2281591 COMMUNITY ASPHALT CORP.	4.008	5.000	C 2004	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*
4484131	3.707	5.429	C 2030	0012	SPRIDE	5.8	5.7	5.8	5.5	5.3*	5.1*	5.0*	5.1*	5.0*	5.1*	4.9*	5.0*	4.8*	4.9*	5.1*	4.7*
86200000 858 DIANA DR(5.2R)	5.000	5.429	R 1	6 35	CRACKING							10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
			3 7.7	33000	RIDE	7.0	6.6	6.5	5.9	6.6	6.2	6.3	6.6	6.3	6.6	6.4					
				FC95	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0
				(2004)	RIDE	6.5	6.6	6.6	6.0	6.0	6.3	6.2	5.7	5.7	5.7	5.3*					
4484131	3.707	5.429	C 2030	0012	SPRIDE																
86200000 858 THREE ISLANDS BLVD(5.0L)	5.000	5.429	L 1	6 35	CRACKING							10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
			3 7.7	33000	RIDE	6.5	6.1	5.7	6.1	5.9	6.0	6.2	6.1	5.7							
				FC95	CRACKING	9.5	9.5	9.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*
				(2004)	RIDE	6.0	6.0	5.9	5.5	5.5	5.7	5.1*	5.1*	5.0*	5.0*	4.7*	4.4*				
4484131	3.707	5.429	C 2030	0012	SPRIDE																
86200000 858 NE 2 AVE(3.7L)	3.707	5.000	L 1	1 35	CRACKING	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	
2281591 COMMUNITY ASPHALT CORP.	4.008	5.000	C 2004	0012	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*
4484131	3.707	5.429	C 2030	0012	SPRIDE	6.4	6.7	6.7	5.9	6.0	5.8	5.6	5.6	5.7	5.5	5.5	5.5	5.3*	5.6	5.2*	
86200000 858 HOLIDAY PARK(2.2C)	2.166	3.707	L 1	1 40	CRACKING	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	
4137911 WEEKLEY ASPHALT PAVING, IN	2.407	3.707	L 2008	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.9	7.5
			(2010)	SPRIDE	6.5	6.6	6.5	6.6	6.4	6.5	6.0	6.2	6.3	6.3	6.3	6.2	6.0	6.3	6.3	6.3	5.9
86200000 858 SR 7(0.0C)	0.000	2.166	L 1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	6.5	6.5	6.5	
4287331 COMMUNITY ASPHALT CORP.	0.220	2.166	C 2017	0012	CRACKING	6.5	6.5	6.5	6.5	6.5	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5
			(2020)	SPRIDE	7.3	7.0	7.2	7.1	7.1	6.4	6.2	7.3	7.1	7.1	7.1	7.1	7.1	7.0	7.0	7.0	6.6
86210000 736 SR 7(0.0C)	0.000	1.720	R 1	1 40	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5				10.0	10.0	10.0	10.0	
			2 7.1	26000	RIDE	7.0	7.7	7.8	7.8	7.0	7.2	6.6	6.4				6.6	6.6	6.5	6.5	
				DGFC	CRACKING	10.0	10.0	10.0	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*
				(2010)	RIDE	6.2	6.2	6.4	6.0	5.8	5.9	5.8	5.7	5.7	5.6	5.6	5.7	5.5	5.6	5.6	5.2*
4484141	0.000	1.720	C 2030	0012	SPRIDE																
86210000 736	1.720	2.350	R 1	1 40	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5				10.0	10.0	10.0	10.0	
			2 13.8	43000	RIDE	7.7	7.1	6.9	7.1	6.0	6.5	5.6	5.8				8.0	8.2	8.1	8.1	
				FC125	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.5	8.0	
				(2010)	RIDE	8.1	8.2	8.1	8.0	7.3	8.1	8.0	7.9	7.7	7.7	7.7	7.7	7.3	7.4	7.0	
86210000 736 SEVENTEENTH AVE SW R(2.4R)	2.350	2.698	R 1	6 40	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5				9.5	9.0	9.0	9.0	
4339671 GENERAL ASPHALT CO., INC.	2.355	2.620	C 2014	0226	CRACKING	9.0	9.0	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0
			(2016)	RIDE	4.3*	4.6*	4.4*														
86210000 736 NINTH AVE SW(3.0C)	2.698	4.033	R 1	1 35	CRACKING	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*			10.0	10.0	10.0	10.0	
2281801 WEEKLEY ASPHALT PAVING, IN	2.698	4.033	C 2007	0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.2	7.0
			(2009)	SPRIDE	6.1	6.5	6.6	5.9	5.7	5.5	5.2*	5.3*	5.3*	5.3*	5.3*	5.4*	5.2*	5.1*	5.2*	5.2*	4.8*
86210000 736 NINTH AVE SW(3.0C)	2.698	4.033	L 1	1 35	CRACKING	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*			10.0	10.0	10.0	10.0	
2281801 WEEKLEY ASPHALT PAVING, IN	2.698	4.033	C 2007	0012	CRACKING	9.5	9.5	9.5	8.5	8.5	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.5	6.0*
			(2009)	SPRIDE	6.3	6.3	6.3	5.6	5.6	5.4*	5.0*	5.3*	5.2*	5.0*	5.1*	5.2*	5.1*	5.2*	5.1*	4.7*	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR														FUTURE
SR US	G BMP	G EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKMX-P		=====															
ITMSEG-P	(AGE ONE YEAR)				ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)	
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKMX-F																	
86210000	2.350	2.698	L 2	13.8	6 40	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0				9.0	9.0	9.0		
736					43000	RIDE	7.5	8.1	8.3	7.3	6.8	6.0	6.5	7.1				4.9*	4.7*	4.9*		
SIXTEENTH AVE SW	L(2.4L)				DGFC																	
4339671	2.355	2.620	C 2014	0226	CRACKING	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.9	8.0	
GENERAL ASPHALT CO., INC.	(2016)				RIDE	4.7*	4.6*	4.6*														
86210000	1.720	2.350	L 2	13.8	1 40	CRACKING	10.0	10.0	10.0	8.5	7.0	7.0	7.0	6.5				10.0	10.0	10.0		
736					43000	RIDE	7.4	7.5	7.7	7.4	6.4	5.8	6.2	6.3				7.9	7.6	7.7		
SW 22 TERR(1.8L)					FC125																	
			(2010)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.7	7.5		
					RIDE	7.7	7.7	7.5	7.5	7.5	7.5	7.5	7.4	7.2	7.1	7.0	7.0	7.0	7.1	6.7		
86210000	0.000	1.720	L 2	7.1	1 40	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0				10.0	10.0	10.0		
736					26000	RIDE	7.8	8.0	7.6	7.3	7.1	6.3	6.5	6.2				6.1	6.1	6.0		
SR 7(0.0C)					DGFC																	
			(2010)		CRACKING	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.0	8.0	7.0	6.5*	6.5*	6.5*	6.5*	7.4*	6.0*	
					RIDE	5.8	5.7	5.8	5.6	5.7	5.7	5.5	5.6	5.3*	5.3*	5.2*	5.2*	5.1*	4.7*			
4484141	0.000	1.720	C 2030	0012																		
86220000	0.000	1.600	R 3	1 3.8	8 45	CRACKING	9.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0		
817					45000	RIDE	7.1	6.9		7.9	7.1	7.1	7.0	7.0	7.1	7.0	7.0	7.0	7.1	6.9		
MIRAMAR PKWY(0.7C)					FC125																	
2280781	0.000	1.340	C 2000	0012	CRACKING	9.0	8.5	8.5	8.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0				
WEEKLEY ASPHALT PAVING, IN	(2003)				S RIDE	6.9	7.0	7.5	6.8	6.9	6.6	6.6	6.6	6.6	6.8	6.7	6.9					
86220000	1.600	2.432	R 3	1 3.2	1 45	CRACKING	9.0	9.0	9.0	9.0	9.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
817					55000	RIDE	7.1	6.9	7.0	6.8	6.6	6.5	8.1	7.6	7.8	7.7	7.7	7.6	7.6			
MISSING DESCRIPTION I(2.1R)					FC125																	
4062781	1.347	2.572	C 2003	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.1	5.5*		
PAVEX CORPORATION	(2006)				SPRIDE	7.5	7.5	7.6	7.2	7.2	7.1	7.1	6.9	6.9	7.0	6.8	6.9	6.9	6.9	6.5		
86220000	2.432	6.468	R 3	1 3.8	1 45	CRACKING	9.0	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0		
817					50500	RIDE	7.5	7.7	7.6	7.6	6.8	7.0	6.9	6.9	6.7	6.6	6.8	8.1	8.0			
PINES BLVD(2.6C)					FC125																	
4137961	2.432	6.394	C 2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	8.4	7.0		
COMMUNITY ASPHALT CORP.	(2011)				SPRIDE	7.9	7.8	7.7	7.5	7.5	7.4	7.4	7.3	7.1	7.1	7.1	7.1	7.1	7.0	6.6		
86220000	6.468	8.035	R 3	1 3.3	1 45	CRACKING	10.0	10.0	9.0	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		
817					45500	RIDE	7.8	7.9	7.8	7.7	7.5	7.3	7.2	7.2	7.1	7.1	7.1	7.0	6.8			
ORANGE DR(6.5R)					FC125																	
4216721	6.468	7.744	C 2011	0012	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.1	6.0*		
GENERAL ASPHALT CO., INC.	(2013)				SPRIDE	8.4	8.2	8.3	7.8	7.5	7.4	7.4	7.3	7.4	7.2	7.4	7.2	7.1	6.8	6.4		
86220000	8.035	8.456	R 3	1 7.8	1 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	1.0*	10.0	10.0	10.0	10.0	10.0	7.5	7.5		
817					63000	RIDE	7.8	8.0	8.1	7.9	7.6	7.6	7.4	7.3	7.5	7.6	7.6	7.4	7.4			
NOVA DR(8.2R)					FC125																	
			(2017)		CRACKING	7.5	7.5	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
					RIDE	7.3	6.8	7.4		8.1	8.2	8.1	8.2	8.1	7.9	8.2	7.7	7.9	7.5			
86220000	8.456	10.276	R 3	1 3.1	8 45	CRACKING	2.0*	1.0*	1.0*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0		
817					50500	RIDE	7.4	7.4	7.4	7.2	6.5	6.5		7.3	7.3	7.3	7.3	7.3	7.0			
S 1900 BLOCK(8.7C)					FC125																	
2280791	8.851	10.270	C 2004	0012	CRACKING	9.0	8.5	8.5	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5			
PAVEX CORPORATION	(2007)				SPRIDE	7.2	6.9	7.3	6.7	6.8	6.9	6.7	6.6	6.6	6.7	6.6	6.7	6.5	6.5			
86220000	10.276	13.262	R 3	1 5.8	1 45	CRACKING	2.0*	2.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
817					50000	RIDE	7.3	7.2	6.8		7.8	7.8	7.7	7.5	7.7	7.8	7.7	7.7	7.7			
BROWARD BLVD(10.3R)					FC125																	
2280801	10.205	13.537	C 2001	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.6	7.0		
COMMUNITY ASPHALT CORP.	(2004)				SPRIDE	7.6	7.6	7.7	6.9	6.9	6.9	6.8	6.8	6.8	6.8	6.8	6.9	6.8	6.8	6.4		
86220000	13.262	15.614	R 3	1 1.7	1 45	CRACKING	9.0	9.0	8.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	10.0	10.0		
817					60500	RIDE	7.9	7.8	7.9	7.7	7.2	7.2	7.1	7.0	6.8	7.0	7.0	7.1	7.9	7.9		
NW 30 PL(13.4R)					DGFC																	
			(2021)		CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	9.0	
					RIDE	7.9	7.8	7.8	7.4	7.5	7.3	7.3	7.3	7.3	7.6	7.6	7.5	7.6	7.5	7.1		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD

RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	%T	AADT	RATINGS		2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)							=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-F	ASTYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
CONTRACTOR (AGE ONE YEAR)																					(PMRS)	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F																	
86220000	15.614	18.000	R	1	1	45	CRACKING	8.5	8.5	6.5	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0		
817			3	4.7	52000	RIDE		7.5	7.5	7.4	7.1	6.8	6.8	6.6	6.5	6.7	6.7	6.6	7.9	7.9		
NW 58 ST(15.7C)					FC95																	
4153221	13.408	18.002	C	2009	0012	CRACKING		10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	8.0	6.5	
GENERAL ASPHALT CO., INC.				(2011)	SPRIDE			7.9	7.8	7.8	7.4	7.5	7.3	7.3	7.3	7.5	7.5	7.5	7.5	7.4	7.0	
86220000	18.000	21.003	R	1	2	45	CRACKING	9.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0		
817			3	17.7	39000	RIDE		7.8	7.7	7.6	7.5	6.7	6.4*	6.3	5.8	6.0	6.2	8.0	7.8	7.8		
SW 1 CT(18.1R)					FC125																	
4137971	18.000	21.003	C	2008	0012	CRACKING		10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.8	7.5	
PAVEX CORPORATION				(2010)	SPRIDE			7.7	7.7	7.8	7.3	7.4	7.4	7.3	7.2	7.1	7.2	6.9	7.1	7.1	6.7	
86220000	18.002	21.003	L	1	2	45	CRACKING	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0		
817			3	17.7	39000	RIDE		6.6	6.5	6.3*	6.8	6.1*	6.0*	5.7	5.1*	5.6	5.2*	7.8	7.7	7.5		
FIRST CT SW(18.1L)					FC125																	
4137971	18.000	21.003	C	2008	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.8	7.5	
PAVEX CORPORATION				(2010)	SPRIDE			7.5	7.4	7.5	7.0	7.1	7.2	7.0	6.9	6.8	6.8	6.5	6.7	6.8	6.4	
86220000	15.614	18.002	L	1	1	45	CRACKING	7.5	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0		
817			3	4.7	52000	RIDE		7.4	7.6	7.5	7.4	6.7	6.7	6.5	6.4	6.6	6.4	6.5	8.1	8.0		
NW 58 ST(15.7C)					FC95																	
4153221	13.408	18.002	C	2009	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.2	8.0	
GENERAL ASPHALT CO., INC.				(2011)	SPRIDE			7.9	7.9	7.9	7.5	7.5	7.4	7.3	7.3	7.3	7.3	7.3	7.3	7.1	6.7	
86220000	13.262	15.614	L	1	1	45	CRACKING	9.0	9.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5	6.5	10.0	10.0		
817			3	1.7	60500	RIDE		6.6	6.7	6.7	6.7	6.4*	6.1*	6.2	6.0	6.1	6.2	6.3	8.1	8.0		
OAKLAND PARK(13.6L)					DGFC																	
				(2021)	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	
					RIDE			7.9	7.9	7.9	7.5	7.5	7.4	7.3	7.3	7.3	7.2	7.3	7.3	7.2	6.8	
86220000	10.276	13.262	L	1	1	45	CRACKING	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
817			3	5.8	50000	RIDE		6.8	6.8	6.6		7.7	7.7	7.7	7.6	7.7	7.5	7.6	7.6	7.5		
BROWARD BLVD(10.3L)					FC125																	
2280801	10.205	13.537	C	2001	0012	CRACKING		9.0	9.0	8.5	8.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	8.0	8.3	6.5	
COMMUNITY ASPHALT CORP.				(2004)	SPRIDE			7.4	7.4	7.5	6.8	6.8	6.8	6.7	6.7	6.7	6.7	6.6	6.5	6.4	6.0	
86220000	8.397	10.276	L	1	8	45	CRACKING	4.5*	4.5*	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	9.0		
817			3	3.1	50500	RIDE		6.9	6.9	6.9	6.7	6.1*	6.1*		7.1	7.0	7.1	7.0	7.1	6.9		
VALENCIA DR(8.5L)					FC125																	
2280791	8.851	10.270	C	2004	0012	CRACKING		9.0	8.5	8.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.6		
PAVEX CORPORATION				(2007)	SPRIDE			7.0	6.8	7.3	6.7	6.8	6.8	6.5	6.6	6.6	6.5	6.5	6.7	6.6		
86220000	8.114	8.397	L	1	1	45	CRACKING	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5		
817			3	7.8	63000	RIDE		7.1	7.3	7.3	7.2	7.0	7.1	6.9	6.9	7.0	7.0	7.0	6.9	6.9		
EARL MORRALL PASS(8.2L)					FC125																	
				(2017)	CRACKING			8.5	8.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.5	
					RIDE			7.0	7.0	7.1		7.6	7.0	6.6	7.3	7.2	6.9	7.3	7.4	7.3	6.9	
86220000	6.468	8.114	L	1	1	45	CRACKING	9.0	9.0	7.5	7.5	7.5	7.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*		
817			3	3.3	45500	RIDE		7.1	7.5	7.3	7.0	6.6	6.6	6.5	6.2	6.3	6.5	6.3	6.3	6.3		
ORANGE DR(6.5L)					FC125																	
4216721	6.468	7.744	C	2011	0012	CRACKING		10.0	10.0	9.0	9.0	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	7.3	6.0*	
GENERAL ASPHALT CO., INC.				(2013)	SPRIDE			8.0	7.9	7.9	7.9	7.5	7.4	7.5	7.4	7.2	7.2	7.2	7.1	7.2	6.8	
86220000	2.432	6.468	L	1	1	45	CRACKING	9.0	9.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0		
817			3	3.8	50500	RIDE		7.5	7.3	7.2	7.3	6.8	6.6	6.4	6.7	6.6	6.6	6.9	8.3	8.1		
PINES BLVD(2.6C)					FC125																	
4137961	2.432	6.394	C	2008	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.9	7.5	
COMMUNITY ASPHALT CORP.				(2011)	SPRIDE			7.9	7.9	7.9	7.6	7.6	7.6	7.5	7.4	7.4	7.4	7.3	7.3	7.2	6.8	
86220000	1.600	2.432	L	1	1	45	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
817			3	3.2	55000	RIDE		6.4*	6.2*	6.2*	6.4*	5.9*	5.6*	8.0	7.6	7.7	7.7	7.7	7.7	7.5		
HOWARD FOREMAN(2.1L)					FC125																	
4062781	1.347	2.572	C	2003	0012	CRACKING		10.0	9.0	9.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.5	6.0*	
PAVEX CORPORATION				(2006)	SPRIDE			7.5	7.6	7.5	7.3	7.2	6.9	7.1	7.1	7.0	7.0	7.0	6.9	6.9	6.5	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																									
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE	
INTERSECT	AT	(MP)	(SIDE)							=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P																				
CONTRACTOR	(AGE ONE YEAR)				ASTYPE						2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																				
86230000	2.524	3.021	L	1	35	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	4.5*	4.5*		
822			3	4.3	45000	RIDE					8.1	8.1	5.6	8.0	7.1	7.0	7.1	6.4	6.9	7.1	7.0	6.9	6.6		
N 29 AVE(2.7C)					FC125																				
4246741	2.524	3.015	C	2013	0012	CRACKING					4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5	
RANGER CONSTRUCTION INDUST				(2016)		SPRIDE					6.2	6.4	6.1	7.5	7.3	7.0	7.2	7.1	7.2	7.1	7.0	6.7	7.1	6.7	
86230000	0.000	2.524	L	1	40	CRACKING					9.0	7.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0		
822			3	4.1	47000	RIDE					7.9	7.8	7.6	7.7	7.0	7.1	6.8	6.8	6.7	6.8	6.7	6.7	8.1		
HOLLYWOOD CITY LIMITS(0.0C)					FC95																				
4168831	0.022	2.679	C	2010	0012	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.0	
GENERAL ASPHALT CO., INC. (2012)						SPRIDE					8.0	8.0	8.1	7.7	7.8	7.7	7.6	7.6	7.4	7.5	7.5	7.4	7.5	7.1	
86470000	0.000	0.576	R	5	1	65	CRACKING				7.5	7.5	7.5	7.5	6.5	7.5	7.5	7.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	
91	3.3	3.9	3	9.3	148897	RIDE					7.8	8.7	8.6	8.6	7.9	7.9	7.6	7.6	7.5	7.3	7.2	7.8	7.9		
HEFT(0.4R)					FC5M																				
4379901	0.000	0.465	R	2022	0012	CRACKING					10.0	10.0		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	10.0	10.0	9.0	
RANGER CONSTRUCTION INDUST				(2024)		SPRIDE					7.8	7.8		8.1	8.2	8.2	8.1	8.0	8.1	8.2	8.2	8.4	8.3	8.2	
86470000	0.576	2.590	R	5	1	65	CRACKING				6.5		10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	6.5	4.5*	10.0		
91	48.0	50.0	3	9.3	148897	RIDE					8.4		8.7	8.7	8.1	8.0	8.0	7.9	7.8	7.7	7.6	7.6	7.7		
4060958	0.749	2.590	C	2011	0226	CRACKING					10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	4.5*	3.5*	4.5*	5.5*	3.0*	
COMMUNITY ASPHALT CORP. (2012)						SPRIDE					7.9	7.8	7.8	8.0	7.9	7.9	7.8	7.6	7.9	7.9	7.7	7.7	7.5	7.4	
4462231	0.000	3.500	C	2024	0548																				
86470000	2.590	3.163	R	5	1	65	CRACKING				4.5*		10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	6.5	4.5*	10.0		
91	50.0	50.6	3	9.3	148897	RIDE					8.4		8.7	8.7	8.1	8.0	8.0	7.9	7.8	7.7	7.6	7.6	7.4		
					FC5M																				
4462231	0.000	3.500	C	2024	0548						10.0	10.0	9.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	6.5	7.2	5.0*	
						CRACKING					7.5	7.8	8.1	8.2	8.1	8.1	8.0	7.9	7.9	8.0	7.7	7.8	7.8	7.7	
86470000	3.163	6.924	R	5	1	65	CRACKING				4.5*		10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	6.5	4.5*			
91	50.6	54.4	3	9.3	154800	RIDE					8.4		8.7	8.7	8.1	8.0	8.0	7.9	7.8	7.7	7.6	7.6			
4060958	3.163	6.924	R	2011	0226	CRACKING					10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	4.5*	3.5*	4.5*	5.5*	3.5*	
COMMUNITY ASPHALT CORP. (2013)						SPRIDE					8.0	7.9	7.6	8.1	8.0	8.0	7.9	7.9	8.0	8.0	7.9	7.8	7.8	7.7	
4462241	3.500	7.000	C	2024	0548																				
86470000	6.924	9.450	R	5	1	65	CRACKING				4.5*		10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	6.5	4.5*			
91	54.4	56.9	4	13.6	158200	RIDE					8.4		8.7	8.7	8.1	8.0	8.0	7.9	7.8	7.7	7.6	7.6			
					FC5M																				
4513641	7.000	10.101	C	2026	0012									10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	5.5*	3.5*	
						CRACKING								8.4	8.4	8.4	8.3	8.3	8.3	8.3	8.3	8.3	8.2	8.1	
86470000	9.450	10.115	R	5	1	65	CRACKING				9.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0				10.0		
91	56.9	57.5	4	13.6	159000	RIDE					8.7	8.5	8.5	8.5	7.7	7.7	7.7	7.7	7.6				7.9		
4060944	9.500	12.530	R	2009	0213	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	
COMMUNITY ASPHALT CORP. (2012)						SPRIDE					8.1	8.0	8.0	8.0	8.0	8.0	7.9	7.8	8.1	8.0	8.1	8.1	8.0	7.9	
4513641	7.000	10.101	C	2026	0012																				
86470000	10.115	11.189	R	5	7	65	CRACKING				9.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0				10.0		
91	57.5	58.6	4	13.6	159000	RIDE					8.7	8.5	8.5	8.5	7.7	7.7	7.7	7.7	7.6				7.9		
4420611	10.099	11.175	R	2023	0012	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0		10.0	9.0	
GENERAL ASPHALT CO., INC. (2025)						SPRIDE					8.1	8.0	8.0	8.0	8.0	8.0	7.9	7.8	8.1	8.0	8.1		8.1	8.0	
86470000	11.189	11.862	R	5	1	65	CRACKING				9.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0				10.0		
91	58.6	59.3	4	13.6	159000	RIDE					8.7	8.5	8.5	8.5	7.7	7.7	7.7	7.7	7.6				7.9		
					FC5M																				
						CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	10.0	10.0	10.0	10.0	9.8	8.5	
						RIDE					8.1	8.0	8.0	8.0	8.0	8.0	7.9	7.8	8.4	8.6	8.3	8.3	8.3	8.2	
86470000	11.862	16.762	R	5	7	65	CRACKING				7.5	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0						
91	59.3	64.2	4	13.6	147800	RIDE					8.5	8.4	8.4	7.7	7.7	7.7	7.7	7.7	7.6						
4420611	11.845	15.007	R	2023	0012	CRACKING							10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	10.0	9.0
GENERAL ASPHALT CO., INC. (2025)						SPRIDE							7.9	7.8	7.8	7.8	7.7	7.9	8.1	8.1	8.1	7.8	7.8	8.4	8.3

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

ALL SYSTEM PAVEMENT CONDITION FORECAST

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD

RDWYID	SR	US	BMP	G	BMP	G	EMP	LN	RW	SYS	TYP	SPD	DISTRESS	RATINGS	SURVEYED YEAR												FUTURE	
INTERSECT	AT	(MP)	(SIDE)																									
ITMSEG-P	W	BMP	W	EMP	RW	FY-P	WKMX-P	ASTYPE																				
CONTRACTOR	(AGE ONE YEAR)														2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
ITMSEG-F	W	BMP	W	EMP	RW	FY-F	WKMX-F																				(PMRS)	
86470000 91	16.762 64.2	17.480 64.9	R 4	5 13.6	1 129500	65 OGFC	CRACKING RIDE	10.0 8.2	10.0 8.2	9.0 8.2	9.0 8.1	6.5 7.1	4.5* 6.9	4.5* 7.4	3.5* 7.0	3.5* 7.2	3.5* 7.2											
				(2022)			CRACKING RIDE		10.0 7.9	10.0 7.8	10.0 7.8	10.0 7.8	9.0 7.8	9.0 7.7	9.0 7.9		10.0 8.4	10.0 8.2	10.0 8.4	9.7 8.4	8.5 8.3							
86470000 91	17.480 64.9	18.012 65.4	R 4	5 13.6	7 129500	65 FC5M	CRACKING RIDE	9.0 8.2	6.5 8.2	6.5 8.1	6.5 8.1	6.5 7.6	4.5* 6.9	4.5* 7.4	3.5* 7.0	3.5* 7.2	3.5* 7.2											
4420611 GENERAL	17.499 ASPHALT	18.001 CO., INC.	R 2023 (2025)		0012		CRACKING SPRIDE		10.0 7.9	10.0 7.8	10.0 7.8	10.0 7.8	9.0 7.8	9.0 7.7	9.0 7.9	9.0 8.1	9.0 8.2	7.5 8.0	6.5 8.0	10.0 8.2	9.0 8.1							
86470000 91	18.012 65.4	18.934 66.4	R 4	5 13.6	1 129500	65 FC5M	CRACKING RIDE	9.0 8.2	6.5 8.2	6.5 8.1	6.5 8.1	6.5 7.6	4.5* 6.9	4.5* 7.4	3.5* 7.0	3.5* 7.2	3.5* 7.2											
4060974 RUSSELL 4460241	12.484 ENGINEERING, INC	18.934 23.811	R 2010 (2014) C 2023		0213 0012		CRACKING SPRIDE		10.0 7.9	10.0 7.8	10.0 7.8	10.0 7.8	9.0 7.8	9.0 7.7	9.0 7.9	9.0 8.1	9.0 8.2	7.5 8.0	6.5 8.0	8.2 8.0	6.0* 7.9							
86470000 91	18.934 66.4	25.912 73.3	R 3	5 13.6	1 101300	65 FC5	CRACKING RIDE	10.0 8.5	8.5 8.5	8.5 8.4	6.5 8.4	6.5 8.0	6.5 7.9	6.5 7.8	6.5 7.8	6.5 7.7	6.5 7.7	6.5 7.7	6.5 7.6	6.5 7.6								
4061505 COMMUNITY 4460241	18.660 ASPHALT	25.912 23.811	R 2012 (2014) C 2023		0226 0012		CRACKING SPRIDE		10.0 8.2	10.0 8.2	10.0 8.3	10.0 8.3	10.0 8.3	10.0 8.2	10.0 8.1	10.0 8.2	9.0 8.2	7.5 8.2	6.5 8.1	7.0 8.1	5.0* 8.0							
86470000 91	18.774 66.2	25.912 73.3	L 3	5 13.6	8 101300	65 FC226	CRACKING RIDE	9.0 8.2	7.5 8.2	7.5 8.2	7.5 8.2	7.0 7.6	6.0* 7.4	6.0* 7.4	6.0* 7.3	6.0* 7.3	6.0* 7.2	6.0* 7.2	6.0* 7.2	6.0* 7.1								
4061505 COMMUNITY 4460241	18.960 ASPHALT	25.912 23.811	L 2012 (2014) C 2023		0226 0012		CRACKING SPRIDE		10.0 8.1	10.0 8.2	10.0 8.2	10.0 8.2	10.0 8.2	7.5 8.1	6.5 8.0	6.5 8.1	4.5* 8.1	4.5* 8.0	4.5* 8.0									
86470000 91	16.360 63.8	18.774 66.2	L 4	5 13.6	1 129500	65 OGFC	CRACKING RIDE	7.5 8.1	7.5 8.2	6.5 8.1	6.5 8.1	4.5* 7.6	4.5* 7.6	4.5* 7.4	4.5* 7.4	4.5* 7.1			10.0 8.0									
				(2022)			CRACKING RIDE	10.0 7.7	10.0 7.6	10.0 7.8	9.0 7.9	9.0 7.9	9.0 7.9	7.5 7.8			10.0 8.2	10.0 8.1	10.0 8.2	9.3 8.1	8.0 8.0							
86470000 91	11.816 59.2	16.360 63.8	L 4	5 13.6	7 147800	65 FC5	CRACKING RIDE	6.5 8.4	6.5 8.4	4.5* 8.4	4.5* 8.3	10.0 7.9	10.0 7.9	10.0 7.8	10.0 7.9	10.0 7.6			10.0 7.8									
4420611 GENERAL	11.845 ASPHALT	16.321 CO., INC.	L 2023 (2025)		0012		CRACKING SPRIDE	10.0 7.7	10.0 7.6	10.0 7.8	9.0 7.9	9.0 7.9	9.0 7.9	7.5 7.8	6.5 7.6	6.5 7.9	4.5* 7.9	4.5* 7.7	3.5* 7.1	10.0 8.5	9.0 8.4							
86470000 91	10.950 58.4	11.816 59.2	L 4	5 13.6	1 159000	65 FC5M	CRACKING RIDE	4.5* 8.6	4.5* 8.6	4.5* 8.5	3.5* 8.5	10.0 7.9	10.0 7.9	10.0 7.8	10.0 7.9	10.0 7.6			10.0 7.8									
				(2021)			CRACKING RIDE		10.0 8.0	10.0 8.1	10.0 8.1	10.0 8.1	10.0 8.0	9.0 7.9	7.5 7.9	10.0 8.6	10.0 8.5	10.0 8.5	10.0 8.5	9.5 8.5	8.0 8.4							
86470000 91	10.068 57.5	10.950 58.4	L 4	5 13.6	7 159000	65 FC5	CRACKING RIDE	4.5* 8.6	4.5* 8.6	4.5* 8.5	3.5* 8.5	10.0 7.9	10.0 7.9	10.0 7.8	10.0 7.9	10.0 7.6			10.0 7.8									
4420611 GENERAL	10.099 ASPHALT	11.023 CO., INC.	L 2023 (2025)		0012		CRACKING SPRIDE		10.0 8.0	10.0 8.1	10.0 8.1	10.0 8.1	10.0 8.0	9.0 7.9	7.5 7.9	7.5 8.2	7.5 8.2	7.5 8.2	6.5 8.2	10.0 8.3	9.0 8.2							
86470000 91	6.899 54.3	10.068 57.5	L 4	5 13.6	1 158200	65 FC5M	CRACKING RIDE	4.5* 8.1		10.0 8.8	10.0 8.8	10.0 8.2	10.0 8.1	10.0 8.1	10.0 8.0	10.0 7.9			10.0 8.1									
				(2015)			CRACKING RIDE			10.0 8.3	10.0 8.4	10.0 8.3	10.0 8.3	10.0 8.3	10.0 8.3	10.0 8.4			9.0 8.3	7.5 8.3	5.5* 8.2							
4513641	7.000	10.101	C 2026		0012																							
86470000 91	5.711 53.1	6.899 54.3	L 4	5 9.3	1 154800	65 FC5	CRACKING RIDE	4.5* 8.1		10.0 8.8	10.0 8.8	10.0 8.2	10.0 8.1	10.0 8.1	10.0 8.0	10.0 7.9			10.0 8.1									
				(2015)			CRACKING RIDE			10.0 8.0	10.0 7.9	10.0 7.8	9.0 7.8	9.0 7.8	7.5 7.7	7.5 7.9	7.5 8.1	7.5 8.0	7.5 7.9	8.3 8.1	6.0* 8.0							
4462241	3.500	7.000	C 2024		0548																							

```

**" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```

ALL SYSTEM PAVEMENT CONDITION FORECAST

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD

RDWYID SR	US AT	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													FUTURE
		G_BMP	G_EMP	LN	%T	AADT		RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
		(MP)	(SIDE)					=====														
		ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P															
CONTRACTOR	(AGE ONE YEAR)				FY-F	WKMX-F			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F																						
86470000 91		3.375 50.8	5.711 53.1	L 3	5 9.3	1 154800	65 FC5M	CRACKING RIDE	4.5* 8.4		10.0 8.8	10.0 8.8	10.0 8.2	10.0 8.1	10.0 8.1	10.0 8.0	10.0 7.9	7.0 7.7	6.5 7.7	4.5* 7.6		
4060958 COMMUNITY 4462241		3.163 3.500	5.711 7.000	L C	2011 (2013) 2024	0226 SPRIDE	0548	CRACKING RIDE	10.0 8.2	10.0 8.2	10.0 8.2	9.0 8.3	9.0 8.2	9.0 8.2	6.5 8.1	4.5* 7.9	3.5* 8.2	1.0* 8.1	1.0* 8.0	1.0* 8.0	4.5* 7.8	2.5* 7.7
86470000 91		2.590 50.0	3.375 50.8	L 4	5 9.3	1 154800	65 FC5M	CRACKING RIDE	4.5* 8.4		10.0 8.8	10.0 8.8	10.0 8.2	10.0 8.1	10.0 8.1	10.0 8.0	10.0 7.9	7.0 7.7	6.5 7.7	4.5* 7.6		
4462231		0.000	3.500		(2016) C 2024		0548	CRACKING RIDE				10.0 8.1	10.0 8.1	10.0 8.0	9.0 7.9	7.5 7.9	7.5 8.0	6.5 8.0	6.5 7.9	6.5 7.9	7.0 7.7	5.0* 7.6
86470000 91		0.576 48.0	2.590 50.0	L 3	5 9.3	1 148897	65 FC5M	CRACKING RIDE	4.5* 8.4		10.0 8.8	10.0 8.8	10.0 8.2	10.0 8.1	10.0 8.1	10.0 8.0	10.0 7.9	7.0 7.7	6.5 7.7	4.5* 7.6		
4060958 COMMUNITY 4462231		0.749 0.000	2.590 3.500	C C	2011 (2013) 2024	0226 SPRIDE	0548	CRACKING RIDE	10.0 8.2	10.0 8.2	10.0 8.1	9.0 8.2	9.0 8.1	9.0 8.0	7.5 7.9	6.5 7.9	6.5 8.0	4.5* 8.0	3.5* 7.9	3.5* 7.9	5.0* 7.8	3.0* 7.7
86470000 91		0.000 3.3	0.576 3.9	L 3	5 9.3	1 148897	65 FC5M	CRACKING RIDE	9.0 8.7	9.0 8.7	9.0 8.6	9.0 8.6	9.0 7.9	9.0 7.8	7.5 7.8	7.5 7.7	6.5 7.6	4.5* 7.6	4.5* 7.4	4.5* 8.1	10.0 8.1	10.0 8.0
4379901 RANGER CONSTRUCTION	0.000 INDUST(	0.000 0.439	0.439 L	2022 (2024)		0012 SPRIDE		CRACKING RIDE	10.0 8.2	10.0 8.2	10.0 8.1	10.0 8.2	10.0 8.2	10.0 8.2	10.0 8.2	9.0 8.2	9.0 8.3	7.5 8.3	7.5 8.3	10.0 8.2	10.0 8.1	9.0 8.0
86471000 821		0.000 40.2	5.811 46.0	R 4	5 5.7	1 97600	70 FC5M	CRACKING RIDE	10.0 8.7	10.0 8.7	10.0 8.7	10.0 8.6	8.5 8.3	8.5 8.2	8.5 8.2	8.5 8.1	8.5 8.2	7.0 7.9	7.0 8.1	10.0 8.1	10.0 8.1	10.0 8.2
					(2023)			CRACKING RIDE	10.0 8.4	10.0 8.3	10.0 8.3	10.0 8.5	9.0 8.5	9.0 8.5	7.5 8.4	7.5 8.3			10.0 8.2	10.0 8.2	9.5 8.2	8.0 8.1
86471000 821		5.811 46.0	6.818 47.0	R 3	5 5.7	1 84100	70 FC5M	CRACKING RIDE	8.5 8.3	8.5 8.1	6.5 7.9	6.5 7.8	6.5 7.8		10.0 8.0	10.0 8.1	10.0 8.1	10.0 8.1	9.0 8.1	9.0 7.9	9.0 8.1	9.0 8.1
					(2023)			CRACKING RIDE	9.0 8.1	9.0 8.1	9.0 8.1	9.0 8.2	9.0 8.1	9.0 8.1	9.0 8.0			10.0 8.0	10.0 8.1	9.0 8.1	7.5 8.0	
86471000 821		6.818 47.0	7.149 47.3	R 2	5 5.7	7 84100	70 FC5M	CRACKING RIDE	10.0 7.8	10.0 7.8	10.0 7.7	10.0 7.7	10.0 7.3	10.0 7.5	10.0 7.0	10.0 6.7	10.0 6.8	10.0 6.9	9.0 7.0	9.0 7.1		
					(2025)			CRACKING RIDE	10.0 7.8	10.0 7.6	10.0 7.8	10.0 7.6	10.0 7.6	10.0 7.6	10.0 7.5	10.0 7.4	10.0 7.4	9.0 7.4	9.0 7.5		10.0 8.4	9.0 8.3
86471000 821		7.149 47.3	7.706 47.9	R 1	5 5.7	7 84100	70 HFST	CRACKING RIDE	10.0 7.8	10.0 7.8	10.0 7.7	10.0 7.7	10.0 7.3	10.0 7.5	10.0 7.0	10.0 6.7	10.0 6.8	10.0 6.9	9.0 7.0	9.0 7.1		
FL TPK(7.7C)					(2025)			CRACKING RIDE	10.0 7.4	10.0 7.2	10.0 7.0	10.0 7.8	10.0 7.7	10.0 7.9	10.0 7.6	10.0 7.3	10.0 7.4	9.0 7.3	9.0 7.3		10.0 7.7	9.0 7.6
86471000 821		7.207 47.4	7.706 47.9	L 2	5 5.7	7 84100	70 FC5M	CRACKING RIDE	10.0 7.8	10.0 7.9	10.0 8.3	10.0 7.9	10.0 6.7	10.0 7.7	10.0 7.1	10.0 6.9	10.0 7.2	10.0 7.2	7.5 7.2	7.0 7.4		
					(2025)			CRACKING RIDE	10.0 8.0	10.0 7.8	10.0 8.0	10.0 7.7	10.0 7.9	10.0 7.5	9.0 7.8	9.0 7.4	9.0 7.6	9.0 7.4	9.0 7.6		10.0 7.7	9.0 7.6
86471000 821		6.973 47.1	7.207 47.4	L 2	5 5.7	7 84100	70 FC5M	CRACKING RIDE	10.0 7.8	10.0 7.9	10.0 8.3	10.0 7.9	10.0 6.7	10.0 7.7	10.0 7.1	10.0 6.9	10.0 7.2	10.0 7.2	7.5 7.2	7.0 7.4		
					(2025)			CRACKING RIDE	10.0 7.2	10.0 7.2	10.0 7.3	10.0 7.6	10.0 7.4	9.0 7.8	9.0 7.2			9.0 7.4		10.0 8.0	9.0 7.9	
86471000 821		6.102 46.3	6.973 47.1	L 3	5 5.7	1 84100	70 FC5M	CRACKING RIDE	10.0 7.8	10.0 7.9	10.0 8.3	10.0 7.9	10.0 6.7	10.0 7.7	10.0 7.1	10.0 6.9	10.0 7.2	10.0 7.2	7.5 7.2	7.0 7.4		
					(2023)			CRACKING RIDE	10.0 7.2	10.0 7.2	10.0 7.3	10.0 7.6	10.0 7.4	9.0 7.8	9.0 7.2				10.0 8.2	10.0 8.1	9.3 8.0	8.0 7.9

```

**" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```


FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 4 COUNTY = BROWARD																								
RDWYID	SR	US	G_BMP	EMP LN	RW LN	SYS %T	TYP AADT	SPD	DISTRESS RATINGS	SURVEYED YEAR														FUTURE
INTERSECT AT (MP SIDE)	W_BMP	W_EMP LN	W_RW LN	W_FY-P	W_KMX-P	W_ASTYP	W_FY-F	W_KMX-F	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2030 (PMRS)
86471000 821	0.000 40.2	6.102 46.3	L 4	5 5.7	1 5.7	70 97600	CRACKING RIDE	FC5M		10.0 8.8	10.0 8.8	10.0 8.8	10.0 8.8	8.5 8.5	8.5 8.5	8.5 8.3	8.5 8.4	8.5 8.3	8.5 8.4	8.5 8.3		10.0 8.4		
					(2023)		CRACKING RIDE			10.0 8.4	10.0 8.3	10.0 8.4	9.0 8.6	9.0 8.5	9.0 8.5	9.0 8.4	9.0 8.4			10.0 8.4	10.0 8.4	10.0 8.4	8.5 8.3	
86472000 869	0.000 0.0	1.774 1.8	R 3	5 6.6	1 6.6	65 116000	CRACKING RIDE	FC5M		9.0 7.5	9.0 7.7	7.0 7.7	9.0 8.2			10.0 7.4	10.0 7.3	10.0 7.3	10.0 7.4	10.0 7.3	10.0 7.3	10.0 7.2		
BEGIN SECTION(0.0C)																								
2323521 BERGERON LAND DEVELOPMENT, (2006)	0.000 0.500	8.173 4.100	C C	2002 2025	0218 0213	CRACKING SPRIDE				10.0 7.2	10.0 7.3	10.0 8.1	10.0 8.3	10.0 8.3	10.0 8.2	10.0 8.2	10.0 8.3	10.0 8.3	10.0 8.3	10.0 8.2	10.0 8.2	9.0 8.2	6.0* 8.1	
86472000 869	1.774 1.8	2.187 2.2	R 3	5 6.6	1 6.6	65 104200	CRACKING RIDE	FC5		7.0 8.2	7.0 8.2	6.5 8.3	6.5 7.7			10.0 7.4	10.0 7.3	10.0 7.3		10.0 7.7	10.0 7.5	10.0 7.6		
					(2010)		CRACKING RIDE			10.0 7.6	10.0 7.6	10.0 7.5	10.0 7.6	10.0 7.6	10.0 7.3	10.0 7.5	10.0 7.6	9.0 7.6	7.5 7.6	7.5 7.1	7.5 7.1	7.3 7.1	5.0* 7.0	
4371551	0.500	4.100	C	2025	0213																			
86472000 869	2.187 2.2	8.174 8.2	R 3	5 6.6	1 6.6	65 94800	CRACKING RIDE	FC5M		10.0 8.5	10.0 8.6	10.0 8.6	10.0 8.5			10.0 7.9	10.0 7.9	10.0 7.9	10.0 8.0	9.0 8.1	9.0 7.9	9.0 7.9		
4310893 THE DE MOYA GROUP INC. (2015)	2.852 4.100	8.174 7.500	C C	2013 2026	0012 0213	CRACKING SPRIDE				9.0 7.9	9.0 7.8	10.0 8.4	10.0 8.1	10.0 8.1	10.0 8.0	10.0 8.0	9.0 8.0	9.0 8.2	9.0 8.2	9.0 8.2	9.0 8.2	7.5 8.1	5.5* 8.0	
86472000 869	8.174 8.2	14.000 14.0	R 3	5 6.6	1 6.6	65 71100	CRACKING RIDE	FC5M		6.5 7.7	10.0 8.7	10.0 8.7	10.0 8.6	10.0 8.0	9.0 8.0	9.0 8.0	9.0 8.0		10.0 7.9	10.0 8.0	10.0 7.9	10.0 8.0		
4061471	8.000	14.000	C	2006 (2009)	0213	CRACKING RIDE				10.0 8.0	10.0 7.9	9.0 8.0	9.0 8.2	9.0 8.2	9.0 8.0	9.0 8.1	9.0 8.0	9.0 8.2	9.0 8.2	7.5 8.2	7.5 8.2	7.5 8.1	5.0* 8.0	
4354611	9.000	12.000	C	2024	0213																			
86472000 869	14.000 14.0	19.665 19.7	R 3	5 6.6	1 6.6	65 90400	CRACKING RIDE	FC5		6.5 8.2	10.0 8.7	10.0 8.7	10.0 8.6	10.0 8.0	9.0 8.0	9.0 8.0			10.0 8.1	10.0 8.1	10.0 8.0	10.0 8.1		
4061531	14.000	21.800	C	2005 (2009)	0213	CRACKING RIDE				10.0 8.1	10.0 8.1	10.0 8.2	9.0 8.4	9.0 8.4	9.0 8.1	9.0 8.3	9.0 8.3	9.0 8.4	9.0 8.4	9.0 8.3	9.0 8.4	8.2 8.3	5.5* 8.2	
4354615	14.800	18.400	C	2027	0213																			
86472000 869	19.665 19.7	21.835 21.8	R 3	5 6.6	1 6.6	65 43900	CRACKING RIDE	FC5		9.0 8.1	10.0 8.3	10.0 8.3	9.0 8.0	9.0 7.7	9.0 7.5	9.0 7.5	9.0 7.3			10.0 7.4	10.0 7.5	10.0 7.5		
WATERWAYS BLVD(21.3R)																								
4061531	14.000	21.800	C	2005 (2010)	0213	CRACKING RIDE				10.0 7.5	10.0 7.5	9.0 7.5	9.0 7.4	6.5 7.3	6.5 7.3	6.5 7.3	6.5 7.1	6.5 7.2	6.5 7.4	6.5 7.1	6.5 7.1	6.2* 7.1	3.5* 7.0	
4372241	18.000	21.000	C	2030	0213																			
86472000 869	21.248 21.2	21.835 21.8	L 3	5 6.6	1 6.6	45 43900	CRACKING RIDE	FC3		9.0 7.9	10.0 8.1	10.0 8.4	10.0 8.3	10.0 7.5	10.0 7.5	10.0 7.5	10.0 7.6		10.0 7.3	10.0 7.3	10.0 7.2	10.0 7.3		
C/L OF POWERLINE RD(21.8C)																								
4061531	14.000	21.800	C	2005 (2009)	0213	CRACKING RIDE				10.0 7.3	10.0 7.2	9.0 7.2	9.0 7.1	9.0 7.3	9.0 7.1	9.0 7.0	9.0 6.9	9.0 6.6	9.0 6.9	9.0 7.0	9.0 7.0	8.4 6.9	6.0* 6.8	
86472000 869	19.665 19.7	21.248 21.2	L 2	5 6.6	1 6.6	65 92800	CRACKING RIDE	FC5		9.0 7.9	10.0 8.1	10.0 8.4	10.0 8.3	10.0 7.5	10.0 7.5	10.0 7.5				10.0 7.8	10.0 7.8			
4061531	14.000	21.800	C	2005 (2011)	0213	CRACKING RIDE				10.0 7.8	10.0 7.7	10.0 7.9	10.0 7.8	10.0 7.8	10.0 7.8	10.0 7.7	10.0 7.7	10.0 7.7	9.0 7.8	9.0 7.7	9.0 7.7	7.3 7.7	5.0* 7.6	
4372241	18.000	21.000	C	2030	0213																			
86472000 869	14.000 14.0	19.665 19.7	L 3	5 6.6	1 6.6	65 90400	CRACKING RIDE	FC5		6.5 8.1	10.0 8.5	10.0 8.5	10.0 8.5	10.0 7.9	10.0 7.9	9.0 7.8			10.0 8.0	10.0 8.0	10.0 7.9	10.0 8.0		
4061531	14.000	21.800	C	2005 (2009)	0213	CRACKING RIDE				10.0 8.0	10.0 8.0	9.0 8.1	9.0 8.3	9.0 8.3	9.0 8.3	9.0 8.2	9.0 8.2	9.0 8.4	9.0 8.4	9.0 8.3	9.0 8.3	8.2 8.3	5.5* 8.2	
4354615	14.800	18.400	C	2027	0213																			
86472000 869	8.174 8.2	14.000 14.0	L 3	5 6.6	1 6.6	65 71100	CRACKING RIDE	FC5M		6.5 8.1	10.0 8.5	10.0 8.5	10.0 8.5	10.0 7.9	10.0 7.9	9.0 7.8				10.0 8.0	10.0 8.0	10.0 8.0		
4061471	8.000	14.000	C	2006 (2010)	0213	CRACKING RIDE				10.0 8.0	10.0 8.0	10.0 8.1	10.0 8.2	10.0 8.2	9.0 8.2	9.0 8.1	9.0 8.1	9.0 8.2	9.0 8.3	9.0 8.2	9.0 8.2	8.2 7.5	5.5* 7.4	
4354611	9.000	12.000	C	2024	0213																			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2026 - 2031, EXTRACTED ON 08/28/2025**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

-----								DISTRICT = 4			COUNTY = BROWARD			-----											
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR															FUTURE		
SR US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012					
INTERSECT AT (MP SIDE)																									
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P																				
CONTRACTOR (AGE ONE YEAR)					ASTYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030				
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																(PMRS)				
86472000	2.224	8.174	L	5	2	65	CRACKING	6.5	6.5	4.5*	3.5*			10.0	10.0	9.0	9.0	9.0	9.0	9.0					
869	2.2	8.2	3	6.6	94800	RIDE		8.1	8.1	8.1	8.0			7.6	7.6	7.6	7.6	7.6	7.6	7.5					
4310893	2.852	8.174	C	2013	0012	FC5M	CRACKING	9.0	6.5		10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	5.5*				
THE DE MOYA GROUP INC.				(2016)	SPRIDE			7.4	7.4		7.9	8.0	8.0	7.9	7.9	8.0	8.0	8.0	8.0	7.5	7.4				
4371556	4.100	7.500	C	2026	0213																				
86472000	1.609	2.224	L	5	1	65	CRACKING	7.0	7.0	7.0	7.0			10.0	10.0	10.0		10.0	10.0	10.0					
869	1.6	2.2	3	6.6	104200	RIDE		8.3	7.7	8.1	7.9			7.4	7.4	7.4		7.7	7.7	7.7					
					FC5		CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.2	4.5*				
				(2010)	RIDE			7.7	7.7	7.7	7.8	7.8	7.7	7.7	7.7	7.5	7.6	7.3	7.4	7.4	7.3				
4371551	0.500	4.100	C	2025	0213																				
86472000	0.000	1.609	L	5	1	65	CRACKING	9.0	6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0					
869	0.0	1.6	3	6.6	116000	RIDE		8.2	8.2	8.1	8.0			7.4	7.4	7.4	7.6	7.5	7.2	7.1					
BEGIN SECTION(0.0C)					FC5M																				
4310891	0.570	1.505	L	2012	0012	FC5M	CRACKING	10.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.0				
RANGER CONSTRUCTION INDUST(2015)					RIDE			7.1	7.1	8.5	8.3	8.3	8.4	8.3	8.3	8.5	8.4	8.4	8.4	8.4	8.3				
4371551	0.500	4.100	C	2025	0213																				

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).