FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 4 COUNTY = INDIAN RIVER ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
88003000	0.000	0.715	R	1	2	45	CRACKING	7.5	7.5			10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0	7.0															
656			2	3.4	11200		RIDE	6.1*	5.8*			7.0	6.8	7.3	7.1	7.1	7.0	7.0	6.7	6.8															
SR 5(0.0C)					FC125M																														
4305932	0.000	0.716	C	2017		0012	CRACKING	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	8.9	10.0	9.0														
COMMUNITY ASPHALT CORP.				(2020)			SPRIDE	6.8	6.6	6.2	6.3	6.1		7.5	7.4	7.3	7.9	7.8	7.4	6.8	6.5														
88003000	1.611	1.978	R	1	1	45	CRACKING	9.0	9.0			10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0															
656			2	6.0	1400		RIDE	5.1*	5.2*			6.8	6.6	6.9	6.8	6.7	6.4	6.7	6.6	6.6															
INDIAN BAY DR(1.7R)					FC125																														
2286071	0.000	1.971	C	2002		0012	CRACKING	9.0	9.0	9.0	8.0	8.0	8.0	7.0	6.0*	6.0*	6.0*	6.0*	6.7	5.9*	4.5*														
COMMUNITY ASPHALT CORP.				(2005)			SPRIDE	6.7	6.5	5.9	5.7	5.5	5.5	5.2*	5.2*	5.2*	5.2*	5.2*	5.0*	5.1*	4.8*														
88003000	1.612	1.978	L	1	1	45	CRACKING	7.5	7.5			10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0															
656			2	6.0	1400		RIDE	5.1*	5.2*			7.0	6.1	6.7	6.6	6.6	6.7	6.7	6.3	6.5															
SR A1A(2.0C)					FC125																														
2286071	0.000	1.971	C	2002		0012	CRACKING	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	5.5*		6.0*	6.0*	5.4*	5.1*	3.5*															
COMMUNITY ASPHALT CORP.				(2005)			SPRIDE	6.3	6.3	6.1	5.5	5.3*	5.3*	5.2*	5.1*		5.1*	5.0*	5.4*	5.1*	4.8*															
88003000	0.000	0.709	L	1	2	45	CRACKING	6.5	6.5			10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0	7.0															
656			2	3.4	11200		RIDE	6.3*	6.3*			7.5	7.3	7.5	7.4	7.0	7.0	7.1	6.6	6.5															
SR 5(0.0C)					FC125M																														
4305932	0.000	0.716	C	2017		0012	CRACKING	7.0	7.0	7.0	6.5	6.5		10.0	10.0	10.0	10.0	10.0	8.8	8.5	7.5														
COMMUNITY ASPHALT CORP.				(2020)			SPRIDE	6.6	6.4	6.2	6.2	5.9		7.2	7.2	7.5	7.7	7.5	7.0	7.5	7.2														
88010000	0.000	1.615	R	1	1	50	CRACKING	4.0*	3.5*	3.5*	3.5*	4.0*	3.5*	3.5*	1.0*	1.0*	1.0*	1.0*	1.0*	1.0*															
5	1		3	5.4	30500		RIDE	8.6	8.4	8.2	7.2	7.2	6.8	7.1	7.1	7.4	7.2	6.9	6.9	6.7															
21 ST SE(0.4R)					FC5																														
2285834	0.427	1.829	C	2012		0213	CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.1	9.0	7.0														
				(2017)			RIDE				7.8	7.7	7.5	7.5	7.4	7.5	7.5	7.1	7.4	7.6	7.5														
88010000	1.615	3.550	R	1	1	45	CRACKING	4.0*	3.5*	3.5*	3.5*	4.0*	3.5*	3.5*	1.0*	1.0*			10.0	10.0															
5	1		3	4.5	35500		RIDE	8.6	8.4	8.2	7.2	7.2	6.8	7.1	7.1	7.4			8.7	8.4															
RIVERSIDE DR(1.7R)					FC95																														
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	10.0	9.5	9.0														
				(2025)			RIDE	8.4	8.4	8.3	8.1	8.2	8.2	8.2	8.1	8.1	8.1	8.1	8.0	7.9	7.6														
88010000	3.550	4.058	R	1	1	45	CRACKING	10.0	9.5	9.5	9.5	9.5			10.0	10.0	10.0	10.0	10.0	10.0															
5	1		3	4.6	22000		RIDE	8.4	8.1	8.0	7.5	7.6			8.3	8.2	8.3	8.2	8.1	8.1															
VISTA GARDENS(3.6R)					FC95																														
2285833	3.432	4.071	C	2005		0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.0	7.9	6.5														
SHELTRA & SON CONST. CO.			I	(2008)			SPRIDE	7.9	8.0	7.9	7.6	7.6	7.7	7.7	7.3	7.6	7.7	7.6	7.5	7.7	7.4														
88010000	4.058	4.779	R	1	7	45	CRACKING	6.0*	6.0*	6.0*	5.5*	4.0*		10.0	10.0	10.0	10.0	10.0	8.5	8.5															
5	1		2	4.6	24000		RIDE	7.7	7.7	7.3	6.9	6.6		8.3	7.6	7.5	7.2	7.4	7.3	7.3															
CR 612(4.3C)					FC125M																														
4461071	4.082	4.779	R	2023		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.0	6.5	6.5	6.5	6.5	5.5*	5.5*	10.0	9.5														
RANGER CONSTRUCTION INDUST				(2026)			SPRIDE	7.4	7.3	6.7	6.8	6.7	7.4	7.1	6.7	6.7	6.7	6.3	6.9	8.0	7.7													
88010000	4.779	5.845	R	1	7	35	CRACKING	8.0	8.0	8.0	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	8.5	8.5															
5	1		2	4.3	22240		RIDE	8.1	7.3	7.5	6.9	7.0		7.7	7.6	7.5	7.2	7.4	7.3	7.3															
TWELFTH ST(4.8C)					FC95M																														
4476481	4.779	5.845	R	2025		0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.4	10.0	9.5														
TIMOTHY ROSE CONTRACTING,				(2026)			RIDE	7.4	7.3	6.7	6.8	6.7	6.6	6.5	6.6	6.2	6.4	6.4	6.6	8.0	7.7													
88010000	5.845	7.268	R	1	1	35	CRACKING	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	4.5*	3.5*		10.0	10.0	10.0															
5	1		2	3.6	20400		RIDE	8.0	7.5	7.7	7.3	7.2	7.0	7.2	7.3	7.2		8.3	8.3	8.2															
SR 60 WB(5.9C)					FC95																														
4152911	5.846	7.294	R	2009		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	9.1	9.3	8.0														
COMMUNITY ASPHALT CORP.				(2011)			SPRIDE	8.1	8.0	7.7	7.3	7.6	7.4	6.7	7.2	7.2	7.4	7.0	7.1	7.3	7.0													
88010000	7.268	7.930	R	1	1	45	CRACKING	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0															
5	1		2	2.8	33500		RIDE	8.0	7.5	7.7	7.3	7.2	7.0	7.2		8.2	7.7	7.9	7.9	8.0															
BEACON RD(7.3R)					FC95																														
2286231	7.277	14.800	C	2006		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	8.0	8.9	8.7	7.5														
COMMUNITY ASPHALT CORP.				(2009)			SPRIDE	7.9	7.9	7.3	7.4	7.4	7.3	7.2	7.2	7.1	7.2	7.2	7.0	7.0	6.7													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 4 COUNTY = INDIAN RIVER ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYS / %T / FY-P	TYP SPD / AADT / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
88010000	7.930	13.625	R	1	1 55	CRACKING	6.0*	4.0*	4.0*	4.0*	4.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0															
5	1		2	9.2	25500	RIDE	8.7	7.6	8.1	7.1	6.8	6.5	6.6		8.1	8.0	8.0	8.1	8.0															
38 ST(8.0R)					FC2																												
2286231	7.277	14.800	C	2006	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.6	7.9	5.5*													
COMMUNITY ASPHALT CORP.				(2009)	SPRIDE		8.1	8.0	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.0	7.9													
88010000	13.625	14.860	R	1	1 45	CRACKING	7.0	6.5	6.5	5.5*	5.5*	4.0*	4.0*		10.0	10.0	10.0	10.0	10.0															
5	1		2	9.2	25500	RIDE	8.9	7.8	8.4	7.8	7.3	7.1	7.1		7.8	7.7	7.7	7.6	7.6															
81 ST(13.7C)					FC95																												
2286231	7.277	14.800	C	2006	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	7.7	7.6	6.0*													
COMMUNITY ASPHALT CORP.				(2009)	SPRIDE		7.7	7.5	7.3	7.3	7.3	7.3	7.4	7.3	7.3	7.3	7.3	7.3	7.1	6.8													
88010000	14.860	18.770	R	1	1 50	CRACKING	6.0*	5.5*	3.5*	3.5*	3.5*	1.5*	1.5*		10.0	10.0	10.0	10.0	10.0															
5	1		2	4.8	24500	RIDE	8.8	7.7	8.3	7.2	6.7	6.4*	6.6		7.8	7.7	7.7	7.7	7.7															
IRBY LN(15.6R)					FC5																												
2286151	14.911	18.806	C	2006	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	6.5	6.5	6.5	6.5	4.0*													
COMMUNITY ASPHALT CORP.				(2009)	SPRIDE		7.8	7.7	8.0	8.0	8.0	8.0	8.0	8.1	8.0	8.0	8.0	8.0	8.0	7.9													
4498121	14.548	18.770	C	2027	0012																												
88010000	18.770	20.250	R	1	1 35	CRACKING	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5														
5	1		2	4.8	22000	RIDE	7.3	6.9		7.7	7.5	7.1	7.5	7.6	7.5	7.3	7.3	7.3	7.2														
CR 512(18.8C)					DGFC																												
4323251	18.760	20.221	R	2023	0012	CRACKING	9.5	9.5	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	9.5													
RANGER CONSTRUCTION INDUST				(2025)	RIDE		7.4	7.2	7.4	7.3	7.1	7.0	7.0	6.8	7.0	6.9	6.8	8.0	8.1	7.8													
88010000	20.250	22.269	R	1	1 45	CRACKING	8.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5														
5	1		2	4.8	22500	RIDE	8.7	8.6	8.5	7.9	7.9	7.8	8.1	8.1	8.1	7.9	7.9	7.8	7.7														
JACKSON ST(20.3C)					FC95M																												
2286031	18.740	22.269	C	2001	0012	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	6.5	5.0*													
COMMUNITY ASPHALT CORP.				(2004)	SPRIDE		7.8	7.8	7.7	7.7	7.7	7.6	7.5	7.5	7.4	7.5	7.4	7.6	7.5	7.2													
4476461	20.215	22.269	C	2024	0012																												
88010000	20.250	22.269	L	1	1 45	CRACKING	5.0*	5.0*	5.0*	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5														
5	1		2	4.8	22500	RIDE	8.9	8.5	8.6	7.8	7.8	7.6	8.0	8.0	8.0	8.0	8.0	7.7	7.9														
JACKSON ST(20.3C)					FC95M																												
2286031	18.740	22.269	C	2001	0012	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	5.0*													
COMMUNITY ASPHALT CORP.				(2004)	SPRIDE		7.9	7.9	7.7	7.7	7.7	7.6	7.6	7.5	7.5	7.6	7.5	7.4	7.3	7.0													
4476461	20.215	22.269	C	2024	0012																												
88010000	18.770	20.250	L	1	1 35	CRACKING	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5														
5	1		2	4.8	22000	RIDE	7.4	7.0		7.6	7.4	7.2	7.5	7.5	7.5	7.4	7.3	7.3	7.2														
CR 512(18.8C)					DGFC																												
4323251	18.760	20.221	L	2023	0012	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	7.0	6.0*	6.0*	6.0*	6.0*	10.0	10.0	9.5													
RANGER CONSTRUCTION INDUST				(2025)	SPRIDE		7.2	7.1	7.2	7.0	7.1	6.9	6.9	6.9	6.9	6.8	6.7	8.1	8.1	7.8													
88010000	14.860	18.770	L	1	1 50	CRACKING	6.0*	6.0*	6.0*	6.0*	6.0*	4.0*	3.5*		10.0	10.0	10.0	10.0	9.5															
5	1		2	4.8	24500	RIDE	8.6	7.3	8.3	7.2	6.9	6.7	6.9		7.6	7.5	7.5	7.5	7.5															
93 ST(15.4L)					FC5																												
2286151	14.911	18.806	C	2006	0012	CRACKING	9.5	8.0	8.0	8.0	8.0	7.5	7.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	2.0*													
COMMUNITY ASPHALT CORP.				(2009)	SPRIDE		7.6	7.5	7.8	7.8	7.8	7.7	7.8	7.8	7.8	7.8	7.8	7.8	7.7	7.6													
4498121	14.548	18.770	C	2027	0012																												
88010000	13.625	14.860	L	1	1 45	CRACKING	7.0	7.0	7.0	6.0*	6.0*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0															
5	1		2	9.2	25500	RIDE	8.8	8.2	8.5	7.8	7.6	7.4	7.6		8.3	8.2	8.2	8.2	8.2															
81 ST(13.7C)					FC95																												
2286231	7.277	14.800	C	2006	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.1	8.0	6.5													
COMMUNITY ASPHALT CORP.				(2009)	SPRIDE		8.1	8.1	7.9	7.5	7.9	7.7	7.6	7.8	7.7	7.7	7.6	7.8	7.7	7.4													
88010000	7.930	13.625	L	1	1 55	CRACKING	4.0*	4.0*	4.0*	3.5*	4.0*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0															
5	1		2	9.2	25500	RIDE	8.6	8.0	8.1	6.7	6.4*	6.1*	6.5		8.2	8.1	8.2	8.1	8.1															
CR 5A(8.0L)					FC2																												
2286231	7.277	14.800	C	2006	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.6	8.4	6.0*													
COMMUNITY ASPHALT CORP.				(2009)	SPRIDE		8.1	8.1	8.2	8.2	8.2	8.1	8.2	8.2	8.2	8.2	8.1	8.0	8.0	7.9													
88010000	7.268	7.930	L	1	1 45	CRACKING	8.0	8.0	8.0	8.0	7.0	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0															
5	1		2	2.8	33500	RIDE	8.1	7.2	7.8	7.1	7.1	7.1	7.2		8.3	8.3	8.2	8.1	8.1															
SIDE ROAD(7.5C)					FC95																												
2286231	7.277	14.800	C	2006	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	9.2	8.5	7.0													
COMMUNITY ASPHALT CORP.				(2009)	SPRIDE		8.1	8.1	7.8	7.7	7.8	7.6	7.2	7.7	7.7	7.7	7.4	7.6	7.6	7.3													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 4 COUNTY = INDIAN RIVER ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / RW FY-P / ASTYPE / RW FY-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2031 (PMRS)
88010000	5.845	7.268	L	1	1	35	CRACKING	8.0	8.0	8.0	8.0	7.0	6.0*	6.0*	4.5*	3.5*		10.0	10.0	10.0	
5 1			2	3.6	20400		RIDE	8.1	7.2	7.8	7.1	7.1	7.1	7.2	6.9	6.9		8.1	8.0	7.9	
SR 60 WB(5.9C)					FC95																
4152911	5.846	7.294	L	2009	0012		CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.7	8.7	7.5
COMMUNITY ASPHALT CORP.				(2011)			SPRIDE	7.9	7.9	7.7	7.6	7.7	7.5	6.7	7.5	7.4	7.6	7.4	7.1	7.1	6.8
88010000	4.779	5.845	L	1	7	35	CRACKING	5.5*	5.5*	5.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	
5 1			2	4.3	22240		RIDE	8.0	7.1	7.7	6.9	6.9		7.7	7.5	7.5	7.4	7.4	7.3	7.3	
TWELFTH ST(4.8C)					FC95M																
4476481	4.779	5.845	L	2025	0012		CRACKING	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.0	7.0	7.0	10.0	9.5
TIMOTHY ROSE CONTRACTING,				(2026)			SPRIDE	7.3	7.3	6.8	6.6	6.7	6.6	6.5	6.6	6.6	6.7	6.3	6.8	7.9	7.6
88010000	4.058	4.779	L	1	7	45	CRACKING	5.0*	4.0*	4.0*	4.0*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	
5 1			2	4.6	24000		RIDE	7.6	7.2	7.1	6.3*	6.0*		7.6	7.5	7.5	7.4	7.4	7.3	7.3	
CR 612(4.3C)					FC125M																
4461071	4.082	4.779	L	2023	0012		CRACKING	9.0	9.0	8.5	8.5	8.5	7.0	6.5	6.0*	6.0*	5.5*	5.5*	5.5*	10.0	9.5
RANGER CONSTRUCTION INDUST				(2026)			SPRIDE	7.3	7.3	6.8	6.6	6.7	7.6	7.1	6.8	6.8	6.6	6.5	6.4	7.7	7.4
88010000	1.615	4.058	L	1	1	45	CRACKING	8.0	7.0	6.0*	4.0*	4.0*	4.0*	4.0*	1.0*	0.0*			10.0	10.0	
5 1			3	4.5	35500		RIDE	8.7	8.2	8.5	7.7	7.6	7.4	7.6	7.5	7.5			8.7	8.5	
CR 606(2.1C)					FC95																
2285835	1.829	3.533	C	2008	0213		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	9.4	9.5	8.0
SHELTRA & SON CONST. CO. I				(2012)			SPRIDE	8.5	8.5	8.4	8.4	8.3	8.3	8.1	8.1	8.1	8.0	7.9	8.1	7.9	7.6
88010000	0.000	1.615	L	1	1	50	CRACKING	8.0	7.0	6.0*	4.0*	4.0*	4.0*	4.0*	1.0*	0.0*	0.0*	0.0*	0.0*	0.0*	
5 1			3	5.4	30500		RIDE	8.7	8.2	8.5	7.7	7.6	7.4	7.6	7.5	7.5	7.5	7.3	7.2	6.9	
UNSIGNED(0.4L)					FC5																
2285834	0.427	1.829	C	2012	0213		CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.7	8.8	7.0
				(2017)			RIDE				8.1	8.1	8.1	8.1	8.0	8.1	8.1	8.0	8.0	8.0	7.9
88050000	5.879	6.390	C	1	2	40	CRACKING	6.5	6.5	6.5				4.5*	3.5*	1.0*		4.5*	4.5*	4.5*	
510			2	6.3	15800		RIDE	6.3*	6.7	5.9				5.4*	5.2*	5.6		4.5*	4.2*	4.3*	
SR 5(5.9C)					FC95M																
4270221	5.860	6.380	C	2013	0012		CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.7	9.5	8.5
COMMUNITY ASPHALT CORP.				(2015)			RIDE	4.3*	8.2	7.8	7.5	7.5	7.4	7.3	7.1	7.2	7.3	7.1	7.1	4.9*	4.6*
88050000	6.390	6.582	C	1	1	40	CRACKING	6.5	6.5	6.5				4.5*	3.5*	1.0*		10.0	10.0	10.0	
510			2	6.3	15800		RIDE	6.3*	6.7	5.9				5.4*	5.2*	5.6		7.7	7.6	7.6	
WABASSO CAUSEWAY PAR(6.5C)					FC95																
4138031	6.378	7.697	C	2008	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5
CONE & GRAHAM, INC.				(2011)			SPRIDE	7.6	7.4	7.5	8.2	8.6	8.5	8.5	8.4	8.3	8.4	8.4	8.3	8.3	8.0
88050000	6.838	7.217	C	1	1	40	CRACKING	6.5	6.5	6.5				4.5*	3.5*	1.0*		10.0	10.0	10.0	
510			2	6.3	15800		RIDE	6.3*	6.7	5.9				5.4*	5.2*	5.6		7.7	7.6	7.6	
PARK ENTR(6.9C)					FC95																
4138031	6.378	7.697	C	2008	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.6	8.9	7.5
CONE & GRAHAM, INC.				(2011)			SPRIDE	7.6	7.4	7.5	8.2	8.0	7.8	7.8	7.7	7.8	7.6	7.7	7.5	7.6	7.3
88050000	7.538	8.245	R	1	1	40	CRACKING	5.5*	3.5*	8.0				4.5*	3.5*	1.0*		10.0	10.0	10.0	
510			1	6.3	15800		RIDE	6.2*	6.3	5.8				5.4*	5.2*	5.6		7.7	7.6	7.6	
MICHAEL CREEK CIR(7.8R)					FC95																
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.0	8.0	8.0	7.0	8.0	7.6	6.5
				(2011)			RIDE	7.6	7.4	7.5	7.2	7.2	7.0	6.9	6.8	6.6	6.7	6.6	6.1	6.1	5.8
88050000	8.245	8.485	R	1	1	40	CRACKING	10.0	10.0	10.0				4.5*	3.5*	1.0*		10.0	10.0	10.0	
510			1	6.3	15800		RIDE	8.4	8.3	8.2				5.4*	5.2*	5.6		7.7	7.6	7.6	
					DGFC																
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.0	8.0	8.0	7.0	9.5	10.0	9.5
				(2025)			RIDE	7.6	7.4	7.5	7.2	7.2	7.0	6.9	6.8	6.6	6.7	6.6	7.7	7.8	7.5
88050000	8.245	8.485	L	1	1	40	CRACKING	10.0	10.0	10.0				4.5*	3.5*	1.0*		10.0	10.0	10.0	
510			1	6.3	15800		RIDE	8.4	8.3	8.2				5.4*	5.2*	5.6		7.7	7.6	7.6	
4138031	8.244	8.485	L	2008	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	8.5	8.5	9.2	10.0	8.5
CONE & GRAHAM, INC.				(2011)			SPRIDE	7.6	7.4	7.5	7.2	7.2	7.0	6.9	6.6	6.9	6.8	6.6	7.1	7.4	7.1

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 4 COUNTY = INDIAN RIVER ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	LN	%T	AADT	DISTRESS RATINGS / SURFTYPE / WKMX-P / ASTYPE / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
88050000	7.538	8.245	L				1		40	CRACKING	5.5*	3.5*	8.0				4.5*	3.5*	1.0*		10.0	10.0	10.0													
510							1	6.3	15800	RIDE	6.2*	6.3	5.8				5.4*	5.2*	5.6		7.7	7.6	7.6													
JUNGLE TR(8.0C)									FC95																											
										CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	8.5	8.5	8.4	8.4	7.0												
								(2011)		RIDE	7.6	7.4	7.5	7.2	7.2	7.0	6.9	6.6	6.9	6.8	6.6	6.4	6.4	6.1												
88060000	0.000	0.825	R				1		65	CRACKING	10.0	10.0	10.0	10.0						10.0	10.0	10.0	10.0													
60							2	24.3	8313	RIDE	8.5	8.2	8.3	8.1						8.1	8.2	8.3	8.1													
									FC5M																											
								(2010)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	5.3*	4.7*	2.0*												
										RIDE	8.2	8.1	8.4	8.3	8.3	8.2	8.4	8.4	8.4	8.4	8.4	8.4	8.3	8.2												
88060000	0.825	11.628	R				1		65	CRACKING	9.5	9.5	7.0	7.0					10.0	10.0	10.0	10.0	10.0													
60							2	24.3	8313	RIDE	8.9	8.3	8.6	7.7					8.2	8.1	8.1	8.1	8.1													
NO NAME(2.3C)									FC5M																											
								(2009)		CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.5	7.5	6.5	6.5	4.8*	4.2*	1.5*												
										RIDE	8.0	8.0	8.2	8.1	8.0	7.8	8.2	8.1	8.1	8.1	8.1	8.0	7.9	7.8												
88060000	11.628	14.634	R				1		65	CRACKING	5.5*	5.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	10.0	10.0													
60							2	24.3	8313	RIDE	9.0	8.0	8.7	8.1				8.2	8.2	8.0	8.0	8.0	8.0													
SIDE ROAD(14.5R)									FC5M																											
2285971	11.628	14.634	C	2002					0213	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.0	6.5	6.5	6.5	6.5	4.3*	3.7*	1.0*												
VEZINA, LAWRENCE & PISCITE(2008)									S	RIDE	7.9	7.8	8.0	7.9	7.8	7.6	7.8	7.7	7.7	7.6	7.6	7.6	7.4	7.3												
4484441	7.916	15.056	C	2030					0012																											
88060000	14.634	15.052	R				1		65	CRACKING	5.5*	5.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	10.0	10.0													
60							2	24.3	8313	RIDE	9.0	8.0	8.7	8.1				8.3	8.4	8.2	8.1	8.1	8.1													
									FC5M																											
2285961	14.634	19.000	C	2002					0213	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.0	7.5	7.5	7.5	7.5	6.5	4.3*	1.5*												
VEZINA, LAWRENCE & PISCITE(2008)									S	RIDE	8.0	7.9	8.3	8.3	8.3	8.1	8.5	8.5	8.5	8.5	8.5	8.4	8.1	8.0												
4484441	7.916	15.056	C	2030					0012																											
88060000	15.052	22.389	R				1		7	65	CRACKING	5.5*	5.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	10.0	10.0													
60							2	23.1	7100	RIDE	9.0	8.0	8.7	8.1				8.3	8.4	8.2	8.1	8.1	8.1													
154 AVE(16.0R)									FC5M																											
4476471	15.056	22.395	R	2024					0012	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.0	7.5	7.5	7.5	7.5	6.5	10.0	9.0												
RANGER CONSTRUCTION INDUST(2026)										RIDE	8.0	7.9	8.3	8.3	8.3	8.1	8.5	8.5	8.5	8.5	8.5	8.4	8.7	8.6												
88060000	22.389	22.920	R				1		45	CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0	10.0	10.0													
60							3	12.8	15300	RIDE	7.8	8.2	8.5	7.9	7.4	7.2	7.9	7.7	7.8	7.0	7.2	8.3	8.2												
									FC125																											
								(2016)		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.2	8.1	7.0												
										RIDE	8.1	8.1	7.9	8.0	7.9	8.0	7.8	7.8	7.9	7.9	7.8	7.7	7.7	7.4												
88060000	22.920	26.184	R				1		45	CRACKING	3.5*	3.5*	3.0*	3.0*	3.0*	1.0*	1.0*	0.0*	0.0*			10.0	10.0													
60							3	22.0	18500	RIDE	7.0	6.6	6.4*	5.3*	5.1*	4.7*	5.1*	4.9*	4.7*			8.8	8.6												
AMERICAN WAY(23.0R)									FC95																											
2286271	23.923	26.072	C	2008					0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.1	9.1	8.0												
RANGER CONSTRUCTION INDUST(2012)										SPRIDE	8.6	8.6	8.3	8.3	8.3	8.3	8.2	8.2	8.2	8.2	8.2	8.2	8.2	7.9												
88060000	26.184	27.151	R				1		45	CRACKING	10.0	10.0	10.0	10.0	10.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5													
60							3	6.4	33500	RIDE	8.9	8.2	8.7	8.2	8.0	8.1	8.3	8.0	8.2	8.0	8.1	7.5	7.2												
63 CT(26.4R)									FC95R																											
4246381	26.184	27.111	C	2012					0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.5	9.5	7.9	8.5	7.5												
RANGER CONSTRUCTION INDUST(2014)										SPRIDE	8.5	8.5	8.3	8.2	8.3	8.2	8.1	8.1	8.0	8.1	8.0	8.0	8.0	7.7												
88060000	27.151	27.920	R				1		45	CRACKING	6.0*	4.0*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	9.5	9.5	9.5													
60							3	5.6	32500	RIDE	7.7	6.7	7.3	7.0	6.8		8.5	8.0	8.0	7.9	8.0	7.8	7.5												
CR 613(27.2C)									FC125																											
2285681	27.101	28.086	C	2004					0012	CRACKING	9.5	9.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.8	8.8	7.5												
COMMUNITY ASPHALT CORP.								(2007)		SPRIDE	7.9	7.7	8.1	7.8	7.9	8.0	8.0	8.0	8.0	8.0	8.1	7.8	7.9	7.6												
88060000	27.920	28.448	R				1		45	CRACKING	6.0*	4.0*	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	8.0													
60							3	2.8	29500	RIDE	7.7	6.7	7.3	7.2	7.0	6.8	7.1	6.4	7.1	7.0	6.9	6.9	6.9												
WINN DIXIE(28.0R)									FC95MR																											
										CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	9.1	10.0	9.0												
								(2024)		RIDE	6.9	6.8	6.4	6.4	6.6	6.3	6.5	6.4	6.2	6.3	7.7	7.6	7.6	7.3												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 4 COUNTY = INDIAN RIVER ----------

RDWYID / SR / US / G_BMP / G_EMP / LN / %T / AADT / RATINGS	BMP / EMP / RW / SYS / TYP / SPD	DISTRESS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE
INTERSECT AT (MP|SIDE) / SURFTYPE ========																
ITMSEG-P / W_BMP / W_EMP / RW / FY-P / WKMX-P																
CONTRACTOR (AGE_ONE YEAR) / ASTYPE			2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031
ITMSEG-F / W_BMP / W_EMP / RW / FY-F / WKMX-F																(PMRS)
88060000 / 28.448 / 29.564	R / 1 / 1 / 45	CRACKING	6.0*	4.0*	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	8.0	
60 / 3 / 2.8 / 29500		RIDE	7.7	6.7	7.3	7.2	7.0	6.8	7.1	6.4	7.1	7.0	6.9	6.9	6.9	
38 AVE(28.5R)		FC125M														
4360951 / 28.408 / 29.545	R / 2018 / 0012	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.5
RANGER CONSTRUCTION INDUST(2020)		SPRIDE	6.9	6.8	6.4	6.4	6.6	6.3	8.1	8.1	8.1	8.1	7.9	7.9	7.9	7.6
88060000 / 29.564 / 30.665	C / 1 / 1 / 40	CRACKING	9.5	9.5	9.5	9.5	8.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	
60 / 3 / 2.9 / 9200		RIDE	8.1	8.0	8.2	7.4	7.0	7.2	7.5	7.2	7.6	7.4	7.4	7.4	7.2	
VERO BEACH AVE(29.6L)		FC125														
4035961 / 29.518 / 30.620	C / 2007 / 0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.0	7.0	7.0	7.0	5.5*
COMMUNITY ASPHALT CORP. / (2009)		SPRIDE	7.2	7.5	7.3	6.9	7.1	6.8	6.9	6.7	6.9	6.9	6.9	6.9	6.6	6.3
4484431 / 29.564 / 31.253	C / 2029 / 0012															
88060000 / 30.665 / 30.920	C / 1 / 1 / 40	CRACKING	9.0	8.0	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	10.0	10.0	10.0	
60 / 2 / 2.9 / 9200		RIDE	7.6	7.4	6.9	6.7	7.4	7.5	7.1	7.0	6.8	7.5	7.4	6.8	6.6	
SR 5(30.7C)		FC125														
4035961 / 30.620 / 30.868	C / 2007 / 0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.8	7.5	6.0*
COMMUNITY ASPHALT CORP. / (2011)		SPRIDE	6.7	5.9	5.6										6.2	5.9
4484431 / 29.564 / 31.253	C / 2029 / 0012															
88060000 / 30.920 / 31.196	R / 1 / 1 / 40	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	
60 / 2 / 4.2 / 8500		RIDE	8.5	7.9	8.1	7.8	6.9	7.5	7.6	7.2	7.1	8.0	7.9	7.6	7.7	
SIXTH AVE(30.9C)		FC125														
4035961 / 30.868 / 33.296	R / 2007 / 0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.3	7.3	6.0*
COMMUNITY ASPHALT CORP. / (2010)		SPRIDE	7.7	7.9	7.3	6.7	6.7	6.8	7.0	7.0	7.0	7.0	6.7	6.4	6.4	6.1
4484431 / 29.564 / 31.253	C / 2029 / 0012															
88060000 / 31.196 / 31.798	R / 1 / 1 / 45	CRACKING	7.0	7.0	7.0	7.0	7.0	4.5*	4.5*	3.5*		10.0	10.0	10.0	10.0	
60 / 2 / 3.5 / 30500		RIDE	7.6	6.8	7.3	6.2*	6.1*	5.8	6.2	6.0		7.9	7.5	7.5	7.6	
INDIAN RIVER BLVD(31.2R)		FC125														
4035961 / 30.868 / 33.296	R / 2007 / 0012	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.0	9.0	9.0	9.0	8.4	8.4	7.0
COMMUNITY ASPHALT CORP. / (2010)		SPRIDE	7.5	7.4	7.0	7.2	6.9	7.0	7.1	7.0	6.9	7.0	6.9	6.9	6.9	6.6
88060000 / 31.798 / 32.316	R / 1 / 1 / 45	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5		10.0	10.0	10.0	10.0	
60 / 2 / 3.5 / 33000		RIDE	7.1	6.9	6.8	6.4*	6.9	6.1	6.1	5.7		7.4	7.1	7.6	7.6	
FRONTAGE ROAD(31.8R)		FC125														
4035961 / 30.868 / 33.296	R / 2007 / 0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.0	7.6	6.7	5.5*
COMMUNITY ASPHALT CORP. / (2010)		SPRIDE	7.5	7.5	7.1	7.4	7.2	7.1	6.9	6.9	6.7	6.8	6.5	6.7	6.1	5.8
88060000 / 33.042 / 33.639	R / 1 / 1 / 35	CRACKING	6.0*	6.0*	9.5	9.5	9.5	9.0	6.5	6.5		10.0	10.0	10.0	10.0	
60 / 2 / 13.6 / 23400		RIDE	4.3*	6.7	7.9	7.2	7.1	6.6	6.9	7.1		7.7	7.9	7.6	7.7	
INDIAN RIVER DR(33.2R)		FC125														
		CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.9	8.6	7.0
(2010)		RIDE	7.9	7.4	7.2	5.8	6.5	6.9	6.5	6.2	6.7	6.6	6.5	6.8	6.2	5.9
88060000 / 33.042 / 33.639	L / 1 / 1 / 35	CRACKING	7.0	6.0*	10.0	9.5	9.5	9.0	7.5	6.5		10.0	10.0	10.0	10.0	
60 / 2 / 13.6 / 23400		RIDE	4.7*	4.7*	7.9	7.4	7.5	7.1	7.2	7.2		7.8	7.8	7.7	7.5	
INDIAN RIVER DRIVE E(33.2L)		FC125														
		CRACKING	10.0	9.0	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	8.6	8.5	8.0
(2025)		RIDE	7.7	7.0	6.7	6.2	6.4	6.2	5.9	6.2	6.3	6.4	6.1	5.9	6.2	5.9
88060000 / 31.798 / 32.316	L / 1 / 1 / 45	CRACKING	10.0	10.0	10.0	9.5	9.5	9.0	7.5	6.5		10.0	10.0	10.0	10.0	
60 / 2 / 3.5 / 33000		RIDE	7.8	7.6	7.7	7.1	7.0	6.8	6.7	6.8		7.6	7.2	7.6	7.6	
SPUR(31.8L)		FC125														
4035961 / 30.868 / 33.296	L / 2007 / 0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.8	8.4	7.0
COMMUNITY ASPHALT CORP. / (2010)		SPRIDE	7.5	7.5	6.6	7.0	7.3	7.3	6.5	6.9	6.5	6.8	6.6	7.1	6.5	6.2
88060000 / 31.196 / 31.798	L / 1 / 1 / 45	CRACKING	7.0	7.0	7.0	7.0	7.0	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	
60 / 2 / 3.5 / 30500		RIDE	6.3*	6.6	6.0*	5.7*	5.5*	5.1*	5.5	5.5		7.4	7.5	7.2	7.3	
SPUR(31.2L)		FC125														
4035961 / 30.868 / 33.296	L / 2007 / 0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	9.0	9.0	7.5
COMMUNITY ASPHALT CORP. / (2010)		SPRIDE	7.1	7.2	6.6	6.8	6.7	6.4	6.2	6.7	6.8	6.5	6.6	6.2	6.6	6.3
88060000 / 30.920 / 31.196	L / 1 / 1 / 40	CRACKING	9.5	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	
60 / 2 / 4.2 / 8500		RIDE	7.9	7.1	7.5	7.0	7.3	6.9	7.1	7.2	7.5	6.7	6.4	7.0	6.7	
88060001/20 ST(30.9L)		FC125														
4035961 / 30.868 / 33.296	L / 2007 / 0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.0	7.0	7.3	6.8	5.5*
COMMUNITY ASPHALT CORP. / (2010)		SPRIDE	6.9	6.9	7.2	7.1	6.9	6.6	6.9	6.4	6.5	6.4	5.9		6.5	6.2
4484431 / 29.564 / 31.253	C / 2029 / 0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 4 COUNTY = INDIAN RIVER ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / CONTRACTOR (AGE_ONE YEAR)	BMP / G_BMP / LN / %T / AADT / SURFTYPE / ASTYPE	EMP / G_EMP / RW / SYS / TYP / SPD / WKMX-P / FY-P / WKMX-F	DISTRESS RATINGS	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
88060000	28.448	29.564	L	1	1	45	CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	8.0										
60			3	2.8	29500		RIDE	7.8	7.2	7.5	7.3	7.2	7.0	7.2	7.3	7.3	7.2	7.1	7.1	7.0										
38 AVE(28.5L)						FC125M																								
4360951	28.408	29.545	L	2018		0012	CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.4	8.5									
RANGER CONSTRUCTION INDUST			(2020)			SPRIDE	RIDE	7.1	7.0	6.6	6.8	6.8	6.7	8.4	8.2	8.2	8.3	8.1	8.1	8.2	7.9									
88060000	27.920	28.448	L	1	1	45	CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	8.0										
60			3	2.8	29500		RIDE	7.8	7.2	7.5	7.3	7.2	7.0	7.2	7.3	7.3	7.2	7.1	7.1	7.0										
CLEMAN(28.1C)						FC95MR																								
							CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	6.5	4.5*	4.5*		10.0	9.1	10.0	9.0									
			(2024)				RIDE	7.1	7.0	6.6	6.8	6.8	6.7	6.8	6.7	6.4		7.8	7.7	7.3	7.0									
88060000	27.151	27.920	L	1	1	45	CRACKING	6.0*	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0										
60			3	5.6	32500		RIDE	7.8	7.2	7.5	7.3	7.1		8.2	7.9	8.1	8.0	8.1	7.8	7.6										
CR 613(27.2C)						FC125																								
2285681	27.101	28.086	C	2004		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.8	9.1	7.5									
COMMUNITY ASPHALT CORP.			(2007)			SPRIDE	RIDE	7.8	7.7	8.1	7.8	7.9	7.8	8.1	7.9	7.9	8.0	8.1	7.8	8.0	7.7									
88060000	26.184	27.151	L	1	1	45	CRACKING	10.0	10.0	10.0	10.0	10.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5										
60			3	6.4	33500		RIDE	8.7	8.1	8.3	8.1	8.0	8.0	8.2	8.3	8.0	7.7	7.4	7.4	7.5										
63 CT(26.5L)						FC95R																								
4246381	26.184	27.111	C	2012		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.5	9.5	8.3	8.0	7.0									
RANGER CONSTRUCTION INDUST			(2014)			SPRIDE	RIDE	8.6	8.2	8.4	8.2	8.4	8.4	8.3	8.3	8.4	8.3	8.3	8.3	8.3	8.0									
88060000	22.920	26.184	L	1	1	45	CRACKING	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	4.0*	4.0*			10.0	10.0										
60			3	22.0	18500		RIDE	7.9	8.1	7.5	6.9	7.1	6.9	6.7	6.9	6.8			8.7	8.5										
NINETIETH AVE(23.1C)						FC95																								
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	10.0	10.0	9.5									
			(2025)				RIDE	8.5	8.5	8.3	8.2	8.3	8.2	8.2	8.2	8.2	8.2	8.2	8.2	8.1	7.8									
88060000	22.426	22.920	L	1	1	45	CRACKING	3.0*	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	6.5	10.0	10.0										
60			3	12.8	15300		RIDE	7.8	8.1	8.1	7.6	7.4	6.9	7.3	6.6	7.4	7.4	7.5	8.4	8.2										
						FC125																								
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.6	8.3	7.0									
			(2016)				RIDE	8.3	8.1	8.5	8.4	8.2	8.2	8.1	8.1	8.1	8.0	8.0	8.0	7.7	7.4									
88060000	15.023	22.426	L	1	7	65	CRACKING	5.5*	5.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	10.0	10.0										
60			2	23.1	7100		RIDE	9.0	8.0	8.7	8.1				8.2	8.2	8.0	8.0	8.0	7.9										
CR 512(15.1L)						FC5M																								
4476471	15.056	22.395	L	2024		0012	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.0	7.5	7.5	7.5	7.5	6.0*	10.0	9.0									
RANGER CONSTRUCTION INDUST			(2026)			SPRIDE	RIDE	7.8	7.7	8.0	7.9	7.9	7.8	8.0	7.9	7.9	7.9	7.9	7.8	8.7	8.6									
88060000	14.634	15.023	L	1	1	65	CRACKING	5.5*	5.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	10.0	10.0										
60			2	24.3	8313		RIDE	9.0	8.0	8.7	8.1				8.2	8.2	8.0	8.0	8.0	7.9										
						FC5M																								
2285961	14.634	19.000	C	2002		0213	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.0	7.5	7.5	7.5	7.5	6.0*	5.5*	3.0*									
VEZINA, LAWRENCE & PISCITE			(2008)			S	RIDE	7.8	7.7	8.0	7.9	7.9	7.8	8.0	7.9	7.9	7.9	7.9	7.8	7.5	7.4									
4484441	7.916	15.056	C	2030		0012																								
88060000	11.628	14.634	L	1	1	65	CRACKING	5.5*	5.5*	3.5*	3.5*				10.0	10.0	10.0	10.0	10.0	10.0										
60			2	24.3	8313		RIDE	9.0	8.0	8.7	8.1				8.2	8.2	8.0	8.1	8.0	7.9										
						FC5M																								
2285971	11.628	14.634	C	2002		0213	CRACKING	10.0	10.0	9.5	9.5	9.5	9.0	9.0	6.5	6.5	6.5	6.5	5.9*	5.4*	2.5*									
VEZINA, LAWRENCE & PISCITE			(2008)			S	RIDE	7.9	7.8	7.7	7.8	7.7	7.5	7.6	7.5	7.5	7.4	7.4	7.3	7.2	7.1									
4484441	7.916	15.056	C	2030		0012																								
88060000	0.900	11.628	L	1	1	65	CRACKING	9.5	9.5	7.0	7.0						10.0	10.0	10.0	10.0	10.0									
60			2	24.3	8313		RIDE	8.9	8.3	8.6	7.7						8.2	8.2	8.2	8.3	8.2									
BLUE CYPRESS RD(1.5L)						FC5M																								
							CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	5.4*	4.6*	2.0*									
			(2009)				RIDE	8.2	8.1	8.3	8.2	8.2	8.1	8.3	8.3	8.3	8.2	8.2	8.2	8.1	8.0									
88060000	0.000	0.900	L	1	1	65	CRACKING	10.0	10.0	10.0	10.0							10.0	10.0	10.0	10.0									
60			2	24.3	8313		RIDE	8.5	8.2	8.3	8.1							8.2	8.2	8.2	8.2									
						FC5M																								
							CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.0	4.5*									
			(2010)				RIDE	8.2	8.1	8.4	8.3	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.3									

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 4 COUNTY = INDIAN RIVER ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / CONTRACTOR (AGE_ONE YEAR)	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS / RATINGS / SURFTYPE / ASTYPE	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2031 (PMRS)
88060001	0.000	1.364	C	1	1	40	CRACKING	8.0	8.0	7.0	6.0*	6.0*	6.0*	6.0*	4.5*		10.0	10.0	10.0	10.0	
60			4	3.4	8400		RIDE	7.7	7.0	7.3	7.2	6.6	6.7	6.9	6.7		7.5	7.4	7.3	7.5	
88060000/20TH ST(0.0L)					DGFC																
4035961	0.268	0.895	C	2007	0012		CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*
COMMUNITY ASPHALT CORP.				(2010)			SPRIDE	7.3	7.2	7.1	6.6	6.8	7.0	6.7	6.6	6.9	6.8	6.6	6.5	6.6	6.3
4484431	0.000	1.364	C	2029	0012																
88060009	0.057	0.114	C	1	6	35	CRACKING					10.0	10.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	
60			2	3.8	2900		RIDE														
SR 5(0.1C)																					
							CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	4.5*	4.5*	4.5*	3.0*
				(2005)			RIDE														
4484431	0.057	0.114	C	2029	0012																
88070000	0.000	5.474	C	1	1	45	CRACKING	10.0	10.0	10.0	9.5	8.0	6.5	6.5	6.5	6.5	6.5	3.5*		10.0	
A1A			2	5.4	7000		RIDE	8.9	8.4	8.5	8.0	7.9	7.8	7.9	7.8	7.6	7.5	7.4		8.6	
OCEAN TRAIL LN(0.1R)					DGFC																
4216951	0.000	5.474	C	2011	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.0	7.0	7.0	6.5	6.5	6.5	5.5*
RANGER CONSTRUCTION INDUST				(2013)			RIDE	8.5	8.5	8.3	8.2	8.2	8.2	8.1	8.0	7.9	7.9	7.8	7.8	7.7	7.4
4498181	0.000	5.459	C	2027	0012																
88070000	5.474	7.280	C	1	1	45	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.0	8.0	8.0	8.0	8.0	8.0	
A1A			2	16.7	11300		RIDE	8.2	7.8	7.9	7.4	7.4	7.0	7.2	7.2	7.1	7.0	7.0	7.0	6.8	
JASMINE LN(5.5R)					FC95M																
4439961	5.459	7.257	C	2022	0012		CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	10.0	10.0	9.5
				(2025)			RIDE	6.8	6.8	7.2	7.1	7.1	6.9	6.8	6.9	6.7	6.9	6.8	7.5	7.4	7.1
88070000	7.280	8.658	C	1	1	35	CRACKING	4.0*	4.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	
A1A			2	4.0	14100		RIDE	8.1	7.7		7.4	7.3	7.2	7.4	7.4	7.3	7.3	7.2	7.1	7.1	
CYPRESS RD(7.3C)					FC125																
2286041	7.135	10.330	C	2001	0012		CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.9	8.7	7.0
RANGER CONSTRUCTION INDUST				(2004)			SPRIDE	7.2	7.1	6.8	6.6	6.6	6.4	6.4	6.2	6.4	6.3	6.3	6.3	6.3	6.0
88070000	8.658	15.395	C	1	1	50	CRACKING	6.0*	6.0*	6.0*	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.5	
A1A			2	16.7	10300		RIDE	8.6	7.8	8.2	7.8	7.8	7.6	7.9	7.8	7.8	7.6	7.5	7.2	7.0	
SILVER SHORES DR(8.7L)					FC125M																
							CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*		10.0	10.0	9.5	9.5	8.5
				(2023)			RIDE	6.9	7.0	6.9	6.8	6.8	6.7	6.7	6.6		7.9	7.8	7.8	7.8	7.5
88070000	15.395	22.364	C	1	1	50	CRACKING	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	8.5	8.5	
A1A			2	6.8	8800		RIDE	7.9	7.4	7.6	8.2	8.2	8.0	8.2	8.2	8.1	7.9	7.9	7.7	7.6	
SANDPIPER W(15.4L)					FC125																
2286051	15.184	22.686	C	2002	0012		CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	6.5	6.5	6.5	6.5	6.5	6.5	5.0*
COMMUNITY ASPHALT CORP.				(2004)			SPRIDE	7.5	7.5	7.4	7.4	7.3	7.2	7.2	7.0	7.1	7.0	6.9	6.9	6.9	6.6
4456182	15.395	21.905	C	2029	0012																
88081000	0.000	6.400	R	4	1	70	CRACKING		10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	6.5	6.5	5.5*		
9 I95	140.6	147.0	3	14.7	51000		RIDE		8.4	8.7	8.1	7.9	7.8	7.9	7.8	7.7	7.3	7.0	6.9		
					FC5M																
4130481	0.000	6.840	C	2011	0213		CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.3	7.9	6.0*
				(2017)			RIDE				8.6	8.6	8.5	8.6	8.6	8.6	8.6	8.6	8.5	8.5	8.4
88081000	6.400	19.198	R	4	1	70	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	6.5	6.5	6.5	
9 I95	147.0	159.8	3	14.7	50000		RIDE	9.0	8.5	8.8	8.2	8.2	8.1	8.3	7.8	8.1	7.9	7.8	8.0	8.1	
					FC5M																
							CRACKING	6.5						10.0	10.0	10.0	10.0	10.0	9.1	8.7	7.0
				(2020)			RIDE	8.0						8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.5
88081000	6.400	19.198	L	4	1	70	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	7.0	6.5	5.5*	5.5*	5.5*	
9 I95	147.0	159.8	3	14.7	50000		RIDE	8.9	8.4	8.8	8.2	8.1	8.0	8.3	8.2	8.0	7.9	7.7	7.8	7.6	
					FC5M																
							CRACKING	5.5*						10.0	10.0	10.0	9.0	9.0	8.8	8.5	7.0
				(2020)			RIDE	7.6						8.6	8.6	8.6	8.5	8.6	8.5	8.5	8.4
88081000	0.000	6.400	L	4	1	70	CRACKING		10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	6.5	6.5	5.5*		
9 I95	140.6	147.0	3	14.7	51000		RIDE		8.4	8.7	8.1	8.0	7.9	8.0	8.0	7.9	7.6	7.4	7.3		
					FC5M																
4130481	0.000	6.840	C	2011	0213		CRACKING				10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.1	7.6	5.5*
				(2017)			RIDE				8.6	8.5	8.5	8.6	8.6	8.6	8.6	8.5	8.5	8.5	8.4

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 01/30/2026

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 4 COUNTY = INDIAN RIVER ----------

RDWYID / SR / US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW	SYS	TYP	SPD	DISTRESS RATINGS / SURFTYPE / ASTYPE / WKMX-P / WKMX-F	SURVEYED YEAR 2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	FUTURE 2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2031 (PMRS)
88470000	0.000	5.200	R	5	7	70	CRACKING	10.0	9.5	9.5	9.5	9.5	7.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0															
91	173.1	178.3	2	16.0		38200	RIDE	8.9	8.3	8.5	7.6	7.2	6.7	7.2	6.8	7.4	7.3	8.4	8.4	8.4															
							FC5HP																												
4444031	0.000	5.287	C	2024		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	4.9*	10.0	9.0															
RANGER CONSTRUCTION INDUST(2026)							SPRIDE	8.3	8.3	8.6	8.5	8.5	8.5	8.7	8.6	8.5	8.5	8.4	8.2	8.9	8.8													
88470000	5.200	7.992	R	5	1	70	CRACKING	8.0	8.0	8.0		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5															
91	178.3	181.1	2	16.0		38200	RIDE	8.8	8.0	8.4		8.0	8.0	8.2	8.1	8.1	8.0	8.0	7.9	7.8															
							FC5M																												
4351671	5.200	8.000	C	2017		0012	CRACKING	9.5	8.0	7.0	7.0	6.5		10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0															
COMMUNITY ASPHALT CORP.				(2020)			SPRIDE	7.7	7.6	8.0	7.9	7.9		9.1	9.0	9.0	9.0	9.0	8.9	8.9	8.8													
88470000	15.464	17.452	R	5	1	70	CRACKING	7.0	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
91	188.6	190.6	2	16.0		38200	RIDE	9.0	7.5	8.9	8.1	7.7	7.7	7.9	7.9	7.9	7.7	7.8	7.8	7.6															
							FC5M																												
4351681	15.464	17.444	C	2017		0012	CRACKING	10.0	9.5	8.0	8.0	8.0		10.0	10.0	10.0	10.0	10.0	10.0	9.7	8.0															
RANGER CONSTRUCTION INDUST(2020)							SPRIDE	7.7	7.5	7.7	7.4	7.7		8.9	8.9	8.8	8.9	8.9	8.9	8.9	8.8													
88470000	15.464	17.452	L	5	1	70	CRACKING	7.0	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
91	188.6	190.6	2	16.0		38200	RIDE	8.9	7.6	8.5	7.6	7.2	7.1	7.5	7.6	7.5	7.4	7.4	7.1	7.2															
							FC5M																												
4351681	15.464	17.444	C	2017		0012	CRACKING	9.5	8.0	8.0	7.5	7.5		10.0	10.0	10.0	10.0	10.0	9.1	9.0	7.5															
RANGER CONSTRUCTION INDUST(2020)							SPRIDE	7.2	7.2	7.1	7.0	7.2		9.0	8.9	8.9	8.9	8.9	8.9	8.8	8.7													
88470000	5.200	7.992	L	5	1	70	CRACKING	9.5	8.0	8.0		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5															
91	178.3	181.1	2	16.0		38200	RIDE	8.9	8.3	8.5		7.7	7.8	8.0	8.0	8.0	7.9	7.9	7.9	7.8															
							FC5M																												
4351671	5.200	8.000	C	2017		0012	CRACKING	9.5	8.0	7.0	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	9.8	9.0	7.5															
COMMUNITY ASPHALT CORP.				(2020)			SPRIDE	7.8	7.7	7.9	7.8	7.8	7.8	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.0													
88470000	0.000	5.200	L	5	7	70	CRACKING	10.0	10.0	10.0	9.5	9.5	9.0	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0															
91	173.1	178.3	2	16.0		38200	RIDE	8.9	8.3	8.6	7.8	7.6	7.2	7.4	7.2	7.0	6.5	8.4	8.5	8.5															
							FC5HP																												
4444031	0.000	5.287	C	2024		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	6.5	6.5	4.5*	10.0	9.0															
RANGER CONSTRUCTION INDUST(2026)							SPRIDE	8.5	8.4	8.6	8.5	8.5	8.4	8.6	8.6	8.5	8.4	8.4	8.0	8.8	8.7													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2031 FORECASTED BY PAVEMARS (PMRS).