

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3 CONTRACTOR = ANDERSON COLUMBIA CO., INC.																					
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)					%T	=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-F	WKM-F															
CONTRACTOR (AGE ONE YEAR)							2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F	WKM-F														(PMRS)	
46002000	1.001	1.590	C	1	1	CRACKING	9.0	9.0	7.0	7.0	7.0	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0		
327			2	35	4000	RIDE	7.0	6.9	7.0	6.4	6.3	5.8	5.1*	5.2*	5.3*	7.6	7.3	7.3	7.1		
SR 368(1.0C)					2.8																
4134281	1.019	1.513	C	2008	0012	CRACKING	8.5	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	5.0*	
ANDERSON COLUMBIA CO., INC(2009)					FC95M	RIDE	7.3	7.1	7.2	7.0	6.9	6.9	6.6	6.9	6.2	6.6	6.4	6.3	6.2	5.8	
4508181	1.007	1.552	C	2026	0012																
46010000	0.000	0.451	R	1	7	CRACKING	10.0	10.0	10.0	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
30 98			2	45	28000	RIDE	8.9	8.7	8.7	8.7		8.4	8.0	8.0	8.3	8.3	8.3	8.3	8.3		
					5.3																
4377591	0.000	0.451	R	2021	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	4.5*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)					FC5	RIDE	8.3	8.2	8.2	8.2	8.2	8.1	8.1	8.1	8.2	8.0	8.1	8.0	8.5	8.3	
46010000	0.850	1.106	R	1	7	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
30 98			2	45	28000	RIDE	8.7	8.7	8.6	8.5	7.8	7.7	7.8	7.8	7.9	7.9	7.8	7.9	7.9		
					5.3																
4377591	0.850	1.106	R	2021	0012	CRACKING	10.0	8.5	8.5	7.0	7.0	7.0	6.5	6.5	6.5	4.5*	4.5*	3.5*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)					FC5	RIDE	7.8	7.8	7.7	7.8	7.8	7.8	7.8	7.9	7.7	7.7	7.6	7.5	8.4	8.2	
46010000	9.178	10.408	C	1	1	CRACKING	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	8.5	8.5		
30			2	35	12500	RIDE	8.0	7.7	7.6	7.4	6.4	6.4	6.0	7.4	7.6	7.0	6.9	6.9	6.8		
YOUNG ST(9.4L)					3.9																
4063191	7.253	13.743	C	2005	0012	CRACKING	8.5	8.5	8.5	7.5	6.0*	6.0*	6.0*	3.5*	3.5*	3.5*	3.5*	6.0*	6.3*	4.0*	
ANDERSON COLUMBIA CO., INC(2007)					DGFC	RIDE	6.8	6.7	6.7	6.5	6.5	6.3	6.2	6.2	6.0	5.8	5.7	5.9	5.8	5.4*	
46010000	10.649	12.370	C	1	1	CRACKING	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	8.5	8.5			
30			2	35	12000	RIDE	8.0	7.7	7.6	7.4	6.4	6.4	6.0	7.4	8.0	7.7	7.7	7.7	7.0		
AZALEA ST(10.6L)					3.9																
4063191	7.253	13.743	C	2005	0012	CRACKING	8.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	6.0*	6.6	4.5*	
ANDERSON COLUMBIA CO., INC(2007)					DGFC	RIDE	7.6	7.5	7.5	7.4	7.6	7.6	7.1	7.0	7.0	6.8	6.8	6.7	6.6	6.2	
46010000	13.694	15.769	R	1	1	CRACKING	8.5	8.5	7.0	5.0*	5.0*	5.0*	5.0*	5.0*	5.0*	5.0*	10.0	10.0	10.0		
30			2	45	28500	RIDE	8.0	8.0	7.9	7.8	7.5	7.2	6.9	7.3	7.3	7.3	8.4	8.3	8.3		
RAMP FROM THOMAS DR(13.7R)					3.9																
4090231	13.743	15.554	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.9	6.0*	
ANDERSON COLUMBIA CO., INC(2010)					FC125	RIDE	8.2	8.2	8.2	8.0	8.0	7.7	7.8	7.8	7.7	7.7	7.7	7.4	7.0		
46010000	13.694	15.769	L	1	1	CRACKING	8.5	8.5	7.5	7.0	7.0	5.0*	5.0*	5.0*	5.0*	5.0*	10.0	10.0	10.0		
30			2	45	28500	RIDE	8.0	7.9	7.6	7.7	6.9	6.6	6.4	6.4	6.7	6.7	8.3	8.3	8.2		
FLAGG AVE(13.8L)					3.9																
4090231	13.743	15.554	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	7.0	7.0	7.5	5.5*	
ANDERSON COLUMBIA CO., INC(2010)					FC125	RIDE	8.1	8.2	8.1	8.0	8.1	8.0	8.0	7.9	7.9	7.8	7.8	7.6	7.7	7.3	
46010000	0.836	1.106	L	1	7	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
30 98			2	45	28000	RIDE	8.5	8.4	8.7	8.5	7.7	6.9	7.9	8.2	8.2	8.2	8.2	8.2	8.1		
					5.3																
4377591	0.836	1.106	L	2021	0012	CRACKING	10.0	8.5	8.5	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.0*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)					FC5	RIDE	8.1	8.1	8.1	8.2	8.2	8.1	8.3	8.2	8.2	8.2	8.0	8.0	8.6	8.4	
46010000	0.000	0.451	L	1	7	CRACKING	10.0	10.0	10.0	8.5		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0		
30 98			2	45	28000	RIDE	9.1	9.1	9.0	8.9		8.4	8.1	8.2	8.3	8.2	8.2	8.4	8.3		
					5.3																
4377591	0.000	0.451	L	2021	0012	CRACKING	8.5	8.5	7.5	7.5	7.0	7.0	6.0*	6.0*	5.5*	5.5*	5.5*	5.5*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)					FC5	RIDE	8.3	8.2	8.2	8.2	8.2	8.1	8.1	8.1	8.1	7.9	7.9	7.9	8.5	8.3	
46010001	0.000	0.440	R	1	7	CRACKING	9.0	9.0	9.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	9.0	9.0	9.0		
30 98			2	45	28000	RIDE	8.0	8.1	8.0	7.1	6.9	6.1*	7.7	7.2	7.9	7.9	7.5	7.5	7.4		
SR 30(0.0C)					5.3																
4377591	0.000	0.440	R	2021	0012	CRACKING	8.5	8.5	9.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	5.5*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)					FC5	RIDE	7.4	7.4	7.9	8.0	8.1	8.0	8.0	8.1	7.8	7.9	8.0	7.9	8.8	8.6	
46010001	0.000	0.440	L	1	7	CRACKING	9.0	9.0	9.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
30 98			2	45	28000	RIDE	7.9	7.6	7.3	7.5	6.7	6.0*	7.5	6.7	8.2	8.2	7.7	7.8	7.6		
SR 30(0.0C)					5.3																
4377591	0.000	0.440	L	2021	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	6.5	6.5	6.5	5.5*	5.5*	3.5*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)					FC5	RIDE	7.5	7.5	7.9	8.0	7.3	7.7	7.9	7.9	7.9	7.8	7.8	7.7	8.9	8.7	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3 CONTRACTOR = ANDERSON COLUMBIA CO., INC.																									
RDWYID	SR	US	BMP	G BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE	
INTERSECT AT (MP SIDE)	AT	MP	W BMP	W BMP	W EMP	LN	LN	LN	LN	LN	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2030
ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	ITMSEG-P	(PMRS)
CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)	CONTRACTOR (AGE ONE YEAR)
ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F	ITMSEG-F
48190000	297		0.931	3.603	L	1	1	CRACKING	7.5	6.5	4.5*	2.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5		
MANDEVILLE LN(1.4L)					2	45	33500	RIDE	8.4	8.4	7.9	7.7	8.3	8.2	8.2	8.2	8.2	8.2	8.4	8.3	8.3	8.2	8.2		
2186791			0.931	3.603	C	2003	0012	CRACKING	9.0	9.0	9.0	9.0	8.0	8.0	7.9	7.9	7.0	7.0	7.0	6.0*	6.0*	5.5*	5.1*	2.5*	
ANDERSON COLUMBIA CO., INC(2004)							FC125	RIDE	8.2	8.1	7.7	7.8	7.7	7.7	7.7	7.7	7.0	7.8	7.8	7.7	7.7	7.6	7.6	7.2	
4508041			1.016	3.617	C	2026	0012																		
48190000	297		0.000	0.931	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0		
MOBILE HWY(0.0C)					2	45	18400	RIDE	8.7	8.7	8.5	8.5	8.5	7.6	8.3	8.2	8.2	8.2	8.0	8.0	8.0	8.0	8.0	8.0	
2185791			0.025	0.863	C	1996	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	5.5*	5.5*	3.5*	3.0*	0.5*	
ANDERSON COLUMBIA CO., INC(1997)							FC3	RIDE	7.6	7.7	7.0	7.4	7.6	8.0	7.9	8.0	7.9	8.0	7.6	7.1	7.6	7.6	7.8	7.4	
4475891			0.000	1.013	C	2024	0012																		
48260000	8	110	0.222	9.000	R	4	1	CRACKING	7.9	7.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5		
			0.2	9.0	2	70	36000	RIDE	6.6	7.0			8.4	8.4	8.3	8.4	8.4	7.9	8.3	8.3	8.2	8.2	8.2		
2224721			0.222	9.722	C	2001	0005	CRACKING	9.5	9.5	9.5	9.5	9.0	9.0	9.0	8.0	8.0	8.0	5.5*	5.5*	5.5*	5.5*	6.2*	2.5*	
ANDERSON COLUMBIA CO., INC(2004)							FC5	RIDE	8.1	8.2	8.0	8.2	8.3	8.4	8.5	8.5	8.5	8.5	8.5	8.5	8.4	8.4	8.4	8.3	
2224122			0.222	8.898	C	2025	0012																		
48260000	8	110	0.222	9.000	L	4	1	CRACKING	7.5	5.9*			10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5		
			0.2	9.0	2	70	36000	RIDE	6.7	7.3			8.4	8.4	8.3	8.3	8.1	8.4	8.3	8.3	8.2	8.2	8.2		
2224721			0.222	9.722	C	2001	0005	CRACKING	9.5	9.5	9.5	9.5	9.0	9.0	9.0	8.0	8.0	8.0	5.5*	5.5*	5.5*	5.5*	6.2*	2.5*	
ANDERSON COLUMBIA CO., INC(2004)							FC5	RIDE	8.1	8.2	8.1	8.3	8.3	8.4	8.5	8.5	8.5	8.6	8.6	8.5	8.4	8.4	8.4	8.3	
2224122			0.222	8.898	C	2025	0012																		
50030000	10	90	11.482	12.460	R	1	7	CRACKING	9.5	9.5	9.5	8.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
FLYING J(11.6R)					2	45	18200	RIDE	8.7	8.5	8.5	8.2	7.6	7.7	8.4	8.6	8.6	8.6	8.6	8.5	8.4	8.4	8.3		
4346451			11.482	13.442	C	2023	0012	CRACKING	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	5.5*	5.5*	10.0	9.0	
ANDERSON COLUMBIA CO., INC(2025)							FC125	RIDE	8.1	8.0	7.9	7.9	7.4	7.5	7.6	7.6	7.5	7.5	7.5	7.5	7.5	7.4	8.3	7.9	
50030000	10	90	12.460	13.442	R	1	7	CRACKING	9.5	9.5	8.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
BOAT RAMP(13.3R)					2	55	18200	RIDE	8.8	8.4	8.4	8.4	7.8	7.6	8.4	8.6	8.6	8.6	8.6	8.5	8.4	8.4	8.3		
4346451			11.482	13.442	C	2023	0012	CRACKING	10.0	9.5	9.0	9.0	9.0	7.5	4.5*	4.5*	3.5*	3.5*	0.0*	0.0*	0.0*	10.0	9.0		
ANDERSON COLUMBIA CO., INC(2025)							FC5M	RIDE	8.4	8.2	8.0	8.3	8.3	8.2	8.3	8.2	8.1	8.0	7.8	7.6	8.5	8.5	8.3		
50030000	10	90	12.460	13.442	L	1	7	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0		
RIVER PARK DR(12.7L)					2	55	18200	RIDE	8.9	8.8	8.7	8.8	8.3	8.2	8.3	8.6	8.5	8.5	8.5	8.4	8.3	8.3	8.2		
4346451			11.482	13.442	C	2023	0012	CRACKING	7.0	6.5	6.5	6.5	6.5	6.5	3.5*	3.5*	0.0*	0.0*	0.0*	0.0*	0.0*	10.0	9.0		
ANDERSON COLUMBIA CO., INC(2025)							FC5M	RIDE	8.2	8.1	7.8	8.1	8.1	8.0	7.9	7.8	7.6	7.5	7.5	7.1	6.7	8.5	8.3		
50030000	10	90	11.482	12.460	L	1	7	CRACKING	10.0	10.0	10.0	9.5	8.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0		
DUPONT RD(11.6L)					2	45	18200	RIDE	8.6	8.5	8.4	8.2	7.5	7.5	8.3	8.6	8.5	8.5	8.5	8.4	8.3	8.2	8.2		
4346451			11.482	13.442	C	2023	0012	CRACKING	7.0	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	6.0*	10.0	9.0		
ANDERSON COLUMBIA CO., INC(2025)							FC125	RIDE	7.3	7.3	7.1		7.6	7.4	7.4	7.5	7.4	7.4	7.4	7.4	7.4	7.0	8.4	8.0	
51010000	30	98	9.326	11.070	C	1	1	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	8.5		8.0	7.0	7.0	7.0	7.0	7.0		
MAGELLAN ST(9.4R)					2	45	8500	RIDE		8.8	8.8	8.7	8.4	8.3	8.1			8.3	8.2	8.1	8.0	8.0	8.0		
4269571			8.744	11.633	C	2012	0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	5.4*	3.5*		
ANDERSON COLUMBIA CO., INC(2013)							FC95	RIDE	8.6	8.5	8.4	8.3	8.3	8.2	8.0	8.1	8.0	7.8	7.9	7.8	7.8	7.8	7.4		
4335692			8.744	11.633	C	2025	0012																		
51030000	22		5.639	12.174	C	1	1	CRACKING	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5		
SHORTY KEMP RD(6.1L)					2	60	3200	RIDE	8.4	8.8	8.7	8.7	8.4	8.4	8.2	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.2		
4216411			5.418	12.136	C	2012	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	5.0*	
ANDERSON COLUMBIA CO., INC(2013)							FC95M	RIDE	8.5	8.7	8.6	8.4	8.4	8.4	8.3	8.3	8.2	8.3	8.2	8.3	8.2	8.3	8.2	7.8	
4546311			0.000	12.138	C	2028	0012																		
52002000	8	110	0.000	8.370	R	4	1	CRACKING	4.9*	4.0*			10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	7.0			
			94.5	102.8	2	70	20500	RIDE	5.9*	5.4*			8.9	8.4	8.2	8.2	8.3	8.3	8.2	8.2	7.7	7.9	7.8		
4252772			0.000	8.370	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	4.0*	
ANDERSON COLUMBIA CO., INC(2014)							FC5	RIDE		8.2	8.2	8.5	8.5	8.7	8.6	8.5	8.7	8.6	8.6	8.5	8.4	8.4	8.4	8.3	
4252773			0.000	8.370	C	2025	0012																		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = ANDERSON COLUMBIA CO., INC.													
RDWYID	SR	US	BMP	G BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE	
INTERSECT	AT	(MP)	(SIDE)			LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
ITMSEG-P	W BMP	W BMP	W EMP	RW	FY-P	WKM-F	WKM-F	WKM-F	WKM-F	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	(PMRS)	
CONTRACTOR	(AGE)	ONE	YEAR																						
ITMSEG-F	W BMP	W BMP	W EMP	RW	FY-F	WKM-F	WKM-F	WKM-F	WKM-F																
52002000	0.000	8.370	L	4	1	CRACKING	5.0*	5.3*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.0	7.0			
8 I10	94.5	102.8	2	70	20500	RIDE	6.3*	6.0*		8.9	8.4	8.3	8.2	8.3	8.2	8.1	7.8	7.6	7.6						
4252772	0.000	8.370	C	12	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	6.5	6.5	6.5	6.5	6.5	4.0*		
ANDERSON	COLUMBIA	CO., INC	(2014)		FC5	RIDE		8.3	8.4	8.6	8.6	8.8	8.6	8.6	8.6	8.6	8.6	8.8	8.7	8.6	8.6	8.5	8.4		
4252773	0.000	8.370	C	2025	0012																				
52010000	0.000	7.463	C	1	7	CRACKING	3.5*	3.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	7.0	7.0			
10 90			2	55	2600	RIDE	8.4	8.2	8.6	8.5	8.3	8.3	8.1	8.3	8.1	8.3	8.2	8.0	8.0	8.0	7.9	7.8			
MORROW RD (3.8R)					12.8																				
4377601	0.000	6.621	C	2024	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	10.0	9.0			
ANDERSON	COLUMBIA	CO., INC	(2025)		FC125	RIDE	7.5	7.7	7.6	7.6	7.7	7.7	7.6	7.7	7.7	7.6	7.6	7.6	7.4	7.4	7.4	8.0	7.6		
52010000	19.069	21.824	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	7.0			
10 90			2	55	3300	RIDE	8.9	8.2	8.8	8.8	8.4	8.4	8.3	8.5	8.5	8.4	8.4	8.4	8.4	8.3	8.2				
MARSH RD (19.1R)					12.2																				
4362691	19.069	21.824	C	2018	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	5.5*	5.5*	10.0	9.0	7.5		
ANDERSON	COLUMBIA	CO., INC	(2019)		FC125	RIDE	8.2	8.1	8.0	8.0	8.0	8.0	8.3	8.3	8.1	7.9	7.9	7.9	7.9	7.8	7.8	7.8	7.4		
52010000	23.813	27.386	C	1	1	CRACKING	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.0	7.0	7.0			
10 90			2	55	6000	RIDE	7.5	7.0	6.0*		8.2	8.1	8.2	8.3	8.4	8.3	8.3	8.3	8.3	8.3	8.2				
MAGNOLIA					12.2																				
4436441	25.462	27.216	C	2022	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	5.5*	5.5*	3.5*	10.0	9.0	7.5		
ANDERSON	COLUMBIA	CO., INC	(2022)		FC125	RIDE	8.1	8.0	7.9	7.7	7.8	7.8	7.6	7.6	7.5	7.6	7.5	7.6	7.4	7.4	8.4	8.2	7.8		
53002000	0.000	10.256	R	4	1	CRACKING	10.0	9.0	8.5	7.0	5.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
8 I10	126.8	137.1	2	70	26187	RIDE	9.0	8.9	8.7	8.7	7.9	7.6	7.3	7.0											
4152581	3.073	9.623	C	2006	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	3.5*		
ANDERSON	COLUMBIA	CO., INC	(2009)		FC5M	RIDE	8.5	8.4	8.3	8.6	8.6	8.6	8.8	8.8	8.8	8.8	8.9	8.8	8.7	8.7	8.7	8.7	8.6		
4506911	0.000	9.684	C	2026	0012																				
53002000	10.256	19.468	R	4	7	CRACKING	8.5	8.5	7.5	7.0	6.5	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
8 I10	137.1	146.3	2	70	23500	RIDE	8.9	8.9	8.9	8.8	8.2	8.2	8.0	8.0	8.0	8.0	8.0	8.6	8.7	8.6	8.6	8.6	8.6		
4456351	10.260	19.486	R	2023	0012	CRACKING	10.0	10.0	9.0	9.0	8.0	8.0	8.0	8.0	6.5	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	9.0		
ANDERSON	COLUMBIA	CO., INC	(2025)		FC5M	RIDE	8.6	8.5	8.5	8.7	8.7	8.7	8.9	9.0	9.0	9.0	9.0	8.9	8.9	8.9	8.7	8.8	8.7		
53002000	19.468	27.046	R	4	1	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0			
8 I10	146.3	153.8	2	70	21500	RIDE			9.0	8.9	8.4	8.6	8.5	8.5	8.6	8.5	8.5	8.5	8.5	8.3	8.3	8.1			
4327401	19.468	25.224	C	2017	0012	CRACKING	9.0	9.0	7.5	6.5	6.5														
ANDERSON	COLUMBIA	CO., INC	(2019)		FC5M	RIDE	8.3	8.0	7.9	8.2	8.2														
53002000	27.046	33.260	R	4	1	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
8 I10	153.8	160.1	2	70	23500	RIDE			9.0	8.9	8.4	8.6	8.5	8.6	8.6	8.6	8.6	8.6	8.6	8.5	8.4	8.4	8.4		
4327402	27.018	33.260	C	2017	0012	CRACKING	10.0	10.0	9.0	9.0	8.0	8.0													
ANDERSON	COLUMBIA	CO., INC	(2020)		FC5M	RIDE	8.3	8.2	8.2	8.4	8.4	8.4													
53002000	27.046	33.260	L	4	1	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
8 I10	153.8	160.1	2	70	23500	RIDE			9.0	9.0	8.4	8.5	8.4	8.6	8.6	8.6	8.5	8.4	8.3	8.3	8.3	8.3	8.3		
4327402	27.018	33.260	C	2017	0012	CRACKING	10.0	8.5	7.0	7.0	6.5	6.5													
ANDERSON	COLUMBIA	CO., INC	(2020)		FC5M	RIDE	8.3	8.2	8.0	8.3	8.3	8.3													
53002000	19.468	27.046	L	4	1	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0		
8 I10	146.3	153.8	2	70	21500	RIDE			9.0	9.0	8.4	8.5	8.5	8.4	8.4	8.4	8.4	8.3	8.2	8.0	8.0	7.9			
4327401	19.468	25.224	C	2017	0012	CRACKING	9.0	8.0	8.0	6.5	4.5*														
ANDERSON	COLUMBIA	CO., INC	(2019)		FC5M	RIDE	7.8	7.8	7.5	8.0	8.0														
53002000	13.609	19.468	L	4	7	CRACKING	8.5	8.5	7.5	7.0	6.5	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
8 I10	140.4	146.3	2	70	21500	RIDE	8.7	8.8	8.9	8.6	8.4	8.3	8.2	8.1	8.4	8.7	8.7	8.7	8.6	8.5					
4456351	10.260	19.486	L	2023	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	9.0	9.0		
ANDERSON	COLUMBIA	CO., INC	(2025)		FC5M	RIDE	8.5	8.4	8.3	8.6	8.6	8.6	8.9	8.9	8.9	9.0	8.9	8.7	8.6	8.9	8.9	8.8	8.8		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

ALL SYSTEM PAVEMENT CONDITION FORECAST

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

WYID SR	US INTERSECT	BMP AT	G_BMP (MP)	EMP G_EMP (SIDE)	RW LN	SYSTEM SPEED	TYPE AADT	DISTRESS RATINGS	SURVEYED YEAR												FUTURE	
									2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011		2012
									2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024		2025
ITMSEG-P CONTRACTOR	W_BMP (AGE)	W_EMP ONE YEAR	RW	FY-F	WKM-X SURF_TYPE	WKM-X F																
53020000 10 90 THIRD AVE(19.6C)	19.446	20.302	R	1 45	1 6600	CRACKING RIDE	7.5 8.4	7.0 8.3	8.5 8.0	3.5* 7.8	3.0* 6.8	10.0 8.3	10.0 8.3	10.0 8.4	10.0 8.2	10.0 8.1	10.0 8.1	10.0 8.1	10.0 8.1	9.5 8.0		
4063241 ANDERSON	19.454	23.352	C	2004	0012	CRACKING RIDE	9.5 8.0	9.5 8.0	9.5 7.9	9.5 7.8	9.5 7.8	8.5 7.7	8.5 7.8	7.5 7.7	7.5 7.7	7.5 7.6	6.0* 7.5	6.0* 7.4	4.9* 7.3	2.5* 6.9		
4531511	15.571	23.661	C	2027	0012																	
53020000 10 90 DAIRY RD(20.7L)	20.302	22.655	C	1 55	1 6100	CRACKING RIDE	7.5 8.4	7.0 8.3	8.5 8.0	3.5* 7.8	3.0* 6.8	10.0 8.3	10.0 8.3	10.0 8.4	10.0 8.2	10.0 8.1	10.0 8.1	10.0 8.1	9.5 8.0			
4063241 ANDERSON	19.454	23.352	C	2004	0012	CRACKING RIDE	9.5 8.0	9.5 8.0	9.5 7.9	9.5 7.8	9.5 7.8	8.5 7.7	8.5 7.8	7.5 7.7	7.5 7.6	7.5 7.8	6.0* 7.7	5.5* 7.7	3.0* 7.3			
4531511	15.571	23.661	C	2027	0012																	
53020000 10 90 THIRD AVE(19.6C)	19.446	20.302	L	1 45	1 6600	CRACKING RIDE	7.5 8.4	7.0 8.3	8.5 8.0	3.5* 7.8	3.0* 6.8	10.0 8.3	10.0 8.3	10.0 8.4	10.0 8.2	10.0 8.1	10.0 8.1	10.0 8.1	9.5 8.0			
4063241 ANDERSON	19.454	23.352	C	2004	0012	CRACKING RIDE	9.5 8.0	9.5 8.0	9.5 7.9	9.5 7.8	9.5 7.8	8.5 7.7	8.5 7.8	7.5 7.7	7.5 7.6	7.5 7.1	6.0* 7.1	6.0* 7.1	4.6* 7.0	2.5* 6.6		
4531511	15.571	23.661	C	2027	0012																	
53020000 10 90 OLD US RD(0.9L)	0.685	3.305	L	1 45	8 21500	CRACKING RIDE	3.5* 6.3*	10.0 8.7	10.0 8.7	10.0 8.5	10.0 8.0	10.0 8.2	10.0 8.1	9.0 8.4	9.0 8.3	9.0 8.3	9.0 8.2	8.0 8.2	8.0 8.1			
2193741 ANDERSON	0.000	3.236	C	2000	0012	CRACKING RIDE	8.0 8.0	8.0 8.0	8.0 7.7	8.0 7.9	8.0 7.8	7.0 7.7	6.0* 7.7	6.0* 7.7	6.0* 7.6	6.0* 7.6	5.5* 7.6	5.5* 7.6				
4455411	0.687	3.310	C	2023	0012																	
53020000 10 90 SR-166/JEFFERSON ST(0.0L)	0.000	0.685	L	2 45	1 19900	CRACKING RIDE	7.5 4.7*	10.0 8.5	10.0 8.3	10.0 7.9	10.0 7.6	9.5 7.7	9.5 7.0	8.5 7.2	8.0 7.1	9.0 7.7	9.0 7.6	9.0 7.7	9.0 7.8			
4246211 ANDERSON	0.182	0.604	C	2015	0012	CRACKING RIDE	9.0 7.6	9.0 7.4	9.0 7.1	10.0 8.4	10.0 8.3	10.0 8.4	10.0 8.2	10.0 8.2	8.5 8.2	8.5 8.0	7.0 7.4	7.0 7.4	7.4 7.3	5.5* 6.9		
4246211	0.182	0.604	C	2015	0012																	
53030000 75 231	0.000	0.586	R	1 65	1 6700	CRACKING RIDE	6.0* 7.8	4.5* 8.3	10.0 8.5	10.0 8.8	10.0 8.4											

```

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```


FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = ANDERSON COLUMBIA CO., INC.													
RDWYID	SR	US	G	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	RATINGS	SURVEYED YEAR										FUTURE			
INTERSECT AT (MP SIDE)	AT	(MP SIDE)					LN	SPEED	AADT	%T	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	W	BMP	W	EMP	RW	FY-P	W	WKMX-P				2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
CONTRACTOR (AGE ONE YEAR)																								(PMRS)	
ITMSEG-F	W	BMP	W	EMP	RW	FY-F	W	WKMX-F																	
53030035	0.708	4.979	L	1	1	CRACKING	3.5*	3.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5		
75 231			2	65	6100	RIDE	8.0	7.9	9.0	9.0	8.4	8.5	8.5	8.6	8.6	8.5	8.5	8.5	8.5	8.5	8.5	8.4	8.4		
C/D 0.586	53030000	(0.7C)			21.0																				
4397401	1.567	4.806	L	2021	0012	CRACKING	9.5	9.5	9.0	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	9.4	8.0		
ANDERSON COLUMBIA CO., INC					FC5M	RIDE	8.3	8.3	8.2	8.4	8.3	8.2	8.3	8.4	8.3	8.2	8.3	8.4	8.3	8.6	8.6	8.6	8.6	8.4	
53040000	0.000	7.369	C	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*		
71			2	55	5300	RIDE	8.6	8.6	8.4	8.4	8.0	8.0	8.0	8.0	8.0	7.8	7.7	7.6	7.6	7.6	7.6	7.6	7.6		
BIG BONE LN(0.1L)					9.6																				
4230651	0.000	7.356	C	2013	0012	CRACKING	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	5.5*	
ANDERSON COLUMBIA CO., INC					FC95M	RIDE	7.4	8.8	8.6	8.4	8.3	8.2	8.2	8.0	8.0	7.9	8.1	8.0	7.9	8.1	8.0	7.8	7.4		
53040000	7.369	7.940	R	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.5	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*		
71			1	45	8200	RIDE	8.6	8.6	8.4	8.4	8.0	8.0	8.1	8.0	7.9	7.8	7.7	7.6	7.6	7.6	7.6	7.6	7.6		
CR-280/ROCKY CRK RD(7.5R)					12.0																				
4230651	7.356	7.780	C	2013	0012	CRACKING	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	5.5*		
ANDERSON COLUMBIA CO., INC					FC95M	RIDE	7.4	8.8	8.6	8.4	8.3	8.2	8.2	8.0	8.0	7.9	7.9	8.0	7.9	8.0	7.9	7.9	7.5		
53040000	7.940	8.526	R	1	4	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	10.0		
71			2	45	19700	RIDE	8.4	8.3	8.3	8.1	7.8	7.8	7.6	7.8	7.6	7.5	7.3	7.3	7.3	7.3	7.3	8.2			
SIDE ROAD(8.0C)					9.6																				
4230651	8.044	8.861	C	2013	0012	CRACKING	10.0	10.0		9.4	9.4	9.4	9.3	9.4	9.4	9.2	9.1	9.1	9.1	9.1	8.9	8.5			
ANDERSON COLUMBIA CO., INC					LGD	RIDE	8.2	8.1		8.1	7.9	7.5	8.0	8.1	8.2	8.1	7.7	8.0	8.2	8.0	8.2	8.0			
53040000	8.526	8.853	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.5	8.5			
71			2	45	19700	RIDE	8.4	8.3	8.4	8.3	8.3	8.4	8.2	7.8	7.6	7.5	7.3	7.3	7.3	7.3	7.3	7.6			
WHITE TAIL RD(8.5C)					9.6																				
4457601	8.528	9.301	R	2024	0012	CRACKING	8.5	8.5		8.5	7.5	7.5	7.0	7.0	7.0	6.0*	6.0*	5.5*	8.7	7.5					
ANDERSON COLUMBIA CO., INC					FC95M	RIDE	7.6	7.5		7.4	7.6	7.5	7.3	7.4	7.4	7.2	7.1	7.2	8.2	7.8					
53040000	8.853	10.216	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5			
71			2	45	17500	RIDE	8.5	8.5	8.4	8.3	8.3	8.4	8.2	7.6	8.0	7.3	7.6	7.6	7.6	7.6	7.6	7.6			
ANDERSON COLUMBIA(9.1R)					7.2																				
2193491	8.138	10.217	C	1997	0213	CRACKING	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	6.0*	6.0*	5.5*	3.5*	1.0*					
ANDERSON COLUMBIA CO., INC					FC3	RIDE	7.6	7.5	7.6	7.4	7.6	7.5	7.3	7.4	7.4	7.2	7.1	7.2	7.1	7.1	6.7				
4457601	9.334	10.216	R	2024	0012																				
53040000	8.853	10.216	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5			
71			2	45	17500	RIDE	8.5	8.6	8.5	8.4	8.3	8.3	8.2	8.2	8.3	8.1	7.7	8.1	8.0	8.0	8.0	8.0			
2193491	8.138	10.217	C	1997	0213	CRACKING	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	6.0*	5.5*	3.5*	1.0*						
ANDERSON COLUMBIA CO., INC					FC3	RIDE	8.0	8.0	7.7	7.7	7.8	7.5	7.8	7.8	7.6	7.5	7.5	7.4	7.4	7.3	7.3	6.9			
4457601	8.528	10.216	L	2024	0012																				
53040000	8.600	8.853	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5			
71			2	45	19700	RIDE	8.5	8.6	8.5	8.4	8.3	8.3	8.2	7.6	7.6	7.5	7.5	7.4	7.4	7.4	7.3	8.0			
4457601	8.608	9.301	L	2024	0012	CRACKING	8.5	8.5		8.5	7.5	7.5	7.0	6.0*	5.5*	5.5*	3.5*	3.5*	9.0	8.0					
ANDERSON COLUMBIA CO., INC					FC95M	RIDE	8.0	8.0		7.7	7.8	7.8	7.8	7.6	7.5	7.5	7.4	7.4	7.6	7.6	7.6	7.2			
53040000	7.940	8.600	L	1	4	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	10.0			
71			2	45	19700	RIDE	8.5	8.5	8.2	8.0	7.7	7.8	7.6	7.6	7.6	7.5	7.5	7.4	7.4	7.3	8.5				
SIDE ROAD(8.0C)					9.6																				
4230651	8.044	8.861	C	2013	0012	CRACKING	10.0	10.0		9.4	9.4	9.4	9.3	9.3	9.4	9.5	9.5	9.5	9.5	9.5	9.4	9.0			
ANDERSON COLUMBIA CO., INC					LGD	RIDE	8.5	8.4		8.0	7.7	7.7	8.1	8.0	8.0	8.0	7.5	7.5	7.8	8.0	7.8	7.8			
53040000	7.369	7.940	L	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.5	8.5	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*			
71			1	45	8200	RIDE	8.6	8.6	8.4	8.4	8.0	8.0	7.7	7.6	7.6	7.8	7.7	7.6	7.6	7.6	7.6	7.6			
DOVE REST DR(7.4L)					12.0																				
4230651	7.356	7.780	C	2013	0012	CRACKING	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	5.5*	
ANDERSON COLUMBIA CO., INC					FC95M	RIDE	7.4	8.8	8.6	8.4	8.3	8.2	8.2	8.0	8.0	7.9	7.6	7.6	7.6	7.5	7.5	7.1			
53050000	6.971	10.560	R	1	1	CRACKING	10.0	8.5	8.5	7.5	6.5	3.5*	3.5*	1.0*											
75 231			2	65	12200	RIDE	8.9	8.9	8.8	8.7	7.9	7.6	7.0	6.5											
SPRINGFIELD RD(8.9C)					27.3																				
4397221	7.018	10.495	R	2020	0012	CRACKING	10.0	10.0	8.5	8.5	7.5	7.0	5.5*	4.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.6	7.5			
ANDERSON COLUMBIA CO., INC					FC5M	RIDE	8.4	8.4	8.2	8.5	8.5	8.3	8.4	8.5	9.0	8.9	8.9	8.9	8.8	8.8	8.8	8.6			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = ANDERSON COLUMBIA CO., INC.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = ANDERSON COLUMBIA CO., INC.												
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	RATINGS	SURVEYED YEAR													FUTURE
INTERSECT	AT	(MP)	(SIDE)								2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-F	WKM-F	WKM-F	WKM-F	WKM-F	WKM-F	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
CONTRACTOR	(AGE)	(ONE)	(YEAR)	CONTRACTOR	(AGE)	(ONE)	(YEAR)	CONTRACTOR	(AGE)	(ONE)	(YEAR)	CONTRACTOR	(AGE)	(ONE)	(YEAR)	CONTRACTOR	(AGE)	(ONE)	(YEAR)	CONTRACTOR	(AGE)	(ONE)	(YEAR)	(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F	WKM-F	WKM-F	WKM-F	WKM-F	WKM-F														
53130000	3.373	4.210	L	1	1	CRACKING	10.0	10.0	10.0	10.0	9.0	8.5	8.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0		
69			1	45	2600	RIDE	8.6	8.4	8.5	8.3	7.4	7.7	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.2	6.8	8.4		
4192941	3.374	4.209	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	4.5*
4546191	0.000	8.432	C	2028	0012	RIDE	8.3	8.3	8.1	7.9	7.8	7.7	7.6	7.5	7.3	7.2	7.1	7.0	6.9	6.8	6.4			
53220000	0.000	10.709	C	1	1	CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
273			2	55	3400	RIDE	7.4	8.6	8.4	8.4	8.2	8.1	8.1	8.2	8.2	8.2	8.2	8.2	8.0	8.0	8.0	8.0	8.0	
CR 164(0.5C)	0.000	10.687	C	2020	0012	CRACKING	8.0	8.0	8.0	7.0	7.0	5.5*	5.5*	5.5*				10.0	10.0	10.0	10.0	10.0	8.5	
ANDERSON	COLUMBIA	CO., INC	(2022)		FC95M	RIDE	7.9	7.9	7.8	7.7	7.5	7.5	7.4	7.4				8.4	8.3	8.4	8.3	8.3	7.9	
54001000	5.000	9.993	R	4	1	CRACKING	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	
8 I10	220.8	225.8	2	70	27000	RIDE	8.7	8.6	9.1	9.0	8.6	8.5	8.4	8.5	7.8	8.3	8.4	8.3	8.4	8.3	8.3	8.2	8.2	
4439731	5.677	9.272	C	2022	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	8.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	9.4	8.5	
ANDERSON	COLUMBIA	CO., INC	(2024)		FC5M	RIDE	8.2	8.3	7.8	8.2	8.1	8.4	8.4	8.3	8.4	8.3	8.3	8.3	9.0	8.9	8.9	8.8		
54001000	5.000	9.993	L	4	1	CRACKING	10.0	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
8 I10	220.8	225.8	2	70	27000	RIDE	8.5	8.6	9.1	9.0	8.6	8.5	8.0	8.4	8.3	8.2	8.3	8.2	8.3	8.2	8.2	8.2	8.2	
4439731	5.677	9.272	C	2022	0012	CRACKING	9.0	9.0	9.0	8.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	
ANDERSON	COLUMBIA	CO., INC	(2024)		FC5M	RIDE	8.2	8.2	7.8	8.3	8.2	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.3	9.0	8.9	8.8	
54020000	0.000	7.120	R	1	1	CRACKING	10.0	10.0	9.5	9.5	9.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
20 27			2	65	5400	RIDE	8.9	8.7	9.1	8.7	8.3	8.2	8.0	8.0	8.1	8.2	8.2	8.2	8.1	8.1	8.2	8.2	8.2	
CODY CHURCH(0.9R)	0.736	7.108	C	2021	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	8.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.6	8.0	
ANDERSON	COLUMBIA	CO., INC	(2022)		FC5M	RIDE	8.1	8.2	8.1	8.4	8.4	8.6	8.5	8.5	8.5	8.5	8.5	8.9	8.9	8.9	8.9	8.8	8.6	
54020000	0.000	7.120	L	1	1	CRACKING	9.5	8.0	7.0	6.5	4.5*	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5		
20 27			2	65	5400	RIDE	8.5	8.7	8.5	8.0	7.5	7.3	7.0	6.9	8.1	8.0	7.8	7.6	7.5	7.5	7.5	7.5	7.5	
GAMBLE RD(3.4C)	0.736	7.108	C	2021	0012	CRACKING	8.5	8.5	8.5	8.5	7.0	7.0	5.5*	5.5*	5.5*			10.0	10.0	10.0	10.0	9.7	8.0	
4415431	0.736	7.108	C	2021	0012	RIDE	7.0	7.5	7.2	7.8	7.8	7.9	7.8	7.8	7.7			8.5	8.4	8.5	8.3	8.3	8.3	
ANDERSON	COLUMBIA	CO., INC	(2023)		FC5M																			
54040000	0.000	6.002	C	1	1	CRACKING	9.0	9.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
55 221			2	60	800	RIDE	7.9	7.9	7.9	8.7	8.5	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	
BAILEY RD(0.9R)	0.000	6.002	C	2021	0012	CRACKING	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	
ANDERSON	COLUMBIA	CO., INC	(2023)		FC95M	RIDE	7.9	8.0	7.5	7.7	7.8	7.8	7.7	7.8	7.7	7.7	7.5	6.0*	10.0	10.0	10.0	10.0	8.5	
55050000	4.164	4.627	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
61			4	45	47000	RIDE	8.5	8.0	8.1	8.1	7.7	7.5	7.6	7.8	7.4	7.4	7.4	7.4	6.8	8.2	8.1	8.0	8.0	
I 10(4.4R)	4.203	4.651	C	2006	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.2	5.0*
2225932	1.145	5.143	C	2027	0012	RIDE	8.1	8.1	8.1	7.0	7.4	7.4	7.3	7.3	7.3	7.3	7.3	7.1	7.3	7.3	7.3	7.3	6.9	
4529381	1.145	5.143	C	2027	0012																			
55050000	4.164	4.627	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
61			3	45	47000	RIDE	8.7	8.2	8.4	8.4	7.9	7.7	7.6	8.0	7.7	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	
55320043	EB OFF(4.4L)				2.5																			
2225932	4.203	4.651	C	2006	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
ANDERSON	COLUMBIA	CO., INC	(2010)		FC125	RIDE	8.1	8.1	8.1	7.5	7.8	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	
4529381	1.145	5.143	C	2027	0012																			
55320000	7.000	10.137	R	4	1	CRACKING	10.0	9.5	9.5	8.0	7.0	6.5	6.5	4.5*						10.0	10.0	10.0		
8 I10	200.6	203.7	3	70	70094	RIDE	8.8	8.7	8.6	8.6	7.9	7.8	7.8	8.0						8.3	8.3	8.3		
2225932	7.008	8.535	C	2006	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	
ANDERSON	COLUMBIA	CO., INC	(2010)		FC5M	RIDE	8.3	8.3	8.3	8.4	8.4	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	
2225896	4.580	10.137	C	2026	0012																			
55320000	7.000	10.137	L	4	1	CRACKING	9.5	9.5	9.5	8.0	7.0	6.5	6.5	4.5*						10.0	10.0	10.0		
8 I10	200.6	203.7	3	70	70094	RIDE	9.0	8.8	8.8	8.7	8.0	7.9	7.8	8.3						8.4	8.3	8.4		
2225932	7.008	8.535	C	2006	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	
ANDERSON	COLUMBIA	CO., INC	(2010)		FC5M	RIDE	8.4	8.3	8.3	8.5	8.5	8.7	8.6	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	
2225896	4.580	10.137	C	2026	0012																			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 3 CONTRACTOR = ANDERSON COLUMBIA CO., INC. -----																								
RDWYID	SR	US	G BMP	EMP LN	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR														FUTURE
INTERSECT AT (MP SIDE)								RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-F	WKM-F	WKM-F	=====	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
CONTRACTOR (AGE ONE YEAR)																						(PMRS)		
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F	WKM-F	WKM-F																	
56040000	0.000	25.610	C	1	1	CRACKING	10.0	10.0	8.5	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*				
65			2	60	600	RIDE	8.7	8.6	8.5	8.5	7.7	7.5	7.6	7.4	7.4	7.4	7.1	7.1	7.1	6.9				
CHERRY ST(0.0L)					17.2																			
4169451	0.000	25.608	C	2010	0221	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.5	7.5	7.6	5.5*		
ANDERSON COLUMBIA CO., INC(2013)					FC95M	RIDE	8.8	8.7	8.5	8.4	8.2	7.9	7.7	7.5	7.7	7.5	7.3	7.1	6.9	6.6	6.7	6.3*		
57002000	0.000	3.112	R	4	1	CRACKING	6.4*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.5			
8 I10	42.5	45.6	2	70	37000	RIDE	7.2		8.7	8.6	8.5	8.3	8.0	8.3	8.0	8.3	8.3	8.2	8.0	7.7	7.4			
4327371	0.000	2.602	C	2016	0012	CRACKING	8.5	7.0	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.3	6.5		
ANDERSON COLUMBIA CO., INC(2017)					FC5M	RIDE	7.3	7.2	6.9	7.6	8.8	8.9	8.6	8.6	8.6	8.8	8.8	8.7	8.7	8.6	8.5			
57002000	3.112	8.283	R	4	1	CRACKING	8.6	8.6		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
8 I10	45.6	50.7	2	70	32484	RIDE	6.6	6.0*		8.8	8.4	8.3	8.3	8.2	8.2	8.2	8.2	8.2	8.0	7.9				
4348371	3.112	8.283	C	2017	0012	CRACKING	9.0	9.0	9.0	9.0	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.0			
ANDERSON COLUMBIA CO., INC(2019)					FC5M	RIDE	7.7	7.8	7.7	8.1	8.0		8.8	8.9	9.0	8.9	8.8	8.7	8.7	8.6				
57002000	8.283	16.975	R	4	1	CRACKING	6.5	6.5		3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	9.0	9.0				
8 I10	50.7	59.4	2	70	32484	RIDE	8.6	8.5		7.7	6.6	5.8*		8.2	8.3	8.3	8.3	8.3	8.2	8.1				
4088781	8.201	16.949	C	2004	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0			
ANDERSON COLUMBIA CO., INC(2007)					FC5	RIDE	8.1	8.0	7.9	8.3	8.3	8.5	8.2	7.5	8.4	8.5	8.5	8.5	8.4	8.3	8.2			
4458151	9.312	16.975	R	2023	0012																			
57002000	8.283	16.975	L	4	1	CRACKING	6.5	6.5		3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0				
8 I10	50.7	59.4	2	70	32484	RIDE	8.4	8.1		7.1	6.1*	5.3*		8.1	8.3	8.3	8.3	8.3	8.3	8.2				
4088781	8.201	16.949	C	2004	0012	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	4.5*	4.5*	4.5*	1.5*		
ANDERSON COLUMBIA CO., INC(2007)					FC5	RIDE	8.3	8.2	8.1	8.4	8.4	8.5	8.3	8.4	8.5	8.5	8.5	8.4	8.4	8.2	8.1			
57002000	3.112	8.283	L	4	1	CRACKING	0.0*	7.9		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5			
8 I10	45.6	50.7	2	70	32484	RIDE	6.3*	6.1*		8.8	8.4	8.2	8.2	8.2	8.2	8.2	8.1	8.0	7.9	7.7				
4348371	3.112	8.283	C	2017	0012	CRACKING	8.5	8.5	7.0	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5			
ANDERSON COLUMBIA CO., INC(2019)					FC5M	RIDE	7.6	7.5	7.5	8.0	8.0		8.6	8.8	8.9	8.9	8.9	8.7	8.7	8.6	8.5			
57002000	0.000	3.112	L	4	1	CRACKING	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5			
8 I10	42.5	45.6	2	70	37000	RIDE	7.5		9.1	8.9	8.6	8.4	8.4	8.3	8.2	8.2	8.0	8.0	7.7	7.2				
4327371	0.000	2.602	C	2016	0012	CRACKING	7.0	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.0			
ANDERSON COLUMBIA CO., INC(2017)					FC5M	RIDE	7.3	7.0	6.9	7.6	8.8	8.9	8.7	8.8	9.0	9.0	9.0	8.9	8.8	8.8	8.7			
57010000	11.344	13.251	R	1	1	CRACKING	7.0	6.5	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0				
10 90			2	55	16896	RIDE	8.5	8.7	8.6	8.2	7.5	7.1		8.2	8.2	8.2	8.2	8.1	8.1	8.1				
ANTIUCH RD(11.6R)					8.6																			
4415421	11.596	13.192	R	2021	0012	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	6.5	4.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	8.5			
ANDERSON COLUMBIA CO., INC(2024)					FC5M	RIDE	8.1	8.0	7.8	7.9	8.0	8.1	7.7	7.9	7.6	7.1	8.5	8.5	8.5	8.5	8.3			
57010000	11.344	13.300	L	1	1	CRACKING	7.0	6.5	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	8.5				
10 90			2	55	16896	RIDE	8.1	8.4	8.1	8.0	7.3	7.0		8.2	8.2	8.2	8.2	8.1	8.0					
GREENLEAF PL(11.6L)					8.6																			
4415421	11.596	13.192	L	2021	0012	CRACKING	8.5	8.5	7.5	6.5	6.5	6.5	6.5	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	8.5			
ANDERSON COLUMBIA CO., INC(2023)					FC5M	RIDE	8.0	8.0	8.0	7.8	8.2	8.1	8.0	8.1	8.1	8.0	8.5	8.6	8.6	8.4				
57040000	7.785	9.575	R	1	1	CRACKING	5.5*	5.5*	5.5*	3.5*	4.5*	3.5*		10.0	10.0	9.0	9.0	9.0						
85			2	55	25000	RIDE	8.9	8.8	8.8	8.6	8.2	8.1		8.1	8.2	8.1	8.2	8.0						
AIRPORT(8.8R)					6.2																			
2202311	7.829	9.070	C	2009	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.3	5.0*				
ANDERSON COLUMBIA CO., INC(2013)					FC5M	RIDE	8.0	8.2	8.2	8.2	8.2	8.2	8.1	8.2	8.2	8.2	8.2	8.1	8.0	8.1	7.9			
57040000	11.623	12.250	R	1	1	CRACKING	10.0	10.0	10.0	10.0	8.5	7.5	7.5	7.5	10.0	8.5	7.5	7.0	7.0					
85			2	35	23500	RIDE	7.7	7.4	8.3	7.3	6.6	6.2	7.2	7.0	6.8	7.1	6.9	7.6	6.8					
EDGE AVE(11.8R)					5.9																			
4287411	11.623	12.168	C	2016	0012	CRACKING	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.6	7.0			
ANDERSON COLUMBIA CO., INC(2017)					FC95M	RIDE	6.7	6.4	6.6	7.2	8.2	8.1	8.1	7.7	8.0	7.9	8.0	7.8	7.8	7.4				
4508191	11.600	13.338	C	2026	0012																			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3															CONTRACTOR = ANDERSON COLUMBIA CO., INC.									
RDWYID	SR	US	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR										FUTURE			
INTERSECT	AT	(MP)	(SIDE)								2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	W	BMP	W	EMP	RW	FY-P	W	KMX-P																
CONTRACTOR	(AGE ONE YEAR)						SURF TYPE																	
ITMSEG-F	W	BMP	W	EMP	RW	FY-F	W	KMX-F																2030 (PMRS)
61010000	13.330	13.609	C	1	8	CRACKING	7.5	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5		
10 90			2	55	4223	RIDE	7.6	7.2	7.2		8.2	8.2	8.2	8.5	8.4	8.2	8.3	8.3	8.3	8.3	8.3	8.0		
2207991	13.465	16.325	C	2002	0012	CRACKING	9.5	9.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	6.5	6.5	5.5*	5.5*	5.5*	5.0*			
ANDERSON	COLUMBIA CO., INC				FC125	RIDE	8.1	7.9	7.9	7.8	7.7	7.7	7.7	7.4	7.5	7.4	7.3	7.2	7.2	7.2	7.2			
61010000	17.955	18.115	R	1	1	CRACKING	6.5	6.5	6.5	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0		
10 90			2	35	7700	RIDE	7.0	6.2*	5.6	5.4*	5.2*	5.1*	5.0*		7.4	7.0	6.8	6.9	6.9	6.9	6.9	7.0		
SIXTH ST(18.0C)					8.7																			
4090221	17.500	19.045	C	2005	0012	CRACKING	7.0	7.0	6.5	6.0*	6.0*	6.0*	5.5*	5.5*	2.5*	2.5*	2.5*					5.0*	3.0*	
ANDERSON	COLUMBIA CO., INC				FC95M	RIDE	6.5	6.2	6.2	6.3	6.2	6.1	5.9	5.7	5.5	5.4*	5.3*					5.2*	4.8*	
4269731	16.277	19.082	C	2022	0012																			
61010000	17.955	18.115	L	1	8	CRACKING	6.5	6.5	6.5	6.5	6.5	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0		
10 90			2	35	7700	RIDE	7.8	7.4	7.2	7.3	6.6	6.5	6.4		8.0	8.0	7.7	7.6	7.6	7.6	7.6	7.4		
SIXTH ST(18.0C)					8.7																			
4090221	17.500	19.045	C	2005	0012	CRACKING	7.0	7.0	6.0*	6.0*	6.0*	6.0*	4.5*	5.5*	2.5*	2.5*	2.5*							
ANDERSON	COLUMBIA CO., INC				FC95M	RIDE	7.3	7.2	6.9	6.5	6.6	6.5	6.3	5.7	5.9	5.8	5.7							
4269731	16.277	19.082	C	2022	0012																			
61060000	0.200	14.205	C	1	1	CRACKING	9.5	9.5	9.5	7.0	7.0	7.0	7.0	6.5	6.5						10.0	10.0		
277			2	60	2800	RIDE	9.0	8.7	8.9	8.7	8.1	8.0	8.2	8.3	8.2						8.5	8.3		
CR 278(0.4R)					13.8																			
4153821	0.004	14.200	C	2009	0012	CRACKING	10.0	8.5	8.5	8.5	8.5	8.5	7.5	7.5	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	3.5*	
ANDERSON	COLUMBIA CO., INC				FC125	RIDE	8.4	7.9	8.3	8.3	8.2	8.3	8.1	8.1	8.1	8.1	8.0	8.0	8.0	8.0	7.9	7.5		
4508071	0.200	14.191	C	2026	0012																			
61080000	24.183	25.405	R	1	1	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	8.0	8.0		
77			1	45	17000	RIDE	7.1	7.4	8.6	8.5	8.2	8.4	8.3	8.4	8.5	8.1	8.3	7.8	8.1					
SHOPPING CENTER(24.2R)					7.1																			
4346671	24.183	25.405	R	2017	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.0	6.5		
ANDERSON	COLUMBIA CO., INC				FC95M	RIDE	7.9	7.8	7.9	7.5	7.7	8.4	8.4	8.4	8.4	8.4	8.3	8.4	8.1	8.2	8.2	7.8		
61080000	26.986	29.826	C	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	7.0	6.5	6.5	6.5	6.5	6.5	6.5	10.0			
77			2	55	3700	RIDE	9.1	8.6	8.9	8.7	8.4	8.2	8.2	8.3	8.2	8.3	8.0	8.0	8.0	8.0	8.3			
HOLLEY AVE(27.1R)					9.3																			
4246251	27.783	29.826	C	2012	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	5.2*	3.5*			
ANDERSON	COLUMBIA CO., INC				FC95M	RIDE	8.1	7.7	7.3	7.2	7.1	6.9	6.5	6.3*	6.4*	6.1*	6.1*	6.0*	5.9*	5.5*				
2207622	26.904	29.826	C	2025	0012																			
61080000	24.183	25.405	L	1	1	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	8.0	8.0	8.0			
77			1	45	17000	RIDE	7.1	7.4	8.6	8.5	8.2	8.4	8.3	8.4	8.5	8.1	8.3	7.8	8.1					
SHOPPING CTR(24.2L)					7.1																			
4346671	24.183	25.405	L	2017	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.1	5.5*			
ANDERSON	COLUMBIA CO., INC				FC3	RIDE	7.9	7.8	7.9	7.5	7.7	8.4	8.4	8.4	8.3	8.3	8.4	8.3	8.3	8.3	7.9			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = ANDERSON COLUMBIA COMPANY																			
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR													FUTURE									
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012										
INTERSECT AT (MP SIDE) %T =====																													
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030									
CONTRACTOR (AGE ONE YEAR)	SURF TYPE																			(PMRS)									
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																								
57010000	13.251	14.234	R	1	1	CRACKING	8.0	6.5	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0										
10 90			2	35	20500	RIDE	8.6	8.6	8.5	8.2	7.6	7.2		8.0	8.3	8.3	8.3	8.3	8.2										
CAYSON AVE(13.5C) 11.3																													
4457581	13.317	14.232	R	2023	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	3.5*	3.5*	10.0	10.0	8.5									
ANDERSON COLUMBIA COMPANY	FC125 RIDE																			8.0									
57010000	13.300	14.234	L	1	1	CRACKING	6.5	6.5	4.5*	3.5*	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0										
10 90			2	35	20500	RIDE	8.3	8.3	8.3	7.9	7.2	7.0		8.1	8.3	8.1	8.3	8.2	8.1										
CAYSON AVE(13.5C) 11.3																													
4457581	13.317	14.232	L	2023	0012	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	7.0	5.5*	5.5*	3.0*	3.0*	10.0	10.0	8.5									
ANDERSON COLUMBIA COMPANY	FC125 RIDE																			8.1									

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3 CONTRACTOR = APAC-FLORIDA INC

[illegible]

**" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 **" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.

2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = APAC-FLORIDA INC																				
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR																						FUTURE
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012											
INTERSECT AT (MP SIDE)					%T	=====																								
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P																									
CONTRACTOR (AGE ONE YEAR)					SURF TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025											
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																								2030 (PMRS)	
57030000	11.600	11.847	L	1	8	CRACKING	3.5*	3.5*	3.5*		10.0	10.0	10.0	8.5	7.0	6.5	6.5	6.5	7.0											
30 98			2	25	49000	RIDE	5.8*	5.5*	5.2*		7.5	7.6	7.5	6.5	6.7	6.5	6.5	6.4	5.9											
FERRY RD SE(11.6L)					4.4																									
2202451	4.657	11.837	C	2002	0012	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*	5.5*												
APAC-FLORIDA INC				(2004)	FC125	RIDE	5.9	5.3*	5.2*	5.5	5.3*	5.4*	5.2*	5.2*	5.2*	5.0*	4.9*	4.6*												
57030000	6.146	11.600	L	1	8	CRACKING	7.0	5.5*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0											
30 98			2	40	43500	RIDE	7.9	7.9	7.5		8.1	8.0	7.8	7.8	7.9	7.9	7.8	7.7	7.6											
SIDE ROAD(6.2C)					4.8																									
2202451	4.657	11.837	C	2002	0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	6.0*	6.0*	6.0*	6.0*												
APAC-FLORIDA INC				(2004)	FC125	RIDE	7.6	7.3	7.3	7.2	7.2	7.4	7.0	7.1	6.9	6.9	6.9	6.6												
4373661	4.657	11.704	C	2023	0012																									
57030000	4.657	5.142	L	1	8	CRACKING	7.0	5.5*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0											
30 98			2	45	48000	RIDE	7.9	7.9	7.5		8.1	8.0	7.8	7.8	7.9	7.9	7.8	7.7	7.6											
JOSIE RD(4.7L)					4.9																									
2202451	4.657	11.837	C	2002	0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*													
APAC-FLORIDA INC				(2004)	FC125	RIDE	7.6	7.3	7.9	7.5	7.6	7.6	7.4	7.4	7.3	7.3	7.3													
4373661	4.657	11.704	C	2023	0012																									

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = APAC-FLORIDA, INC																					
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR																				FUTURE			
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012												
INTERSECT AT (MP SIDE)					%T	=====																									
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P																										
CONTRACTOR (AGE ONE YEAR)					SURF TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030						(PMRS)					
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F																										
48003000	6.750	7.281	L	1	1	CRACKING	7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5												
289			2	45	24000	RIDE	6.4*	8.5	8.3	8.1	8.0	6.8	7.4	6.7	8.2	7.6	8.3	8.1	8.0												
BEAU TERRA LN(6.8C)																															
2186201	6.696	7.281	C	1999	0213	CRACKING	9.5	9.5	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	4.4*	2.0*											
APAC-FLORIDA, INC																															
4269342	6.053	7.281	L	2024	0012		7.6	8.2	7.7	7.3	7.4	7.2	7.5	7.4	7.0	7.0	7.3	7.1	7.0	6.6											
48040000	1.120	2.900	R	1	1	CRACKING	8.0	8.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	8.0	7.5	6.5	6.5												
95 29			2	40	11500	RIDE	6.2*	6.1*	7.7	7.8	7.6	7.1	7.4	7.3	7.5	7.4	7.4	7.3	7.4												
E CROSS ST(1.2R)																															
2186691	1.120	2.974	C	2001	0012	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.0*	6.0*	6.0*	6.0*	6.0*	5.5*	5.5*	3.0*											
APAC-FLORIDA, INC																															
4325681	0.000	3.524	C	2023	0012		7.2	7.2	7.1	6.4	6.8	6.9	6.9	6.7	6.7	6.5	6.4	6.4	6.4	6.0											
48040000	1.120	2.900	L	1	1	CRACKING	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	8.0	8.0	7.5	7.5	6.5	6.5												
95 29			2	40	11500	RIDE	5.9*	5.9*	8.2	7.7	7.5	7.6	7.3	7.4	7.4	7.1	7.1	7.2	7.0												
SCOTT ST W(1.1L)																															
2186691	1.120	2.974	C	2001	0012	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	3.5*	3.0*	0.5*											
APAC-FLORIDA, INC																															
4325681	0.000	3.524	C	2023	0012		7.1	6.9	6.5	7.0	6.6	6.9	6.8	6.8	6.8	6.6	6.6	6.7	6.5	6.1											
58050000	2.065	6.212	R	1	1	CRACKING	10.0	10.0		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5												
87			2	45	16317	RIDE	8.3	7.9		8.9	8.6	8.6	8.5	8.5	8.5	8.5	8.4	8.3	8.3												
RIDGE CREST DR(2.1R)																															
2204051	2.071	6.597	C	2000	0213	CRACKING	9.5	9.5	9.5	9.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.3	5.0*											
APAC-FLORIDA, INC																															
4529451	0.000	6.281	C	2028	0012		8.2	8.1	8.1	8.2	8.1	8.0	7.9	7.9	8.0	7.9	7.9	7.9	7.9	7.5											
58050000	2.065	6.212	L	1	1	CRACKING	10.0	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0												
87			2	45	16317	RIDE	8.3	7.9		8.7	8.5	8.5	8.3	8.1	8.2	8.4	8.2	8.3	8.3												
ROSASCO ST(2.2L)																															
2204051	2.071	6.597	C	2000	0213	CRACKING	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	4.5*											
APAC-FLORIDA, INC																															
4529451	0.000	6.281	C	2028	0012		8.3	8.2	8.2	8.3	8.3	8.3	8.2	8.2	8.2	8.2	8.2	8.3	8.2	7.8											

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3							CONTRACTOR = ARCHER WESTERN CONTRACTORS L															
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR															FUTURE
SR	US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT	AT	(MP)	(SIDE)			%T	=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P																	
CONTRACTOR	(AGE	ONE YEAR)		SURF	TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																(PMRS)	
48013000	0.396	1.336	C	1	1	CRACKING	7.5	7.5	7.5	7.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
742			2	35	11300	RIDE	7.9	8.0	7.5	7.3	6.9	6.8	7.2	7.0	7.2	7.2	6.9	7.1	7.2			
RHODA DR(0.5R)																						
2224341	0.381	1.428	C	2002	0213	CRACKING	10.0	10.0	10.0	10.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	5.9*	3.5*	
ARCHER WESTERN CONTRACTORS(2006)							FC125															
4529471	0.000	1.336	C	2027	0012	RIDE	7.0	7.2	6.5	6.1	6.6	6.6	6.4	6.3	6.3	6.2	6.2	6.2	6.2	6.2	5.8	
55320000	4.580	7.000	R	4	1	CRACKING	10.0	9.5	9.5	8.0	7.0	6.5	6.5	4.5*				10.0	10.0	10.0		
8	I10	198.1	200.6	3	70	70094	RIDE	8.8	8.7	8.6	8.6	7.9	7.8	7.8	8.0			8.3	8.4	8.3		
2225892	4.580	5.936	C	2006	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	6.5	6.5	6.5	6.5	5.5*	2.5*		
ARCHER WESTERN CONTRACTORS(2010)							FC5M															
2225896	4.580	10.137	C	2026	0012	RIDE	8.3	8.1	8.2	8.4	8.3	8.4	8.4	8.4	8.4	8.4	8.3	8.2	8.1	8.0		
55320000	4.573	7.000	L	4	1	CRACKING	9.5	9.5	9.5	8.0	7.0	6.5	6.5	4.5*				10.0	10.0	10.0		
8	I10	198.1	200.6	3	70	70094	RIDE	9.0	8.8	8.8	8.7	8.0	7.9	7.8	8.3			8.4	8.4	8.3		
2225892	4.580	5.936	C	2006	0213	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.0	9.0	8.0	7.5	7.5	6.5	6.5	3.5*		
ARCHER WESTERN CONTRACTORS(2010)							FC5M															
2225896	4.580	10.137	C	2026	0012	RIDE	8.3	8.2	8.2	8.4	8.4	8.5	8.5	8.5	8.5	8.5	8.4	8.3	8.2	8.1		

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3							CONTRACTOR = BAKER INFRASTRUCTURE GROUP I															
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR														FUTURE	
SR	US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)																						
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P	%T	=====															
CONTRACTOR	(AGE ONE YEAR)				SURF_TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																	(PMRS)
61040000	2.332	12.489	R	1	1	CRACKING		5.5*	4.5*		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	7.0	7.0		
79			2	55	6400	RIDE		8.5	8.4		8.3	8.1	8.2	8.1	8.3	8.3	8.2	8.1	8.1	8.0		
HENRY LN(4.1R)																						
2207734	2.332	8.850	C	2011	0213	CRACKING					10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5	7.5	8.3	5.5*	
BAKER INFRASTRUCTURE GROUP(2016)							FC5M	RIDE		8.7	8.6	8.5	8.3	8.3	8.2	8.0	8.0	8.0	8.1	8.1	7.9	

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3															CONTRACTOR = C. W. ROBERTS CONTRACTING, I											
RDWYID	SR	US	BMP	G BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	RATINGS	SURVEYED YEAR										FUTURE					
INTERSECT AT (MP SIDE)											2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-F	WKM-F					2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
CONTRACTOR (AGE ONE YEAR)																								(PMRS)		
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F	WKM-F																				
46050000	0.000	7.716	C	1	1	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0			
20			2	60	5400	RIDE					9.1	9.1	9.1	8.7	8.7	8.5	8.6	8.5	8.5	8.5	8.5	8.5	8.4			
AMETHYST LN(6.5L)					20.3																					
4397441	0.000	7.567	C	2023	0012	CRACKING					8.0	7.5	7.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	8.5		
C. W. ROBERTS CONTRACTING, (2024)					FC95M	RIDE					8.3	8.2	8.1	8.2	8.2	8.0	8.1	8.1	8.0	8.0	8.0	9.0	9.0	8.5		
46060000	7.731	9.901	R	1	1	CRACKING					10.0	10.0	10.0	10.0	10.0	8.5		10.0	10.0	10.0	10.0	10.0	10.0			
77			2	45	30000	RIDE					8.4	8.3	8.1	8.0	7.4	7.3		8.4	8.4	8.4	8.4	8.4	8.4	8.3		
GRASSY POINT RD(7.9R)					5.4																					
2179471	7.553	10.219	C	2004	0213	CRACKING					10.0	10.0	10.0	7.5	7.5	7.5	6.5	6.5	7.0	7.0	7.0	7.0	8.0	8.5	6.5	
C. W. ROBERTS CONTRACTING, (2007)					FC125	RIDE					8.3	8.3	8.2	8.1	8.1	8.0	8.0	7.9	7.7	7.7	7.5	7.5	7.5	7.1		
46060000	7.731	9.901	L	1	1	CRACKING					10.0	10.0	10.0	10.0	10.0	8.5		10.0	10.0	10.0	10.0	10.0	10.0			
77			2	45	30000	RIDE					8.4	8.3	8.1	8.0	7.4	7.3		8.2	8.3	8.4	8.4	8.4	8.4	8.3		
MCKENZIE RD(8.1L)					5.4																					
2179471	7.553	10.219	C	2004	0213	CRACKING					10.0	9.0	8.5	7.0	7.0	7.0	6.5	6.5	7.0	7.0	7.0	7.0	8.0	8.1	6.0*	
C. W. ROBERTS CONTRACTING, (2007)					FC125	RIDE					8.3	8.3	8.2	8.1	8.0	7.9	7.8	7.8	7.3	7.3	7.1	7.1	7.0	7.0	6.6	
46080000	1.813	2.765	C	1	1	CRACKING					10.0	10.0	10.0		10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	7.5			
22			2	45	19900	RIDE					8.7	8.6	8.6		7.8	7.7	7.3	7.4	7.6	7.3	7.4	7.3	7.3			
KIMBREL AVE N(2.1R)					6.8																					
4307881	2.171	2.762	C	2015	0012	CRACKING					7.5	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.4	6.5		
C. W. ROBERTS CONTRACTING, (2017)					FC125	RIDE					6.9	7.3	7.2		8.4	8.4	8.3	8.3	8.2	8.3	8.2	8.2	8.2	8.2	7.8	
46080000	2.765	13.681	C	1	1	CRACKING					8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*		
22			2	60	4500	RIDE					8.8	8.7	8.6	8.4	8.1	7.8	7.4	7.3	7.3	6.9	6.9	6.7	6.6			
CR 22A(2.8C)					6.6																					
4216401	7.500	12.616	C	2012	0012	CRACKING						10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	8.7	7.0		
C. W. ROBERTS CONTRACTING, (2014)					FC125	RIDE						8.4	8.4	8.3	8.3	8.3	8.2	8.2	8.0	8.0	7.9	7.7	7.8	7.4		
46090000	5.648	8.366	R	1	8	CRACKING					10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	6.5		10.0	10.0	10.0			
79			2	55	16200	RIDE					8.7	8.7	8.7	8.7	8.4	8.3	8.1	8.1	8.2		8.7	8.6	8.6			
OLD HWY 79(5.7R)					7.8																					
2179113	5.798	8.366	C	2008	0213	CRACKING					10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*				
C. W. ROBERTS CONTRACTING, (2010)					FC5	RIDE					8.6	8.6	8.5	8.6	8.5	8.5	8.6	8.6	8.5	8.4	8.3	8.2				
4377632	5.648	14.302	C	2024	0012																					
46090000	8.366	14.348	R	1	8	CRACKING					10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	6.5		10.0	10.0	10.0			
79			2	65	16200	RIDE					8.7	8.7	8.7	8.7	8.4	8.3	8.1	8.1	8.2		8.5	8.5	8.5			
VINSON RD(9.4R)					7.8																					
2179114	8.347	14.340	C	2007	0213	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.0*				
C. W. ROBERTS CONTRACTING, (2010)					FC5	RIDE					8.5	8.4	8.3	8.5	8.5	8.4	8.5	8.5	8.5	8.5	8.5	8.4	8.4			
4377632	5.648	14.302	C	2024	0012																					
46090000	8.366	14.348	L	1	8	CRACKING					10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	6.5		10.0	10.0	10.0			
79			2	65	16200	RIDE					8.7	8.7	8.7	8.7	8.4	8.3	8.1	8.1	8.2		8.6	8.6	8.5			
CR 2296(12.4L)					7.8																					
2179114	8.347	14.340	C	2007	0213	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	6.5	6.5	6.5	5.5*				
C. W. ROBERTS CONTRACTING, (2010)					FC5	RIDE					8.5	8.4	8.3	8.6	8.6	8.5	8.6	8.4	8.4	8.4	8.4	8.4	8.2			
4377632	5.648	14.302	C	2024	0012																					
46090000	5.648	8.366	L	1	8	CRACKING					10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.5	6.5		10.0	10.0	10.0			
79			2	55	16200	RIDE					8.7	8.7	8.7	8.7	8.4	8.3	8.1	8.1	8.2		8.7	8.6	8.6			
MARILYN RD(7.3L)					7.8																					
2179113	5.798	8.366	C	2008	0213	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	6.5	6.5	6.5	6.0*				
C. W. ROBERTS CONTRACTING, (2010)					FC5	RIDE					8.6	8.6	8.5	8.5	8.5	8.5	8.5	8.4	8.3	8.2	8.1	8.1				
4377632	5.648	14.302	C	2024	0012																					
46130000	0.000	1.243	C	1	1	CRACKING					10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	7.0	7.0			
389			2	35	8500	RIDE					7.6	7.4	7.8	7.1	7.4	7.4	7.1	7.0	6.4	7.0	6.9	6.3	6.4			
SR 30(0.0C)					12.2																					
4287441	0.078	0.664	C	2014	0012	CRACKING					6.5	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.4	6.5		
C. W. ROBERTS CONTRACTING, (2015)					FC95M	RIDE					6.8	6.5	8.6	8.1	8.0	7.6	8.1	8.0	8.1	8.0	8.0	8.0	7.8	7.4		
46140000	1.198	2.021	R	1	1	CRACKING					10.0	10.0	10.0	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0			
368			2	45	37500	RIDE					8.1	8.1	8.0	8.0	7.2		8.1	8.1	8.3	8.0	8.0	7.8	7.7			
GRANT AVE(1.3C)					3.7																					
4039252	1.206	2.015	C	2004	0012	CRACKING					10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	7.5	7.5	8.0	8.6	6.5		
C. W. ROBERTS CONTRACTING, (2006)					FC125	RIDE					7.4	7.9	7.9	7.8	7.5	7.2	7.2	7.5	7.3	7.4	7.4	7.2	7.2	6.8		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = C. W. ROBERTS CONTRACTING, I												
RDWYID	SR	US	BMP	G BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	RATINGS	SURVEYED YEAR													FUTURE
INTERSECT AT (MP SIDE)						LN	SPEED	AADT	%T	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	W BMP	W BMP	W EMP	W EMP	W EMP	W EMP	FY-P	WKM-F	WKM-F		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
CONTRACTOR (AGE ONE YEAR)																								(PMRS)
ITMSEG-F	W BMP	W BMP	W EMP	W EMP	W EMP	W EMP	FY-F	WKM-F	WKM-F															
46160000	5.679	6.760	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	
30A 98			3	45	46000	RIDE	8.6	8.4	8.8	8.4	7.5	7.4	8.0	7.8	8.2	8.0	8.1	8.0	7.8					
HEATHER(5.7L)					5.5																			
4193121	5.679	6.760	C	2013	0012	CRACKING	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.6	6.0*
C. W. ROBERTS CONTRACTING, (2014)					FC95M	RIDE	7.7	8.9	8.8	8.7	8.6	8.5	8.5	8.4	8.5	8.4	8.5	8.4	8.5	8.5	8.5	8.5	8.5	8.1
47020000	20.728	21.470	C	1	1	CRACKING	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	
71			2	35	8200	RIDE	5.1*	4.7*	5.1*	5.1*	7.8	6.7	6.9	6.5	6.6	6.1	6.5	6.6	6.4					
SHERRY AVE(20.8R)					11.3																			
2180651	20.762	21.626	C	2003	0012	CRACKING	9.0	9.0	9.0	9.0	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	5.5*	3.3*	1.0*	
C. W. ROBERTS CONTRACTING, (2004)					FC125	RIDE	6.3	6.5	6.1	6.0	5.7	6.0	6.0	5.7	6.0	6.0	5.7	5.8	5.6	5.6	5.5	5.3*	4.9*	
4457621	11.082	21.490	C	2025	0012																			
47030000	0.000	3.226	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	
69			2	55	4000	RIDE	8.8	8.8	8.6	8.5	8.2	8.1	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.9	8.0	8.0	8.0	
BLOUNTSTOWN CITY LIMITS(0.0C)					9.9																			
4436471	0.051	3.226	C	2022	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	10.0	10.0	10.0	8.5
C. W. ROBERTS CONTRACTING, (2023)					FC3	RIDE	7.9	8.0	7.4	8.0	8.0	8.1	8.0	7.9	7.9	7.9	8.0	8.5	8.5	8.5	8.4	8.0	8.0	
47040000	15.795	25.062	C	1	1	CRACKING	7.5	7.5	7.5	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	
73			2	60	2200	RIDE	8.3	8.2	8.3	7.9	8.7	8.5	8.5	8.4	8.3	8.4	8.3	8.3	8.3	8.3	8.3	8.3	8.3	
DEMONT RD(15.8R)					16.6																			
4039221	15.596	25.127	C	2003	0012	CRACKING	9.5	9.5	9.5	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	4.9*	2.5*
C. W. ROBERTS CONTRACTING, (2004)					FC125	RIDE	8.2	8.2	7.8	8.0	7.8	8.0	7.8	7.9	7.8	7.9	7.8	7.7	7.7	7.7	7.5	7.5	7.1	
4529361	15.795	25.062	C	2027	0012																			
48050000	19.852	23.676	R	1	1	CRACKING	4.5*	4.5*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	
292 98			2	40	19800	RIDE	5.4*	5.1*	4.5*	4.2*	3.5*		7.3	7.0	6.9	6.8	7.0	6.9	7.0	7.0	6.9	7.0	7.0	
GIMBLE ST W(19.9R)					4.3																			
4397351	19.852	23.601	R	2022	0012	CRACKING	9.5	9.5	9.5	8.0	8.0	8.0	8.0	6.0*	6.0*	6.0*	5.5*	5.5*	10.0	10.0	10.0	10.0	8.5	
C. W. ROBERTS CONTRACTING, (2024)					FC125	RIDE	6.8	6.9	6.7	6.2	6.4	6.5	6.4	6.3	6.1	6.0	5.9	5.9	7.7	7.6	7.6	7.6	7.2	
48050000	19.852	23.676	L	1	1	CRACKING	4.5*	2.0*	1.5*	0.0*	0.0*		10.0	10.0	10.0	9.5	9.5	8.0	8.0					
292 98			2	40	19800	RIDE	6.0*	6.1*	5.2*	4.9*	4.4*		7.3	7.4	7.3	7.3	7.3	7.2	7.2					
GARDEN ST(20.4L)					4.3																			
4397351	19.852	23.601	L	2022	0012	CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	8.5	
C. W. ROBERTS CONTRACTING, (2024)					FC125	RIDE	7.1	6.9	6.6	6.6	6.1	6.3	6.0	6.1	5.9	5.8	5.7	7.8	7.7	7.7	7.7	7.7	7.3	
48050001	0.856	1.000	R	1	1	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5		
292			3	45	27000	RIDE																		
S PACE BLVD(1.0R)					3.9																			
4397351	0.846	1.000	R	2022	0012	CRACKING	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	10.0	10.0	8.5	
C. W. ROBERTS CONTRACTING, (2024)					FC125	RIDE																		7.7
48050001	0.856	1.000	L	1	1	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5		
292			3	45	27000	RIDE																		
SR-292/S PACE BLVD(1.0L)					3.9																			
4397351	0.846	1.000	L	2022	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	10.0	10.0	8.5	
C. W. ROBERTS CONTRACTING, (2024)					FC125	RIDE																		7.1
48110000	4.048	8.140	C	1	7	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	
298			2	45	10300	RIDE	8.9	8.8	8.8	8.6	8.3	8.3	8.2	8.2	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	
HERRON VILLA LN(4.2L)					5.2																			
4436511	4.048	5.939	C	2022	0012	CRACKING	7.5	7.5	7.5	7.5	7.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*					
C. W. ROBERTS CONTRACTING, (2025)					FC95M	RIDE	7.9	8.1	8.1	7.3	7.6	7.8	7.8	7.7	7.7	7.7	7.6	7.5						
48117000	0.154	1.606	R	1	1	CRACKING																		
750			2	40	19100	RIDE																		9.5
CR 95A(0.2C)					3.3																			7.2
4436581	0.187	1.155	R	2022	0012	CRACKING	9.5	9.5	9.5	9.5		8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	10.0	10.0	9.0	7.5	
C. W. ROBERTS CONTRACTING, (2023)					FC125	RIDE	6.6	7.3	7.0	6.8		7.0	7.0	6.8	7.0	7.1	7.5	7.3	7.4	7.4	7.4	7.0	7.0	
48117000	0.154	1.606	L	1	1	CRACKING																		9.5
750			2	40	19100	RIDE																		7.2
CR 95A(0.2C)					3.3																			
4436581	0.187	1.155	L	2022	0012	CRACKING	9.5	9.5	9.5	9.5		8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	10.0	10.0	9.4	8.0	
C. W. ROBERTS CONTRACTING, (2023)					FC125	RIDE	6.6	7.3	7.0	6.8		7.0	7.0	6.8	7.0	7.1	7.5	7.3	7.2	7.2	7.2	6.8	6.8	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 3 CONTRACTOR = C. W. ROBERTS CONTRACTING, I -----																								
RDWYID	SR	US	G BMP	EMP LN	RW LN	SYSTEM SPEED	TYPE AADT	DISTRESS RATINGS	SURVEYED YEAR	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE	
INTERSECT AT (MP SIDE)								=====																
ITMSEG-P	W BMP	W EMP	W RW	FY-P	W KMX-P				2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
CONTRACTOR (AGE ONE YEAR)																						(PMRS)		
ITMSEG-F	W BMP	W EMP	W RW	FY-F	W KMX-F																			
50001000	11.774	20.330	R	4		1	CRACKING	4.0*			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5		
8 I10	171.8	180.4	2	70	28000	32.3	RIDE	6.3*			8.8	8.8	8.3	8.4	8.2	8.4	8.3	8.3	8.3	8.1	8.0	7.9		
4366631	11.774	20.330	C	2018	0012	CRACKING	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	
C. W. ROBERTS CONTRACTING, (2020)					FC5HP	RIDE	7.8	7.7	7.6	7.9	7.9	7.9	7.9	7.9	7.9	8.9	8.9	8.9	8.9	8.8	8.8	8.7	8.6	
50001000	20.330	31.414	R	4		1	CRACKING	8.0	8.0	8.0	8.0	8.0	7.0	7.7	5.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0		
8 I10	180.4	191.5	2	70	35140	7.8	RIDE	8.9	8.7	8.5	8.4	8.4	7.7	7.4	7.6	7.6	7.5			8.2	8.4	8.4		
4152571	25.714	31.433	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	6.5	3.5*	
C. W. ROBERTS CONTRACTING, (2010)					FC5M	RIDE	8.4	8.4	8.3	8.6	8.7	8.6	8.7	8.6	8.8	8.9	8.9	8.9	8.8	8.8	8.7	8.7	8.6	
4531201	20.330	31.414	C	2028	0012																			
50001000	20.315	31.150	L	4		1	CRACKING	8.0	8.0	7.0	7.0	6.0*	6.0*	4.5*	4.5*	4.5*				10.0	10.0	10.0		
8 I10	180.4	191.2	2	70	35140	7.8	RIDE	9.0	8.8	8.7	8.6	7.6	7.7	7.4	7.6	7.5				8.3	8.5	8.4		
4152571	25.714	31.433	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	8.0	8.0	7.5	4.5*		
C. W. ROBERTS CONTRACTING, (2010)					FC5M	RIDE	8.4	8.4	8.4	8.7	8.8	8.8	8.9	9.0	9.0	9.0	9.0	8.9	8.9	8.9	8.9	8.9	8.8	
4531201	20.330	31.414	C	2028	0012																			
50001000	11.460	20.315	L	4		1	CRACKING	5.8*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5		
8 I10	171.5	180.4	2	70	28000	32.3	RIDE	7.4		8.8	8.8	8.4	8.5	8.3	8.4	8.4	8.4	8.4	8.2	8.1	8.0			
4366631	11.774	20.330	C	2018	0012	CRACKING	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	
C. W. ROBERTS CONTRACTING, (2020)					FC5HP	RIDE	7.9	7.9	7.8	8.1	8.2	8.1				9.0	8.9	8.9	8.8	8.9	8.8	8.8	8.7	
50001000	1.155	11.460	L	4		1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.5		
8 I10	161.2	171.5	2	70	22000	24.8	RIDE	9.0	8.7	8.9	8.9	8.4	8.4	8.0	8.5	8.3	8.2	8.1	8.1	7.8	7.7	7.6		
4246191	1.042	11.774	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	7.5	5.0*		
C. W. ROBERTS CONTRACTING, (2014)					FC5M	RIDE		8.5	8.5	8.9	8.9	8.9	8.8	9.0	9.1	9.0	9.0	8.9	8.9	8.9	8.8	8.8	8.7	
50020000	1.538	10.502	C	1		1	CRACKING		10.0	10.0	9.5	9.5	9.5	9.5	9.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5		
12			2	55	5200	8.2	RIDE		8.1	8.5	8.2	8.0	8.1	8.0	8.1	8.1	8.1	7.9	7.6	7.6	7.4			
AIRPORT DR(1.6L)																								
4269301	5.230	10.763	C	2015	0012	CRACKING	6.5	6.5	4.5*		10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.5	7.0	6.9	5.0*			
C. W. ROBERTS CONTRACTING, (2017)					FC95M	RIDE	7.3	7.0	7.0		8.8	8.6	8.4	8.0	8.0	7.8	7.6	7.6	7.6	7.7	7.3			
50020000	10.502	10.906	C	1		1	CRACKING	10.0	9.5	9.5	9.0	9.0	9.0	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5			
159			2	45	2400	6.4	RIDE	8.3	8.1	8.2	8.0	7.3	7.5	7.5	7.2	7.5	7.1	7.2	7.1	7.1	7.3			
4269301	5.230	10.763	C	2015	0012	CRACKING	6.5	6.5	4.5*		10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.6	6.0*		
C. W. ROBERTS CONTRACTING, (2017)					FC95M	RIDE	7.0	6.8	6.8		8.8	8.1	7.8	7.4	7.2	7.1	7.1	7.1	7.1	7.1	7.0	6.6		
50030000	5.333	11.482	R	1		1	CRACKING	7.0	6.0*	5.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
10 90			2	65	13800	6.4	RIDE	9.0	8.8	8.7	8.6	7.8	7.6	8.4	8.6	8.6	8.5	8.4	8.4	8.4	8.3			
OPPORTUNITY LN(5.3R)																								
4436431	5.333	11.482	R	2022	0012	CRACKING	10.0	10.0	8.0	8.0	8.0	8.0	6.5	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	10.0	8.5		
C. W. ROBERTS CONTRACTING, (2023)					FC5M	RIDE	8.3	8.3	8.3	8.5	8.5	8.5	8.5	8.6	8.6	8.6	8.6	8.6	9.0	8.9	8.7	8.5		
50030000	5.333	11.482	L	1		1	CRACKING	7.0	5.0*	4.0*	4.0*	4.0*	2.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0			
10 90			2	65	13800	6.4	RIDE	8.9	8.7	8.6	8.4	7.0	6.9	8.3	8.6	8.5	8.5	8.4	8.3	8.3	8.2			
SCHOOL(6.0L)																								
4436431	5.248	11.475	L	2022	0012	CRACKING	10.0	9.0	7.5	7.5	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	9.5	8.0		
C. W. ROBERTS CONTRACTING, (2023)					FC5M	RIDE	8.3	8.2	8.1	8.5	8.5	8.5	8.4	8.6	8.6	8.5	8.4	9.1	8.9	8.9	8.9	8.7		
50040000	2.910	6.404	R	1		1	CRACKING	9.5	9.5	8.0	7.0	5.5*	5.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5			
63 27			2	55	6272	16.8	RIDE	8.9	8.7	8.7	8.6	7.8	7.2	6.8	8.7	8.7	8.7	8.6	8.6	8.6	8.5			
HINSON CIR(3.0R)																								
4436421	2.920	6.404	R	2022	0012	CRACKING	9.5	8.5	7.0	7.0	7.0	6.5	4.5*	3.5*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0	8.5		
C. W. ROBERTS CONTRACTING, (2023)					FC5M	RIDE	8.5	8.5	8.4	8.5	8.6	8.5	8.6	8.6	8.5	8.5	8.5	8.5	8.9	8.9	8.9	8.7		
50040000	2.910	6.404	L	1		1	CRACKING	9.5	8.0	7.0	6.0*	4.0*	2.0*	1.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5			
63 27			2	55	6272	16.8	RIDE	8.7	8.5	8.5	8.4	7.6	7.1	6.9	8.5	8.5	8.5	8.5	8.4	8.3	8.2			
WAYSIDE FARM RD(3.6L)																								
4436421	2.922	6.404	L	2022	0012	CRACKING	8.0	8.0	7.0	7.0	7.0	7.0	7.0	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	9.6	8.0		
C. W. ROBERTS CONTRACTING, (2023)					FC5M	RIDE	8.2	8.2	8.1	8.3	8.3	8.3	8.3	8.3	8.3	8.2	8.2	8.9	8.8	8.7	8.5			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = C. W. ROBERTS CONTRACTING, I													
RDWYID	SR	US	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	RATINGS	SURVEYED	YEAR										FUTURE			
INTERSECT AT (MP SIDE)												2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	W_KMX-P							2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
CONTRACTOR (AGE ONE YEAR)																								(PMRS)	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	W_KMX-F																				
52050000	14.802	20.872	C	1	7	CRACKING	8.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	
2			2	55	1700	RIDE	8.7	8.5	8.5	8.4	7.9	7.8	7.6	8.9	8.8	8.7	8.6	8.5	8.3						
CHOCTAWHATCHEE LN(14.9R)					15.0																				
4455371	14.802	20.835	C	2023	0012	CRACKING	9.0	8.5	7.5	7.5	7.5	6.5	6.0*	5.5*	3.5*	3.5*	3.0*	3.0*	10.0						
C. W. ROBERTS CONTRACTING, (2025)					FC125	RIDE	8.2	8.0	7.8	8.0	8.0	7.9	7.9	7.8	7.6	7.5	7.4	7.3	8.6						
52050000	20.872	24.837	C	1	1	CRACKING	5.0*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0						
2			2	55	1700	RIDE	7.9	7.5	7.5	8.4	8.2	8.1	8.1	8.2	8.2	8.1	8.1	8.0	7.6						
NEW BAYVIEW CHURCH(21.3L)					20.7																				
4325561	20.872	24.795	C	2017	0012	CRACKING	7.0	6.5	6.5	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0					
C. W. ROBERTS CONTRACTING, (2018)					FC125	RIDE	7.7	7.6	7.4	7.3	7.1	8.4	8.3	8.3	8.3	8.3	8.3	8.2	8.2	8.2	8.2	8.2	8.2	7.8	
52050000	24.837	33.915	C	1	7	CRACKING	8.5	8.0	7.0	6.0*	6.0*	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0						
2			2	55	2138	RIDE	8.9	8.6	8.8	8.7	8.2	7.9	7.9		8.6	8.6	8.5	8.4	8.2						
TEN MILE RD(25.0L)					16.3																				
4455391	29.310	33.915	C	2023	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	6.0*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	9.0					
C. W. ROBERTS CONTRACTING, (2025)					FC125	RIDE	8.2	8.1	8.0	7.9	7.9	7.9	7.7	7.7	7.6	7.4	7.3	7.1	8.0	7.6					
54001000	0.000	5.000	R	4	1	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0					
8	I10	215.8	220.8	2	70	27000	RIDE		8.9	8.5	8.1	7.9	7.8	7.8	7.1	7.5	8.0	7.9	7.8						
4327391	2.244	5.000	C	2016	0012	CRACKING	8.0	8.0	8.0	6.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.1	5.0*				
C. W. ROBERTS CONTRACTING, (2018)					FC5M	RIDE	7.7	7.6	7.3	7.9		8.9	8.9	8.8	8.9	8.9	8.8	8.7	8.6	8.5					
54001000	0.000	5.000	L	4	1	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5						
8	I10	215.8	220.8	2	70	27000	RIDE		9.0	8.5	8.1	7.7	7.8	7.7	7.5	7.3	7.8	7.7	7.4						
4327391	2.244	5.000	C	2016	0012	CRACKING	9.0	9.0	8.0	6.5		10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.4	5.5*					
C. W. ROBERTS CONTRACTING, (2018)					FC5M	RIDE	7.4	7.4	6.9	7.7		8.9	8.9	8.9	8.9	8.8	8.7	8.7	8.6						
54010000	0.000	0.630	C	1	1	CRACKING	9.5	9.5	9.5	8.0	7.0	7.0	7.0	5.5*	4.0*	10.0	10.0	10.0	10.0						
10	90		2	55	4900	RIDE	8.4	8.4	8.3	8.0	7.7	7.5	7.7	7.4	7.4	8.7	8.8	8.7	8.7						
LITTLE EGYPT PLANTATION(0.3R)					9.2																				
4325521	0.000	0.630	C	2017	0012	CRACKING	10.0	10.0	10.0	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	7.0				
C. W. ROBERTS CONTRACTING, (2018)					FC95M	RIDE	8.6	8.6	8.5	8.4	8.3	9.2	8.9	8.7	8.6	8.5	8.5	8.4	8.5	8.1					
54010000	9.992	10.408	C	1	1	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0						
10	90		2	25	5100	RIDE	6.7	6.3*	6.4	8.3	7.3	7.3	7.0	7.4	7.1	6.7	7.1	6.4	6.6						
HICKORY ST N(10.2R)					9.9																				
4397291	10.086	10.326	C	2020	0012	CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	5.5*	10.0	10.0	9.5	8.0					
C. W. ROBERTS CONTRACTING, (2023)					FC95M	RIDE	6.8	6.7	6.0	6.6	6.7	6.7	6.5	6.3	6.3	5.8	7.4	7.4	7.3	6.9					
54010000	10.408	10.800	C	1	1	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	8.0	8.0						
10	90		2	35	7000	RIDE	6.7	6.3*	6.4	8.4	8.1	6.7	7.2	6.9	7.1	7.7	7.8	7.6	7.4						
US-19/SR-57(10.4R)					9.9																				
4397291	10.463	10.790	C	2020	0012	CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	5.5*	10.0	10.0	8.5	7.0					
C. W. ROBERTS CONTRACTING, (2023)					FC95M	RIDE	7.4	7.5	6.4																
54010000	10.800	11.600	R	1	1	CRACKING	9.5	9.5	6.5	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0						
10	90		1	35	7000	RIDE	7.2	8.1	8.3	8.5	7.9	8.4	8.3	7.9	7.8	8.1	8.0	7.5	7.5						
MLK AVE(10.8R)					9.9																				
4397291	10.790	11.447	C	2020	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	8.5					
C. W. ROBERTS CONTRACTING, (2023)					FC95M	RIDE	7.5	7.2	6.9	7.1	6.8	6.8	6.5	6.7	6.2	5.8	8.1	8.0	7.9	7.5					
54010000	11.600	19.903	C	1	1	CRACKING	5.5*	5.5*	4.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5					
10	90		2	55	2700	RIDE	8.0	7.9	8.0	8.8	8.4	8.3	8.1	8.1	7.8	7.7	7.8	7.6	7.6						
BARNHART(12.0R)					10.1																				
4397291	15.709	19.903	C	2020	0012	CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	10.0	10.0	8.5					
C. W. ROBERTS CONTRACTING, (2021)					FC95M	RIDE	7.6	7.8	7.4	7.6	7.6	7.7	7.6	7.5	8.4	8.4	8.6	8.4	8.3	7.9					
54010000	10.800	11.600	L	1	1	CRACKING	9.5	9.5	6.5	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0						
10	90		1	35	7000	RIDE	7.2	8.1	8.3	8.5	7.9	8.4	8.3	7.9	7.8	8.1	8.0	7.5	7.5						
M L KING AVE(10.8L)					9.9																				
4397291	10.790	11.447	C	2020	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	6.0*	10.0	10.0	10.0	8.5					
C. W. ROBERTS CONTRACTING, (2023)					FC95M	RIDE	7.5	7.2	6.9	7.1	6.8	6.8	6.5	6.7	6.2	5.8	8.1	8.0	7.9	7.5					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = C. W. ROBERTS CONTRACTING, I											
RDWYID	SR	US	G BMP	EMP LN	RW LN	SYSTEM SPEED	TYPE AADT	DISTRESS RATINGS	SURVEYED 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE	
INTERSECT AT (MP SIDE)							%T	=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-F	WKM-F			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
CONTRACTOR (AGE ONE YEAR)																						(PMRS)	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F	WKM-F																	
55080000	5.430	12.732	R	1	1	CRACKING	7.0	6.0*	5.5*	5.5*	4.0*	3.5*	3.5*				10.0	10.0	10.0	10.0	10.0		
20 27			2	55	5900	RIDE	8.9	8.7	8.5	8.5	7.6	7.4	7.3				8.5	8.4	8.2	8.1	8.2		
TALLAHASSEE NAT CEM(5.7R)					16.1																		
4397271	3.480	12.732	R	2020	0012	CRACKING	9.5	9.5	7.0	7.0	6.5	6.5	4.5*	4.5*			10.0	10.0	10.0	10.0	10.0	8.5	
C. W. ROBERTS CONTRACTING, (2022)					FC5M	RIDE	8.1	8.0	7.9	8.3	8.4	8.4	8.3	8.4			8.7	8.7	8.6	8.6	8.6	8.4	
55080000	5.430	12.732	L	1	1	CRACKING	9.5	8.0	7.0	7.0	6.0*	4.5*	4.5*				10.0	10.0	10.0	10.0	10.0		
20 27			2	55	5900	RIDE	9.0	8.7	8.8	8.7	7.9	7.8	7.6				8.4	8.4	8.2	8.2	8.2		
MARCH RD(5.7L)					16.1																		
4397271	3.480	12.732	L	2020	0012	CRACKING	9.5	9.5	7.0	7.0	7.0	7.0	4.5*	4.5*			10.0	10.0	10.0	9.7	8.0		
C. W. ROBERTS CONTRACTING, (2022)					FC5M	RIDE	8.1	8.1	8.0	8.4	8.4	8.5	8.4	8.5			8.9	8.9	8.7	8.7	8.5		
55080000	3.460	5.430	L	1	1	CRACKING	8.5	7.0	7.0	6.0*	4.0*	2.0*	2.0*				10.0	10.0	10.0	10.0	8.5		
20 27			2	45	33000	RIDE	8.9	8.7	8.7	8.4	7.6	7.2	6.3				8.7	8.6	8.4	8.2	8.1		
CAY LN(3.7L)					2.3																		
4397271	3.480	12.732	L	2020	0012	CRACKING	8.5	8.5	7.0	7.0	7.0	6.5	4.5*	4.5*			10.0	10.0	10.0	10.0	8.5		
C. W. ROBERTS CONTRACTING, (2022)					FC95M	RIDE	8.0	7.9	7.7	7.8	7.7	7.6	7.6	7.4			8.4	8.1	8.4	8.3	7.9		
55080000	0.000	3.460	L	1	1	CRACKING	4.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0			
20 27			2	45	33000	RIDE	7.1		8.2	8.1	7.4	7.0	7.5	7.5	7.5	7.6	7.4	7.3	7.3	7.1			
US-27/SR-20/SR-61(0.0L)					2.3																		
4307841	0.281	3.460	C	2016	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	7.5	6.0*		
C. W. ROBERTS CONTRACTING, (2018)					FC95M	RIDE	7.2	7.0	7.0	6.7	6.6	7.9	7.7	7.6	7.8	7.6	7.7	7.7	7.6	7.6	7.2		
55100000	1.470	1.998	R	1	1	CRACKING	7.5	6.5	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
363			1	35	16000	RIDE	6.3*	6.2*	5.7	5.2*	7.8	7.9	7.5	7.5	7.8	7.8	7.6	7.6	7.6	7.6	7.4		
KESTNER ST(1.6R)					2.6																		
2198851	1.466	2.349	C	2003	0012	CRACKING	9.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	5.0*	2.5*		
C. W. ROBERTS CONTRACTING, (2004)					FC125	RIDE	7.5	6.7	7.0	6.8	6.5	6.6	6.4	6.4	6.5	6.4	6.5	6.4	6.0	5.9	5.9	5.5	
4508111	0.430	1.998	C	2026	0012																		
55100000	1.470	1.998	L	1	1	CRACKING	7.5	6.5	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
363			1	35	16000	RIDE	6.3*	6.2*	5.7	5.2*	7.8	7.9	7.5	7.5	7.8	7.8	7.6	7.6	7.6	7.6	7.4		
LINCOLN ST(1.5L)					2.6																		
2198851	1.466	2.349	C	2003	0012	CRACKING	9.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	3.5*		
C. W. ROBERTS CONTRACTING, (2004)					FC125	RIDE	7.5	6.7	7.0	6.8	6.5	6.6	6.4	6.4	5.7	6.0	5.7	5.6	5.7	5.7	5.3*		
4508111	0.430	1.998	C	2026	0012																		
55100001	0.000	0.506	C	1	1	CRACKING		5.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			
363			2	30	6200	RIDE		6.2*	5.6	6.0	7.2	7.2	6.7	7.3	6.2	6.3	6.2	6.2	7.0	6.4			
SR-363/ADAMS ST NB(0.0R)					2.8																		
2198861	0.000	0.493	C	2003	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.0	9.0	8.0	8.0	8.0	7.5	7.5	7.5	5.0*		
C. W. ROBERTS CONTRACTING, (2004)					FC125	RIDE	6.7	6.8	6.5	5.9	6.0	5.6	5.1*	5.2*	5.6	5.7	5.0*	5.5	5.5	5.3*	4.9*		
4508111	0.000	0.497	C	2026	0012																		
55120000	2.854	3.282	C	1	1	CRACKING	10.0	9.5	9.5	9.5					10.0	10.0	10.0	10.0	10.0	10.0			
61			1	45	11000	RIDE	8.6	8.2	8.6	8.5					8.1	7.8	7.8	7.8	8.1	7.7	7.6		
FROM SR-61(2.9L)					4.2																		
2197481	2.816	3.654	C	2003	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	6.5	6.5	5.1*	3.0*	
C. W. ROBERTS CONTRACTING, (2006)					FC125	RIDE	7.3	6.9	6.8	6.7	6.9	7.1	6.7	6.5	6.6	6.5	6.5	6.3	6.2	6.3	5.9		
2194842	2.789	6.838	C	2026	0012																		
55120000	3.713	6.838	R	1	1	CRACKING		10.0	10.0	10.0					10.0	10.0	10.0	10.0	10.0	10.0			
61 319			2	45	22000	RIDE		8.1	8.5	8.5					7.7	8.0	8.0	7.9	7.7	7.5	7.6		
BUTTON WILLOW LN(4.0R)					4.2																		
2197481	5.382	6.825	C	2003	0213	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	7.0	7.0	5.5*	5.5*	4.0*	4.0*	4.0*	4.0*	1.5*		
C. W. ROBERTS CONTRACTING, (2006)					FC125	RIDE	7.5	7.2	7.3	7.3	7.2	7.3	7.1	7.1	7.1	7.0	7.0	7.0	6.9	6.9	6.5		
2194842	2.789	6.838	C	2026	0012																		
55120000	3.713	6.838	L	1	1	CRACKING		10.0	10.0	10.0					10.0	10.0	10.0	10.0	10.0	10.0			
61 319			2	45	22000	RIDE		8.1	8.5	8.5					7.9	8.0	8.1	7.8	7.4	7.3	7.5		
CRAWFORDVILLE HWY(3.7L)					4.2																		
2197481	5.382	6.825	C	2003	0213	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	3.0*		
C. W. ROBERTS CONTRACTING, (2006)					FC125	RIDE	7.6	7.5	7.4	7.4	7.3	7.2	7.1	7.1	7.1	7.0	7.0	6.9	6.9	6.9	6.5		
2194842	2.789	6.838	C	2026	0012																		
55120002	0.000	0.386	C	1	1	CRACKING											10.0	10.0	10.0	10.0	10.0		
61			1	45	3800	RIDE											7.7	7.6	7.6	7.2	7.1		
US-319/SR-369 SB(0.0R)					4.2																		
2197481	0.000	0.386	C	2003	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	7.0	7.0	7.0	5.0*		
C. W. ROBERTS CONTRACTING, (2008)					FC125	RIDE	7.3	7.0	7.0	6.2	6.3	6.5	6.4	6.0	6.2	6.2	6.4	6.0	6.0	5.7	5.3*		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3 CONTRACTOR = C. W. ROBERTS CONTRACTING, I																									
RDWYID	SR	US	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE
INTERSECT AT (MP SIDE)									RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	W_KMX-P				=====																
CONTRACTOR (AGE ONE YEAR)																									
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	W_KMX-F																			2030 (PMRS)	
55170000	0.000	1.627	C	1	1	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	7.0	7.0	6.5	6.5	10.0	8.5			
369 319			2	55	14300	RIDE	8.9	8.4	8.7	8.7	8.2	8.3	8.3	8.4	8.4	8.2	8.0	8.5	8.5						
LEON SINKS	GEO AREA(	0.3L)			4.6																				
4377581	0.000	1.627	C	2023	0012	CRACKING	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	5.0*	5.0*	5.0*	3.0*	10.0	10.0	8.5		
C. W. ROBERTS CONTRACTING, (2024)					FC95M	RIDE	8.5	8.4	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.3	8.2	8.3	8.3	8.3	8.9	8.9	8.5		
55170000	3.296	4.430	C	1	1	CRACKING	10.0	10.0	9.5	9.5	9.5					10.0	10.0	10.0	10.0	10.0	10.0	10.0			
369 319			2	45	11000	RIDE	9.1	8.4	8.7	8.7	8.2					8.3	8.6	8.4	8.4	8.5	8.2	8.1			
US 319 NB NEW ALIGN(	3.3R)				4.2																				
2197481	3.303	4.430	C	2003	0213	CRACKING	9.5	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	4.0*		
C. W. ROBERTS CONTRACTING, (2006)					DGFC	RIDE	8.3	8.1	8.1	7.6	7.9	7.8	7.6	7.7	7.8	7.6	7.7	7.8	7.8	7.6	7.7	7.6	7.2		
55170001	0.000	0.672	C	1	1	CRACKING											10.0	10.0	10.0	10.0	10.0	10.0			
369 319			2	45	7100	RIDE											7.9	7.7	7.5	8.3	8.2	8.1			
US-319/SR-369 SB(	0.0L)				6.5																				
2197481	0.000	0.672	C	2003	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	8.0	8.0	8.0	6.9	4.5*		
C. W. ROBERTS CONTRACTING, (2007)					FC125	RIDE	8.1	8.1	7.9	7.8	7.6	7.7	7.6	7.5	7.6	7.5	7.6	7.4	7.4	6.9	6.9	6.9	6.5		
55190000	0.795	1.415	R	1	1	CRACKING	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	7.0	7.0			
373			1	35	18900	RIDE	5.9*		7.9	7.8	7.4	7.3	6.9	7.1	7.0	6.8	6.7	6.4	6.6						
SCHOOL(	0.9R)				6.4																				
4269651	0.912	1.233	C	2014	0012	CRACKING	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	9.0	8.5	7.0			
C. W. ROBERTS CONTRACTING, (2016)					FC125	RIDE	6.4	6.0		7.7	7.8	7.5	7.4	7.6	7.7	7.5	7.7	7.5	7.7	7.5	7.3	6.9			
55190000	1.415	1.780	R	1	1	CRACKING	10.0		10.0	10.0	9.5	9.5	9.5	9.5	9.5	8.0	7.0	7.0	7.0	7.0	7.0				
373			2	35	26000	RIDE	7.8		8.1	7.8	7.0	6.8	6.5	6.7	6.3	6.6	6.1	5.6	6.1	5.6	5.9				
ADAMS ST S(	1.6C)				6.4																				
4269651	1.415	1.680	C	2014	0012	CRACKING	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	7.0				
C. W. ROBERTS CONTRACTING, (2016)					FC125	RIDE	6.1	5.9		8.2	8.1	8.0	7.5	6.7	6.6	6.9	6.9	6.7	6.6	6.2	6.2				
55190000	1.235	1.780	L	1	1	CRACKING	3.5*		10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	7.5				
373			2	35	26000	RIDE	5.2*		8.6	8.7	6.4	6.3	6.5	6.7	5.9	5.6	5.2*	5.1*	5.1*						
ADAMS ST S(	1.6C)				6.4																				
4269651	1.415	1.680	C	2014	0012	CRACKING	7.5	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	6.7	5.0*				
C. W. ROBERTS CONTRACTING, (2016)					FC125	RIDE	4.8*	5.9		8.2	8.1	8.0	7.5	6.7	6.3	6.4	6.5	6.4	6.2	5.8					
55190000	0.795	1.235	L	1	1	CRACKING	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	7.0	7.0	7.0	7.0	7.0				
373			2	35	18900	RIDE	5.9*		7.9	7.8	7.4	7.3	6.9	7.1	7.0	6.8	6.7	6.4	6.6						
HOLTON ST(	0.9L)				6.4																				
4269651	0.912	1.233	C	2014	0012	CRACKING	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	6.5				
C. W. ROBERTS CONTRACTING, (2016)					FC125	RIDE	6.4	6.0		7.7	7.8	7.5	7.4	7.6	7.4	7.4	7.4	7.3	7.3	7.0	6.6				
55320000	0.000	1.074	R	4	1	CRACKING	5.3*	4.8*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5				
8 I10	193.6	194.6	2	70	39000	RIDE	7.9	7.3		8.8	8.2	8.2	8.2	8.2	8.4	8.3	8.2	8.2	8.1	8.0					
BRIDGE #50	L(	0.0C)			21.8																				
4327412	0.233	1.074	C	2016	0012	CRACKING	9.5	9.5	8.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.8	6.0*			
C. W. ROBERTS CONTRACTING, (2017)					FC5M	RIDE	7.9	7.9	7.9	7.9	8.7	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.7	8.6	8.5				
55320000	0.000	1.074	L	4	1	CRACKING	4.8*	4.3*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0				
8 I10	193.6	194.6	2	70	39000	RIDE	8.1	7.4		8.9	8.2	8.2	8.2	8.2	8.3	8.4	8.2	8.1	8.1	8.1					
BRIDGE #50	L(	0.0C)			21.8																				
4327412	0.233	1.074	C	2016	0012	CRACKING	10.0	10.0	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.0			
C. W. ROBERTS CONTRACTING, (2017)					FC5M	RIDE	8.1	8.0	7.9	8.2	8.8	8.9	8.9	8.9	8.9	8.9	8.8	8.9	8.8	8.6	8.5				
55321000	0.000	0.114	R	1	6	CRACKING																			
160			2	35	14600	RIDE																			
SR 61(	0.0C)				3.0																				
4269311	0.000	0.085	C	2014	0012	CRACKING	9.5	9.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0			
C. W. ROBERTS CONTRACTING, (2016)						RIDE																			
4529461	0.030	0.114	C	2026	0012																				
55321000	0.000	0.114	L	1	6	CRACKING																			
160			2	35	14600	RIDE																			
SR 61(	0.0C)				3.0																				
4269311	0.000	0.085	C	2014	0012	CRACKING	9.5	9.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0			
C. W. ROBERTS CONTRACTING, (2016)						RIDE																			
4529461	0.030	0.114	C	2026	0012																				

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = C. W. ROBERTS CONTRACTING, I												
RDWYID	SR	US	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE	
INTERSECT AT (MP SIDE)			G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-F	WKM-F	%T	=====																
CONTRACTOR (AGE ONE YEAR)									2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	(PMRS)	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F	WKM-F																		
57110000	2.705	4.318	L	1	1	CRACKING	3.5*		3.5*	1.0*	1.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5			
189			2	45	50000	RIDE	7.7		7.7	7.7	7.7	8.2	8.0	7.7	7.5	7.5	7.9	7.9	7.9	7.7	7.6			
LEG 028(2.8L)							3.2																	
4362581	3.218	4.188	L	2018	0012	CRACKING	8.5		8.5	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0		
C. W. ROBERTS CONTRACTING, (2019)					FC125	RIDE	7.6		7.3	7.4	7.4	7.6	7.4	7.4	7.8	7.7	7.7	7.7	7.8	7.6	7.6	7.2		
57110028	0.000	1.833	R	1	7	CRACKING	7.5		7.5	7.5	7.5	6.0*	6.0*	6.0*	6.0*	5.5*	10.0	10.0	10.0	10.0	10.0			
393			2	40	24500	RIDE	7.9		7.6	8.2	7.7	7.5	7.1	7.0	6.8	8.5	8.4	8.5	8.5	8.5	8.4			
MIRACLE STRIP(0.0C)							3.4																	
4437442	0.000	1.833	R	2023	0012	CRACKING	8.5		8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.0	6.0*	6.0*	6.0*	6.0*	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2025)					FC95M	RIDE	8.1		8.4	8.3	8.0	8.0	8.0	7.9	7.9	7.6	7.7	7.7	7.4	7.3	8.1	7.7		
57110028	0.000	1.833	L	1	7	CRACKING	7.5		7.5	7.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0			
393			2	40	24500	RIDE	8.2		8.2	8.1	7.8	7.0	6.8	6.2	6.2	6.4	8.6	8.5	8.5	8.3	8.3			
MIRACLE STRIP(0.0C)							3.4																	
4437442	0.000	1.833	L	2023	0012	CRACKING	9.0		8.5	8.5	7.5	7.5	7.5	7.5	7.5	6.0*	5.5*	5.5*	5.5*	3.0*	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2025)					FC95M	RIDE	8.3		8.2	8.1	7.9	7.9	7.9	7.7	7.6	7.5	7.3	7.3	7.2	6.8	8.0	7.6		
58002000	6.193	10.603	R	4	1	CRACKING	8.6		8.8			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0			
8 I10	22.7	27.2	2	70	47500	RIDE	6.6		6.5			8.8	8.2	8.3	8.2	8.1	8.3	8.2	7.8	7.6	7.9			
4415881	6.193	9.378	R	2021	0012	CRACKING	9.0		9.0	9.0	9.0	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*		10.0	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2024)					FC5M	RIDE	7.8		7.7	7.6	8.3	8.3	8.1	8.4	8.5	8.4	8.3		8.9	8.9	8.8			
58002000	11.192	15.232	R	4	1	CRACKING	9.1		9.2			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0			
8 I10	27.7	31.8	2	70	40500	RIDE	6.5		6.5			8.8	8.2	8.3	8.1	8.0	8.2	8.1	7.9	7.8	7.7			
4415881	11.192	14.701	C	2021	0012	CRACKING	9.0		9.0	9.0	9.0	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2024)					FC5M	RIDE	7.6		7.5	7.4	8.0	7.9	7.8	8.1	8.1	8.1	7.9	7.7	7.7	8.9	8.7	8.6		
58002000	11.192	15.232	L	4	1	CRACKING	8.6		8.8			10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0			
8 I10	27.7	31.8	2	70	40500	RIDE	7.0		6.9			8.8	8.3	8.3	8.2	8.2	8.4	8.3	8.1	8.1	8.0			
4415881	11.192	14.701	C	2021	0012	CRACKING	9.0		9.0	9.0	9.0	6.5	6.5	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2024)					FC5M	RIDE	7.9		7.8	7.7	8.3	8.2	8.1	8.4	8.5	8.4	8.3	8.2	8.9	8.5	8.4			
58002000	6.110	10.603	L	4	1	CRACKING	8.8		8.9			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0			
8 I10	22.7	27.2	2	70	47500	RIDE	6.8		6.5			8.8	8.2	8.4	8.3	8.1	8.3	8.2	8.1	8.0	7.8			
4415881	6.193	9.378	L	2021	0012	CRACKING	9.0		9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	4.5*	4.5*		10.0	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2024)					FC5M	RIDE	7.8		7.7	7.5	8.3	8.2	8.1	8.5	8.5	8.4	8.3		8.9	8.8	8.7			
58040000	16.442	17.966	R	1	7	CRACKING	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	10.0	10.0	10.0	10.0	10.0			
87			2	55	17800	RIDE	8.8		8.7	8.7	8.6	8.4	8.4	8.4	8.3	8.3	8.1	8.1	8.0	8.0	8.0			
E MILTON FIRE DEPT(17.1R)							11.3																	
4475901	16.266	17.966	R	2024	0012	CRACKING	10.0		10.0	10.0	10.0	10.0	10.0	9.0	8.0	6.5	6.5	4.5*	3.5*	3.5*	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2025)					FC5M	RIDE	7.9		7.9	7.8	8.1	8.1	7.5	8.0	8.1	8.1	7.9	8.0	8.1	8.8	8.6			
58040000	16.442	17.966	L	1	7	CRACKING	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	10.0	10.0	10.0	10.0	10.0			
87			2	55	17800	RIDE	8.8		8.7	8.7	8.6	8.4	8.4	8.4	8.3	8.3	8.4	8.2	8.1	8.2	8.1			
FORTUNE RD(17.0L)							11.3																	
4475901	16.266	17.835	L	2024	0012	CRACKING	10.0		10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	6.5	4.5*	3.5*	3.5*	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2025)					FC5M	RIDE	8.0		7.9	7.9	8.2	8.1	8.1	8.1	8.0	7.9	7.9	8.0	7.8	8.9	8.7			
59030000	3.828	11.543	C	1	1	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0			
375 319			2	55	5100	RIDE				8.6	8.7	8.1	8.2	7.9	8.1	8.1	8.1	8.1	8.1	8.0	8.0			
DOT RD(4.1L)							12.1																	
4397301	3.828	7.475	C	2020	0012	CRACKING	8.5		7.0	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	8.5		
C. W. ROBERTS CONTRACTING, (2022)					FC125	RIDE	8.0		7.8	7.8	7.6	7.6	7.6	7.5	7.4	7.3	7.3	8.2	8.3	8.1	8.1	7.7		
59100000	0.000	4.100	C	1	7	CRACKING	5.5*		5.0*	5.0*	5.0*	5.0*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0			
267			2	55	6300	RIDE	8.3		8.4	8.4	8.4	8.4	7.7	7.6	8.3	8.4	8.4	8.3	8.3	8.3	8.2			
APALACHICOLA FOREST(1.6L)							10.4																	
4325502	0.000	3.808	C	2024	0012	CRACKING	9.0		7.5	7.5	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	9.0		
C. W. ROBERTS CONTRACTING, (2025)					FC125	RIDE	8.0		8.1	8.1	8.0	8.0	8.0	8.0	8.0	7.9	7.9	8.0	8.0	7.9	8.6	8.2		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 3 CONTRACTOR = C. W. ROBERTS CONTRACTING, I -----																								
RDWYID	SR	US	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE
INTERSECT	AT	(MP)	(SIDE)								2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-F	P																		
CONTRACTOR	(AGE)	ONE	YEAR																					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F	F																		(PMRS)
59110000	14.614	20.725	C	1	1	CRACKING	9.0	7.0																
30 98			2	60	3200	RIDE	8.0	7.8																
CR 59(14.8R)					31.9																			
4377481	14.604	20.725	C	2019	0012	CRACKING	9.0	8.5	8.5	8.5	6.0*	6.0*	5.0*	5.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5
C. W. ROBERTS CONTRACTING, (2021)					FC125	RIDE	7.6	7.5	7.4	7.4	7.3	7.4	7.3	7.3	8.8	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.6	8.2
60002000	18.225	24.024	R	4	1	CRACKING	10.0	8.5	8.5	8.0														
8 I10	85.2	91.0	2	70	23125	RIDE	8.6	8.4	8.3	8.3	7.0	7.6	6.5	7.2	7.4	5.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	
					22.2																			
4436391	18.146	24.062	C	2022	0012	CRACKING	10.0	10.0	9.0	7.0	7.0	6.0*	6.0*	5.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	9.0
C. W. ROBERTS CONTRACTING, (2024)					FC5M	RIDE	8.3	8.3	8.2	8.5	8.4	8.4	8.5	8.5	8.6	8.5	8.5	8.4	8.4	9.0	9.0	9.0	9.0	8.9
60002000	18.225	24.024	L	4	1	CRACKING	10.0	8.5	8.5	8.0	7.0	6.5	5.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
8 I10	85.2	91.0	2	70	23125	RIDE	8.6	8.6	8.4	8.3	7.5	7.5	7.2	7.0	7.2	7.2	8.4	8.4	8.4	8.3	8.3	8.3	8.3	
					22.2																			
4436391	18.146	24.062	C	2022	0012	CRACKING	10.0	10.0	9.0	7.0	7.0	7.0	7.0	6.5	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	9.0
C. W. ROBERTS CONTRACTING, (2024)					FC5M	RIDE	8.2	8.2	8.2	8.5	8.5	8.4	8.5	8.5	8.5	8.5	8.4	8.3	9.1	9.1	9.1	9.1	9.0	
60010000	0.000	14.520	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5		
10 90			2	55	10100	RIDE	8.8	8.8	8.5	8.7	8.4	8.4	8.3	8.4	8.5	8.4	8.5	8.4	8.4	8.2	8.3	8.1		
RAINBOW DR(0.3L)					10.6																			
4246131	2.754	13.605	C	2012	0012	CRACKING			10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.5	5.5*	
C. W. ROBERTS CONTRACTING, (2015)					FC95M	RIDE			8.7	8.6	8.6	8.5	8.5	8.5	8.5	8.5	8.4	8.4	8.4	8.4	8.4	8.2	7.8	
60010000	14.520	15.360	R	1	1	CRACKING	5.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	
10 90			2	45	15400	RIDE	8.1	8.8	8.7	8.5	8.4	8.4	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.2	8.0	8.0	8.0	
AIRPORT ENT(14.8R)					10.6																			
4246131	14.884	15.374	C	2012	0012	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.8	6.0*	
C. W. ROBERTS CONTRACTING, (2015)					FC95M	RIDE			8.7	8.6	8.4	8.5	8.3	8.3	8.4	8.3	8.3	8.3	8.3	8.3	8.2	8.2	7.8	
60010000	15.360	17.375	C	1	1	CRACKING	7.0	10.0	10.0	10.0	9.5	9.0	9.0	7.0	8.5	7.0	7.0	7.0	7.0	7.0	6.0*			
10 90			4	45	16800	RIDE	7.1	8.2	7.8	8.2	7.4	7.9	7.7	7.7	7.6	7.4	7.2	6.7	7.0					
SHOEMAKER DR(15.4L)					10.6																			
4230681	15.487	16.768	L	2012	0012	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.5	7.5	7.0	6.1*	4.5*			
C. W. ROBERTS CONTRACTING, (2014)					FC95M	RIDE			8.6	8.3	8.4	8.3	8.3	8.2	8.2	8.1	8.0	8.1	8.1	8.0	8.0	8.0	7.6	
4546291	15.305	21.905	C	2028	0012																			
60010000	14.520	15.360	L	1	1	CRACKING	5.0*	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	7.5	7.5	7.5	7.5	7.5		
10 90			2	45	15400	RIDE	8.4	8.7	8.6	8.6	8.1	8.2	8.2	8.2	8.4	8.3	8.3	8.1	8.0	8.0	8.0	8.0		
SR 187(14.8L)					10.6																			
4246131	14.884	15.374	C	2012	0012	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.9	6.0*		
C. W. ROBERTS CONTRACTING, (2015)					FC95M	RIDE			8.7	8.6	8.6	8.4	8.4	8.3	8.3	8.3	8.2	8.3	8.2	8.3	8.2	8.2	7.8	
60020000	3.463	4.528	R	1	1	CRACKING	10.0	9.0	9.0	8.0	8.0	5.0*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0		
30 98			3	45	55000	RIDE	8.4	8.4	8.2	8.2	7.3	7.7	7.3	7.8	6.9	6.9	6.9	6.2	8.5	8.5	8.5	8.5		
HIDDEN DUNES(3.5R)					4.4																			
4192981	3.397	4.656	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.0	6.0*		
C. W. ROBERTS CONTRACTING, (2011)					FC95M	RIDE	8.4	8.4	8.4	8.2	8.1	8.2	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.0	8.0	8.0	7.6	
60020000	5.530	7.638	R	1	7	CRACKING	6.0*	5.5*	5.5*					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
30 98			2	55	44500	RIDE	7.9	7.8	7.2					8.2	8.2	8.4	8.4	8.3	8.2	8.1	8.1	8.1		
TOP SAIL RD(5.9R)					4.4																			
4141326	5.907	7.502	R	2021	0213	CRACKING	10.0	9.0	9.0	9.0	7.5	6.5	4.5*	4.5*	4.5*	3.5*	3.5*							
C. W. ROBERTS CONTRACTING, (2025)					FC5	RIDE	8.0	8.0	7.8	8.1	8.1	8.0	8.0	7.9	8.0	7.8	7.8							
60020000	13.214	17.765	R	1	7	CRACKING	6.0*	5.5*	5.5*					10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
30 98			2	55	26000	RIDE	7.9	7.8	7.2					8.4	8.3	8.3	8.3	8.3	8.2	8.1	8.1	8.1		
BAY DR(14.6R)					8.3																			
4436502	13.221	17.765	R	2023	0012	CRACKING	10.0	10.0	9.0	9.0	6.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*							
C. W. ROBERTS CONTRACTING, (2025)					FC5M	RIDE	8.1	8.1	8.0	8.1	8.0	7.9	8.0	8.1	8.0	8.0	8.0							
60020000	13.228	17.765	L	1	7	CRACKING	6.0*	5.5*	5.5*					10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0		
30 98			2	55	26000	RIDE	7.9	7.8	7.2					8.3	8.2	8.3	8.2	8.2	8.2	8.1	8.0	8.0		
DODDLES FOREST RD(13.7L)					8.3																			
4436502	13.221	17.765	L	2023	0012	CRACKING	9.0	9.0	7.5	7.5	6.5	6.5	6.5	4.5*	4.5*	3.5*	3.5*							
C. W. ROBERTS CONTRACTING, (2025)					FC5M	RIDE	8.0	7.8	7.8	7.9	7.7	7.6	7.7	7.7	7.7	7.6	7.5							

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 3 CONTRACTOR = C. W. ROBERTS CONTRACTING, I -----																									
RDWYID	SR	US	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR														FUTURE
INTERSECT AT (MP SIDE)									RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-F	WKM-F	WKM-F	WKM-F	WKM-F	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
CONTRACTOR (AGE ONE YEAR)																									(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F	WKM-F	WKM-F	WKM-F	WKM-F																
60090000	6.075	6.747	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.0	8.0	8.0	8.0	8.0	7.0		
285			2	45	13400	RIDE	8.5	8.4	7.8	8.1	7.8	7.7	7.8	7.7	7.8	7.9	7.3	7.5	7.3	7.0	7.0	6.6			
MOSSY HEAD PLAZA DR(6.6R)					9.7																				
4193181	6.294	6.729	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.4	5.5*		
C. W. ROBERTS CONTRACTING, (2014)					FC95M	RIDE		8.2	8.0	7.9	7.6	7.7	7.3	7.7	7.5	7.6	7.6	7.6	7.6	7.6	7.4	7.4	7.0		
60090000	6.075	6.747	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	7.0	6.0*			
285			2	45	13400	RIDE	7.4	8.1	7.6	7.6	7.7	7.7	7.4	7.7	7.4	7.4	7.1	7.3	6.8	6.6	6.8	6.3			
GREEN ACRES DR(6.2L)					9.7																				
4193181	6.294	6.729	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	6.9	5.0*			
C. W. ROBERTS CONTRACTING, (2014)					FC95M	RIDE		7.9	7.8	7.7	7.7	7.8	7.5	7.2	7.6	7.8	7.7	7.8	7.7	7.8	7.6	7.2			
60100000	0.000	17.890	C	1	1	CRACKING	2.0*	2.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5				
81			2	55	2400	RIDE	8.1	8.3		8.4	8.4	8.4	8.3	8.6	8.6	8.6	8.5	8.4	8.4	8.4	8.4				
SR 20(0.0C)					10.0																				
4377531	0.000	17.890	C	2019	0012	CRACKING	8.5	8.5	7.0	6.0*	5.5*	5.5*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	8.5				
C. W. ROBERTS CONTRACTING, (2021)					FC95H	RIDE		8.4	8.3	8.3	8.1	8.0	8.0	7.9	8.7	8.7	8.6	8.5	8.5	8.5	8.5	8.1			
61002000	0.000	3.800	C	1	1	CRACKING	9.5	9.5	9.5	8.0	7.0	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0				
273			2	55	3700	RIDE	8.8	8.6	8.7	8.4	7.8	7.8	7.7	7.9	7.5	8.6	8.2	8.3	8.1						
GLENWOOD AVE(0.0C)					15.4																				
4436401	0.038	3.047	C	2022	0012	CRACKING	8.5	8.5	7.5	7.5	7.0	6.5	5.5*	5.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	8.5				
C. W. ROBERTS CONTRACTING, (2023)					FC95M	RIDE		8.0	7.9	7.8	8.0	8.1	8.0	7.9	7.8	7.7	8.4	8.3	8.3	8.3	8.3				
61010000	0.564	1.882	C	1	1	CRACKING			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5				
10 90			2	45	3200	RIDE			8.5	8.6	8.3	8.4	8.4	8.5	8.4	8.3	8.4	8.3	8.4	8.4	8.4				
BOAT RAMP RD(0.6R)					9.2																				
4362641	0.564	1.309	C	2018	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5			
C. W. ROBERTS CONTRACTING, (2019)					FC95M	RIDE		8.4	8.3	8.4	7.8	7.8	7.7	8.4	8.4	8.4	8.4	8.4	8.3	8.3	8.3	7.9			
61010000	1.882	5.013	C	1	1	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	7.0	6.0*	6.0*					
10 90			2	55	3300	RIDE		8.3	8.9	8.8	8.4	8.4	8.3	8.4	8.2	8.1	8.0	8.0	8.0	8.0	7.8				
BIRGE RD(3.4C)					12.2																				
4287481	1.882	5.005	C	2015	0226	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0	8.5	6.5				
C. W. ROBERTS CONTRACTING, (2015)					FC95M	RIDE		7.7	7.6	8.9	8.6	8.6	8.6	8.6	8.5	8.5	8.4	8.4	8.4	8.4	8.4	8.0			
61010000	13.609	16.290	C	1	7	CRACKING	6.5	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5				
10 90			2	55	4223	RIDE	8.0	7.5	7.2		8.2	8.2	8.2	8.5	8.4	8.2	8.3	8.3	8.3	8.0					
TRAILOR CT(14.0R)					8.1																				
4457551	14.665	16.198	C	2024	0012	CRACKING	9.5	9.5	8.5	8.5	8.5	8.5	8.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	10.0	9.0				
C. W. ROBERTS CONTRACTING, (2025)					FC95M	RIDE		8.1	7.9	7.9	7.8	7.7	7.7	7.4	7.5	7.4	7.3	7.2	7.2	7.2	8.4	8.0			
61010000	19.075	22.914	C	1	7	CRACKING	3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	7.0					
10 90			2	55	3300	RIDE	8.1	7.8		8.8	8.6	8.6	8.5	8.6	8.7	8.7	8.6	8.6	8.6	8.3					
SPANGENBERG RD(19.2R)					9.3																				
4346711	19.082	22.914	C	2024	0012	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	5.5*	5.5*	5.5*	10.0	9.0					
C. W. ROBERTS CONTRACTING, (2025)					FC125	RIDE		8.5	8.5	8.5	8.2	8.2	8.2	8.0	8.0	8.1	8.0	8.0	8.0	8.6	8.2				
61040000	0.000	0.965	R	1	8	CRACKING	10.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0				10.0				
79			2	65	9800	RIDE	8.7	8.0	8.4	8.3	8.1	8.0	7.8	8.1	8.1	8.1	8.0				8.1				
2179116	0.007	0.565	C	2007	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	6.5	6.5	6.0*	6.0*					
C. W. ROBERTS CONTRACTING, (2012)					FC5	RIDE		8.0	7.8	7.7	7.8	7.7	7.8	7.8	7.8	7.7	7.7	7.6	7.6						
2179119	0.000	0.965	C	2024	0012																				
61040000	0.965	2.332	R	1	1	CRACKING	10.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0				10.0				
79			2	45	9800	RIDE	8.7	8.0	8.4	8.3	8.1	8.0	8.0	8.1	8.1	8.1	8.0				8.5				
SR 20(1.7C)					13.9																				
2207731	0.614	2.332	C	2009	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.6	6.5			
C. W. ROBERTS CONTRACTING, (2012)					FC95M	RIDE		8.4	8.3	8.2	8.3	8.4	8.4	8.3	8.2	8.1	8.0	8.0	8.0	7.9	7.8	7.4			
61040000	0.965	2.332	L	1	1	CRACKING	10.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0				10.0				
79			2	45	9800	RIDE	8.7	8.0	8.4	8.3	8.1	8.0	8.0	8.1	8.1	8.1	8.0				8.6				
CREWS LAKE RD(1.0L)					13.9																				
2207731	0.614	2.332	C	2009	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.0	8.0	7.9	6.0*			
C. W. ROBERTS CONTRACTING, (2012)					FC95M	RIDE		8.6	8.4	8.4	8.3	8.2	8.2	8.0	8.1	7.9	7.9	7.7	7.5	7.4	7.0	7.0			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @# INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = C. W. ROBERTS CONTRACTING, I																						
RDWYID		BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR														FUTURE												
SR	US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
INTERSECT AT (MP SIDE)		W_BMP		W_EMP	RW	FY-P	WKMX-P																											
ITMSEG-P		W_BMP		W_EMP	RW	FY-F	WKMX-F																											
CONTRACTOR (AGE ONE YEAR)		W_BMP		W_EMP	RW	FY-F	WKMX-F																											
ITMSEG-F		W_BMP		W_EMP	RW	FY-F	WKMX-F																											
61040000		0.000	0.965	L	1	8	CRACKING	10.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0				10.0													
79				2	65	9800	RIDE	8.7	8.0	8.4	8.3	8.1	8.0	7.8	8.1	8.1	8.0				8.2													
A STRICKLAND RD W(0.3L)						13.9																												
2179116		0.007	0.565	C	2007	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	6.5	6.5	6.5	6.5															
C. W. ROBERTS CONTRACTING, (2012)						FC5	RIDE	8.2	8.0	7.9	8.1	8.0	8.2	8.1	8.1	8.0	8.0	8.0	8.0															
2179119		0.000	0.965	C	2024	0012																												
61121000		0.000	0.803	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	7.0														
20				2	45	8400	RIDE	9.1	8.4	8.9	8.9	8.3	8.4	8.4	8.5	8.4	8.2	8.1	8.1	8.3														
CAPTAIN FRITZ RD(0.3C)						18.8																												
4307911		0.000	0.803	C	2017	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	10.0	8.5													
C. W. ROBERTS CONTRACTING, (2018)						FC95M	RIDE	8.2	8.0	8.0	8.0	8.0	8.6	8.5	8.5	8.5	8.5	8.5	8.4	8.5	8.1													
61121000		1.322	4.795	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	7.0														
20				2	60	5400	RIDE	9.1	8.4	9.0	8.9	8.3	8.4	8.4	8.5	8.4	8.2	8.1	8.1	8.3														
						20.3																												
4307911		1.322	3.112	C	2017	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0													
C. W. ROBERTS CONTRACTING, (2018)						FC95M	RIDE	8.2	8.1	8.0	8.0	8.0	8.7	8.7	8.7	8.7	8.6	8.6	8.6	8.6	8.6													

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 3 CONTRACTOR = COUCH CONSTRUCTION LP -----																					
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)					%T	=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P																
CONTRACTOR (AGE ONE YEAR)				SURF_TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F															(PMRS)	
48040000	0.000	1.120	C	1	4	CRACKING	8.5	9.2	8.7	8.0	9.1	9.1	9.3	9.3	9.3	9.2	8.8	6.7	6.4*		
95 29			4	30	7000	RIDE	5.1*	5.2*	5.0*	4.9*	4.9*	5.0*	4.9*	4.6*	5.1*	5.0*	4.8*	4.7*	4.6*		
CERVANTES ST(0.0C)																					
2186361	0.011	1.120	C	1998	0227	CRACKING	6.5	6.6	6.7	6.7	6.8	7.4	7.3	8.6	8.3	8.5	8.1	8.0	6.9	6.0*	
COUCH CONSTRUCTION LP				(2000)	LGD	RIDE	4.8*	4.9*	4.8*	4.0*	4.0*	4.1*	4.0*	6.8	6.9	6.7	6.7	6.8	6.6	6.4	
4325681	0.000	3.524	C	2023	0012																

48080060	0.125	1.199	R	1	4	CRACKING	8.6	8.5	9.1	9.2	9.2	9.2	9.0	9.0	8.9	8.2	8.3	7.8	8.3		
30 98			2	40	18900	RIDE	7.9	7.6	7.7	7.5	6.4	6.6	6.5	6.6	6.3	6.1	6.3	6.3	6.3		
CORY FIELD(0.3C)																					
2186371	0.000	2.491	C	1998	0227	CRACKING	8.2	8.2	8.2	8.1	8.0	8.3	8.2	8.2	8.3	8.1	7.9	7.8	7.8	6.5	
COUCH CONSTRUCTION LP				(1999)	LGD	RIDE	6.3	6.8	6.6	6.9	7.1	7.2	6.9	7.1	7.1	7.0	6.9	6.9	6.9	6.7	

48080060	1.499	1.830	R	1	4	CRACKING	8.6	8.5	9.1	9.2	9.2	9.2	9.0	9.0	8.9	8.2	7.3	6.9	5.7*		
30 98			2	40	18900	RIDE	7.9	7.6	7.7	7.5	6.4	6.6	6.5	6.6	6.3	6.1	6.7	5.7	5.4*		
S CAHN ST(1.5R)																					
2186371	0.000	2.491	C	1998	0227	CRACKING	5.7*	5.6*	5.6*	5.6*	5.8*	6.8	6.4*	6.4*	7.6	6.8	6.4*	6.2*	6.3*	5.0*	
COUCH CONSTRUCTION LP				(1999)	LGD	RIDE	6.2	6.6	6.6	6.4	6.7	6.8	6.5	6.4	6.7	6.2	6.2	6.2	6.3	6.1	

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = EDWARD CHADBOURNE INC																				
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR																						FUTURE
SR US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012											
INTERSECT AT	(MP SIDE)				%T	=====																								
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P																									
CONTRACTOR	(AGE ONE YEAR)				SURF_TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030										
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F															(PMRS)										
48080060	4.242	4.463	R	1	6	CRACKING	10.0	10.0	8.5	9.0	9.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5											
30 B98			3	30	10900	RIDE	6.6	6.2*	6.0				6.0	5.5	5.5	5.9	5.1*	4.9*	4.3*											
ALCANIZ ST(	4.3R)				4.9																									
2185701	3.459	4.352	C	1995	0215	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	8.0	7.0	6.0*	5.2*	2.5*										
EDWARD CHADBOURNE INC				(1996)	DGFC	RIDE	4.4*																							
4351783	2.378	4.463	C	2024	0012																									

"" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3							CONTRACTOR = FLORIDA ASPHALT PAVING COMPA															
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR															FUTURE
SR	US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)						%T	=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM	X-P																
CONTRACTOR (AGE ONE YEAR)				SURF	TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																(PMRS)	
51010000	8.744	9.326	C	1		1	CRACKING		10.0	10.0	10.0	10.0	10.0	8.5		8.0	7.0	7.0	7.0	7.0		
30 98			2	45	8500		RIDE		8.8	8.8	8.7	8.4	8.3	8.1		8.3	8.2	8.1	8.0	8.0		
PINE ST(8.8R)					11.5																	
2190401	4.092	11.607	C	1999		0012	CRACKING	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.5*	5.5*	5.5*	3.5*	3.5*	1.0*	
FLORIDA ASPHALT PAVING COM(2001)					FC3		RIDE	7.5	7.9	7.7	7.7	7.6	7.5	7.3	7.5	7.4	7.1	7.2	7.3	7.1	6.7	
4335692	8.744	11.633	C	2025		0012																
51010000	11.070	11.633	C	1		1	CRACKING		10.0	10.0	10.0	10.0	10.0	8.5		8.0	7.0	7.0	7.0	7.0		
30 98			2	45	8500		RIDE		8.8	8.8	8.7	8.4	8.3	8.1		8.3	8.2	8.1	8.0	8.0		
FRYER LN(11.1R)					11.5																	
2190401	4.092	11.607	C	1999		0012	CRACKING	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.0*	4.0*	4.0*	4.0*	4.0*	4.0*	1.5*	
FLORIDA ASPHALT PAVING COM(2001)					FC3		RIDE	7.5	7.3	7.3	7.1	7.1	7.1	6.9	7.0	6.8	6.9	6.8	6.7	6.7	6.3	
4335692	8.744	11.633	C	2025		0012																
61080000	15.669	16.802	C	1		8	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	7.0	6.0*		
77			2	55	5807		RIDE	9.0	8.4	8.8	8.8	8.5	8.5	8.5	8.6	8.6	8.5	8.4	8.3	8.2		
FOREST AVE(15.7L)					11.9																	
2207891	15.669	23.236	C	1998		0012	CRACKING	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*			
FLORIDA ASPHALT PAVING COM(2000)					FC3		RIDE	8.0	7.9	7.8	7.7	7.7	7.7	7.6	7.6	7.3	7.3	7.2	7.1			
2179096	13.365	16.846	C	2023		0213																

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3 CONTRACTOR = GAC CONTRACTORS, INC																						
RDWYID	SR	US	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR										FUTURE	
INTERSECT AT (MP SIDE)	AT	MP	W_BMP	W	EMP	RW	FY-P	WKM-F	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012
ITMSEG-P	W_BMP	W	EMP	RW	FY-F	WKM-F	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)
ITMSEG-F	W_BMP	W	EMP	RW	FY-F	WKM-F	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)	CONTRACTOR	(AGE ONE YEAR)
46020000	1.703	2.950	R	1	1	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	9.0	7.0	10.0	10.0	10.0
30 98			2	45	42000	RIDE	6.4*	8.4	8.2	8.1	7.7	7.4	7.0	7.0	7.0	7.0	7.2	7.3	7.1	8.2	8.2	8.0
DANFORD AVE(1.9C)					4.9																	
4169171	1.263	2.962	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.0	7.0	7.0	5.0*
GAC CONTRACTORS, INC					(2010)	FC95M	8.2	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.7	7.7	7.6	7.5	7.3	7.4	7.2
4475941	1.735	3.004	C	2024	0012	RIDE																
46020000	1.703	2.950	L	1	1	CRACKING	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.5	10.0	10.0	10.0
30 98			2	45	42000	RIDE	6.9	8.4	8.4	8.2	7.8	7.4	7.0	7.0	7.0	7.0	7.2	7.3	7.2	8.0	8.3	8.2
BALTIMORE AVE(1.8L)					4.9																	
4169171	1.263	2.962	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.0	7.0	7.0	5.0*
GAC CONTRACTORS, INC					(2010)	FC95M	8.0	8.1	7.7	8.0	7.9	7.6	7.9	7.8	7.9	7.8	7.7	7.7	7.7	7.4	7.6	7.1
4475941	1.735	3.004	C	2024	0012	RIDE																
46040000	1.120	4.050	R	1	1	CRACKING	10.0	10.0	7.5	7.0	7.0	6.0*	6.0*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	
75 231			2	45	34000	RIDE	8.7	8.8	8.6	8.4	8.0	7.9	7.6	7.2	7.2	7.2	7.2	7.0	7.0	7.0	8.7	8.6
SR 30A(1.1C)					3.7																	
4134331	1.193	4.050	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	5.7*	3.5*
GAC CONTRACTORS, INC					(2011)	FC95M	8.4	8.4	8.3	8.2	8.2	7.9	7.9	7.9	7.9	7.7	7.6	7.4	7.3	7.1	7.1	6.7
4508101	1.130	4.058	C	2026	0012	RIDE																
46040000	4.050	10.541	R	1	1	CRACKING	10.0	10.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*		10.0	10.0	
75 231			2	55	36500	RIDE	8.8	8.6	8.5	8.8	8.1	8.1	7.8	7.7	7.7	7.8	7.6	7.6		8.5	8.5	
RAMP TO CR-2327(5.2R)					10.7																	
4134331	6.004	10.541	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.0	7.0	7.0	7.0	6.6	2.5*
GAC CONTRACTORS, INC					(2011)	FC5M	8.4	8.4	8.4	8.6	8.6	8.6	8.7	8.7	8.7	8.6	8.6	8.6	8.6	8.6	8.6	8.3
46040000	16.313	25.245	R	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5
75 231			2	65	15986	RIDE	9.1	9.0	9.0	9.0	8.6	8.5	8.3	8.3	8.3	8.3	8.1	8.0	8.0	7.8	7.4	7.4
BEAR CREEK RD S R(16.6R)					11.2																	
4230601	16.930	25.245	C	2013	0012	CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	4.5*
GAC CONTRACTORS, INC					(2014)	FC5M	7.1	8.2	8.3	8.6	8.6	8.6	8.7	8.7	8.7	8.6	8.6	8.6	8.6	8.7	8.7	8.4
46040000	16.313	25.245	L	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	6.5	6.5	6.5	6.5	4.5*	4.5*
75 231			2	65	15986	RIDE	9.1	9.0	9.0	8.9	8.2	8.2	8.0	8.0	8.0	8.0	7.9	7.6	7.6	7.6	7.4	7.2
CAMP FLOWERS RD N L(16.4L)					11.2																	
4230601	16.930	25.245	C	2013	0012	CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.5	4.5*
GAC CONTRACTORS, INC					(2014)	FC5M	7.0	8.1	8.3	8.6	8.6	8.5	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.5	8.3
46040000	4.050	10.541	L	1	1	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	6.5		10.0	10.0	
75 231			2	55	36500	RIDE	8.9	8.8	8.7	8.8	8.3	8.3	8.1	8.1	8.1	8.1	8.2	8.1	8.1		8.6	8.5
WAKULLA AVE(4.1L)					10.7																	
4134331	6.004	10.541	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.2	3.5*
GAC CONTRACTORS, INC					(2011)	FC5M	8.5	8.4	8.4	8.7	8.6	8.6	8.8	8.7	8.8	8.7	8.8	8.7	8.7	8.7	8.6	8.4
46040000	1.120	4.050	L	1	1	CRACKING	10.0	10.0	8.5	8.5	7.5	7.5	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0	10.0	
75 231			2	45	34000	RIDE	8.6	8.7	8.5	8.3	7.8	7.1	7.3	7.4	7.3	7.4	7.3	6.7	6.9	8.6	7.8	
SR 30A(1.1C)					3.7																	
4134331	1.193	4.050	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	6.5	4.5*
GAC CONTRACTORS, INC					(2011)	FC95M	8.5	8.2	8.4	8.3	8.3	8.1	8.2	8.0	7.9	7.9	7.9	7.7	7.6	7.5	7.1	
4508101	1.130	4.058	C	2026	0012	RIDE																
57030030	20.481	22.600	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
30 98			3	45	46500	RIDE	8.5	8.4	8.4	8.1	7.8	7.7	7.3	7.3	7.3	7.3	7.8	8.6	8.5	8.5	8.4	
CR 2378(20.6R)					3.2																	
4141323	20.947	22.231	R	2017	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0	10.0	10.0	8.5
GAC CONTRACTORS, INC					(2021)	FC95M	8.4	8.3	8.3	7.8	8.1	8.2				7.9	7.7	7.8	7.7	7.7	7.6	7.2
57030030	23.230	24.529	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	10.0	10.0	10.0	10.0	10.0
30 98			3	45	53000	RIDE	8.7	8.6	8.5	8.3	7.9	8.1	7.8	7.7	7.8	7.7	8.0	8.6	8.5	8.5	8.4	
KEL WEN CIR(23.3R)					4.4																	
4141323	23.391	24.529	R	2017	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	8.5
GAC CONTRACTORS, INC					(2022)	FC95M	8.4	8.3	8.3	7.8	8.1	8.2						7.8	7.8	7.8	7.8	7.4
57030030	23.230	24.529	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
30 98			3	45	53000	RIDE	8.8	7.9	8.6	8.4	8.0	7.7	7.4	7.4	7.4	7.2	8.0	8.7	8.5	8.5	8.3	
LEGENDARY DR(23.4L)					4.4																	
4141323	23.391	24.529	L	2017	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	8.5
GAC CONTRACTORS, INC					(2022)	FC95M	8.4	7.9	8.4	8.2	8.2	8.3						7.4	7.3	7.3	7.3	6.9

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3							CONTRACTOR = GAC CONTRACTORS, INC																			
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR										FUTURE									
SR	US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012						
INTERSECT AT (MP SIDE)							%T																			
ITMSEG-P							W_BMP	W_EMP	RW	FY-P	WKMX-P															
CONTRACTOR							(AGE ONE YEAR)	SURF_TYPE	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030				
ITMSEG-F							W_BMP	W_EMP	RW	FY-F	WKMX-F											(PMRS)				
57030030							20.481	22.600	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0				
30 98									3	45	46500	RIDE	8.4	8.1	8.1	7.6	7.4	7.3	7.0	6.9	8.1	8.7	8.5	8.3		
INDIAN BAYOU TR							(20.9L)																			
4141323							20.947	22.231	L	2017	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0	9.7	8.5		
GAC CONTRACTORS, INC									(2021)	FC95M	RIDE	8.4	7.9	8.4	8.2	8.2	8.3		8.0	7.8	7.8	7.8	7.7	7.3		

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

----- DISTRICT = 3 CONTRACTOR = GLF CONSTRUCTION CORPORATION -----																					
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)					%T	=====															
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-F	P															
CONTRACTOR (AGE ONE YEAR)					SURF_TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-F															(PMRS)	
58040000	11.595	14.352	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	10.0	8.5	8.5	7.0	7.0	5.5*	6.0*		
87			2	65	16100	RIDE	8.9	8.9	8.8	8.7	8.2	8.5	8.5	8.4	8.5	8.4	8.3	8.3	8.3		
SIDE ROAD(12.2C)					11.8																
2204427	12.110	16.266	C	2016	0213	CRACKING	6.0*	6.0*	5.5*	5.5*				10.0	10.0	10.0	10.0	10.0	9.6	7.5	
GLF CONSTRUCTION					FC5M	RIDE	8.3	8.1	8.1	8.1				8.7	8.6	8.4	8.4	8.3	8.2	8.0	
58040000	15.251	16.442	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.5		
87			2	65	16100	RIDE	8.8	8.7	8.7	8.6	8.4	8.4	8.3	8.3	8.6	8.6	8.5	8.5	8.6		
LIBBY LN(15.8R)					11.8																
2204427	12.110	16.266	C	2016	0213	CRACKING	7.5	7.5	7.5	7.5				10.0	10.0	10.0	10.0	10.0	9.6	7.5	
GLF CONSTRUCTION					FC5M	RIDE	8.5	8.5	8.2	8.4				8.6	8.4	8.3	8.3	8.3	8.2	8.0	
58040000	15.251	16.442	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.5		
87			2	65	16100	RIDE	8.8	8.7	8.7	8.6	8.4	8.4	8.3	8.3	8.6	8.6	8.5	8.5	8.6		
FARRINGTON RD(15.7L)					11.8																
2204427	12.110	16.266	C	2016	0213	CRACKING	7.5	7.5	7.5	7.5				10.0	10.0	10.0	10.0	10.0	10.0	8.0	
GLF CONSTRUCTION					FC5M	RIDE	8.5	8.5	8.2	8.4				8.5	8.4	8.2	8.0	8.1	8.1	7.9	
58040000	11.595	14.352	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	10.0	8.5	8.5	7.0	7.0	5.5*	6.0*		
87			2	65	16100	RIDE	8.9	8.9	8.8	8.7	8.2	8.5	8.5	8.4	8.5	8.4	8.3	8.3	8.3		
SIDE ROAD(12.2C)					11.8																
2204427	12.110	16.266	C	2016	0213	CRACKING	6.0*	6.0*	5.5*	5.5*				10.0	10.0	10.0	10.0	10.0	10.0	8.0	
GLF CONSTRUCTION					FC5M	RIDE	8.3	8.1	8.1	8.1				8.7	8.4	8.2	8.2	8.1	8.0	7.8	

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = GRANGER ASPHALT PAVING INC												
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR														FUTURE
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
INTERSECT AT (MP SIDE)					%T	=====																
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P																	
CONTRACTOR (AGE ONE YEAR)					SURF TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F															(PMRS)		
46001000	0.000	3.576	R	1	1	CRACKING	7.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0			
368			2	45	31000	RIDE	7.3	7.1		8.1	7.9	7.8	7.7	7.7	7.8	7.7	7.2	7.5	7.3			
BECK AVE(0.0R)					2.9																	
2179851	0.000	2.900	C	2001	0012	CRACKING	9.0	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	4.5*		
GRANGER ASPHALT PAVING INC(2003)					FC125	RIDE	7.3	7.2	7.4	7.4	7.4	7.0	7.2	7.3	7.2	7.2	7.1	7.1	7.0	6.6		
4508181	0.098	3.567	C	2026	0012																	
46001000	0.000	3.576	L	1	1	CRACKING	7.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0			
368			2	45	31000	RIDE	7.2	7.1		8.3	7.6	7.8	7.6	7.7	7.8	7.8	7.7	7.6	7.4			
ST ANDREWS BLVD(0.0L)					2.9																	
2179851	0.000	2.900	C	2001	0012	CRACKING	9.0	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	7.0	7.0	4.5*		
GRANGER ASPHALT PAVING INC(2003)					FC125	RIDE	7.4	7.4	7.4	7.4	7.4	7.3	7.3	7.3	7.3	7.2	7.1	7.1	7.1	6.7		
4508181	0.098	3.567	C	2026	0012																	

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = GULF-ATLANTIC CONSTRUCTORS,																			
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR													FUTURE									
SR US	G BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012										
INTERSECT AT (MP SIDE)					%T	=====																							
ITMSEG-P	W BMP	W_EMP	RW	FY-P	WKMX-P																								
CONTRACTOR (AGE ONE YEAR)				SURF_TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)									
ITMSEG-F	W BMP	W_EMP	RW	FY-F	WKMX-F																								
48080000	1.042	1.539	R	1	4	CRACKING	5.6*	5.0*	5.3*		9.0	9.0	9.0	9.0	9.0	9.3	9.1	8.5	8.3										
295			2	35	24000	RIDE	5.5*	5.4*	5.1*		4.7*	5.8	5.2*	4.9*	4.7*	4.9*	5.1*	4.8*	4.8*										
SCHOOL ENT(1.1R)																													
2186911	0.960	1.683	C	2002	0227	CRACKING	8.3	8.1	8.0	8.5	8.9	9.0	9.0	9.0	9.0	9.0	8.8	8.8	8.8	8.0									
GULF-ATLANTIC CONSTRUCTORS(2004)					LGD	RIDE	4.9*	4.9*	4.8*	5.9	7.5	7.6	7.7	7.5	7.6	7.3	7.5	7.6	7.4	7.2									
4090132	1.043	4.704	C	2026	0012																								

48080000	1.042	1.539	L	1	2	CRACKING	6.9	6.3*	5.9*		9.0	9.0	9.0	9.0	9.0	9.5	8.6	9.2	7.6										
295			2	35	24000	RIDE	5.7*	6.0*	5.8		4.7*	5.7	5.3*	5.9	5.3*	5.1*	5.3*	5.5	5.3*										
RAYMOND ST(1.1L)																													
2186911	0.960	1.683	C	2002	0227	CRACKING	7.5	8.1	8.0	8.3	8.8	9.1	9.1	9.1	9.1	8.8	8.5	8.3	8.7	7.5									
GULF-ATLANTIC CONSTRUCTORS(2004)					LGD	RIDE	5.4*	5.9	5.5	6.6	7.8	7.8	7.9	7.6	7.7	7.4	7.7	7.8	7.3	7.1									
4090132	1.043	4.704	C	2026	0012																								

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = JONES CONSTRUCTION OF NORTHW													
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR														FUTURE		
SR	US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKMX-P	%T	=====																
ITMSEG-F	CONTRACTOR (AGE ONE YEAR)				SURF_TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)		
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																		
53020000	18.617	19.446	R	1	1	CRACKING	10.0	10.0	9.0	9.0	9.0	8.5	8.5	7.5	7.0	7.0	6.5	6.5	6.5				
10 90			2	45	7800	RIDE	7.9	8.1	7.9	7.6	7.3	7.4	7.6	7.7	7.7	7.5	7.4	7.2	6.8				
0 HARA AVE(18.7C)						8.9																	
4246151	18.679	19.456	C	2013	0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.0	6.0*	6.1*	4.5*			
JONES CONSTRUCTION OF NORT(2014)					FC95M	RIDE	6.6	8.1	8.0	7.9	7.8	7.7	7.6	7.5	7.4	7.3	7.2	7.0	6.9	6.5			
4531511	15.571	23.661	C	2027	0012																		
53020000	18.617	19.446	L	1	1	CRACKING	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.5	6.5	7.0	6.5	6.5	6.5				
10 90			2	45	7800	RIDE	8.2	8.2	8.1	7.9	7.6	7.5	7.3	7.4	7.2	7.5	7.4	7.2	6.8				
0 HARA AVE(18.7C)						8.9																	
4246151	18.679	19.456	C	2013	0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	6.0*	6.0*	4.7*	3.0*			
JONES CONSTRUCTION OF NORT(2014)					FC95M	RIDE	6.6	8.1	8.0	7.9	7.8	7.7	7.6	7.5	7.4	7.3	7.3	7.3	7.3	6.9			
4531511	15.571	23.661	C	2027	0012																		
53060000	8.363	10.726	C	1	1	CRACKING	10.0	10.0	8.5	8.5	8.5	6.5	6.5	6.5	5.5*	5.5*	3.5*	3.5*	10.0				
77			2	35	2952	RIDE	8.4	8.3	8.2	8.0	7.5	7.4	7.1	7.3	7.1	6.8	6.6	6.4	7.9				
BROWN ST(8.4R)						7.4																	
4193061	8.363	10.724	C	2010	0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	7.0	5.5*	4.0*	4.0*	3.3*	1.5*			
JONES CONSTRUCTION OF NORT(2012)					FC95M	RIDE	7.7	7.7	7.6	7.8	7.7	7.6	7.4	7.5	7.4	7.3	7.1	7.1	7.0	6.6			
2193462	8.363	10.726	C	2025	0012																		
53070000	1.323	7.643	C	1	1	CRACKING		10.0	10.0	10.0	10.0	8.5	7.5	7.0	5.5*	5.0*	3.0*	3.0*	10.0				
2			2	55	2200	RIDE		8.9	8.7	8.6	8.2	8.2	8.1	8.2	8.0	7.8	7.3	7.5	8.6				
COTTON ST(1.3C)						15.0																	
4230701	1.332	8.116	C	2011	0226	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	7.0	6.0*	5.5*	4.8*	3.0*			
JONES CONSTRUCTION OF NORT(2012)					FC95M	RIDE	8.5	8.5	8.2	8.2	7.9	7.8	7.6	7.7	7.5	7.4	7.3	7.2	7.1	6.7			
4508061	1.323	7.643	C	2026	0012																		

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3							CONTRACTOR = KIEWIT INFRASTRUCTURE SOUTH													
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR													FUTURE
SR US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
INTERSECT AT	(MP SIDE)				%T	=====														
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P															
CONTRACTOR	(AGE ONE YEAR)				SURF_TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F															(PMRS)
51020000	0.000	0.415	R	1	4	CRACKING	5.1*	4.9*	4.4*	4.8*	5.4*		8.5	8.4	6.7	6.3*	7.8	7.7	7.2	
71			2	35	4600	RIDE	4.3*	5.1*	5.3*	5.0*	4.5*		6.7	6.3	6.5	6.3	6.2	5.1*	5.6	
C C SIMMS PKWY(	0.00C)				14.0															
4090041	0.000	0.413	C	2004	0227	CRACKING	8.1	7.9	7.9	7.8	7.7	7.8	7.8	7.5	7.3	6.1*	5.8*	5.7*	5.7*	5.0*
KIEWIT INFRASTRUCTURE SOUT(2006)					LGD	RIDE	6.3	5.9	6.2	6.7	6.6	6.9	6.2	6.5	6.5	6.4	6.2	6.2	6.2	6.0
4307941	0.006	0.419	C	2026	0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = M OF TALLAHASSEE, INC.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
RDWYID	SR	US	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							</

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = OGLESBY CONSTRUCTION INC.																				
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR																						FUTURE
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012											
INTERSECT AT (MP SIDE)					%T	=====																								
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKMX-P																									
CONTRACTOR (AGE ONE YEAR)					SURF TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025											
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																								2030 (PMRS)	
55060000	3.580	6.150	R	1	1	CRACKING	7.0	7.0	7.0	7.0	6.0*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.5										
10 90			2	45	33500	RIDE	8.0	7.7	7.7	7.6	6.8	6.5		8.1	8.0	7.9	7.9	7.9	7.6	7.6										
BLOUNTSTOWN HWY(4.3R)					2.9																									
4039422	3.532	6.301	C	2006	0774	CRACKING	9.5	9.5	9.5	9.5	9.5	8.0	8.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	4.6*	2.5*									
OGLESBY CONSTRUCTION INC. (2007)					FC125	RIDE	7.6	7.9	7.8	7.3	7.5	7.4	7.2	7.3	7.3	7.3	7.2	7.0	6.9	6.5										
4269373	2.200	6.151	C	2024	0012																									
55060000	3.580	6.150	L	1	1	CRACKING	7.0	7.0	7.0	6.0*	5.5*	5.5*		10.0	10.0	10.0	9.5	9.5	9.5											
10 90			2	45	33500	RIDE	8.0	7.8	7.8	7.7	6.7	6.3*		8.2	8.1	8.1	8.1	8.0	8.0											
ASTER LAKE BLVD(4.0L)					2.9																									
4039422	3.532	6.301	C	2006	0774	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	7.0	6.5	5.5*	5.5*	5.5*	5.5*	5.3*	3.0*										
OGLESBY CONSTRUCTION INC. (2007)					FC125	RIDE	7.8	8.0	7.9	7.8	7.7	7.7	7.3	7.4	7.5	7.6	7.5	7.4	7.2	6.8										
4269373	2.200	6.151	C	2024	0012																									

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3							CONTRACTOR = OLDCASTLE MATERIALS SOUTHEAS															
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR														FUTURE	
SR	US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
INTERSECT AT (MP SIDE)																						
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P	%T	=====															
CONTRACTOR	(AGE_ONE_YEAR)				SURF_TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																	(PMRS)
60002000	0.000	18.225	L	4	1	CRACKING	8.1	8.1		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5			
8	I10	67.0	85.2	2	70	27662	RIDE	6.4*	6.6		8.7	8.3	8.4	8.3	8.1	8.3	8.1	8.0	7.8	7.6		
						13.9																
4309082	0.000	11.225	C	2015	0012	CRACKING	6.5	6.5	4.5*		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.3	6.5		
OLDCASTLE	MATERIALS	SOUTHE	(2017)		FC5M	RIDE	7.5	7.3	6.8		8.8	8.7	8.6	9.0	9.0	9.0	8.9	8.9	8.9	8.8		

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3						CONTRACTOR = OXFORD CONSTRUCTION COMPANY														
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR													FUTURE
SR US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
INTERSECT AT (MP SIDE) %T =====																				
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P															
CONTRACTOR (AGE ONE YEAR)				SURF_TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F															(PMRS)
53090000	14.073	17.840	C	1	1	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.0	6.0*	
71			2	55	2100	RIDE	8.9	8.8	8.7	8.5	8.0	8.1	8.0	8.1	7.9	7.7	7.4	7.5	7.0	
FOURTH AVE(14.1L) 14.0																				
4307821	14.091	17.887	C	2015	0226	CRACKING	5.5*	5.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.8	6.0*
OXFORD CONSTRUCTION COMPAN(2016) FC95M						RIDE	6.3*	6.1*	5.9*	8.6	8.4	8.4	8.2	8.2	8.1	8.0	7.9	7.8	7.6	7.2

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

		DISTRICT = 3										CONTRACTOR = PEAVY & SON CONSTRUCTION CO.												
RDWYID	SR	US	BMP	G	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE
INTERSECT AT (MP SIDE)									RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-F	P			=====															
CONTRACTOR (AGE ONE YEAR)										2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	(PMRS)
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F	F																		
55002000	13.615	15.081	R	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	7.0	7.0	6.5	4.5*	4.5*	4.5*	4.5*	10.0					
263				45	13500	RIDE	8.5	8.2	8.1	8.2	7.9	7.9	7.7	7.8	7.7	7.6	7.2	7.3	8.1					
CAPITAL CIR COMMERCE(14.0R)					7.7																			
4193071	11.849	15.045	C	2011	0226	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.4	5.5*		
PEAVY & SON CONSTRUCTION					FC95M	RIDE	8.1	8.1	8.4	8.0	8.1	7.9	8.0	8.0	8.0	7.9	7.7	7.6	7.5	7.5	7.5	7.1		
55002000	13.615	15.081	L	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	7.0	7.0	6.5	4.5*	4.5*	4.5*	4.5*	10.0					
263				45	13500	RIDE	8.5	8.2	8.1	8.2	7.9	7.9	7.7	7.8	7.7	7.6	7.2	7.3	8.1					
STONELER RD(13.6L)					7.7																			
4193071	11.849	15.045	C	2011	0226	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	6.6	4.5*		
PEAVY & SON CONSTRUCTION					FC95M	RIDE	8.1	8.1	8.4	8.0	8.1	7.9	8.0	8.0	8.0	7.6	7.5	7.5	7.2	7.4	7.0			
55010000	0.000	2.047	R	1	1	CRACKING	7.0	7.5	5.5*	5.5*	4.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
63 27				55	16400	RIDE	8.5	8.4	8.1	7.8	6.6	6.6		8.2	8.4	8.4	8.3	8.3	8.2					
BELKNAP RD(1.7R)					10.6																			
4397391	0.000	2.052	R	2021	0012	CRACKING	10.0	9.5	9.0	9.0	9.0	6.5	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	8.5			
PEAVY & SON CONSTRUCTION					FC5M	RIDE	8.3	8.2	8.2	8.3	8.3	8.4	8.2	8.3	8.2	8.1	8.7	8.8	8.7	8.5				
55010000	7.373	8.108	L	1	1	CRACKING	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	7.5					
63 27				45	40500	RIDE	7.1	6.5	5.8*	8.7	8.1	8.2	8.2	8.2	8.0	8.1	7.9	7.8	7.5					
SHARER RD(7.5L)					5.4																			
4104092	7.397	8.006	L	2016	0547	CRACKING	7.5	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	6.5				
PEAVY & SON CONSTRUCTION					FC125	RIDE	7.4	7.4	7.3	7.1	8.1	8.0	8.0	8.2	8.1	8.1	7.7	7.8	8.0	8.0	7.6			
4529391	2.058	8.108	C	2027	0012																			
55010000	0.000	2.132	L	1	1	CRACKING	6.0*	5.5*	3.5*	3.5*	3.5*	1.0*		10.0	10.0	10.0	10.0	9.5						
63 27				55	16400	RIDE	8.7	8.5	8.2	8.0	6.5	6.4*		8.4	8.4	8.3	8.2	8.2	8.2					
CARTER TR(1.2L)					10.6																			
4397391	0.000	2.052	L	2021	0012	CRACKING	9.5	6.5	6.5	6.5	6.5	6.5	3.5*	0.0*	0.0*	0.0*	10.0	10.0	9.4	8.0				
PEAVY & SON CONSTRUCTION					FC5M	RIDE	8.0	7.9	7.9	8.1	8.0	8.1	8.0	7.9	7.9	7.8	8.9	8.8	8.7	8.5				
55020000	1.126	3.425	R	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	7.5	6.5	6.5	6.5	6.5					
10 90				45	26000	RIDE	8.8	8.0	7.9	8.1	8.0	8.0	7.9	7.7	7.7	7.4	7.4	7.2	7.0					
MAGNOLIA DR(1.1C)					2.9																			
4269611	1.126	3.335	C	2015	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0	8.7	7.0				
PEAVY & SON CONSTRUCTION					FC95M	RIDE	7.1	7.0	6.7	7.9	8.1	8.1	8.0	8.0	8.1	7.9	7.9	7.9	8.0	7.6				
55020000	1.126	3.425	L	1	1	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.0	6.5	6.5	6.5	6.5	4.5*					
10 90				45	26000	RIDE	8.7	8.4	8.5	8.2	7.8	7.5	7.9	8.0	7.6	7.4	7.6	7.0	7.3					
MAGNOLIA DR(1.1C)					2.9																			
4269611	1.126	3.335	C	2015	0012	CRACKING	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5				
PEAVY & SON CONSTRUCTION					FC95M	RIDE	7.0	7.3	7.1	8.0	8.2	8.0	8.0	8.1	7.9	7.9	7.9	7.6	8.0	7.6				
55040000	8.825	9.485	R	1	1	CRACKING	10.0	10.0	10.0	9.5	8.0	6.0*	6.0*	5.5*	3.5*	1.0*	0.0*	10.0	10.0					
363				35	14200	RIDE	8.1	7.8	7.7	7.8	6.7	5.9	5.3*	4.9*	4.3*	4.0*	4.0*	8.0	8.0					
SUNDAY CT(8.8R)					7.0																			
4192961	8.845	9.485	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.5	7.5	7.5	5.5*				
PEAVY & SON CONSTRUCTION					FC95M	RIDE	8.1	8.1	8.0	7.9	7.7	7.7	7.4	7.7	7.4	7.3	6.8	6.7	6.7	6.3				
55040000	9.485	10.603	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	6.5	6.5	6.5					
61				35	18800	RIDE	8.3	7.8	7.9	7.7	6.7	6.9	6.8	6.6	6.7	6.2	6.0	6.5	6.8					
LAURA LEE AVE(9.7R)					7.0																			
4415471	9.516	10.612	R	2021	0012	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.0*	5.5*	5.5*	3.5*	10.0	10.0	10.0	8.5				
PEAVY & SON CONSTRUCTION					FC125	RIDE	7.0	6.6	6.6	6.5	6.8	6.8	6.5	6.6	6.3	6.3	8.1	8.0	8.0	7.6				
55040000	9.485	10.603	L	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	7.0	7.0	6.5	6.5	6.5					
61				35	18800	RIDE	8.1	7.7	7.7	7.9	7.3	7.1	7.1	7.1	7.2	6.9	6.9	7.0	6.6					
BASS ST(9.6L)					7.0																			
4415471	9.516	10.612	L	2021	0012	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	3.5*	10.0	10.0	10.0	10.0	8.5				
PEAVY & SON CONSTRUCTION					FC125	RIDE	6.5	6.5	6.3	6.8	6.5	6.6	6.2	6.3	6.3	6.4	8.1	8.0	8.4	8.0				
55040000	8.825	9.485	L	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5	6.0*	4.5*	4.5*	3.5*	10.0	10.0					
363				35	14200	RIDE	7.9	7.6	7.4	7.6	7.1	6.2	6.0	5.7	5.2*	5.0*	8.5	8.3						
SR 61A(8.9L)					7.0																			
4192961	8.845	9.485	C	2010	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	7.8	6.0*					
PEAVY & SON CONSTRUCTION					FC95M	RIDE	8.5	8.3	8.3	7.7	8.1	8.1	7.4	7.7	7.8	7.7	7.6	7.4	7.5	7.1				

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

CONTRACTOR = PEAVY & SON CONSTRUCTION CO.

RDWID	SR	US	BMP	G_BMP	EMP	W	LN	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR										FUTURE			
INTERSECT	AT	(MP)	(SIDE)					SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
ITMSEG-P	W_BMP	W_EMP	W_C	W_R	FY-P	WKMX-P			%T	=====														
CONTRACTOR	(AGE ONE YEAR)				FY-F	WKMX-F					2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F	W_BMP	W_EMP	W_C	W_R	FY-F	WKMX-F																		
55120000 61	6.838	7.498	L	1	2	45	16400	CRACKING RIDE	10.0 7.6	10.0 7.7	10.0 7.1	10.0 7.7	9.5 6.6	9.5 5.9*	9.5 5.4*	9.5 6.0	6.5 5.1*	6.5 5.3*	3.5* 4.5*	10.0 8.2	10.0 8.2			
ARDEN RD (6.8L)																								
4193501	6.853	7.483	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.5	7.7	5.5*	
PEAVY & SON CONSTRUCTION			C(2011)		FC95M	RIDE	8.1	8.3	8.2	8.1	8.1	8.1	7.9	7.9	7.7	7.7	7.5	7.6	7.1	7.3	6.9			
4508111	6.838	7.498	C	2026	0012																			
55120001 61A	0.000	0.103	C	2	1	45	16400	CRACKING RIDE		10.0 5.3*	10.0 4.6*	10.0	10.0	9.0	9.0	9.0	9.0	9.0	6.5	10.0	10.0			
CRAWFORDVILLE HWY(0.0C)																								
4193501	0.000	0.103	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.1	6.0*		
PEAVY & SON CONSTRUCTION			C(2011)			RIDE																		
4508111	0.000	0.103	C	2026	0012																			
55170000 369 319	1.627	3.296	C	2	1	55	14300	CRACKING RIDE	10.0 9.1	10.0 8.4	9.5 8.7	9.5 8.7	9.5 8.2	9.5 8.3	9.5 8.3	7.0 8.4	7.0 8.4	6.5 8.2	6.5 8.0	6.5 7.4	6.5 7.7			
CR 2204(1.7R)																								
4246161	2.528	3.291	C	2015	0012	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0	7.0	5.5*		
PEAVY & SON CONSTRUCTION			C(2016)		FC95M	RIDE	7.6	7.6	9.0	8.8	8.6	8.6	8.4	8.5	8.4	8.5	8.4	8.4	8.3	8.3	7.9			
55180000 61	0.000	0.184	R	2	1	45	5800	CRACKING RIDE		10.0 5.5*	10.0 5.5*	10.0 4.5*	10.0 4.7*	9.5 4.3*	9.5	9.5	9.5	9.5	9.5	10.0	10.0			
SR-61/ADAMS ST(0.0R)																								
4193501	0.000	0.184	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	7.0	6.5	4.5*		
PEAVY & SON CONSTRUCTION			C(2011)		DGFC	RIDE																		
4508111	0.000	0.184	C	2026	0012																			
55180000 61	0.000	0.184	L	2	1	45	5800	CRACKING RIDE		10.0 7.7	10.0 7.0	10.0 6.4*	10.0 5.5*	9.5 4.8*	9.5	9.5	9.5	9.5	9.5	10.0	10.0			
SR-363/ADAMS ST(0.0L)																								
4193501	0.000	0.184	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	8.0	7.0	5.0*		
PEAVY & SON CONSTRUCTION			C(2011)		DGFC	RIDE																		
4508111	0.000	0.184	C	2026	0012																			
55300000 267	0.000	14.159	C	2	1	60	1950	CRACKING RIDE	7.0 8.9	6.0* 8.4	5.5* 8.7	3.5* 8.7	3.5* 8.0		10.0 8.5	10.0 8.7	10.0 8.4	10.0 8.7	10.0 8.5	10.0 8.7	10.0 8.6	10.0 8.6		
SR-267/SR-267(0.0R)																								
4090121	0.005	14.167	C	2004	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	8.0	8.0	8.0	6.9	4.5*		
PEAVY & SON CONSTRUCTION			C(2006)		FC95	RIDE	8.7	8.6	8.6	8.5	8.6	8.6	8.6	8.5	8.6	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.1	
55320000 8 I10	10.137 203.7	15.665 209.2	R	2	4	70	37500	CRACKING RIDE	9.5 8.9	9.5 8.7	9.5 8.6	8.0 8.6	7.0 7.9	6.5 7.8	6.5 7.8	4.5* 7.7	4.5* 7.7	10.0 8.5	10.0 8.4	10.0 8.5	10.0 8.4			
SR-61/ADAMS ST(0.0R)																								
4176431	10.096	13.787	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	7.0	6.5	6.5	4.5*	4.5*	1.5*			
PEAVY & SON CONSTRUCTION			C(2009)		FC5M	RIDE	8.3	8.3	8.2	8.5	8.5	8.5	8.6	8.5	8.5	8.6	8.5	8.6	8.5	8.4	8.4	8.3	8.2	
4176432	10.137	15.628	C	2025	0012																			
55320000 8 I10	15.665 209.2	22.200 215.8	R	2	4	70	29000	CRACKING RIDE	10.0 8.6		10.0 8.9	10.0 8.9	10.0 8.4	10.0 8.3	10.0 8.3	9.5 8.5	9.5 8.4	9.5 8.3	9.5 7.9	9.5 8.2	9.5 8.1	7.0 8.1		
SR-267/SR-267(0.0R)																								
4289391	15.643	22.200	C	2014	0012	CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.3	6.0*		
PEAVY & SON CONSTRUCTION			C(2015)		FC5M	RIDE	7.8	7.8	8.6	9.0	9.0	9.0	9.1	9.2	9.2	9.2	9.2	9.1	9.1	9.1	9.1	9.1	9.0	
55320000 8 I10	15.665 209.2	22.200 215.8	L	2	4	70	29000	CRACKING RIDE	10.0 8.8		10.0 9.0	10.0 8.9	10.0 8.2	10.0 8.0	10.0 8.1	9.5 8.0	9.5 8.3	7.0 8.0	7.0 7.8	7.0 6.4*	7.0 5.6*			
SR-267/SR-267(0.0R)																								
4289391	15.643	22.200	C	2014	0012	CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.0	8.3	6.0*		
PEAVY & SON CONSTRUCTION			C(2015)		FC5M	RIDE	6.6	7.3	8.6	8.9	8.9	8.9	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.0	
55320000 8 I10	10.137 203.7	15.665 209.2	L	2	4	70	37500	CRACKING RIDE	9.5 9.0	9.5 8.8	9.5 8.8	8.0 8.7	7.0 8.0	6.5 7.9	6.5 7.8	4.5* 7.8	4.5* 7.7	10.0 8.5	10.0 8.4	10.0 8.4	10.0 8.4			
SR-61/ADAMS ST(0.0R)																								
4176431	10.096	13.787	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	6.5	4.5*	4.0*	1.0*			
PEAVY & SON CONSTRUCTION			C(2009)		FC5M	RIDE	8.4	8.3	8.3	8.5	8.5	8.5	8.6	8.6	8.6	8.6	8.6	8.6	8.4	8.4	8.3	8.2		
4176432	10.137	15.628	C	2025	0012																			
56010000 20	12.862	20.970	C	2	1	60	4200	CRACKING RIDE	3.5* 6.8	0.0* 6.7		10.0 9.2	10.0 9.0	10.0 8.9	10.0 8.8	10.0 8.8	9.0 8.8	9.0 8.7	9.0 8.7	7.5 8.6	7.5 8.5			
HOG PEN CAMP GROUND RD(13.8L)																								
4362701	13.057	18.823	C	2019	0012	CRACKING	7.5	7.0	7.0	6.0*	6.0*	6.0*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5		
PEAVY & SON CONSTRUCTION			C(2021)		FC95M	RIDE	8.4	8.3	8.2	8.2	8.1	8.2	8.2	8.2	8.1	8.8	8.7	8.8	8.7	8.7	8.7	8.7	8.3	

** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 ** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.

"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.

2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3																									CONTRACTOR = PHOENIX CONSTRUCTION SERVICE									
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR															FUTURE												
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012															
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKMX-P	%T																												
ITMSEG-P	CONTRACTOR (AGE ONE YEAR)				SURF TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030														
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																				(PMRS)									
48260000	13.370	16.549	R	4	1	CRACKING	8.6	8.5		10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5											
8 I10	13.4	16.5	3	70	70500	RIDE	7.7	7.7		8.9	8.4	8.3	7.1		7.6	8.1	8.1	8.0	8.0	8.0	8.0	8.0	8.0											
					17.3																													
2224771	13.809	16.418	C	2014	0213	CRACKING	9.5	9.5	9.5	9.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	7.0	7.0											
PHOENIX CONSTRUCTION SERVI(2019)					FC5M	RIDE	7.9	7.9	7.4	8.2			8.7	8.6	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.7	8.6											
48260000	13.500	16.549	L	4	1	CRACKING	8.3	8.0		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5											
8 I10	13.5	16.5	3	70	70500	RIDE	7.9	7.4		8.8	8.4	8.4	8.3	8.3	8.1	8.2	8.1	7.9	7.8	7.8	7.8	7.8	7.8											
					17.3																													
2224771	13.809	16.418	C	2014	0213	CRACKING	9.0	7.0	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	7.5											
PHOENIX CONSTRUCTION SERVI(2019)					FC5M	RIDE	7.8	7.8	7.4	8.0			8.5	8.5	8.6	8.6	8.5	8.5	8.5	8.5	8.5	8.4	8.4											

"" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3 CONTRACTOR = PREFERRED MATERIALS, INC.

ROWID	SR	US	BMP	G_BMP	EMP	W_EMP	RW	LN	SYSTEM	TYPE	ADT	DISTRESS	SURVEYED YEAR										FUTURE				
													RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008		2009	2010	2011	2012
INTERSECT	AT	(MP)	(SIDE)																								
ITMSE	G-P	W_BMP	W_EMP	RW	FY	P	WKMX	P																			
CONTRACTOR	(AGE ONE YEAR)																										
ITMSE	F	W_BMP	W_EMP	RW	FY	F	WKMX	F																			
48003000			6.005		7.281	R		1		1	CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	9.5	9.5	9.5	9.5			
289						2	45	24000		3.1	RIDE	6.4*	7.6	7.7	7.4	6.7	6.5	7.5	7.6	7.6	6.9	7.7	7.6	7.5			
CREIGHTON RD(6.1C)																											
4063211			6.013		6.627	C	2005			0012	CRACKING	9.5	9.5	9.5	9.5	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	5.1*	3.0*		
4063211									(2006)	FC3	RIDE	7.5	7.6	6.9	7.2	6.5	6.9	6.9	6.9	6.9	6.6	6.8	6.8	6.8	6.4		
PREFERRED MATERIALS, INC. (2006)																											
48003000			6.005		6.750	L		1		1	CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0		
289						2	45	24000		3.1	RIDE	7.9	7.9	7.8	7.5	6.8	6.9	7.6	7.7	7.8	7.3	7.9	7.6	7.6	7.6		
FROM SR 742 EB(6.0L)																											
4063211			6.013		6.627	C	2005			0012	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	4.0*		
4063211									(2006)	FC125	RIDE	7.5	7.7	7.3	6.8	6.5	6.7	6.6	6.7	6.4	6.5	6.5	6.5	6.5	6.1		
PREFERRED MATERIALS, INC. (2006)																											
4269342			6.053		7.281	L	2024			0012																	
PREFERRED MATERIALS, INC. (2024)																											
48006000			0.000		0.490	R		1		1	CRACKING	8.0	8.0	8.0	7.0	7.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
196						2	35	17700		8.7	RIDE	6.6	6.6	6.9	6.5	6.2		6.3	6.8		6.5	7.9	7.8	7.7	7.7		
RR #339739(0.0C)																											
4153731			0.014		0.501	C	2009			0012	CRACKING	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	5.0*		
4153731							(2010)			FC125	RIDE	7.8	8.0	7.9	6.9	7.2	7.1	7.0	7.1	6.7	6.8	6.8	6.6	6.7	6.3		
PREFERRED MATERIALS, INC. (2010)																											
48006000			0.000		0.490	L		1		1	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	10.0	10.0	10.0	10.0		
196						2	35	17700		8.7	RIDE	7.5	7.2	7.2	6.8	6.0	6.2	6.3	6.0		6.3	7.3	7.3	7.1	7.1		
TARRAGONA ST(0.0L)																											
4153731			0.014		0.501	C	2009			0012	CRACKING	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.1	5.0*		
4153731							(2010)			FC125	RIDE	7.2	7														

```

**" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
**" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```

ALL SYSTEM PAVEMENT CONDITION FORECAST

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3 CONTRACTOR = PREFERRED MATERIALS, INC.

[illegible]

```

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = PREFERRED MATERIALS, INC.													
RDWYID	SR	US	BMP	G BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR												FUTURE
INTERSECT	AT	(MP SIDE)																					
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P																		
CONTRACTOR	(AGE ONE YEAR)				SURF TYPE					2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKMX-F																		
53050001	0.000	0.566	C	1	1	CRACKING	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0		
73			2	55	4900	RIDE	8.7	7.9	8.7	8.3	7.2	8.1	8.1	7.7	7.7	7.5	8.5	8.1	8.2	8.2	8.2		
MP 6.075 OF 53050000(0.0C)					16.1																		
4153831	0.000	0.548	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.5	7.5	8.5	6.5
PREFERRED MATERIALS, INC. (2010)					FC95M	RIDE	7.4	7.1	6.8	8.1	7.9			7.4	7.6	7.9	7.6	7.3	7.9	7.8	7.7	7.3	
54001000	9.993	19.487	R	4	1	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.5	8.5	
8 I10	225.8	235.3	2	70	34500	RIDE				9.1	8.8	8.3		8.2	8.2	8.2	8.2	7.6	7.9	8.1	7.7	8.0	
4325701	11.504	17.059	C	2016	0012	CRACKING	8.5	9.0	8.0	8.0					10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	6.0*
PREFERRED MATERIALS, INC. (2018)					FC5M	RIDE	7.8	7.9	7.6	7.9					8.7	8.6	8.6	8.7	8.6	8.6	8.6	8.5	8.4
54001000	9.993	19.487	L	4	1	CRACKING				10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	
8 I10	225.8	235.3	2	70	34500	RIDE				9.0	8.7	8.4		8.3	8.1	8.2	8.0	8.0	8.1	8.0	7.8		
4325701	11.504	17.059	C	2016	0012	CRACKING	7.0	6.5	6.5	6.5					10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.4	6.5
PREFERRED MATERIALS, INC. (2018)					FC5M	RIDE	7.7	7.8	7.4	7.9					8.8	8.7	8.7	8.7	8.7	8.7	8.7	8.6	8.5
54060000	3.877	8.927	C	1	1	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.5	6.5	6.5	
59			2	55	1463	RIDE	8.3	8.3	8.1	8.0	7.9	7.8	7.7	7.7	7.7	7.5	7.6	7.5	7.6	7.5	7.5	7.3	
BARRINGTON RD(5.7R)					16.4																		
4246081	3.899	8.710	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.0	6.5	4.5*
PREFERRED MATERIALS, INC. (2014)					FC95M	RIDE		8.3	7.7	7.8	7.7			7.9	7.9	7.9	7.8	7.6	7.8	7.7	7.6	7.2	
4546241	3.877	12.034	C	2028	0012																		
54060000	8.927	9.332	C	1	1	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5		
59			2	35	4100	RIDE	8.3	8.3	8.1	8.0	7.9	7.8	7.7	7.8	7.7	8.0	7.8	7.8	7.8	7.7	7.6		
BOND ST(9.0C)					13.4																		
4246081	8.750	9.325	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	8.0	8.0	6.8	5.0*	
PREFERRED MATERIALS, INC. (2014)					FC95M	RIDE		8.6	8.5	7.9	7.9	8.3	8.1	8.2	8.1	7.9	7.9	7.9	8.0	8.0	8.0	7.6	
4546241	3.877	12.034	C	2028	0012																		
54060000	9.332	9.964	R	1	1	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	6.5	6.5	
59			1	45	4100	RIDE	7.3	8.3	8.2	7.9	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.6	7.6	7.6	7.6	7.5	
4246081	9.325	9.964	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0	6.0*	6.0*	4.0*
PREFERRED MATERIALS, INC. (2014)					FC95M	RIDE		8.8	8.6	8.0	7.9	8.0	7.9	8.0	7.9	7.9	7.8	7.7	7.7	7.7	7.6	7.2	
4546241	3.877	12.034	C	2028	0012																		
54060000	9.332	9.964	L	1	6	CRACKING	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	6.5	6.5	
59			1	45	4100	RIDE	6.0*	6.8	8.4	8.3	7.4	6.8	6.9	7.1	7.3	7.2	7.5	7.5	7.6	7.4			
JEFFERSON RD(9.9L)					13.4																		
4246081	9.325	9.964	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	6.5	4.5*	
PREFERRED MATERIALS, INC. (2014)					FC95M	RIDE		8.9	8.7														
4546241	3.877	12.034	C	2028	0012																		
57010000	0.000	3.343	C	1	1	CRACKING	8.5	8.5	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	
10 90			2	60	4300	RIDE	9.0	9.0	8.9	8.7	8.3	8.1	8.0	8.0	8.0	7.9	9.0	9.0	9.0	8.9	8.9		
GARNER LANDING RD(0.0C)					11.3																		
4134451	0.000	3.361	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	8.5	7.5	7.0	6.0*	6.0*	6.0*	7.0	5.0*			
PREFERRED MATERIALS, INC. (2009)					FC95	RIDE	8.8	8.7	8.6	8.5	8.5	8.4	8.3	8.1	8.2	8.1	8.1	8.1	8.1	8.1	8.1	7.7	
4546391	0.000	3.343	C	2028	0012																		
57040000	12.250	13.338	R	1	1	CRACKING	9.0	6.5	6.5	3.5*	8.5	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0		
85			3	35	43500	RIDE	7.4	7.2	7.1	6.7	6.6	6.2	7.2	7.0		8.1	8.1	8.2	8.2	8.2	8.2		
JOHN SIMS PKWY(12.3R)					9.2																		
2201721	12.662	13.410	C	2005	0213	CRACKING	10.0	10.0	10.0	9.0	8.5	8.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.0*	
PREFERRED MATERIALS, INC. (2009)					FC125	RIDE	8.2	8.1	7.4	7.2	7.3	7.1	7.1	7.3	6.9	6.9	6.8	6.8	6.8	6.8	6.8	6.4	
4508191	11.600	13.338	C	2026	0012																		
57040000	12.250	13.338	L	1	1	CRACKING	6.5	6.5	6.5	6.5	8.5	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0		
85			3	35	43500	RIDE	7.2	7.2	7.2	6.6	7.2	7.2	7.0	6.8		8.0	7.9	7.9	7.9	7.7			
KELLEY RD(12.3L)					9.2																		
2201721	12.662	13.410	C	2005	0213	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.4	5.5*			
PREFERRED MATERIALS, INC. (2009)					FC125	RIDE	7.5	7.5	7.3	7.1	7.1	7.1	6.8	7.0	6.6	6.7	6.3	6.0	6.0	6.0	5.6		
4508191	11.600	13.338	C	2026	0012																		
58010000	18.736	27.923	C	1	1	CRACKING	8.5	8.5	7.5	7.5	7.0	6.0*	5.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0		
10 90			2	60	3106	RIDE	9.0	9.0	8.5	8.8	8.1	8.1	7.8	7.3	7.3	7.7	9.1	9.0	8.9	8.9	8.9		
LONGLEAF TRL(18.9L)					13.1																		
4134471	18.785	27.963	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	7.3	5.0*	
PREFERRED MATERIALS, INC. (2009)					FC95	RIDE	8.8	8.8	8.8	8.6	8.6	8.5	8.4	8.4	8.3	8.2	8.2	8.2	8.2	8.1	7.7		
4546411	11.681	27.923	C	2028	0012																		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3							CONTRACTOR = PREFERRED MATERIALS, INC.																
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR															FUTURE	
SR	US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012			
INTERSECT AT (MP SIDE)																							
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P	%T	=====																
CONTRACTOR	(AGE ONE YEAR)				SURF_TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030		
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																		(PMRS)
60070000	0.000	7.808	C	1		1	CRACKING	9.0	9.0	7.5	7.5	7.0	6.0*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0			
83			2	55		8400	RIDE	8.2	8.2	7.9	7.8	7.5	7.4	7.2	8.5	8.4	8.4	8.1	8.3	8.3			
DEFUNIAK	SPRINGS	CITY	LI	(	0.0C)	9.1																	
4114041	0.065	7.880	C	2006		0012	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.5	6.5	4.5*		
PREFERRED MATERIALS, INC. (2007)							FC95M	8.2	8.1	8.0	8.0	8.0	7.9	7.7	7.8	7.6	7.6	7.5	7.4	7.4	7.0		
4436612	0.000	7.890	C	2024		0012																	

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = PRINCE CONTRACTING, LLC																			
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE								
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012										
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKMX-P	%T																							
ITMSEG-P	(AGE ONE YEAR)			SURF	TYPE																								
CONTRACTOR	W BMP	W EMP	RW	FY-F	WKMX-F		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)									
ITMSEG-F																													
60020000	3.025	3.463	R	1	1	CRACKING	10.0	9.0	9.0	8.0	8.0	5.0*	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0										
30 98			3	45	55000	RIDE	8.4	8.4	8.2	8.2	7.3	7.7	7.3	7.8	6.9	6.9	6.2	8.5	8.5										
SANDTRAP RD(3.1R)					4.4																								
4141324	3.205	3.480	C	2017	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0					10.0	10.0	9.4	8.0									
PRINCE CONTRACTING, LLC				(2023)	FC95M	RIDE	8.4	8.4	8.4	8.2	8.1	8.2					7.8	7.7	7.7	7.3									
60020000	3.025	3.463	L	1	1	CRACKING	10.0	10.0	10.0	10.0	8.0	8.5	8.5	8.5	7.5	7.5	7.0	10.0	10.0										
30 98			3	45	55000	RIDE	8.6	8.3	8.3	8.0	8.0	8.2	7.8	8.0	8.1	8.1	8.0	8.4	8.3										
					4.4																								
4141324	3.205	3.480	C	2017	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0					10.0	10.0	9.6	8.5									
PRINCE CONTRACTING, LLC				(2023)	FC95M	RIDE	8.3	8.3	8.3	8.3	8.1	8.1					8.2	8.2	8.3	7.9									
60020001	0.000	3.145	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0		10.0	10.0	10.0	10.0										
30 98			2	55	53000	RIDE	8.5	8.4	7.9	7.8	7.5	7.3	7.1	7.2		8.3	8.2	8.2	8.3										
SANDY CAY DR(0.1R)					4.4																								
4141324	0.000	3.028	C	2017	0213	CRACKING	10.0	10.0	10.0	9.0	9.0						10.0	10.0	9.5	8.0									
PRINCE CONTRACTING, LLC				(2023)	FC95M	RIDE	8.3	8.3	8.3	8.5	8.3						7.4	7.4	7.4	7.0									
60020001	0.000	3.145	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0		10.0	10.0	10.0	10.0										
30 98			2	55	53000	RIDE	8.4	8.4	7.9	7.8	6.9	7.1	7.0	7.2		8.2	8.2	8.1	8.2										
GERONIMO ST N(1.0C)					4.4																								
4141324	0.000	3.028	C	2017	0213	CRACKING	10.0	10.0	10.0	9.0	9.0						10.0	10.0	9.5	8.0									
PRINCE CONTRACTING, LLC				(2023)	FC95M	RIDE	8.2	8.2	8.2	8.5	8.5						7.8	7.8	7.7	7.3									

"" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = ROADS, INC. OF NWF																
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR															FUTURE			
SR	US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012						
INTERSECT	AT	(MP SIDE)				%T	=====																			
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P																					
CONTRACTOR	(AGE	ONE YEAR)		SURF	TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F																(PMRS)					
58010000	15.903	16.532	R			1	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0					
10 90			1	45	8800	13.7	RIDE	8.8	8.7	8.5	8.6	8.3	8.2	8.0	7.6	8.0	8.1	8.0	8.0	8.0	8.0					
MILTON RD E(16.2R)																										
4246111	16.201	16.710	C	2012	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	7.0					
ROADS, INC. OF NWF				(2013)	FC95M	RIDE	8.8	8.6	8.5	8.1	7.9	7.6	7.9	7.8	8.0	7.9	7.9	7.9	7.9	7.7	7.3					
4546411	11.681	27.923	C	2028	0012																					
58010000	16.532	18.736	C	1		1	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	7.5	6.5	6.5	6.0*	5.5*						
10 90			2	60	8800	13.7	RIDE	8.8	8.7	8.5	8.6	8.3	8.2	8.0	7.6	8.1	8.0	7.9	7.8	7.5						
KIM DR(16.5R)																										
4246111	17.720	18.736	C	2012	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.0	7.0	6.8	5.0*					
ROADS, INC. OF NWF				(2013)	FC95M	RIDE	8.8	8.6	8.5	8.5	8.4	8.1	8.2	8.3	8.2	8.2	8.1	8.1	8.0	7.6						
4546411	11.681	27.923	C	2028	0012																					
58010000	15.903	16.532	L	1		1	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	8.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0					
10 90			1	45	8800	13.7	RIDE	8.8	8.7	8.5	8.6	8.3	8.2	8.0	7.6	7.9	8.1	8.0	8.0	8.0	8.1					
EAST MILTON RD(16.2L)																										
4246111	16.201	16.710	C	2012	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.0					
ROADS, INC. OF NWF				(2013)	FC95M	RIDE	8.8	8.6	8.6	8.5	8.4	8.5	8.2	8.3	8.2	8.0	8.3	8.3	8.3	8.1	7.7					
4546411	11.681	27.923	C	2028	0012																					

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = ROBERTS AND ROBERTS, INC.																					
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR										FUTURE														
SR	US	G	BMP	G	EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012									
INTERSECT AT (MP SIDE)										=====																					
ITMSEG-P										W	BMP	W	EMP	RW	FY-P	W	KMX-P														
CONTRACTOR (AGE ONE YEAR)										SURF		TYPE																			
ITMSEG-F										W	BMP	W	EMP	RW	FY-F	W	KMX-F	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
56040000										25.610	28.710	C	1	1	CRACKING	10.0	7.0	7.0	5.5*	5.5*	5.5*	3.0*	3.0*	3.0*	10.0	10.0	10.0	8.5			
65												2	55	3000	RIDE	8.6	8.4	8.6	8.8	8.2	7.9	8.1	7.9	7.9	8.7	8.6	8.4	8.4			
PARK AND RIDE(26.8R)																															
4415451										25.910	28.707	C	2021	0012	CRACKING	8.5	8.5	7.5	7.5	5.5*	5.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	8.5			
ROBERTS AND ROBERTS, INC.												(2023)	FC95M	RIDE	8.0	7.9	7.6	8.0	8.0	8.1	7.8	7.8	7.7	8.6	8.4	8.4	8.0				
56040000										28.710	30.151	C	1	1	CRACKING	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5				
65												2	35	3000	RIDE	7.2	7.2	8.9	8.9	8.2	8.5	8.3	8.3	8.4	8.3	8.3	8.1	8.1			
NE OLD MILL RD(29.1R)																															
4362601										28.707	29.916	C	2018	0012	CRACKING	7.5	7.0	7.0	7.0	5.5*	5.5*	4.0*	10.0	10.0	10.0	10.0	10.0	9.1	7.5		
ROBERTS AND ROBERTS, INC.												(2020)	FC95M	RIDE	7.9	7.9	7.7	7.8	7.7	7.3	7.4	8.4	8.3	8.3	8.2	8.2	8.0	7.6			
56040000										30.151	36.289	C	1	7	CRACKING	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*		10.0	10.0	10.0	10.0	10.0			
65												2	55	1450	RIDE	8.4	8.4	8.0	8.3	7.5	7.3	7.3		8.7	8.6	8.4	7.9	7.8			
KYLE LN NE(30.6L)																															
4457351										30.103	33.511	C	2024	0012	CRACKING	10.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	5.5*	5.5*	5.5*	5.5*	10.0	9.0		
ROBERTS AND ROBERTS, INC.												(2025)	FC125	RIDE	7.5	7.2	6.8	7.2	6.9	7.0	6.7	6.9	6.8	6.7	6.7	6.7	8.4	8.0			

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = ROBERTS C W CONTRACTING INC													
RDWYID	SR	US	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR													FUTURE
INTERSECT	AT	(MP	SIDE)				%T	=====	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012		
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	X-P																	
CONTRACTOR	(AGE	ONE	YEAR)						2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030	
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	X-F																(PMRS)	
47030000	3.572	5.502	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0		
69			2	55	2048	RIDE	8.8	8.8	8.6	8.5	8.2	8.1	8.0	8.0	8.0	8.0	8.0	8.0	7.9	8.0	8.0		
MIKE STEVENS RD NE(3.6R)																							
2180561	0.000	11.156	C	1996	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	7.5	7.5	7.5	7.0	4.5*	
ROBERTS C W CONTRACTING					IN(1998)	FC3	7.9	8.0	7.5	7.9	7.8	8.0	8.0	8.0	8.0	8.0	8.0	7.9	8.0	7.9	8.0	7.6	
4508161	3.216	11.157	C	2026	0012	RIDE																	
47030000	5.822	11.157	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0		
69			2	55	2048	RIDE	8.8	8.8	8.6	8.5	8.2	8.1	8.0	8.0	8.0	8.0	8.0	8.0	7.9	8.0	8.0		
CR 194(5.9L)																							
2180561	0.000	11.156	C	1996	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	7.1	4.5*	
ROBERTS C W CONTRACTING					IN(1998)	FC3	7.9	8.0	8.0	8.0	7.9	8.1	8.0	8.0	8.0	8.0	8.0	8.0	7.9	7.9	7.9	7.5	
4508161	3.216	11.157	C	2026	0012	RIDE																	
56010000	9.368	12.862	C	1	1	CRACKING	1.0*	0.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5		
20			2	60	4600	RIDE	5.6*	5.3*		9.2	9.0	8.9	8.8	8.8	8.8	8.8	8.7	8.7	8.7	8.6	8.5		
DIRT RD(9.9R)																							
2199511	9.368	12.835	C	2001	0012	CRACKING	7.5	7.0	7.0	6.0*	6.0*	6.0*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	3.0*	
ROBERTS C W CONTRACTING					IN(2003)	FC3	8.4	8.3	8.2	8.2	8.1	8.2	8.0	8.1	8.2	8.2	8.2	8.2	8.2	8.2	8.2	7.8	
2199512	9.368	12.843	C	2025	0012	RIDE																	

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

```

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

```

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = SUPERIOR CONSTRUCTION COMPAN										
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR													FUTURE
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	
INTERSECT AT (MP SIDE) %T =====																				
ITMSEG-P	W BMP	W EMP	RW	FY-P	WKM-X-P															
CONTRACTOR	(AGE ONE YEAR)				SURF TYPE		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030
ITMSEG-F	W BMP	W EMP	RW	FY-F	WKM-X-F															(PMRS)
46010100	1.849	1.953	R	1	6	CRACKING									10.0	10.0	10.0	10.0	10.0	
30 98			2	45	69718	RIDE											8.4	8.5	8.4	
BULLNOSE OF BRIDGE(2.0C) 5.6																				
2179763	1.856	1.953	C	2015	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5
SUPERIOR	CONSTRUCTION	COMP(2021)			FC95M	RIDE	8.2	8.4	8.2	8.1	8.1	7.9	7.8	7.7	8.4	8.5				

46010100	1.885	1.953	L	1	6	CRACKING									10.0	10.0	10.0	10.0	10.0	
30 98			3	45	69718	RIDE												8.5		
BULLNOSE OF BRIDGE(2.0C) 5.6																				
2179763	1.856	1.953	C	2015	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.5
SUPERIOR	CONSTRUCTION	COMP(2021)			FC95M	RIDE														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = WESTFIELD INSURANCE COMPANY															
RDWYID	SR	US	BMP	G_BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR														FUTURE
INTERSECT	AT	(MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	P																	
ITMSEG-P	CONTRACTOR	(AGE ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F																		
ITMSEG-F										2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)		
55010000			2.047	6.340	R	1	1	CRACKING	7.0	7.5	5.5*	5.5*	4.5*	1.0*			10.0	10.0	10.0	10.0	10.0	10.0			
63 27					2	45	19500	RIDE	8.5	8.4	8.1	7.8	6.6	6.6			8.9	8.8	8.8	8.8	8.7	8.4			
TOWER RD(2.2R)							5.4																		
4063261			0.159	7.048	C	2005	0012	CRACKING	10.0	10.0	9.5	9.5	9.5	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	5.8*	3.5*		
WESTFIELD INSURANCE COMPAN(2007)							FC95M	RIDE	8.6	8.5	8.5	8.2	8.2	8.3	8.2	8.1	8.1	8.1	8.1	8.1	8.0	8.1	7.7		
4529391			2.058	8.108	C	2027	0012																		
55010000			2.132	6.340	L	1	1	CRACKING	6.0*	5.5*	3.5*	3.5*	3.5*	1.0*			10.0	10.0	10.0	10.0	10.0	10.0			
63 27					2	45	19500	RIDE	8.7	8.5	8.2	8.0	6.5	6.4*			8.9	8.8	8.7	8.6	8.5	8.4			
RED AND SAMS LN(2.2L)							5.4																		
4063261			0.159	7.048	C	2005	0012	CRACKING	10.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	5.5*	3.5*		
WESTFIELD INSURANCE COMPAN(2007)							FC95M	RIDE	8.4	8.4	8.3	8.2	8.2	8.1	8.1	8.0	8.0	8.0	7.8	7.9	7.7	7.8	7.4		
4529391			2.058	8.108	C	2027	0012																		
55020000			0.000	1.126	R	1	1	CRACKING	9.0	7.5	7.5	7.5	7.5	6.5			10.0	10.0	10.0	10.0	10.0	9.5			
10 90					2	35	27000	RIDE	6.5	6.8	6.7	6.0	5.5	5.1*			7.1	6.6	6.3	6.2	6.4	6.6			
US-27/SR-20/SR-61(0.0R)							3.2																		
4039421			0.000	1.132	C	2005	0012	CRACKING	9.5	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	5.5*	3.5*		
WESTFIELD INSURANCE COMPAN(2007)							FC125	RIDE	6.6	6.5	6.3	6.2	6.0	6.0	5.8	6.0	6.1	6.1	6.1	5.6	5.5	5.3*	4.9*		
4039423			0.000	1.126	C	2025	0012																		
55020000			0.000	1.126	L	1	1	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0			10.0	10.0	10.0	10.0	10.0	9.5			
10 90					2	35	27000	RIDE	7.5	7.5	6.9	7.0	6.5	5.8			7.5	7.4	7.3	7.2	7.1	7.1			
MONROE(0.0C)							3.2																		
4039421			0.000	1.132	C	2005	0012	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	6.0*	6.0*	6.0*	6.0*	4.0*		
WESTFIELD INSURANCE COMPAN(2007)							FC125	RIDE	7.2	6.7	6.9	6.5	6.3	6.2	6.1	6.4	6.5	6.4	6.4	6.0	5.7	6.1	5.7		
4039423			0.000	1.126	C	2025	0012																		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = WHITE CONSTRUCTION CO																			
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED YEAR										FUTURE												
SR US	G_BMP	G_EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012										
INTERSECT AT (MP SIDE)						%T																							
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKMX-P																								
CONTRACTOR (AGE ONE YEAR)				SURF_TYPE			2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030									
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKMX-F															(PMRS)									
59040000	0.000	2.580	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5										
363			2	45	1750	RIDE	8.9	8.8	8.7	8.9	8.2	8.3	8.3	8.1	8.4	8.0	8.5	8.5	8.5										
RIVERSIDE DR(0.0C)						12.9																							
2205191	0.010	2.582	C	1997	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.5	8.0	8.7	6.0*									
WHITE CONSTRUCTION CO				(1998)	FC3	RIDE	8.5	8.3	8.2	8.4	8.4	8.2	8.3	8.2	8.3	8.1	8.2	8.1	8.1	7.7									

"" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 "" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2025 - 2030, EXTRACTED ON 02/27/2025**

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 3										CONTRACTOR = WHITE CONSTRUCTION CO INC																			
RDWYID	BMP	EMP	RW	SYSTEM	TYPE	DISTRESS	SURVEYED	YEAR										FUTURE											
SR US	G BMP	G EMP	LN	SPEED	AADT	RATINGS	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012										
INTERSECT AT (MP SIDE)	W BMP	W EMP	RW	FY-P	WKMX-P	%T																							
ITMSEG-P	(AGE ONE YEAR)																												
CONTRACTOR	W BMP	W EMP	RW	FY-F	WKMX-F		2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)									
ITMSEG-F																													
54090000	0.000	13.050	C	1	1	CRACKING	2.0*		10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0									
59			2	55	1050	RIDE	6.1*		8.6	8.3	8.3	8.3	8.3	8.2	7.5	7.3	8.4	8.3	8.3										
SR 30(0.0C)					30.0																								
2194431	0.000	13.769	C	2000	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0									
WHITE CONSTRUCTION CO INC (2002)					FC125	RIDE	8.2	8.3	8.0	7.9	7.9	8.0	8.0	7.9	7.9	7.8	7.9	7.9	7.9	7.9									
4531521	0.000	13.774	C	2027	0012																								
54090000	13.050	13.774	C	1	1	CRACKING	4.5*		10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.0									
59			2	45	1050	RIDE	6.2*		8.3	7.8	7.8	8.0	7.8	8.0	7.8	7.7	7.9	7.9	7.9	7.8									
CR 59(13.1R)					30.0																								
2194431	0.000	13.769	C	2000	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	4.5*									
WHITE CONSTRUCTION CO INC (2002)					FC125	RIDE	7.9	8.0	7.9	7.1	7.4	7.4	7.4	7.5	7.5	7.4	7.5	7.6	7.6	7.2									
4531521	0.000	13.774	C	2027	0012																								
55002000	3.250	4.748	R	1	8	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5										
263			1	45	17200	RIDE		8.4	8.7	8.8	8.4	8.4	8.3	8.5	8.3	8.3	8.2	8.1	8.0	8.0									
CR 2203(3.5C)					8.3																								
2198231	0.011	8.019	C	1999	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	8.0	7.0	7.0	7.0	7.0	7.0	7.0										
WHITE CONSTRUCTION CO INC (2001)					FC95M	RIDE	8.0	7.9	7.9	7.8	7.9	7.8	7.6	7.6	7.6	7.6	7.5	7.5	7.5										
4157829	3.430	6.670	C	2022	0213																								
55002000	3.250	4.748	L	1	8	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5										
263			1	45	17200	RIDE		8.4	8.7	8.8	8.4	8.4	8.3	8.5	8.3	8.3	8.2	8.1	8.0	8.0									
CR 2203(3.5C)					8.3																								
2198231	0.011	8.019	C	1999	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	8.0	7.0	5.5*	5.5*	5.0*	5.0*	5.0*										
WHITE CONSTRUCTION CO INC (2001)					FC3	RIDE	8.0	7.9	7.9	7.8	7.9	7.8	7.6	7.6	7.3	7.2	7.1	7.0	7.0										
4157829	3.430	6.670	C	2022	0213																								

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2030 FORECASTED BY PAVEMARS (PMRS).