FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = AGI DE MOYA JOINT VENTURE ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ======== 2013	SURVEYED YEAR 2000 2014	2001 2015	2002 2016	2003 2017	2004 2018	2005 2019	2006 2020	2007 2021	2008 2022	2009 2023	2010 2024	2011 2025	2012 2030 (PMRS)	FUTURE
87471000	38.580	39.500	R	5	1	CRACKING	8.0	8.0			10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	
821	38.6	39.5	3	60	101500 5.7	RIDE	8.7	8.8			7.7	7.7	7.8	7.8	7.9	7.9	7.4	7.6	7.6	
4355421	38.764	39.438	R	2020	0213	CRACKING	9.0	9.0	9.0	9.0				10.0	10.0	10.0	10.0	10.0	10.0	8.5
AGI DE MOYA JOINT VENTURE (2020)					FC5M	RIDE	7.4	7.4	7.3	7.7				8.2	7.9	8.1	8.1	8.1	8.1	8.0
87471000	38.524	39.326	L	5	1	CRACKING	9.5	9.5			10.0	10.0	10.0	10.0	10.0	9.5	8.0	6.5	10.0	
821	38.5	39.3	3	60	101500 5.7	RIDE	8.8	8.9			7.6	7.6	7.6	7.7	7.8	7.8	7.6	8.0	8.3	
4355421	33.273	39.095	L	2020	0213	CRACKING	10.0	10.0	10.0	10.0				10.0	10.0	10.0	10.0	10.0	9.4	8.0
AGI DE MOYA JOINT VENTURE (2020)					OGFC	RIDE	8.3	8.3	8.3	8.5				8.2	8.1	8.0	8.1	7.7	7.6	7.5

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = AMERICAN ENGINEERING & DEVEL ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP / W_BMP	EMP / G_EMP / W_EMP / W_EMP	RW / LN / RW / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / WKMX-P / WKMX-F / %T / SURF_TYPE	DISTRESS RATINGS / =========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87030000	12.067	13.605	R	1	1	CRACKING	10.0	9.5	9.5	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5																
5 1			2	30	48000	RIDE	6.3*	6.4*	6.0	6.2	5.3*	5.2*	5.2*	4.2*	5.4*	5.2*	5.0*															
HILTON MIAMI DOWNTOW(12.1R)					5.7																												
4146241	12.067	13.482	C	2009	0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.7	7.0													
AMERICAN ENGINEERING & DEV(2013)				FC95		RIDE	7.8	7.4	7.3	6.1	6.2	6.0	6.1	5.9	6.1	5.7	5.8	5.3*	5.0*	4.5*													
87030000	12.067	13.605	L	1	1	CRACKING	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.5	6.5	6.5	6.5																
5 1			2	30	48000	RIDE	6.5	6.4*	6.2	6.0	5.2*	5.0*	4.6*	4.3*	4.7*	4.8*	4.3*															
NE 16 ST(12.1L)					5.7																												
4146241	12.067	13.482	C	2009	0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.7	7.0													
AMERICAN ENGINEERING & DEV(2013)				FC95		RIDE	7.2	6.7	6.3	6.3	5.9	5.6	5.8	5.9	5.5	5.4*	5.2*	5.4*	5.2*	4.7*													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = APAC-FLORIDA INC ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ======== 	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87160000	8.041	8.745	R	1	1	CRACKING	7.5	7.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	
9336			2	30	27500	RIDE	7.7	7.7	7.2	6.7	6.3	7.2	7.5	7.0	6.8	6.8	7.2	7.1	6.9	
CAVES AVE(8.1C)					7.6															
4056591	8.041	8.735	R	2003	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.4	6.5
APAC-FLORIDA INC				(2005)	FC125	RIDE	7.1	7.0	6.6	6.7	6.6	7.0	6.7	6.4	6.8	6.3	6.8	6.3	6.2	5.7
4459921	7.057	8.705	C	2023	0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = ASPHALT GROUP, INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / RW FY-F	SYSTEM SPEED / WKMX-P / WKMX-F	TYPE AADT / %T / SURF_TYPE	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87004000	2.545	4.921	R	4	7	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	10.0	10.0	
112 I195	2.5	4.9	3	55	119000	RIDE	8.5	8.5	8.3	8.3	7.7	7.8	7.6	7.8	8.1	7.7	7.7	7.9	7.9	
SIDE ROAD(4.6C)					4.2															
4446221	1.898	4.350	R	2022	9924	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	10.0	9.0
ASPHALT GROUP, INC.				(2025)	FC5	RIDE	7.9	7.9	7.9	8.1	8.1	8.2	8.2	8.3	8.3	8.2	8.2	8.3	8.5	8.4
87004000	2.545	4.921	L	4	7	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	10.0	10.0	
112 I195	2.5	4.9	3	55	119000	RIDE	8.5	8.4	8.4	8.3	7.9	7.8	7.7	7.8	7.9	7.8	7.8	7.9	8.1	
SIDE ROAD(4.6C)					4.2															
4446221	1.898	4.796	L	2022	9924	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	9.0	10.0	9.0
ASPHALT GROUP, INC.				(2025)	FC5	RIDE	8.2	8.1	8.1	8.3	8.3	8.0	8.3	8.3	8.4	8.4	8.3	8.1	8.4	8.3
87004000	1.805	2.137	L	4	7	CRACKING	10.0	10.0	9.5	9.5	9.5	7.5	7.5	6.5	6.5	4.5*	4.5*	10.0	10.0	
112 I195	1.8	2.1	3	55	119000	RIDE	8.6	8.6	8.5	8.4	7.9	7.8	7.6	7.4	7.7	7.6	7.6	7.9	8.1	
					4.2															
4446221	1.898	4.796	L	2022	9924	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	10.0	9.0
ASPHALT GROUP, INC.				(2025)	FC5	RIDE	8.2	8.1	8.1	8.3	8.3	8.3	8.3	8.3	8.5	8.4	8.3	8.3	8.4	8.3
87140000	12.147	14.453	R	1	1	CRACKING	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.5	7.5	7.5		
7 441			3	45	58500	RIDE	8.0	8.1	8.1	7.9	7.2	7.3	7.2	7.1	7.0	6.4	6.7	6.5		
FRONTAGE DR(12.2R)					5.2															
4180941	12.147	14.453	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.5	8.0
ASPHALT GROUP, INC.				(2013)	FC95	RIDE	8.3	8.3	7.7	7.7	7.7	8.0	7.8	7.9	7.7	7.6	7.7	7.7	7.6	7.1
87140000	12.147	14.453	L	1	1	CRACKING	9.0	9.0	8.0	7.0	6.0*	6.0*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*		
7 441			3	45	58500	RIDE	7.8	7.5	7.8	7.6	6.8	6.8	6.8	6.7	6.8	6.6	6.7	6.6		
NW 181 ST(12.5L)					5.2															
4180941	12.147	14.453	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	7.5	7.5	8.7	7.0
ASPHALT GROUP, INC.				(2013)	FC95	RIDE	8.3	8.2	7.3	7.7	6.9	7.6	7.6	7.5	7.4	7.4	7.4	7.3	7.2	6.7
87240000	2.985	4.894	R	1	1	CRACKING	10.0	9.0	9.0	8.0	8.0	6.5	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	
9			3	35	36000	RIDE	8.3	8.1	8.0	7.7	7.2	7.2	6.7	6.5	6.5	6.4	6.3	6.3	6.2	
NW 14 ST(3.2C)					7.3															
4226121	2.985	4.894	C	2011	0012	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.8	7.5
ASPHALT GROUP, INC.				(2014)	FC125	RIDE	6.0	8.0	7.9	7.8	7.6	7.5	7.4	7.1	7.2	7.1	6.9	6.9	7.0	6.5
87240000	2.985	4.894	L	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	6.5	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	
9			3	35	36000	RIDE	8.2	7.7	7.7	7.9	6.8	6.6	6.6	6.4	6.0	5.5	5.2*	6.0	6.1	
NW 14 ST(3.2C)					7.3															
4226121	2.985	4.894	C	2011	0012	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.0	5.5*
ASPHALT GROUP, INC.				(2014)	FC125	RIDE	6.0	7.9	7.7	7.7	7.6	7.6	7.5	7.1	7.0	7.1	6.9	6.4	4.6*	4.1*
90030000	0.000	0.415	C	1	6	CRACKING	7.5	7.0	4.5*	4.5*	4.5*	2.0*	2.0*	2.0*	2.0*	2.0*	2.0*	2.0*	10.0	
5 1			2	45	14300	RIDE	8.0	8.4	8.5	7.5	6.5	6.9	7.0	6.6	6.2	6.1	5.7	5.9	7.4	
INDUSTRIAL RD(0.0R)					9.9															
4056122	0.000	0.440	C	2010	0221	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.5	6.5	6.5	5.8*	4.0*
ASPHALT GROUP, INC.				(2012)	OGFC	RIDE	7.3	7.3	7.3	7.0	7.0	6.8								

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = ASTALDI CONSTRUCTION CORP. ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87002000	0.000	0.889	R	1	1	CRACKING	6.5	6.5	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*			
823			2	45	34500	RIDE	7.1	7.2	7.1	7.2	6.4*	6.5	6.3	6.0	6.2	6.0	5.9			
OKEECHOBEE RD(0.0C)					5.8															
2499413	0.000	0.628	C	2009	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.1	7.5
ASTALDI CONSTRUCTION CORP.(2013)					FC125	RIDE	6.7	7.0	6.5	5.9	5.9	5.7	5.4*	5.6	5.6	5.5	5.3*	5.4*	5.6	5.1*
87002000	0.000	0.889	L	1	1	CRACKING	4.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*	3.5*			
823			3	45	34500	RIDE	7.3	7.2	7.2	7.2	6.4*	6.3*	6.1	5.9	6.0	6.0	6.1			
OKEECHOBEE RD(0.0C)					5.8															
2499413	0.000	0.628	C	2009	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5
ASTALDI CONSTRUCTION CORP.(2013)					FC125	RIDE	7.3	7.2	6.8	6.3	6.4	6.4	6.3	6.1	5.9	5.9	5.9	5.8	5.9	5.4*

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = ATLANTIC CIVIL INC ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87020000   3.277  5.278  R    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   6.5   6.5   6.5   6.5   6.5   7.0
5    1                  2   45  29000 RIDE      8.1   8.1   8.1   5.8*  7.4   7.2   7.2   7.3   7.3   7.1   7.0   7.2
SW 308 ST/NE 11 ST( 3.4C)          7.2
4106251    3.620  5.278  C 2011   0005 CRACKING       10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   8.9   7.0
ATLANTIC CIVIL INC        (2014) FC5   RIDE            8.0   7.9   8.0   8.0   8.0   7.8   7.9   7.9   7.8   7.7   7.5   7.6   7.4
-----------------------------------------------------------------------------------------------------------------------------------
87020000   3.277  5.278  L    1      1 CRACKING  6.5   6.0*  6.0*  5.5*  5.5*  4.0*  4.0*  4.0*  4.0*  3.5*  3.5*  3.5*
5    1                  2   45  29000 RIDE      8.5   8.5   8.3   8.1   7.4   7.2   7.2   7.0   7.0   6.9   6.8   6.6
SW 308 ST/NE 11 ST( 3.4C)          7.2
4106251    3.620  5.278  C 2011   0005 CRACKING       10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   7.5   7.5   8.7   7.0
ATLANTIC CIVIL INC        (2014) FC5   RIDE            8.0   7.9   8.0   7.9   7.8   7.5   7.8   7.7   7.6   7.6   7.3   7.4   7.2
-----------------------------------------------------------------------------------------------------------------------------------
87026005   0.312  0.767  R    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
860                     2   35  48500 RIDE      6.7   6.9   6.7   6.4   6.3   6.0   7.8   7.4   7.4   7.5   7.4   7.5   7.5
NW 87 AVE( 0.6C)                   3.4
4165901    0.307  0.799  C 2005   0221 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.0   8.0   8.7   6.5
ATLANTIC CIVIL INC        (2006) DGFC  RIDE      7.4   7.4   7.2   7.3   7.0   7.1   7.1   7.2   6.8   6.8   7.1   6.9   7.0   6.5
4388642    0.439  1.316  C 2029   0218
-----------------------------------------------------------------------------------------------------------------------------------
87026005   0.312  0.767  L    1      1 CRACKING  6.5   6.5   6.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0
860                     3   40  48500 RIDE      6.8   6.6   6.5   6.4   6.0   6.1   8.3   7.9   7.0   8.1   8.2   8.1   7.9
NW 87 AVE( 0.6C)                   3.4
4165901    0.307  0.799  C 2005   0221 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.5   6.5
ATLANTIC CIVIL INC        (2006) DGFC  RIDE      7.8   7.9   7.7   7.9   7.8   7.7   7.8   7.7   7.6   7.7   7.8   7.4   7.7   7.2
4388642    0.439  1.316  C 2029   0218
-----------------------------------------------------------------------------------------------------------------------------------
87240000  10.823 11.113  R    1      6 CRACKING 10.0  10.0  10.0   9.0   7.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0
9                       3   45  45500 RIDE      8.0   7.5   7.7   7.5   7.3         7.3   6.9   7.4   7.5   7.6   7.0   6.5
OPA LOCKA CITY LIMITS(10.9C)       7.7
4068041   10.859 13.690  C 2003   0005 CRACKING 10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.0   9.0   9.0   9.0   9.0   7.5   5.5*
ATLANTIC CIVIL INC        (2006) FC95  RIDE      6.6   5.7   6.1                           6.3   6.3
4439141   10.941 11.239  C 2023   0012
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = BACALLAO CONSTRUCTION & ENGI ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                                                              (PMRS)

87020000  10.400 11.380  R    1      7 CRACKING  8.0   8.0   7.5                    10.0  10.0  10.0  10.0  10.0  10.0  10.0
5    1                   2   45  37000 RIDE      8.2   8.1   8.1                     7.7   7.8   8.0   7.9   7.9   7.9   7.8
SW 224 ST(10.5R)                   7.2
4478021    9.730 11.911  C 2024   0012 CRACKING 10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   7.5   7.5   6.5  10.0   9.0
BACALLAO CONSTRUCTION & EN(2025) OGFC  RIDE      7.8   7.8   7.6   7.6   7.3   7.5   7.2   7.4   7.4   7.4   7.3   7.0   7.7   7.5
-----------------------------------------------------------------------------------------------------------------------------------
87020000  10.400 11.380  L    1      7 CRACKING  3.5*  4.0*  4.5*                   10.0  10.0  10.0  10.0  10.0  10.0  10.0
5    1                   3   45  37000 RIDE      7.1   7.0   6.7                     7.5   7.6   7.7   7.8   7.6   7.7   7.6
MIAMI AVE(10.5L)                   7.2
4478021    9.730 11.911  C 2024   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   7.5   7.5   6.5  10.0   9.0
BACALLAO CONSTRUCTION & EN(2025) OGFC  RIDE      7.5   7.6   7.3   7.2   7.2   7.2   7.1   7.1   7.1   7.0   7.0   6.9   7.3   7.1
-----------------------------------------------------------------------------------------------------------------------------------
87038000   3.278  4.911  R    1      7 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0
932                     2   40  38000 RIDE      8.3   7.4   7.6   6.9   6.9   6.6   6.4   6.3   6.2   7.5   7.3   7.4   7.3
5TH AVE W( 3.3C)                   8.1
4347683    3.392  4.907  C 2022   0012 CRACKING  9.0   9.0   9.0   8.5   7.0   7.0   7.0   7.0   6.5   6.5   6.5   6.5  10.0   9.5
BACALLAO CONSTRUCTION & EN(2025) FC125 RIDE      6.9   7.0   7.0   6.5   6.6   6.5   6.6   6.4   6.4   6.5   6.3   6.3   6.8   6.3
-----------------------------------------------------------------------------------------------------------------------------------
87038000   3.278  4.911  L    1      7 CRACKING 10.0  10.0  10.0  10.0  10.0   8.5   8.5   8.5   8.5  10.0  10.0  10.0  10.0
932                     2   40  38000 RIDE      7.7   7.6   7.2   7.2   6.7   5.9   6.2   5.8   6.3   7.0   6.3   6.5   6.5
W 3 AVE( 3.3L)                     8.1
4347683    3.392  4.907  C 2022   0012 CRACKING  9.0   9.0   8.5   8.5   7.0   6.5   6.5   6.5   6.5   6.5   6.5   6.5  10.0   9.5
BACALLAO CONSTRUCTION & EN(2025) FC125 RIDE      6.4   6.3   6.3   6.5   6.4   6.5   6.3   6.2   6.2   6.2   6.2   5.9   6.5   6.0
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = BERGERON LAND DEVELOPMENT, I ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87037000   0.000  0.183  R    1      6 CRACKING  6.5   7.0   7.0   6.0*  6.0*  6.0*  6.0*  6.0*  6.0*  4.5*  4.5*  4.5*  9.5
907                     2   30  31500 RIDE      5.3*  5.2*  4.5*  5.2*  4.4*  4.2*  4.2*  4.2*  4.2*  3.9*  4.4*  3.9*
SR A1A( 0.0C)                    3.8
2499111    0.028  0.183  R 2013   0005 CRACKING  9.5   9.5   8.5        10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.7   7.5
BERGERON LAND DEVELOPMENT,(2017) FC95M RIDE
-------------------------------------------------------------------------------------------------------------------------------------
87037000   0.000  0.183  L    1      6 CRACKING  9.0   7.0   6.0*  6.0*  6.0*  6.0*  6.0*  6.0*  6.0*  4.5*  4.5*  4.5*  9.5
907                     2   30  31500 RIDE      5.8*  5.6*  5.0*  4.4*  4.2*  3.6*  3.6*  4.0*  3.9*  4.2*  4.4*  3.8*
SR A1A( 0.0C)                    3.8
2499111    0.028  0.402  L 2013   0005 CRACKING  9.5   9.5   8.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.2   8.0
BERGERON LAND DEVELOPMENT,(2017) FC95M RIDE
-------------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = BREWER CO OF FLORIDA INC ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / %T / WKMX-P / SURF_TYPE / WKMX-F	DISTRESS RATINGS / =========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87060000	12.627	14.047	R	1	8	CRACKING	3.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	8.5														
A1A			2	40	44000	RIDE	6.1*		8.2	7.8	7.2	7.3	7.3	7.3	7.6	7.5	7.5	7.4	7.3													
					3.4																												
2501851	12.659	14.073	C	2000	0012	CRACKING	8.5	8.5	8.5	7.5	6.0*	6.0*	6.0*	6.0*	5.5*	5.5*	3.0*	3.0*															
BREWER CO OF FLORIDA INC				(2002)	FC95M	RIDE	7.2	7.2	7.3	7.1	6.9	6.8	6.8	6.6	6.4	6.3	6.2	6.1															
4309492	12.631	14.024	C	2022	0012																												
87060000	12.627	14.047	L	1	8	CRACKING	3.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5														
A1A			2	40	44000	RIDE	6.4*		8.1	7.6	7.0	7.2	6.8	7.0	7.1	7.4	7.5	7.4	7.3													
					3.4																												
2501851	12.659	14.073	C	2000	0012	CRACKING	8.5	8.5	8.5	7.5	6.0*	6.0*	6.0*	5.5*	3.5*	1.0*	0.0*	0.0*															
BREWER CO OF FLORIDA INC				(2002)	FC95M	RIDE	7.1	7.0	6.8	6.7	6.4	6.6	6.2	6.3	6.1	6.3	6.2	5.9															
4309492	12.631	14.024	C	2022	0012																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = BUDGET CONSTRUCTION CO., INC ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87066000   2.926  3.741  R    1      1 CRACKING  9.0   9.0   9.0   7.5   7.5   7.5   7.5   7.5   6.5   6.5        10.0  10.0
922                      2   30  23000 RIDE      4.4*  5.1*  5.3*  4.8*  4.2*  4.1*  4.3*  5.5   4.7*  4.8*        6.3   6.3
BISCAYNE BLVD( 3.0C)                 5.8
4180711    2.920  3.684  C 2008   0012 CRACKING 10.0  10.0  10.0   8.5   8.5   8.5   8.5   8.5   8.5   8.5   7.5   7.5   8.3   6.5
BUDGET CONSTRUCTION CO., I(2011) FC95  RIDE      6.0   6.4   5.7   4.7*  4.5*  4.4*  4.2*  4.0*  4.0*  4.0*  3.9*  3.9*  3.7*  3.2*
4439351    3.201  3.741  C 2024   0015
-------------------------------------------------------------------------------------------------------------------------------------
87066000   2.926  3.741  L    1      1 CRACKING 10.0   9.5   8.0   8.0   8.0   7.5   6.5   6.5   6.5   6.5        10.0  10.0
922                      2   30  23000 RIDE      7.3   6.7   7.1   7.0   6.2   5.9   5.9   5.5   5.4*  5.2*        6.3   6.3
BISCAYNE BLVD( 3.0C)                 5.8
4180711    2.920  3.684  C 2008   0012 CRACKING 10.0  10.0  10.0   8.5   8.5   8.5   8.5   8.5   8.5   8.5   7.5   7.5   8.8   7.0
BUDGET CONSTRUCTION CO., I(2011) FC95  RIDE      6.0   6.4   5.7   4.7*  4.5*  4.4*  4.2*  4.0*  5.2*  5.1*  5.0*  4.8*  4.7*  4.2*
4439351    3.201  3.741  C 2024   0015
-------------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = CENTRAL FLORIDA EQUIPMENT ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87010000   9.356 13.679  C    1      1 CRACKING       10.0  10.0  10.0   9.0   9.0   9.0   9.0   7.5   7.0
5    1                  2   55  25000 RIDE            8.4   8.5   8.3   7.9   7.7   7.8   7.9   7.8   7.6
FRONTAGE RD( 9.5L)                 7.2
2498562    8.750 11.610  C 2010   0005 CRACKING 10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   8.0   8.0   8.0   7.5   6.9   5.0*
CENTRAL FLORIDA EQUIPMENT (2013) FC5   RIDE      8.0   8.0   7.9   7.9   7.9   7.9   7.8   7.9   7.9   7.9   7.9   7.9   7.8   7.6
-----------------------------------------------------------------------------------------------------------------------------------
87030000  13.605 15.048  R    1      1 CRACKING  3.5*  1.0*  1.0*  1.0*  1.0*  1.0*  1.0*             10.0  10.0  10.0  10.0
5    1                  2   35  36500 RIDE      5.7*  5.5*  5.6   4.9*  4.4*  4.2*  4.3*              7.2   6.9   7.0   6.8
BAY POINT ENT(14.0R)               5.7
2502241   13.635 15.405  C 2005   0005 CRACKING 10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.3   6.5
CENTRAL FLORIDA EQUIPMENT (2009) DGFC  RIDE      6.6   6.7   6.7   6.9   6.9   6.7   6.6   6.6   6.5   6.3   6.3   6.0   6.3   5.8
4478301   13.568 15.025  C 2026   0012
-----------------------------------------------------------------------------------------------------------------------------------
87030000  13.605 15.048  L    1      1 CRACKING  3.5*  3.5*  3.5*  7.0   1.0*  1.0*  1.0*             10.0  10.0  10.0  10.0
5    1                  2   35  36500 RIDE      8.2   8.3   7.9   5.6   6.8   6.5   6.3               7.2   7.1   7.0   7.0
NE 39 ST(13.7L)                    5.7
2502241   13.635 15.405  C 2005   0005 CRACKING 10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.5   8.5   8.5   8.5   8.5   8.0   6.5
CENTRAL FLORIDA EQUIPMENT (2009) DGFC  RIDE      6.7   6.8   6.6   7.0   6.8   6.6   6.4   6.5   6.2   6.5   6.4   6.2   6.3   5.8
4478301   13.568 15.025  C 2026   0012
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

```
---------------------------------   DISTRICT = 6      CONTRACTOR = CENTRAL FLORIDA EQUIPMENT RE ---------------------------------

RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                  FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                          (PMRS)


87060002   0.000  0.198  R    1      6 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   7.5
A1A                     2   35  38000 RIDE      7.1   7.5   7.0   7.6   5.4*  5.4*  5.2*  4.9*  5.4*  5.8   5.7
COLLINS AV AT 44 ST( 0.0C)          4.2
4275051    0.007  0.154  C 2014   0012 CRACKING  7.5   7.5   7.5        10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   7.9   6.5
CENTRAL FLORIDA EQUIPMENT (2017) DGFC  RIDE      5.5   5.6   5.1*        5.6   5.1*  5.0*
4439311    0.000  0.215  C 2025   0012
-------------------------------------------------------------------------------------------------------------------------------------
87060002   0.000  0.198  L    1      6 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   7.5
A1A                     2   35  38000 RIDE      7.8   7.5   6.3   6.3   7.2   6.4   5.9   6.5   5.9   5.7   5.5
SR A1A( 0.0L)                       4.2
4275051    0.007  0.154  C 2014   0012 CRACKING  7.5   7.5   7.5        10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   8.4   7.0
CENTRAL FLORIDA EQUIPMENT (2017) DGFC  RIDE      5.5   5.1*  5.1*        5.6   5.1*  5.0*
4439311    0.000  0.215  C 2025   0012
-------------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = COMMUNITY ASPHALT CORP. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / RW FY-F	SYSTEM SPEED / WKMX-P / SURF_TYPE / WKMX-F	TYPE AADT / %T	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
87001000	0.000	1.125	R	1	1	CRACKING	9.0	7.5	4.5*	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0														
94			2	50	22500	RIDE	7.9	8.0	7.9	7.7	6.6	6.6	6.5	7.9	7.9	7.9	7.5	7.6	7.7														
KROME AVE/SW 177 AVE(0.0C)					7.7																												
4124681	0.010	1.397	C	2006	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.8	5.5*													
COMMUNITY ASPHALT CORP.			(2007)	FC5		RIDE	7.5	7.6	7.6	7.9	7.7	7.5	7.8	7.9	7.8	7.8	7.7	7.7	7.6	7.4													
87001000	0.000	1.125	L	1	1	CRACKING	9.0	7.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0														
94			2	50	22500	RIDE	8.1	8.1	8.1	7.7	6.9	6.9	6.8	8.0	7.9	7.8	7.7	7.7	7.6														
KROME AVE/SW 177 AVE(0.0C)					7.7																												
4124681	0.010	1.397	C	2006	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	8.3	6.0*													
COMMUNITY ASPHALT CORP.			(2007)	FC5		RIDE	7.6	7.6	7.6	7.8	7.8	7.3	7.6	7.7	7.8	7.9	7.7	7.7	7.5	7.3													
87008000	3.114	4.888	R	1	1	CRACKING	9.0	9.0	9.0	9.5	9.5	9.5	9.5	8.0	7.0	6.5	6.5	10.0	10.0														
916			2	40	22500	RIDE	7.1	7.0	6.5	6.2	5.6	5.7	5.6	5.9	5.7	5.7	5.5	7.2	6.8														
NW 47 AVE(3.1R)					5.9																												
4198561	3.288	4.979	C	2009	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.3	6.5													
COMMUNITY ASPHALT CORP.			(2011)	FC125		RIDE	6.0	6.6	6.6	6.4	6.1	6.1	6.2	5.8	6.0	5.9	5.6	5.7	5.6	5.1*													
4499471	3.099	4.812	C	2026	0012																												
87008000	3.114	4.888	L	1	1	CRACKING	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.5	7.5	7.5	7.5	10.0	10.0														
916			2	40	22500	RIDE	7.3	7.2	7.1	6.7	6.3	6.1	6.0	6.1	6.6	6.4	5.9	7.2	6.8														
NW 42 AVE/LEJEUNE RD(3.6L)					5.9																												
4198561	3.288	4.979	C	2009	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.5	7.0													
COMMUNITY ASPHALT CORP.			(2011)	FC125		RIDE	6.0	6.6	6.6	6.4	6.1	6.1	6.2	5.8	6.3	6.4	6.2	6.0	6.1	5.6													
4499471	3.099	4.812	C	2026	0012																												
87008001	0.000	0.301	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	7.0	7.0	7.0														
916			3	30	11000	RIDE	8.3	7.9	8.0	8.1	7.7	7.6	7.0	8.0	7.7	7.7	7.5	7.0	7.2														
LEG 001(0.0C)					5.1																												
4311721	0.043	0.301	C	2016	0012	CRACKING	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5													
COMMUNITY ASPHALT CORP.			(2018)	DGFC		RIDE	6.5	7.6	7.6	7.9	7.8	8.2	7.8	7.8	7.7	7.7	7.7	7.7	7.7	7.2													
87018000	0.775	2.534	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0														
852			2	45	32500	RIDE	8.1	8.0	7.8	8.1	7.5	7.8	7.3	7.8	7.8	8.1	7.5	7.5	7.8														
NW 1700 BLK(0.8C)					4.6																												
4083012	0.759	2.534	C	2004	0012	CRACKING	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.6	6.5													
COMMUNITY ASPHALT CORP.			(2007)	FC125		RIDE	7.9	7.9	7.8	7.7	7.7	7.8	7.8	7.6	7.6	7.6	7.5	7.5	7.5	7.0													
4478261	0.766	2.430	R	2026	0226																												
87018000	0.775	2.534	L	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0														
852			2	45	32500	RIDE	7.9	7.9	7.9	8.0	7.5	7.1	7.0	7.7	7.8	8.1	7.7	7.3	7.7														
NW 1700 BLK(0.8C)					4.6																												
4083012	0.759	2.534	C	2004	0012	CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	9.0	7.0													
COMMUNITY ASPHALT CORP.			(2007)	FC125		RIDE	7.7	7.7	7.6	7.6	7.5	7.6	7.6	7.5	7.6	7.6	7.7	7.7	7.4	6.9													
4478261	0.772	2.516	L	2026	0226																												
87026000	2.829	5.529	R	1	1	CRACKING	5.5*	5.5*	5.0*	5.0*	5.0*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0														
860			3	40	41000	RIDE	6.6	6.7	6.6	6.4	5.3*	4.8*		7.3	7.4	7.3	7.3	7.0	6.8														
SR 817(3.0C)					5.6																												
2498871	1.110	4.424	C	2001	0218	CRACKING	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.5	7.5	7.5	7.0	7.0	7.0	5.0*													
COMMUNITY ASPHALT CORP.			(2007)	FC95		RIDE	7.1	6.9	7.0	6.6	6.5	6.5	6.3	6.3	6.3	6.3	6.2	6.3	6.0	5.5													
4478001	2.828	5.505	C	2025	0012																												
87026000	2.829	5.529	L	1	1	CRACKING	6.0*	6.0*	6.0*	6.0*	4.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0														
860			3	40	41000	RIDE	7.1	7.1	7.1	6.8	4.8*	4.3*		7.6	7.7	7.7	7.7	7.4	7.1														
NW 28 PL(2.8L)					5.6																												
2498871	1.110	4.424	C	2001	0218	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	8.5	7.5	7.0	7.0	7.0	7.0	7.0	5.0*													
COMMUNITY ASPHALT CORP.			(2007)	FC95		RIDE	7.2	7.2	7.0	7.1	7.0	6.9	6.9	6.8	6.5	6.5	6.5	6.6	6.3	5.8													
4478001	2.828	5.505	C	2025	0012																												
87026005	0.000	0.312	R	1	6	CRACKING	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*														
860			2	35	48500	RIDE	8.1	8.7	8.2	7.8	6.6	6.8	6.7	7.1	7.3	6.6	6.6	6.7	6.7														
ON RAMP 87075617(0.0R)					3.4																												
4274511	0.000	0.187	R	2013	0226	CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
COMMUNITY ASPHALT CORP.			(2014)	DGFC		RIDE	6.4	7.7	7.6																								
87026005	0.000	0.312	L	1	6	CRACKING	9.0	9.0	7.5	7.5	7.5	7.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*														
860			2	40	48500	RIDE	8.4	8.2	8.1	8.2	7.2	7.2	7.0	7.0	7.4	6.9	7.3	6.9	6.9														
OFF RAMP 87075626(0.0L)					3.4																												
4274511	0.000	0.187	L	2013	0226	CRACKING	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
COMMUNITY ASPHALT CORP.			(2014)	DGFC		RIDE	6.8	8.1	7.5																								

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = COMMUNITY ASPHALT CORP. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / %T / SURF_TYPE / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87030000	10.834	11.368	R	1	1	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	8.0	7.0	6.5	6.5	6.5	10.0	10.0														
5 1			4	30	34500	RIDE	6.9	7.1	7.3	6.9	6.5	6.3	5.8	6.3	6.9	6.4	5.9	8.2	7.9														
SIDE ROAD(11.0C)					5.7																												
4146231	10.816	11.283	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.3	6.5													
COMMUNITY ASPHALT CORP.				(2011)	FC95	RIDE	7.7	7.8	7.9	6.1	6.5	6.8	6.9	6.6	6.5	6.0	6.4	6.0	6.3	5.8													
87030000	11.368	11.789	R	1	6	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0			10.0	10.0	10.0	10.0														
5 1			3	30	36000	RIDE	6.9	7.9	5.4*	6.1	5.7	5.2*	5.1*			6.9	6.6	6.0	6.0														
NE 8 ST(11.5C)					4.4																												
2498352	11.280	11.856	C	2005	0005	CRACKING	10.0	10.0	10.0	9.5	9.5	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0	6.5													
COMMUNITY ASPHALT CORP.				(2009)	DGFC	RIDE	5.8	5.6	5.4*	5.9	5.4*	5.3*	5.1*	5.2*	5.4*	5.5																	
4439111	11.283	11.713	C	2024	0012																												
87030000	11.368	11.789	L	1	2	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5		10.0	10.0	10.0	10.0														
5 1			3	30	36000	RIDE	7.2	7.6	7.3	6.6	5.3*	5.7	5.3*	4.7*		6.2	5.6	5.9	6.3														
NE 7 ST(11.4L)					4.4																												
2498352	11.280	11.856	C	2005	0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.9	6.0*													
COMMUNITY ASPHALT CORP.				(2009)	DGFC	RIDE	6.0	5.8	5.6	4.5*	4.6*	4.0*	4.3*	3.9*	4.0*	3.9*	3.8*	3.8*	3.7*	3.2*													
4439111	11.283	11.713	C	2024	0012																												
87030000	10.834	11.368	L	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5		6.5	6.5	10.0	10.0														
5 1			4	30	34500	RIDE	7.2	7.3	6.6	6.5	5.5	5.7	5.7	5.0*		5.5	4.8*	7.2	7.1														
SE 1 ST(10.9L)					5.7																												
4146231	10.816	11.283	C	2008	0012	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.0	9.0	8.3	6.5													
COMMUNITY ASPHALT CORP.				(2011)	FC95	RIDE	7.0	5.6	6.7	6.0	5.7	5.9	6.1	5.9	5.5	5.1*	5.2*	5.1*	5.0*	4.5*													
87038000	0.000	1.178	R	1	1	CRACKING	7.5	7.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0														
932			2	40	16200	RIDE	6.8	7.2	6.8	8.0	6.8	6.8	6.7	6.8	7.0	6.8	6.7	6.6	5.8														
OKEECHOBEE RD(0.0C)					7.9																												
4075771	0.000	3.421	C	2002	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.6	6.5													
COMMUNITY ASPHALT CORP.				(2005)	FC125	RIDE	6.0	6.0	6.2	5.6	5.8	5.6	5.6	5.3*	5.7	5.6	5.9	5.6	5.4*	4.9*													
4459931	0.579	2.942	R	2024	0012																												
87038000	1.178	1.341	R	1	6	CRACKING	10.0	10.0	10.0		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
932			3	40	46500	RIDE	8.1	7.9	7.9		7.4	7.0	7.0	7.1	7.3	7.2	7.1	7.2	7.1														
W 19 CT(1.2R)					8.6																												
4075771	0.000	3.421	C	2002	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	9.5	7.5													
COMMUNITY ASPHALT CORP.				(2004)	FC125	RIDE	7.1	7.1	6.7	6.6																							
4459931	0.579	2.942	R	2024	0012																												
87038000	9.209	9.700	C	1	1	CRACKING	6.0*	6.0*	6.0*	5.5*	5.5*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0														
932			2	30	11600	RIDE	5.3*	5.5*	5.7	5.1*	4.7*	4.6*		7.1	6.4	6.8	6.6	7.0	6.5														
NE 2 AVE(9.2C)					7.9																												
4083031	8.843	9.700	C	2004	0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.1	6.0*													
COMMUNITY ASPHALT CORP.				(2007)	FC125	RIDE	6.6	6.6	6.6	5.7	5.9	5.7	5.6	6.0	5.4*	5.4*	5.4*	5.3*	5.5	5.0*													
4478181	9.219	9.683	C	2025	0012																												
87038000	1.341	3.278	L	1	1	CRACKING	9.0	9.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0														
932			3	40	46500	RIDE	6.5	7.6	7.7	7.2	7.1	7.8	7.1	7.6	6.8	7.2	7.1	7.1	7.0														
W 16 AVE(1.6C)					8.6																												
4075771	0.000	3.421	C	2002	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	8.7	6.5													
COMMUNITY ASPHALT CORP.				(2005)	FC125	RIDE	6.6	6.9	7.1	7.1	7.2	7.2	6.9	6.4	7.2	6.9	7.1	7.1	7.1	6.6													
4459931	1.017	2.942	L	2024	0012																												
87038000	1.178	1.341	L	1	1	CRACKING	9.0	9.0	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
932			3	40	46500	RIDE	6.5	7.6	7.7		7.5	7.7	7.1	7.8	7.8	7.8	7.6	7.8	7.4														
TN LN TO W 20 AVE(1.3L)					8.6																												
4075771	0.000	3.421	C	2002	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	7.5													
COMMUNITY ASPHALT CORP.				(2004)	FC125	RIDE	7.4	7.6	7.4	7.4	7.5	7.4	7.3	6.8	7.1	6.6	7.0	7.3	7.3	6.8													
4459931	1.017	2.942	L	2024	0012																												
87038000	0.000	1.178	L	1	1	CRACKING	10.0	10.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
932			2	40	16200	RIDE	6.0*	6.5	7.2	7.4	6.3	6.8	6.4	5.8	6.6	6.7	6.4	6.5	6.1														
OKEECHOBEE RD(0.0C)					7.9																												
4075771	0.000	3.421	C	2002	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.7	6.5													
COMMUNITY ASPHALT CORP.				(2005)	FC125	RIDE	6.0	5.8	5.9	6.2	6.0	5.7	5.7	5.3*	6.0	5.9	6.0	5.5	5.7	5.2*													
87044000	3.265	6.218	R	1	1	CRACKING	7.5	7.5	7.5	7.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0														
976			3	40	50500	RIDE	7.1	6.7	7.1	6.8	5.6		6.7	7.4	6.5	7.4	7.3	7.1	7.1														
SW 84 AVE(3.4C)					6.4																												
4056481	3.182	6.218	C	2002	0012	CRACKING	10.0	9.5	9.0	9.0	9.0	9.0	9.0	8.0	8.0	7.0	7.0	7.0	7.0	5.0*													
COMMUNITY ASPHALT CORP.				(2006)	FC125	RIDE	7.2	7.3	7.0	7.0	6.6	7.1	7.1	7.2	7.0	7.1	6.9	6.9	6.8	6.3													
4459911	4.341	6.064@	C	2024	0012																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = COMMUNITY ASPHALT CORP. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / SYSTEM SPEED / RW FY-P / SURF_TYPE / RW FY-F	TYPE / AADT / %T / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
87044000	3.265	6.218	L	1	1	CRACKING	9.0	9.0	9.0	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0														
976			3	40	50500	RIDE	7.1	6.8	7.1	5.0*	5.8		6.2	6.8	6.2	6.7	6.7	6.4	6.4														
SW 84 AVE(3.4C)					6.4																												
4056481	3.182	6.218	C	2002	0012	CRACKING	10.0	9.5	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0	8.6	6.5													
COMMUNITY ASPHALT CORP.				(2006)	FC125	RIDE	6.8	6.6	6.7	6.4	6.5	6.8	6.8	6.7	6.8	6.7	6.8	6.7	6.8	6.3													
4459911	4.341	6.064@	C	2024	0012																												
87046000	0.445	1.292	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0														
990			2	45	15200	RIDE	7.5	7.3	7.2	7.0	6.6	6.7	6.8	6.9	6.6	6.7	6.6	6.7	6.6														
KENDALE BLVD (S)(0.5C)					4.0																												
4363431	0.445	1.232	R	2018	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	9.0													
COMMUNITY ASPHALT CORP.				(2020)	FC125	RIDE	6.5	6.3	6.2	6.7	6.3	6.6	6.3	7.8	7.8	7.7	7.7	7.7	7.3	6.8													
87046000	1.292	2.970	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	8.0														
990			2	35	14700	RIDE	8.5	8.5	8.1	8.2	7.7	7.1	7.2	7.4	7.2	7.3	7.4	7.4	7.2														
SW 95 CT(1.4R)					3.7																												
4363421	1.258	2.196	C	2018	0012	CRACKING	8.0	8.0	7.0	6.0*	6.0*	6.0*	5.5*	10.0	10.0	10.0	10.0	10.0	9.6	8.5													
COMMUNITY ASPHALT CORP.				(2020)	FC125	RIDE	7.0	7.0	7.1	7.3	7.4	7.2	7.2	7.5	7.6	7.8	7.7	7.8	7.3	6.8													
87046000	0.445	1.292	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	8.0	8.0														
990			2	45	15200	RIDE	7.3	7.2	7.2	6.7	7.1	6.7	6.5	6.4	6.4	6.4	6.4	6.2	6.5														
KENDALE BLVD (S)(0.5C)					4.0																												
4363431	0.476	1.232	L	2018	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.7	8.5													
COMMUNITY ASPHALT CORP.				(2020)	FC125	RIDE	6.4	6.5	6.4	6.9	6.8	6.4	6.2	7.7	7.6	7.6	7.6	7.7	7.1	6.6													
87047000	8.128	8.678	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0															
973			2	40	35000	RIDE	7.5	7.7	7.6	7.2	6.9	6.4	5.9	6.8	6.8	6.8	6.7	6.6															
POINCIANA CONDO(8.2R)					2.2																												
4198521	8.128	8.472	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.3	7.0													
COMMUNITY ASPHALT CORP.				(2013)	FC125	RIDE	7.9	7.8	7.6	6.9	7.0	6.8	6.8	6.5	6.6	6.4	6.6	6.4	6.4	5.9													
87047000	8.678	9.505	R	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	10.0	10.0														
973			3	40	48500	RIDE	7.3	7.3	7.3	7.0	6.5	6.5	6.5	6.6	6.6	6.7	6.5	8.4	8.0														
PARK BLVD(8.8C)					4.2																												
4180901	8.665	9.482	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
COMMUNITY ASPHALT CORP.				(2011)	FC95	RIDE	8.0	8.2	7.8	8.2	8.0	8.0	7.5	7.9	7.8	7.9	7.9	7.9	7.7	7.2													
87047000	8.678	9.505	L	1	1	CRACKING	9.5	8.0	8.0	7.0	6.0*	6.5	5.0*	5.0*	5.0*	5.0*	5.0*	10.0	10.0														
973			3	40	48500	RIDE	7.2	7.4	7.3	6.7	6.5	6.7	6.1	6.6	6.5	6.1	6.4	8.2	8.2														
PARK BLVD(8.8C)					4.2																												
4180901	8.665	9.482	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
COMMUNITY ASPHALT CORP.				(2011)	FC95	RIDE	8.1	8.1	8.1	8.0	8.0	7.6	7.8	7.5	7.9	7.9	7.9	7.8	7.7	7.2													
87047000	8.128	8.678	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5														
973			2	40	35000	RIDE	7.2	7.5	7.6	7.3	6.6	6.2	6.8	5.8	6.4	6.4	6.3	6.0	5.7														
SW 4 ST(8.3C)					2.2																												
4198521	8.128	8.472	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.4	7.0													
COMMUNITY ASPHALT CORP.				(2013)	FC125	RIDE	7.8	7.6	7.7	7.6	6.8	7.3	7.0	7.1	7.3	7.0	7.1	7.1	7.1	6.6													
87052000	1.999	3.112	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	7.0	7.0	7.0	7.0	7.0	6.5	6.5														
924			2	30	21000	RIDE	8.0	7.6	7.4	7.7	7.3	7.1	7.1	7.2	6.6	6.5	6.6	6.7	6.6														
SR 7(2.0C)					4.8																												
4308091	2.084	3.112	C	2015	0012	CRACKING	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.9	7.5													
COMMUNITY ASPHALT CORP.				(2017)	FC95A	RIDE	6.5	6.2	6.2	6.1	7.4	6.9	7.0	6.9	6.8	6.8	6.5	6.4	6.2	5.7													
87052000	1.999	3.112	L	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5														
924			2	30	21000	RIDE	7.1	7.5	7.1	7.5	7.2	6.6	6.7	6.6	6.2	6.1	6.8	6.7	6.6														
SR 7(2.0C)					4.8																												
4308091	2.084	3.112	C	2015	0012	CRACKING	6.0*	6.0*	6.0*	6.0*	10.0	10.0	10.0	9.0	9.0	9.0	8.5	8.5	8.8	7.5													
COMMUNITY ASPHALT CORP.				(2017)	FC95A	RIDE	6.4	6.2	6.2	6.2	7.2	6.6	6.9	6.5	6.8	6.7	6.3	6.4	5.9	5.4*													
87054000	0.508	3.019	R	1	1	CRACKING	6.5	6.5	6.5		10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	7.5														
972			2	35	32500	RIDE	6.0*	5.9*	5.4*		5.6	5.4*	5.2*	5.0*	5.4*	5.3*	5.1*	5.0*	5.0*														
SW 36 AVE(0.7C)					8.2																												
4275131	0.500	2.954	R	2013	0012	CRACKING	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.5	8.4	7.0													
COMMUNITY ASPHALT CORP.				(2016)	FC95	RIDE	4.8*	4.7*	4.6*	6.4	6.0	6.1	5.9	5.9	5.7	5.7	5.5	5.4*	5.3*	4.8*													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = COMMUNITY ASPHALT CORP. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / SYSTEM SPEED / RW FY-P / FY-F	TYPE / AADT / %T / WKMX-P / SURF_TYPE / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
87054000	1.021	3.019	L	1	1	CRACKING	6.0*	6.0*	6.0*		10.0	10.0	10.0	9.5	9.5	7.0	6.5	6.5	6.5														
972			2		32500	RIDE	5.9*	5.9*	5.8*		5.7*	5.6*	5.3*	5.6*	5.6*	5.5*	4.9*	4.5*	4.6*													
SW 32 AVE(1.0C)					8.2																												
4275131	1.086	2.943	L	2013	0012	CRACKING	6.5	6.5	6.5	10.0	9.5	9.5	9.0	9.0	8.0	6.5	4.5*	4.5*	6.0*	4.5*													
COMMUNITY ASPHALT CORP.				(2016)	FC95	RIDE	4.1*	4.7*	4.6*	6.3*	6.1*	5.5*	5.9*	5.6*	5.7*	5.5*	5.4*	5.1*	5.2*	4.7*													
87060000	1.082	2.715	R	1	1	CRACKING	10.0	10.0	9.5	9.5	9.5	7.5	6.5	4.5*	4.5*	3.5*	3.5*	10.0	10.0														
A1A 41			3	45	78000	RIDE	8.7	8.6	8.6	8.5	7.9	7.9	7.8	7.8	7.9	7.8	7.7	7.8	7.8														
SIDE ROAD(1.4C)					4.9																												
4146351	1.082	2.717	C	2008	0012	CRACKING	10.0	10.0	10.0	9.5	9.5	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.7	6.5													
COMMUNITY ASPHALT CORP.				(2011)	FC2	RIDE	7.8	7.9	7.8	8.1	8.1	7.9	8.1	8.1	8.1	8.0	8.0	8.1	7.9	7.7													
87060000	3.670	4.663	C	1	6	CRACKING	8.0	7.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5														
A1A			2	30	18000	RIDE	5.2*	4.9*	4.7*	5.2*	4.5*	4.4*	4.0*	3.9*	4.1*	4.2*	4.1*	4.5*	4.3*														
6 ST(3.7C)					10.9																												
2502361	3.673	4.550	C	2013	0012	CRACKING	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.2	7.0													
COMMUNITY ASPHALT CORP.				(2016)	DGFC	RIDE	4.3*	3.9*																									
87060000	1.082	2.715	L	1	1	CRACKING	9.5	9.0	7.5	6.5	6.5	6.5	3.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0														
A1A 41			3	45	78000	RIDE	8.3	8.4	8.6	8.2	7.5	7.4	7.3	7.2	7.2	7.2	6.8	8.0	7.9														
SIDE ROAD(1.4C)					4.9																												
4146351	1.082	2.717	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.4	6.5													
COMMUNITY ASPHALT CORP.				(2011)	FC2	RIDE	8.0	8.1	8.1	8.4	8.3	8.3	8.3	8.3	8.2	8.2	8.2	7.8	8.1	7.9													
87066000	0.000	1.650	C	1	1	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5		10.0	10.0	10.0	9.5	9.5	9.5														
922			4	35	32000	RIDE	6.3*	6.8	6.7	6.2	5.7	6.0		6.9	6.8	6.9	6.5	6.6	6.7														
NW 7 AVE(0.0C)					4.8																												
4075911	0.133	1.886	C	2004	0012	CRACKING	9.5	9.5	9.5	9.0	9.0	9.0	8.0	8.0	7.0	7.0	6.5	6.5	7.9	6.0*													
COMMUNITY ASPHALT CORP.				(2007)	DGFC	RIDE	6.4	6.4	6.4	5.4*	5.2*	5.1*	5.2*	4.8*	5.1*	5.4*	5.1*	4.9*	5.0*	4.5*													
87072000	1.117	3.084	R	1	1	CRACKING	9.0	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
985			4	40	24000	RIDE	6.7	6.7	6.8	6.4	6.3	7.2	7.0	7.1	6.9	6.9	6.8	7.0	6.5														
SW 86 ST(1.2C)					4.4																												
4076061	0.000	3.004	C	2003	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.3	6.5													
COMMUNITY ASPHALT CORP.				(2005)	FC125	RIDE	6.8	6.7	6.6	6.3	6.3	6.1	5.8	6.2	6.1	5.9	5.7	5.8	5.5	5.0*													
4499481	1.109	3.084	C	2027	0012																												
87072000	1.117	3.084	L	1	1	CRACKING	7.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
985			3	40	24000	RIDE	6.0*	6.0*	5.9	5.4*	5.3*	6.4	6.3	6.4	6.3	6.3	6.8	7.0	6.5														
SW 86 ST(1.2C)					4.4																												
4076061	0.000	3.004	C	2003	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	6.0*													
COMMUNITY ASPHALT CORP.				(2005)	FC125	RIDE	6.8	6.7	6.6	6.3	6.3	6.1	5.8	6.2	6.1	5.9	5.7	5.8	5.0*	4.5*													
4499481	1.109	3.084	C	2027	0012																												
87080000	2.678	3.718	C	1	1	CRACKING	10.0	10.0	10.0	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5	4.5*														
934			3	35	16500	RIDE	8.4	8.0	7.6	7.4	6.9	6.5	5.9	6.3	6.2	5.9	5.9	5.8	6.0														
BAY DR W(2.7L)					9.7																												
4226171	2.678	3.718	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	8.2	6.5													
COMMUNITY ASPHALT CORP.				(2013)	DGFC	RIDE	8.1	7.4	7.3	7.6	7.6	7.3	7.2	7.3	6.9	7.1	7.1	6.9	6.9	6.4													
87080000	3.718	4.175	C	1	6	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0	9.0														
934			2	35	11300	RIDE	7.6	6.5	5.6	5.8	5.5	4.5*	3.9*	4.4*	4.1*	4.6*	4.4*	3.7*	3.7*														
BAY DR E(3.7C)					9.7																												
4198251	3.718	4.175	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	6.0*													
COMMUNITY ASPHALT CORP.				(2013)	FC95	RIDE	7.2	6.4	6.7	5.1*	4.9*	4.7*	4.4*	4.2*																			
4439261	3.692	4.165	C	2026	0012																												
87080347	0.000	1.042	C	1	1	CRACKING	10.0	10.0	10.0	8.0	8.0	8.0	7.5	6.5	6.5	6.5	5.5*	5.5*	5.5*														
934			3	35	22500	RIDE	7.2	6.6	6.6	6.8	6.4	6.1	6.0	6.2	6.5	6.3	4.8*	5.2*	5.7														
BAY DR E(0.0C)					9.7																												
4226161	0.312	1.042	C	2010	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	7.0													
COMMUNITY ASPHALT CORP.				(2013)	DGFC	RIDE	7.0	6.8	6.5	6.8	6.3	6.2	6.0	5.9	5.7	5.6	5.8	5.5	5.7	5.2*													
4525571	0.122	1.042	C	2027	0012																												
87090000	5.280	7.300	R	1	8	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5														
25 27			3	50	31166	RIDE	8.9	8.7	8.8	8.7	8.3	8.2	8.1	8.1	8.2	8.0	8.1	8.0	8.0														
NW 138 ST(5.7C)					3.8																												
2497581	5.166	10.187	C	1998	0012	CRACKING	8.5	8.5	8.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5															
COMMUNITY ASPHALT CORP.				(2000)	FC2	RIDE	7.9	7.8	7.9	8.1	8.0	8.0	8.1	8.0	7.9	7.9	7.9	7.8															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = COMMUNITY ASPHALT CORP. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / SYSTEM / RW FY-P / SURF_TYPE / FY-F	TYPE / SPEED / %T / WKMX-P / WKMX-F	AADT	DISTRESS RATINGS ========	SURVEYED YEAR 2000 / 2013	2001 / 2014	2002 / 2015	2003 / 2016	2004 / 2017	2005 / 2018	2006 / 2019	2007 / 2020	2008 / 2021	2009 / 2022	2010 / 2023	2011 / 2024	2012 / 2025	FUTURE 2030 (PMRS)
87090000	7.300	8.200	R	1	8	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	
25 27			3	50	31166	RIDE	8.9	8.7	8.8	8.7	8.3	8.2	8.1	8.1	8.2	8.0	8.1	8.0	8.0	
NW 116 WAY(7.5R)					3.8															
2497581	5.166	10.187	C	1998	0012	CRACKING	8.5	8.5	8.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5			
COMMUNITY ASPHALT CORP.				(2000)	FC2	RIDE	7.9	7.8	7.9	8.1	8.0	8.0	8.1	8.0	7.9	7.9	7.9			
4232515	6.346	8.114	C	2022	0218															
87090000	9.037	10.027	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.5	
25 27			3	45	45500	RIDE	8.9	8.7	8.8	8.7	8.3	8.2	8.1	8.1	8.2	8.0	8.1	8.0	8.0	
					17.5															
2497581	5.166	10.187	C	1998	0012	CRACKING	8.5	8.5	8.0	6.5	6.5	6.5	6.5	7.0	7.0	7.0	6.5	6.5	7.2	4.5*
COMMUNITY ASPHALT CORP.				(2000)	FC5	RIDE	7.9	7.8	7.9	8.1	8.0	8.0	8.1	7.9	8.1	8.2	7.9	7.8	8.0	7.8
4232513	9.502	10.169	C	2024	0213															
87090000	9.037	10.027	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	
25 27			3	45	45500	RIDE	8.9	8.7	8.8	8.7	8.3	8.2	8.1	8.0	8.1	7.7	7.8	7.9	7.9	
JOHN HILL RD(9.6L)					17.5															
2497581	5.166	10.187	C	1998	0012	CRACKING	9.5	9.5	9.5	8.0	8.0	8.0	8.0	7.5	6.5	6.5	6.5	6.5	8.2	5.5*
COMMUNITY ASPHALT CORP.				(2000)	FC2	RIDE	7.8	7.8	7.7	7.7	7.5	7.7	7.8	7.9	7.9	8.0	8.0	8.0	7.9	7.7
4232513	9.502	10.169	C	2024	0213															
87090000	8.200	8.572	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	
25 27			3	50	31166	RIDE	8.9	8.7	8.8	8.7	8.3	8.2	8.1	8.0	8.1	7.7	7.8	7.9	7.9	
					3.8															
2497581	5.166	10.187	C	1998	0012	CRACKING	9.5	9.5	9.5	9.0	9.0	9.0	9.0	7.5	4.5*	4.5*	3.5*	3.5*	7.0	4.0*
COMMUNITY ASPHALT CORP.				(2000)	FC5M	RIDE	7.8	7.8	7.7	8.2	8.1	8.0	8.1	8.2	8.2	8.1	8.1	8.0	7.9	7.7
4232514	8.114	9.502	C	2031	0218															
87090000	7.054	8.200	L	1	8	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	
25 27			3	50	31166	RIDE	8.9	8.7	8.8	8.7	8.3	8.2	8.1	8.0	8.1	7.7	7.8	7.9	7.9	
HIALEAH GDNS BLVD(7.5L)					3.8															
2497581	5.166	10.187	C	1998	0012	CRACKING	9.5	9.5	9.5	9.0	9.0	9.0	9.0	7.5	4.5*	4.5*	3.5*			
COMMUNITY ASPHALT CORP.				(2000)	FC2	RIDE	7.8	7.8	7.7	8.2	8.1	8.0	8.1	8.2	8.2	8.1	8.1			
4232515	6.346	8.114	C	2022	0218															
87090000	4.540	7.054	L	1	8	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	
25 27			2	55	30000	RIDE	8.9	8.7	8.8	8.7	8.3	8.2	8.1	8.0	8.1	7.7	7.8	7.9	7.9	
NW 138 ST(5.7C)					22.5															
2497581	5.166	10.187	C	1998	0012	CRACKING	9.5	9.5	9.5	9.0	9.0	9.0	9.0	7.5	4.5*	4.5*	3.5*	6.5		
COMMUNITY ASPHALT CORP.				(2000)	FC2	RIDE	7.8	7.8	7.7	8.2	8.1	8.0	8.1	8.2	8.2	8.1	8.1	8.1		
87120000	0.297	2.440	R	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	8.0	8.0	8.0	8.0	7.5	6.5	6.5		
90 41			2	55	24500	RIDE	8.2	8.3	8.3	8.3	7.6	7.6	6.9	7.4	7.3	7.2	7.4	7.2		
SW 157 AV(2.0R)					11.0															
4231341	0.243	2.440	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.4	6.5
COMMUNITY ASPHALT CORP.				(2013)	FC5	RIDE	8.4	8.4	8.4	8.4	8.4	8.4	8.5	8.5	8.4	8.3	8.3	8.3	8.4	8.2
87120000	0.390	2.440	L	1	1	CRACKING	10.0	10.0	9.5	9.5	9.5	7.0	6.5	4.5*	3.5*	3.5*	3.5*	3.5*		
90 41			2	55	24500	RIDE	8.3	8.5	8.2	7.8	7.5	7.4	6.6	7.1	6.8	7.2	6.3*	6.2*		
					11.0															
4231341	0.243	2.440	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.0	9.0	9.0	8.7	7.0
COMMUNITY ASPHALT CORP.				(2013)	FC5	RIDE	8.3	8.3	8.1	8.1	8.2	8.3	8.3	8.3	8.2	8.0	8.2	8.2	8.2	8.0
87133000	0.000	2.544	R	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	6.5	6.5	6.5	
825			3	40	37000	RIDE	8.5	8.2	8.4	8.2	7.8	7.7	7.5	7.3	7.4	7.5	7.1	7.4	7.1	
SW 128 ST(0.0C)					4.6															
4293471	0.022	2.531	C	2014	0226	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.6	8.5
COMMUNITY ASPHALT CORP.				(2016)	FC95A	RIDE	6.9	7.2	6.9	8.1	8.0	7.8	7.8	7.9	7.9	7.9	7.8	7.9	7.6	7.1
87133000	0.000	2.544	L	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	
825			3	40	37000	RIDE	8.4	8.2	8.4	8.0	7.4	7.2	7.3	7.6	7.4	7.4	7.4	7.3	7.3	
SW 128 ST(0.0C)					4.6															
4293471	0.022	2.531	C	2014	0226	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5
COMMUNITY ASPHALT CORP.				(2016)	FC95A	RIDE	7.0	7.1	7.0	8.1	7.9	7.8	7.8	7.9	7.7	7.7	7.7	7.7	7.7	7.2
87140000	3.091	5.610	R	1	1	CRACKING	6.5	6.5	4.5*	4.5*	10.0	10.0	8.0	8.0	7.0	7.0	7.0	7.0	6.5	
7 441			4	35	30500	RIDE	6.3*	5.7*	6.0	5.6	7.1	6.8	6.7	6.5	6.2	6.3	6.2	5.9	5.3*	
43RD ST NW(3.5R)					4.1															
4308171	3.460	5.649	C	2015	0012	CRACKING	6.5	6.5	6.5	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.0
COMMUNITY ASPHALT CORP.				(2018)	FC95A	RIDE	5.7	5.7	5.4*	4.4*		6.6	6.5	6.1	5.8	5.8	5.5	5.6	5.7	5.2*

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = COMMUNITY ASPHALT CORP. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / FY-P / FY-F	SYSTEM / SPEED / RW WKMX-P / WKMX-F	TYPE / AADT / %T / SURF_TYPE	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87140000	3.091	5.610	L	1	1	CRACKING	6.5	6.5	4.5*	4.5*	10.0	10.0	10.0	7.0	7.0	7.0	7.0	7.0	6.5														
7 441			3	30	30500	RIDE	5.8*	5.6*	5.5	5.2*	6.5	6.2	6.0	6.8	6.6	6.3	6.2	5.9	5.3*													
NW 7 AVE(3.5L)					4.1																												
4308171	3.460	5.649	C	2015	0012	CRACKING	6.5	6.5	6.5	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	8.0													
COMMUNITY ASPHALT CORP.				(2018)	FC95A	RIDE	5.7	5.7	5.4*	4.4*		6.6	6.5	6.1	5.8	5.3*	5.2*	5.1*	5.1*	4.6*													
87170000	3.701	4.935	R	1	1	CRACKING	9.0	9.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0														
826			4	45	67500	RIDE	8.0	8.1	8.0	7.4	6.8	6.9	6.7	6.6		8.0	7.6	7.9	7.8														
INTERAMA BLVD(4.8R)					4.2																												
4076302	3.701	5.085	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	8.2	6.0*													
COMMUNITY ASPHALT CORP.				(2009)	FC5	RIDE	7.6	7.4	7.1	7.8	7.5	7.7	7.6	7.8	7.6	7.7	7.1	7.3	7.1	6.9													
4525621	3.720	5.105	C	2030	0012																												
87210000	0.000	1.704	R	1	1	CRACKING	9.0	7.5	7.5	7.5	7.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*														
856			3	55	41000	RIDE	7.1	6.5	7.6	8.1	7.0	7.3	7.1	7.3	6.8	7.0	7.0	6.9	6.9														
BISCAYNE BLVD(0.0C)					2.6																												
4284861	0.000	1.125	C	2013	0012	CRACKING	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.6	7.0													
COMMUNITY ASPHALT CORP.				(2015)	FC5	RIDE	7.3	6.8	7.5	7.9	7.7	7.6	7.8	7.5	7.7	7.6	7.7	7.7	7.4	7.2													
87210000	0.000	1.704	L	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*														
856			3	45	41000	RIDE	7.7	7.8	7.8	7.5	7.1	7.3	7.3	7.2	7.1	6.8	7.4	7.3	6.8														
BISCAYNE BLVD(0.0C)					2.6																												
4284861	0.000	1.125	C	2013	0012	CRACKING	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.4	6.5													
COMMUNITY ASPHALT CORP.				(2015)	FC5	RIDE	6.9	6.8	8.1	7.7	8.1	8.0	8.1	8.0	7.9	7.8	7.7	7.8	7.7	7.5													
87240000	11.345	13.110	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	6.5	6.5	6.5														
9			2	50	29452	RIDE	8.4	8.5	8.5	8.3	7.8	7.8	7.7	7.7	7.7	7.8	7.2	7.5	7.4														
NW 22 AVE(11.8C)					8.4																												
4291841	11.237	13.318	C	2014	0012	CRACKING	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.8	7.0													
COMMUNITY ASPHALT CORP.				(2016)	FC5A	RIDE	7.4	7.1	7.2	8.1	8.1	8.1	8.0	8.0	8.0	8.0	8.0	8.0	7.9	7.7													
87240000	13.110	13.690	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	6.0*	5.5*	5.5*	5.5*														
9			2	50	31500	RIDE	8.4	8.5	8.5	8.3	7.8	7.8	7.7	7.7	6.9	6.7	7.0	6.7	6.4*														
SR 7 / US 441 SB(13.7R)					10.6																												
4284762	13.281	13.690	C	2012	0012	CRACKING	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.9	6.0*													
COMMUNITY ASPHALT CORP.				(2014)	OGFC	RIDE	6.7	8.1	8.2	8.2	8.2	8.2	8.1	8.0	7.8	7.7	7.6	7.6	7.2	7.0													
87240000	13.110	13.690	L	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5														
9			2	50	31500	RIDE	8.2	8.0	7.9	8.2	7.6	7.6	7.1	7.4	7.4	7.3	7.6	7.3	7.3														
					10.6																												
4284762	13.281	13.690	C	2012	0012	CRACKING	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	5.5*													
COMMUNITY ASPHALT CORP.				(2014)	OGFC	RIDE	7.3	8.0	8.5	8.3	8.3	8.3	8.3	8.3	8.1	8.3	7.9	7.9	7.9	7.7													
87240000	11.345	13.110	L	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5														
9			2	50	29452	RIDE	8.2	8.0	7.9	8.2	7.6	7.6	7.1	7.4	7.4	7.3	7.6	7.3	7.3														
NW 22 AVE(11.8C)					8.4																												
4291841	11.237	13.318	C	2014	0012	CRACKING	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	6.0*													
COMMUNITY ASPHALT CORP.				(2016)	FC5A	RIDE	7.3	7.2	7.2	8.2	8.1	8.2	8.1	8.0	8.1	8.1	8.0	8.0	7.9	7.7													
87260000	16.379	19.053	R	1	1	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	7.0	7.0	7.0														
826	16.4	19.1	3	55	143500	RIDE	8.3		8.2	8.5	8.1	7.9	8.0	8.0	8.0	8.0	7.8	7.9	7.7														
DIRECTION CHANGES AT THI(16.9C)					5.9																												
4291351	16.417	19.063	C	2014	0012	CRACKING	6.5	6.5	6.5		10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.3	6.5													
COMMUNITY ASPHALT CORP.				(2017)	FC5M	RIDE	7.8	7.7	7.7		8.2	8.2	8.2	8.2	8.2	8.3	8.2	8.1	8.1	7.9													
4471651	8.355	17.950	C	2022	0213																												
87260000	19.053	22.273	R	1	1	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	7.0	7.0	7.0														
826	19.1	22.3	3	55	130000	RIDE	8.3	8.3	8.9	8.7	8.0	7.3	7.9	8.1	8.2	8.2	8.0	8.0	7.9														
					5.1																												
4327432	19.053	21.623	C	2016	0012	CRACKING	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.6	8.0													
COMMUNITY ASPHALT CORP.				(2018)	FC5M	RIDE	7.8	7.7	7.6	7.9	7.9	8.4	8.3	8.4	8.4	8.4	8.4	8.4	8.3	8.1													
87260000	22.273	23.014	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	8.0														
826	22.3	23.0	4	55	141000	RIDE	8.3	8.3	8.8	8.6	8.2	8.1	8.0	7.6	8.2	8.1	7.8	8.0	7.7														
					4.2																												
4327433	22.220	23.046	C	2016	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.2	7.5													
COMMUNITY ASPHALT CORP.				(2018)	FC5M	RIDE	8.0	8.0	7.9	8.2	8.1	8.4	8.4	8.5	8.5	8.5	8.5	8.5	8.4	8.2													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = COMMUNITY ASPHALT CORP. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87260000  22.273 23.046  L    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   7.0   7.0   7.0   7.0
826         22.3   23.0  4   55 141000 RIDE      8.5   8.3   8.9   8.3   8.1   8.2   8.1   7.8   8.2   8.1   8.0   7.8   7.9
                                   4.2
4327433   22.220 23.046  C 2016   0012 CRACKING  6.5   6.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.7   8.0
COMMUNITY ASPHALT CORP.   (2018) FC5M  RIDE      7.8   7.6   7.6   8.2   8.2   8.5   8.6   8.7   8.8   8.8   8.6   8.8   8.8   8.6

87260000  19.053 22.273  L    1      1 CRACKING  4.5* 10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   7.0   7.0   7.0   7.0
826         19.1   22.3  3   55 130000 RIDE      8.3   8.3   8.8   8.7   8.0   8.2   8.1   7.7   8.2   8.2   8.0   7.9   7.8
                                   5.1
4327432   19.053 21.623  C 2016   0012 CRACKING  6.5   6.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.8   8.5
COMMUNITY ASPHALT CORP.   (2018) FC5M  RIDE      7.7   7.7   7.6   7.9   7.8   8.6   8.5   8.7   8.6   8.6   8.7   8.6   8.6   8.4

87260000  16.379 19.053  L    1      1 CRACKING  4.5*       10.0  10.0  10.0  10.0  10.0   9.5   9.5   7.0   7.0   6.5   6.5
826         16.4   19.1  3   55 143500 RIDE      8.3         8.2   8.1   7.6   7.7   7.6   7.0   7.8   7.8   7.7   7.5   7.5
DIRECTION CHANGES AT THI(16.9C)    5.9
4291351   16.417 19.063  C 2014   0012 CRACKING  6.5   6.5   6.5        10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.5   7.0
COMMUNITY ASPHALT CORP.   (2017) FC5M  RIDE      7.5   7.4   7.3         8.5   8.4   8.5   8.6   8.5   8.6   8.5   8.5   8.5   8.3
4471651    8.355 17.950  C 2022   0213
-------------------------------------------------------------------------------------------------------------------------------------
87281000   9.598 11.735  R    1      1 CRACKING  9.0   9.0   9.0   9.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
953                      3   40  18900 RIDE      5.9*  5.9*  5.4*  5.8   7.5   7.1   7.1   7.1   7.2   6.8   7.1   6.8   6.8
SR 932( 9.7C)                      8.2
4056561    9.704 11.735  C 2002   0012 CRACKING 10.0   9.5   9.0   9.0   9.0   8.0   8.0   8.0   8.0   7.0   7.0   7.0   7.0   5.0*
COMMUNITY ASPHALT CORP.   (2004) FC125 RIDE      6.7   6.8   6.5   6.4   6.5   6.6   6.6   6.4   6.5   6.6   6.5   6.3   6.4   5.9
4478031    9.717 11.695  C 2027   0012
-------------------------------------------------------------------------------------------------------------------------------------
87281000   9.722 11.735  L    1      1 CRACKING  9.0   9.0   9.0   9.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
953                      3   40  18900 RIDE      6.8   6.6   6.8   6.3   7.8   7.7   7.6   7.3   7.6   7.6   7.7   7.5   7.6
E 50 ST( 9.8L)                     8.2
4056561    9.704 11.735  C 2002   0012 CRACKING 10.0   9.5   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.0   8.0   8.5   6.5
COMMUNITY ASPHALT CORP.   (2004) FC125 RIDE      7.5   7.4   7.2   6.6   6.4   7.0   7.1   7.0   7.0   7.1   7.1   6.9   6.9   6.4
4478031    9.717 11.695  C 2027   0012
-------------------------------------------------------------------------------------------------------------------------------------
87471000  33.000 34.909  R    5      8 CRACKING  8.0   8.0              10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0
821         33.0   34.9  3   60 109900 RIDE      8.7   8.8               7.7   7.7   7.7   7.7   7.8   7.8   7.4   7.6   7.6
                                   5.7
2519291   31.747 39.623  C 2000   0218 CRACKING  9.0   9.0   6.5   6.5   6.5   6.5   6.5   6.5   5.5*
COMMUNITY ASPHALT CORP.   (2004) FC2   RIDE      7.5   7.4   7.4   7.7   7.6   7.4   7.6   7.7   7.8
4355421   33.273 39.438  C 2020   0213

87471000  35.445 38.580  R    5      8 CRACKING  8.0   8.0              10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0
821         35.4   38.6  3   60 101500 RIDE      8.7   8.8               7.7   7.7   7.7   7.7   7.8   7.8   7.4   7.6   7.6
                                   5.7
2519291   31.747 39.623  C 2000   0218 CRACKING  9.0   9.0   6.5   6.5         3.5*  3.5*  6.5   6.5
COMMUNITY ASPHALT CORP.   (2004) FC2   RIDE      7.5   7.4   7.4   7.7         8.3   8.3   8.5   8.4
4355421   33.273 39.438  C 2020   0213
-------------------------------------------------------------------------------------------------------------------------------------
90020000  10.085 10.730  C    1      1 CRACKING  8.5   8.5   8.5   8.5   8.0   8.0   8.0   7.0   8.0   6.5   6.5   4.5*  4.5*
5    1                   2   55  18000 RIDE      7.9   7.8   7.9   7.6   7.2   6.7   7.1   7.1   7.1   6.9   6.7   6.5   6.4*
BAY POINT DR(10.3R)                9.9
4256007   10.085 10.730  C 2012   0226 CRACKING  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.2   8.0
COMMUNITY ASPHALT CORP.   (2014) FC95  RIDE      6.4*  7.3   7.5   7.3   7.3   7.2   7.1   7.2   7.1   6.6   7.0   7.1   7.1   6.6

90020000  16.158 18.585  C    1      1 CRACKING  9.0   8.0   7.0   7.0   6.5   4.0*  4.0*  4.5*  4.5*  4.5* 10.0  10.0  10.0
5    1                   2   45  17800 RIDE      8.4   8.4   8.4   8.2   7.6   7.4   7.5   7.3   6.6   7.0   7.6   7.7   7.7
DROST DR(16.5R)                    9.9
4181001   16.140 18.576  C 2008   0012 CRACKING 10.0  10.0  10.0  10.0   9.0   7.5   6.5   6.5   4.5*  4.5*  4.5*  3.5*  3.5*  1.5*
COMMUNITY ASPHALT CORP.   (2010) FC5   RIDE      7.7   7.7   7.7   7.6   7.6   7.5   7.4   7.5   7.4   7.4   7.3   7.2   7.1   6.9
4438981   16.178 18.583  C 2023   0012
-------------------------------------------------------------------------------------------------------------------------------------
90030000   1.545  2.051  R    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   8.0   7.5   7.5   7.0   7.0   7.0   7.0   7.0
5    1                   1   45  14300 RIDE      7.9   7.9   7.8   7.6   7.1   7.1   7.0   7.1   7.0   7.0   7.0   6.8   6.8
LONG BEACH BLVD( 1.9R)             9.9
4291431    1.683  1.975  C 2014   0012 CRACKING  7.0   7.0   7.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.1   8.0
COMMUNITY ASPHALT CORP.   (2016) FC95A RIDE      6.6   6.6   6.6   8.0   8.0   7.8   7.7   7.8   7.8   7.8   7.8   7.8   7.7   7.2

-------------------------------------------------------------------------------------------------------------------------------------
90030000   1.545  2.051  L    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   8.0   7.5   7.5   7.0   6.5   6.5   6.5   6.5
5    1                   1   45  14300 RIDE      7.9   7.9   7.8   7.6   7.1   7.1   7.0   7.1   6.3   6.6   6.1   6.1   6.1
                                   9.9
4291431    1.683  1.975  C 2014   0012 CRACKING  6.5   6.5   6.5  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0  10.0   9.1   8.0
COMMUNITY ASPHALT CORP.   (2016) FC95A RIDE      5.9   5.5   5.4*  8.0   7.9   7.9   7.8   7.7   7.8   7.8   7.7   7.6   7.6   7.1
-------------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = COMMUNITY ASPHALT CORP. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                                                              (PMRS)

90040000   1.003  6.455  R    1      1 CRACKING  9.0   7.5   7.5   7.0   7.0   6.5   4.5*  3.5*  3.5*  3.5*  3.5*  3.5*  3.5*
5    1                   2   45  33500 RIDE      8.0   8.0   7.9   7.7   7.4   7.2   7.2   7.0   6.8   6.6   6.6   6.4   5.1*
MARATHON PARK ENT( 1.2R)                9.9
4198541    2.180  5.982  C 2010   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.7   7.0
COMMUNITY ASPHALT CORP.   (2013) FC95  RIDE      8.0   7.9   8.0   7.8   7.8   7.5   7.5   7.6   7.6   7.6   7.6   7.6   7.5   7.0
-----------------------------------------------------------------------------------------------------------------------------------
90040000   1.003  6.455  L    1      1 CRACKING  9.0   7.5   7.0   7.0   7.0   5.5*  3.5*  3.5*  3.5*  1.0*  1.0*  1.0*  1.0*
5    1                   2   45  33500 RIDE      8.2   8.2   8.1   7.8   7.3   6.9   6.9   6.8   6.8   6.6   6.6   6.3   5.8
37 STREET( 1.1L)                        9.9
4198541    2.180  5.982  C 2010   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.0   8.7   7.0
COMMUNITY ASPHALT CORP.   (2013) FC95  RIDE      7.9   7.8   7.7   7.6   7.6   7.6   7.4   7.4   7.4   7.4   7.3   7.2   7.2   6.7
-----------------------------------------------------------------------------------------------------------------------------------
90060000  16.313 17.105  R    1      1 CRACKING 10.0  10.0   8.0   8.0   8.0   8.0   7.5   7.0   6.5   4.5*  4.5*  4.5*  4.5*
5    1                   2   45  30000 RIDE      8.3   8.3   8.3   7.9   7.7   7.5   7.6   7.7   7.6   7.4   7.3   7.2   6.6
BESSIE RD(16.7R)                        9.9
4255991   16.465 17.105  C 2012   0012 CRACKING  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.9   7.5
COMMUNITY ASPHALT CORP.   (2014) FC95  RIDE      6.8   8.3   8.1   7.9   7.8   7.9   7.8   7.7   7.7   7.8   7.7   7.7   7.6   7.1
-----------------------------------------------------------------------------------------------------------------------------------
90060000  25.728 26.207  L    1      1 CRACKING 10.0  10.0   9.0   9.0   7.5   6.0*  6.0*  6.0*  4.5*  4.5*  4.5*  4.5* 10.0
5    1                   2   45  39000 RIDE      8.9   8.9   8.9   8.7   8.2   8.0   8.0   8.0   7.7   7.3   7.2   6.8   8.4
SPUR(25.7L)                             9.9
4198531   25.728 25.951  L 2010   0012 CRACKING 10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   7.5   6.5   6.5   6.5   6.6   4.5*
COMMUNITY ASPHALT CORP.   (2012) OGFC  RIDE      8.4   8.4   7.6   8.2   8.1   8.0   8.0   7.9   8.0   8.0   7.9   7.8   7.8   7.6
4439211   23.203 26.177  C 2023   0012

90060000  16.313 17.105  L    1      1 CRACKING 10.0  10.0  10.0   9.0   9.0   9.0   7.5   7.5   6.5   4.5*  4.5*  4.5*  4.5*
5    1                   2   45  30000 RIDE      8.1   8.2   8.0   7.8   6.9   7.0   6.7   6.8   6.9   6.7   6.7   6.4   6.6
ROYAL POINCIANA(16.3L)                  9.9
4255991   16.465 17.105  C 2012   0012 CRACKING  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.3   8.0
COMMUNITY ASPHALT CORP.   (2014) FC95  RIDE      6.4   8.0   7.4   7.3   7.5   7.3   7.2   7.2   7.1   7.2   7.1   7.0   6.9   6.4
-----------------------------------------------------------------------------------------------------------------------------------
90060001   0.000  2.494  C    1      1 CRACKING  9.0   9.0   9.0   8.5   7.5   6.0*  6.0*  6.0*  6.0*  6.0*  6.0*  6.0* 10.0
5    1                   2   45  16000 RIDE      8.3   8.1   8.1   7.6   6.7   6.6   7.4   7.4   7.1   6.7   6.4   6.3   8.1
N OCEAN BAY DR( 0.0R)                   9.2
4198531    0.000  2.494  C 2010   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   7.0   5.0*
COMMUNITY ASPHALT CORP.   (2012) OGFC  RIDE      8.1   8.1   8.1   8.2   8.3   8.1   8.0   8.1   8.1   8.1   8.0   8.0   7.9   7.7
-----------------------------------------------------------------------------------------------------------------------------------
90060002   0.000  0.772  C    1      1 CRACKING  8.5   8.5   8.5   7.5   7.0   6.0*  6.0*  6.0*  6.0*  6.0*  6.0*  6.0* 10.0
5    1                   2   45  17000 RIDE      7.9   8.4   7.9   7.5   6.7   6.3*  6.4   6.2   5.6   5.0*  5.5   5.2*  8.4
US-1/SR-5/ID90060000( 0.0C)             8.0
4198491    0.000  0.772  R 2010   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   8.7   7.0
COMMUNITY ASPHALT CORP.   (2012) DGFC  RIDE      8.4   8.4   8.1   7.9   8.1   7.7   7.8   7.8   7.6   7.6   7.7   7.7   7.7   7.2
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = FERREIRA CONSTRUCTION CO., I ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ======== 	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87085000	3.603	4.245	R	1	1	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.0	7.0	6.5	6.5	6.5	6.5	
933			2	35	22500	RIDE	7.2	7.5	7.3	7.1	6.3	6.5	5.8	6.1	6.3	6.0	6.0	5.8	5.8	
MISSING DESCRIPTION I(3.7R)					12.0															
4308161	3.603	4.245	C	2015	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.8	7.5
FERREIRA CONSTRUCTION CO.,(2016)					FC125	RIDE	5.6	5.8	5.7		6.4	5.6	6.0	5.9	5.4*	5.9	5.9	6.0	5.5	5.0*
87085000	3.603	4.245	L	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	
933			2	35	22500	RIDE	7.2	7.4	7.1	6.9	6.2	6.3	5.8	6.4	6.3	6.4	5.7	6.2	5.7	
NW 29 TER(3.7L)					12.0															
4308161	3.603	4.245	C	2015	0012	CRACKING	7.5	6.5	6.5	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.7	6.5
FERREIRA CONSTRUCTION CO.,(2016)					FC125	RIDE	5.7	4.9*	5.4*		5.6	5.5	5.5	5.6	5.3*	5.4*	5.2*	5.5	5.3*	4.8*

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = FLORIDA ENGINEERING & DEVELO ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / %T / WKMX-P / SURF_TYPE / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87060000	5.750	6.686	C	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	6.5															
A1A			3	30	9300	RIDE	7.0	6.7	6.3	5.6	5.6	5.4*	5.1*	5.2*	5.2*	5.0*	4.8*	4.4*															
28 ST(5.8L)					10.9																												
4439021	5.657	6.644	C	2023	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			10.0	9.5	9.0													
FLORIDA ENGINEERING & DEVE				(2024)	FC95	RIDE	7.7	7.3	6.6	5.3*	5.4*	4.9*	4.6*	4.0*	2.8*			3.7*	3.9*	3.4*													
87060000	8.406	8.658	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0														
A1A			3	30	14500	RIDE	7.1	6.7	7.0	6.7	5.8	5.5	5.0*	7.5	6.7	6.0	6.0	5.6	5.5														
TRN LN FR INDIAN CRK(8.4L)					10.9																												
4308132	8.411	8.643	C	2022	0015	CRACKING	10.0	9.0	9.0	8.5	8.5	6.5	6.5	6.5	5.5*	5.5*	5.5*	10.0	10.0	9.5													
FLORIDA ENGINEERING & DEVE				(2024)	FC95	RIDE	5.6	4.9*	5.0*	4.8*	4.6*	4.3*	4.3*	4.3*	4.6*	4.2*	4.4*	3.6*	4.6*	4.1*													
87060001	3.014	3.231	C	1	7	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0														
A1A			3	30	24000	RIDE	7.4	6.7	6.5	6.5	5.5	5.2*	4.5*	5.9	5.6	5.5	5.9	6.3	6.4														
SR 907 *(3.0C)					7.5																												
4308132	3.029	3.218	C	2022	0015	CRACKING	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	6.0*	6.0*	6.0*	5.5*	10.0	9.5													
FLORIDA ENGINEERING & DEVE				(2025)	DGFC	RIDE	6.0	5.7	6.0											6.8													
87090000	18.527	19.288	C	1	7	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5		10.0	10.0	10.0	10.0	10.0														
25 27			2	30	18200	RIDE	7.5	7.2	7.3	7.0	6.1	5.9	5.6		7.2	7.7	7.6	7.3	6.8														
SEVENTH AVE NW(18.5C)					5.1																												
4439101	18.773	19.253	R	2023	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	9.5													
FLORIDA ENGINEERING & DEVE				(2025)	FC125	RIDE	6.9	6.8	7.4	6.7	6.6	6.2	5.9	5.6	6.5	6.4	6.5	5.9	6.4	5.9													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO ----------

```
RDWYID        BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87075000   0.000  0.490  R    4      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
93   I75     0.0    0.5  2   70 154500 RIDE      9.1   8.7   8.5   7.9   7.3   7.8   7.7   7.7   7.9   8.0   8.1   8.1   8.0
E END OF BR OVR 826( 0.0C)        10.4
2516301    0.000  5.458  C 1991   0210 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   7.4   2.5*
GENERAL ASPHALT CO        (1992) FC5M  RIDE      8.2   8.0   8.0   8.2   8.2   8.1   8.1   7.9   8.2   8.3   8.2   8.1   8.0   7.9
4459881    0.000  0.490  C 2024   0012
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / %T / W_BMP / W_EMP / W_EMP	EMP / G_EMP / W_EMP	RW / LN / RW / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / WKMX-P / SURF_TYPE / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87001000	4.846	5.488	R	1	1	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	8.0	8.0	8.0	8.0															
94			4	45	86000	RIDE	8.4	8.2	8.5	8.0	7.5	7.4	7.5	7.6	7.7	7.6	7.6	7.3	7.4															
SW 127 AV(5.0C)					3.8																													
4332642	4.855	5.419	R	2020	0012	CRACKING	8.0	8.0	8.0	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	9.0														
GENERAL ASPHALT CO., INC.				(2021)	FC95M	RIDE	7.4	7.3	7.2	7.6	7.1	7.5	7.0	7.3	8.2	8.2	8.4	8.4	8.1	7.6														
87001000	7.630	10.700	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0	8.0	7.5	7.5															
94			3	45	37000	RIDE	8.4	8.4	8.5	8.2	7.5	7.1	7.3	7.4	7.3	7.2	7.3	7.5	7.5															
SW 97 AVE(8.1C)					4.3																													
4311701	8.154	9.876	C	2018	0012	CRACKING	7.5	7.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	9.7	9.0														
GENERAL ASPHALT CO., INC.				(2021)	FC125	RIDE	7.2	7.3	7.1	7.8	7.7	7.7	7.5	7.7	7.4	7.5	7.6	7.5	7.3	6.8														
87001000	7.630	10.700	L	1	1	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	7.5	7.5	7.5															
94			4	45	37000	RIDE	8.4	8.4	8.4	8.1	7.5	7.4	7.5	7.6	7.6	7.5	7.2	7.3	7.3															
SW 102 AVE(7.6L)					4.3																													
4311701	8.154	9.876	C	2018	0012	CRACKING	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	9.6	8.5														
GENERAL ASPHALT CO., INC.				(2021)	FC125	RIDE	7.1	7.1	7.1	7.5	7.4	7.1	6.9	7.4	7.4	7.4	7.4	7.4	7.2	6.7														
87001000	4.716	5.488	L	1	1	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.0															
94			4	45	86000	RIDE	7.5	7.4	7.8	7.7	6.7	6.6	6.0	6.7	6.8	6.7	6.1	5.9	6.6															
SIDE ROAD(4.8C)					3.8																													
4332642	4.967	5.419	L	2020	0012	CRACKING	8.0	8.0	8.0	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	9.7	9.0														
GENERAL ASPHALT CO., INC.				(2021)	FC95M	RIDE	6.5	6.5	6.4	6.8	6.8	6.8	6.0	6.8	8.2	7.9	8.1	8.0	7.8	7.3														
87008000	2.045	3.114	R	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	7.0	7.0	7.0	7.0															
916			2	45	29000	RIDE	8.6	8.3	8.3	7.9	7.5	7.0	7.5	7.2	7.5	7.1	7.2	7.1	7.5															
RED RD(2.0C)					5.1																													
4311711	2.090	3.133	C	2015	0226	CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.7	8.5														
GENERAL ASPHALT CO., INC.				(2016)	FC125	RIDE	7.1	7.1	7.1	7.9	7.6	7.7	7.7	7.3	7.6	7.7	7.7	7.5	7.6	7.1														
87008000	2.045	3.114	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	7.0	7.0															
916			2	45	29000	RIDE	8.7	8.1	8.7	8.4	7.4	7.2	7.1	7.3	7.4	7.4	7.0	7.1	7.5															
RED RD(2.0C)					5.1																													
4311711	2.090	3.133	C	2015	0226	CRACKING	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	10.0	8.5														
GENERAL ASPHALT CO., INC.				(2016)	FC125	RIDE	7.2	7.1	7.1	7.8	7.6	7.6	7.7	7.6	7.7	7.7	7.4	7.3	7.3	6.8														
87015000	2.051	3.032	R	1	1	CRACKING	10.0	10.0	10.0	10.0	7.0	8.0	7.0	6.5	3.5*	3.5*	10.0	10.0	10.0															
989			2	35	38000	RIDE	7.4	7.4	7.5	6.9	6.4	6.3	6.5	5.9	6.2	5.9	7.7	7.5	7.5															
TRN LN TO OLD CUTLER(2.1R)					2.0																													
4146211	2.051	3.032	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.1	6.0*														
GENERAL ASPHALT CO., INC.				(2010)	FC5	RIDE	7.2	7.2	6.8	7.2	7.0	7.0	6.7	6.8	6.2	6.1	6.0	6.2	6.0	5.8														
87015000	2.051	3.032	L	1	1	CRACKING	10.0	10.0	10.0	7.5	8.0	8.0	6.5	6.5	5.5*	3.5*	10.0	10.0	10.0															
989			2	35	38000	RIDE	7.1	6.8	6.7	6.4	6.2	6.3	5.7	5.9	5.2*	5.8	7.7	7.5	7.5															
SW 220 ST/OLD CUTLER(2.2L)					2.0																													
4146211	2.051	3.032	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.0														
GENERAL ASPHALT CO., INC.				(2010)	FC5	RIDE	7.2	7.2	6.8	7.2	7.0	7.0	6.7	6.8	6.2	6.1	6.0	6.2	5.9	5.7														
87016000	0.000	0.814	C	1	1	CRACKING	10.0	9.5	9.0	9.0	9.0	8.0	9.0	8.0	7.0	6.5	7.0	7.0	7.0															
112			4	30	38000	RIDE	5.4*	5.5*	5.9	5.5	5.0*	4.3*	4.1*	4.0*	4.1*	4.0*	4.1*	4.1*	3.8*															
ALTON RD(0.0C)					4.2																													
4198241	0.000	0.677	C	2012	0012	CRACKING	7.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	8.0	8.4	7.0														
GENERAL ASPHALT CO., INC.				(2014)	DGFC	RIDE	3.7*	6.5	5.7	4.3*							4.1*	4.4*	4.6*	4.1*														
87020000	11.380	14.123	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0															
5 1			3	45	42000	RIDE	8.7	8.7	8.5	8.4	8.1	7.9	7.9	8.1	8.1	8.0	8.0	7.9	7.7															
AUBURN AVE(11.4R)					6.3																													
4291881	12.014	14.123	C	2014	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5														
GENERAL ASPHALT CO., INC.				(2016)	FC95A	RIDE	7.7	7.6	7.3	8.4	8.4	8.2	8.1	8.1	8.2	8.1	8.0	8.0	7.9	7.4														
87020000	14.123	15.240	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	6.5	6.5	6.5	6.5															
5 1			3	45	29000	RIDE	8.7	8.7	8.7	8.5	8.2	8.1	8.1	8.2	8.3	8.2	8.1	8.0	7.5															
SW 183 ST(14.1R)					5.5																													
4284872	14.139	15.151	C	2018	0012	CRACKING	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.5														
GENERAL ASPHALT CO., INC.				(2020)	FC2	RIDE	7.0	7.1	7.0	7.5	7.1	7.1	7.4	7.4	7.5	7.5	7.2	7.2	7.6	7.4														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / %T / SURF_TYPE / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87020000	17.386	19.709	R	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	6.5	6.5	6.5	6.5	6.5															
5 1			3	45	68000	RIDE	8.6	8.6	8.6	8.4	7.9	7.8	7.7	7.8	7.9	7.8	7.7	7.6	7.5															
HOWARD DR(17.4C)					3.6																													
4255131	17.386	19.550	C	2012	0012	CRACKING	6.5	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5														
GENERAL ASPHALT CO., INC.			(2015)		FC125	RIDE	7.3	7.2	8.4	8.3	8.1	8.1	8.1	8.1	8.1	8.1	8.0	8.0	7.9	7.4														
87020000	17.386	19.709	L	1	1	CRACKING	9.0	8.5	8.5	7.5	7.0	7.0	7.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*															
5 1			3	45	68000	RIDE	8.7	8.6	8.3	8.3	7.8	7.7	7.6	7.6	7.7	7.6	7.5	7.3	7.0															
HOWARD DR(17.4C)					3.6																													
4255131	17.386	19.550	C	2012	0012	CRACKING	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0														
GENERAL ASPHALT CO., INC.			(2015)		FC125	RIDE	6.9	6.6	8.2	8.3	8.1	8.0	7.8	8.0	7.9	7.9	7.9	7.9	7.8	7.3														
87020000	11.380	14.123	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	7.0	7.0	7.0	7.0	6.5	6.5															
5 1			3	45	42000	RIDE	8.6	8.5	8.5	8.2	7.7	7.7	7.5	7.6	7.7	7.6	7.4	7.4	7.3															
SW 117 AVE(11.7L)					6.3																													
4291881	12.014	14.123	C	2014	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9	7.5														
GENERAL ASPHALT CO., INC.			(2016)		FC95A	RIDE	7.4	7.1	7.0	8.3	8.2	8.1	7.7	8.0	8.0	7.8	8.0	7.8	7.4	6.9														
87026000	0.000	2.829	R	1	1	CRACKING	7.5	7.5	7.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0															
860			3	45	32000	RIDE	6.4*	6.5	6.1*		7.0	6.8	6.5	6.3	5.5	5.4*	5.3*	5.2*	5.0*															
RED RD(0.0C)					4.0																													
4275182	1.185	2.829	C	2021	0012	CRACKING	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	9.6	9.0														
GENERAL ASPHALT CO., INC.			(2023)		FC95M	RIDE	5.1*	4.8*	5.2*	4.6*	4.5*	4.5*	4.3*	4.2*	4.1*	4.1*	6.6	6.4	6.3	5.8														
87026000	0.000	2.829	L	1	1	CRACKING	9.0	9.0	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
860			3	45	32000	RIDE	5.6*	5.6*	5.0*		6.9	6.9	6.6	6.5	6.7	6.7	6.8	6.7	6.6															
RED RD(0.0C)					4.0																													
4275182	1.185	2.829	C	2021	0012	CRACKING	10.0	10.0	9.0	8.5	8.5	7.5	7.0	6.5	6.5	6.5	10.0	10.0	9.6	9.0														
GENERAL ASPHALT CO., INC.			(2023)		FC95M	RIDE	6.5	6.6	6.5	6.0	6.1	6.0	5.9	5.8	5.6	5.5	7.7	7.6	7.5	7.0														
87027000	1.183	2.491	R	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	8.0	6.5	6.5	4.5*	10.0	10.0	10.0															
969			3	45	28000	RIDE	6.8	6.5	7.6	7.3	7.0	6.8	6.2	6.7	6.7	6.6	7.6	7.5	7.1															
MILITARY RD R(1.9R)					8.6																													
4146221	1.225	2.361	C	2008	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.1	5.0*														
GENERAL ASPHALT CO., INC.			(2010)		FC5	RIDE	7.4	7.2	7.4	7.2	7.3	6.9	7.4	7.2	7.0	7.3	6.9	6.9	7.1	6.9														
4525681	1.212	2.491	C	2029	0012																													
87027000	2.491	5.406	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.5	7.0	7.0	7.0	7.0															
969			3	45	36000	RIDE	7.8	7.1	6.9	6.7	6.7	6.5	6.0	5.8	6.2	6.3	6.3	6.2	5.7															
NW 30 ST(2.7R)					11.0																													
4293451	2.491	4.303	C	2016	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.1	8.0														
GENERAL ASPHALT CO., INC.			(2018)		FC95M	RIDE	5.7	5.9	5.9	6.8	6.8	7.8	7.7	7.7	7.6	7.5	7.5	7.3	7.4	6.9														
87027000	2.491	5.406	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.0	7.0	7.0	7.0	7.0															
969			3	45	36000	RIDE	7.7	7.8	7.5	7.2	6.7	6.1*	6.7	6.7	6.8	6.6	6.6	6.3	6.2															
NW 31 ST(2.8L)					11.0																													
4293451	2.491	4.303	C	2016	0012	CRACKING	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.3	8.0														
GENERAL ASPHALT CO., INC.			(2018)		FC95M	RIDE	6.6	6.4	6.3	6.9	6.9	7.6	7.4	7.4	7.3	7.4	7.2	7.1	7.1	6.6														
87027000	1.183	2.491	L	1	1	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	8.0	6.5	6.5	6.5	10.0	10.0	10.0															
969			3	45	28000	RIDE	7.8	7.6	7.3	6.8	6.5	6.4*	5.8	6.0	6.5	6.4	7.7	7.3	7.5															
TRN LN TO NW 12 ST(1.2L)					8.6																													
4146221	1.225	2.361	C	2008	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	8.3	6.0*														
GENERAL ASPHALT CO., INC.			(2010)		FC5	RIDE	7.4	7.3	7.4	7.5	7.1	7.3	7.4	7.4	7.2	7.4	7.1	7.4	7.4	7.2														
4525681	1.212	2.491	C	2029	0012																													
87030000	0.840	1.650	R	1	1	CRACKING	9.0	9.0	9.0	9.0	8.0	8.0	8.0	7.5	6.5	6.5	6.5	6.5	6.5															
5 1			3	45	50000	RIDE	7.8	8.0	8.0	7.8	7.2	7.2	7.0	7.2	7.2	7.2	7.1	7.1	6.9															
SW 68 CT(1.1R)					2.7																													
4274191	0.840	1.442	C	2012	0012	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.6	8.5														
GENERAL ASPHALT CO., INC.			(2015)		DGFC	RIDE	6.8	6.2	8.3	8.0	8.0	7.8	8.0	7.9	7.9	8.0	8.0	7.8	7.5	7.0														
87030000	1.650	4.347	R	1	7	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	8.0															
5 1			3	40	75000	RIDE	6.8	6.5	6.5	8.1	7.6	7.6	7.6	7.6	7.8	7.7	7.3	7.5	7.5															
SW 63 AVE(1.9R)					3.8																													
4439161	1.651	4.387	R	2022	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	10.0	9.5														
GENERAL ASPHALT CO., INC.			(2025)		FC125	RIDE	7.4	7.5	7.3	7.6	7.7	7.6	7.7	7.6	7.7	7.7	7.6	7.7	7.9	7.4														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87030000  19.267 21.350  R    1      1 CRACKING 10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.5   9.5   8.0   8.0   7.5   7.5
5    1                   3   35  46500 RIDE      7.4   7.3   7.3   7.0   6.5   6.7   5.8   6.3   5.9   6.4   5.8   5.4*  6.2
MIAMI BLVD N(19.3C)                  5.7
4291901   19.553 21.225  C 2014   0012 CRACKING  7.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.2   8.0
GENERAL ASPHALT CO., INC. (2017) FC95M RIDE      6.0   5.8   5.6   6.4   8.0   7.9   7.8   7.4   7.4   7.1   7.1   6.9   7.1   6.6
-----------------------------------------------------------------------------------------------------------------------------------
87030000  19.370 21.350  L    1      2 CRACKING 10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.5   8.0   8.0   8.0   7.5   7.5
5    1                   3   35  46500 RIDE      7.8   8.4   7.7   7.2   6.8   6.6   6.3   6.1   6.4   6.2   6.2   6.3   6.3
NE 124 ST(19.4L)                     5.7
4291901   19.553 21.225  C 2014   0012 CRACKING  7.5   7.5   7.5   7.5  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.1   8.0
GENERAL ASPHALT CO., INC. (2017) FC95M RIDE      6.0   6.0   5.9   6.1   7.0   7.2   7.2   6.8   6.6   7.7   6.6   6.3   5.8   5.3*

87030000   1.650  4.376  L    1      7 CRACKING  6.0*  6.0*  6.0* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
5    1                   3   45  75000 RIDE      7.5   7.4   7.5   8.0   7.4   7.4   7.3   7.4   7.5   7.3   7.5   7.5   7.3
SW 62 AV/PAUL TEVIS( 2.1C)           3.8
4439161    1.651  4.387  L 2022   0012 CRACKING 10.0   9.5   9.5   9.5   9.0   9.0   9.0   9.0   7.5   6.5   6.5   6.5  10.0   9.5
GENERAL ASPHALT CO., INC. (2025) FC125 RIDE      7.4   7.4   7.2   7.5   7.5   7.4   7.4   7.3   7.3   7.4   7.1   7.0   8.0   7.5

87030000   0.840  1.650  L    1      1 CRACKING  7.5   7.0   7.0   7.0   7.0   7.0   7.0   6.5   6.5   4.5*  4.5*  4.5*  4.5*
5    1                   3   45  50000 RIDE      8.0   8.1   7.9   7.9   7.3   7.2   7.2   7.3   7.4   7.3   7.2   7.1   6.9
KENDALL DR( 0.8L)                    2.7
4274191    0.840  1.442  C 2012   0012 CRACKING  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   7.5
GENERAL ASPHALT CO., INC. (2015) DGFC  RIDE      6.9   6.9   8.3   8.2   8.0   7.7   7.9   8.0   7.9   7.8   7.5   7.6   7.4   6.9
-----------------------------------------------------------------------------------------------------------------------------------
87044000   8.098  8.466  C    1      1 CRACKING  6.5   7.5   9.5   5.5*  9.0   5.5*  7.5   6.5   6.5   9.0   9.0   9.0   9.0
976                      2   35  39500 RIDE      7.8   7.1   5.9   7.4   5.7   5.2*  6.2   5.9   5.3*  5.1*  5.1*  4.7*  4.9*
SW 38 AVE( 8.1C)                     6.4
4284792    8.100  8.432  C 2018   0015 CRACKING  9.0   9.5   9.0   9.0   9.0   9.0   9.0  10.0  10.0  10.0  10.0  10.0   8.8   8.0
GENERAL ASPHALT CO., INC. (2020) FC125 RIDE      4.8*  5.3*  5.1*  3.7*  4.1*                      6.1   5.3*  5.1*  5.1*  5.3*  4.8*
-----------------------------------------------------------------------------------------------------------------------------------
87052000   0.132  1.999  R    1      1 CRACKING  6.0*  6.0*  6.0*  5.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
924                      3   40  35500 RIDE      7.1   7.0   7.3   7.1   7.9   7.4   7.2   7.3   7.6   7.3   7.4   7.3   7.4
NW 24 AVE( 0.3C)                     9.3
4399811    0.395  1.999  C 2022   0012 CRACKING 10.0  10.0  10.0   8.5   7.0   7.0   7.0   7.0   7.0   7.0         10.0  10.0   9.5
GENERAL ASPHALT CO., INC. (2024) FC95M RIDE      7.1   7.2   7.3   7.5   7.4   7.3   7.3   7.0   7.1   7.1          8.2   8.1   7.6
-----------------------------------------------------------------------------------------------------------------------------------
87052000   0.000  1.999  L    1      1 CRACKING  7.0   7.0   7.0   5.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0
924                      3   40  35500 RIDE      6.6   6.6   6.6   6.5   7.7   7.5   7.0   7.0   6.8   6.7   6.9   6.9   6.8
NW 27 AVE( 0.0C)                     9.3
4399811    0.395  1.999  C 2022   0012 CRACKING  9.0   9.0   9.0   8.5   7.0   7.0   7.0   7.0   7.0   7.0         10.0  10.0   9.5
GENERAL ASPHALT CO., INC. (2024) FC95M RIDE      6.9   6.7   6.8   7.1   7.1   6.6   6.8   6.8   6.8   6.6          8.0   7.9   7.4
-----------------------------------------------------------------------------------------------------------------------------------
87053000   1.183  1.572  R    1      6 CRACKING 10.0  10.0  10.0   9.5   9.5   9.5   9.5   7.0   6.5   6.5   6.5   6.5   6.5
968                      3   40  49000 RIDE      7.4   7.7   7.4   7.2   7.5   7.1   7.1   7.1   7.5   7.3   7.4   7.2   6.5
FLORIDA BLVD( 1.3R)                  5.1
4291941    1.183  1.498  C 2017   0012 CRACKING  6.5   6.5   6.5   6.5   6.5         10.0  10.0  10.0  10.0  10.0  10.0   8.8   8.0
GENERAL ASPHALT CO., INC. (2019) DGFC  RIDE      6.1   6.9   6.2   6.9   6.3

87053000   1.572  1.774  R    1      6 CRACKING  9.5   9.5   8.0   9.5   9.5   9.5   9.5   9.5   9.5  10.0  10.0  10.0  10.0
968                      2   40  45500 RIDE      5.9*  6.0*  5.7   5.6   6.6   5.5   5.3*  4.8*  5.5   7.2   7.1   6.3
SW 71 AVE( 1.6R)                     4.3
4146291    1.577  1.782  C 2008   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.0   8.0   7.7   6.0*
GENERAL ASPHALT CO., INC. (2009) DGFC  RIDE

87053000   1.774  5.900  R    1      1 CRACKING  9.5   9.5   8.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   7.0   7.0
968                      2   40  38000 RIDE      5.9*  6.0*  5.7   7.1   6.7   7.0   6.8   6.9   6.8   6.9   6.6   6.3   6.3
CR 962( 1.8C)                        2.8
4252713    1.774  4.534  C 2017   0012 CRACKING  7.0   7.0   7.0   7.0   7.0   7.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.0
GENERAL ASPHALT CO., INC. (2019) FC95M RIDE      6.2   6.2   5.9   6.3   5.9   6.4   6.9   6.7   6.6   6.7   6.6   6.5   6.5   6.0
-----------------------------------------------------------------------------------------------------------------------------------
87053000   1.774  5.900  L    1      1 CRACKING  7.0   7.0   7.0  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   7.0   7.0
968                      2   40  38000 RIDE      4.9*  5.3*  4.9*  7.1   6.7   6.5   6.2   6.2   6.2   6.4   5.9   5.5   5.6
CR 962( 1.8C)                        2.8
4252713    1.774  4.534  C 2017   0012 CRACKING  7.0   7.0   7.0   7.0   7.0   7.0  10.0  10.0   9.0   9.0   9.0   9.0   8.8   8.0
GENERAL ASPHALT CO., INC. (2019) FC95M RIDE      5.5   5.6   5.6   5.6   5.6   5.6   6.6   6.7   6.6   6.7   6.4   6.3   6.2   5.7
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87053000   1.572  1.774  L    1      6 CRACKING 10.0  10.0   7.0   7.0   7.0   7.0   7.0   6.5   6.5  10.0  10.0  10.0  10.0
968                     2   40  45500 RIDE      7.6   7.3   4.9*  4.2*  4.7*  5.0*  4.3*  5.2*  5.3*  6.7   7.1   6.9
SHOPPING CENTER ENT( 1.6L)            4.3
4146291    1.577  1.782  C 2008   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   7.5   7.5   7.8   6.0*
GENERAL ASPHALT CO., INC. (2009) DGFC  RIDE

87053000   1.183  1.572  L    1      6 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   8.0   7.0   7.0   7.0   7.0
968                     3   40  49000 RIDE      7.6   7.3   7.6   7.4   7.1   6.7   6.5   6.8   6.2   6.2   6.7   5.6   6.2
NW 75 AVE( 1.2L)                      5.1
4291941    1.183  1.498  C 2017   0012 CRACKING  7.0   7.0   7.0   7.0   7.0         10.0  10.0  10.0  10.0  10.0  10.0   8.8   8.0
GENERAL ASPHALT CO., INC. (2019) DGFC  RIDE      6.6   5.9   5.7   6.0   5.8
-------------------------------------------------------------------------------------------------------------------------------------
87054000   3.019  4.190  R    1      1 CRACKING  8.0   8.0   8.0   7.0   7.0   7.0   6.5   6.5   6.5   4.5*  4.5* 10.0  10.0
972                     2   40  23000 RIDE      7.9   7.8   7.7   7.4   6.6   6.5   6.2   6.2   6.3   6.2   6.0   7.9   7.8
MISSING DESCRIPTION I( 3.0R)          9.4
4124751    2.943  4.591  C 2008   0012 CRACKING 10.0  10.0  10.0   8.5   8.5   8.5   8.5   8.5   8.5   8.5   8.5   8.5   9.0   7.5
GENERAL ASPHALT CO., INC. (2011) FC95  RIDE      7.7   7.5   7.7   7.2   7.0   6.8   6.8   6.8   6.6   6.7   6.4   6.3   6.3   5.8
4459981    2.953  4.672  C 2025   0012

87054000   4.190  4.672  C    1      6 CRACKING  8.0   7.0   7.0   7.0   7.0   7.0   7.0   6.5   6.5   4.5*  4.5* 10.0  10.0
972                     4   35  17700 RIDE      7.2   4.5*  4.4*  4.3*  2.8*  3.7*  3.6*  3.7*  4.5*  3.9*  3.6*  7.4   7.2
SW 15 RD/BROADWAY( 4.2C)              8.2
4124751    2.943  4.591  C 2008   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.0   8.0   8.2   6.5
GENERAL ASPHALT CO., INC. (2011) DGFC  RIDE      6.8   6.2   6.4   5.8   5.3*  5.2*  5.0*
4459981    2.953  4.672  C 2025   0012
-------------------------------------------------------------------------------------------------------------------------------------
87055000   1.689  3.978  R    1      1 CRACKING 10.0  10.0   9.0   9.0   9.0   7.5   7.5   7.5   6.5   6.5   6.5   6.5   6.5
986                     2   40  36500 RIDE      7.5   7.2   7.5   7.3   7.1   6.5   6.0   6.4   5.9   6.0   6.1   5.9   5.9
SW 109 PL( 1.7C)                      4.0
4276511    1.697  4.018  R 2013   0012 CRACKING  6.5   6.5  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.0   8.0   8.0   8.7   7.5
GENERAL ASPHALT CO., INC. (2015) FC125 RIDE      5.7   5.6   6.3   6.5   6.9   7.0   7.0   7.0   6.9   6.8   6.9   6.9   6.9   6.4

87055000   3.978  5.800  R    1      1 CRACKING 10.0  10.0   9.0   9.0   9.0   7.5   7.5   7.5   6.5   6.5   6.5   6.5   6.5
986                     2   40  41000 RIDE      7.5   7.2   7.5   7.3   7.1   7.2   6.6   7.1   7.3   7.0   7.0   7.0   7.2
SR 973( 4.0C)                         2.3
4226141    4.179  5.812  C 2011   0012 CRACKING  6.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.3   8.0
GENERAL ASPHALT CO., INC. (2014) FC95  RIDE      7.1   8.3   7.9   7.5   7.4   7.9   7.9   7.8   7.8   7.8   7.7   7.7   7.7   7.2
-------------------------------------------------------------------------------------------------------------------------------------
87055000   3.978  5.800  L    1      1 CRACKING 10.0  10.0  10.0   9.5   9.5   6.5   6.5   6.5   6.5   6.5   6.5   5.5*  5.5*
986                     2   40  41000 RIDE      7.3   6.9   7.2   7.3   6.5   6.6   6.0   6.4   6.4   6.0   6.2   6.2   6.0
SR 973( 4.0C)                         2.3
4226141    4.179  5.812  C 2011   0012 CRACKING  5.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.1   7.5
GENERAL ASPHALT CO., INC. (2014) FC95  RIDE      6.0   8.0   7.3   7.3   7.3   7.4   7.4   7.3   7.2   7.3   7.3   7.3   7.3   6.8

87055000   1.689  3.978  L    1      1 CRACKING  9.5   9.5   9.5   9.5   9.5   7.5   7.5   7.5   6.5   3.5*  3.5*  3.5*  3.5*
986                     2   40  36500 RIDE      7.5   7.5   7.4   7.2   6.6   6.6   6.3   6.4   6.1   6.2   6.1   6.0   5.6
SW 109 PL( 1.7C)                      4.0
4276511    1.697  3.838  L 2013   0012 CRACKING  3.5*  3.5* 10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   8.8   7.5
GENERAL ASPHALT CO., INC. (2015) FC125 RIDE      5.7   5.6   7.2   6.7   6.9   6.9   6.8   6.9   6.7   6.6   6.8   6.6   6.5   6.0
-------------------------------------------------------------------------------------------------------------------------------------
87060000   4.814  5.490  C    1      1 CRACKING  7.5   7.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5
A1A                     4   30  21000 RIDE      5.5*  4.5*        5.8   5.1*  5.7   4.2*  3.9*  5.3*  5.5   5.2*  5.5   4.8*
17 ST( 4.9C)                         25.2
4255041    4.814  5.649  C 2012   0012 CRACKING  9.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   8.5   7.0
GENERAL ASPHALT CO., INC. (2014) FC95  RIDE      4.5*  7.3   6.7   6.1   6.1   5.3*  5.6   5.2*  5.5   5.6   5.4*  5.6   5.5   5.0*

87060000   5.490  5.750  C    1      8 CRACKING 10.0  10.0  10.0        10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5
A1A                     4   30  21000 RIDE      6.5   6.1*  5.9         6.3   5.8   5.8   5.6   5.0*  5.0*  4.9*  4.6*  4.4*
25 ST( 5.6R)                         25.2
4255041    4.814  5.649  C 2012   0012 CRACKING  9.5  10.0  10.0  10.0  10.0
GENERAL ASPHALT CO., INC. (2014) FC95  RIDE      4.5*  7.3   6.7   6.1   6.1

87060000   8.658  9.775  C    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   7.5   7.5   7.5   6.5  10.0
A1A                     3   30  14500 RIDE      7.1   6.7   7.0   6.7   5.8   5.5   5.0*  4.6*  5.1*  5.5   5.3*  5.2*  7.4
65 ST( 8.9L)                         10.9
4245791    8.658  9.579  R 2010   0012 CRACKING 10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.5   8.5   6.5   6.5   6.5   6.5   5.0*
GENERAL ASPHALT CO., INC. (2012) FC95  RIDE      7.0   6.1   6.1   6.4   5.8   6.1   5.8   5.6   5.2*  4.6*  5.1*  5.0*  4.9*  4.4*
4499441    8.640  9.782  C 2027   0012
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87060000  14.047 16.052  R    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   8.5   7.0   6.5   6.5   6.5   6.5   6.5
A1A                     3   30  58000 RIDE      8.3   8.0   7.5   6.6   6.1   6.8   6.4   6.3   6.3   6.0   6.0   5.8   5.6
SUNNY ISLES/SR 826(14.6R)          10.9
4309491   14.046 16.052  R 2017   0012 CRACKING  6.5   6.5   6.5   6.5   6.5   6.5   5.5* 10.0  10.0  10.0  10.0  10.0   8.9   8.0
GENERAL ASPHALT CO., INC. (2020) FC95M RIDE      5.3*  5.7   5.7   5.6   5.2*  4.2*  4.0*  7.0   7.0   6.9   6.7   6.5   6.5   6.0
-----------------------------------------------------------------------------------------------------------------------------------
87060000  14.047 16.191  L    1      1 CRACKING 10.0  10.0  10.0   9.0   9.0   9.0   9.0   6.5   6.5   4.5*  6.5   6.5   6.5
A1A                     3   35  58000 RIDE      8.3   8.2   7.5   7.2   7.5   7.6   7.4   7.4   7.5   7.4   7.3   7.2   7.1
BAYVIEW DR/158 ST(14.1L)           10.9
4309491   14.046 16.275  L 2017   0012 CRACKING  6.5   6.5   6.5   6.5   6.5   6.5   5.5* 10.0  10.0  10.0   9.5   9.5   9.6   8.5
GENERAL ASPHALT CO., INC. (2020) FC95M RIDE      6.9   6.9   6.9   6.8   6.4   5.5   5.4*  7.6   7.4   7.4   7.1   7.1   6.9   6.4
-----------------------------------------------------------------------------------------------------------------------------------
87066000   1.650  2.926  R    1      1 CRACKING 10.0   9.5   9.5   9.5   9.5   9.5         7.5   6.5   6.5   6.5   6.5   6.5
922                     2   35  30000 RIDE      6.9   6.7   6.7   6.2   5.5   5.7         5.5   4.7*  4.8*  4.7*  5.1*  5.1*
NE 7 CT( 1.7R)                      5.8
4291371    1.650  2.926  C 2015   0012 CRACKING  4.5*  4.5*  3.5*  3.5* 10.0  10.0  10.0  10.0   9.5   9.5   8.5   8.5   8.4   7.0
GENERAL ASPHALT CO., INC. (2017) FC95A RIDE      4.7*  4.8*  4.8*  4.6*  7.0   7.1   7.2   6.8   6.5   6.0   6.0   5.5   5.7   5.2*
-----------------------------------------------------------------------------------------------------------------------------------
87066000   1.650  2.926  L    1      1 CRACKING 10.0  10.0   9.5   9.5   9.5   9.5         6.5   6.5   6.5   6.5   6.5   6.5
922                     2   35  30000 RIDE      6.5   6.7   6.7   6.2   5.7   6.0         5.5   5.4*  5.2*  5.1*  5.1*  5.1*
NE 8 AVE( 1.8C)                     5.8
4291371    1.650  2.926  C 2015   0012 CRACKING  4.5*  4.5*  3.5*  3.5* 10.0  10.0  10.0  10.0   9.0   9.0   8.5   8.5   8.5   7.5
GENERAL ASPHALT CO., INC. (2017) FC95A RIDE      4.7*  4.8*  4.8*  4.6*  7.0   7.1   7.2   6.8   6.6   6.4   5.9   5.6   5.5   5.0*
-----------------------------------------------------------------------------------------------------------------------------------
87070000   8.151 10.733  R    1      1 CRACKING  9.5   9.5   8.0   8.0   8.0   8.0   8.0   7.0   7.0   6.0*  6.0*  6.0*  6.0*
997                     2   55  20300 RIDE      7.8   7.7   7.7   7.5   7.1   7.1   6.3*  7.1   7.1   7.1   7.2   6.7   6.5
SIDE ROAD(10.2C)                   20.8
2496158    8.151 10.935  C 2015   0213 CRACKING  6.0* 10.0  10.0  10.0        10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.1   7.5
GENERAL ASPHALT CO., INC. (2018) FC5M  RIDE      6.5   8.8   8.2   8.2         8.4   8.4   8.4   8.4   8.4   8.4   8.4   8.4   8.2
-----------------------------------------------------------------------------------------------------------------------------------
87070000   8.151 10.733  L    1      1 CRACKING  9.5   9.5   8.0   8.0   8.0   8.0   8.0   7.0   7.0   6.0*  6.0*  6.0*  6.0*
997                     2   55  20300 RIDE      7.8   7.7   7.7   7.5   7.1   7.1   6.3*  7.1   7.1   7.1   7.2   6.7   6.5
SIDE ROAD(10.2C)                   20.8
2496158    8.151 10.935  C 2015   0213 CRACKING  6.0* 10.0  10.0  10.0        10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.2   7.5
GENERAL ASPHALT CO., INC. (2018) FC5M  RIDE      6.5   8.8   8.2   8.2         8.4   8.4   8.4   8.4   8.4   8.4   8.3   8.3   8.1
-----------------------------------------------------------------------------------------------------------------------------------
87072000   0.000  0.736  R    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   7.5   6.5   4.5*  4.5*  4.5*  4.5*  3.5*
985                     4   35  25000 RIDE      7.1   6.8   7.1   6.9   5.7   6.3   5.7   6.2   6.4   6.2   6.3   6.4   6.1
KILLIAN PKWY( 0.0C)                 2.2
4259131    0.163  0.940  C 2013   0012 CRACKING  3.5*  3.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.8   7.5
GENERAL ASPHALT CO., INC. (2015) DGFC  RIDE      6.1   6.1   7.9   7.7   7.5   7.4   7.1   7.4   7.3   7.0   7.2   6.9   6.9   6.4
-----------------------------------------------------------------------------------------------------------------------------------
87072000   0.000  0.736  L    1      1 CRACKING 10.0  10.0  10.0  10.0   9.0   9.0   7.5   4.5*  4.5*  4.5*  4.5*  4.5*  3.5*
985                     3   35  25000 RIDE      6.3*  7.0   6.9   6.1   5.7   4.9*  5.1*  5.8   5.6   5.8   6.3   6.4   6.1
KILLIAN PKWY( 0.0C)                 2.2
4259131    0.163  0.940  C 2013   0012 CRACKING  3.5*  3.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
GENERAL ASPHALT CO., INC. (2015) DGFC  RIDE      6.1   6.1   7.9   7.7   7.5   7.4   7.1   7.4   7.3   7.0   7.2   6.9   6.9   6.4
-----------------------------------------------------------------------------------------------------------------------------------
87080001   0.000  0.761  C    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   8.0   7.0   7.0   7.0   7.0
934                     2   35  18000 RIDE      7.8   7.6   7.6   7.3   6.3   6.5   6.3   6.6   6.6   6.9   6.3   6.3   5.9
SR 934( 0.0L)                       9.7
4106463    0.000  0.680  C 2011   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.2   7.5
GENERAL ASPHALT CO., INC. (2013) FC95  RIDE      8.3   8.1   7.4   7.5   7.1   7.0   7.0   6.8   6.7   6.4   6.5   6.8   6.6   6.1
-----------------------------------------------------------------------------------------------------------------------------------
87080900  36.311 37.987  R    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.5   8.0   7.0   6.5   6.5   6.5   6.5
934                     3   40  35500 RIDE      7.8   7.5   7.6   7.4   7.1   7.1   7.0   7.0   7.1   7.1   6.9   7.2   7.2
SR 9(36.4C)                         8.9
4291471   36.330 37.754  C 2014   0012 CRACKING  6.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0   9.5   9.0   8.0   8.0   9.1   8.0
GENERAL ASPHALT CO., INC. (2017) FC95A RIDE      7.1   6.8   6.9   7.2   8.2   8.2   8.1   8.1   8.1   8.0   7.9   7.9   7.8   7.3
-----------------------------------------------------------------------------------------------------------------------------------
87080900  36.311 37.987  L    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.5   8.0   7.0   7.0   7.0   7.0   6.5
934                     3   40  35500 RIDE      8.1   8.1   8.0   7.7   7.2   7.2   7.2   7.2   7.4   7.4   7.3   7.1   6.9
SR 9(36.4C)                         8.9
4291471   36.330 37.754  C 2014   0012 CRACKING  6.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   8.0
GENERAL ASPHALT CO., INC. (2017) FC95A RIDE      7.0   6.8   6.7   6.7   7.9   8.1   8.0   7.9   7.9   8.0   7.9   7.7   7.1   6.6
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87090000  17.514 18.527  C    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5   7.0   6.5   6.5   6.5   6.5
25   27                 2   35  19900 RIDE      7.3   7.8   7.8   7.5   7.0   6.7   6.4   6.2   6.1   5.7   6.1   6.0   5.5
NW 17 AVE(17.5C)                  3.8
4291591   17.594 18.527  C 2013   0012 CRACKING  6.5   6.5        10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   8.4   7.0
GENERAL ASPHALT CO., INC. (2016) FC95  RIDE      5.2*  5.9         7.7   7.4   7.2   7.3   7.0   6.8   6.8   6.2   6.3   6.2   5.7
-----------------------------------------------------------------------------------------------------------------------------------
87091000   0.000  4.075  C    1      7 CRACKING       10.0  10.0   9.5   9.5   9.5   9.5   9.5   9.5   9.5   9.5   9.5   9.0
994                    2   45  10400 RIDE           8.4   8.2   8.1   7.5   7.2   7.3   7.5   7.3   7.3   7.3   7.2   7.0
KROME AVE( 0.0C)                 12.7
4439071    0.175  2.460  C 2023   0012 CRACKING  9.0   9.0   9.0   9.0   9.0   8.5   8.5   8.5   7.5         7.0   7.0  10.0   9.5
GENERAL ASPHALT CO., INC. (2025) FC125 RIDE      7.0   6.8   7.0   7.2   7.2   7.3   7.3   7.3   7.3         7.2   7.1   7.3   6.8
-----------------------------------------------------------------------------------------------------------------------------------
87150000  13.799 17.492  R    1      4 CRACKING 10.0   8.5   8.5   7.5  10.0   7.0   6.0*  6.0*  6.0*  4.0*  3.5*  3.5*  3.5*
997                    2   50  34000 RIDE      7.7   7.3   7.5   7.2   6.6   6.5   6.7   6.7   6.6   6.4*  6.0*  6.5   6.3*
HOWARD DR(13.9R)                 11.2
2496147   13.789 17.310  C 2016   0213 CRACKING  3.5*  3.5* 10.0  10.0  10.0               9.4   9.9   9.4   9.5   9.4   9.4   9.0
GENERAL ASPHALT CO., INC. (2020) LGD   RIDE      6.1*  6.0*  8.8   8.4   8.3               8.5   8.5   8.5   8.5   8.5   8.5   8.3
-----------------------------------------------------------------------------------------------------------------------------------
87150000  13.799 17.492  L    1      4 CRACKING 10.0   8.5   8.5   7.5  10.0   7.0   6.0*  6.0*  6.0*  4.0*  3.5*  3.5*  3.5*
997                    2   50  34000 RIDE      7.7   7.3   7.5   7.2   6.6   6.5   6.7   6.7   6.6   6.4*  6.0*  6.5   6.3*
HOWARD DR(13.9L)                 11.2
2496147   13.789 17.310  C 2016   0213 CRACKING  3.5*  3.5* 10.0  10.0  10.0               9.4  10.0   9.4   9.4   9.4   9.4   9.0
GENERAL ASPHALT CO., INC. (2020) LGD   RIDE      6.1*  6.0*  8.8   8.4   8.3               8.3   8.4   8.3   8.3   8.3   8.2   8.0
-----------------------------------------------------------------------------------------------------------------------------------
87160000   0.000  5.068  C    1      1 CRACKING  3.5*  1.0*  0.0*  0.0*  0.0* 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0
9336                   2   45   2300 RIDE      7.5   7.2   7.2   6.5   5.4*  7.5   7.6   7.8   7.8   7.6   7.6   7.5   7.4
DIRT RD( 1.4C)                   14.6
4056582    0.000  7.066  C 2003   0012 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   8.0   6.5   6.5   4.5*  4.5*  4.5*  4.5*  2.0*
GENERAL ASPHALT CO., INC. (2005) FC5   RIDE      7.4   7.3   7.2   7.5   7.5   7.5   7.5   7.7   7.6   7.7   7.3   7.5   7.5   7.3
4459871    0.000  5.068  C 2023   0012

87160000   5.068  6.103  C    1      1 CRACKING  3.5*  1.0*  0.0*  0.0*  0.0* 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0
9336                   2   45   2300 RIDE      7.5   7.2   7.2   6.5   5.4*  7.5   7.6   7.8   7.8   7.6   7.6   7.5   6.7
SW 372 ST( 5.3R)                 14.6
4056582    0.000  7.066  C 2003   0012 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   7.5   6.5   6.5   6.5   5.5*  3.0*
GENERAL ASPHALT CO., INC. (2005) FC5   RIDE      7.1   7.0   7.1   7.8   7.8   7.8   7.7   7.9   7.9   7.8   7.6   7.7   7.8   7.6
4459891    5.068  7.057  C 2023   0012

87160000   7.066  8.041  C    1      1 CRACKING  4.5*  4.5*  0.0*  0.0*  0.0* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
9336                   2   45  27500 RIDE      7.9   7.5   7.7   7.2   6.0*  8.0   8.1   8.1   8.1   8.1   8.0   8.0   7.9
FLORIDA CITY CITY LIMITS( 7.1L)   7.6
4106402    7.066  8.013  C 2003   0012 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.5   8.5   8.5   7.4   5.5*
GENERAL ASPHALT CO., INC. (2005) DGFC  RIDE      7.9   7.9   7.7   7.6   7.7   7.4   7.4   7.6   7.7   7.4   7.5   7.3   7.6   7.1
4459921    7.057  8.705  C 2023   0012
-----------------------------------------------------------------------------------------------------------------------------------
87240000   4.894  7.227  R    1      7 CRACKING  9.0   9.0   9.0   9.0   7.5   7.5   6.5  10.0  10.0  10.0  10.0  10.0  10.0
9                      2   35  33000 RIDE      6.6   6.6   6.4   6.3   5.9   5.7   5.7   6.9   6.6   6.7   6.8   6.7   6.5
NW 38 ST( 4.9C)                   7.7
4291852    5.019  7.184  C 2021   0012 CRACKING 10.0  10.0  10.0  10.0   8.0   8.0   7.0   7.0   7.0   7.0   7.0   6.5  10.0   9.5
GENERAL ASPHALT CO., INC. (2025) FC125 RIDE      6.4   6.3   6.3   5.9   5.8   5.9   5.6   5.6   5.6   5.7   5.5   4.8*  6.3   5.8

87240000   7.227  8.834  R    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   7.5   6.5   6.5
9                      2   40  31000 RIDE      7.9   7.9   7.8   7.4   7.2   6.9   6.8   6.6   6.7   6.7   6.8   6.7   6.6
SR 934( 7.3C)                     7.7
4291851    7.227  8.741  R 2014   0012 CRACKING  6.5   6.5   4.5*       10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.8   7.5
GENERAL ASPHALT CO., INC. (2017) FC95A RIDE      6.6   6.6   6.6         7.9   7.9   7.8   7.7   6.9   6.8   6.8   6.6   6.6   6.1

87240000   8.834  9.648  R    1      1 CRACKING 10.0  10.0  10.0   9.0   9.0   6.5   6.5   6.5   4.5*  4.5*  4.5*  4.5*  4.5*
9                      3   45  38000 RIDE      8.2   8.2   8.2   7.9   7.6   7.5   7.2   7.1   7.3   7.1   6.9   7.1   6.8
SR 932( 8.9C)                     7.7
4256591    8.873  9.687  C 2012   0226 CRACKING  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.5   8.5   7.7   6.5
GENERAL ASPHALT CO., INC. (2014) FC95  RIDE      6.7   8.1   8.0   7.9   7.9   7.7   7.8   7.7   7.7   7.6   7.6   7.5   7.6   7.1
-----------------------------------------------------------------------------------------------------------------------------------
87240000   8.834  9.648  L    1      1 CRACKING 10.0  10.0   9.0   8.0   8.0   8.0   8.0   7.5   6.5   6.5   6.5   6.5   6.5
9                      2   45  38000 RIDE      8.3   8.2   8.2   8.1   7.3   7.1   7.1   6.9   7.2   7.1   6.9   7.2   7.0
SR 932( 8.9C)                     7.7
4256591    8.873  9.687  C 2012   0226 CRACKING  6.5  10.0  10.0  10.0  10.0  10.0  10.0   9.0   8.5   8.5   8.5   8.5   8.7   7.5
GENERAL ASPHALT CO., INC. (2014) FC95  RIDE      7.0   8.1   8.0   7.7   7.8   7.7   7.8   7.6   7.5   7.4   7.4   7.3   7.0   6.5
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87240000   7.227  8.834  L    1      1 CRACKING 10.0  10.0   9.0   9.0   9.0   7.0   7.0   7.0   7.0   6.5   6.5   6.5   6.5
9                        2   40  31000 RIDE      7.6   7.7   7.6   7.7   7.1   7.1   7.1   6.8   7.0   6.9   6.9   7.2   7.0
SR 934( 7.3C)                     7.7
4291851    7.701  8.834  L 2014   0012 CRACKING  6.5   6.5   4.5*        10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   8.0
GENERAL ASPHALT CO., INC. (2017) FC95A RIDE      7.0   6.7   6.9         8.0   7.8   7.9   7.8   7.4   7.1   7.0   6.8   6.8   6.3

87240000   4.894  7.227  L    1      7 CRACKING  7.5   7.5   7.5   7.5   7.5   7.5   6.5  10.0  10.0  10.0  10.0  10.0  10.0
9                        2   35  33000 RIDE      6.2*  6.2*  5.5   5.6   5.2*  4.9*  5.3*  6.8   6.8   6.8   6.8   6.8   6.7
NW 38 ST( 4.9C)                   7.7
4291852    5.019  7.184  C 2021   0012 CRACKING 10.0  10.0   9.0   8.5   7.0   7.0   7.0   7.0   7.0   7.0   7.0   7.0  10.0   9.5
GENERAL ASPHALT CO., INC. (2025) FC125 RIDE      6.5   6.2   6.4   5.7   5.7   5.6   5.5   5.5   5.3*  5.4*  5.3*  5.2*  6.6   6.1
-----------------------------------------------------------------------------------------------------------------------------------
87250000   0.691  1.192  R    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.5   7.0   7.0   7.0   7.0   7.0
944                      2   40  27000 RIDE      7.7   7.8   7.5   7.0   6.5   6.5   6.4   6.3   6.4   6.3   6.1   6.1
SE 7 AVE( 0.8R)                   8.1
4182391    0.436  1.192  C 2010   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5   7.0   7.0   7.0   7.0   7.3   6.0*
GENERAL ASPHALT CO., INC. (2013) DGFC  RIDE      8.2   7.9   8.0   7.8   7.5   7.4   7.7   6.9   7.0   6.5   6.5   6.3   6.5   6.0
-----------------------------------------------------------------------------------------------------------------------------------
87250000   0.691  1.192  L    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.5   7.0   7.0   7.0   7.0   7.0
944                      2   40  27000 RIDE      7.6   7.5   7.2   7.0   6.3   6.3   6.2   6.1   6.2   6.1   5.7   5.8
E 7 AVE( 0.8L)                    8.1
4182391    0.436  1.192  C 2010   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.5   7.0
GENERAL ASPHALT CO., INC. (2013) DGFC  RIDE      7.8   7.2   6.9   7.8   7.4   7.6   7.5   7.3   7.4   7.1   6.7   6.7   6.7   6.2
-----------------------------------------------------------------------------------------------------------------------------------
87471000  33.142 34.689  L    5      8 CRACKING  9.5   9.5               10.0  10.0  10.0  10.0   9.5   8.0   8.0   8.0
821         33.1   34.7  3   60 109900 RIDE      8.8   8.9                7.6   7.6   7.6   7.7   7.8   7.8   7.6   7.6   7.6
                                  5.7
4311001   33.263 35.400  L 2016   0012 CRACKING  8.0   8.0   6.5   6.5         9.0   9.0   9.0   7.5
GENERAL ASPHALT CO., INC. (2018) FC2   RIDE      7.5   7.5   7.5   7.7         7.7   7.8   8.0   7.8
4355421   33.273 39.438  C 2020   0213
-----------------------------------------------------------------------------------------------------------------------------------
90010000   0.000  0.401  C    1      7 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.5
5    1                   2   25   7700 RIDE      6.8   6.9   7.2   5.6   5.5   5.3*  6.6   5.1*  5.6   5.2*
FLEMING ST( 0.0C)                 8.5
4438921    0.000  0.401  C 2022   0012 CRACKING  9.5   9.5   9.5   9.5   9.5   8.0   6.5   6.5   6.5   4.5*  3.5*       10.0   9.5
GENERAL ASPHALT CO., INC. (2025) UNKW  RIDE                                                                                   6.2   5.7
-----------------------------------------------------------------------------------------------------------------------------------
90020000   0.000  0.942  R    1      1 CRACKING  5.5*  5.5* 10.0  10.0  10.0  10.0   9.5   8.0   7.0   7.0   7.0   4.5*  4.5*
5    1                   2   45  26000 RIDE      8.1   7.8   8.0   7.6   7.0   6.9   7.0   7.1   7.0   7.0   6.6   6.4   6.1
S OF MCDONALD AVE( 0.0C)          9.9
4291401    0.000  4.484  R 2014   0012 CRACKING  4.5*  3.5*  3.5*  3.5*        10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.8   7.5
GENERAL ASPHALT CO., INC. (2018) FC125 RIDE      5.9   5.8   5.4*  5.8         8.0   7.9   7.9   7.9   7.8   7.9   7.9   7.9   7.4

90020000   0.942  1.466  R    1      1 CRACKING  5.5*  5.5* 10.0  10.0  10.0  10.0   9.5   8.0   7.0   7.0   7.0   4.5*  4.5*
5    1                   2   55  26000 RIDE      8.1   7.8   8.0   7.6   7.0   6.9   7.0   7.1   7.0   7.0   6.6   6.4*  6.1*
                                  9.9
4291401    0.000  4.484  R 2014   0012 CRACKING  4.5*  3.5*  3.5*  3.5*        10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.1   7.5
GENERAL ASPHALT CO., INC. (2018) FC5M  RIDE      5.9*  5.8*  5.4*  5.8*        8.0   7.9   7.9   7.9   7.8   7.9   8.0   7.9   7.7

90020000   1.967  5.213  R    1      1 CRACKING  9.0   8.0   6.5   5.5* 10.0  10.0  10.0   9.0   8.0   8.0   8.0   6.5   6.5
5    1                   2   55  22500 RIDE      8.3   8.2   8.2   7.9   6.9   6.9   6.9   7.1   7.1   7.0   6.8   6.7   6.6
NAVY YARD ENT( 2.3R)              9.9
4291401    0.000  4.484  R 2014   0012 CRACKING  6.5   6.5   6.5   4.5*        10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.2   7.5
GENERAL ASPHALT CO., INC. (2018) FC5M  RIDE      6.4*  6.3*  6.1*  6.4*        8.1   7.9   8.1   8.1   8.1   8.1   8.1   8.1   7.9

90020000   6.356  6.778  C    1      1 CRACKING  8.5   8.5   8.5   8.5   8.5   8.0   8.0   5.5*  5.0*  5.0*  3.5*  3.5*  3.5*
5    1                   2   45  18000 RIDE      7.4   7.4   7.2   6.9   6.4*  6.1*  6.2   6.2   6.1   6.0   5.8   5.6   5.2*
BOAT RAMP( 6.5R)                  9.9
4231351    6.356  6.781  C 2011   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   8.3   7.0
GENERAL ASPHALT CO., INC. (2013) FC95  RIDE      8.1   7.9   8.0   7.4   7.4   7.3   7.2   7.2   7.1   7.2   6.9   6.9   6.9   6.4

90020000   7.170 10.085  C    1      1 CRACKING  8.5   8.5   8.5   8.5   8.0   8.0   8.0   7.0   6.0*  6.0*  6.0*  6.0*  6.0*
5    1                   2   55  18000 RIDE      7.9   7.8   7.9   7.6   7.2   6.7   7.1   7.1   7.0   6.7   6.7   6.5   6.5
BLUE WATER DR( 9.8R)              9.9
4284771    6.778 10.085  C 2013   0012 CRACKING  6.0*  6.0* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
GENERAL ASPHALT CO., INC. (2015) FC95  RIDE      6.3*  6.1*  8.3   7.8   7.9   7.8   7.6   7.6   7.6   7.6   7.7   7.7   7.7   7.2
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM / SPEED / SURF_TYPE	TYPE / AADT / %T / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
90020000	10.730	11.388	C	1	1	CRACKING	8.5	8.5	8.5	8.5	8.0	8.0	8.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*														
5 1			2	55	18000	RIDE	7.9	7.8	7.9	7.6	7.2	6.7	7.1	7.1	6.6	6.4*	6.4*	6.1*	5.9*													
					9.9																												
4284771	10.730	11.388	C	2013	0012	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
GENERAL ASPHALT CO., INC.			(2015)	FC95		RIDE	5.6*	5.5*	8.4	7.6	7.5	7.5	7.2	7.3	7.3	7.1	7.4	7.5	7.4	6.9													
90020000	11.388	14.899	C	1	1	CRACKING	9.0	9.0	9.0	7.5	7.5	7.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*														
5 1			2	45	18000	RIDE	8.0	8.0	8.1	7.7	6.9	7.1	6.6	6.4	6.3	6.1	6.1	5.7	5.7													
S POINT DR(12.1R)					9.9																												
4231361	11.388	14.899	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	7.5													
GENERAL ASPHALT CO., INC.			(2013)	DGFC		RIDE	8.6	8.4	8.3	7.8	7.8	7.7	7.6	7.7	7.6	7.5	7.6	7.6	7.5	7.0													
90020000	14.899	15.274	C	1	1	CRACKING	8.0	8.0	6.5	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0														
5 1			2	45	18000	RIDE	8.5	8.5	8.8	8.3	7.3	7.0	7.6	7.8	7.3	7.2	7.1	7.1	7.0														
					9.9																												
4124821	14.899	15.274	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	6.5	6.5	6.5	4.5*	4.5*	3.5*	3.7*	1.5*													
GENERAL ASPHALT CO., INC.			(2008)	FC2		RIDE	7.2	7.1	7.1	6.9	6.8	6.9	6.8	7.1	7.0	7.1	6.9	6.8	6.8	6.6													
4438981	14.899	15.284	C	2023	0012																												
90020000	21.747	22.890	C	1	1	CRACKING	6.5	4.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
5 1			2	45	17800	RIDE	8.5	8.4	8.5	8.1	7.1	7.1	7.0	7.2	7.2	7.2	7.4	7.3	7.3														
AMBERJACK RD(22.2R)					9.9																												
4103551	22.167	22.921	C	2004	0012	CRACKING	10.0	10.0	10.0	10.0	8.5	7.5	7.0	7.0	5.5*	5.5*	5.5*	5.5*	5.5*	3.5*													
GENERAL ASPHALT CO., INC.			(2006)	FC95		RIDE	7.3	7.3	7.2	7.3	7.3	7.3	7.2	7.3	7.3	7.3	7.1	7.1	7.2	6.7													
4439201	21.747	22.916	C	2023	0012																												
90020000	22.890	24.987	C	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	7.5	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*														
5 1			2	45	18800	RIDE	7.6	7.6	7.6	7.4	6.7	6.3*	6.5	6.4	6.1	5.8	5.6	5.4*	5.4*														
MIDDLE TORCH RD(23.3L)					8.6																												
4231371	22.952	24.086	L	2013	0012	CRACKING	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5													
GENERAL ASPHALT CO., INC.			(2015)	FC95M		RIDE	5.2*	5.1*	8.3	7.8	7.7	7.7	7.6	7.6	7.6	7.7	7.6	7.7	7.5	7.0													
90020000	1.967	5.213	L	1	1	CRACKING	7.0	7.0	6.5	6.5	10.0	10.0	10.0	10.0	8.0	7.5	6.5	6.5	6.5														
5 1			2	55	22500	RIDE	7.9	7.9	8.0	7.8	6.7	6.7	6.7	7.0	6.9	6.8	6.6	6.4*	6.1*														
CALLE UNO(4.9L)					9.9																												
4291401	0.000	4.703	L	2014	0012	CRACKING	6.5	6.5	4.5*	4.5*		10.0	10.0	10.0	10.0	9.0	9.0	7.5	8.3	7.0													
GENERAL ASPHALT CO., INC.			(2018)	FC5M		RIDE	6.0*	5.9*	5.4*	6.1*		8.0	7.9	8.1	8.1	8.1	8.0	8.0	8.0	7.8													
90020000	0.942	1.466	L	1	1	CRACKING	6.5	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	6.5	4.5*	4.5*														
5 1			2	55	26000	RIDE	8.3	8.4	8.1	7.9	7.2	7.1	7.1	7.3	7.2	7.1	6.8	6.4*	6.1*														
					9.9																												
4291401	0.000	4.703	L	2014	0012	CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.3	6.0*													
GENERAL ASPHALT CO., INC.			(2018)	FC5M		RIDE	5.7*	5.4*	4.9*	5.8*		8.1	7.8	8.1	8.1	8.1	8.1	8.3	8.2	8.0													
90020000	0.000	0.942	L	1	1	CRACKING	6.5	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.0	8.0	6.5	4.5*	4.5*														
5 1			2	45	26000	RIDE	8.3	8.4	8.1	7.9	7.2	7.1	7.1	7.3	7.2	7.1	6.8	6.4	6.1														
US-1/SR-5/ID90010000(0.0L)					9.9																												
4291401	0.000	4.703	L	2014	0012	CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.3	8.0													
GENERAL ASPHALT CO., INC.			(2018)	FC125		RIDE	5.7	5.4*	4.9*	5.8		8.1	7.8	8.1	8.1	8.1	8.1	7.8	7.9	7.4													
90030000	0.415	1.545	C	1	1	CRACKING	7.5	7.0	4.5*	4.5*	4.5*	2.0*	2.0*	2.0*	2.0*		10.0	10.0	10.0														
5 1			2	45	14300	RIDE	8.0	8.4	8.5	7.5	7.4	7.5	7.7	7.0	6.5		7.5	7.4	7.4														
BEACH DR(0.6L)					9.9																												
4438971	0.414	1.545	C	2022	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	7.5	6.5	6.5	4.5*	4.5*		10.0	9.6	9.0													
GENERAL ASPHALT CO., INC.			(2024)	DGFC		RIDE	7.3	7.4	7.4	7.0	7.0	7.0	6.6	6.7	6.8	6.7		7.7	7.8	7.3													
90030000	2.724	4.209	C	1	1	CRACKING	9.0	8.0	6.5	5.5*	10.0	10.0	10.0	10.0	10.0	10.0		10.0	10.0														
5 1			2	55	14300	RIDE	8.6	8.5	8.5	8.1	7.9	8.0	7.9	7.9	7.8	7.9		7.5	7.6														
SIDE ROAD(3.8L)					9.9																												
4438951	2.051	3.794	C	2022	0012	CRACKING	9.5	9.5	9.5	9.0	7.5	6.5	6.5	6.5	4.5*	4.5*		10.0	10.0	9.5													
GENERAL ASPHALT CO., INC.			(2024)	FC125		RIDE	7.5	7.5	7.5	7.6	7.5	7.5	7.4	7.5	7.5	7.4		7.4	7.5	7.0													
90030000	15.672	16.059	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0														
5 1			2	35	14000	RIDE	8.4	8.0	7.7	7.6	7.6	7.4	7.4	7.5	7.3	7.0	7.1	7.1	7.0														
					9.9																												
4291873	15.725	16.060	C	2017	0012	CRACKING	8.0	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0													
GENERAL ASPHALT CO., INC.			(2020)	FC95M		RIDE	6.7	6.4	6.7	6.4	6.4	6.8			7.8	7.8	7.7	7.7	7.8	7.3													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

90030000  16.059 16.872  C    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0   9.0   8.0   6.5   6.5   4.5*  4.5*  4.5*  4.5*
5    1                   2   35  14000 RIDE      8.8   9.0   8.9   8.2   8.4   7.5   7.3   7.8   7.5   7.4   7.3   7.2   6.5
CAMP GROUNDS(16.1R)                 9.9
4256005   16.060 16.702  C 2014   0012 CRACKING  4.5*  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   8.0
GENERAL ASPHALT CO., INC. (2016) FC125 RIDE      6.6   6.2   5.6   7.6   7.6   7.5   7.5   7.3   7.4   7.3   7.3   7.1   7.3   6.8
-----------------------------------------------------------------------------------------------------------------------------------
90040000   6.455  9.509  C    1      1 CRACKING  9.0   9.0   9.0   9.0   7.5   7.5   7.5   6.5   4.5*  4.5*  4.5*  4.5*  4.5*
5    1                   2   55  16300 RIDE      7.8   7.7   7.8   7.6   6.9   6.7   6.5   6.7   6.4*  6.3*  6.0*  5.9*  6.3*
DOLPHIN AVE( 8.3R)                  6.4
4256004    6.455  9.393  C 2014   0012 CRACKING  4.5*  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.8   7.5
GENERAL ASPHALT CO., INC. (2016) FC125 RIDE      6.4*  6.2*  6.0*  8.3   8.3   8.2   8.2   8.2   8.2   8.1   8.1   8.1   8.1   7.6

90040000   9.509 11.713  C    1      1 CRACKING  7.0   7.0   6.5   5.5*  3.5*  2.5*  2.5*  2.5*  2.5*  2.5*  2.5*        10.0
5    1                   2   55  16300 RIDE      8.7   8.5   8.5   8.3   7.4   7.0   7.0   7.3   7.2   6.9   6.9         8.1
KYLE AVE( 9.7L)                     6.4
4055826    9.393 11.637  C 2008   0005 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.4   6.5
GENERAL ASPHALT CO., INC. (2012) FC5   RIDE      8.0   7.9   8.0   8.0   8.0   7.9   7.9   8.0   7.9   7.9   7.8   7.8   7.8   7.6
-----------------------------------------------------------------------------------------------------------------------------------
90050000   8.527 11.137  C    1      1 CRACKING  3.5*  3.5* 10.0  10.0  10.0  10.0   9.0   9.0   7.5   7.0   6.5   6.5   6.5
5    1                   2   55  14500 RIDE      8.0   7.9   8.5   8.3   7.7   7.8   7.7   7.8   7.8   7.6   7.4   7.2   6.9
SOUTH LAYTON DR( 8.7R)              9.2
4322761    8.530 14.126  C 2014   0012 CRACKING  4.5*  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.3   8.0
GENERAL ASPHALT CO., INC. (2016) FC95M RIDE      6.9   6.7   6.5   8.3   8.2   8.1   8.0   8.1   8.1   8.1   8.0   8.1   8.0   7.5

90050000  12.000 14.072  C    1      1 CRACKING  8.5   8.5   8.5   8.5   8.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
5    1                   2   50  14500 RIDE      8.0   8.0   7.8   7.6   7.2   7.2   7.4   7.6   7.6   7.6   7.5   7.5   7.4
                                    9.2
4322761    8.530 14.126  C 2014   0012 CRACKING  9.0   9.0   7.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
GENERAL ASPHALT CO., INC. (2016) FC95M RIDE      7.4   7.4   7.2   8.2   8.1   8.1   8.0   8.0   8.1   8.0   8.1   8.1   8.1   7.6
-----------------------------------------------------------------------------------------------------------------------------------
90060000   3.712  4.183  C    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   7.5   7.5   7.5   7.5   7.5
5    1                   2   45  14700 RIDE      7.7   7.7   7.7   7.5   7.3   7.1   6.9   7.2   6.7   6.6   6.0   6.1   6.5
                                   10.4
4256006    3.712  4.563  C 2016   0012 CRACKING  7.5   7.5   7.5   7.5   6.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0
GENERAL ASPHALT CO., INC. (2018) FC95M RIDE      6.1   6.0   5.9   5.9   5.9   8.0   7.9   7.9   7.9   7.9   8.0   7.3   8.0   7.5

90060000   4.564  7.685  C    1      1 CRACKING 10.0   9.0   8.0   8.0   8.0   7.0   6.5   6.5   4.5*  4.5*  4.5*  4.5*  4.5*
5    1                   2   45  14700 RIDE      9.0   9.0   9.0   8.7   8.3   8.3   8.3   7.9   7.7   7.6   8.1   7.9   7.6
FRONTAGE RD( 6.2L)                 10.4
4256006    5.971  7.675  C 2016   0012 CRACKING  4.5*  4.5*  4.5*  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0
GENERAL ASPHALT CO., INC. (2018) FC95M RIDE      7.5   7.4   7.3   7.8   7.7   8.4   8.3   8.2   8.2   8.2   8.2   8.2   8.2   7.7

90060000   7.685 11.939  C    1      1 CRACKING 10.0   9.0   8.0   8.0   8.0   7.0   6.5   6.5   6.5   6.5   4.5*  4.5*  4.5*
5    1                   2   45  23000 RIDE      9.0   9.0   9.0   8.7   8.3   8.3   8.3   8.3   8.1   8.0   8.1   7.9   7.6
PALM AVE( 7.7R)                    12.3
4256003    7.675 10.240  C 2013   0012 CRACKING  4.5*  4.5*  4.5*        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0
GENERAL ASPHALT CO., INC. (2017) DGFC  RIDE      7.5   7.4   7.3         8.5   8.5   8.4   8.4   8.4   8.4   8.4   8.4   8.4   7.9

90060000  11.939 13.135  C    1      1 CRACKING  7.5   6.5   4.5*  4.5*  4.5*        10.0  10.0  10.0  10.0        10.0  10.0
5    1                   2   45  23000 RIDE      7.9   8.2   7.8   7.6   6.9         6.6   6.8   6.7   6.7         7.7   7.7
NB OFF WEIGH(12.2R)                12.3
4055826   11.769 13.209  C 2008   0005 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.0   8.0   6.5   6.5   6.5   4.5*
GENERAL ASPHALT CO., INC. (2011) FC5   RIDE      7.7   7.7   7.6   7.6   7.5   7.4   7.3   7.3   7.2   7.3   7.2   7.0   6.9   6.7
4497381   11.931 13.459  C 2027   0012

90060000  17.105 18.507  R    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.5   8.5   7.0   7.0   7.0   7.0
5    1                   2   45  30000 RIDE      8.4   8.4   8.3   8.1   7.7   7.7   7.7   7.9   7.8   7.7   7.7   7.8   7.7
OCEAN BLVD(17.7R)                  9.9
4256008   17.105 18.279  C 2013   0012 CRACKING  7.0   7.0   7.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
GENERAL ASPHALT CO., INC. (2016) DGFC  RIDE      7.2   7.3   7.1   8.4   8.3   8.3   8.2   8.2   8.2   8.3   8.2   8.1   8.1   7.6

90060000  18.507 19.253  C    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.0   8.0   7.0   7.0   7.0
5    1                   2   45  17000 RIDE      8.2   8.3   8.2   7.9   7.6   7.3   7.5   7.4   7.5   7.2   7.0   7.1
JULEP RD(18.6C)                    9.9
4256009   18.507 19.232  C 2013   0012 CRACKING  9.5   9.5   9.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
GENERAL ASPHALT CO., INC. (2016) FC2   RIDE      7.2   7.3   7.4   8.1   8.1   8.0   7.9   7.7   7.9   7.7   7.6   7.7   7.6   7.4
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GENERAL ASPHALT CO., INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / %T / WKMX-P / SURF_TYPE / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
90060000	19.253	22.623	R	1	1	CRACKING	9.0	9.0	9.0	8.5	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	7.0															
5 1			2	50	31000	RIDE	8.0	8.0	7.8	7.5	7.2	7.2	7.2	7.3	7.2	7.0	7.1	7.0	6.7														
PEACE AVE(20.2R)					12.2																													
4198481	19.298	22.682	R	2013	0012	CRACKING	7.0	7.0		10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.6															6.0*
GENERAL ASPHALT CO., INC. (2016)				FC5		RIDE	6.3*	6.5		8.2	8.3	8.2	8.2	8.2	8.3	8.3	8.3	8.3	8.2															8.0
90060000	22.623	23.218	C	1	1	CRACKING	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5															
5 1			2	50	20000	RIDE	8.0	8.0	8.1	7.7	7.4	7.4	7.3	7.5	7.5	7.5	7.4	7.3	7.3															
					9.9																													
4198481	22.682	23.218	C	2013	0012	CRACKING	8.5	8.5		10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0															7.5
GENERAL ASPHALT CO., INC. (2016)				FC5		RIDE	7.2	7.2		7.5	7.5	7.4	7.8	7.8	7.9	7.9	7.9	7.8	7.9															7.7
90060000	25.728	32.450	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	7.5	7.0	6.5	6.5	6.5	6.5															
5 1			2	45	37500	RIDE	8.8	8.8	8.9	8.7	8.2	8.2	8.1	8.2	8.2	8.2	8.1	7.8	7.7															
TRN LN TO ATLANTIC B(25.8R)					9.9																													
4198461	29.243	32.432	C	2013	0012	CRACKING	6.5	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.9															7.5
GENERAL ASPHALT CO., INC. (2016)				FC5		RIDE	7.6	7.6		8.3	8.3	8.3	8.1	8.3	8.3	8.3	8.3	8.3	8.3															8.1
90060000	26.207	32.459	L	1	1	CRACKING	9.0	8.5	7.5	7.5	6.0*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*	4.5*															
5 1			2	45	37500	RIDE	8.5	8.2	8.3	8.1	7.9	7.4	7.1	7.1	6.9	6.7	6.7	6.6	6.4															
SIDE ROAD(26.2L)					9.9																													
4198461	29.243	32.432	C	2013	0012	CRACKING	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.9															7.0
GENERAL ASPHALT CO., INC. (2015)				FC5		RIDE	6.5	6.0	8.1	8.4	8.4	8.4	8.3	8.4	8.4	8.4	8.4	8.4	8.4															8.2
90060000	19.253	22.623	L	1	1	CRACKING	9.0	8.5	8.5	7.0	7.0	6.0*	6.0*	6.0*	6.0*	4.0*	4.0*	4.0*	4.0*															
5 1			2	45	31000	RIDE	8.1	8.0	8.2	7.7	6.9	6.5	7.6	7.5	7.2	6.7	6.9	6.3	6.1															
LEG 002 *(19.3L)					12.2																													
4198481	19.376	22.682	L	2013	0012	CRACKING	4.0*	4.0*		10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.6															7.0
GENERAL ASPHALT CO., INC. (2016)				FC5		RIDE	5.6	5.2*		8.2	8.3	8.3	8.2	8.3	8.3	8.3	8.3	8.3	8.3															8.1
90060000	17.105	18.507	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.0															
5 1			2	45	30000	RIDE	7.0	7.4	7.4	7.5	6.9	7.0	7.0	7.1	7.1	7.1	6.7	6.8	6.7															
TAVERNIER TOWNE(17.7L)					9.9																													
4256008	17.105	18.279	C	2013	0012	CRACKING	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1															8.0
GENERAL ASPHALT CO., INC. (2016)				DGFC		RIDE	6.5	6.1	5.7	8.2	8.1	7.9	8.0	7.9	7.9	7.9	7.8	7.8	7.7															7.2
90060001	2.494	3.105	C	1	1	CRACKING	9.0	9.0	9.0	8.5	7.5	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	7.0															
5 1			2	50	16000	RIDE	8.3	8.1	8.1	7.6	6.7	6.6	7.4	7.4	7.1	6.7	6.4*	6.3*	5.8*															
BUTTONWOOD BAY(3.1R)					9.2																													
4198481	2.494	3.026	C	2013	0012	CRACKING	7.0	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.2															6.5
GENERAL ASPHALT CO., INC. (2016)				FC5		RIDE	5.4*	5.0*		8.3	8.4	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.4															8.2

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GILBERT SOUTHERN CORP ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)


87270000   0.000  0.145  R    4      4 CRACKING  7.9   6.9   8.5   8.2   8.2   8.5   8.4   8.1   8.0   9.3   9.1   9.0   8.9
5    I95     0.0    0.1  2   45  32500 RIDE      7.2   7.6   7.4   7.4   6.7   6.7   6.3   6.4   7.0   8.0   8.2   7.9   8.2
BRICKELL AVE NB( 0.0R)             2.3
2516621    0.070 13.440  C 1999   0217 CRACKING  8.8   8.8   8.8   8.7   8.7   9.3   9.0   9.0   9.0   9.1   8.8   8.8   8.8   7.5
GILBERT SOUTHERN CORP     (2002) LGD   RIDE      8.3   8.3   8.3   8.5   8.4   8.3   8.3   8.2   8.3   8.3   8.6   8.2   8.3   8.1
4439421    0.000  1.547  C 2023   0227

87270000   0.145  0.975  R    4      4 CRACKING  7.9   6.9   8.5   8.2   8.2   8.5   8.4   8.1   8.0   9.3   9.1   9.0   8.9
5    I95     0.1    1.0  3   45  63500 RIDE      7.2   7.6   7.4   7.4   6.7   6.7   6.3   6.4   7.0   8.0   8.2   7.9   8.2
BRICKELL AVE SB( 0.1R)             2.3
2516621    0.070 13.440  C 1999   0217 CRACKING  8.8   8.8   8.8   8.7   8.7   9.0   8.8   8.8   8.6   9.1   8.8   8.9   8.9   8.0
GILBERT SOUTHERN CORP     (2002) LGD   RIDE      8.3   8.3   8.3   8.5   8.4   8.4   8.3   8.5   8.4   8.5   8.4   8.4   8.5   8.3
4439421    0.000  1.547  C 2023   0227
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = GOSALIA CONCRETE CONSTRUCTOR ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN %T RW FY-P RW FY-F	SYSTEM SPEED FY-P WKMX-F	TYPE AADT WKMX-P WKMX-F	DISTRESS RATINGS ======== 2013	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87270000	10.170	12.167	R	4	4	CRACKING	8.7	8.7	8.8	8.8	8.9	8.7	8.2	8.0	8.1	9.0	7.8	7.8	7.2	
9A I95	10.2	12.2	4	60	209000	RIDE	7.6	8.6	8.6	8.6	8.1	8.1	7.8	7.8	7.0	7.8	5.6*	5.7*	5.8*	
					3.5															
4307902	8.823	12.091	R	2015	0227	CRACKING	5.4*	4.6*	2.7*		9.3	9.3	9.2	9.1	9.0	9.1	8.9	8.8	8.5	8.0
GOSALIA CONCRETE CONSTRUCT(2017) LGD						RIDE	6.1*	6.4*	5.6*		7.9	8.1	7.9	8.3	8.2	8.2	8.0	8.0	8.1	7.9
4370533	10.791	12.087	R	2024	0213															
87270000	8.823	10.202	L	4	4	CRACKING	8.2	9.4	9.3	9.2	9.1	9.1	8.2	8.0	8.0	7.6	7.6	7.1	6.6	
9A I95	8.8	10.2	4	60	206000	RIDE	6.9	8.7	8.8	8.7	7.9	7.8	7.9	6.4*	6.9	7.4	7.3	6.2*	6.2*	
					3.5															
4307901	8.823	10.163	L	2015	0227	CRACKING	6.0*	5.6*	5.2*	8.5	9.1	9.3	9.1	8.9	8.8	8.2	7.8	8.0	7.9	7.5
GOSALIA CONCRETE CONSTRUCT(2016) LGD						RIDE	5.9*	5.8*	5.4*	8.2	8.0	8.1	7.9	8.2	8.2	8.1	8.0	7.8	7.6	7.4

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = H & J ASPHALT, INC ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM SPEED / WKMX-P / WKMX-F	TYPE AADT / %T / SURF_TYPE	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87037000	1.539	2.590	R	1	1	CRACKING	6.5	6.5	4.5*	9.5	9.5	9.5	10.0	10.0	10.0	10.0	9.5	8.5	8.5														
907			2	30	50000	RIDE	5.8*	5.5*	5.9	7.1	6.3	4.8*	6.4	6.3	5.6	5.9	5.8	5.3*	5.5														
MICHIGAN AVE(1.5R)					3.4																												
4075712	1.524	2.700	C	2004	0012	CRACKING	8.5	8.5	8.0	6.5	6.5	6.5	6.5	5.5*	3.5*	3.5*	3.5*	3.5*	3.5*	1.5*													
H & J ASPHALT, INC				(2006)	FC125	RIDE	5.3*	5.2*	5.1*	4.1*	4.1*	4.0*	3.9*	3.7*	3.8*	3.8*	3.8*	3.6*	3.5*	3.0*													
4291931	1.519	2.914	C	2027	0005																												
87037000	1.539	2.583	L	1	1	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	9.5	8.5	8.5														
907			2	30	50000	RIDE	6.4*	6.2*	6.2	5.8	5.7	5.4*	6.5	6.4	6.0	6.3	6.2	5.7	5.9														
MICHIGAN AVE(1.5L)					3.4																												
4075712	1.524	2.700	C	2004	0012	CRACKING	8.5	8.5	8.0	8.0	8.0	8.0	8.0	6.5	4.5*	4.5*	4.5*	4.5*	4.5*	2.5*													
H & J ASPHALT, INC				(2006)	FC125	RIDE	6.0	5.8	5.7	5.1*	5.0*	5.0*	4.8*	4.7*	4.6*	4.9*	4.6*	4.4*	4.4*	3.9*													
4291931	1.519	2.914	C	2027	0005																												
87044000	6.218	7.800	R	1	1	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	7.5	7.5	6.5	3.5*	3.5*	3.5*	10.0														
976			2	35	45500	RIDE	8.1	7.4	7.9	7.3	6.8	6.5	6.2	6.2	5.3*	6.0	5.9	5.9	8.0														
ALAHAMBRA CIR(6.3C)					3.1																												
4180931	6.218	8.100	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	8.9	7.5													
H & J ASPHALT, INC				(2012)	FC95	RIDE	8.0	7.5	7.6	7.4	7.4	7.7	7.5	7.4	7.1	7.1	7.1	7.1	7.2	6.7													
87044000	7.800	8.098	L	1	1	CRACKING	9.5	9.5	9.5	9.5	9.0	7.5	6.5	6.5	6.5	9.0	6.5	5.5*	10.0														
976			2	35	39500	RIDE	7.7	7.5	7.6	7.3	6.3	5.9	5.9	5.9	5.4*	5.4*	5.4*	5.6	7.6														
SALZEDO ST(7.9L)					6.4																												
4180931	6.218	8.100	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.6	7.0													
H & J ASPHALT, INC				(2012)	FC95	RIDE	7.4	7.0	6.7	6.5	6.5	6.7	4.8*	5.0*	4.8*	5.0*	5.1*	5.0*	4.4*	3.9*													
4460011	7.782	8.086	C	2025	0012																												
87047000	0.362	2.399	C	1	1	CRACKING	6.0*	6.0*	7.0	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
973			2	40	14700	RIDE	6.5	6.7	7.0	6.5	5.9	7.1	7.0	7.1	7.2	7.1	6.9	7.3	7.1														
SW 128 ST(0.4C)					2.8																												
2502251	0.399	2.430	C	2003	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.4	6.5													
H & J ASPHALT, INC				(2005)	FC125	RIDE	7.2	7.1	7.0	6.7	6.6	6.6	6.1	6.3	6.2	5.9	6.0	6.0	5.5	5.0*													
4525631	0.039	2.903	C	2029	0012																												
87047000	2.399	2.920	C	1	1	CRACKING	6.0*	6.0*	7.0	7.0	7.0	9.0	9.0	7.5	8.0	6.5	10.0	10.0	10.0														
973			2	40	19300	RIDE	6.5	6.7	7.0	6.5	5.9	6.5	6.6	6.8	5.9	6.1	6.3	6.6	6.5														
SW 94 ST(2.5C)					2.7																												
4146271	2.399	2.920	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.0	9.0	8.0	8.0	8.0	7.5	6.0*													
H & J ASPHALT, INC				(2010)	FC125	RIDE	6.6	6.3	6.6	6.5	5.9	5.5	5.2*	5.8	5.7	5.6	5.7	5.7	5.3*	4.8*													
4525631	0.039	2.903	C	2029	0012																												
87047000	2.920	5.945	R	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	8.0	6.5	4.5*	4.5*	10.0	10.0	10.0														
973			2	40	20500	RIDE	6.8	6.7	6.7	6.2	5.7	5.5	5.5	5.5	5.5	5.3*	7.2	6.8	6.7														
KENDALL DR(2.9C)					3.0																												
4146271	2.920	5.945	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.7	7.0													
H & J ASPHALT, INC				(2010)	FC95	RIDE	7.0	6.8	6.8	6.6	6.3	6.6	6.4	6.4	6.4	6.2	6.2	6.2	6.2	5.7													
87047000	2.920	5.945	L	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	6.5	6.5	10.0	10.0	10.0														
973			2	40	20500	RIDE	6.8	6.4*	6.7	6.2	5.9	6.0	5.9	5.8	5.8	5.3*	6.7	6.9	6.8														
KENDALL DR(2.9C)					3.0																												
4146271	2.920	5.945	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0													
H & J ASPHALT, INC				(2010)	FC95	RIDE	6.7	6.7	6.7	6.6	6.5	6.6	6.2	6.5	6.4	6.2	6.1	6.2	6.2	5.7													
87055000	1.124	1.689	R	1	1	CRACKING	9.5	9.5	9.0	9.0	9.0	9.0	7.5	7.5	7.5	10.0	10.0	10.0	10.0														
986			2	40	34000	RIDE	7.0	7.1	6.8	7.2	6.5	6.3	5.8	6.0	6.1	7.0	7.2	7.2	7.0														
SW 113 PL(1.4C)					7.4																												
4124761	1.124	1.883	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.3	5.5*													
H & J ASPHALT, INC				(2009)	DGFC	RIDE	6.9	6.9	5.9	6.6	6.2	6.9	6.9	6.7	6.7	6.8	6.6	6.4	6.7	6.2													
87055000	1.124	1.689	L	1	1	CRACKING	9.0	7.5	5.5*	5.5*	4.5*	4.5*	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0														
986			2	40	34000	RIDE	7.7	7.9	8.0	7.5	6.8	6.8	6.2	6.5	6.5	7.4	7.3	7.3	7.5														
SUNSET ST PLAZA(1.2L)					7.4																												
4124761	1.124	1.883	C	2007	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	7.5													
H & J ASPHALT, INC				(2009)	DGFC	RIDE	7.5	7.1	6.8	7.0	7.3	7.4	7.2	7.3	7.3	7.2	7.3	7.3	7.3	6.8													
87060000	3.114	3.670	R	1	6	CRACKING	9.5	9.5	9.5	8.0	8.0	7.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*														
A1A 41			3	35	39500	RIDE	7.2	7.2	7.0	6.3	5.5	5.7	5.3*	5.2*	5.2*	5.1*	5.1*	4.8*	5.0*														
ALTON RD(3.2R)					6.0																												
4146361	3.175	3.670	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.9	7.5													
H & J ASPHALT, INC				(2013)	FC95	RIDE	7.0	7.0	6.9	6.0	5.9	5.6	5.4*	4.6*																			

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = H & J ASPHALT, INC ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / FY-P / FY-F	SYSTEM TYPE / SPEED / %T / WKMX-P / WKMX-F	AADT	DISTRESS RATINGS ======== / SURF_TYPE	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87060000	3.114	3.670	L	1	1	CRACKING	9.0	9.0	9.0	8.0	8.0	8.0	7.5	6.5	6.5	3.5*	3.5*	3.5*	3.5*															
A1A 41			3	35	39500	RIDE	6.8	6.6	5.9	5.6	4.8*	4.8*	4.4*	4.5*	4.5*	4.6*	4.0*	4.4*	4.4*														
WEST AVE(3.1L)					6.0																													
4146361	3.175	3.670	C	2011	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.6	6.0*														
H & J ASPHALT, INC				(2013)	FC95	RIDE	7.2	7.1	7.1	6.1	5.9	5.9	5.8	5.5	5.4*	5.4*	5.2*	5.3*	5.2*	4.7*														
87066000	4.546	5.245	R	1	1	CRACKING	9.0	9.0	8.0	8.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5															
922			2	30	29500	RIDE	4.9*	4.4*	6.1	6.4	6.7	6.5	6.4	6.5	6.4	5.9	6.2	6.3	6.2														
BROADVIEW DR E(4.8C)					7.6																													
4291372	4.546	5.245	C	2014	0012	CRACKING	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	6.9	5.5*														
H & J ASPHALT, INC				(2017)	FC95A	RIDE	6.1	6.1	5.7	4.1*	7.6	6.7	6.8	6.6	6.7	6.6	6.3	5.8	5.8	5.3*														
87066000	4.546	5.245	L	1	6	CRACKING	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	6.5	6.5	6.5															
922			2	30	29500	RIDE	5.0*	5.8*	6.1	5.6	5.6	5.7	5.6	5.7	5.6	5.5	5.5	5.1*	5.5														
BAY VIEW DR W(4.6L)					7.6																													
4291372	4.546	5.245	C	2014	0012	CRACKING	5.5*	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	7.9	6.5														
H & J ASPHALT, INC				(2017)	FC95A	RIDE	5.2*	4.9*	3.9*	4.0*	6.8	6.4	6.2	6.4																				
87080900	34.211	34.448	C	1	6	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	10.0	10.0	9.5	8.0	8.0	8.0	8.0															
934			4	30	17400	RIDE	4.5*	4.8*	4.1*	5.9	5.7	4.5*	5.7	5.1*	4.1*	4.5*	4.2*	4.0*	4.0*														
E 22 ST(34.3R)					9.7																													
4284831	34.264	34.435	C	2013	0226	CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.9	7.5														
H & J ASPHALT, INC				(2015)	DGFC	RIDE	3.9*	4.2*																										
87080900	34.448	36.311	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0															
934			2	40	30000	RIDE	7.6	7.2	7.3	7.1	6.3	6.7	6.5	6.5	6.5	6.2	6.3	6.6	6.5														
E 5 AVE(34.6C)					9.7																													
4311781	34.458	36.311	C	2015	0012	CRACKING	8.0	8.0	8.0	7.0	10.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.9	7.5														
H & J ASPHALT, INC				(2017)	FC95A	RIDE	6.3	6.4	5.8	6.1	7.0	6.7	6.8	6.6	6.4	6.9	6.4	6.4	6.2	5.7														
87080900	34.448	36.311	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0															
934			2	40	30000	RIDE	8.1	8.1	8.0	7.8	7.0	6.9	6.7	7.0	7.0	6.7	6.7	6.6	6.6														
E 5 AVE(34.6C)					9.7																													
4311781	34.458	36.311	C	2015	0012	CRACKING	7.0	7.0	7.0	7.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.1	8.0														
H & J ASPHALT, INC				(2017)	FC95A	RIDE	6.4	6.2	6.3	6.1	7.4	7.4	7.4	6.8	7.0	7.1	6.6	6.6	6.9	6.4														
87085000	0.000	0.659	C	1	1	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	7.0	6.5	6.5	6.5	6.5	6.5															
933			2	30	8100	RIDE	7.6	7.4	7.5	7.2	6.3	6.3	6.4	6.0	6.1	6.0	5.9	5.5	5.7														
SR 972(0.0C)					6.8																													
4291451	0.138	0.659	L	2014	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.5	6.0*														
H & J ASPHALT, INC				(2016)	FC125	RIDE	5.5	5.5	5.1*		6.6	6.6	6.4	6.3	6.2	6.6	6.3	6.2	6.2	5.7														
87090000	14.902	15.254	R	1	6	CRACKING	7.5	7.5	7.5	7.0	7.0	7.0	10.0	7.0	7.0	7.0	7.0	7.0	7.0															
25 27			2	40	65000	RIDE	6.4*	6.2*	6.2	6.1	5.6	5.4*	6.9	6.4	6.4	6.2	6.9	6.4	6.9														
TN LN FR LEJEUNE RD(15.0R)					8.2																													
4259792	15.031	15.193	R	2018	0012	CRACKING	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	9.3	8.5														
H & J ASPHALT, INC				(2021)	FC125	RIDE	6.1	6.3	6.3	5.7	5.6	6.2																						
87090000	19.288	19.674	C	1	6	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.0		10.0	10.0	10.0	10.0	10.0															
25 27			4	30	18200	RIDE	5.6*	5.7*	6.2	5.0*	4.8*	5.2*	4.0*		6.6	6.0	5.5	5.7	5.7															
MIAMI AVE N(19.3C)					5.1																													
4291592	19.317	19.653	C	2017	0015	CRACKING	10.0	10.0	10.0	10.0	10.0		3.5*	10.0	10.0	10.0	9.0	9.0	8.9	8.0														
H & J ASPHALT, INC				(2020)	FC125	RIDE	6.6	6.4	6.5	6.4			4.0*		5.3*																			
87120000	15.195	17.501	C	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	6.5	4.5*	10.0	10.0	10.0															
90 41			3	30	20000	RIDE	7.2	7.0	7.3	7.0	6.0	5.8	5.4*	5.6	5.6	5.4*	7.3	7.1	6.5															
SW 25 AV(15.2C)					3.8																													
4146461	15.195	17.501	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	7.6	6.0*														
H & J ASPHALT, INC				(2010)	DGFC	RIDE	6.5	6.2	5.9	5.9	5.5	5.8	5.7	5.3*	5.0*	4.9*	5.0*	4.9*	4.8*	4.3*														
4460001	15.157	17.475	C	2024	0015																													
87120001	0.452	2.998	C	1	1	CRACKING	9.0	9.0	6.5	4.5*	4.5*	4.5*	4.5*	2.0*		10.0	10.0	10.0	10.0															
90 41			3	30	15500	RIDE	6.9	6.6	6.3	6.1	4.8*	4.7*	4.6*	4.4*		6.7	6.7	6.4	6.3															
SW 3 AV(0.5C)					3.8																													
4124811	0.000	2.933	C	2006	0012	CRACKING	10.0	9.5	9.0	9.0	8.0	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5	5.0*														
H & J ASPHALT, INC				(2009)	FC95	RIDE	6.1	5.8	5.5	5.4*	5.6	5.7	5.7	5.7	5.5	5.6	5.5	5.5	5.3*	4.8*														
4478081	0.452	2.989	C	2026	0012																													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = H & J ASPHALT, INC ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87240000   0.000  1.739  R    1      1 CRACKING  9.0   9.0   9.0   9.0   7.5   7.5   7.5   6.5  10.0  10.0  10.0  10.0  10.0
9                        2   40  37500 RIDE      7.1   7.2   7.4   7.4   6.8   7.0   6.6   6.5   7.5   7.7   7.2   7.4   6.7
DIXIE HWY S( 0.0C)                 5.0
4146881    0.056  1.739  C 2005   0008 CRACKING 10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.5   8.5   8.3   6.5
H & J ASPHALT, INC        (2008) DGFC  RIDE      6.8   6.3   6.7   6.8   6.6   6.5   6.1   6.1   6.0   6.1   6.1   6.4   6.0   5.5

87240000  10.028 10.823  R    1      1 CRACKING 10.0  10.0  10.0   9.0   7.5   7.5   6.5   6.5   6.5   6.5   4.5*  4.5*  4.5*
9                        3   45  52000 RIDE      8.0   7.5   7.7   7.5   7.3   7.0   6.7   6.3   6.6   6.6   6.4   6.7   6.6
NW 122 ST(10.0C)                  10.7
4284761   10.006 10.818  C 2013   0012 CRACKING  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.9   7.5
H & J ASPHALT, INC        (2015) FC125 RIDE      6.7   6.4   7.9   7.3   7.3   7.3   7.3   7.7   6.8   6.9   7.2   6.8   6.1   5.6
-----------------------------------------------------------------------------------------------------------------------------------
87240000  10.028 10.823  L    1      1 CRACKING 10.0  10.0   9.0   8.0   8.0   8.0   8.0   7.5   6.5   6.5   4.5*  4.5*  4.5*
9                        3   45  52000 RIDE      8.3   8.2   8.2   8.1   7.3   7.1   7.1   6.9   7.2   7.1   7.6   7.4   7.4
NW 122 ST(10.0C)                  10.7
4284761   10.006 10.818  C 2013   0012 CRACKING  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.7   7.5
H & J ASPHALT, INC        (2015) FC125 RIDE      7.1   6.8   8.0   7.8   7.7   7.7   7.6   7.6   7.4   7.4   7.4   7.3   7.3   6.8

87240000   0.000  1.739  L    1      1 CRACKING  9.0   9.0   7.5   7.5   7.5   7.5   4.5*  4.5* 10.0  10.0  10.0  10.0  10.0
9                        2   40  37500 RIDE      6.9   7.7   7.5   7.7   7.1   6.8   6.3   6.5   7.5   7.5   6.8   7.3   7.4
DIXIE HWY S( 0.0C)                 5.0
4146881    0.056  1.739  C 2005   0008 CRACKING 10.0  10.0   9.0   9.0   9.0   8.5   8.5   8.5   8.5   8.5   8.5   8.5   8.5   6.5
H & J ASPHALT, INC        (2008) DGFC  RIDE      6.6   7.1   7.0   7.1   6.6   6.6   6.4   6.5   6.3   6.3   6.5   6.3   6.4   5.9
-----------------------------------------------------------------------------------------------------------------------------------
87281000   0.000  0.400  R    1      1 CRACKING  9.0   9.0   9.0   7.5   7.5   6.5   4.5*  4.5*  6.5   6.5   6.5   6.5   6.5
953                      2   40  23500 RIDE      7.3   7.6   7.5   6.9   6.8   6.4   6.2   6.7   5.1*  5.6   5.3*  5.5   5.3*
DIXIE HWY S( 0.0C)                 2.9
4284821    0.213  0.397  C 2011   0012 CRACKING 10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.8   7.5
H & J ASPHALT, INC        (2013) FC95  RIDE      5.9   5.8   5.5   5.4*  5.2*  5.5   5.3*  5.3*  5.1*  5.0*  5.1*  4.8*  5.0*  4.5*
4460021    0.034  0.462  C 2025   0012

87281000   5.494  5.945  R    1      6 CRACKING  9.5   9.5   9.5   9.5   9.0        10.0  10.0  10.0  10.0  10.0  10.0  10.0
953                      3   35  49500 RIDE      6.1*  6.4*  6.1   6.7   6.6         6.7   6.9   7.0   6.9   6.9   6.8   6.7
SR 948( 5.6C)                      4.6
4259792    5.536  5.945  R 2018   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0  10.0  10.0  10.0  10.0   9.1   8.0
H & J ASPHALT, INC        (2021) FC125 RIDE      6.3   6.5   5.4*

87281000   5.945  8.177  R    1      1 CRACKING  9.5   9.5   9.0   9.0   9.0   7.5   7.5   7.5   7.5   5.5*  5.5*  5.5*  5.5*
953                      2   40  40000 RIDE      7.6   7.6   7.3   7.3   6.6   7.0   6.9   6.7   6.7   6.6   6.3   6.6   6.4
ELEVENTH PL SE( 6.0C)              3.4
4274201    5.945  8.177  R 2012   0226 CRACKING  5.5*        10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   8.9   7.5
H & J ASPHALT, INC        (2015) DGFC  RIDE      6.1         6.6   5.9   6.0   6.3   6.2   6.2   6.1   6.0   6.0   5.9   5.9   5.4*
-----------------------------------------------------------------------------------------------------------------------------------
87281000   5.945  8.177  L    1      1 CRACKING  9.5   9.5   9.0   7.5   7.5   7.5   7.5   7.5   7.5   5.5*  4.5*  4.5*  4.5*
953                      2   40  40000 RIDE      7.7   7.9   7.6   7.5   6.6   7.0   6.8   6.8   6.7   6.4   6.5   6.4   5.8
ELEVENTH PL SE( 6.0C)              3.4
4274201    5.945  8.177  L 2012   0226 CRACKING  4.5*        10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.8   7.5
H & J ASPHALT, INC        (2015) DGFC  RIDE      6.0         6.0   6.0   5.6   6.2   6.0   5.9   5.9   5.7   5.7   5.8   5.7   5.2*

87281000   0.000  0.400  L    1      6 CRACKING  8.0   8.0   6.5   6.5   6.5   6.5   6.5   6.5   6.5   6.5   6.5   6.5   6.5
953                      2   40  23500 RIDE      6.3*  6.1*  6.5   6.1   5.7   5.0*  5.5   4.9*  4.8*  5.8   5.1*  5.3*  5.6
DIXIE HWY S( 0.0C)                 2.9
4284821    0.213  0.397  C 2011   0012 CRACKING 10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.8   7.5
H & J ASPHALT, INC        (2013) FC95  RIDE      5.8   5.9   5.2*  4.0*
4460021    0.034  0.462  C 2025   0012
-----------------------------------------------------------------------------------------------------------------------------------
87470000   0.000  0.202  L    5      6 CRACKING  7.5   7.5   7.5   6.5   6.5   6.5   6.5   6.5   6.5  10.0   9.5   9.5   9.5
91           0.0    0.2  1   55 107000 RIDE      8.0   8.0   8.1   7.1   7.0   6.3*  6.0*  5.8*  6.1*  7.3   6.8   7.0   7.3
BRIDGE #38( 0.0C)                  9.3
4146471    0.086  0.324  C 2008   0012 CRACKING  9.5               6.5   6.5   6.5   6.5   6.5   4.5*  4.5*  4.5*  4.5*  4.5*  2.0*
H & J ASPHALT, INC        (2009) FC5M  RIDE      7.1
4370535    0.096  1.222  C 2024   0213
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = H&R PAVING INC ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM / SPEED / WKMX-P / WKMX-F	TYPE / AADT / %T / SURF_TYPE	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87002000	4.969	7.777	R	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	7.0	7.0														
823			3	45	46000	RIDE	8.3	8.0	8.2	7.7	7.6	7.5	7.5	7.1	7.3	6.9	6.9	6.7	6.6														
NW 142 ST(5.0C)					7.2																												
4308031	4.969	7.777	C	2016	0012	CRACKING	7.0	7.0	6.5	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.5													
H&R PAVING INC				(2019)	FC95A	RIDE	6.6	6.5	6.2	6.3	6.3		7.1	7.0	7.0	6.9	6.8	6.8	6.8	6.3													
87002000	4.969	7.777	L	1	1	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	6.5	6.5	6.5														
823			3	45	46000	RIDE	8.1	8.1	8.0	7.9	7.5	7.2	6.9	6.7	6.7	6.6	6.3	6.6	6.3														
NW 142 ST(5.0C)					7.2																												
4308031	4.969	7.777	C	2016	0012	CRACKING	6.5	6.5	6.5	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.0													
H&R PAVING INC				(2019)	FC95A	RIDE	6.1	6.1	6.0	6.1	6.0		6.5	6.4	6.5	6.4	6.4	6.4	6.3	5.8													
87026000	6.470	8.848	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0														
860			2	40	46500	RIDE	8.4	8.2	8.2	8.2	7.8	7.6	7.6	7.6	7.6	7.6	7.7	7.5	7.7														
NORTH MIAMI BEACH CITY L(6.6R)					4.0																												
4308051	6.584	7.818	C	2014	0012	CRACKING	7.0	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.7	7.5													
H&R PAVING INC				(2016)	FC95A	RIDE	7.4	7.3	7.2	7.4	7.2	7.1	7.1	7.1	7.0	6.9	7.0	7.0	6.9	6.4													
87026000	8.848	9.311	R	1	6	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	7.0	7.0	7.0														
860			3	40	46000	RIDE	7.0	7.9	7.4	7.5	6.8	6.9	6.5	6.5	6.6	6.6	6.8	6.5	6.7														
NE 23 CT(8.9R)					2.0																												
4308052	8.865	9.225	R	2014	0012	CRACKING	7.0	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0													
H&R PAVING INC				(2017)	FC95A	RIDE	6.5	6.0	6.3																								
87026000	8.848	9.311	L	1	6	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	6.5	6.5														
860			2	30	46000	RIDE	7.7	7.6	7.9	7.6	7.2	7.3	7.2	6.9	7.1	7.0	7.0	6.8	6.9														
NE 23 CT(8.9L)					2.0																												
4308052	8.792	9.225	L	2014	0012	CRACKING	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.1	7.0													
H&R PAVING INC				(2017)	FC95A	RIDE	6.6	6.6	6.3																								
87026000	6.470	8.848	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.0	6.5	6.5														
860			2	30	46500	RIDE	7.7	7.6	7.9	7.6	7.2	7.3	7.2	6.9	7.1	7.0	7.0	6.8	6.9														
NE 5 AV(6.5L)					4.0																												
4308051	6.584	7.818	C	2014	0012	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.0	6.5													
H&R PAVING INC				(2016)	FC95A	RIDE	6.6	6.6	6.3	7.4	7.4	7.3	7.1	7.1	7.1	7.1	7.1	7.1	6.9	6.4													
87030000	6.639	8.293	R	1	1	CRACKING	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0														
5 1			3	45	80000	RIDE	7.5	8.8	8.7	8.4	8.0	8.1	8.0	8.0	8.1	8.0	7.9	8.0	7.9														
SECOFFEE TER(6.7R)					2.7																												
4334554	7.131	8.293	C	2019	0012	CRACKING	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0													
H&R PAVING INC				(2021)	FC95M	RIDE	7.5	7.2	7.4	7.5	7.6	7.3	7.4	7.5	6.9	6.8	6.9	6.9	6.8	6.3													
87030000	6.646	8.293	L	1	1	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.0														
5 1			3	45	80000	RIDE	6.2*	8.6	8.6	8.3	7.8	8.1	7.9	8.0	8.1	8.1	7.9	7.9	7.8														
SW 24 AVE(6.8L)					2.7																												
4334554	7.131	8.293	C	2019	0012	CRACKING	8.0	8.0	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0													
H&R PAVING INC				(2021)	FC95M	RIDE	7.8	7.8	7.7	7.7	7.8	7.3	7.7	7.6	7.2	7.0	7.0	6.8	7.0	6.5													
87037000	2.981	3.750	R	1	1	CRACKING	6.5	6.5	4.5*	9.5	9.5	9.5	10.0	10.0	10.0	9.0	7.0	7.0	7.0														
907			2	30	40000	RIDE	5.8*	5.5*	5.9	7.1	6.3	4.8*	6.4	6.3	5.6	5.9	5.8	5.4*	5.9														
ALTON BYPASS(3.0R)					5.6																												
4075711	2.700	5.659	C	2003	0012	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.0*	5.0*	5.0*	5.0*	5.0*	3.0*													
H&R PAVING INC				(2006)	FC125	RIDE	6.0	5.9	5.6	4.8*	4.7*	4.7*	4.6*	4.5*	4.5*	4.6*	4.5*	4.4*	4.4*	3.9*													
4560221	2.965	5.524	C	2027	0012																												
87037000	3.750	4.125	R	1	2	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.5	5.5*	5.5*	5.5*														
907			2	30	40000	RIDE	5.8*	5.5*	5.9	4.4*	3.9*	2.1*	6.0	4.6*	4.0*	3.7*	3.6*	3.2*	3.3*														
LAKEVIEW DR(3.8R)					5.6																												
4075711	2.700	5.659	C	2003	0012	CRACKING	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.0*	5.0*	5.0*	5.0*	5.0*	3.0*													
H&R PAVING INC				(2006)	FC125	RIDE	5.7	5.5	5.8	4.4*	4.5*	4.4*	4.1*	4.1*	4.1*	3.9*	4.0*	4.4*	3.9*	3.4*													
4560221	2.965	5.524	C	2027	0012																												
87037000	4.125	5.440	R	1	1	CRACKING	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.5	5.5*	5.5*	5.5*														
907			2	30	40000	RIDE	5.8*	5.5*	5.9	4.4*	3.9*	2.1*	6.0	4.6*	4.0*	3.7*	3.6*	3.2*	3.3*														
W 53 ST(4.2C)					5.6																												
4075711	2.700	5.659	C	2003	0012	CRACKING	5.5*	5.5*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*	0.0*													
H&R PAVING INC				(2006)	FC125	RIDE	6.3	6.3	5.3*	3.9*	3.6*	3.4*	3.1*	3.1*	3.0*	2.9*	2.6*	2.5*	2.6*	2.1*													
4560221	2.965	5.524	C	2027	0012																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = H&R PAVING INC ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM SPEED / WKMX-P / WKMX-F	TYPE AADT / %T / SURF_TYPE	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87037000	3.750	5.440	L	1	1	CRACKING	6.5	6.5	6.5	4.5*	4.5*	4.5*	10.0	10.0	10.0	9.0	5.5*	5.5*	5.5*														
907			2	30	40000	RIDE	6.4*	6.2*	6.2	5.7	5.0*	5.0*	6.2	5.9	5.3*	6.0	5.9	5.4*	5.7														
NORTH BAY RD(3.8L)					5.6																												
4075711	2.700	5.659	C	2003	0012	CRACKING	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	5.5*	4.5*	4.5*	4.5*	4.5*	4.5*	2.5*													
H&R PAVING INC				(2006)	FC125	RIDE	5.6	5.7	5.4*	4.5*	4.5*	4.5*	4.3*	4.2*	4.3*	4.2*	4.1*	4.1*	4.0*	3.5*													
4560221	2.965	5.524	C	2027	0012																												
87037000	2.583	2.957	L	1	6	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5														
907			1	30	40000	RIDE	6.4*	6.2*	6.2	5.8	5.7	5.4*	7.2	7.1	6.8	7.2	7.2	7.0	6.8														
3600 BLOCK(2.7C)					5.6																												
4075711	2.700	5.659	C	2003	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	8.5	8.5	8.5	8.5	7.9	6.0*													
H&R PAVING INC				(2006)	DGFC	RIDE	6.9	6.4	6.5	6.9	6.9	6.9	6.3																				
4291931	1.519	2.914	C	2027	0005																												
87038000	4.911	8.320	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5														
932			3	40	41000	RIDE	8.1	8.1	7.8	7.7	7.3	7.4	7.3	7.2	7.2	7.4	7.3	7.3	7.2														
E 10 CT(4.9R)					7.9																												
4311761	5.240	8.150	C	2015	0012	CRACKING	8.5	8.5	8.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.2	8.0													
H&R PAVING INC				(2017)	FC125	RIDE	7.2	7.2	7.1	7.3	7.8	7.8	7.6	7.6	7.6	7.6	7.6	7.6	7.4	6.9													
87038000	4.911	8.320	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	9.0	8.5	8.5	8.5														
932			3	40	41000	RIDE	7.7	7.4	7.2	6.9	6.5	6.5	6.3	6.2	6.2	6.6	6.5	6.5	6.3														
E 10 CT(4.9L)					7.9																												
4311761	5.240	8.150	C	2015	0012	CRACKING	8.5	8.5	8.5	6.5	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.9	7.5													
H&R PAVING INC				(2017)	FC125	RIDE	6.1	6.3	6.3	6.2	7.2	7.3	7.0	6.8	7.1	6.8	6.8	6.7	6.6	6.1													
87072000	3.084	4.189	R	1	1	CRACKING	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	5.5*	5.5*	10.0	10.0	10.0														
985			4	40	26000	RIDE	7.2	7.4	6.8	6.3	6.2	6.5	6.4	5.9	6.2	6.1	6.9	6.8	6.8														
SW 52 ST(3.3R)					4.0																												
4146421	3.004	4.142	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	8.0	7.9	6.0*													
H&R PAVING INC				(2010)	FC95	RIDE	6.7	6.7	6.8	6.4	6.4	6.4	6.0	6.1	5.9	5.9	5.9	6.0	5.9	5.4*													
4525691	3.084	5.148	C	2029	0012																												
87072000	4.189	5.139	R	1	1	CRACKING	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	5.5*	5.5*	6.5	10.0	10.0														
985			4	40	28500	RIDE	7.2	7.4	6.8	6.3	6.2	6.5	6.4	5.9	6.2	6.1	5.9	7.4	7.0														
SW 38 ST(4.3C)					2.0																												
2495932	4.189	5.185	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.1	6.5													
H&R PAVING INC				(2011)	FC125	RIDE	7.0	7.1	7.2	6.9	7.1	6.9	6.9	7.0	6.7	6.4	6.0	6.3	6.0	5.5													
4525691	3.084	5.148	C	2029	0012																												
87072000	4.189	5.139	L	1	1	CRACKING	9.0	9.0	9.0	8.0	7.5	6.5	6.5	5.5*	5.5*	5.5*	6.5	10.0	10.0														
985			3	40	28500	RIDE	7.0	6.6	6.7	6.5	6.1	5.9	6.1	6.0	6.1	6.1	5.9	7.4	7.0														
SW 38 ST(4.3C)					2.0																												
2495932	4.189	5.185	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.3	5.5*													
H&R PAVING INC				(2011)	FC125	RIDE	7.0	7.1	7.2	6.9	7.1	6.9	6.9	7.0	6.7	6.4	6.0	6.3	6.2	5.7													
4525691	3.084	5.148	C	2029	0012																												
87072000	3.084	4.189	L	1	1	CRACKING	9.0	9.0	9.0	8.0	7.5	6.5	6.5	5.5*	5.5*	5.5*	10.0	10.0	10.0														
985			3	40	26000	RIDE	7.0	6.6	6.7	6.5	6.1	5.9	6.1	6.0	6.1	6.1	6.9	6.8	6.8														
SW 55 TER(3.1L)					4.0																												
4146421	3.004	4.142	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.0	8.0	8.3	6.5													
H&R PAVING INC				(2010)	FC95	RIDE	6.7	6.7	6.8	6.4	6.4	6.4	6.0	6.1	5.9	5.9	5.9	6.0	5.5	5.0*													
4525691	3.084	5.148	C	2029	0012																												
87085000	0.659	2.002	C	1	1	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	7.0	6.5	6.5		10.0	10.0														
933			4	30	18300	RIDE	7.2	7.1	6.5	5.9	5.9	5.9	5.4*	5.5	5.3*	5.0*		6.6	6.3														
SW 12 ST(0.7C)					1.7																												
4327482	0.667	1.449	C	2017	0015	CRACKING	10.0	10.0	9.0	9.0	9.0	6.5	6.5	9.0	8.0	8.0	8.0	8.0	8.5	7.5													
H&R PAVING INC				(2020)	FC95	RIDE	6.3	5.7	4.7*	4.7*	4.5*	4.5*	5.4*	4.7*	4.4*	4.3*	4.4*	4.2*	4.2*	3.7*													
87120000	7.195	9.755	R	1	1	CRACKING	9.5	9.5	9.5	9.5	9.5	9.0	6.5	6.5	3.5*	3.5*	3.5*	3.5*	3.5*														
90 41			4	45	54000	RIDE	8.2	8.2	8.3	8.2	7.5	7.5	7.0	7.3	7.3	6.8	7.3	7.1	7.0														
SW 105 AVE(7.2R)					3.8																												
4251451	7.045	9.056	C	2012	0012	CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.8	7.5													
H&R PAVING INC				(2015)	FC95	RIDE	6.8		7.0	7.5	7.2	7.9	7.9	7.8	7.7	7.7	7.7	7.7	7.6	7.1													
87120000	7.195	9.755	L	1	1	CRACKING	9.5	9.5	9.0	9.0	9.0	8.0	6.5	6.5	4.5*	3.5*	3.5*	3.5*	3.5*														
90 41			4	45	54000	RIDE	8.5	8.5	8.5	8.3	7.5	7.6	7.0	7.4	7.2	7.1	7.2	7.0	6.9														
RUBEN DARIO AV/SW97A(8.0C)					3.8																												
4251451	7.045	9.056	C	2012	0012	CRACKING	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.3	7.0													
H&R PAVING INC				(2015)	FC95	RIDE	6.6		7.4	7.9	7.5	7.9	7.9	7.8	7.9	7.8	7.7	7.8	7.7	7.2													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = H&R PAVING INC ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / RW FY-F	SYSTEM SPEED / SURF_YEAR	TYPE AADT / WKMX-P / WKMX-F	DISTRESS RATINGS / %T / SURF_TYPE	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87120000	6.372	6.840	L	1	1	CRACKING	10.0	10.0	9.5	9.5	9.5	8.0	8.0	8.0	8.0	6.5	6.5	6.5	6.5														
90 41			3	45	56500	RIDE	8.2	7.9	8.3	8.3	7.5	7.6	7.1	7.7	7.6	7.6	7.6	7.7	7.1														
SIDE ROAD(6.7C)					6.8																												
4251451	6.558	7.045	C	2012	0012	CRACKING	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.4	7.0													
H&R PAVING INC				(2015)	FC95	RIDE	7.1		7.4	7.9	7.5	7.9	7.8	7.8	7.8	7.8	8.0	7.6	7.6	7.1													
87140000	11.087	11.896	C	1	1	CRACKING	6.5	4.5*	7.5	4.5*	7.5	7.0	4.5*		10.0	10.0	10.0	10.0	10.0														
7 441			2	40	34500	RIDE	6.3*	6.7	7.0	7.0	6.4	6.4	5.9		6.0	5.6	6.2	6.1	6.3														
BEGIN SEC 87140001(11.9L)					5.2																												
4077391	11.087	12.283	C	2005	0012	CRACKING	10.0	10.0	10.0	8.5	8.5	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	4.5*													
H&R PAVING INC				(2008)	DGFC	RIDE	6.1	6.3	6.0	5.9	6.3	6.3	6.3	6.2	6.1	6.0	5.9	6.0	6.0	5.5													
87190000	2.869	3.767	R	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	6.5	6.5														
909			2	40	16100	RIDE	7.5	7.7	7.6	7.2	6.9	6.7	6.5	6.4	6.1	6.1	5.8	5.6	5.8														
NE 153 ST(3.0R)					1.9																												
4308191	2.854	3.767	C	2015	0012	CRACKING	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.7	7.5													
H&R PAVING INC				(2017)	FC95A	RIDE	5.4*	5.5	5.6		6.9	6.8	6.4	6.6	6.5	6.4	6.2	6.2	6.0	5.5													
87190000	2.869	3.767	L	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	6.5	6.5														
909			2	40	16100	RIDE	7.8	7.7	7.3	7.3	6.6	6.5	6.4	6.5	6.3	6.2	6.0	6.1	6.3														
NE 153 ST(3.0L)					1.9																												
4308191	2.854	3.767	C	2015	0012	CRACKING	6.5	6.0*	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.3	7.0													
H&R PAVING INC				(2017)	FC95A	RIDE	6.0	6.1	6.0	6.7	6.8	6.2	6.2	6.2	6.2	6.2	6.5	6.3	6.1	5.6													
87220000	0.000	3.352	R	1	1	CRACKING	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0														
948			3	40	69000	RIDE	8.5	8.5	8.5	8.2	7.5	7.7	7.6	7.7	7.8	7.6	7.6	7.5	7.5														
87260391 NB ON(0.0R)					5.3																												
4291361	1.167	3.352	C	2014	0012	CRACKING	7.0	7.0	6.5	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.1	8.0													
H&R PAVING INC				(2016)	FC95A	RIDE	7.3	7.1	7.1	7.7	7.6	7.4	7.4	7.2	7.3	7.2	7.2	7.1	7.0	6.5													
87260000	24.200	24.708	R	1	1	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	6.5	4.5*	3.5*	3.5*	10.0	10.0														
826	24.2	24.7	2	40	51500	RIDE	8.1	8.3	8.0	7.7	6.8	6.6	7.0	7.0	7.3	7.1	7.1	7.1	7.0														
NW 171 ST(24.4R)					5.1																												
4180881	24.090	24.538	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.3	6.5													
H&R PAVING INC				(2011)	FC95	RIDE	6.9	6.5	6.5	5.9	5.9	5.5	5.1*	6.1	6.5	6.4	6.0	5.9	5.6	5.1*													
87260000	24.209	24.708	L	1	1	CRACKING	8.0	8.0	8.0	7.5	7.5	7.5	6.5	6.5	4.5*	3.5*	3.5*	10.0	10.0														
826	24.2	24.7	2	40	51500	RIDE	7.0	7.6	7.6	7.9	6.1	6.0	6.6	6.6	6.6	6.4	6.3	7.1	7.0														
NW 7 AVE(24.4L)					5.1																												
4180881	24.090	24.538	C	2009	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.7	7.0													
H&R PAVING INC				(2011)	FC95	RIDE	6.9	6.8	6.9	6.5	6.2	5.7	6.4	6.3	6.4	5.7	5.7	5.9	5.7	5.2*													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = HALLEY ENGINEERING CONTRACTO ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW / SURF_TYPE	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / %T / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87030000	10.389	10.556	R	1	8	CRACKING	8.5	8.5	8.5	7.5	7.5	7.5	7.5	7.0	7.0	6.5	6.5	6.5	6.5														
90 41			3	30	33000	RIDE	7.6	7.6	6.5	6.5	5.7	5.5	6.2	6.1	6.2	5.6	5.1*	5.3*	4.9*													
					2.7																												
4124738	10.396	10.556	C	2016	0012	CRACKING	6.5	6.5	6.5	6.5	3.5*	9.0																					
HALLEY ENGINEERING CONTRAC			(2018)		DGFC	RIDE	5.2*	4.5*																									
87030000	21.350	24.278	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	6.5														
5 1			4	45	61000	RIDE	8.7	8.6	8.6	8.3	7.8	7.7	7.5	7.4	7.6	7.5	7.3	7.2	7.2														
NE 156 ST(21.4R)					1.8																												
4308081	21.255	24.278	R	2016	0012	CRACKING	6.5	6.5	6.5	6.5	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0													
HALLEY ENGINEERING CONTRAC			(2019)		FC95A	RIDE	7.2	7.1	6.8	7.2	7.3		8.4	8.3	8.2	8.2	8.0	8.2	8.0	7.5													
87030000	23.965	24.278	L	1	6	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	7.0														
5 1			3	45	80500	RIDE	7.6	7.6	7.8	7.4	6.8	6.6	6.3	6.8	6.6	6.4	6.8	6.7	6.4														
					4.1																												
4308081	24.077	24.278	L	2016	0012	CRACKING	7.0	7.0	7.0	7.0	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0													
HALLEY ENGINEERING CONTRAC			(2019)		FC95A	RIDE	6.7	6.5	6.5	6.9	6.4		8.0	8.1	8.1	7.9	7.9																
87030000	21.350	23.965	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	7.5	7.5	7.5	7.5	6.5														
5 1			4	45	61000	RIDE	8.6	8.5	8.4	8.1	7.6	7.3	7.4	7.5	7.5	7.4	7.0	7.2	7.1														
SR 826(21.9C)					1.8																												
4308081	21.225	24.077	L	2016	0012	CRACKING	6.5	6.5	6.5	6.5	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0													
HALLEY ENGINEERING CONTRAC			(2019)		FC95A	RIDE	7.0	7.1	6.8	7.2	7.2		8.2	8.1	8.1	8.1	7.8	8.0	7.7	7.2													
87030000	10.221	10.556	L	1	6	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	7.5	7.5	6.5	6.5														
90 41			3	30	33000	RIDE	7.3	7.4	7.0	6.3	5.4*	4.9*	5.5	6.3	4.6*	5.3*	5.7	5.6	5.8														
SR 90 *(10.3L)					2.7																												
4124738	10.396	10.556	C	2016	0012	CRACKING	6.5	6.5	6.5	6.5	5.5*	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.1	7.0													
HALLEY ENGINEERING CONTRAC			(2018)		DGFC	RIDE	4.8*	4.5*	4.5*																								
87039000	0.000	2.462	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5														
992			2	45	35000	RIDE	7.6	7.6	7.9	7.6	7.2	7.0	7.1	7.1	7.1	7.2	7.0	7.1	6.8														
SW 113 AVE(0.2R)					3.7																												
4332862	0.155	2.190	R	2017	0012	CRACKING	7.5	7.5	7.5	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	9.0	8.0													
HALLEY ENGINEERING CONTRAC			(2020)		FC95A	RIDE	6.9	7.0	6.9	7.1	6.8	7.1		7.5	7.4	7.3	7.1	6.9	7.0	6.5													
87039000	0.000	2.462	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5														
992			2	45	35000	RIDE	7.6	7.7	7.9	7.6	7.1	7.1	7.2	7.3	7.1	7.1	6.9	6.8	6.8														
FRONTAGE RD(0.4C)					3.7																												
4332862	0.330	2.190	L	2017	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	9.1	8.0													
HALLEY ENGINEERING CONTRAC			(2020)		FC95A	RIDE	6.6	6.5	6.8	7.2	7.2	7.2		7.1	7.1	6.9	6.9	6.9	6.6	6.1													
87044000	1.727	3.265	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0														
976			3	40	48500	RIDE	8.7	8.5	8.7	8.6	8.2	8.0	7.4	8.0	7.2	7.9	7.5	7.3	7.4														
SW 100 AVE(1.8R)					3.4																												
4363551	1.739	3.265	C	2018	0012	CRACKING	8.0	8.0	8.0	6.5	6.5	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0													
HALLEY ENGINEERING CONTRAC			(2020)		FC95M	RIDE	7.7	7.5	7.5	7.8	7.7	7.7	7.7	8.2	8.1	8.1	8.1	8.1	8.1	7.6													
87044000	1.727	3.265	L	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	8.0	8.0	8.0	8.0	8.0														
976			3	40	48500	RIDE	8.6	8.6	8.7	8.6	8.0	7.9	7.2	7.7	7.8	7.8	7.7	7.6	7.6														
SW 99 CT(1.8L)					3.4																												
4363551	1.739	3.265	C	2018	0012	CRACKING	7.5	7.5	7.5	6.5	6.5	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0													
HALLEY ENGINEERING CONTRAC			(2020)		FC95M	RIDE	7.4	7.3	7.4	7.6	7.6	7.6	7.6	8.0	8.0	7.9	8.0	8.0	7.9	7.4													
87070000	10.733	14.275	R	1	1	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*														
997			2	55	20300	RIDE	7.8	7.7	7.7	7.5	7.1	7.1	6.3*	7.1	7.1	7.1	7.2	6.7	6.5														
NW 122 AVE(12.0R)					20.8																												
2496155	10.935	13.841	C	2016	0213	CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5													
HALLEY ENGINEERING CONTRAC			(2018)		FC5A	RIDE	6.5	8.8	8.2	8.2	8.2	8.2	8.2	8.1	8.1	8.1	8.1	8.0	8.0	7.8													
87070000	10.733	14.275	L	1	1	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*														
997			2	55	20300	RIDE	7.8	7.7	7.7	7.5	7.1	7.1	6.3*	7.1	7.1	7.1	7.2	6.7	6.5														
NW 130 ST/NW 122 AVE(12.0L)					20.8																												
2496155	10.935	13.841	C	2016	0213	CRACKING	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.8	8.5													
HALLEY ENGINEERING CONTRAC			(2018)		FC5A	RIDE	6.5	8.8	8.2	8.2	8.2	8.3	8.3	8.3	8.3	8.3	8.2	8.2	8.2	8.0													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = HALLEY ENGINEERING CONTRACTO ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM / SPEED / WKMX-P / WKMX-F	TYPE / AADT / %T / SURF_TYPE	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
87090000	0.000	4.540	R	1	1	CRACKING	8.0	8.0	8.0	7.0	7.0	7.5	6.5	6.5	4.5*	3.5*	3.5*	3.5*	3.5*															
25 27			2	60	32000	RIDE	7.7	7.8	7.6	7.1	6.6	6.5	6.3*	6.3*	6.3*	6.2*	6.1*	5.7*	5.7*															
KROME AVE(0.4R)					32.5																													
4232512	0.000	4.591	C	2022	0213	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	10.0	9.3	8.5														
HALLEY ENGINEERING CONTRAC			(2024)		FC5M	RIDE	5.8*	8.3	8.4	8.5	8.5	8.4	8.5	8.5	8.5	8.5	8.4	8.0	8.0	7.8														
87090000	0.000	4.540	L	1	1	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	8.0	6.5	4.5*	3.5*	3.5*	3.5*	3.5*															
25 27			2	60	32000	RIDE	8.3	8.2	8.1	7.7	7.0	6.9	6.8	6.8	6.9	6.5	6.5	6.2*	6.1*															
NW 186 ST(1.0L)					32.5																													
4232512	0.000	4.591	C	2022	0213	CRACKING	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	8.0	8.0	10.0	9.1	8.0														
HALLEY ENGINEERING CONTRAC			(2024)		FC5M	RIDE	6.1*	8.3	8.4	8.5	8.5	8.4	8.5	8.5	8.4	8.5	8.2	8.2	8.0	7.8														
87091000	5.000	6.811	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
994			2	40	27500	RIDE	8.3	8.3	8.4	8.1	7.6	7.6	7.4	7.4	7.4	7.5	7.3	7.2	7.0															
SW 127 AVE(5.1C)					8.2																													
4293413	5.416	6.825	C	2021	0012	CRACKING	9.5	9.5	9.5	9.0	8.0	8.0	6.5	6.5	6.5	4.5*	10.0	10.0	10.0	9.0														
HALLEY ENGINEERING CONTRAC			(2023)		FC95M	RIDE	6.8	7.2	7.2	7.3	7.3	7.2	7.0	7.3	7.2	7.1	7.7	7.6	7.5	7.0														
87091000	7.142	7.952	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0															
994			2	40	16400	RIDE	7.8	7.8	7.8	7.1	7.3	7.2	7.2	7.0	6.5	6.7	6.3	6.3	6.5															
MARLIN RD(7.5R)					3.0																													
4293412	7.120	7.943	C	2021	0012	CRACKING	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	9.6	9.0														
HALLEY ENGINEERING CONTRAC			(2023)		FC95M	RIDE	6.6	6.4	6.4	6.6	6.2	6.3	5.8	6.1	6.2	6.3	6.6	7.2	7.4	6.9														
87091000	7.142	7.952	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0															
994			2	40	16400	RIDE	8.3	8.3	8.0	7.4	6.6	6.2	6.4	6.4	5.9	6.4	6.0	6.1	6.3															
SW 109 AVE(7.3L)					3.0																													
4293412	7.120	7.943	C	2021	0012	CRACKING	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	9.6	9.0														
HALLEY ENGINEERING CONTRAC			(2023)		FC95M	RIDE	6.0	5.9	5.9	6.6	6.1	6.3	6.1	5.9	6.1	6.0	7.3	7.2	7.1	6.6														
87091000	5.000	6.811	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
994			2	40	27500	RIDE	8.3	8.2	8.2	8.0	7.2	7.2	6.9	7.1	7.1	6.9	6.8	6.6	6.6															
SW 127 AVE(5.1C)					8.2																													
4293413	5.416	6.825	C	2021	0012	CRACKING	9.5	9.5	9.5	9.5	8.0	6.5	6.5	6.5	6.5	4.5*	10.0	10.0	9.5	8.5														
HALLEY ENGINEERING CONTRAC			(2023)		FC95M	RIDE	6.7	6.7	6.8	7.1	6.9	6.9	6.2	6.8	6.6	6.6	7.3	7.3	7.2	6.7														
87150000	2.813	8.027	R	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.0	7.0	7.0	7.0	7.0	7.0															
997			2	45	27500	RIDE	8.5	8.5	8.5	8.2	7.8	7.6	7.6	7.7	7.7	7.7	7.6	7.4	7.5															
NE 9 ST(2.9R)					12.1																													
4273691	3.825	7.499	C	2019	0213	CRACKING	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0		10.0	10.0	10.0	9.4	8.5														
HALLEY ENGINEERING CONTRAC			(2022)		FC125	RIDE	7.5	7.3	7.4	7.2	7.2	8.1	7.9	8.0		6.8	6.7	6.7	6.5	6.0														
87150000	8.027	13.278	R	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.0			10.0	10.0	10.0															
997			2	45	32500	RIDE	8.5	8.5	8.5	8.2	7.8	7.6	7.6	7.7			7.5	7.5	7.6															
HAINLINE MILL DR(8.9C)					3.9																													
4273692	7.499	10.750	C	2018	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	9.2	8.0														
HALLEY ENGINEERING CONTRAC			(2021)		FC5M	RIDE	7.5	7.4	7.4	7.3	7.2	6.9	6.9	7.0	7.9	7.9	7.8	7.8	7.7	7.5														
87150000	13.278	13.799	R	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	9.5	8.5	7.0	7.0	6.5	6.5	6.5															
997			2	45	34000	RIDE	8.5	8.5	8.5	8.2	7.8	7.9	7.9	8.0	7.9	7.8	7.7	7.4	7.5															
					11.2																													
4273693	11.702	13.702	C	2018	0213	CRACKING	5.5*	5.5*	5.5*	3.5*	10.0	10.0		10.0	10.0	10.0	10.0	10.0	9.1	8.0														
HALLEY ENGINEERING CONTRAC			(2020)		FC5M	RIDE	7.3	7.2	7.2	7.3	8.4	8.5		7.8	7.8	7.7	7.8	7.9	7.6	7.4														
87150000	8.027	13.799	L	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.0	7.0	7.0	6.5	6.5	6.5															
997			2	45	34000	RIDE	8.5	8.5	8.5	8.2	7.8	7.6	7.6	7.7	7.9	7.8	7.7	7.4	7.5															
SW 224 ST(8.4L)					11.2																													
4273692	7.499	10.750	C	2018	0213	CRACKING	5.5*	5.5*	5.5*	3.5*	10.0	10.0			10.0	10.0	10.0	10.0	9.5	8.5														
HALLEY ENGINEERING CONTRAC			(2021)		FC5M	RIDE	7.3	7.2	7.2	7.3	8.4	8.5			7.4	7.3	7.3	7.3	7.1	6.9														
87150000	2.813	8.027	L	1	1	CRACKING	10.0	10.0	10.0	10.0	9.5	9.5	8.5	8.0	7.0	7.0	7.0	7.0	7.0															
997			2	45	27500	RIDE	8.5	8.5	8.5	8.2	7.8	7.6	7.6	7.7	7.7	7.7	7.6	7.4	7.5															
NW 9 ST(2.9L)					12.1																													
4273691	3.825	7.499	C	2019	0213	CRACKING	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0		10.0	10.0	10.0	9.5	8.5														
HALLEY ENGINEERING CONTRAC			(2022)		FC125	RIDE	7.5	7.3	7.4	7.2	7.2	8.1	7.9	8.0		6.8	6.7	6.7	6.6	6.1														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = HALLEY ENGINEERING CONTRACTO ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP	RW LN RW RW	SYSTEM SPEED %T FY-P FY-F	TYPE AADT WKMX-P WKMX-F	DISTRESS RATINGS ======== 2013	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87260000	0.000	1.063	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	7.0	
826	0.0	1.1	2	45	62000	RIDE	8.4	8.3	8.4	8.0	7.7	7.5	7.6	7.7	7.5	7.6	7.6	7.7	7.2	
SOUTH DIXIE HWY(0.0C)					4.3															
4327431	0.000	0.957	R	2016	0012	CRACKING	7.0	7.0	6.5	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.7	8.0
HALLEY ENGINEERING CONTRAC				(2018)	FC5M	RIDE	7.4	7.5	7.5	7.5		8.0	8.2	8.2	8.1	8.1	8.0	8.0	8.0	7.8
87260000	1.063	2.271	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0	7.0	
826	1.1	2.3	3	55	101500	RIDE	8.4	8.3	8.4	8.5	7.9	7.9	7.9	7.8	8.0	7.7	7.9	7.9	7.9	
					3.9															
4308212	1.343	2.271	R	2016	0012	CRACKING	6.5	6.5	6.5	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.8	8.5
HALLEY ENGINEERING CONTRAC				(2018)	FC5M	RIDE	7.8	7.7	7.7	7.9		7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.8	7.6
87260000	1.343	2.039	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0	7.0	6.5	
826	1.3	2.0	3	55	101500	RIDE	6.3*	8.3	8.4	8.4	7.6	7.9	7.8	7.3	8.0	8.0	7.9	7.8	7.4	
					3.9															
4308212	1.343	1.879	L	2016	0012	CRACKING	6.5	6.5	6.5	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.7	8.0
HALLEY ENGINEERING CONTRAC				(2018)	FC5M	RIDE	7.6	7.4	7.5	7.6		8.2	8.1	8.2	8.2	8.1	8.1	8.2	8.2	8.0
87260000	0.000	1.343	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	
826	0.0	1.3	2	55	62000	RIDE	6.3*	8.3	8.4	8.0	7.2	7.6	7.7	7.1	7.9	7.5	7.7	7.3	7.2	
SR 5(0.0L)					4.3															
4327431	0.000	1.154	L	2016	0012	CRACKING	8.0	7.0	7.0	6.5		10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.2	7.5
HALLEY ENGINEERING CONTRAC				(2018)	FC5M	RIDE	7.3	7.3	7.2	7.2		8.0	7.6	7.8	7.8	7.8	7.5	7.8	7.8	7.6
87471000	0.284	0.538	C	5	1	CRACKING	8.0	8.0	10.0	7.5	6.5	8.0	6.5	7.5	6.5	7.5	4.5*		10.0	
821	0.3	0.5	2	65	25150	RIDE	8.8	8.9	7.5	8.0	7.4	7.1	7.7	7.0	7.6	7.1	7.2		7.8	
					5.7															
4404231	0.284	0.538	C	2020	0012	CRACKING	10.0	10.0	9.0	10.0	10.0	6.5	3.5*	3.5*		10.0	10.0	10.0	9.5	8.0
HALLEY ENGINEERING CONTRAC				(2022)	FC5M	RIDE	7.8	7.9	7.5			7.2	7.4	7.4		8.0	8.0	8.0	7.9	7.8
87471000	0.538	2.371	R	5	1	CRACKING	8.0	8.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	
821	0.5	2.4	2	65	50300	RIDE	8.8	8.9	8.8	8.4	8.0	8.0	7.9	7.8	7.9	8.0	7.7		7.9	
					5.7															
4404231	0.538	2.500	C	2020	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	6.5	6.5		10.0	10.0	10.0	9.7	8.5
HALLEY ENGINEERING CONTRAC				(2022)	FC5M	RIDE	7.8	7.8	7.7	8.2	8.1	8.1	8.2	8.3		8.4	8.4	8.4	8.3	8.2
87471000	3.759	5.112	R	5	1	CRACKING	8.0	8.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	
821	3.8	5.1	2	65	78335	RIDE	8.8	8.9	8.8	8.4	8.0	8.0	7.9	7.8	7.9	8.0	7.7		7.9	
					5.7															
4404231	3.800	5.100	C	2020	0012	CRACKING	10.0	10.0	9.0	9.0	9.0			9.0	7.5	10.0	10.0	10.0	9.7	8.5
HALLEY ENGINEERING CONTRAC				(2022)	FC5M	RIDE	7.8	7.8	7.7	8.2	8.1			8.2	8.5	8.4	8.4	8.4	8.4	8.3
4441111	3.289	6.824	C	2025	0213															
87471000	32.404	33.000	R	5	8	CRACKING	8.0	8.0			10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	
821	32.4	33.0	3	60	114500	RIDE	8.7	8.8			7.7	7.7	7.7	7.7	7.8	7.8	7.4	7.6	7.6	
					5.7															
4276851	31.543	33.275	R	2013	0548	CRACKING	9.0	9.0		10.0	10.0	10.0	10.0	10.0	10.0					
HALLEY ENGINEERING CONTRAC				(2016)	FC5M	RIDE	7.5	7.4		8.6	8.5	8.5	8.5	8.6	8.4					
87471000	3.485	5.120	L	5	1	CRACKING	9.5	9.5	9.5	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5		10.0	
821	3.5	5.1	2	65	78335	RIDE	8.8	8.9	8.8	8.6	8.0	7.9	7.7	7.7	7.9	7.9	7.8		8.3	
					5.7															
4404231	3.800	5.100	C	2020	0012	CRACKING	10.0	10.0	10.0	9.0	9.0			7.5		10.0	10.0	10.0	9.6	8.0
HALLEY ENGINEERING CONTRAC				(2022)	FC5M	RIDE	8.2	8.1	8.0	8.3	8.3			8.4		8.4	8.4	8.4	8.4	8.3
4441111	3.289	6.824	C	2025	0213															
87471000	0.538	2.350	L	5	1	CRACKING	9.5	9.5	9.5	8.0	8.0	8.0	6.5	6.5	6.5	6.5	6.5		10.0	
821	0.5	2.4	2	65	50300	RIDE	8.8	8.9	8.8	8.6	8.0	7.9	7.7	7.7	7.9	7.9	7.8		8.3	
					5.7															
4404231	0.538	2.500	C	2020	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	7.5	3.5*	3.5*		10.0	10.0	10.0	10.0	8.5
HALLEY ENGINEERING CONTRAC				(2022)	FC5M	RIDE	8.2	8.1	8.0	8.3	8.3	8.1	8.0	8.2		8.5	8.4	8.4	8.4	8.3

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = HORIZON CONTRACTORS, INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / WKMX-P / WKMX-F / %T / SURF_TYPE	DISTRESS RATINGS / =========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87030000	18.057	19.267	R	1	1	CRACKING	7.5	7.5	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0														
5 1			2	35	37000	RIDE	6.4*	5.8*	7.4	7.0	6.8	6.5			7.0	7.1	6.8	6.6	6.8														
NE 107 ST(18.1R)					9.1																												
2501331	18.017	19.267	C	2004	0005	CRACKING	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5														4.5*
HORIZON CONTRACTORS, INC. (2008)					FC95	RIDE	6.8	6.7	6.8	5.7	5.6	5.5	5.5	5.5	5.3*	5.4*	5.2*	5.1*	5.2*														4.7*
4439121	18.042	19.307	C	2024	0012																												
87030000	18.057	19.370	L	1	1	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0			10.0	10.0	10.0	10.0	10.0														
5 1			2	35	37000	RIDE	7.2	6.6	7.6	7.5	6.9	6.1			7.0	7.0	6.6	6.9	6.8														
PLAZA(18.1L)					9.1																												
2501331	18.017	19.267	C	2004	0005	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.8														7.0
HORIZON CONTRACTORS, INC. (2008)					FC95	RIDE	6.8	6.9	6.7	5.9	6.1	5.9	5.7	5.3*	5.7	5.7	5.5	5.4*	5.5														5.0*
4439121	18.042	19.307	C	2024	0012																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = J V A ENGINEERING CONTRACTOR ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / %T / WKMX-P / SURF_TYPE / WKMX-F	DISTRESS RATINGS / ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87053001	0.000	0.780	C	1	1	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0														
968			3	30	22500	RIDE	7.6	7.7	7.5	7.0	6.1	6.0	5.6	7.4	7.9	7.6	7.5	7.5	6.8														
SR 968/W FLAGLER ST(0.0L)					3.4																												
4146332	0.270	0.737	C	2016	0005	CRACKING	9.0	8.5	7.5	7.5	7.5		10.0	10.0	10.0	10.0	10.0	10.0	8.8	8.0													
J V A ENGINEERING CONTRACT(2019)					FC95A	RIDE	7.2	6.6	6.4	6.3	5.9		7.3	6.2	5.9	5.8	5.9	5.7	6.0	5.5													
4507331	0.000	1.933	C	2027	0234																												
87053001	0.780	1.948	C	1	1	CRACKING	9.0	9.0	9.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	6.5	6.5														
968			3	30	16500	RIDE	6.2*	6.3*	6.0	6.0	6.9	6.2	5.8	5.9	5.6	5.2*	5.2*	5.0*	4.6*														
SW 16 AVE(0.9C)					3.8																												
4183122	0.791	1.954	C	2017	0005	CRACKING	6.5	6.5	6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	9.1	8.0													
J V A ENGINEERING CONTRACT(2020)					FC95M	RIDE	4.5*	4.3*	4.1*	4.1*	4.1*			6.6	6.3	6.5	6.0	6.1	6.1	5.6													
4507331	0.000	1.933	C	2027	0234																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = KIEWIT INFRASTRUCTURE SOUTH ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87270000	0.975	1.494	R	4	4	CRACKING	7.9	9.4	8.1	8.1	7.8	8.0	7.9	7.2	7.0	9.3	8.0	8.2	8.3	
5 I95	1.0	1.5	3	55	63500	RIDE	7.2	6.4*	6.4*	6.1*	4.7*	4.7*	4.7*	4.6*	5.1*	8.2	8.1	8.4	8.4	
					2.3															
2516623	0.000	2.900	C	2007	0217	CRACKING	8.3	8.3	8.2	8.2	8.2	8.6	8.2	8.2	8.3	8.5	8.1	8.3	8.4	7.5
KIEWIT INFRASTRUCTURE SOUT(2009) LGD						RIDE	8.4	8.4	8.2	8.5	8.4	8.4	8.4	8.4	8.4	8.5	8.4	8.1	8.5	8.3
4439421	0.000	1.547	C	2023	0227															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = M. VILA & ASSOCIATES, INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87030000  16.686 18.057  R    1      1 CRACKING  3.5*  3.5*  1.0*  1.0*  1.0*  1.0*             10.0  10.0  10.0  10.0  10.0
5    1                   2   35  50000 RIDE      7.1   7.0   6.8   6.4   5.9   5.7               7.5   7.5   7.3   7.3   7.1
NE 88 TER(16.7R)                   5.7
2502221   16.620 18.057  C 2004   0005 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   8.5   8.5   8.5   8.5   8.8   7.0
M. VILA & ASSOCIATES, INC.(2008) FC95  RIDE      7.1   7.1   6.9   6.7   6.5   6.6   6.4   6.2   6.3   6.2   6.4   6.4   6.3   5.8
4478271   16.676 18.042  C 2026   0012
-------------------------------------------------------------------------------------------------------------------------------------
87030000  16.686 18.057  L    1      1 CRACKING  4.5*  4.5*  3.5*  3.5*  1.0*  1.0*             10.0  10.0  10.0  10.0  10.0
5    1                   2   35  50000 RIDE      7.2   7.1   6.8   6.2   5.9   5.6               7.6   7.6   7.5   7.0   7.3
SR 915(16.7L)                      5.7
2502221   16.620 18.057  C 2004   0005 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5   8.5   8.5   8.5   8.5   8.9   7.0
M. VILA & ASSOCIATES, INC.(2008) FC95  RIDE      7.3   7.0   7.1   6.8   6.6   6.6   6.5   6.4   6.4   6.4   6.4   6.3   6.3   5.8
4478271   16.676 18.042  C 2026   0012
-------------------------------------------------------------------------------------------------------------------------------------
87072000   7.118  7.604  L    1      1 CRACKING 10.0  10.0   9.0   7.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
985                       3   40  59000 RIDE      5.9*  6.6   6.7   6.3         8.0   8.0   8.0   7.8   7.8   7.6   7.7   7.5
FOUNTAIN BLEU BLVD( 7.2C)          6.9
2497712    7.154  7.604  C 2002   0213 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   7.5   7.5   7.0   7.0   8.2   6.0*
M. VILA & ASSOCIATES, INC.(2005) FC125 RIDE      7.4   7.3   7.2   6.9   6.9   6.8   6.9   6.7   6.3   6.4   6.3   6.6   5.9   5.4*
4525601    6.827  7.604  C 2027   0012
-------------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = MARKS BROTHERS, INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87120000  10.370 15.195  C    1      8 CRACKING       10.0  10.0   9.5   9.5  10.0   9.5  10.0   9.5   9.5   9.5   9.5   9.5
90   41                 2   35  40000 RIDE            7.5   7.2   6.9   6.4   7.0   5.9   7.1   6.0   5.9   5.7   5.6   5.5
SW 73 CT(10.4L)                  1.9
4088801   10.244 15.677  C 2001   9924 CRACKING  9.5   9.5   9.5   9.5   9.5   9.0   9.0   9.0   9.0   9.0   8.0   8.0
MARKS BROTHERS, INC.      (2001) FC95M RIDE      5.4*  5.7   5.5   5.6   5.5   5.7   5.4*  5.6   5.5   5.3*  5.3*  5.4*
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = MASTEC CIVIL, LLC ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM SPEED / SURF_TYPE	TYPE AADT / %T / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
87004000	0.486	0.793	R	4	4	CRACKING	8.7	9.0	9.0	9.2	9.1	9.1	9.1	8.4	8.2	9.0	9.0	8.9	8.8														
112 I195	0.5	0.8	1	55	115000	RIDE	6.8	6.9	6.9	6.3*	6.2*	5.9*	5.9*	6.3*	6.0*	6.3*	5.6*	4.7*															
					4.2																												
4055781	0.114	2.136	C	2010	0024	CRACKING		9.3	9.3	9.3	9.2	9.0	9.0	9.0	9.1	9.1	8.7	8.8	8.3	7.5													
MASTEC CIVIL, LLC				(2014)	LGD	RIDE		7.4	7.7	8.1	8.2	8.1	8.1	8.2	7.8	8.2	8.2	8.1	8.2	8.0													
87004000	0.793	1.278	R	4	4	CRACKING	8.6	8.3	8.1	8.1	8.0	8.0	8.0	7.6	7.5	7.5	7.5	8.1	8.0														
112 I195	0.8	1.3	3	55	147500	RIDE	7.3	7.4	7.3	7.2	6.0*	6.1*	6.0*	6.2*	6.3*	5.9*	6.1*	5.8*	6.0*														
					3.2																												
4055781	0.114	2.136	C	2010	0024	CRACKING		9.3	9.2	9.1	9.0	9.2	9.1	9.0	9.2	8.8	8.9	9.1	9.0	8.5													
MASTEC CIVIL, LLC				(2014)	LGD	RIDE		7.7	7.5	8.1	8.4	8.2	8.2	7.9	7.8	8.3	8.2	8.0	8.3	8.1													
87004000	1.583	1.805	R	4	4	CRACKING	7.7	8.7	8.5	8.2	8.3	7.6	7.6	6.5	6.4*	8.2	8.2	8.3	8.0														
112 I195	1.6	1.8	3	55	119000	RIDE	7.1	6.7	6.4*	6.6	5.5*	4.9*	5.1*	6.3*	5.1*	6.1*	6.0*	5.9*	6.1*														
					4.2																												
4055781	0.114	2.136	C	2010	0024	CRACKING		9.4	9.0	8.9	8.9	9.1	9.1	9.0	9.2	8.9	8.9	9.4	9.4	8.5													
MASTEC CIVIL, LLC				(2014)	LGD	RIDE		7.6	7.0	7.8	7.8	7.6	7.9	8.0	8.2	8.0	8.2	7.7	7.8	7.6													
87004000	1.583	1.805	L	4	4	CRACKING	7.0	7.8	6.2*	7.3	7.0	5.9*	6.0*	5.1*	4.9*	6.3*	6.3*	6.9	6.7														
112 I195	1.6	1.8	3	55	119000	RIDE	6.2*	5.7*	5.7*	6.5	4.8*	5.6*	5.0*	5.6*	6.1*	5.7*	5.8*	5.4*	6.0*														
					4.2																												
4055781	0.114	2.136	C	2010	0024	CRACKING		9.1	8.9	8.7	8.6	9.0	8.9	8.1	8.7	8.3	8.3	9.4	8.6	8.0													
MASTEC CIVIL, LLC				(2014)	LGD	RIDE		7.7	7.7	8.2	8.1	8.1	8.1	8.1	8.1	8.2	8.3	8.1	8.0	7.8													
87004000	0.793	1.278	L	4	4	CRACKING	8.3	9.3	8.5	8.6	8.6	8.0	8.1	7.7	7.6	8.1	7.9	7.7	7.6														
112 I195	0.8	1.3	3	55	147500	RIDE	7.3	7.1	7.2	7.1	6.3*	6.2*	6.2*	5.7*	6.1*	6.0*	5.9*	5.9*	5.9*														
					3.2																												
4055781	0.114	2.136	C	2010	0024	CRACKING		9.2	9.2	9.1	9.1	9.3	9.2	9.2	8.8	8.6	9.1	9.4	9.2	8.5													
MASTEC CIVIL, LLC				(2014)	LGD	RIDE		7.9	8.2	8.2	8.4	8.4	8.2	8.4	8.4	8.4	8.2	8.4	8.4	8.2													
87004000	0.486	0.793	L	4	4	CRACKING	6.2*	8.8	8.3	8.3	8.3	7.9	8.1	7.8	7.6	8.3	8.3																
112 I195	0.5	0.8	2	55	115000	RIDE	6.9	6.8	7.0	6.6	6.1*	6.0*	5.8*	6.2*	6.4*	6.1*	6.2*																
					4.2																												
4055781	0.114	2.136	C	2010	0024	CRACKING		9.1	8.9	8.8	8.8	9.2	9.1	9.1	9.3	8.7	8.6	9.4	9.2	8.5													
MASTEC CIVIL, LLC				(2014)	LGD	RIDE		7.6	7.9	8.0	8.2	8.2	7.9	8.1	8.2	7.8	7.9	8.1	8.2	8.0													
87004000	0.363	0.486	L	3	4	CRACKING	2.6*	4.0*	6.2*	6.0*	8.7	7.1	6.7	5.4*	4.8*	5.1*	6.4*																
112	0.4	0.5	2	55	115000	RIDE	7.5	7.5	7.2	7.5	6.7	6.1*	6.8	6.4*	6.6	6.1*	6.1*																
					4.2																												
4055781	0.114	2.136	C	2010	0024	CRACKING		9.2	8.8	8.8	8.4	9.4	9.1	9.0	8.9	8.4	8.7	8.6	8.7	8.0													
MASTEC CIVIL, LLC				(2014)	LGD	RIDE		7.4	7.2	8.0	8.1	8.0	8.1	8.2	8.3	8.2	8.1	8.3	8.0	7.8													
87004000	0.000	0.363	L	3	4	CRACKING	7.4	9.0	8.0	8.5	9.1	8.8	8.2	7.8	7.9	8.2	7.8	8.2	8.0														
112	0.0	0.4	1	55	115000	RIDE	6.9	6.6	6.8	6.8	5.5*	5.9*	5.9*	6.0*	6.2*	6.0*	6.0*	5.1*															
NW 11 AVE(0.0C)					4.2																												
4055781	0.114	2.136	C	2010	0024	CRACKING		9.2	8.8	8.5	8.4	8.8	8.8	8.7	9.0	8.3	8.7	9.1	9.2	8.5													
MASTEC CIVIL, LLC				(2014)	LGD	RIDE		7.4	7.7	7.8	8.2	8.3	8.2	8.3	8.4	8.4	8.1	8.3	8.2	8.0													
87047000	5.945	8.128	R	1	1	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0														
973			2	40	27000	RIDE	6.5	6.4*	6.5	6.2	5.6	5.4*	5.3*		7.2	7.1	6.8	6.8	6.7														
BIRD RD(6.0C)					4.2																												
4075871	7.086	8.154	C	2004	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.0	8.0	8.4	6.5													
MASTEC CIVIL, LLC				(2008)	FC95	RIDE	6.7	6.3	6.3	6.3	5.9	6.1	6.0	6.1	6.2	5.9	6.0	5.9	5.9	5.4*													
87047000	5.945	8.128	L	1	1	CRACKING	7.5	6.5	6.5	6.5	6.5	6.5	4.5*		10.0	10.0	10.0	10.0	10.0														
973			2	40	27000	RIDE	6.6	6.7	6.5	6.2	5.9	5.2*	5.6		7.6	7.2	7.0	6.9	6.8														
BIRD RD(6.0C)					4.2																												
4075871	7.086	8.154	C	2004	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	6.5													
MASTEC CIVIL, LLC				(2008)	FC95	RIDE	6.6	6.8	6.8	6.7	6.5	6.3	6.2	6.4	6.1	5.9	6.0	6.1	5.8	5.3*													
87120000	2.440	5.481	R	1	1	CRACKING	10.0	10.0	10.0	9.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0														
90 41			3	45	39500	RIDE	8.2	8.3	8.3	8.3			6.5	6.8	6.9	6.8	7.3	7.1	6.8														
SW 152 AV(2.5R)					8.9																												
2497042	2.152	4.022	C	2002	0213	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	8.4	6.5													
MASTEC CIVIL, LLC				(2006)	DGFC	RIDE	7.1	7.1	6.5	6.6	6.3	6.7	6.7	6.9	6.8	6.8	6.8	6.9	6.6	6.1													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = MASTEC CIVIL, LLC ----------

```
RDWYID        BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87120000   2.440  5.481  L    1      1 CRACKING 10.0  10.0   9.5   9.5              10.0  10.0  10.0  10.0  10.0  10.0  10.0
90   41                 3   45  39500 RIDE      8.3   8.5   8.2   7.8               6.3   7.2   7.3   7.3   7.4   7.4   7.3
TN LN FR SW 137 AVE( 4.0L)          8.9
2497042    2.152  4.022  C 2002   0213 CRACKING 10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.1   7.0
MASTEC CIVIL, LLC         (2006) DGFC  RIDE      7.2   7.3   7.0   6.6   6.3   6.7   6.5   6.7   6.8   6.8   6.9   7.0   6.9   6.4
-----------------------------------------------------------------------------------------------------------------------------------
87471000  11.940 12.571  R    5      1 CRACKING  8.0   8.0   7.0   7.0   6.5   6.5   6.5   6.5   6.5   6.5   6.5  10.0  10.0
821         11.9   12.6  3   65 176000 RIDE      8.8   8.9   8.8   8.4   8.0   8.0   7.9   7.8   7.9   7.7   7.5   7.8   7.9
                                   5.7
4154881   11.767 12.300  R 2013   0213 CRACKING 10.0  10.0                    10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.4   7.5
MASTEC CIVIL, LLC         (2018) FC5M  RIDE      7.8   7.8                     8.1   8.0   8.2   7.9   8.2   8.0   8.1   8.1   8.0
4372111    7.200 12.878  C 2025   9924

87471000  12.571 14.100  R    5      1 CRACKING  8.0   8.0   8.0   7.0   6.5   6.5   6.5   6.5   6.5   6.5   6.5  10.0  10.0
821         12.6   14.1  5   60 176000 RIDE      8.4   8.4   8.3   8.2   7.4   7.3   7.2   7.2   7.2   7.4   7.2   7.7   7.9
                                   5.7
4154881   12.300 14.473  R 2013   0213 CRACKING 10.0  10.0                    10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.0
MASTEC CIVIL, LLC         (2018) FC5M  RIDE      7.7   7.7                     7.5   7.6   7.6   7.6   7.7   7.7   7.6   7.7   7.6
-----------------------------------------------------------------------------------------------------------------------------------
87471000  12.864 14.100  L    5      1 CRACKING  8.0   8.0   8.0   8.0   8.0   8.0   8.0   6.5   4.5*  4.5*        10.0  10.0
821         12.9   14.1  5   60 176000 RIDE      8.5   8.5   8.4   8.2   7.5   7.4   7.3   7.3   7.4   7.5         7.9   8.0
                                   5.7
4154881   12.571 14.473  L 2013   0213 CRACKING 10.0  10.0                    10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.4   7.5
MASTEC CIVIL, LLC         (2018) FC5M  RIDE      8.0   8.0                     7.8   8.1   8.1   7.8   7.8   7.8   7.8   7.8   7.7

87471000  11.767 12.864  L    5      1 CRACKING  9.5   9.5   9.5   8.0   8.0   8.0   6.5   6.5   6.5   6.5        10.0  10.0
821         11.8   12.9  3   65 176000 RIDE      8.8   8.9   8.8   8.6   8.0   7.9   7.7   7.7   7.9   7.6         7.6   7.8
                                   5.7
4154881   11.767 12.571  L 2013   0213 CRACKING 10.0  10.0                    10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   7.5
MASTEC CIVIL, LLC         (2018) FC5M  RIDE      7.7   7.7                     7.7   7.9   8.0   7.9   7.9   7.8   7.9   7.9   7.8
4372111    7.200 12.878  C 2025   9924
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = MCM CORP. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87002000   0.889  2.354  R    1      1 CRACKING  6.5   6.5   4.5*  3.5*  3.5*  3.5*  3.5*  3.5*  3.5*  3.5*  3.5*
823                     3   45  42500 RIDE      7.1   7.2   7.1   7.2   6.4*  6.5   6.3   6.0   6.2   6.0   5.9
W 29 ST( 1.3C)                   5.5
2499415    0.889  2.354  C 2012   0213 CRACKING  4.5*                        10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.3   8.0
MCM CORP.                  (2018) FC125 RIDE      5.6                         6.7   6.3   6.4   6.3   6.3   6.2   5.9   6.1   5.6
-----------------------------------------------------------------------------------------------------------------------------------
87002000   0.889  2.354  L    1      1 CRACKING  4.5*  4.5*  3.5*  3.5*  3.5*  3.5*  3.5*  3.5*  3.5*  3.5*  3.5*
823                     3   45  42500 RIDE      7.3   7.2   7.2   7.2   6.4*  6.3*  6.1   5.9   6.0   6.0   6.1
W 29 ST( 1.3C)                   5.5
2499415    0.889  2.354  C 2012   0213 CRACKING  4.5*                        10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.1   8.0
MCM CORP.                  (2018) FC125 RIDE      5.3*                        6.8   6.7   6.8   6.3   6.4   6.3   6.3   6.3   5.8
-----------------------------------------------------------------------------------------------------------------------------------
87080900  31.090 33.196  R    1      1 CRACKING  8.0   8.0   7.5   7.5   7.5              10.0  10.0  10.0  10.0  10.0  10.0
934                     3   45  54000 RIDE      7.0   6.7   6.9   6.2*  5.7*              7.9   7.8   8.1   7.9   7.8   7.9
EB ENT FROM SR 826 SB  L(31.1C)    9.7
2499851   31.281 33.248  C 2003   0213 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   8.0   8.0   8.0   8.0   9.0   7.0
MCM CORP.                  (2007) FC95  RIDE      7.7   7.7   7.7   7.1   7.0   6.9   6.9   6.9   7.0   6.9   6.8   6.8   6.9   6.4
4525661   31.090 33.196  C 2027   0012
-----------------------------------------------------------------------------------------------------------------------------------
87080900  31.090 33.196  L    1      1 CRACKING  9.0   9.0   9.0   8.0   8.0              10.0  10.0  10.0  10.0  10.0  10.0
934                     3   45  54000 RIDE      6.3*  6.5   6.5   6.0*  5.7*              8.3   8.2   8.1   8.0   8.1   8.0
OFF RAMP 87260399(31.1L)         9.7
2499851   31.281 33.248  C 2003   0213 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.0   7.0
MCM CORP.                  (2007) FC95  RIDE      7.9   7.9   7.8   7.4   7.0   7.4   6.9   6.8   6.8   7.0   6.9   6.8   6.7   6.2
4525661   31.090 33.196  C 2027   0012
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = ODEBRECHT CONSTRUCTION, INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87070000   0.000  0.780  R    1      1 CRACKING  9.5   9.5   9.5   9.5        10.0  10.0  10.0  10.0  10.0  10.0   8.5   8.5
997                     2   55  20300 RIDE      7.9   7.7   7.7   8.1         7.2   6.5   7.2   7.1   6.9   7.0   7.2   7.0
SR 90/US-41( 0.0C)                 20.8
2496143    0.000  0.657  C 2015   0213 CRACKING  8.5   8.5   8.5   7.5   7.5             10.0  10.0  10.0  10.0  10.0   9.5   8.0
ODEBRECHT CONSTRUCTION, IN(2020) FC5M  RIDE      6.9   6.9   6.4*  6.6   6.4*             8.1   8.0   8.0   8.0   8.0   8.0   7.8
-----------------------------------------------------------------------------------------------------------------------------------
87070000   0.000  0.780  L    1      1 CRACKING  9.5   9.5   9.5   9.5        10.0  10.0  10.0  10.0  10.0  10.0   8.5   8.5
997                     2   55  20300 RIDE      7.9   7.7   7.7   8.1         7.2   6.5   7.2   7.1   6.9   7.0   7.2   7.0
SR 90/US-41( 0.0C)                 20.8
2496143    0.000  0.657  C 2015   0213 CRACKING  8.5   8.5   8.5   7.5   7.5             10.0  10.0  10.0  10.0  10.0   9.1   8.0
ODEBRECHT CONSTRUCTION, IN(2020) FC5M  RIDE      6.9   6.9   6.4*  6.6   6.4*             8.0   7.6   7.8   7.8   7.8   7.7   7.5
-----------------------------------------------------------------------------------------------------------------------------------
87110000  25.210 25.715  C    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   8.0   7.0   7.0   6.5   6.5
90   41                 4   55   6700 RIDE      8.3   8.5   8.2   8.2   7.6   7.6   6.7   6.8   7.1   6.8   6.7   7.2   6.9
KROME AVE(25.7C)                   10.3
2496143   25.207 25.548  C 2015   0213 CRACKING  6.5   6.5   6.5                         10.0  10.0  10.0  10.0  10.0   8.9   7.5
ODEBRECHT CONSTRUCTION, IN(2020) FC5M  RIDE      6.9   6.7   6.2*                         7.5   7.5   7.6   7.7   7.5   7.5   7.3
-----------------------------------------------------------------------------------------------------------------------------------
87120000   0.000  0.297  R    1      1 CRACKING 10.0  10.0  10.0   9.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
90   41                 2   55  24500 RIDE      8.2   8.3   8.3   8.3         7.7   7.0   7.5   7.2   6.7   6.5   6.6   7.0
KROME AVENUE( 0.0C)                11.0
2496143    0.000  0.305  C 2015   0213 CRACKING 10.0  10.0  10.0  10.0                     10.0  10.0  10.0  10.0  10.0   9.5   8.0
ODEBRECHT CONSTRUCTION, IN(2020) FC5M  RIDE      6.9   7.1   7.2                          7.0   7.1   7.3   7.0   6.8   7.0   6.8
-----------------------------------------------------------------------------------------------------------------------------------
87120000   0.000  0.390  L    1      1 CRACKING 10.0  10.0   9.5   9.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
90   41                 2   55  24500 RIDE      8.3   8.5   8.2   7.8         7.4   6.4*  6.6   6.4*  6.6   6.8   6.8   7.1
KROME AVENUE( 0.0C)                11.0
2496143    0.000  0.305  C 2015   0213 CRACKING 10.0  10.0  10.0  10.0                     10.0  10.0   9.0   9.0   9.0   8.8   7.5
ODEBRECHT CONSTRUCTION, IN(2020) FC5M  RIDE      6.9   6.9   6.4*                         7.8   7.9   7.7   7.8   7.6   7.2   7.0
-----------------------------------------------------------------------------------------------------------------------------------
87150000  17.492 22.388  R    1      1 CRACKING 10.0   8.5   8.5   7.5  10.0   7.0   6.0*  6.0*  6.0*  4.0*  3.5*  3.5*  3.5*
997                     2   55  30000 RIDE      7.7   7.3   7.5   7.2   6.6   6.5   6.7   6.7   6.6   6.4*  6.0*  6.5   6.3*
SR 90(22.4C)                       15.6
2496143   17.333 22.253  C 2015   0213 CRACKING  3.5*  3.5*  1.0*  1.0*  1.0*             10.0  10.0  10.0  10.0  10.0  10.0   8.5
ODEBRECHT CONSTRUCTION, IN(2020) FC5M  RIDE      6.1*  6.0*  6.2*  5.7*  5.3*             8.2   8.2   8.0   8.0   8.0   8.0   7.8
-----------------------------------------------------------------------------------------------------------------------------------
87150000  17.492 22.388  L    1      1 CRACKING 10.0   8.5   8.5   7.5  10.0   7.0   6.0*  6.0*  6.0*  4.0*  3.5*  3.5*  3.5*
997                     2   55  30000 RIDE      7.7   7.3   7.5   7.2   6.6   6.5   6.7   6.7   6.6   6.4*  6.0*  6.5   6.3*
SW 58 ST(18.8L)                    15.6
2496143   17.333 22.253  C 2015   0213 CRACKING  3.5*  3.5*  1.0*  1.0*  1.0*             10.0  10.0  10.0  10.0  10.0   9.7   8.5
ODEBRECHT CONSTRUCTION, IN(2020) FC5M  RIDE      6.1*  6.0*  6.2*  5.7*  5.3*             8.2   8.2   8.1   8.0   8.0   7.9   7.7
-----------------------------------------------------------------------------------------------------------------------------------
87200000  12.823 12.936  R    4      6 CRACKING  6.8   8.3   7.8   7.9   7.3   7.5   7.2   5.4*  4.5*  3.5*  3.4*  4.3*  4.8*
836  I395    1.1    1.2  2   55 157000 RIDE      6.7   6.0*  6.0*
                                   3.7
2516883   12.621 13.048  R 2013   0213 CRACKING  6.8               8.9   7.0   8.2   7.6   7.5   7.4   7.6   7.0   8.4   7.5   7.0
ODEBRECHT CONSTRUCTION, IN(2016) CONC  RIDE


87200000  12.936 13.048  R    4      6 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   7.0   6.5   6.5   6.5   6.5   6.5
836  I395    1.2    1.3  3   55 157000 RIDE      6.1*  7.3   6.0*  6.1*
BEG SEC 060(13.0C)                 3.7
2516883   12.621 13.048  R 2013   0213 CRACKING  6.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   7.0
ODEBRECHT CONSTRUCTION, IN(2015) OGFC  RIDE
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = OHLA USA, INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                        (PMRS)

87020000   0.000  2.696  R    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5
5    1                   2   45  30000 RIDE      8.2   8.1   8.1   8.0   7.4   7.4   7.3   7.4   7.4   7.4   7.3   7.2   7.3
CARD SOUND RD( 0.0R)                  11.9
4418271    1.368  2.679  R 2021   0012 CRACKING  9.5   9.5   9.5   9.5   9.5   6.5   6.5   6.5   6.5   6.5   6.5  10.0   9.2   8.0
OHLA USA, INC.            (2024) FC2   RIDE      7.3   7.3   7.3   7.1   6.8   6.7   6.5   6.7   6.7   6.6   6.6   7.2   7.2   7.0
-----------------------------------------------------------------------------------------------------------------------------------
87020000   1.800  2.696  L    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
5    1                   3   45  30000 RIDE      8.1   7.9   8.0   7.8   7.3   7.4   7.4   7.4   7.5   7.5   7.4   7.4   7.4
FLORIDA CITY CITY LIMITS( 1.9C)       11.9
4418271    1.871  2.443  L 2021   0012 CRACKING 10.0  10.0   9.5   9.0   9.0   8.0   8.0   8.0   8.0   8.0  10.0  10.0  10.0   9.0
OHLA USA, INC.            (2023) FC125 RIDE      7.4   7.4   7.3   7.5   7.4   7.4   7.2   7.3   7.2   7.3   7.7   7.6   7.3   6.8

87020000   0.000  1.800  L    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
5    1                   2   45  30000 RIDE      8.4   8.4   8.4   8.3   7.8   7.8   7.8   7.8   7.9   7.8   7.7   7.6   7.5
CARD SOUND RD( 0.0C)                  11.9
4418121    0.000  0.862  C 2021   0012 CRACKING 10.0  10.0   9.5   9.5   9.5   7.0   7.0   7.0   7.0   7.0  10.0  10.0  10.0   9.0
OHLA USA, INC.            (2023) FC2   RIDE      7.4   7.3   7.3   7.4   7.1   7.2   7.1   7.1   6.8   6.8   6.9   7.0   7.0   6.8
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = P J CONSTRUCTORS INC ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ======== 	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87008000	7.114	7.231	C	1	1	CRACKING	10.0	10.0	9.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	8.0	6.5	6.5	
916			3	40	15000	RIDE	8.5	8.3	7.6	8.1	7.8	7.6	6.3	7.3	6.8	7.1	6.4	6.3	6.4	
SR 7(7.1C)					5.1															
2495821	5.294	7.383	C	1993	0213	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*		5.3*	3.0*
P J CONSTRUCTORS INC				(1998)	DGFC	RIDE	6.9	6.8	6.8	7.1	7.0	6.7	7.1	6.9	6.4	5.5	5.9		4.7*	4.2*
4525591	7.125	7.234	C	2027	0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = PAN AMERICAN CONSTRUCTION L ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / WKMX-P / WKMX-F / %T / SURF_TYPE	DISTRESS RATINGS / =========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87090000	16.871	17.514	C	1	1	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5														
25 27			4	30	25500	RIDE		8.1	7.6	7.9	6.6	7.2	6.4	6.5	7.1	7.2	6.6	7.2	7.0														
NW 23 AV(16.9C)					2.6																												
2494891	15.236	17.473	C	1997	0005	CRACKING	8.5	8.5	8.5	8.5	9.5	9.5	9.5	9.5	8.0	8.0	8.0	8.0	9.2	7.0													
PAN AMERICAN CONSTRUCTION (2001)			FC3			RIDE	7.5	7.2	7.2	7.1	7.6	7.4	7.6	7.6	7.4	7.2	7.3	6.8	7.1	6.6													
4525971	16.892	17.594	C	2029	0012																												
87281000	8.177	9.598	R	1	1	CRACKING	7.5	6.5	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0														
953			2	40	36500	RIDE	5.4*	5.4*	8.5	8.4	7.7	7.5	7.6	7.5	7.7	6.7	7.4	6.8	6.8														
SIDE ROAD(8.2C)					4.6																												
2501931	8.210	9.725	C	2000	0012	CRACKING	9.0	9.0	9.0	9.0	8.5	7.5	7.0	7.0	7.0	6.5	6.5	6.5	6.7	4.5*													
PAN AMERICAN CONSTRUCTION (2002)			FC125			RIDE	6.8	6.4	6.1	6.6	6.3	6.7	6.6	6.5	6.3	6.5	6.5	6.4	6.3	5.8													
4439271	8.673	9.686	R	2023	0012																												
87281000	8.177	9.722	L	1	1	CRACKING	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0														
953			2	40	36500	RIDE	6.6	6.6	8.3	7.8	7.8	7.8	7.7	7.7	7.8	7.6	7.5	7.4	7.6														
SIDE ROAD(8.2C)					4.6																												
2501931	8.210	9.725	C	2000	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	7.0	7.0	7.0	7.0	7.0	7.0	7.1	5.0*													
PAN AMERICAN CONSTRUCTION (2002)			FC125			RIDE	7.5	7.1	6.8	7.3	6.8	7.5	7.4	7.3	7.2	7.3	7.2	7.3	7.2	6.7													
4439271	8.215	9.686	L	2023	0012																												

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = PAVEX CORP. ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ======== 	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87190000	0.597	2.869	R	1	2	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	
909			2	40	20500	RIDE	7.5	7.7	7.6	7.2	6.9	6.7	6.5	6.4	6.7	6.5	6.4	6.3	6.2	
SR 915(0.6C)					3.5															
2499451	0.000	3.767	C	1994	0012	CRACKING	9.0	9.0	9.0	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	4.5*
PAVEX CORP.				(1996)	DGFC	RIDE	6.3	6.3	6.1	5.5	5.4*	5.5	5.4*	5.3*	5.3*	5.2*	5.2*	5.2*	5.2*	4.7*
4439361	0.866	2.858	C	2023	0012															
87190000	0.597	2.869	L	1	2	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	
909			2	40	20500	RIDE	7.8	7.7	7.3	7.3	6.6	6.5	6.4	6.5	7.4	7.4	7.2	7.2	6.9	
SR 915(0.6C)					3.5															
2499451	0.000	3.767	C	1994	0012	CRACKING	9.0	9.0	9.0	8.5	8.5	8.0	8.0	8.0	8.0	7.0	7.0	7.0	7.0	4.5*
PAVEX CORP.				(1996)	DGFC	RIDE	7.2	6.9	6.5	6.1	5.8	6.1	5.8	5.8	5.9	5.8	5.7	5.5	5.5	5.0*
4439361	0.866	2.858	C	2023	0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = PCL CIVIL CONSTRUCTORS, INC. ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87270000	12.167	13.354	R	4	4	CRACKING	8.4	8.3	7.9	7.8	9.2	9.0	9.0	8.7	8.6	7.9	7.6	7.6	7.4	
9A I95	12.2	13.4	3	55	171500	RIDE	6.9	8.8	8.0	7.8	8.1	8.2	7.9	7.7	7.7	7.8	7.7	7.3	7.9	
					3.5															
4293011	12.131	13.368	R	2014	0227	CRACKING	7.1	7.0	6.3*		9.4	9.3	9.4	9.3	9.3	9.0	9.2	8.7	8.7	8.0
PCL CIVIL CONSTRUCTORS, IN(2017) LGD						RIDE	7.3	7.1	6.8		8.3	8.4	8.4	8.6	8.5	8.3	8.5	8.3	8.2	8.0
4370534	11.300	13.360	R	2024	0213															
87270000	12.091	13.354	L	4	4	CRACKING	7.2	9.3	8.7	8.1	8.6	9.0	7.8	7.5	7.5	7.5	5.6*	5.1*	4.6*	
9A I95	12.1	13.4	3	55	171500	RIDE	6.3*	8.6	8.5	8.6	7.6	7.5	7.4	7.7	7.7	7.6	7.2	6.8	7.1	
					3.5															
4293011	12.131	13.172	L	2014	0227	CRACKING	4.6*	4.1*	2.7*	4.8*	9.2	9.3	9.2	8.9	9.1	8.3	8.3	8.8	8.7	8.0
PCL CIVIL CONSTRUCTORS, IN(2017) LGD						RIDE	6.7	6.2*	6.2*	7.4	8.1	8.1	8.0	7.8	8.2	8.1	8.1	8.3	7.9	7.7

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = PETRO HYDRO, INC ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ======== 	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87034000	2.185	3.641	C	1	1	CRACKING	10.0	10.0	9.0	9.0	9.0	8.0	7.0		10.0	10.0	10.0	8.5	8.5	
915			4	30	24352	RIDE	7.3	7.4	7.2	7.0	6.6	6.5	6.3		6.4	6.4	6.3	6.2	6.3	
NE 123 ST(2.2C)					2.0															
4146871	2.369	3.641	C	2005	0008	CRACKING	8.5	8.5	8.5	8.5	7.5	7.0	6.5	6.5	6.5	6.5	6.5	6.5	7.8	6.0*
PETRO HYDRO, INC				(2008)	FC95	RIDE	6.3	5.7	6.1	5.6	5.4*	5.3*	5.1*	4.8*	4.7*	4.6*	4.5*	4.4*	4.3*	3.8*
4439321	2.557	3.668	C	2023	0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = PREFERRED MATERIALS, INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87008000   4.888  5.102  C    1      6 CRACKING  9.0   7.5   7.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0
916                     5   40   9500 RIDE      5.0*  5.4*  4.9*  6.0   5.2*  4.9*  7.8   6.8   6.3         7.1   7.1   6.1
END 87008001 ONE-WAY( 4.9L)          5.1
4077241    4.826  5.073  C 2004   0012 CRACKING  9.5   9.5   9.5   9.5   9.5   9.5   9.5   8.0   6.5   6.5   6.5   6.5   6.5   4.5*
PREFERRED MATERIALS, INC. (2006) FC95  RIDE      6.1   6.6   6.4   5.8   6.2   5.7   5.7   6.0   5.7   5.3*  6.2
4478051    4.812  5.130  C 2024   0012
-----------------------------------------------------------------------------------------------------------------------------------
87060000   6.686  8.080  R    1      1 CRACKING  9.5   9.0   6.5   6.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0   8.5   8.5
A1A                     3   35  33000 RIDE      8.1   7.9   7.8   7.6   7.1   7.0   6.9   8.4   8.3   7.9   7.4   7.2   7.5
FOUNTAINBLEAU HOTEL( 6.7R)           6.8
4106451    6.713  8.692  C 2004   0012 CRACKING  8.5   8.5   8.5   8.5   8.5   8.5   8.0   8.0   6.5   6.5   5.5*  5.5*  5.5*  3.5*
PREFERRED MATERIALS, INC. (2007) DGFC  RIDE      7.3   7.4   7.4   7.4   7.5   7.3   7.3   7.3   7.3   7.3   7.0   7.4   7.2   6.7
4499461    7.149  8.409  C 2027   0012
-----------------------------------------------------------------------------------------------------------------------------------
87060000   7.214  8.406  L    1      1 CRACKING  7.5   6.5   4.5*  4.5*  4.5*  4.5*  4.5*  10.0  10.0  10.0   8.5   8.5   8.5
A1A                     3   35  33000 RIDE      6.9   6.8   7.1   6.4   5.8   5.8   5.7   8.2   7.8   8.0   7.8   7.8   8.0
INDIAN CREEK DR( 8.4L)               6.8
4106451    6.713  8.692  C 2004   0012 CRACKING  8.5   8.5   8.5   8.5   8.5   8.5   8.5   8.5   7.0   7.0   7.0   7.0   7.0   5.0*
PREFERRED MATERIALS, INC. (2007) DGFC  RIDE      7.8   8.0   7.3   7.6   7.6   7.6   7.4   7.4   7.3   7.4   6.9   7.0   7.0   6.5
4499461    7.149  8.409  C 2027   0012
-----------------------------------------------------------------------------------------------------------------------------------
87062000   4.072  5.064  R    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0  10.0  10.0  10.0   9.5   9.5   9.5
959                     2   40  22000 RIDE      6.5   6.1*  5.8   5.6   5.3*  5.1*  5.0*  7.6   7.5   7.2   6.6   6.8   6.8
SEVENTH ST SW( 4.1C)                 3.7
4124781    4.082  5.540  C 2004   0012 CRACKING  9.5   9.5   9.5   8.0   8.0   8.0   8.0   8.0   7.0   7.0   7.0   7.0   7.0   5.0*
PREFERRED MATERIALS, INC. (2007) FC125 RIDE      6.5   6.5   5.9   5.7   5.9   5.7   6.0   5.7   5.7   5.6   5.5   5.6   5.5   5.0*
4478041    4.088  5.393  C 2025   0012

87062000   5.064  5.424  R    1      1 CRACKING  9.0   9.0   9.0   8.0   8.0   8.0   7.5  10.0  10.0  10.0  10.0  10.0  10.0
959                     3   40  35000 RIDE      7.6   7.5   7.7   7.4   7.0   6.8   6.7   7.6   7.9   8.0   7.5   7.8   7.7
BLUE LAGOON DR( 5.3C)                4.8
4124781    4.082  5.540  C 2004   0012 CRACKING 10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   8.0   8.0   8.0   8.0   8.3   6.5
PREFERRED MATERIALS, INC. (2007) FC125 RIDE      7.7   7.7   7.8   7.6   7.4   7.1   7.3   7.3   7.3   7.2   7.1   7.2   6.8   6.3
4478041    4.088  5.393  C 2025   0012
-----------------------------------------------------------------------------------------------------------------------------------
87062000   5.064  5.424  L    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   7.5   7.5  10.0  10.0  10.0  10.0  10.0  10.0
959                     3   40  35000 RIDE      7.6   8.0   7.5   7.6   5.5   5.8   5.2*  8.1   7.7   7.3   7.1   7.3   7.1
BLUE LAGOON DR( 5.3C)                4.8
4124781    4.082  5.540  C 2004   0012 CRACKING 10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   6.5   6.5   6.5   6.5   6.5   4.5*
PREFERRED MATERIALS, INC. (2007) FC125 RIDE      7.0   6.7   6.7   6.8   6.2   6.1   7.0   6.5   6.7   6.8   6.6   6.1   5.7   5.2*
4478041    4.088  5.393  C 2025   0012

87062000   4.072  5.064  L    1      1 CRACKING  9.0   9.0   9.0   8.0   8.0   8.0   7.0  10.0  10.0  10.0  10.0  10.0  10.0
959                     3   40  22000 RIDE      6.6   6.2*  6.2   4.8*  5.0*  5.2*  5.0*  6.7   7.6   7.2   6.5   7.0   7.1
SEVENTH ST SW( 4.1C)                 3.7
4124781    4.082  5.540  C 2004   0012 CRACKING 10.0   9.5   9.5   8.0   8.0   8.0   8.0   8.0   5.5*  5.5*  5.5*  5.5*  5.5*  3.5*
PREFERRED MATERIALS, INC. (2007) FC125 RIDE      7.0   6.5   5.9   5.7   5.9   5.7   6.0   5.7   6.5   6.6   6.3   6.2   6.4   5.9
4478041    4.088  5.393  C 2025   0012
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = RANGER CONSTRUCTION INDUSTRI ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                                                                              (PMRS)

87020000  19.709 20.042  R    1      1 CRACKING  9.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0
5    1                   3   45  94000 RIDE      8.3   7.9   7.9   7.7   7.1   7.5   7.5   7.5   7.7   7.7   7.4   7.5   7.3
FLAGLER BLVD(19.8R)                  5.2
2500721   19.605 20.042  C 1999   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   8.3   5.5*
RANGER CONSTRUCTION INDUST(2001) FC5   RIDE      7.3   7.6   7.4   7.7   7.6   7.6   7.7   8.0   7.9   8.1   7.8   8.1   8.1   7.9
4439081   19.807 20.042  C 2025   0012
-----------------------------------------------------------------------------------------------------------------------------------------
87020000  19.709 20.042  L    1      6 CRACKING  6.5  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.5   9.5
5    1                   3   45  94000 RIDE      8.1   8.7   8.2   8.5   7.5   7.7   7.6   7.8   7.8   7.8   7.7   7.7   7.7
PALMETTO EXP(19.9L)                  5.2
2500721   19.605 20.042  C 1999   0012 CRACKING  9.5   9.5   9.5   9.5   9.5   9.5   9.5   9.0   9.0   8.0   8.0   8.0   8.0   5.0*
RANGER CONSTRUCTION INDUST(2001) FC5   RIDE      7.7   7.5   7.8   7.5   7.6   7.7   7.5   7.7
4439081   19.807 20.042  C 2025   0012
-----------------------------------------------------------------------------------------------------------------------------------------
87020001   0.000  0.543  C    1      1 CRACKING 10.0  10.0  10.0  10.0   9.5   9.5   9.5   8.0   7.5   7.5   7.5   7.5   7.5
5    1                   3   45  27500 RIDE      8.4   8.4   8.3   8.0   7.8   7.8   7.8   7.5   7.9   7.8   7.8   7.7   7.7
AUTOPARTS( 0.0R)                     7.2
4284871    0.000  0.560  C 2013   0012 CRACKING  9.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5   7.0
RANGER CONSTRUCTION INDUST(2014) FC125 RIDE      6.4   8.3   8.1   8.1   8.0   8.0   8.0   8.0   7.8   8.0   7.6   7.8   7.7   7.2

-----------------------------------------------------------------------------------------------------------------------------------------
87030000   0.000  0.840  R    1      1 CRACKING  9.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.5
5    1                   3   45  48000 RIDE      7.8   8.7   8.6   8.1   7.7   7.8   7.8   8.0   8.0   8.0   7.9   7.9   7.7
JOHNSON DR( 0.0C)                    3.2
2499781    0.000  0.840  C 1999   0012 CRACKING  9.5   8.0   8.0   8.0   8.0   7.5   7.5   7.5   7.5   6.5   6.5   6.5   6.5   3.5*
RANGER CONSTRUCTION INDUST(2001) FC5   RIDE      8.0   7.7   6.4   7.6   7.8   7.8   7.6   7.6   7.6   7.5   7.6   7.2   7.5   7.3
4439081    0.000  0.791  C 2025   0012
-----------------------------------------------------------------------------------------------------------------------------------------
87030000   0.000  0.840  L    1      1 CRACKING  7.5  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.5   9.5
5    1                   3   45  48000 RIDE      8.0   8.7   8.6   8.4   7.7   7.9   7.5   7.8   7.7   7.7   7.9   7.7   7.6
JOHNSON DR( 0.0C)                    3.2
2499781    0.000  0.840  C 1999   0012 CRACKING  9.5   8.5   8.5   8.5   8.5   8.5   8.5   8.5   8.0   8.0   8.0   8.0   8.4   5.5*
RANGER CONSTRUCTION INDUST(2001) FC5   RIDE      7.6   7.6   7.6   7.8   7.8   7.4   7.6   7.5   7.6   7.7   7.4   7.0   6.9   6.7
4439081    0.000  0.791  C 2025   0012
-----------------------------------------------------------------------------------------------------------------------------------------
87060000  16.052 17.717  R    1      1 CRACKING 10.0  10.0   9.5   8.0   8.0   8.0   7.5   6.5   6.5   4.5*  4.5*  4.5*  4.5*
A1A                                  2   30  33500 RIDE      7.7   7.7   7.6   7.6   6.8   6.7   6.4   6.8   6.8   7.0   6.7   6.4   6.3
SIDE ROAD(16.7C)                    11.3
4295231   16.288 17.714  R 2013   0012 CRACKING  4.5*  4.5* 10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.1   8.0
RANGER CONSTRUCTION INDUST(2015) FC125 RIDE      6.2   5.0*  7.2   7.1   7.3   6.8   6.5   6.7   6.5   6.6   6.4   6.3   6.1   5.6

-----------------------------------------------------------------------------------------------------------------------------------------
87060000  16.191 17.717  L    1      1 CRACKING 10.0   9.5   8.0   8.0   8.0   8.0   7.5   6.5   6.5   4.5*  4.5*  4.5*  4.5*
A1A                                  2   35  33500 RIDE      7.0   7.0   7.3   7.0   6.8   6.7   6.2   6.6   6.6   6.5   6.3   6.1   5.9
SR 856 EB(16.2L)                    11.3
4295231   16.487 17.714  L 2013   0012 CRACKING  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.6   8.5
RANGER CONSTRUCTION INDUST(2015) FC125 RIDE      5.9   5.7   7.2   7.3   7.3   7.1   7.0   7.0   6.6   6.6   6.2   6.3   5.9   5.4*

-----------------------------------------------------------------------------------------------------------------------------------------
87062000   2.038  3.024  C    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   7.5   7.5   7.5   6.5   6.5   6.5
959                                  2   35  14400 RIDE      7.6   7.8   7.6   7.5   7.1   7.0   6.8   7.1   7.1   7.0   6.7   6.7   6.7
BIRD RD( 2.0C)                       4.0
4227232    2.063  2.997  C 2013   0012 CRACKING  6.5   6.5  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.6   8.5
RANGER CONSTRUCTION INDUST(2015) FC95  RIDE      6.6   6.7   8.0   7.2   7.1   7.1   6.9   6.5   6.4   6.5   6.7   6.5   6.8   6.3

-----------------------------------------------------------------------------------------------------------------------------------------
87072000   5.139  5.931  R    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.0   8.0   8.0   8.0   8.0
985                                  3   40  45500 RIDE      6.7   6.8   6.7   6.4   6.0   6.0   5.6   5.8   6.0   6.0   6.1   6.0   5.8
SW 24 ST/CORAL WAY( 5.2C)            4.0
4311771    5.161  5.931  C 2015   0012 CRACKING  8.0   8.0   8.0   8.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.2   8.0
RANGER CONSTRUCTION INDUST(2017) FC125 RIDE      6.0   5.9   5.7   6.3   8.2   8.0   7.6   8.0   7.7   8.0   8.1   8.0   7.6   7.1

-----------------------------------------------------------------------------------------------------------------------------------------
87072000   5.139  5.931  L    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.0   7.0   7.0   7.0   7.0   7.0
985                                  3   40  45500 RIDE      7.1   7.0   6.9   6.9   6.1   5.7   6.5   6.5   6.5   6.5   6.2   6.4   6.4
SW 24 ST/CORAL WAY( 5.2C)            4.0
4311771    5.161  5.931  C 2015   0012 CRACKING  7.0   7.0   7.0   7.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.6   8.5
RANGER CONSTRUCTION INDUST(2017) FC125 RIDE      6.4   6.4   6.4   6.7   8.2   7.8   7.5   8.0   8.0   8.2   8.2   8.0   8.0   7.5

-----------------------------------------------------------------------------------------------------------------------------------------
87110000   3.967 13.928  C    1      1 CRACKING 10.0   9.5   9.5   9.5   9.5   9.5   8.0   8.0   8.0   7.0   7.0   6.5   6.5
90   41                              2   55   6700 RIDE      8.9   8.6   8.7   8.6   7.9   7.8   7.1   7.0   7.1   7.0   7.1   7.3   7.1
LOOP RD( 4.1R)                      10.3
4291622    8.118 13.131  C 2016   0012 CRACKING  5.5*  5.5*  5.5*  5.5*  3.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.6   8.5
RANGER CONSTRUCTION INDUST(2018) FC95M RIDE      7.0   6.9   6.7   7.5   7.5   8.5   8.4   8.3   8.1   8.1   8.1   8.1   8.1   7.6
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = ROADWAY CONSTRUCTION LLC ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM / SPEED / WKMX-P / WKMX-F	TYPE / AADT / %T / SURF_TYPE	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	FUTURE 2030 (PMRS)
87044000	0.280	1.727	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0	8.0														
976			3	40	44500	RIDE	8.7	8.5	8.7	8.6	8.2	8.0	7.4	8.0	7.2	7.9	7.5	7.3	7.4														
SW 112 AVE(0.6C)					8.2																												
4363552	0.282	1.727	C	2020	0012	CRACKING	8.0	8.0	8.0	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	9.5	8.5													
ROADWAY CONSTRUCTION LLC			(2023)	FC95M		RIDE	7.7	7.5	7.5	7.8	7.7	7.7	7.7	7.7	7.8	7.6	8.5	8.5	8.5	8.0													
87044000	0.280	1.727	L	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	8.0	8.0	8.0	8.0	8.0														
976			3	40	44500	RIDE	8.6	8.6	8.7	8.6	8.0	7.9	7.2	7.7	7.8	7.8	7.7	7.6	7.6														
SW 11500 BLOCK(0.3L)					8.2																												
4363552	0.282	1.727	C	2020	0012	CRACKING	7.5	7.5	7.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	10.0	10.0	9.5	8.5													
ROADWAY CONSTRUCTION LLC			(2023)	FC95M		RIDE	7.4	7.3	7.4	7.6	7.6	7.6	7.6	7.8	7.7	7.8	8.3	8.3	8.3	7.8													
87060001	2.498	3.014	R	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5		10.0	10.0	10.0	9.0														
A1A			3	30	33000	RIDE	6.2*	5.9*	5.6	5.7	5.6	5.8	6.0	5.3*		6.6	6.0	6.1	5.2*														
CONDO ENTRANCE(2.6R)					6.8																												
4308131	2.498	2.831	R	2019	0015	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	9.6	8.5													
ROADWAY CONSTRUCTION LLC			(2021)	DGFC		RIDE	5.4*	5.3*	5.5	4.8*	4.5*	4.5*	4.6*	4.2*	6.2	6.2	6.3	6.1	6.1	5.6													
87060001	2.498	3.014	L	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.5		10.0	10.0	10.0	9.5														
A1A			3	30	33000	RIDE	6.5	6.5	6.4	5.8	5.5	5.4*	5.2*	5.4*		7.1	6.9	6.9	7.0														
67 ST(2.6L)					6.8																												
4308131	2.616	3.014	L	2019	0015	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	10.0	10.0	10.0	10.0	10.0	9.0													
ROADWAY CONSTRUCTION LLC			(2021)	DGFC		RIDE	7.3	7.0	6.9	5.7	6.6	5.9	5.3*		7.4	7.3	7.5	7.5	7.0	6.5													
87085000	3.014	3.603	R	1	7	CRACKING	7.0	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	9.5	9.5	9.5														
933			2	35	22500	RIDE	4.0*	4.6*	4.1*	4.0*	3.5*	3.8*	6.0	6.0	5.6	5.6	5.2*	5.0*	5.6														
NW 20 ST(3.0C)					12.0																												
4327484	3.014	3.603	C	2022	0015	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	10.0	9.5													
ROADWAY CONSTRUCTION LLC			(2025)	DGFC		RIDE	5.5	5.7	5.3*	4.9*	4.5*	3.8*	4.5*	4.6*	3.9*	4.4*	4.0*	4.0*	4.9*	4.4*													
87085000	3.014	3.603	L	1	7	CRACKING	9.0	9.0	7.5	7.5	7.5	7.5	10.0	10.0	10.0	10.0	9.5	9.5	9.5														
933			2	35	22500	RIDE	4.0*	4.8*	4.2*	3.8*	3.7*	3.5*	7.1	6.6	6.4	6.3	5.8	6.2	5.9														
NW 20 ST(3.0C)					12.0																												
4327484	3.014	3.603	C	2022	0015	CRACKING	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	10.0	9.5													
ROADWAY CONSTRUCTION LLC			(2025)	DGFC		RIDE	5.8	5.8	6.2	4.7*	5.0*	4.8*	4.7*	4.8*	4.3*	4.8*	4.6*	4.6*	4.9*	4.4*													
87140000	6.211	8.062	R	1	1	CRACKING	6.5	6.5	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5														
7 441			2	35	29500	RIDE	7.0	6.8	4.8*	7.5	7.0	6.8	6.9	6.9	6.9	6.4	6.9	6.8	6.7														
SIDE ROAD(6.2C)					4.2																												
4308173	6.211	8.062	C	2020	0012	CRACKING	9.5	9.5	9.0	9.0	9.0	9.0	8.0	7.0	7.0		10.0	10.0	10.0	9.0													
ROADWAY CONSTRUCTION LLC			(2023)	FC95M		RIDE	6.7	6.6	6.5	5.3*	5.0*	5.3*	5.1*	5.1*	4.9*		7.1	7.1	7.1	6.6													
87140000	8.062	10.431	R	1	1	CRACKING	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5														
7 441			2	35	27000	RIDE	5.9*	5.9*	5.8	7.5	7.0	6.8	6.9	6.9	6.9	6.4	6.9	6.8	6.7														
NW 117 ST(8.1R)					2.6																												
4308174	8.062	10.431	C	2020	0012	CRACKING	9.5	9.5	9.0	9.0	9.0	7.0	7.0	6.0*			10.0	10.0	10.0	9.0													
ROADWAY CONSTRUCTION LLC			(2023)	FC95M		RIDE	6.7	6.6	6.5	5.7	5.6	5.7	5.6	5.6			7.3	7.2	7.0	6.5													
87140000	8.062	10.431	L	1	1	CRACKING	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5														
7 441			2	35	27000	RIDE	6.5	6.4*	6.1	8.1	7.6	7.5	7.3	7.4	7.4	7.3	7.4	7.3	7.2														
NW 117 ST(8.1L)					2.6																												
4308174	8.062	10.431	C	2020	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	7.0	6.0*			10.0	10.0	10.0	9.0													
ROADWAY CONSTRUCTION LLC			(2023)	FC95M		RIDE	7.2	7.3	6.9	6.1	5.7	5.9	5.7	5.7			7.5	7.3	7.3	6.8													
87140000	6.211	8.062	L	1	1	CRACKING	4.5*	4.5*	4.5*	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5														
7 441			2	40	29500	RIDE	5.3*	5.2*	4.5*	6.9	6.3	6.3	6.3	6.4	6.3	6.3	6.3	6.4	6.5														
SIDE ROAD(6.2C)					4.2																												
4308173	6.211	8.062	C	2020	0012	CRACKING	8.0	8.0	8.0	7.0	7.0	7.0	7.0	6.0*	6.0*		10.0	10.0	9.6	9.0													
ROADWAY CONSTRUCTION LLC			(2023)	FC95M		RIDE	6.4	6.3	5.9	5.2*	4.8*	4.9*	4.8*	4.7*	4.7*		6.6	6.6	6.5	6.0													

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = RUSSELL ENGINEERING, INC ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87053000   5.900  6.348  R    1      1 CRACKING  7.5   7.5   7.5   6.5   6.5   6.5   4.5*  4.5*  4.5*  3.5*  3.5*  3.5*  3.5*
968                     2   40  31500 RIDE      5.2*  5.1*  5.7   3.1*  2.5*  3.0*  2.2*  2.6*  2.9*  3.0*  2.9*  2.9*  2.9*
SW 29 AVE( 5.9R)                   5.6
4180911    6.022  6.324  C 2016   0005 CRACKING  3.5*  3.5*  3.5*  3.5*  0.0*             10.0  10.0  10.0   9.5   9.5   8.9   8.0
RUSSELL ENGINEERING, INC  (2020) FC95M RIDE      2.7*  2.6*                                5.0*  4.9*  4.8*  5.1*  4.6*  4.5*  4.0*
-----------------------------------------------------------------------------------------------------------------------------------
87053000   5.900  6.348  L    1      6 CRACKING  7.0   7.0   7.0   8.5   8.5   8.5   8.5   8.0   6.5   3.5*  3.5*  3.5*  3.5*
968                     2   40  31500 RIDE      4.9*  5.3*  4.9*  3.5*  3.1*  2.4*  2.4*  2.8*  2.4*  2.8*  2.4*  2.2*  2.7*
NW 27 CT( 6.0L)                    5.6
4180911    6.022  6.324  C 2016   0005 CRACKING  3.5*  3.5*  3.5*  3.5*  0.0*             10.0  10.0  10.0  10.0  10.0   9.0   8.0
RUSSELL ENGINEERING, INC  (2020) FC95M RIDE      2.0*  2.0*                                5.0*
-----------------------------------------------------------------------------------------------------------------------------------
87270000  10.202 12.091  L    4      4 CRACKING  7.6   9.4   8.8   8.7   8.7   8.6   7.3   7.0   7.0   6.1*  5.9*  4.1*  3.7*
9A   I95    10.2   12.1  4   60 209000 RIDE      7.1   8.6   8.7   7.8   7.6   7.4   7.2   7.1   6.6   6.5   6.4*  5.4*  5.7*
                                   3.5
4275151   10.985 11.938  L 2013   0227 CRACKING  2.9*  3.3*  8.9   8.9   8.8   8.8   8.7   8.6   8.3   8.4   8.3   7.6   7.6   7.0
RUSSELL ENGINEERING, INC  (2015) LGD   RIDE      5.4*  5.2*  4.6*  7.7   7.8   7.9   7.7   8.0   7.9   7.9   7.8   7.7   7.7   7.5
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = SEACOAST INC. ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ======== 	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87170000	5.364	5.727	C	1	7	CRACKING	9.0	8.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0			10.0	10.0	
826			4	35	23000	RIDE	5.7*	4.9*	7.1	7.4	7.6	7.5	6.3	6.5	7.3			6.6	5.8	
COLLINS AVE(5.7C)					4.0															
4365252	5.234	5.663	C	2021	0012	CRACKING	10.0	10.0	10.0	8.0	8.0	8.0	8.0	8.0	6.5	6.5	6.5		10.0	9.5
SEACOAST INC.				(2025)	DGFC	RIDE	5.4*	5.5	5.5	5.5	4.7*	4.6*	4.6*	4.5*	4.2*	4.4*	4.2*		5.9	5.4*

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = SOUTHEASTERN ENGINEERING CON ----------

```
RDWYID        BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87062000   3.024  3.678  C    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   7.5   7.5   7.5   6.5   6.5   6.5
959                     2   35  22500 RIDE      7.6   7.8   7.6   7.5   7.1   7.0   6.8   7.1   7.1   7.0   6.7   6.7   6.7
SW 22 ST( 3.2L)                   3.7
4227231    3.087  3.497  C 2012   0012 CRACKING  6.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.7   7.5
SOUTHEASTERN ENGINEERING C(2015) FC95  RIDE      6.6         7.0   6.3   6.3   6.4   6.1   5.9   6.2   5.9   6.1   6.1   6.0   5.5

87062000   3.678  4.072  C    1      1 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5   8.5   7.0   6.5   6.5   6.5
959                     3   35  22500 RIDE      7.5   6.5   6.4   6.0   5.7   6.0   6.8   5.7   5.6   6.3   6.9   5.7   5.8
SW 14 ST( 3.7L)                   3.7
4227231    3.737  4.012  C 2012   0012 CRACKING  6.5        10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.5   9.5   9.4   8.0
SOUTHEASTERN ENGINEERING C(2015) FC95  RIDE                  7.5   6.7   6.6   6.2   6.3   6.1   5.7   5.5   5.7   6.1   6.2   5.7
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = THE DE MOYA GROUP INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM / SPEED / SURF_TYPE	TYPE / AADT / %T / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000 / 2013	2001 / 2014	2002 / 2015	2003 / 2016	2004 / 2017	2005 / 2018	2006 / 2019	2007 / 2020	2008 / 2021	2009 / 2022	2010 / 2023	2011 / 2024	2012 / 2025	FUTURE 2030 (PMRS)
87008001	0.533	2.779	C	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5	6.5	6.5	6.5	10.0	10.0	10.0	
916			3	40	11000	RIDE	7.7	7.8	8.1	7.4	6.5	6.5	6.2	6.3	6.4	6.2	7.3	7.0	7.0	
NW 8 AVE(0.7R)					5.1															
4146181	0.519	2.522	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	7.0
THE DE MOYA GROUP INC.				(2010)	DGFC	RIDE	7.0	7.0	7.0	7.1	7.0	7.0	6.9	6.9	6.8	6.8	6.6	6.5	6.5	6.0
87019000	0.178	2.977	R	1	1	CRACKING	9.0	9.0	7.5	6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	
817			3	45	41500	RIDE	7.5	7.4	7.4	7.2	6.5	6.6	6.7	6.6	6.7	7.7	7.8	7.6	7.7	
SR 9 SB(0.2R)					7.1															
4124701	0.164	2.977	C	2007	0012	CRACKING	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	2.5*
THE DE MOYA GROUP INC.				(2009)	FC5	RIDE	7.6	7.5	7.5	7.9	7.8	7.8	7.7	7.6	7.8	7.7	7.7	7.7	7.6	7.4
4439371	0.178	1.847@	C	2023	0012															
87019000	0.178	2.977	L	1	1	CRACKING	7.0	7.0	6.5	6.5	6.5	6.5	6.5	3.5*	3.5*	10.0	10.0	10.0	10.0	
817			3	45	41500	RIDE	7.6	7.7	7.7	7.6	7.0	6.9	6.9	6.9	6.9	7.8	7.8	7.8	7.8	
BURLINGTON ST(0.2L)					7.1															
4124701	0.164	2.977	C	2007	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	2.5*
THE DE MOYA GROUP INC.				(2009)	FC5	RIDE	7.5	7.6	7.4	7.9	7.8	7.9	7.7	7.7	7.9	7.8	7.7	7.7	7.6	7.4
4439371	0.178	1.847@	C	2023	0012															
87090000	10.027	12.125	R	1	1	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5		10.0	10.0	10.0	10.0	10.0	10.0	
25 27			3	40	60500	RIDE	6.3*	6.4*	6.2	6.1	5.9	5.6		8.0	8.2	8.1	8.0	8.0	8.1	
NW 79 AVE(10.0R)					11.7															
2501052	10.442	11.575	C	2004	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.9	7.0
THE DE MOYA GROUP INC.				(2007)	DGFC	RIDE	7.9	8.0	8.0	7.8	7.7	7.6	7.6	6.9	7.0	7.0	7.0	7.0	7.1	6.6
4525651	10.562	12.133	C	2030	0012															
87090000	12.125	13.493	R	1	1	CRACKING	2.0*	2.0*	2.0*			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
25 27			3	40	62000	RIDE	4.6*	4.7*	4.6*			7.4	7.2	7.1	7.0	6.6	7.2	7.2	7.3	
SIDE ROAD(12.1C)					15.5															
2498391	11.818	13.486	C	2001	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	9.0	7.0
THE DE MOYA GROUP INC.				(2005)	DGFC	RIDE	6.9	6.9	6.9	7.2	7.1	7.1	7.0	6.9	6.9	6.8	6.7	6.9	6.6	6.1
4478281	12.133	14.665	C	2026	0012															
87090000	13.493	14.902	R	1	1	CRACKING	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
25 27			3	40	65000	RIDE	5.3*	5.5*	5.2*	4.0*		7.3	6.9	7.1	7.0	6.4	6.8	6.8	6.7	
CURTISS PKWY(13.6R)					8.2															
2498392	13.486	14.774	C	2001	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.6	6.5
THE DE MOYA GROUP INC.				(2005)	DGFC	RIDE	6.7	6.8	6.8	6.3	6.3	6.1	6.0	5.8	6.2	6.2	6.2	5.9	6.0	5.5
4478281	12.133	14.665	C	2026	0012															
87090000	13.493	14.732	L	1	1	CRACKING	6.5	6.5	6.5	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
25 27			3	40	65000	RIDE	5.3*	5.5*	5.2*	4.3*		7.3	7.1	7.2	6.9	6.9	7.0	6.9	6.9	
PALM AVE(13.6L)					8.2															
2498392	13.486	14.774	C	2001	0213	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.9	7.0
THE DE MOYA GROUP INC.				(2005)	DGFC	RIDE	6.8	6.9	6.9	6.0	5.9	6.1	5.9	5.8	5.7	5.9	5.8	5.5	5.7	5.2*
4478281	12.133	14.665	C	2026	0012															
87090000	12.125	13.493	L	1	1	CRACKING	6.5	6.5	6.5			10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	
25 27			3	40	62000	RIDE	7.1	7.0	7.2			7.4	7.4	7.4	7.6	7.0	7.3	7.4	7.3	
SIDE ROAD(12.1C)					15.5															
2498391	11.818	13.486	C	2001	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.1	7.0
THE DE MOYA GROUP INC.				(2005)	DGFC	RIDE	7.2	7.1	7.3	6.8	6.8	6.7	6.8	6.8	6.8	6.7	6.4	6.6	6.5	6.0
4478281	12.133	14.665	C	2026	0012															
87090000	10.027	12.125	L	1	1	CRACKING	6.5	6.5	6.5	7.0	7.0			10.0	10.0	10.0	10.0	10.0	10.0	
25 27			3	50	60500	RIDE	7.1	7.0	7.2	6.9	6.3*			8.2	8.1	8.0	7.9	7.9	7.8	
FRONTAGE RD(10.4L)					11.7															
2501052	10.442	11.575	C	2004	0213	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.2	7.5
THE DE MOYA GROUP INC.				(2007)	DGFC	RIDE	7.7	7.6	7.7	7.1	7.1	7.1	7.0	6.8	6.8	6.7	6.4*	6.8	6.8	6.3*
4525651	10.562	12.133	C	2030	0012															
90003000	0.759	2.588	C	1	1	CRACKING	1.0*	1.0*	1.0*	1.0*	1.0*	1.0*	0.0*			10.0	10.0	10.0	10.0	
A1A			4	30	14500	RIDE	5.6*	5.7*	5.4*	5.1*	4.6*	3.7*	4.3*			6.6	6.2	6.4	6.3	
FARALDO CIR(1.3L)					8.5															
2505482	0.830	2.895	C	2005	0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.6	8.0
THE DE MOYA GROUP INC.				(2009)	DGFC	RIDE	6.3	6.3	6.2	6.0	6.0	6.0	5.9	5.9	5.9	5.9	5.7	5.9	5.9	5.4*
90030000	5.487	6.129	R	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	8.0	7.5	7.5	6.5	6.5	10.0	10.0	10.0	
5 1			2	55	14300	RIDE	8.1	7.8	7.9	7.4	6.9	6.5	6.4*	6.8	6.3*	5.8*	7.2	7.1	7.2	
					9.9															
4146481	5.465	5.977	C	2008	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.8	5.5*
THE DE MOYA GROUP INC.				(2010)	FC5	RIDE	7.2	7.2	7.2	7.1	7.2	7.1	6.6	6.7	6.7	6.8	6.8	6.8	6.7	6.5
4478061	5.465	7.283	C	2024	0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = THE DE MOYA GROUP INC. ----------

```
RDWYID        BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

90030000   6.129  7.282  C    1      1 CRACKING  7.5   7.5   7.0   6.5   6.5   5.5*  3.5*  3.5*  3.5*  3.5* 10.0  10.0  10.0
5    1                   2   55  14000 RIDE      8.2   8.6   8.3   7.7   7.5   7.4   7.5   7.1   7.0   6.8   7.5   7.5   7.6
                                   9.9
4146481    5.977  7.284  C 2008   0012 CRACKING 10.0  10.0  10.0   9.0   9.0   8.0   8.0   8.0   6.5   6.5   6.5   6.5   6.5   4.5*
THE DE MOYA GROUP INC.    (2010) FC5   RIDE      7.7   7.6   7.6   7.7   7.7   7.6   7.6   7.7   7.7   7.7   7.6   7.4   7.3   7.1
4478061    5.465  7.283  C 2024   0012
-----------------------------------------------------------------------------------------------------------------------------------
90030000   5.487  6.129  L    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   7.5   7.5   7.5   6.5   6.5  10.0  10.0  10.0
5    1                   2   55  14300 RIDE      8.2   8.0   8.2   7.9   7.7   7.5   7.7   6.8   6.4*  6.2*  7.3   7.4   7.4
                                   9.9
4146481    5.465  5.977  C 2008   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.7   6.5
THE DE MOYA GROUP INC.    (2010) FC5   RIDE      7.5   7.4   7.4   7.3   7.2   7.1   7.2   7.3   7.3   7.3   7.3   7.3   7.4   7.2
4478061    5.465  7.283  C 2024   0012
-----------------------------------------------------------------------------------------------------------------------------------
90050000   0.000  0.864  C    1      1 CRACKING  6.5   6.5   5.0*  4.5*  4.5*  2.0*  1.0*  1.0*  1.0*  1.0*  1.0*  3.5* 10.0
5    1                   2   55  14500 RIDE      8.4   8.1   8.4   8.2   7.0   6.8   6.8   7.1   7.2   6.7   6.7   7.0   7.9
W OF TOMS HARBOR BRIDGE( 0.0C)      9.2
4256001    0.187  8.530  C 2013   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   8.9   7.5
THE DE MOYA GROUP INC.    (2015) FC95  RIDE      7.9   7.9   8.5   8.4   8.4   8.3   8.3   8.3   8.2   8.3   8.1   8.1   8.1   7.6

90050000   1.144  1.778  R    1      1 CRACKING  4.0*  4.0* 10.0  10.0  10.0   9.0   9.0   7.5   7.5   6.5   6.5   6.5   6.5
5    1                   1   55  14500 RIDE      8.0   8.0   8.6   8.4   7.9   7.8   7.8   7.9   7.9   7.8   7.7   7.6   7.5
                                   9.2
4256001    0.187  8.530  C 2013   0012 CRACKING  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
THE DE MOYA GROUP INC.    (2015) FC95  RIDE      7.3   7.3   7.8   7.6   7.5   7.0   7.4   7.4   7.5   7.6   7.4   7.4   7.4   6.9

90050000   1.778  3.517  C    1      1 CRACKING  4.0*  4.0* 10.0  10.0  10.0  10.0   9.0   9.0   9.0   8.0   7.5   7.5   6.5
5    1                   2   55  14500 RIDE      8.0   8.0   8.3   8.2   7.6   7.5   7.6   7.7   7.6   7.5   7.3   7.0   6.7
CORAL KEY VILLAGE( 3.2R)            9.2
4256001    0.187  8.530  C 2013   0012 CRACKING  6.5   4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0  10.0   8.5
THE DE MOYA GROUP INC.    (2015) FC95  RIDE      6.7   6.4*  8.5   8.1   8.1   7.9   7.7   7.9   7.9   7.9   7.8   7.8   7.8   7.3

90050000   5.784  8.527  C    1      1 CRACKING  3.5*  3.5* 10.0  10.0  10.0  10.0   9.0   9.0   7.5   7.0   6.5   6.5   6.5
5    1                   2   55  14500 RIDE      8.0   7.9   8.5   8.3   7.7   7.8   7.7   7.8   7.8   7.6   7.4   7.2   6.9
LAYTON CITY LIMITS( 8.4R)           9.2
4256001    0.187  8.530  C 2013   0012 CRACKING  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
THE DE MOYA GROUP INC.    (2015) FC95  RIDE      6.9   6.7   8.6   8.1   8.0   8.0   8.0   7.9   7.9   7.8   7.7   7.7   7.7   7.2
-----------------------------------------------------------------------------------------------------------------------------------
90050000   1.144  1.778  L    1      1 CRACKING  4.0*  4.0* 10.0  10.0  10.0   9.0   9.0  10.0  10.0   9.5   9.0   9.0   9.0
5    1                   1   55  14500 RIDE      8.0   8.0   8.6   8.4   7.9   7.8   7.8   8.2   8.2   7.8   7.9   8.0   8.0
                                   9.2
4256001    0.187  8.530  C 2013   0012 CRACKING  9.0   9.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
THE DE MOYA GROUP INC.    (2015) FC95  RIDE      8.0   7.9   8.3   7.9   8.0   7.9   7.9   8.0   7.9   7.9   7.9   7.8   7.9   7.4
-----------------------------------------------------------------------------------------------------------------------------------
90060000  13.135 16.313  C    1      1 CRACKING  7.5   7.0   7.0   6.5   6.5   4.5*  4.5*  4.5*  4.5*  4.5* 10.0  10.0  10.0
5    1                   2   45  30000 RIDE      8.5   8.5   8.5   8.1   7.4   7.4   7.5   7.4   7.3   7.0   7.6   7.6   7.6
FRONTAGE RD(13.5R)                  9.9
4146491   13.027 16.322  C 2008   0012 CRACKING 10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   6.5   4.5*  4.5*  4.5*  4.5*  2.5*
THE DE MOYA GROUP INC.    (2010) FC5M  RIDE      7.7   7.6   7.6   7.7   7.7   7.6   7.5   7.7   7.6   7.6   7.5   7.5   7.5   7.3
4478101   13.459 16.412  C 2028   0012
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = THE STOUT GROUP LLC ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                                                                              (PMRS)


87017000   0.000  0.145  C    1      6 CRACKING  9.5   9.5   9.5   9.5   9.0   9.0   9.5   9.0   9.5   9.0   9.5   9.0   9.0
913                     4   30  19000 RIDE      6.7   5.9*  4.3*  5.7   5.0*  4.5*  4.7*  5.1*  4.7*  5.4*
SW 1 AVE( 0.0C)                  2.7
4291491    0.000  0.161  C 2015   0015 CRACKING  9.0   9.0   9.0         9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.5   7.5
THE STOUT GROUP LLC       (2017)       RIDE
4459951    0.010  0.363  C 2024   0012
-------------------------------------------------------------------------------------------------------------------------------------------
87027000   0.000  0.479  R    1      1 CRACKING 10.0  10.0  10.0   9.5   9.5   9.5   9.5   7.0   6.5   6.5  10.0  10.0  10.0
969                     3   40  24500 RIDE      8.0   7.2   7.4   5.4*  5.2*  5.2*  5.5   5.5   5.6   5.8   7.7   7.2   7.5
FLAGLER ST( 0.0C)                10.0
4293453    0.019  0.436  C 2021   0012 CRACKING 10.0  10.0  10.0   6.5   6.5   6.5   6.5   6.5   5.5*  5.5* 10.0  10.0   9.2   8.5
THE STOUT GROUP LLC       (2023) FC125 RIDE      7.7   7.7   7.7   7.4   6.9   7.1   7.2   6.8   6.9   7.6   6.9   7.2   7.5   7.0
-------------------------------------------------------------------------------------------------------------------------------------------
87027000   0.000  0.479  L    1      1 CRACKING 10.0  10.0  10.0   9.5   9.5   9.5   9.5   9.5   7.0   7.0  10.0  10.0  10.0
969                     3   40  24500 RIDE      7.5   7.6   7.2   7.5   5.7   6.0   5.7   6.5   6.2   6.6   7.1   7.6   7.0
FLAGLER ST( 0.0C)                10.0
4293453    0.019  0.436  C 2021   0012 CRACKING 10.0  10.0  10.0   9.0   9.0   9.0   6.5   6.5   5.5*  5.5* 10.0  10.0  10.0   9.0
THE STOUT GROUP LLC       (2023) FC125 RIDE      7.6   7.6   7.6   7.8   7.0   7.3   7.5   7.3   7.2   7.6   7.9   7.7   7.8   7.3
-------------------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = TRANS FLORIDA DEVELOPMENT CO ----------

RDWYID SR US INTERSECT AT (MP|SIDE) ITMSEG-P CONTRACTOR (AGE_ONE YEAR) ITMSEG-F	BMP G_BMP W_BMP SURF_TYPE W_BMP	EMP G_EMP W_EMP W_EMP	RW LN RW RW	SYSTEM SPEED FY-P FY-F	TYPE AADT %T WKMX-P WKMX-F	DISTRESS RATINGS ======== 	SURVEYED YEAR 2000 2013	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2030 (PMRS)
87020000	5.278	7.001	R	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	6.5	6.5	6.5	6.5	6.5			
5 1			2	45	43000	RIDE	8.1	8.1	8.1	5.8*	7.4	7.2	7.2	7.3	7.3	7.1	7.0			
SW 284 ST(5.4R)					4.2															
4106252	5.278	7.001	C	2010	0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0
TRANS FLORIDA DEVELOPMENT (2013) FC5						RIDE	7.5	7.5	7.6	7.7	7.7	7.7	7.4	7.7	7.6	7.4	7.6	7.4	7.6	7.4
87020000	5.278	7.001	L	1	1	CRACKING	6.5	6.0*	6.0*	5.5*	5.5*	4.0*	4.0*	4.0*	4.0*	3.5*	3.5*			
5 1			2	45	43000	RIDE	8.5	8.5	8.3	8.1	7.4	7.2	7.2	7.0	7.0	6.9	6.8			
SW 284 ST(5.4L)					4.2															
4106252	5.278	7.001	C	2010	0005	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	8.3	6.5
TRANS FLORIDA DEVELOPMENT (2013) FC5						RIDE	7.5	7.6	7.6	7.8	7.8	7.8	7.3	7.7	7.5	7.6	7.5	7.4	7.2	7.0

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = WEEKLEY ASPHALT PAVING, INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)              %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87001000   2.716  4.846  R    1      1 CRACKING 10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   8.0   8.0
94                      3   45  48000 RIDE      8.5   8.5   8.5   8.3   7.8   7.7   7.6   7.9   7.8   7.6   7.5   7.5   7.4
SW 149 AVE( 2.9R)                   3.3
4332643    2.730  4.822  R 2021   0012 CRACKING  8.0   8.0   8.0   6.5   6.5   6.5   6.5   4.5*  4.5*  4.5* 10.0  10.0   9.6   9.0
WEEKLEY ASPHALT PAVING, IN(2023) FC95M RIDE      7.4   7.4   7.2   7.4   7.1   7.3   6.7   7.3   7.4   7.1   7.6   7.6   7.5   7.0
-----------------------------------------------------------------------------------------------------------------------------------
87001000   2.716  4.716  L    1      1 CRACKING 10.0  10.0  10.0  10.0   9.0   9.0   9.0   9.0   8.5   8.5   8.5   8.5   8.0
94                      3   45  48000 RIDE      8.3   8.1   8.2   8.1   7.7   7.6   7.2   7.4   7.4   7.4   7.4   7.2   7.2
SW 149 AVE( 2.9L)                   3.3
4332643    2.730  4.828  L 2021   0012 CRACKING  8.0   8.0   7.0   6.5   6.5   6.5   4.5*  3.5*  3.5*  3.5* 10.0  10.0   9.6   9.0
WEEKLEY ASPHALT PAVING, IN(2023) FC95M RIDE      7.2   7.1   7.1   7.1   6.9   6.9   6.8   6.9   6.9   6.8   7.4   7.5   7.4   6.9
-----------------------------------------------------------------------------------------------------------------------------------
87002000   7.777  9.459  R    1      1 CRACKING  7.5   7.5   7.5   7.5   7.5   7.5   7.5   7.5  10.0  10.0  10.0  10.0  10.0
823                     3   45  51000 RIDE      8.1   8.3   8.0   7.9   7.6   7.3   7.1   6.9   7.6   7.4   7.4   7.5   7.4
NW 189 ST( 7.9C)                    4.0
4146171    7.781  9.699  C 2005   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   9.0   9.0   6.5   7.5   6.9   4.5*
WEEKLEY ASPHALT PAVING, IN(2008) FC5   RIDE      7.4   7.4   7.3   7.3   7.1   7.0   7.0   6.8   7.1   7.0   7.0   6.8   6.9   6.7
4525671    7.752  9.399  C 2028   0012
-----------------------------------------------------------------------------------------------------------------------------------
87002000   7.777  9.459  L    1      1 CRACKING  7.5   7.5   7.5   6.5   6.5   6.5   6.5   6.5  10.0  10.0  10.0  10.0  10.0
823                     3   45  51000 RIDE      8.1   8.1   7.9   8.2   7.5   7.4   7.2   7.0   6.8   6.7   6.9   6.8   6.7
NW 189 ST( 7.9C)                    4.0
4146171    7.781  9.699  C 2005   0012 CRACKING 10.0  10.0   9.5   9.0   9.0   9.0   9.0   9.0   9.0   9.0   6.5   7.5   6.5   4.0*
WEEKLEY ASPHALT PAVING, IN(2008) FC5   RIDE      6.7   6.6   6.7   6.6   6.6   6.5   6.5   6.4   6.6   6.4   6.5   6.5   6.4   6.2
4525671    7.752  9.399  C 2028   0012
-----------------------------------------------------------------------------------------------------------------------------------
87008000   5.102  7.114  C    1      1 CRACKING  9.0   9.0   9.0   9.0   9.0   9.0   9.0   9.0   7.5   6.5   6.5   6.5   6.5
916                     3   40  15000 RIDE      7.7   7.6   7.6   7.2   6.7   6.4   6.5   6.4   6.6   6.4   6.1   6.4   6.4
NW 26 CT( 5.1R)                     5.1
4291461    5.102  7.007  C 2014   0012 CRACKING  6.5   6.5   6.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
WEEKLEY ASPHALT PAVING, IN(2016) FC95A RIDE      5.7   5.7   5.5   7.5   7.4   7.4   7.4   7.2   7.3   7.0   7.3   7.0   7.1   6.6
-----------------------------------------------------------------------------------------------------------------------------------
87019000   2.977  4.007  R    1      1 CRACKING  7.0   7.0   7.0   7.0   7.0   7.0   7.0   7.0   6.5   6.5   6.5   4.5*  4.5*
817                     3   45  45000 RIDE      8.3   8.3   8.4   8.2   7.7   7.6   7.4   7.4   7.4   7.6   7.6   7.4   7.4
NW 187 ST( 3.0R)                    8.8
4291861    2.977  4.007  C 2014   0012 CRACKING  4.5*  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.1   8.0
WEEKLEY ASPHALT PAVING, IN(2016) FCA   RIDE      7.4   7.3   7.3   8.3   8.2   8.2   8.0   8.0   8.0   8.1   8.0   7.7   7.7   7.2

87019000   4.007  4.866  R    1      1 CRACKING  7.0   7.0   7.0   7.0   7.0   7.0   7.0   7.0   6.5  10.0  10.0  10.0  10.0
817                     3   45  45000 RIDE      8.3   8.3   8.4   8.2   7.7   7.6   7.4   7.4   7.4   7.1   7.3   7.0   7.0
NW 203 ST( 4.1R)                    8.8
4291863    4.007  4.853  C 2022   0012 CRACKING 10.0  10.0   9.0   6.5   6.5   3.5*  0.0*  0.0*  0.0*  0.0*        10.0   9.6   9.0
WEEKLEY ASPHALT PAVING, IN(2024) FC95M RIDE      7.2   7.1   7.1   7.1   7.2   7.0   6.9   6.8   7.2   7.0         7.0   6.9   6.4
-----------------------------------------------------------------------------------------------------------------------------------
87019000   4.007  4.866  L    1      1 CRACKING  8.5   8.5   8.5   7.5   7.5   7.5   7.0   7.0   7.0  10.0  10.0  10.0  10.0
817                     3   45  45000 RIDE      8.3   8.5   8.2   8.2   7.7   7.2   7.0   6.8   7.0   7.1   7.1   6.7   6.8
NW 207 ST( 4.4C)                    8.8
4291863    4.007  4.853  C 2022   0012 CRACKING 10.0  10.0   9.0   6.5   6.5   3.5*  0.0*  0.0*  0.0*  0.0*        10.0   9.5   9.0
WEEKLEY ASPHALT PAVING, IN(2024) FC95M RIDE      7.1   7.2   7.0   7.1   7.1   6.6   6.8   5.7   6.7   6.7         7.2   6.8   6.3

87019000   2.977  4.007  L    1      1 CRACKING  8.5   8.5   8.5   7.5   7.5   7.5   7.0   7.0   7.0   6.5   6.5   4.5*  4.5*
817                     3   45  45000 RIDE      8.3   8.5   8.2   8.2   7.7   7.2   7.0   6.8   7.0   7.2   7.0   7.2   7.1
NW 191 ST( 3.2C)                    8.8
4291861    2.977  4.007  C 2014   0012 CRACKING  4.5*  4.5*  4.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
WEEKLEY ASPHALT PAVING, IN(2016) FC95A RIDE      6.9   7.1   6.8   8.5   8.4   8.4   8.1   8.3   8.3   8.3   8.3   7.9   7.9   7.4
-----------------------------------------------------------------------------------------------------------------------------------
87020000  15.240 17.386  R    1      1 CRACKING 10.0  10.0  10.0   9.5   9.5   9.5   9.5   8.0   6.5   6.5   6.5   6.5   6.5
5    1                  3   45  60500 RIDE      8.6   8.6   8.6   8.4   7.9   7.8   7.7   7.8   7.9   7.8   7.7   7.6   7.5
COLONIAL DR(15.5C)                  7.2
4253481   15.265 17.408  R 2012   0012 CRACKING  6.5  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5
WEEKLEY ASPHALT PAVING, IN(2014) FC95  RIDE      7.3   8.0   7.9   7.9   7.8   7.8   7.5   7.6   7.7   7.6   7.6   7.7   7.6   7.1
-----------------------------------------------------------------------------------------------------------------------------------
87020000  15.240 17.386  L    1      1 CRACKING  9.0   8.5   8.5   7.5   7.0   7.0   7.0   6.5   4.5*  4.5*  4.5*  4.5*  4.5*
5    1                  3   45  60500 RIDE      8.7   8.6   8.3   8.3   7.8   7.7   7.6   7.6   7.7   7.6   7.5   7.3   7.0
BEG SECTION 87020001(15.3L)         7.2
4253481   15.265 17.408  L 2012   0012 CRACKING  3.5* 10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5   8.5   8.5   8.5   8.6   7.0
WEEKLEY ASPHALT PAVING, IN(2014) FC95  RIDE      6.9   8.0   7.9   7.9   7.9   7.8   7.4   7.7   7.6   7.6   7.6   7.5   7.6   7.1
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = WEEKLEY ASPHALT PAVING, INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM SPEED / WKMX-P / SURF_TYPE / WKMX-F	TYPE AADT / %T	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
87026000	5.529	6.470	R	1	1	CRACKING	8.5	8.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0															
860			3	40	43000	RIDE	6.3*	7.2	5.7	5.7	6.9	6.9	6.4	7.0	7.1	6.4	6.6	6.7	6.3														
END FRONTAGE RD(5.6R)					4.0																													
4124721	5.561	6.601	C	2005	0012	CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.0	8.0	8.0	8.0	8.0	8.3	6.5														
WEEKLEY ASPHALT PAVING,			IN(2007)		FC95	RIDE	6.5	6.0	6.3	6.4	6.3	6.0	6.1	6.2	6.0	5.8	6.2	5.9	6.0	5.5														
4478011	5.505	6.474	C	2025	0012																													
87026000	5.529	6.470	L	1	2	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0															
860			3	40	43000	RIDE	7.7	8.1	7.9	7.9	7.0	6.9	6.6	7.7	7.9	8.0	8.0	7.9	7.7															
MIAMI GARDENS DR(5.6L)					4.0																													
4124721	5.561	6.601	C	2005	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.6	6.5														
WEEKLEY ASPHALT PAVING,			IN(2007)		FC95	RIDE	7.6	7.5	7.4	7.5	7.4	7.5	6.9	7.3	7.2	7.2	7.0	7.0	6.4	5.9														
4478011	5.505	6.474	C	2025	0012																													
87026005	0.767	3.664	R	1	1	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	7.0	7.0	6.5	6.5	10.0															
860			2	40	38000	RIDE	6.7	6.7	6.3	6.0	6.0	6.0	5.8	5.2*	5.7	5.8	5.8	5.7	7.4															
NW 84 CT(0.8R)					4.0																													
4077361	0.767	2.543	C	2010	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	8.5	9.0	7.5														
WEEKLEY ASPHALT PAVING,			IN(2012)		FC95	RIDE	7.5	7.4	7.3	7.0	7.1	7.0	6.9	7.0	6.9	6.8	6.8	6.8	6.4	5.9														
87026005	0.767	3.664	L	1	1	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	4.5*	10.0															
860			2	40	38000	RIDE	6.8	6.6	6.5	6.4	6.0	6.1	6.0	5.7	5.9	6.0	6.0	6.0	7.6															
IBIS VILLA S ENT(0.8L)					4.0																													
4077361	0.767	2.543	C	2010	0012	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	7.5	7.5	7.5	7.5	8.7	7.0														
WEEKLEY ASPHALT PAVING,			IN(2012)		FC95	RIDE	7.5	7.5	7.3	7.1	7.1	7.0	6.9	6.9	6.9	6.9	6.9	6.9	6.4	5.9														
87030000	24.278	24.907	R	1	1	CRACKING	7.0			10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	7.0	7.0															
5 1			4	45	56000	RIDE	7.3			8.1	7.3	7.1	7.1	7.2	7.6	7.5	7.4	7.2	7.0															
AVENTURA BLVD(24.3R)					2.1																													
4146243	24.354	24.927	R	2015	0012	CRACKING	7.0	7.0	7.0	7.0	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5														
WEEKLEY ASPHALT PAVING,			IN(2018)		FC95A	RIDE	6.9	7.1	6.9	6.5	5.9	7.9	7.7	7.7	7.7	7.4	7.7	7.7	7.5	7.0														
87030000	24.907	25.402	R	1	1	CRACKING	7.0	7.0	6.5	6.5	6.5	6.5		10.0	10.0	10.0	10.0	10.0	10.0															
5 1			3	45	56000	RIDE	7.3	8.0	8.5	7.9	7.4	7.3		8.1	7.8	8.0	7.5	7.7	7.6															
NE 209 ST(25.0C)					2.1																													
4146243	24.927	25.464	R	2015	0012	CRACKING	9.0	9.0	9.0	9.0	9.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0															
WEEKLEY ASPHALT PAVING,			IN(2018)		FC95A	RIDE	7.6	7.3	7.3	7.2	7.3	7.8	7.7	7.2	7.6	7.7	7.7	7.6	6.8	6.3														
87030000	24.278	25.402	L	1	1	CRACKING	9.0			10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0															
5 1			3	45	56000	RIDE	8.2			7.8	7.4	7.5	7.5	7.4	7.4	7.7	7.6	7.2	6.9															
SPUR(24.6L)					2.1																													
4146243	24.278	25.464	L	2015	0012	CRACKING	8.0	8.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0														
WEEKLEY ASPHALT PAVING,			IN(2018)		FC95A	RIDE	6.8	6.6	6.6	7.2	6.5	8.1	8.1	8.1	7.8	8.1	8.3	7.8	7.9	7.4														
87034000	3.641	5.867	C	1	1	CRACKING	10.0	10.0	9.0	9.0	9.0	8.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5															
915			4	40	26000	RIDE	7.8	7.4	7.2	7.7	6.6	6.5	6.5	6.1	6.2	6.1	6.2	6.0	6.0															
NE 147 ST(3.7L)					2.0																													
4226201	3.641	5.867	C	2013	0012	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	8.7	7.5														
WEEKLEY ASPHALT PAVING,			IN(2015)		FC95	RIDE	6.0	5.7	6.9	6.7	6.4	6.5	6.1	6.2	6.1	6.2	5.9	5.7	5.8	5.3*														
87040102	0.000	0.506	C	1	1	CRACKING																												
925			4	30	17500	RIDE																												
MIAMI CITY LIMITS(0.0C)					2.2																													
4293004	0.138	0.403	C	2020	0012	CRACKING				4.5*	4.5*	4.5*	4.5*	3.5*	3.5*	10.0	10.0	10.0	8.9	8.0														
WEEKLEY ASPHALT PAVING,			IN(2022)		FC95M	RIDE				3.7*	3.5*	3.9*	3.5*	3.4*	3.3*	5.2*	4.4*	4.6*	4.4*	3.9*														
87053000	0.000	1.183	R	1	1	CRACKING	9.0	9.0	9.0	8.0	9.0	9.0	7.5	7.5	6.5	4.5*	4.5*	4.5*																
968			3	40	52500	RIDE	7.1	7.4	7.6	7.1	6.9	6.3	6.1	6.4	6.5	6.4	6.4	6.3																
GALLOWAY RD(0.0C)					8.9																													
4198501	0.000	1.119	C	2010	0015	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.8	7.5														
WEEKLEY ASPHALT PAVING,			IN(2013)		DGFC	RIDE	6.9	6.7	6.6	7.5	7.1	7.2	7.4	7.4	7.3	7.2	6.9	7.0	6.8	6.3														
87053000	0.000	1.183	L	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	9.5	6.5	6.5	4.5*	4.5*	4.5*																
968			3	40	52500	RIDE	8.3	8.2	7.8	8.1	7.4	7.2	7.1	6.5	7.1	7.0	6.5	6.6																
GALLOWAY RD(0.0C)					8.9																													
4198501	0.000	1.119	C	2010	0015	CRACKING	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.5	7.0														
WEEKLEY ASPHALT PAVING,			IN(2013)		DGFC	RIDE	7.1	6.8	6.7	7.1	7.1	6.9	7.1	7.3	7.3	7.3	7.0	7.3	6.7	6.2														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = WEEKLEY ASPHALT PAVING, INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW LN / RW FY-P / FY-F	SYSTEM / SPEED / SURF_TYPE	TYPE / AADT / %T / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000 / 2013	2001 / 2014	2002 / 2015	2003 / 2016	2004 / 2017	2005 / 2018	2006 / 2019	2007 / 2020	2008 / 2021	2009 / 2022	2010 / 2023	2011 / 2024	2012 / 2025	FUTURE 2030 (PMRS)
87060000	4.663	4.814	C	1	6	CRACKING	7.5	7.5	10.0	9.5	9.5	9.5	9.5	8.0	7.0	6.5	6.5	10.0	10.0	
A1A			4	30	21000	RIDE	5.5*	4.5*	5.1*	4.9*	5.4*	4.8*	4.5*	5.1*	4.3*	4.5*	3.9*	5.4*	6.0	
HOTEL ENTRANCE(4.7R)					25.2															
4180671	4.584	4.800	C	2009	0015	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.5	6.0*	6.0*	5.3*	3.5*
WEEKLEY ASPHALT PAVING,			IN(2011)		FC95	RIDE	5.8	5.4*												
87060000	9.775	11.691	C	1	1	CRACKING	10.0	10.0	10.0	9.5	9.5	9.5	7.0	7.0	6.5	6.5	6.5	4.5*	4.5*	
A1A			3	30	20500	RIDE	8.1	7.6	7.1	7.2	6.3	5.9	6.1	6.1	6.2	6.0	6.0	6.0	5.7	
76 ST(9.8C)					10.9															
4198581	9.775	11.769	C	2012	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.0	8.0	8.5	7.0
WEEKLEY ASPHALT PAVING,			IN(2014)		FC95	RIDE		7.1	7.1	6.6	6.4	6.3	6.1	5.7	5.9	5.8	5.7	5.6	5.5	5.0*
87060000	11.691	12.386	R	1	1	CRACKING	10.0	9.5	9.5	9.5	9.5	10.0	10.0	10.0	7.0	7.0	7.0	7.0	7.0	
A1A			3	30	44000	RIDE	8.2	8.2	8.1	8.0	7.4	6.4	5.9	5.7	5.6	5.5	5.8	5.8	5.5	
SAINT REGIS(11.7R)					3.4															
4291441	11.750	12.302	R	2013	0012	CRACKING	7.0	7.0	10.0	10.0	10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	8.1	7.0
WEEKLEY ASPHALT PAVING,			IN(2015)		FC95	RIDE	5.0*	5.3*	6.6	6.3	5.7	5.8	5.8	5.6	5.5	5.4*	5.3*	5.2*	4.9*	4.4*
87060000	11.691	12.386	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	6.5	6.5	6.5	6.5	6.5	
A1A			3	30	44000	RIDE	8.6	8.5	8.5	8.3	7.7	7.7	7.5	7.2	7.6	7.5	7.5	7.3	7.0	
BAL HARBOUR(11.7L)					3.4															
4291441	11.750	12.302	L	2013	0012	CRACKING	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.1	8.0
WEEKLEY ASPHALT PAVING,			IN(2015)		FC95	RIDE	7.1	7.0	7.2	6.9	6.9	6.5	6.2	6.0	5.9	6.1	5.8	5.6	5.8	5.3*
87060001	1.947	2.498	C	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	7.0	6.5	
A1A			3	30	24000	RIDE	7.6	7.5	6.9	6.7	6.1	5.7	5.6	6.0	6.3	5.9	6.2	5.6	5.7	
74 ST(2.0C)					7.5															
4198581	1.855	2.590	C	2012	0012	CRACKING	6.5	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.5	8.5	8.5	8.5	8.6	7.0
WEEKLEY ASPHALT PAVING,			IN(2014)		FC95	RIDE	5.5	7.0	6.5	6.2	6.1	5.7	5.0*	4.4*	4.6*	4.4*	4.2*	3.8*	4.1*	3.6*
4438991	0.045	2.476	C	2023	0012															
87066000	5.245	5.548	C	1	6	CRACKING	9.0	9.0		10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	7.5	6.5	
922			4	30	29500	RIDE	4.9*	4.4*		5.5	5.3*	4.7*	4.3*	4.2*	4.2*	4.2*	3.9*	3.5*	3.7*	
BAY DR(5.3R)					7.6															
4274211	5.176	5.480	C	2013	0012	CRACKING	7.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	7.5	7.2	6.0*
WEEKLEY ASPHALT PAVING,			IN(2015)		FC125	RIDE	2.9*	3.6*	5.1*											
87080000	0.000	0.676	C	1	1	CRACKING	5.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	7.5	7.5	7.5	7.0	
934			4	35	26000	RIDE	7.1	7.0	7.1	6.4		6.4	6.5	6.0	7.5	6.3	6.6	6.4	6.6	
BISCAYNE BLVD(0.0C)					9.7															
4274521	0.000	0.662	C	2014	0012	CRACKING	7.0	7.0	6.0*		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.0	8.0
WEEKLEY ASPHALT PAVING,			IN(2017)		FC95A	RIDE	6.4	6.2	6.0		7.9	7.8	7.8	6.9	6.9	7.2	6.8	6.7	6.7	6.2
87080000	0.676	2.678	R	1	1	CRACKING	8.0	8.0	7.5	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	4.5*	4.5*	3.5*	
934			3	30	44000	RIDE	7.8	7.8	7.5	7.4	6.8	6.7	6.6	6.3	6.8	6.6	6.5	6.4	6.3	
EB EXIT TO BAYSHORE CT(0.7R)					3.6															
4311801	0.676	2.678	C	2015	0012	CRACKING	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	9.5	9.5	9.0	9.0	8.8	7.5
WEEKLEY ASPHALT PAVING,			IN(2017)		FC95M	RIDE	6.2	6.2	6.3	6.0	8.0	7.6	7.8	7.5	7.6	7.7	7.6	7.3	7.4	6.9
87080000	0.676	2.678	L	1	1	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	8.0	7.0	6.5	6.5	6.5	6.5	4.5*	
934			3	35	44000	RIDE	7.6	7.7	7.7	7.3	6.9	6.7	6.5	6.5	6.6	6.0	6.3	6.1	5.7	
TRN LN TO BAYSHORE(0.7L)					3.6															
4311801	0.676	2.678	C	2015	0012	CRACKING	4.5*	4.5*	4.5*	4.5*	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.0	8.0
WEEKLEY ASPHALT PAVING,			IN(2017)		FC95M	RIDE	5.7	5.5	5.5	5.7	7.9	7.6	7.7	7.0	7.5	7.5	7.0	7.3	7.4	6.9
87080900	33.196	33.627	R	1	2	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0	
934			2	35	30500	RIDE	6.7	6.4*	6.4	6.3	5.6	5.8	5.3*	5.4*	5.5		6.7	7.0	6.4	
W 3 AVE(33.3R)					13.3															
4180661	33.196	34.211	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	5.5*
WEEKLEY ASPHALT PAVING,			IN(2010)		FC95	RIDE	6.1	6.3	5.9	5.4*	5.6	5.7	5.3*	5.0*	5.1*	5.0*	4.9*	4.5*	5.2*	4.7*
4439091	33.196	34.211	C	2024	0012															
87080900	33.627	34.211	R	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5		10.0	10.0	10.0	
934			2	35	30500	RIDE	6.7	7.6	7.5	7.0	7.2	7.3	7.1	6.5	7.2		7.3	7.3	7.3	
SIDE ROAD(33.6C)					13.3															
4180661	33.196	34.211	C	2008	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*
WEEKLEY ASPHALT PAVING,			IN(2010)		FC95	RIDE	6.8	6.8	6.4	6.5	6.6	6.1	6.2	5.9	6.0	6.0	5.8	5.3*	5.7	5.2*
4439091	33.196	34.211	C	2024	0012															

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = WEEKLEY ASPHALT PAVING, INC. ----------

RDWYID / SR US / INTERSECT AT (MP|SIDE) / ITMSEG-P / CONTRACTOR (AGE_ONE YEAR) / ITMSEG-F	BMP / G_BMP / W_BMP	EMP / G_EMP / W_EMP	RW / LN / RW	SYSTEM / SPEED / FY-P / FY-F	TYPE / AADT / %T / SURF_TYPE / WKMX-P / WKMX-F	DISTRESS RATINGS ========	SURVEYED YEAR 2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	FUTURE 2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2030 (PMRS)
87080900	37.987	38.617	R	1	6	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	6.5		10.0	10.0															
934			2	40	27000	RIDE	5.7*	6.3*	6.3	5.0*	4.7*	5.4*	5.2*	5.2*	5.4*	5.7		6.4	6.1															
NW 10 AVE(38.2R)					9.7																													
4274521	38.069	38.557	C	2014	0012	CRACKING	8.5	8.5	8.5		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.8	7.5														
WEEKLEY ASPHALT PAVING,			IN(2017)		FC95A	RIDE	6.3	6.3	6.1		6.9																							
87080900	38.617	40.027	C	1	6	CRACKING	7.5	6.5	6.5	6.5	6.5	6.5	3.5*	4.5*	3.5*	3.5*	3.5*	3.5*	3.5*															
934			4	35	27400	RIDE	7.1	7.0	7.2	6.7	5.7	5.7	5.6	5.2*	5.9	5.5	5.7	5.5	5.4*															
MIDAS ENTRANCE(38.6L)					9.7																													
4274521	38.557	40.027	C	2014	0012	CRACKING	3.5*	3.5*	2.5*		10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.8	7.5														
WEEKLEY ASPHALT PAVING,			IN(2017)		FC95A	RIDE	5.2*	5.3*	5.4*																									
87080900	37.987	38.617	L	1	6	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.0	7.0	7.0		10.0	10.0															
934			2	40	27000	RIDE	6.8	6.3*	6.4	6.4	4.9*	6.8	6.2	6.8	6.7	6.2		6.4	6.1															
ELEVENTH CT NW(38.0L)					9.7																													
4274521	38.069	38.557	C	2014	0012	CRACKING	8.5	8.5	8.5		10.0	10.0	10.0	10.0	8.0	8.0	8.0	8.0	8.4	7.0														
WEEKLEY ASPHALT PAVING,			IN(2017)		FC95A	RIDE	6.3	6.3	6.1		6.9																							
87080900	33.627	34.211	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5		10.0	10.0	10.0															
934			2	35	30500	RIDE	6.7	5.9*	5.7	5.4*	4.9*	5.3*	5.0*	4.7*	5.4*		7.5	7.4	6.7															
SIDE ROAD(33.6C)					13.3																													
4180661	33.196	34.211	C	2008	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*														
WEEKLEY ASPHALT PAVING,			IN(2010)		FC95	RIDE	6.6	6.6	6.9	5.8	5.7	5.9	6.1	5.9	5.5	5.6	5.4*	5.5	5.2*	4.7*														
4439091	33.196	34.211	C	2024	0012																													
87080900	33.196	33.627	L	1	1	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		10.0	10.0	10.0															
934			2	35	30500	RIDE	6.9	7.2	6.8	6.7	4.5*	5.1*	4.7*	5.4*	5.3*		5.8	5.9	5.1*															
W 3 AVE(33.3L)					13.3																													
4180661	33.196	34.211	C	2008	0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	8.8	7.0														
WEEKLEY ASPHALT PAVING,			IN(2010)		FC95	RIDE	5.7	5.9	5.9	5.8	5.6	4.9*	5.5	4.7*	4.8*	5.3*	4.9*	5.0*	4.9*	4.4*														
4439091	33.196	34.211	C	2024	0012																													
87140000	5.610	6.211	R	1	1	CRACKING	6.5	6.5	4.5*	4.5*		10.0	9.0	9.0	8.0	8.0	8.0	8.0	8.0															
7	441		3	35	32000	RIDE	7.0	6.8	4.8*	7.3		6.9	6.4	7.1	6.4	6.2	6.4	6.2	6.1															
SR 934(5.6C)					4.7																													
4308172	5.657	6.214	C	2018	0012	CRACKING	8.0	8.0	8.0	8.0	8.0	8.0	8.0			10.0	10.0	10.0	9.1	8.5														
WEEKLEY ASPHALT PAVING,			IN(2022)		FC95M	RIDE	6.1	6.1	6.1	5.0*	5.1*	5.4*	5.2*			6.7	6.4	6.3	6.4	5.9														
87140000	5.610	6.211	L	1	1	CRACKING	4.5*	4.5*	4.5*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0															
7	441		3	35	32000	RIDE	5.3*	5.2*	4.5*	3.5*		6.3	6.1	6.1	6.1	6.0	6.0	6.0	5.8															
SR 934(5.6C)					4.7																													
4308172	5.657	6.214	C	2018	0012	CRACKING	9.5	9.5	9.5	9.5	9.5	9.5	9.5			10.0	10.0	10.0	9.0	8.0														
WEEKLEY ASPHALT PAVING,			IN(2022)		FC95M	RIDE	5.8	5.4*	5.3*	5.3*	5.6	5.3*	5.1*			6.2	6.2	5.7	5.9	5.4*														
87170000	0.373	3.701	R	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	10.0	10.0	10.0	10.0	10.0															
826			3	35	57000	RIDE	8.1	8.2	8.1	8.1	7.4	7.3	7.2	7.4	8.1	7.8	7.9	7.7	7.7															
TN LN TO NW 2 AVE(0.5R)					3.4																													
4126372	2.015	3.557	C	2006	0012	CRACKING	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.3	6.5														
WEEKLEY ASPHALT PAVING,			IN(2008)		DGFC	RIDE	7.5	7.4	7.1	7.1	6.8	7.0	7.0	6.8	7.0	6.9	6.8	6.7	6.6	6.1														
4525611	0.512	3.667	C	2030	0012																													
87170000	0.373	3.701	L	1	1	CRACKING	10.0	10.0	10.0	9.0	9.0	9.0	9.0	7.5	10.0	10.0	10.0	10.0	10.0															
826			3	35	57000	RIDE	8.0	8.0	7.6	8.0	7.3	7.0	7.2	7.0	7.8	7.7	7.8	7.7	7.7															
TRN LN TO NW 2 AVE(0.5L)					3.4																													
4126372	2.015	3.557	C	2006	0012	CRACKING	9.0	9.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.0	7.5	8.6	7.0														
WEEKLEY ASPHALT PAVING,			IN(2008)		DGFC	RIDE	7.6	7.4	7.3	7.3	6.8	6.8	6.9	6.6	6.9	6.7	6.6	6.5	6.5	6.0														
4525611	0.512	3.667	C	2030	0012																													
87190000	0.000	0.513	R	1	7	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	10.0	10.0	10.0	10.0															
909			2	40	20500	RIDE	7.4	7.1	7.2	7.2	6.2	6.0	6.0	5.8	6.9	5.7	5.9	6.2	6.0															
NE 118 TER(0.0R)					3.5																													
4399761	0.000	0.270	R	2022	0012	CRACKING	10.0	10.0	9.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	10.0	9.5														
WEEKLEY ASPHALT PAVING,			IN(2025)		FC95M	RIDE	5.9	5.8	5.8	5.6	5.3*	5.7	5.6	5.1*	5.2*	4.9*	4.9*	4.7*	4.9*	4.4*														
87190000	0.000	0.513	L	1	7	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	10.0	10.0	10.0	9.5	9.5															
909			2	40	20500	RIDE	7.4	7.1	7.2	7.2	6.2	6.0	6.0	5.8	7.5	6.8	7.4	6.9	6.6															
SR-924/NE 119 ST(0.0L)					3.5																													
4399761	0.000	0.415	L	2022	0012	CRACKING	9.5	9.0	8.5	8.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	10.0	9.5														
WEEKLEY ASPHALT PAVING,			IN(2025)		FC95M	RIDE	6.7	6.4	6.4	5.8	5.5	5.6	5.2*	5.3*	5.0*	5.1*	4.7*	4.5*	5.4*	4.9*														

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).

FLORIDA DEPARTMENT OF TRANSPORTATION

ALL SYSTEM PAVEMENT CONDITION FORECAST

PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN -- 2026 - 2031, EXTRACTED ON 08/28/2025

SORT BY CONTRACTOR RDWYID MILEPOST R ASCENDING L DESCENDING

---------- DISTRICT = 6 CONTRACTOR = WEEKLEY ASPHALT PAVING, INC. ----------

```
RDWYID       BMP    EMP RW SYSTEM TYPE DISTRESS SURVEYED YEAR                                                                                FUTURE
 SR   US   G_BMP  G_EMP LN SPEED  AADT RATINGS  2000  2001  2002  2003  2004  2005  2006  2007  2008  2009  2010  2011  2012
INTERSECT AT (MP|SIDE)             %T ========
ITMSEG-P   W_BMP  W_EMP RW FY-P WKMX-P
CONTRACTOR (AGE_ONE YEAR)    SURF_TYPE          2013  2014  2015  2016  2017  2018  2019  2020  2021  2022  2023  2024  2025  2030
ITMSEG-F   W_BMP  W_EMP RW FY-F WKMX-F                                                                                                (PMRS)

87240000   1.739  2.985  R    1      1 CRACKING 10.0  10.0  10.0   8.5   7.0   7.0   6.5   4.5*  4.5*  4.5* 10.0  10.0  10.0
9                        3   40  38500 RIDE      8.4   8.3   8.3   8.1   7.0   6.7   6.6   6.6   6.3   6.4   7.1   6.9   6.7
SEVENTH ST SW( 1.8C)                5.7
4198471    1.739  2.975  C 2009   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0  10.0   8.5   8.5   8.5   8.6   7.0
WEEKLEY ASPHALT PAVING, IN(2010) FC95  RIDE      6.6   6.5   6.4   6.7   6.6   6.5   6.3   6.0   5.9   6.2   5.8   6.3   6.2   5.7
-----------------------------------------------------------------------------------------------------------------------------------
87240000   1.739  2.985  L    1      1 CRACKING 10.0  10.0   9.0   7.5   7.5   6.5   6.5   4.5*  4.5*  4.5* 10.0  10.0  10.0
9                        3   35  38500 RIDE      7.8   7.9   7.8   7.2   6.2   6.3   6.3   6.0   5.3*  5.6   7.1   6.7   6.8
SEVENTH ST SW( 1.8C)                5.7
4198471    1.739  2.975  C 2009   0012 CRACKING 10.0  10.0  10.0  10.0  10.0  10.0  10.0   9.0   7.5   7.5   7.5   8.0   8.7   7.0
WEEKLEY ASPHALT PAVING, IN(2010) FC95  RIDE      6.4   6.6   6.7   6.4   6.2   6.4   6.3   6.3   6.3   6.2   6.2   6.1   6.0   5.5
-----------------------------------------------------------------------------------------------------------------------------------
87250000   4.526  5.822  C    1      1 CRACKING 10.0  10.0   8.0   8.0   8.0        10.0  10.0  10.0   8.5   8.5   8.5   8.5
944                      4   40  16900 RIDE      6.1*  5.7*  5.9   5.5   5.4*        6.6   6.5   6.7   6.6   6.1   5.8   6.0
ENT FROM SR 9A( 4.6C)               1.0
4282782    4.517  5.761  C 2018   0012 CRACKING  8.5   8.5   8.5   7.0   7.0   6.5   6.5   6.5  10.0  10.0  10.0  10.0   8.8   8.0
WEEKLEY ASPHALT PAVING, IN(2021) FC95M RIDE      5.5   5.2*  5.1*  5.5   5.1*  5.2*  5.0*  4.6*  6.4   6.2   6.2   5.9   5.7   5.2*
-----------------------------------------------------------------------------------------------------------------------------------
```

"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
"*" INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@" INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2030 FORECASTED BY PAVEMARS (PMRS).