



Florida Department of Transportation

RON DESANTIS
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

KEVIN J. THIBAUT
SECRETARY

July 9, 2019

Khoa Nguyen
Director, Office of Technical Services
Federal Highway Administration
3500 Financial Plaza, Suite 400
Tallahassee, Florida 32312

Re: State Specifications Office
Section: **005**
Proposed Specification: **SP0050901 Control of the Work – General Inspection Requirements – Cooperation by the Contractor.**

Dear Mr. Nguyen:

We are submitting, for your approval, two copies of the above referenced Special Provision.

The changes are proposed by John Westphal. The deletion of the Special Provision will be addressed in Section 5-9.1.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via email to stefanie.maxwell@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at 414-4140.

Sincerely,

Stefanie D. Maxwell, P.E.
Manager, Program Management Office

SM/rf

Attachment

cc: Florida Transportation Builders' Assoc.
State Construction Engineer

**CONTROL OF THE WORK – GENERAL INSPECTION REQUIREMENTS –
COOPERATION BY THE CONTRACTOR.**

(REV ~~2-10-94~~4-1-19)(~~7-19~~)

SUBARTICLE 5-9.1 is ~~expanded by the following~~ deleted:

~~Provide and maintain throughout the life of the Contract, two utility boats meeting or exceeding the following minimum requirements:~~

| | Utility Boat |
|--|--|
| (A) Size | |
| (a) Length | 19 feet |
| (b) Width (Beam) | 7 feet |
| (c) Load Capacity | 2,400 pounds |
| (d) Cabin | |
| (1) Length | None |
| (2) Width | None |
| (3) Height | None |
| (B) Construction | |
| (a) Bottom Plating | 3/16 inch |
| (b) Side and Cabin Plating | 1/8 inch |
| (c) Deck and Cockpit | |
| Tread Plating | 1/8 inch |
| (d) Plating Material | Marine Aluminum |
| (e) Seams and Joints | Welded |
| (C) Drive Power | |
| (a) Outboard | two each, 75 HP, total 150 HP |
| (b) Inboard-Outboard | None |
| (c) Fuel Tank | Required |
| (D) Equipment | |
| (a) Mechanical Steering Control | |
| Speed Control and Light | |
| Control Systems Located | |
| Forward | Required |
| (b) Electric Start Mechanism | |
| Located Forward | Required |
| (c) Anchor and 300 foot Rope | 20 pound |
| (d) Navigation Lights | Required |
| (e) Width of Shear Line | |
| Rubber Bumper | 3 inches |
| (f) Heavy Duty Seating | |
| Accommodations | two each |

~~Furnish fuel and docking facilities for these boats. The docking facilities' location and adequacy are subject to the approval of the Engineer.~~

~~The Engineer and their staff will be permitted to travel on any or all floating equipment and boats used in the work performed.~~

SP0050901

All Jobs

———~~Include the costs of furnishing and maintaining the boats, including fuel and docking facilities, in the Contract unit prices for other items of the Contract.~~

**CONTROL OF THE WORK – GENERAL INSPECTION REQUIREMENTS –
COOPERATION BY THE CONTRACTOR.**

(REV 4-1-19)

SUBARTICLE 5-9.1 is deleted: