

ORIGINATION FORM

Proposed Revisions to the Specifications

(Please provide all information - incomplete forms will be returned)

Date:

Office:

Originator:

Specification Section:

Telephone:

Article/Subarticle:

email:

Associated Section(s) Revisions:

Will the proposed revision require changes to:

Publication	Yes	No	Office Staff Contacted
Standard Plans Index			
Traffic Engineering Manual			
FDOT Design Manual			
Construction Project Administration Manual			
Basis of Estimate/Pay Items			
Structures Design Guidelines			
Approved Product List			
Materials Manual			

Will this revision necessitate any of the following:

Design Bulletin

Construction Bulletin

Estimates Bulletin

Materials Bulletin

Are all references to external publications current?

Yes

No

If not, what references need to be updated? (Please include changes in the redline document.)

Why does the existing language need to be changed?

Summary of the changes:

Are these changes applicable to all Department jobs?

Yes

No

If not, what are the restrictions?

Contact the State Specifications Office for assistance in completing this form.

Daniel Strickland 850-414-4130 Daniel.Strickland@dot.state.fl.us Rebecca Arcia 850-414-4155 Rebecca.Arcia@dot.state.fl.us
Darla Hunsicker 850-414-4114 Darla.Hunsicker@dot.state.fl.us Valencia Cunningham 850-414-4101 Valencia.Cunningham@dot.state.fl.us



RON DESANTIS
GOVERNOR

KEVIN J. THIBAUT, P.E
SECRETARY

M E M O R A N D U M

DATE: July 1, 2021
TO: Specification Review Distribution List
FROM: Daniel Strickland, P.E., State Specifications Engineer
SUBJECT: Proposed Specification: **9970000 Traffic Monitoring Site Materials.**

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

This change was proposed by Eric Griffin from the Transportation Data and Analytics to implement a new Section in Division III for Traffic Monitoring Site Materials. The proposed specification is associated with Section 695.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or online at <http://fdotewp1.dot.state.fl.us/programmanagement/development/industryreview.aspx> . Comments received after **July 29 2021**, may not be considered. Your input is encouraged.

DS/ra

Attachment

**TRAFFIC MONITORING SITE MATERIALS
(REV 6-23-21)**

The following new Section is added after Section 996.

SECTION 997
TRAFFIC MONITORING SITE MATERIALS

997-1 Description.

This Section governs the requirements for all traffic monitoring site (TMS) material as shown in the Plans and Standard Plans.

Provide products compatible with all other TMS APL equipment. Any electronics unit or software submitted for approval must be compatible with or convert the data into a format compatible with the Department's polling and processing software. Any substitute software modules submitted must be tested and approved.

Provide products constructed of corrosion-resistant materials, such as plastic, stainless steel, anodized aluminum, brass, or gold-plated metal. All fasteners exposed to the elements shall be Type 304 or 316 passivated stainless steel.

997-1.1 Approved Product List Submittal Requirements: Manufacturers seeking evaluation of their product for inclusion on the APL shall submit an application in accordance with Section 6 including documentation identified in Table 997-1 and this Section. Documentation must demonstrate that the product meets the requirements of this Section.

<u>Table 997-1</u>	
<u>Documentation</u>	<u>Requirements</u>
<u>Technical Data Sheets</u>	<u>Provide information as required in this Section.</u>
<u>Product Label</u>	<u>Provide equipment permanently marked with manufacturer name or trademark, part number, and date of manufacture or serial number.</u>
<u>Product Sample</u>	<u>When requested, submit a product sample.</u>
<u>Installation Instructions</u>	<u>Required.</u>
<u>Product Photo</u>	<u>Display significant features of the products.</u>

997-2 Vehicle Sensors (Non-Weight).

997-2.1 General: Non-weight vehicle sensors include microwave vehicle detection system (MVDS), axle sensors, and non-motorized sensors.

997-2.2 Axle Sensor and Non-Motorized Sensor: In-Roadway axle sensors shall meet the physical characteristics in Table 997-2.

<u>Table 997-2</u> <u>Physical Characteristics, Axle Sensor</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
<u>Sensor Element Dimensions</u>	<u>Technical Data Sheet</u>	<u>Approximately 6 ft. to 10 ft. in length, 3/16 in. to 3/8 in. in diameter (varies by manufacturer)</u>
<u>Sensor Element Material</u>	<u>Technical Data Sheet</u>	<u>Pressure sensing piezoelectric</u>
<u>Pavement Operating Temperature Range</u>	<u>Technical Data Sheet</u>	<u>Minimum 0°F to +150°F</u>
<u>Output Signal</u>	<u>Technical Data Sheet</u>	<u>Minimum +200mV or produce a charge signal for passenger car/pickup truck axle @ 70°F with less than 10% negative signal for non-WIM axle sensors</u>
<u>Environmental Requirements</u>	<u>Technical Data Sheet</u>	<u>NEMA TS-2-2016, Section 3.</u>

In-Sidewalk and Shared Use Path non-motorized sensors shall meet the physical characteristics in Table 997-3.

<u>Table 997-3</u> <u>Physical Characteristics, Non-Motorized Sensor</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
<u>Sensor Element Dimensions</u>	<u>Technical Data Sheet</u>	<u>Approximately 3 ft. in length, 3/16 in. to 3/8 in. in diameter (varies by manufacturer)</u>
<u>Sensor Element Material</u>	<u>Technical Data Sheet</u>	<u>Pressure sensing piezoelectric</u>
<u>Pavement Operating Temperature Range</u>	<u>Technical Data Sheet</u>	<u>Minimum 0°F to +150°F</u>
<u>Output Signal Range</u>	<u>Technical Data Sheet</u>	<u>Minimum +34 mV (front axle) and +65mV (rear axle), 220 lb. Passenger bicycle, at 7.3 MPH</u>
<u>Environmental Requirements</u>	<u>Technical Data Sheet</u>	<u>NEMA TS-2-2016, Section 3.</u>

997-3 Weight Sensors (In-Roadway).

997-3.1 General: Weight sensors include bending plates, Class I piezoelectric sensors, and quartz piezoelectric sensors.

997-3.2 Bending Plate: Provide bending Plate Weigh-In-Motion systems that utilize plates with strain gauges bonded to the underside. The weigh pads shall meet the physical characteristics in Table 997-4.

<u>Table 997-4</u> <u>Physical Characteristics, Bending Plate, Weigh Pad</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
<u>Sensor Size</u>	<u>Technical Data Sheet</u>	<u>20 in. wide x 70 in. or 50 in. long</u>
<u>Operating Temperature Range</u>	<u>Technical Data Sheet</u>	<u>-50°F to 176°F</u>
<u>Scale Capacity</u>	<u>Technical Data Sheet</u>	<u>45000 pounds per axle and overload protected to 80000 pounds per axle</u>
<u>Environmental Requirements</u>	<u>Technical Data Sheet</u>	<u>NEMA TS-2-2016, Section 3.</u>

997-3.3 Piezoelectric Axle Sensor (Class I): Class I sensors collect Weigh-In-Motion data. The vehicle sensor shall meet the physical characteristics in Table 997-5.

<u>Table 997-5</u> <u>Physical Characteristics, Piezoelectric Axle Sensor, Class I</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
<u>Sensor Size</u>	<u>Technical Data Sheet</u>	<u>6 ft. to 8 ft.</u> <u>Flat Element 0.26 in. wide x 0.063 in. thick</u>
<u>Operating Temperature Range</u>	<u>Technical Data Sheet</u>	<u>-40°F to 160°F</u>
<u>Temperature sensitivity</u>	<u>Technical Data Sheet</u>	<u>0.2%/°F</u>
<u>Output Uniformity</u>	<u>Technical Data Sheet</u>	<u>5% to 7%</u>
<u>Output Signal</u>	<u>Technical Data Sheet</u>	<u>250 mV for 400-pound wheel load at 70 F° and 55 mph</u> <u>[250 mV for 181 kg wheel load at 21 C° and 88 kph] Minimum</u>
<u>Insulation Resistance</u>	<u>Technical Data Sheet</u>	<u>> 500 MΩ</u>
<u>Passive Signal Cable</u>	<u>Technical Data Sheet</u>	<u>RG 58 C/U with High Density Polyethylene Outer Jacket 0.187” [4.75 mm] OD</u>
<u>Center Core</u>	<u>Technical Data Sheet</u>	<u>16-gauge, flat braided, silver plated copper wire</u>
<u>Piezoelectric Material</u>	<u>Technical Data Sheet</u>	<u>Spiral Wrapped PVDF piezoelectric film</u>
<u>Cable Capacitance</u>	<u>Technical Data Sheet</u>	<u>27 pF/ft [89 pF/m]</u>
<u>Piezoelectric Coefficient</u>	<u>Technical Data Sheet</u>	<u>34 pC/N – nominal</u>
<u>Life</u>	<u>Technical Data Sheet</u>	<u>40 Million ESAL’s[Minimum]</u>
<u>Environmental Requirements</u>	<u>Technical Data Sheet</u>	<u>NEMA TS-2-2016, Section 3.</u>

997-3.4 Quartz Piezoelectric Sensor: The quartz piezoelectric sensors collect Weigh-In-Motion data. The quartz sensor shall meet the physical characteristics in Table 997-6.

<u>Table 997-6</u> <u>Physical Characteristics, Quartz Piezoelectric Sensor</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
<u>Measuring Range wheel load (At a referenced tire contact area)</u>	<u>Technical Data Sheet</u>	<u>0 to 34000 pounds (8 in. by 12.6 in.)</u>
<u>Overload (twin wheel)</u>	<u>Technical Data Sheet</u>	<u>55000 pounds</u>
<u>Sensitivity – Nominal</u>	<u>Technical Data Sheet</u>	<u>7.6 ± 12% pC/lbf</u>
<u>Sensitivity shift over sensor length</u>	<u>Technical Data Sheet</u>	<u><± 3%</u>
<u>Threshold</u>	<u>Technical Data Sheet</u>	<u><0.1 lbf</u>
<u>Linearity</u>	<u>Technical Data Sheet</u>	<u><± 2% Full Scale Output</u>
<u>Hysteresis</u>	<u>Technical Data Sheet</u>	<u>≤ 2% Full Scale Output</u>
<u>Natural Frequency</u>	<u>Technical Data Sheet</u>	<u>> 5 kHz</u>
<u>Operating Temperature range</u>	<u>Technical Data Sheet</u>	<u>-40°F to 176°F</u>
<u>Temperature coefficient of sensitivity</u>	<u>Technical Data Sheet</u>	<u>-0.04%/°F</u>
<u>Operating Speed</u>	<u>Technical Data Sheet</u>	<u>5 MPH to 100 MPH</u>
<u>Insulation resistance</u>	<u>Technical Data Sheet</u>	<u>> 100 giga ohms</u>
<u>Capacitance with 130 ft. cable</u>	<u>Technical Data Sheet</u>	<u>8 to 12 nano farad</u>
<u>Environmental Requirements</u>	<u>Technical Data Sheet</u>	<u>NEMA TS-2-2016, Section 3.</u>

997-4 Solar Power Unit.

997-4.1 General: Provide solar power unit consisting of the following components: solar panel(s) and mounting hardware; 12 V storage battery; and voltage regulator with wiring and associated mounting hardware.

997-4.2 Solar Panel Configured for Nominal 12 V_{DC}: Solar panels cannot have internal voltage regulators and must be capable of multiple arrays and series or parallel wiring configurations. Meet the physical characteristics in Table 997-7:

<u>Table 997-7</u> <u>Physical Characteristics, Solar Panel</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
<u>Peak power range</u>	<u>Technical Data Sheet</u>	<u>80 to 130 watts.</u>
<u>Voltage</u>	<u>Technical Data Sheet</u>	<u>Maximum power greater than 16.5 V at 77°F</u>
<u>Current</u>	<u>Technical Data Sheet</u>	<u>Maximum power greater than 2.85 A at 77°F.</u>
<u>Photovoltaic modules construction</u>	<u>Technical Data Sheet</u>	<u>Mono or poly-crystalline cells.</u>
<u>AppFrame construction</u>	<u>Technical Data Sheet</u>	<u>Anodized aluminum.</u>
<u>Mounting hardware construction</u>	<u>Technical Data Sheet</u>	<u>Anodized, galvanized or stainless-steel.</u>

997-4.3 Battery 12 V: Meet the physical characteristics in Table 997-8:

<u>Table 997-8</u> <u>Physical Characteristics, Battery 12 V</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
		<u>Rechargeable for photovoltaic application.</u>
		<u>Valve regulated lead-calcium gelled electrolyte or absorbed glass mat.</u>
<u>Case Construction</u>	<u>Technical Data Sheet</u>	<u>ABS Plastic or Polypropylene.</u>
<u>Current discharge rate</u>	<u>Technical Data Sheet</u>	<u>Minimum of 100 hours at 0.9 amperes.</u>
<u>Dimensions</u>	<u>Technical Data Sheet</u>	<u>Approximately 12 inches by 7 inches by 9 inches.</u>

997-4.4 Voltage Regulator Configured for Nominal 12 V_{DC}: Meet the physical characteristics in Table 997-9:

<u>Table 997-9</u> <u>Physical Characteristics, Voltage Regulator</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
<u>Voltage for battery charging.</u>	<u>Technical Data Sheet</u>	<u>Minimum of 13.5 V_{DC}.</u>
		<u>Begin charging when battery voltage is 13.3 V or less.</u>
		<u>Discontinue charging when battery voltage is 14.5 V.</u>
<u>Quiescent current</u>	<u>Technical Data Sheet</u>	<u>Maximum 15 mA.</u>
<u>Operating Temperature range</u>	<u>Technical Data Sheet</u>	<u>0 to 122°F.</u>
<u>Dimensions</u>	<u>Technical Data Sheet</u>	<u>Approximately 2 inches by 5 inches by 1 inch.</u>

997-5 Site Modem: Meet the physical characteristics in Table 997-10:

<u>Table 997-10</u> <u>Physical Characteristics, Site Modem</u>		
<u>Property</u>	<u>Documentation</u>	<u>Requirements</u>
<u>Configuration</u>	<u>Technical Data Sheet</u>	<u>1.The device shall be field configurable to be powered from 12 V_{DC}.</u> <u>2.The device shall have the ability and be configured to utilize a network service that shall be at a minimum 4G LTE with fallback to 3G EV-DO.</u>

<p><u>Protocols:</u> The device shall have the ability to utilize, at a minimum, the following protocols:</p>	<p><u>Technical Data Sheet</u></p>	<ol style="list-style-type: none"> 1. <u>Network: TCP/IP, UDP/IP, Domain Name System (DNS)</u> 2. <u>Routing: Network Address Translation (NAT), Host Port Routing, DHCP, Point-to-Point Protocol over Ethernet (PPPoE), VLAN, Virtual Router Redundancy Protocol (VRRP), Reliable Static Route.</u> 3. <u>Application: Short Message Service (SMS), Telnet/SSH, Reverse Telnet, Simple Mail Transfer Protocol (SMTP), SNMP, SNTp, Reliable Static Route</u> 4. <u>Serial: TCP/UDP Packet Assembly Disassembly (PAD) Mode, Modbus (ASCII, RTU, Variable), Point-to-Point Protocol (PPP)</u>
<p><u>Event Reporting:</u> The device shall have the capability to record and report, at a minimum, the following events in plain text:</p>	<p><u>Technical Data Sheet</u></p>	<ol style="list-style-type: none"> 1. <u>Network parameters</u> 2. <u>Data usage</u> 3. <u>Power</u> 4. <u>Device temperature</u> 5. <u>Digital input</u> 6. <u>Global Positioning</u> 7. <u>System/Automatic</u> 8. <u>Vehicle Locator (GPS/AVL)</u> 9. <u>Timer</u>
<p><u>Security:</u> The device shall have the following security provisions:</p>	<p><u>Technical Data Sheet</u></p>	<ol style="list-style-type: none"> 1. <u>Ability to establish VPN tunnels.</u> 2. <u>IPsec, Secure Sockets Layer (SSL), and Generic Routing Encapsulation (GRE) VPN client</u> 3. <u>Port forwarding and Demilitarized Zone (DMZ)</u> 4. <u>Port filtering</u> 5. <u>Trusted IP</u> 6. <u>MAC address filtering</u>
<p><u>Operating Temperature range</u></p>	<p><u>Technical Data Sheet</u></p>	<p><u>Minimum 0 to 158°F.</u></p>

<p><u>Antenna: Use an antenna that meets the following requirements:</u></p>	<p><u>Technical Data Sheet</u></p>	<p><u>1. Dual diversity</u> <u>2. Minimum NEMA rating of NEMA 3</u> <u>3. Frequencies: F₁ = 824 to 896 MHz, F₂ = 1850 to 1990 MHz, F₃ = 1850 to 1955 MHz, F₄ = 1710 to 1770 MHz, F₅ = 2110 to 2170 MHz</u> <u>4. Voltage Standing Wave Ratio (VSWR) of 1.5:1 or less at resonant point</u> <u>5. 50 Ω nominal impedance</u> <u>6. Gain of 3.0 dB to 5.15 dB</u> <u>7. Omni-directional radiation pattern</u> <u>8. Vertical polarization</u> <u>9. Glass-filled polypropylene radome</u> <u>10. Adhesive mounting or Bolt mount</u> <u>11. SMA male plug connectors 10 ft. (minimum) coaxial length</u></p>
--	------------------------------------	--