ORIGINATION FORM

Proposed Revisions to the Specifications

(Please provide all information - incomplete forms will be returned)

Date:	Office:				
Originator:	Specification Section:				
Telephone:	Article/Subarticle:				
email:					
Will the proposed revision require changes to:					
Publication	Yes	No	Office	Staff Contacted	
Standard Plans Index					
Traffic Engineering Manual					
FDOT Design Manual					
Construction Project Administration Manual					
Basis of Estimate/Pay Items					
Structures Design Guidelines					
Approved Product List					
Materials Manual					
Will this revision necessitate any of the following	ng:				
Design Bulletin Construction Bulletin	E	Estimates Bulletin		Materials Bulletin	
Are all references to external publications current?		Yes	No		
If not, what references need to be updated? (PI	ease inclu	ude changes	in the redline d	ocument.)	
Why does the existing language need to be changed?					
Summary of the changes:					
Summary of the changes.					
Are these changes applicable to all Department If not, what are the restrictions?	: jobs?	Yes	No		



RICK SCOTT GOVERNOR 605 Suwannee Street Tallahassee, FL 32399-0450 MIKE DEW SECRETARY

MEMORANDUM

DATE: October 18, 2018

TO: Specification Review Distribution List

FROM: Dan Hurtado, P.E., State Specifications Engineer

SUBJECT: Proposed Specification: 7010401 Profiled Thermoplastic Pavement Markings.

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

This change was proposed by Paul Gentry of the State Program Management Office, Product Evaluation Section, to specify the surface temperature when applying thermoplastic markings.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or online at http://www2.dot.state.fl.us/ProgramManagement/Development/IndustryReview.aspx. Comments received after November 15, 2018, may not be considered. Your input is encouraged.

DH/dt Attachment

PROFILED THERMOPLASTIC PAVEMENT MARKINGS. (REV 9-11-18)

SUBARTICLE 701-4.1 is deleted and the following substituted:

701-4.1 General: Remove existing pavement markings such that scars or traces of removed markings will not conflict with new pavement markings by a method approved by the Engineer. Cost for removing conflicting pavement markings during maintenance of traffic operations to be included in Maintenance of Traffic, Lump Sum.

Before applying pavement markings, remove any material that would adversely affect the bond of the pavement markings by a method approved by the Engineer.

Before applying pavement markings to any portland cement concrete surface, apply a primer, sealer or surface preparation adhesive of the type recommended by the manufacturer. Offset longitudinal lines at least 2 inches from construction joints of portland cement concrete pavement.

Apply pavement markings to dry surfaces only, and when the ambient air and surface temperature is at least 50°F and rising for asphalt surfaces and 60°F and rising for concrete surfaces.

Apply pavement markings to the same tolerances in dimensions and in alignment specified in 710-5. When applying pavement marking over existing markings, ensure that no more than 2 inches on either end and not more than 1 inch on either side of the existing line is visible.

Conduct field tests in accordance with FM 5-541. Take test readings representative of the pavement marking performance. Remove and replace pavement markings not meeting the requirements of this Section at no additional cost to the Department.