



Florida Department of Transportation

RICK SCOTT
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

MIKE DEW
SECRETARY

November 29, 2018

Khoa Nguyen
Director, Office of Technical Services
Federal Highway Administration
3500 Financial Plaza, Suite 400
Tallahassee, Florida 32312

Re: State Specifications Office
Section: **711**
Proposed Specification: **7110402 Thermoplastic Pavement Markings.**

Dear Mr. Nguyen:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

The changes are proposed by Paul Gentry of the State Program Management Office, Product Evaluation Section, specify where preformed thermoplastic is to be used.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via email to dan.hurtado@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at 414-4130.

Sincerely,

Signature on file

Dan Hurtado, P.E.
State Specifications Engineer

DH/dt

Attachment

cc: Florida Transportation Builders' Assoc.
State Construction Engineer

THERMOPLASTIC PAVEMENT MARKINGS.**(REV ~~9-11-18~~ 2-18 ~~11-27-18~~)**

SUBARTICLE 711-4.2.3 is deleted and the following substituted:

711-4.2.3 Preformed Thermoplastic: Apply 0.125 inch or 125 mils of preformed thermoplastic material. Use Ppreformed thermoplastic shall be used for all-bicycle markings, and-shared use path markings, 24 inch markings of the special emphasis crosswalks, route shields, ramp exit numbers, and-roundabout informational markings, white dotted lines (2'-4') with trailing black contrast, and black contrast arrows, messages, and symbols.

Measure, record and certify on Department approved form and submit to the Engineer, the thickness of the pavement markings in accordance with FM 5-541.

THERMOPLASTIC PAVEMENT MARKINGS.**(REV 11-27-18)**

SUBARTICLE 711-4.2.3 is deleted and the following substituted:

711-4.2.3 Preformed Thermoplastic: Apply 0.125 inch or 125 mils of preformed thermoplastic material. Use preformed thermoplastic for bicycle markings, shared use path markings, 24 inch markings of the special emphasis crosswalks, route shields, ramp exit numbers, roundabout informational markings, white dotted lines (2'-4') with trailing black contrast, and black contrast arrows, messages, and symbols.

Measure, record and certify on Department approved form and submit to the Engineer, the thickness of the pavement markings in accordance with FM 5-541.