ORIGINATION FORM

Proposed Revisions to the Specifications

(Please provide all information - incomplete forms will be returned)

Date:		Office:			
Originator:		Specification Section:			
Telephone:		Article/Subarticle:			
email:					
**Will the proposed	revision require changes to	o:			
Publication		Yes	No		Staff Contacted ate contacted
Standa	rd Plans Index				
Traffic Engineering Manual					
FDOT Design Manual					
Construction Project Administration Manual					
Basis of Estimate/Pay Items					
Structures Design Guidelines					
Approved Product List					
Materials Manual					
	t be completed prior to pro		oposed revi	sions.	
Design Bulletin	Construction Bulletin	E	stimates Bu	lletin	Materials Bulletin
Are all references to external publications curr		ent?	Yes	No	
If not, what reference	es need to be updated? (Pl	lease incli	ude changes	in the redline do	cument.)
Why does the existing	ng language need to be cha	nged?			
Summary of the cha	nges:				
Are these changes applicable to all Department jobs? If not, what are the restrictions?			Yes	No	



RON DESANTIS GOVERNOR KEVIN J. THIBAULT, P.E. SECRETARY

MEMORANDUM

DATE: November 25, 2020

TO: Specification Review Distribution List

FROM: Daniel Strickland, P.E., State Specifications Engineer

SUBJECT: Proposed Specification: 3300904 HOT MIX ASPHALT - GENERAL

CONSTRUCTION REQUIREMENTS

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

The changes are proposed by Rich Hewitt from the State Construction Office to add speed tables and raised crosswalks to the straightedge testing exception areas in the Standard Specification.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or online at http://fdotewp1.dot.state.fl.us/programmanagement/development/industryreview.aspx.

Comments received after **December 28, 2020**, may not be considered. Your input is encouraged.

DS/dh

Attachment

HOT MIX ASPHALT - GENERAL CONSTRUCTION REQUIREMENTS (REV 10-5-20)

SUBARTICLE 330-9.4.5.2 is deleted and the following substituted:

330-9.4.5.2 Straightedge Exceptions: Straightedge testing will not be required in the following areas: shoulders, intersections, tapers, crossovers, sidewalks, shared use paths, parking lots, raised crosswalks, speed tables, and similar areas, or in the following areas when they are less than 250 feet in length: turn lanes, acceleration/deceleration lanes and side streets. The limits of the intersection will be from stop bar to stop bar for both the mainline and side streets.

As an exception, in the event the Engineer identifies an objectionable surface irregularity in the above areas, straightedge and address all deficiencies in excess of 3/8 inch in accordance with 330-9.5.

The Engineer may waive straightedge requirements for transverse joints at the beginning and end of the project, at the beginning and end of bridge structures, at manholes, and at utility structures if the deficiencies are caused by factors beyond the control of the Contractor, as determined by the Engineer. In addition, the Engineer may also waive the straightedging requirements on ramps and superelevated sections where the geometrical orientation of the pavement results in an inaccurate measurement with the rolling straightedge.