ORIGINATION FORM

Proposed Revisions to the Specifications

(Please provide all information - incomplete forms will be returned)

Date:		Office:			
Originator:		Specification Section:			
Telephone:		Article/Subarticle:			
email:					
**Will the proposed	revision require changes to	o:			
Publication		Yes	No		Staff Contacted ate contacted
Standa	rd Plans Index				
Traffic Engineering Manual					
FDOT Design Manual					
Construction Project Administration Manual					
Basis of Estimate/Pay Items					
Structures Design Guidelines					
Approved Product List					
Materials Manual					
	t be completed prior to pro		oposed revi	sions.	
Design Bulletin	Construction Bulletin	E	stimates Bu	lletin	Materials Bulletin
Are all references to external publications curr		ent?	Yes	No	
If not, what reference	es need to be updated? (Pl	lease incli	ude changes	in the redline do	cument.)
Why does the existing	ng language need to be cha	nged?			
Summary of the cha	nges:				
Are these changes applicable to all Department jobs? If not, what are the restrictions?			Yes	No	



RON DESANTIS GOVERNOR

KEVIN J. THIBAULT, P.E. SECRETARY

MEMORANDUM

DATE: November 5, 2020

TO: Specification Review Distribution List

FROM: Daniel Strickland, P.E., State Specifications Engineer

SUBJECT: Proposed Specification: **5220703 CONCRETE SIDEWALK AND**

DRIVEWAYS

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

The changes are proposed by Bobby Bull from the Roadway Design Office to clarify requirements for sidewalk cross slopes to meet ADA Standards in the Standard Specification.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or online at http://fdotewp1.dot.state.fl.us/programmanagement/development/industryreview.aspx. Comments received after December 2, 2020, may not be considered. Your input is encouraged.

DS/dh

Attachment

CONCRETE SIDEWALK AND DRIVEWAYS (REV 11-3-20)

ARTICLE 522-7 is expanded by the following:

522-7 Finishing.

522-7.1 Screeding: Strike-off the concrete by means of a wood or metal screed, used perpendicular to the forms, to obtain the required grade and remove surplus water and laitance.

522-7.2 Surface Requirements: Imprint concrete as detailed in the Plans, otherwise provide a broom finish. Ensure that the surface variations are not more than 1/4 inch under a 10-foot straightedge or more than 1/8 inch on a 5-foot transverse section. Finish the outer edges of the concrete with an edging tool having a radius of 1/2 inch.

522-7.3 Sidewalk Cross Slope Requirements: Construct sidewalk with cross slope as shown in the Plans and Standard Plans. When a cross slope is specified, this cross slope is not to be exceeded. Sidewalks must have some cross slope, but no more than 2.0%, in either the positive or negative direction after construction.