

EXPECTED IMPLEMENTATION JULY 2021

D

710 PAINTED PAVEMENT MARKINGS (REV 9-28-20) (FA 1-8-21) (7-21)

ARTICLE 710-2 is deleted and the following substituted:

710-2 Materials.

Use only materials listed on the Department's Approved Product List (APL) meeting the following requirements:

Standard Paint 971-1 and 971-3

Durable Paint 971-1 and 971-4

Glass Spheres 971-1 and 971-2

The Engineer will take random samples of all material in accordance with the Department's Sampling, Testing and Reporting Guide schedule.

R

SUBARTICLE 710-4.1.1 is deleted and the following substituted:

710-4.1.1 Painted Pavement Markings (Final Surface): On concrete surfaces or newly constructed asphalt, the painted pavement markings (final surface) will include one application of standard paint applied to the final surface.

For center line and edge line rumble strip installations where the pavement marking is placed within the grinding, apply a second application of standard paint within 24 hours of each day's grinding operation.

Do not apply final surface paint for bicycle arrows or bicycle messages, 24 inch longitudinal bars in special emphasis crosswalks, or route shields where preformed thermoplastic will be applied.

A

SUBARTICLE 710-11.2 is deleted and the following substituted:

710-11.2 Painted Pavement Markings (Final Surface): Price and payment for painted pavement markings (final surface) will be full compensation for all applications of painted pavement markings in accordance with 710-4.1.1 and 710-9.1.

F

T