9930100 SPECIFICATION COMMENTS FROM INTERNAL/INDUSTRY REVIEW

Stefanie D. Maxwell, P.E. Work 850-414-4140 Stefanie.Maxwell@dot.state.fl.us

Comments: (Internal 10-22-20)

Please see my markup in the attached that expands pavement mounted to surface-mounted in Article 993-2.2.4.1 to match the NTPEP work plan.

Response:

(Specifications Office) Done.

Deborah Ihsan Work Phone: 954-777-4387 E-Mail: Deborah.ihsan@dot.state.fl.us

Comments: (Industry11-10-20)

Section 993-1.2.1 need to be supplemented with Type 4, so as to read as - 993-1.23 Retroreflective Sheeting: 993-1.23.1 Retroreflective Sheeting: The retroreflective sheeting for object markers shall meet the requirements of Section 994, sheeting Types IV, V or XI. The retroreflective area shall be in accordance with the MUTCD. The retroreflective sheeting shall be permanently adhered to 0.040 inch0.040-inch sheet aluminum for Type 2 markers and 0.080 - inch sheet aluminum for Type 1, 3 and Type 4, end of the road markers. Section 993-2.2.4.1 reads "993-2.2.4.1 Pavement/Surface mounted: Use the Metropolitan Delineator Applications category for Hot Weather with a minimum of 10 impacts (default testing procedure uses a maximum of 200 impacts)". Comment- please verify if the word "Metropolitan" is necessary. Thanks for the opportunity to review.

Response:
