ORIGINATION FORM

Proposed Revisions to the Specifications

(Please provide all information - incomplete forms will be returned)

Date:	Office:				
Originator:	Specification Section:				
Telephone:	Article/Subarticle:				
email:	Α	Associated Section(s) Revisions:			
Will the proposed revision require changes to:					
Publication	Yes	No	Office S	Staff Contacted	
Standard Plans Index					
Traffic Engineering Manual					
FDOT Design Manual					
Construction Project Administration Manual					
Basis of Estimate/Pay Items					
Structures Design Guidelines					
Approved Product List					
Materials Manual					
		1			
Will this revision necessitate any of the following	ng:				
Design Bulletin Construction Bulletin	E:	stimates Bulle	etin	Materials Bulletin	
Are all references to external publications current? Yes No					
If not, what references need to be updated? (Pl	ease inclu	ıde changes iı	n the redline do	ocument.)	
Why does the existing language need to be cha	ngod2				
willy does the existing language need to be tha	iigeu:				
Summary of the changes:					
Are these changes applicable to all Department If not, what are the restrictions?	jobs?	Yes	No		



RON DESANTIS GOVERNOR 605 Suwannee Street Tallahassee, FL 32399-0450 KEVIN J. THIBAULT, P.E. SECRETARY

MEMORANDUM

DATE: December 2, 2021

TO: Specification Review Distribution List

FROM: Daniel Strickland, P.E., State Specifications Engineer

SUBJECT: Proposed Specification: 6630000 Signal Priority and Preemption Systems.

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change.

This change was proposed by Derek Vollmer from the Traffic Engineering and Operations Office to move the materials language from Division II to Division III. The proposed specification change is associated with the changes made to Section 995.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or online at http://fdotewp1.dot.state.fl.us/programmanagement/development/industryreview.aspx. Comments received after **December 30, 2021,** may not be considered. Your input is encouraged.

DS/ra

Attachment

SIGNAL PRIORITY AND PREEMPTION SYSTEMS (REV 11-17-21)

SECTION 663 is deleted and the following substituted:

663-1 Description.

Furnish and install a signal priority and preemption system as shown in the Plans. The signal preemption system must recognize and respond to the priority of each user. Meet the requirements of Section 603.

663-2 Materials.

Use signal priority and preemption system equipment that meet the requirements of Section 995 and are listed on the Department's Approved Product List (APL). Ensure that all materials furnished, assembled, fabricated or installed are new products.

Signal priority and preemption system equipment may utilize optical, GPS, and radio frequency based technologies.

663-2.1 Functional Requirements: Ensure that in-vehicle equipment operates without requiring any action from the vehicle operator or occupants once power is applied.

663-2.1.1 Security: The system must include features that secure the system and restrict its configuration and operation to authorized users and vehicles only.

663-2.1.2 Vehicle Identification: The system must be able to assign a unique identifier for each authorized vehicle. The system must be able to associate the identifier with vehicle information such as vehicle classification (e.g., fire, police, rescue, transit), owner/operator, and priority level.

663-2.1.3 Configuration and Management: The system must allow authorized local and remote users to set and read all user programmable features and retrieve data collected by the system. The manufacturer must provide computer software required to configure, operate, and maintain the system at no additional cost to the Department.

663-2.1.4 Logging: The system installed in the field cabinet must store a record of events, including time, vehicle ID, class, priority level, and approaching direction for all vehicles detected. The log must operate on a first in, first out (FIFO) principle with a minimum capacity of 5,000 events.

663-2.1.5 Detection Range and Accuracy: The priority and preemption system must be capable of detecting and identifying multiple authorized vehicles at various ranges up to 2,500 feet. The system must be able to determine the approaching direction of authorized vehicles. The detection range and programming of emergency (high priority) and transit signal (low priority) preemption shall be adjustable from within the traffic signal cabinet. High priority ealls must override low priority calls.

The system must service preemption calls having equal priority on a first-come, first-served basis.

663-2.2 Preemption System Cabinet Electronics: The priority and preemption system must be compatible with NEMA TS 1, NEMA TS 2, Type 170, and Type 2070 traffic signal controllers and their respective cabinets.

The system must be able to provide calls to the controller via input file and detector rack. The system must include two channel or four channel detector card units compatible with NEMA TS 2-2003 v02.06. The system must include a shelf mount option.

The system must be able to provide emergency preemption (high priority) and transit signal (low priority) preemption calls to the controller. Detectors must include programmable timers that allow the operator to configure detector call extension as well as limit the length of channel output calls. Channel outputs must deliver a constant signal while emergency vehicles are detected for high priority preemption activation. Channel outputs must deliver a pulsed output for low priority preemption activation. Inputs and outputs must be optically isolated. 663-2.2.1 Serial Interface: Ensure that the serial ports support data rates up to 115 kbps; error detection procedures utilizing parity bits (i.e., none, even, and odd); and stop bits (1 or 2). Serial interface ports may utilize RJ-45 connectors, D-sub connectors, or screw terminals. 663-2.2.2 Network Interface: Ensure that local area network (LAN) connections support the requirements detailed in the Institute of Electrical and Electronics Engineers (IEEE) IEEE 802.3 Standard for 10/100 Ethernet connections. Ensure that the connector complies with applicable Electronic Industries Alliance (EIA) and Telecommunications Industry Association (TIA) requirements. 663-2.3 Optical Preemption Detectors: Optical preemption detectors must respond to light impulses generated from a visible or infrared light source. 663-2.4 Intersection Radio/GPS Modules: Radio/GPS preemption systems must include radio/GPS modules that transmit a beacon signal and receive data transmitted by Radio/GPS vehicle equipment. 663-2.5 Mechanical Specifications: Ensure equipment is permanently marked with manufacturer name or trademark, part number, and date of manufacture or serial number. Ensure that every conductive contact surface or pin is gold plated or made of a noncorrosive, conductive metal. Do not use self-tapping screws on the exterior of the assembly. All external parts must be made of corrosion-resistant materials, such as plastic, stainless steel, anodized aluminum, brass, or gold-plated metal. Detector cards must include indicators for power and vehicle detection. Detector cards must include a test switch that can be used to manually generate detector calls that the system provides during normal operations. 663-2.6 Electrical Specifications: Provide equipment that operates on a nominal voltage of 120 volts alternating current (VAC). If the device requires operating voltages of less than 120 V_{AC}, supply the appropriate voltage converter. 663-2.7 Environmental Specifications: Ensure system electronics perform all required functions during and after being subjected to the environmental testing procedures described in

663-3 Installation.

Installation of materials must be in accordance with the manufacturer's instructions. Install the emergency preemption system including installation of detectors with all necessary hardware and software, mounting hardware, cabling, and all other associated electronics in cabinet necessary to create a fully functional emergency preemption system.

NEMA TS 2. Sections 2.2.7, 2.2.8, and 2.2.9. Detectors and detector connections that are

Ensure that status indicators remain unobstructed and visible.

exposed to the elements must be weatherproof and designed for outdoor use.

663-3.1 Field Testing: Subject the system to field acceptance tests (FATs). Develop and submit a test plan for FATs to the Engineer for approval. The Engineer reserves the right to witness all FATs.

663-4 Warranty.

Ensure that the manufacturer will furnish replacements for any part or equipment found to be defective during the warranty period at no cost to the Department or the maintaining agency within 10 calendar days of notification.

Ensure that the priority and preemption system has a manufacturer's warranty covering defects for five years.

663-5 Method of Measurement.

The Contract unit price for each signal priority and preemption system, furnished and installed, will include furnishing, placement, and testing of all equipment and materials, and for all tools, labor, hardware, operational software packages and firmware, supplies, support, personnel training, shop drawings, documentation, and incidentals necessary to complete the work.

663-6 Basis of Payment.

Price and payment will be full compensation for all work specified in this Section. Payment will be made under:

Item No. 663- 1- Signal Priority and Preemption System