



Florida Department of Transportation

RON DESANTIS
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

JARED W. PERDUE, P.E.
SECRETARY

October 30, 2023

Khoa Nguyen
Director, Office of Technical Services
Federal Highway Administration
3500 Financial Plaza, Suite 400
Tallahassee, Florida 32312

Re: State Specifications Office
Section: 710
Proposed Specification: **7100401 Painted Pavement Markings.**

Dear Mr. Nguyen:

We are submitting, for your approval, two copies of the above referenced Supplemental Specification.

The changes are proposed by David Amato to address certain concessions related to the application of performed thermoplastic.

Please review and transmit your comments, if any, within two weeks (10 business days). Comments should be sent via email daniel.strickland@dot.state.fl.us.

If you have any questions relating to this specification change, please call me at (850) 414-4130.

Sincerely,

Signature on file

Daniel Strickland, P.E.
State Specifications Engineer

DS/jb

Attachment

cc: Florida Transportation Builders' Assoc.
State Construction Engineer

PAINTED PAVEMENT MARKINGS.
(REV 5-22-23)

SUBARTICLE 710-4.1.1 is deleted and the following substituted:

710-4.1.1 Painted Pavement Markings (Final Surface): On concrete surfaces or newly constructed asphalt, the painted pavement markings (final surface) will include one application of standard paint applied to the final surface, except as noted herein.

For center line and edge line rumble strip installations where the pavement marking is placed within the grinding, apply a second application of standard paint within 24 hours of each day's grinding operation.

Do not apply final surface paint ~~for bicycle arrows or bicycle messages, 24 inch longitudinal bars in special emphasis crosswalks, or route shields~~ where preformed thermoplastic is required in 711-4.2.3 ~~will be applied~~.

Do not apply final surface paint where permanent tape will be applied.

PAINTED PAVEMENT MARKINGS.

(REV 5-22-23)

SUBARTICLE 710-4.1.1 is deleted and the following substituted:

710-4.1.1 Painted Pavement Markings (Final Surface): On concrete surfaces or newly constructed asphalt, the painted pavement markings (final surface) will include one application of standard paint applied to the final surface, except as noted herein.

For center line and edge line rumble strip installations where the pavement marking is placed within the grinding, apply a second application of standard paint within 24 hours of each day's grinding operation.

Do not apply final surface paint where preformed thermoplastic is required in 711-4.2.3.

Do not apply final surface paint where permanent tape will be applied.