

ROADSIDE DITCH OR CANAL CLEANING AND GRADING.
(REV 10-1-15) (FY 2024-25)

The following new Section is added after Section 120:

SECTION 120-50
ROADSIDE DITCH OR CANAL CLEANING AND GRADING

120-50.1 Description.

Clean and grade ditch and canal to allow free and unobstructed flow of drainage water.

Reshape and remove undesirable materials in ditches, slopes, or canal restoration according to the line, grade, and typical section for the particular roadway or special grades, as provided by the Engineer. Related work will include site preparation, erosion control, spreading and grading materials, or hauling and disposing of excess materials, as specified in the work document.

120-50.2 Materials.

Salvageable material, as determined by the Engineer, will be identified as fill material for low areas within the project limits or will be stockpiled in areas designated by the Engineer. Materials that are used within the project limits shall be uniformly distributed over specified areas. Provide locations for disposal of all debris and undesirable material in accordance with applicable local and state laws. The cost of disposing all debris and undesirable material will be included in the contract unit price for cleaning and reshaping the ditches or canals.

120-50.3 Construction Methods.

120-50.3.1 General: Coordinate with the utility companies for the location of all underground utilities prior to beginning work where digging or grading work is required.

Details of the limits, finish grade, or special grade requirements will be provided on the work document, by the Engineer. Do all layout work as required.

Front slopes of ditches will not exceed a six horizontal to one vertical slope, except in areas that a special grade is required. Fill and grade eroded areas to the specified line and grade. Completed work will result in a flat bottom ditch. V-shaped ditches will not be permitted. Ditches will be free of obstructions with smooth transitions of grade or slope changes. Canals will be cleaned and reshaped as specified in the work document. Take sufficient precautions to prevent pollution and follow all Federal, State, and local regulations when cleaning and reshaping canals or ditches.

Stockpiling of removed materials within the right of way for later disposal will require prior approval of the Engineer. Materials stockpiled within the project limits will be removed within ten calendar days, unless otherwise approved by the Engineer. Stockpiled materials will not be located so as to create a hazard. The work site will be clean and free of debris.

Comply with Rule 62C-52 and Rule 5B-57, Florida Administrative Code, and control the introduction, movement, or spread of prohibited aquatic plants, plant pests, or noxious weeds.

120-50.3.2 Erosion Control: Provide prevention, control, abatement of erosion and water pollution as specified in Section 104. When no separate items for payment are included in

the Bid Price Proposal for the Contract, the cost of erosion control will be incidental to the work being performed and will not be paid for separately.

120-50.4 Method of Measurement.

The quantity to be paid for will be the length of ditch or canal measured in linear feet, completed and accepted, including the work necessary to clean and reshape the ditch or canal areas to the specified line and grade. Variations, as specified in the work document, between the typical section and the completed and accepted ditch width of greater than ten percent will be cause for adjustment (increase or decrease) in the linear foot quantity. The adjustment will be the average final ditch width divided by the standard (typical) ditch width. The linear feet under this item will be adjusted by the percentage calculated.

120-50.5 Basis of Payment.

Price and payment will be full compensation for all work specified in this Section, including materials and incidentals necessary to complete the work.

Payment will be made under the items specified in the Bid Price Proposal.