

To: FDOT-DDE DPME

cc: Robert Greer/CO/FDOT@FDOT, Ananth Prasad/CO/FDOT@FDOT,

William N Nickas/CO/FDOT@FDOT, Bruce

Dietrich/CO/FDOT@FDOT, Duane F Brautigam/CO/FDOT@FDOT,

Sharon E Holmes/CO/FDOT@FDOT, Elwin

Broome/CO/FDOT@FDOT, marvin.williams@fhwa.dot.gov, Jim

Mills/CO/FDOT@FDOT

Subject: Portable Temporary Low Profile Barrier

We have recently posted Interim Index 412, Portable Temporary Low Profile Barrier for Roadside Safety, Sheets 1-5 of 5 on the Roadway Design Office web site under Interim Standards for 2002. It will soon also be added to the Interim Standards for the 2004 Design Standards.

This barrier is applicable for design speeds of 45 mph or less where a low profile is desired to maintain sight distance at intersections and driveways. This Interim may be used beginning immediately. Please note that availability of this device will be limited initially, since the precast industry will need time for mobilizing and tooling up to begin fabrication. This should be considered in establishing project schedules when calling for this device.

The Roadway Design Office web site for Interim Standards is:

http://www.dot.state.fl.us/rddesign/rd/Interims.htm

Please advise appropriate staff and consultants.

Brian A. Blanchard, P.E. Florida Department of Transportation State Roadway Design Engineer (850) 414-4377

email: brian.blanchard@dot.state.fl.us