

Florida Department of Transportation

RICK SCOTT GOVERNOR 605 Suwannee Street Tallahassee, FL 32399-0450 JIM BOXOLD SECRETARY

ROADWAY DESIGN BULLETIN 15-05

(FHWA Approved: February 26, 2015)

DATE: February 26, 2015

TO: District Directors of Transportation Operations, District Directors of

Transportation Development, District Design Engineers, District Consultant Project Management Engineers, District Construction Engineers, District Maintenance Engineers, District Geotechnical Engineers, District Structures Design Engineers, District Roadway Design Engineers, District Traffic

Operations Engineers, Program Management Engineers

FROM: Michael Shepard, P.E., State Roadway Design Engineer Multi-Shyurl

COPIES: Brian Blanchard, Tom Byron, Duane Brautigam, David Sadler, Lora

Hollingsworth, Tim Lattner, Trey Tillander, Mark Wilson, Bruce Dana, John Krause, Robert Robertson, Bob Crim, Rudy Powell, Greg Schiess, Nicholas Finch (FHWA), Jeffrey Ger (FHWA), Chad Thompson (FHWA), Phillip Bello

(FHWA)

SUBJECT: High Tension Cable Barrier (HTCB)

This bulletin rescinds the Suspension of High Tension Cable Barrier Systems issued by Project Management Memorandum 14-02, and announces the release of a revised Developmental Specification Dev540. Additionally, this bulletin introduces the new Developmental Design Standards (DDS) Index D450, High Tension Cable Barrier, with its Instructions for Developmental Design Standards (IDDS). These documents are available for viewing on the Developmental Specifications and DDS website.

REQUIREMENTS

- 1. **DDS** Index D450, High Tension Cable Barrier, has been released.
- 2. *IDDS*-450, *High Tension Cable Barrier*, has been released. This provides developmental design guidance to be used in addition to *PPM*, *Vol. 1*, *Chapter 4*.
- 3. The *Basis of Estimates Manual* pay item structure for *High Tension Cable Barrier System*, **904-540-** A has been revised to include the following new pay items:

A = Type

13 - (HTCB Length of Need Segment) per LF

14 - (End Terminal) per EA

15 - (End Terminal Foundation, Misc. Drilled Shaft) per CY

16 - (Concrete Mow Strip) per LF

COMMENTARY

Since the original implementation of HTCB by the FDOT, several national research publications have been issued which provide detailed design guidance, system requirements, and installation recommendations. The majority of this research has been summarized in the *National Cooperative Highway Research Program (NCHRP) Report 711*. As a result, the above referenced documents have been prepared or revised to include recommendations from *NCHRP Report 711* and reinstate the use of HTCB for FDOT projects.

BACKGROUND

The use of HTCB was suspended under *Project Management Memorandum 14-02* to allow the Roadway Design Office an opportunity to reevaluate the design process, system requirements, and construction procedures. The use of HTCB will still be executed through developmental processes to allow for any additional clarification or updates as the HTCB industry continues to advance.

IMPLEMENTATION

DDS-D450 and its IDDS is available for use on applicable current or future projects with approval from the Roadway Design Office. Follow the <u>Usage Process</u> as outlined in the link at the top of the <u>DDS webpage</u>.

To meet the requirements of this bulletin, when High Tension Cable Barrier is approved for use on a project insert the **DDS** Index D450 drawings in the Plans as described in the **PPM**, Vol. 2, Section 3.8.

The *Developmental Specification* Dev540 must be requested through the District Specifications Office.

Roadway Design Bulletin 15-05 High Tension Cable Barrier Page 3 of 3

CONTACT

Derwood Sheppard, P.E. Design Standards Engineer Florida Department of Transportation 605 Suwannee Street, MS 32 Tallahassee, FL 32399-0450 Phone (850)-414-4334 derwood.sheppard@dot.state.fl.us

MAS/dcs