

SPIRAL TIE ELEVATION



SECTION A-A

ALTERNATE STRAND PATTERNS

20 ~ 0.6" Ø, CFRP 7-Strand, at 34 kips
20 ~ ½" Ø, CFRP Single-Strand, at 33 kips

NOTES:
1. Work this Index with Index D22600 – Notes and Details for Square CFRP & SS Prestressed Concrete Piles and Index D22601 – Square CFRP & SS Prestressed Concrete Pile Splices.
2. Any of the given Strand Patterns may be utilized.
   The strands shall be located as follows:
   Place one strand at each corner and place the remaining strands equally spaced between the corner strands.
   The total strand pattern shall be concentric with the nominal concrete section of the pile.



SECTION D-D
(See Nondrivable Unforeseen Reinforced Precast Pile Build-Up Detail)



SECTION E-E
(See Drivable Prestressed Precast Pile Splice Detail)



SECTION F-F
(See Drivable Preplanned Prestressed Precast Pile Splice Detail)

CFRP PILE SPLICE REINFORCEMENT DETAILS

12/17/2015 2:17:05 PM



ELEVATION

** See Note No. 4 on Index No. 22601



SECTION A-A

STRAND PATTERN

28 ~ ½" Ø, HSSS at 26 kips

NOTES:
1. Work this Index with Index No. 22600 – Notes and Details for Square CFRP & SS Prestressed Concrete Piles and Index No. 22601 – Square CFRP & SS Prestressed Concrete Pile Splices.
2. Any of the given Strand Patterns may be utilized. The strands shall be located as follows: Place one strand at each corner and place the remaining strands equally spaced between the corner strands. The total strand pattern shall be concentric with the nominal concrete section of the pile.



SECTION D-D

(See Nondrivable Unforeseen Reinforced Precast Pile Build-Up Detail)



SECTION E-E

(See Drivable Prestressed Precast Pile Splice Detail)



SECTION F-F

(See Drivable Preplanned Pile Splice Detail)

SS PILE SPLICE REINFORCEMENT DETAILS

SS PRESTRESSED PILE DETAILS

12/23/2015 10:39:16 AM

LAST REVISION	REVISION	DESCRIPTION:	FDOT FY 2016-17 DESIGN STANDARDS	24" SQUARE CFRP & SS PRESTRESSED CONCRETE PILE	INDEX NO.	SHEET NO.
01/01/16					22624	2 of 2