


DOUBLED WHEN WORKERS PRESENT



<u>EXHIBIT B</u> DEDICATED LANE INSIDE OR OUTSIDE - ONE LANE CLOSED (Outside Lane Closure is a Mirror Image of this Exhibit)

SYMBOLS

Work Area

■ Channelizing Device (See Index No. 600)

☐ Work Zone Sign

DESCRIPTION:

Advance Warning Vehicle Equipped with
Advance Warning Arrow Board
and Truck/Trailer Mounted Attenuator

GENERAL NOTES

- 1. This Plan is for lane closures that exceed three hours.
- 2. If the closed lane is a dedicated lane, Exhibit A shall be used at Ramp Plazas only. If the closed lane is a cash or mixed-use lane, Exhibit A may be used at Ramp or Mainline Plazas.
- 3. A truck/trailer mounted attenuator is required.
- 4. Exhibit B shall be used at Ramp Plazas only.
- 5. Lane use control lights, signs, or signals over toll lanes shall be switched to the appropriate symbol, message, or correct color prior to the start of any lane closure. They should also be switched at project completion.
- 6. At least 48 hours prior to any closure, other than emergencies, the plaza manager shall be notified for security and staffing.


MAINLINE PLAZAS & RAMP PLAZAS

LAST REVISION 07/01/15

FDOT

FY 2017-18
DESIGN STANDARDS

INDEX NO. **667** SHEET NO. **5 of 6**



WORK NOT DONE WITHIN TRAVEL LANE - ONE LANE CLOSED

SYMBOLS

Work Area

- Channelizing Device (See Index No. 600)
- Work Zone Sign

DESCRIPTION:

Lane Identification + Direction of Traffic

Advance Warning Vehicle Equipped with Advance Warning Arrow Board and Truck/Trailer Mounted Attenuator

GENERAL NOTES

- 1. This Plan is for lane closures that are three hours or less.
- 2. This Plan is to be used at Ramp or Mainline Plazas.
- 3. This plan can be used for any lane, with appropriate modifications, even if it is not in the center of the Plaza.
- 4. Lane use control lights, signs, or signals over toll lanes shall be switched to the appropriate symbol, message, or correct color prior to the start of any lane closure. They should also be switched at project completion.
- 5. At least 48 hours prior to any closure, other than emergencies, the plaza manager shall be notified for security and staffing.
- 6. A Truck/Trailer Mounted Attenuator is required for all aerial work operations (lift truck). For non-aerial operations, the Truck Mounted Attenuator or additional devices may be required by the Engineer based on the work being performed.

SHORT-TERM CLOSURES

REVISION 07/01/15

FY 2017-18 DESIGN STANDARDS

TOLL PLAZA TRAFFIC CONTROL STANDARDS

INDEX NO. 667

SHEET NO. 6 of 6