

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2021 - 2026, EXTRACTED ON 02/16/2021**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = BRADFORD																									
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR																	FUTURE
SR US	G_BMP	G_EMP	LN	%T	AADT		RATINGS	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008					
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	=====																		
ITMSEG-P	(AGE_ONE YEAR)							2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2026 (REG)				
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-F																				
28010000	0.000	5.291	R 1	1 65	CRACKING			1.0*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0					
200 301			2 18.7	24680	RIDE			8.0	7.9	7.7	7.9		8.8	8.9	8.9	8.5	8.4	8.4	8.6	8.6					
CR 221 WYE(0.8R)					FC5																				
2080131	0.055	8.075	C 1999	0221	CRACKING			9.5	9.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	4.7				
APAC-FLORIDA INC			(2001)		SPRIDE			8.5	8.4	8.4	8.4	8.3	8.4	8.3	8.5	8.4	8.6	8.6	8.7	8.5	8.5				
4472041	0.000	5.291	C 2024	0012																					
28010000	6.038	6.923	R 1	1 55	CRACKING			1.0*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0					
200 301			2 22.1	33000	RIDE			8.0	7.9	7.7	7.9		8.8	8.9	8.9	8.5	8.4	8.4	8.6	8.6					
COMMERCIAL DR L(6.1R)					FC5																				
2080131	0.055	8.075	C 1999	0221	CRACKING			9.5	9.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	4.7				
APAC-FLORIDA INC			(2001)		SPRIDE			8.5	8.4	8.4	8.4	8.3	8.4	8.3	8.5	8.4	8.6	8.5	8.6	8.4	8.3				
28010000	6.923	8.044	R 1	1 35	CRACKING			1.0*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5					
200 301			2 22.1	33000	RIDE			8.0	7.9	7.7	7.9		8.8	8.9	8.9	8.0	7.9	7.8	8.1	8.0					
ALEXANDER ST(7.0R)					FC125M																				
4342981	6.923	8.044	C 2017	0012	CRACKING			9.5	9.5	9.5	8.0	8.0	7.0	7.0	7.0	6.5	6.5		10.0	10.0					
ANDERSON COLUMBIA CO., INC(2020)			(2020)		SPRIDE			7.7	7.7	7.8	7.5	7.7	7.3	7.2	7.2	7.0	7.3		8.1	8.0					
28010000	8.044	8.954	R 1	1 30	CRACKING				10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.0	10.0	10.0					
200 301			2 22.1	21000	RIDE				8.5	8.3	7.9	7.7	7.4	7.2	7.2	7.1	6.7	6.5	8.2	8.1					
MADISON ST(8.1C)					FC125M																				
4361561	8.044	8.954	C 2017	0012	CRACKING			10.0	10.0	9.5	8.0	8.0	7.0	6.5	6.5	6.5	6.5		10.0	10.0					
ANDERSON COLUMBIA CO., INC(2020)			(2020)		SPRIDE			7.9	7.8	7.6	7.3	7.3	7.2	6.4	6.8	6.4	6.6		7.7	7.7					
28010000	8.954	9.875	R 1	1 45	CRACKING			2.5*	2.0*	2.0*	2.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5					
200 301			2 22.1	20000	RIDE			7.8	7.5	7.6	7.7		7.9	8.2	8.1	7.9	7.9	7.8	8.1	8.0					
ANDREWS ST(9.0C)					FC125M																				
4323091	8.954	14.320	C 2017	0012	CRACKING			8.0	7.0	7.0	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*	6.0*		10.0	10.0					
ANDERSON COLUMBIA CO., INC(2020)			(2020)		SPRIDE			7.8	7.8	7.6	7.5	7.4	7.2	6.8	7.2	6.9	7.1		8.5	8.5					
28010000	9.875	11.362	R 1	7 55	CRACKING			1.0*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0					
200 301			2 22.1	20000	RIDE			7.9	7.6	8.0	7.8		8.7	8.9	8.8	8.3	8.3	8.3	8.5	8.5					
UNSIGN(10.1R)					FC5M																				
4323091	8.954	14.320	C 2017	0012	CRACKING			10.0	9.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0			10.0					
ANDERSON COLUMBIA CO., INC(2021)			(2021)		SPRIDE			8.4	8.3	8.3	8.3	8.2	8.1	8.1	8.4	8.3	8.5			8.9					
28010000	11.916	14.330	R 1	7 65	CRACKING			1.0*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0					
200 301			2 22.1	19200	RIDE			7.9	7.6	8.0	7.8		8.7	8.9	8.8	8.3	8.3	8.3	8.5	8.5					
NE 196 TER(12.3R)					FC5M																				
4323091	8.954	14.320	C 2017	0012	CRACKING			10.0	9.5	8.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0			10.0					
ANDERSON COLUMBIA CO., INC(2021)			(2021)		SPRIDE			8.4	8.3	8.3	8.3	8.2	8.1	8.1	8.4	8.3	8.5			9.1					
28010000	14.330	15.857	R 1	1 45	CRACKING			1.0*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5					
200 301			2 22.1	19200	RIDE			7.9	7.6	8.0	7.8		8.7	8.2	8.3	7.8	7.8	7.6	7.8	7.6					
CR-225/LAKE ST(15.4R)					FC125M																				
4286921	14.320	15.857	C 2014	0012	CRACKING			8.5	7.0	7.0	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	9.5	7.5	7.1				
ANDERSON COLUMBIA CO., INC(2015)			(2015)		SPRIDE			7.0	6.9	6.3	6.2	5.9	7.7	8.3	8.4	8.4	8.4	8.2	8.3	8.2	8.1				
28010000	15.857	20.227	R 1	1 65	CRACKING			3.5*	1.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5					
200 301			2 25.6	20500	RIDE			8.0	7.8	8.2	8.2		8.9	8.9	8.9	8.4	8.4	8.3	8.5	8.5					
CR 125(16.3C)					FC5M																				
4323151	15.857	20.078	C 2017	0012	CRACKING			8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0				
ANDERSON COLUMBIA CO., INC(2019)			(2019)		SPRIDE			8.4	8.3	8.3	8.3	8.3	8.2	8.2	8.5	8.4		8.9	8.9	8.9	8.9				
28010000	15.857	20.227	L 1	1 65	CRACKING			2.0*	2.0*	1.0*	1.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5					
200 301			2 25.6	20500	RIDE			8.0	8.0	8.0	8.2		8.9	8.9	8.8	8.4	8.3	8.4	8.5	8.5					
CR 125(16.3C)					FC5M																				
4323151	15.857	20.078	C 2017	0012	CRACKING			8.0	8.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0		10.0	10.0	10.0	10.0				
ANDERSON COLUMBIA CO., INC(2019)			(2019)		SPRIDE			8.4	8.3	8.3	8.3	8.3	8.2	8.1	8.4	8.4		8.9	8.9	8.9	8.9				
28010000	14.330	15.857	L 1	1 45	CRACKING			4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	9.0	9.0	9.0	8.0	6.5					
200 301			2 22.1	19200	RIDE			8.1	8.0	8.2	8.3		8.8	8.3	8.2	7.9	7.9	7.6	7.6	7.6					
NW 219 ST(14.8L)					FC125M																				
4286921	14.320	15.857	C 2014	0012	CRACKING			6.5	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5				
ANDERSON COLUMBIA CO., INC(2015)			(2015)		SPRIDE			7.4	7.3	6.9	7.0	7.0	7.0	8.3	8.4	8.3	8.4	8.1	8.2	8.1	7.9				

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2026 FORECASTED BY SIMPLE LINEAR REGRESSION (REG).

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DWDYID		BMP		EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR											FUTURE														
SR	US	G_BMP	G_EMP	G_LN	T	%T	AADT	RATINGS	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2026
INTERSECT AT (MP SIDE)		W_BMP		W_EMP	W_LN	FW	FY-P	WKMX-P	=====																										
CONTRACTOR (AGE_ONE YEAR)		W_BMP		W_EMP	W_LN	FW	FY-F	WKMX-F																											
ASTYPE																																			
28010000		11.916	14.330		L	1	7	65	CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
200 301					2	22.1		19200	RIDE	8.1	8.0	8.2	8.3		8.8	8.9	8.9	8.3	8.3	8.3	8.5	8.5													
NW 196 ST(12.3L)								FC5M																											
4323091		8.954	14.320		C	2017		0012	CRACKING	10.0	9.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0			10.0													
ANDERSON COLUMBIA CO., INC(2021)									SPRIDE	8.4	8.4	8.3	8.3	8.1	8.1	8.0	8.3	8.2	8.6			9.0													
28010000		9.875	11.362		L	1	7	55	CRACKING	4.5*	4.5*	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
200 301					2	22.1		20000	RIDE	8.1	8.0	8.2	8.3		8.8	8.9	8.9	8.3	8.3	8.3	8.5	8.5													
NW 36TH AVE(10.1L)								FC5M																											
4323091		8.954	14.320		C	2017		0012	CRACKING	10.0	9.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0			10.0													
ANDERSON COLUMBIA CO., INC(2021)									SPRIDE	8.4	8.4	8.3	8.3	8.1	8.1	8.0	8.3	8.2	8.6			8.8													
28010000		8.954	9.875		L	1	1	45	CRACKING	2.0*	2.0*	1.0*	1.0*		10.0	10.0	10.0	9.5	9.5	8.0	8.0	6.5													
200 301					2	22.1		20000	RIDE	7.7	7.6	7.9	8.2		8.0	8.3	8.1	7.9	7.8	7.5	7.6	7.4													
ANDREWS ST(9.0C)								FC125M																											
4323091		8.954	14.320		C	2017		0012	CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5			10.0	10.0												
ANDERSON COLUMBIA CO., INC(2020)									SPRIDE	6.9	7.0	6.8	7.3	7.4	7.2	6.9	7.1	6.8	7.0			8.5	8.3												
28010000		8.044	8.954		L	1	1	30	CRACKING		10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	6.0*	6.0*	10.0	10.													

```

** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
"@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
2026 FORECASTED BY SIMPLE LINEAR REGRESSION (REG).

```

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2021 - 2026, EXTRACTED ON 02/16/2021**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = BRADFORD																							
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR															FUTURE
SR US	G_BMP	G_EMP	LN	%T	AADT		RATINGS	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008			
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKM-F	ASTYPE	=====																
CONTRACTOR (AGE ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKM-F			2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2026 (REG)		
28020000	0.000	10.095	C	1	1	60	CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	9.5	9.5	7.0	7.0	6.5	6.5			
100			2	6.1		6600	RIDE	7.8		8.0	9.0	8.9	8.7	8.7	8.5	7.9	7.9	7.9	7.9	7.7			
SE 3 AVE(0.2L)						FC125M																	
2079566	4.035	10.168	C	2010		0012	CRACKING	4.5*	4.5*	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	8.0	8.0		
V. E. WHITEHURST & SONS, I				(2011)			RIDE	7.6	7.3	8.2	8.2	8.1	8.0	7.8	7.7	7.6	7.6	7.5	7.5	7.6	7.0		
28020000	10.095	11.570	C	1	1	45	CRACKING	6.0*		10.0	10.0	10.0	10.0	10.0	9.5	9.5	10.0		10.0	10.0			
100			2	6.0		8600	RIDE	7.8		8.0	9.0	8.9	8.7	8.7	8.5	7.9	7.9		8.2	8.0			
CR 100A(10.2R)						FC125M																	
4323141	10.240	11.133	C	2017		0012	CRACKING	9.5	9.5	9.5	8.0	8.0	8.0	8.0	8.0	7.0	7.0	10.0	10.0	10.0	10.0		
V. E. WHITEHURST & SONS, I				(2019)			SPRIDE	8.1	7.8	7.9	7.8	7.7	7.7	7.6	7.7	7.6	7.7	8.1	7.9	8.0	7.7		
28020000	11.570	12.829	C	1	8	35	CRACKING	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	9.5		10.0	10.0			
100			2	14.4		8000	RIDE	8.2	8.6	8.4	8.5	8.4	8.2	8.3	8.2	7.7	7.7		7.5	7.8			
SR 200(11.6C)						FC125M																	
2079562	11.626	22.169	C	2005		0012	CRACKING	9.5	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	7.0	5.5*	5.5*				
ANDERSON COLUMBIA CO., INC				(2007)			RIDE	7.3	7.0	7.0	6.8	6.7	6.6	6.5	6.6	6.4	6.3	6.9	6.5				
4361791	11.622	22.169	C	2019		0012																	
28020000	12.829	13.680	C	1	7	60	CRACKING	9.0	8.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	4.5*	4.5*		10.0	10.0			
100			2	16.7		5395	RIDE	8.2	8.2	8.1	8.6	8.5	8.2	8.3	8.0	7.5	7.5		8.3	8.3			
CR 100 A(13.5L)						FC125M																	
4361791	12.858	13.404	C	2019		0012	CRACKING	10.0	9.5	9.5	8.0	7.0	6.5	6.5	6.5	6.5			10.0				
PREFERRED MATERIALS, INC. (2021)							SPRIDE	8.3	8.2	8.1	8.0	8.0	7.9	7.8	7.7	7.6			8.1				
28020000	13.680	22.169	C	1	7	60	CRACKING	9.0	8.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	4.5*	4.5*		10.0	10.0			
100			2	16.7		5395	RIDE	8.2	8.2	8.1	8.6	8.5	8.2	8.3	8.0	7.5	7.5		8.3	8.3			
CROSBY LAKE CEMETERY(13.9L)						FC125M																	
4361791	16.174	20.162	C	2019		0012	CRACKING	10.0	9.5	9.5	8.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	4.5*	10.0			
PREFERRED MATERIALS, INC. (2021)							SPRIDE	8.3	8.2	8.1	8.0	8.0	7.9	7.8	7.7	7.6	7.7	7.5	6.9	8.7			
28030000	0.000	0.691	C	1	1	30	CRACKING	10.0	10.0	9.0	9.0	9.0	8.0	8.0	8.0	8.0	7.0	7.0	7.0	10.0			
16			2	3.8		8100	RIDE	7.9	8.0	8.1	6.8	6.9	6.7	7.1	6.9	6.5	6.2	5.8	5.9	8.1			
SR 200(0.0C)						FC125M																	
2080022	0.000	3.701	C	2007		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.5	8.5	8.5	8.0	8.0		
PREFERRED MATERIALS, INC. (2008)							RIDE	7.6	7.9	7.7	7.5	7.7	7.5	7.5	7.4	7.6	7.6	8.0	7.8	7.2	7.2		
28030000	0.691	3.701	C	1	1	60	CRACKING	10.0	10.0	9.5	9.5	9.5	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	10.0			
16			2	6.1		5500	RIDE	8.8	8.8	8.8	8.7	8.6	8.2	8.5	8.4	7.8	7.7	7.6	6.9	8.7			
FAXON LN(1.1L)						FC125M																	
2080022	0.000	3.701	C	2007		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	9.5	9.5	8.5	8.5	8.0	7.9		
PREFERRED MATERIALS, INC. (2008)							RIDE	8.5	8.3	8.5	8.4	8.2	8.2	8.1	8.1	8.1	8.1	8.1	8.1	8.1	7.8		
28030001	0.000	3.860	C	1	1	55	CRACKING	10.0	9.0	8.0	6.0*	4.5*	1.5*	1.5*	1.5*	10.0	10.0	10.0	10.0	10.0			
16			2	3.8		4000	RIDE	7.8	7.9	8.3	8.5	8.3	8.2	8.0	7.7	8.3	8.2	8.3	7.4	8.3			
ENT TO FSP(0.3R)						FC125																	
2080202	0.000	9.184	C	2002		0012	CRACKING	10.0	8.5	8.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	5.5*	4.3		
ANDERSON COLUMBIA CO., INC(2004)							SPRIDE	8.2	8.0	8.1	8.1	7.9	7.8	7.8	7.8	7.7	7.7	7.6	7.7	7.3	7.3		
28030001	3.860	7.250	C	1	1	60	CRACKING	8.0	7.0	6.0*	6.0*	4.5*	1.5*	1.5*	1.5*	10.0	10.0	10.0	10.0	10.0			
16			2	3.8		5600	RIDE	7.9	8.3	8.0	8.5	8.3	8.2	8.0	7.7	8.3	8.2	8.3	7.4	8.3			
NW 216TH ST(4.2L)						FC125																	
2080202	0.000	9.184	C	2002		0012	CRACKING	10.0	8.5	8.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	4.6		
ANDERSON COLUMBIA CO., INC(2004)							SPRIDE	8.2	8.0	8.1	8.1	7.9	7.8	7.8	7.8	7.7	7.7	7.6	7.7	7.9	7.5		
28030001	7.250	7.790	C	1	1	40	CRACKING	8.0	7.0	6.0*	6.0*	4.5*	1.5*	1.5*	1.5*	10.0	10.0	10.0	10.0	10.0			
16			2	3.8		5600	RIDE	7.9	8.3	8.0	8.5	8.3	8.2	8.0	7.7	8.3	8.2	8.3	7.4	8.3			
NW 177TH ST(7.3R)						FC125M																	
(2020)							CRACKING	10.0	8.5	8.5	7.5	7.0	7.0	7.0	7.0	7.0	7.0	6.5	10.0	10.0			
							RIDE	8.2	8.0	8.1	8.1	7.9	7.8	7.8	7.8	7.7	7.7	7.6	7.6	7.5			
28030001	7.790	9.184	C	1	1	40	CRACKING	10.0	9.0	8.0	7.0	7.0	7.0	6.0*	6.0*	10.0	10.0	10.0	10.0	10.0			
16			2	3.8		6200	RIDE	8.5	8.5	8.5	8.0	8.0	7.7	7.6	7.4	8.1	8.0	7.8	7.2	8.0			
HARLEY CIR(7.9R)						FC125																	
2080202	0.000	9.184	C	2002		0012	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	7.0	7.0	7.0	7.0	6.0*	6.0*	6.0*	4.7		
ANDERSON COLUMBIA CO., INC(2004)							SPRIDE	7.8	7.7	7.9	7.8	7.7	7.7	7.7	7.4	7.4	7.5	7.3	7.3	7.2	7.1		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2026 FORECASTED BY SIMPLE LINEAR REGRESSION (REG).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2021 - 2026, EXTRACTED ON 02/16/2021**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = BRADFORD																									
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR																	FUTURE
SR US	G_BMP	G_EMP	LN	%T	AADT		RATINGS	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008					
INTERSECT AT (MP SIDE)							=====																		
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM	X-P																			
CONTRACTOR (AGE ONE YEAR)							ASTYPE	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2026				
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM	X-F															(REG)				
28040000	0.000	5.708	C	1	1	60	CRACKING	7.0	7.0	7.0	7.0	7.0	7.0	6.5	6.5	6.5	6.5	6.5	6.5	3.5*					
18			2	6.2		900	RIDE	9.0	8.9	8.4	8.6	8.7	8.2	8.2	7.8	7.6	7.8	7.6	7.7	7.8					
SW 206 AVE(1.8L)						FC125																			
2079732	0.000	5.509	C	2007	0221		CRACKING	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.5	7.0	6.3				
ANDERSON COLUMBIA CO., INC(2009)						SPRIDE		8.6	8.2	8.3	8.0	7.7	7.1	7.2	7.5	7.4	7.0	7.0	7.1	7.0	6.1				
28050000	0.000	0.379	C	1	6	25	CRACKING	10.0	10.0	9.5	9.5	9.5	9.5	9.5	9.5	9.0	9.0	9.0	9.0	6.5					
230			2	4.0		2200	RIDE	6.4*	6.7	6.6	5.6*	5.8*	5.9*	5.4*	7.2	6.4	6.5	6.5	7.0	6.6					
SR 200(0.0C)						FC125																			
							CRACKING	6.5	6.5	6.5	6.5	6.5	6.5	6.5	5.5*	5.5*	5.5*	5.5*	5.5*	3.5*	3.5				
							RIDE	6.4	6.4	6.3	6.3	6.2	5.0*	4.7*	4.4*	4.4*	4.5*	4.3*	4.4*						
28050000	0.379	3.843	C	1	1	55	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.5	9.5	8.0	8.0	8.0	7.0	6.5					
230			2	7.9		2900	RIDE	8.9	8.9	8.8	8.8	8.8	8.2	8.7	8.7	8.2	8.1	8.0	8.1	7.9					
REDGRAVE ST(0.4R)						FC125R																			
4244821	0.694	3.843	C	2013	0012		CRACKING	6.5	6.5	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	8.5	7.0	6.6				
V. E. WHITEHURST & SONS, I(2014)						SPRIDE		7.8	7.3	7.4	7.1	6.8	8.5	8.3	8.2	7.9	7.6	7.0	6.9	6.5	5.1				
28060000	0.000	0.657	C	1	1	55	CRACKING	10.0	9.5	9.5	9.5	9.5	9.5	8.0	8.0	7.0	8.0	8.0	6.5	4.5*					
231			2	4.7		4200	RIDE	9.1	9.2	9.1	7.7	7.9	8.0	8.3	8.2	7.7	7.6	7.3	7.7	7.5					
SW 114 ST(0.3L)						FC125																			
2079783	0.000	0.671	C	2007	0012		CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	9.0	8.5	7.5	7.0	6.6				
ANDERSON COLUMBIA CO., INC(2009)						SPRIDE		8.2	7.8	8.1	7.8	7.4	7.3	7.2	7.3	7.3	7.3	7.1	7.3	7.3	6.7				
28090000	0.000	3.560	C	1	1	55	CRACKING	6.5	6.5	6.5	6.5	6.5	4.5*	3.5*	2.5*	2.5*	2.5*		10.0	10.0					
21			2	6.3		9900	RIDE	8.4	8.4	8.3	7.9	7.6	7.5	7.3	5.8*	6.2*	6.1*		8.4	8.3					
SE 16TH ST(0.8L)						FC125M																			
2079472	0.000	3.560	C	2005	0012		CRACKING	10.0	10.0	10.0	8.5	8.5	8.5	7.0	7.0	7.0	7.0	6.0*	6.0*	5.5*	3.7				
V. E. WHITEHURST & SONS, I(2007)						SPRIDE		8.4	8.3	8.2	8.1	8.1	8.1	8.0	7.9	7.8	7.8	7.7	7.7	7.7	7.4				
28125000	0.000	7.166	R	1	7	70	CRACKING																		
223 A301			2	18.7		1000	RIDE																		
N END BR #280061(0.0C)						FC5M																			
							CRACKING													10.0					
							RIDE													8.8					
28125000	0.000	7.166	L	1	7	70	CRACKING																		
223 A301			2	18.7		1000	RIDE																		
N END BR #280061(0.0C)						FC5M																			
							CRACKING													10.0					
							RIDE													8.9					

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2026 FORECASTED BY SIMPLE LINEAR REGRESSION (REG).