

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2021 - 2026, EXTRACTED ON 02/16/2021**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = SUWANNEE																						
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR														FUTURE
SR US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	=====	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008		
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKMX-P																	
ITMSEG-P	(AGE_ONE YEAR)				ASTYPE			2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2026 (REG)	
CONTRACTOR (AGE_ONE YEAR)	W_BMP	W_EMP	RW	FY-F	WKMX-F																	
ITMSEG-F																						
37010000	0.000	4.983	C	1	7 60	CRACKING		5.5*	5.5*		10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	8.5		
10 90			2	4.7	3100	RIDE		8.0	8.0		8.9	8.9	8.8	8.8	8.6	7.9	8.1	8.0	7.9	8.0		
OLD LOCATION OF SR 10(0.1L)					FC125M																	
4342961	0.000	4.952	C	2019	0012	CRACKING		7.0	7.0	7.0	7.0	7.0	6.5	6.0*	6.0*	6.0*	4.0*	3.5*	3.5*	10.0		
ANDERSON COLUMBIA CO., INC(2021)					SPRIDE			7.8	7.9	7.8	7.6	7.6	7.6	7.4	7.5	7.4	7.5	7.4	7.3	8.7		
37010000	4.983	6.252	R	1	1 60	CRACKING		4.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
10 90			2	4.7	3100	RIDE		7.3	7.5		8.1	8.3	8.2	8.3	8.3	7.9	8.0	7.9	7.8	7.8		
					FC125M																	
						CRACKING		8.5	8.5	8.5	8.5	10.0	10.0	10.0	10.0	10.0	9.5		10.0	7.5		
					(2020)	RIDE		7.8	7.9	7.8	7.8	8.7	8.5	8.4	8.3	8.3	8.2		8.4	8.3		
37010000	6.252	12.270	C	1	7 60	CRACKING		3.5*	3.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
10 90			2	4.7	7700	RIDE		8.0	8.0		8.8	8.8	8.7	8.8	8.8	8.1	8.0	8.0	7.8	7.9		
161 RD(6.4R)					FC125M																	
4342961	6.261	10.177	C	2019	0012	CRACKING		8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	7.0	4.5*	3.5*	3.5*	10.0		
ANDERSON COLUMBIA CO., INC(2021)					SPRIDE			7.8	8.0	7.8	7.7	7.5	7.5	7.5	7.3	7.2	7.3	7.0	7.0	8.5		
37010000	12.270	13.320	C	1	7 35	CRACKING		8.5	8.5	7.5	6.0*	5.5*	3.5*		10.0	10.0	10.0	8.5	8.5	8.5		
10 90			2	4.7	8000	RIDE		7.9	8.0	7.9	6.8	6.6	6.7		8.5	8.1	8.1	7.7	7.6	7.6		
GREEN AVE(12.4R)					FC125M																	
						CRACKING		8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	6.0*	4.5*	3.5*	3.5*	10.0		
					(2021)	RIDE		7.8	7.9	7.5	7.4	7.3	7.4	7.3	7.3	7.3	7.3	7.2	7.2	7.7		
37010000	13.320	15.090	C	1	7 45	CRACKING		6.5	6.5	5.5*	5.5*	5.5*	4.5*		10.0	10.0	10.0	8.5	8.5	8.5		
10 90			2	3.7	5500	RIDE		8.5	8.5	8.3	8.1	8.0	7.9		8.5	8.1	8.1	7.7	7.6	7.6		
CONNER ST(13.3C)					FC125M																	
						CRACKING		8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	6.0*	4.5*	3.5*	3.5*	10.0		
					(2021)	RIDE		7.8	7.9	7.5	7.4	7.3	7.4	7.3	7.3	7.3	7.3	7.2	7.2	8.4		
37010000	15.090	26.152	C	1	1 60	CRACKING		5.5*	5.5*	5.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
10 90			2	3.7	8700	RIDE		8.6	8.2	8.0	8.4	8.7	8.7	8.7	8.7	8.4	8.3	8.2	8.1	8.0		
97TH LN(15.3L)					FC3																	
2108001	14.676	26.152	C	1999	0221	CRACKING		10.0	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	4.5*	4.0*	4.0*	4.0*	2.9	
ANDERSON COLUMBIA CO., INC(2000)					SPRIDE			7.9	8.0	7.8	7.7	7.6	7.6	7.5	7.6	7.6	7.7	7.7	7.7	7.7	7.1	
4432831	14.628	26.152	C	2022	0012																	
37010000	4.983	6.252	L	1	1 60	CRACKING		4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0		
10 90			2	4.7	3100	RIDE		7.4	7.4		7.9	8.3	8.2	8.6	8.6	7.8	8.0	8.0	7.9	7.9		
169 RD(5.3L)					FC125M																	
						CRACKING		8.5	7.5	7.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	7.5	7.5	7.0	5.4	
					(2013)	RIDE		7.8	7.8	7.5	7.6	8.8	8.5	8.5	8.3	8.3	8.3	8.2	8.4	8.4	8.0	
37030000	0.000	0.449	C	1	1 35	CRACKING		10.0	9.0	9.0	6.5	6.5	4.5*	4.5*	3.5*	10.0	10.0	10.0	10.0	10.0		
20 27			2	10.9	5200	RIDE		8.0	8.1	7.9	6.7	7.1	7.2	6.3	6.6	7.9	7.9	7.7	7.4	7.9		
SR 249(0.1L)					FC125																	
2127343	0.000	8.530	C	2003	0012	CRACKING		10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	4.0*	4.0	
ANDERSON COLUMBIA CO., INC(2004)					SPRIDE			7.9	7.8	7.8	7.7	7.7	7.6	7.6	7.4	7.4	7.4	7.3	7.1	7.3	7.1	
37030000	0.449	3.962	C	1	1 60	CRACKING		7.0	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0		
20 27			2	10.9	4600	RIDE		8.7	8.8	8.5	8.6	8.4	8.1	7.8	7.6	8.5	8.5	8.5	8.5	8.6		
83 PL(0.7L)					FC125																	
2127343	0.000	8.530	C	2003	0012	CRACKING		10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.0	6.0*	6.0*	6.0*	4.0*	4.0	
ANDERSON COLUMBIA CO., INC(2004)					SPRIDE			8.5	8.4	8.4	8.3	8.0	8.0	8.0	7.9	8.0	7.9	7.9	7.9	7.9	7.6	
37030000	3.962	4.857	C	1	1 60	CRACKING		7.0	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	1.0*	10.0	10.0	10.0	10.0	10.0		
20 27			2	8.3	5700	RIDE		8.7	8.8	8.5	8.6	8.4	8.1	7.8	7.6	8.5	8.5	8.5	8.5	8.5		
US-129/SR-49(4.2R)					FC125																	
2127343	0.000	8.530	C	2003	0012	CRACKING		10.0	10.0	10.0	9.0	8.5	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	4.0*	4.0	
ANDERSON COLUMBIA CO., INC(2004)					SPRIDE			8.5	8.4	8.4	8.3	8.2	7.9	8.1	7.9	7.9	8.0	7.8	7.9	7.9	7.6	
37030000	4.857	8.623	C	1	1 60	CRACKING		7.0	7.0	5.5*	5.5*	3.5*	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0		
20 27			2	8.3	5700	RIDE		8.7	8.8	8.5	8.6	8.4	8.3	7.8	7.8	8.5	8.5	8.5	8.5	8.4		
274 PL(5.1R)					FC125																	
2127343	0.000	8.530	C	2003	0012	CRACKING		10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	7.0	7.0	6.0*	6.0*	4.0*	4.0	
ANDERSON COLUMBIA CO., INC(2004)					SPRIDE			8.4	8.3	8.2	8.1	8.1	7.9	8.0	7.9	7.9	7.9	7.9	7.9	7.5		

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 @ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2026 FORECASTED BY SIMPLE LINEAR REGRESSION (REG).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2021 - 2026, EXTRACTED ON 02/16/2021**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = SUWANNEE																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR													
SR US	G_BMP	G_EMP	LN	%T	AADT	RATINGS		1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	FUTURE
INTERSECT AT (MP SIDE)							=====														
ITMSEG-P	W_BMP	W_EMP	RW	FY-P	WKM-M	P															
CONTRACTOR (AGE_ONE YEAR)																					
ITMSEG-F	W_BMP	W_EMP	RW	FY-F	WKM-M	F														(REG)	
37050000	0.424	1.046	C	1	1	55	CRACKING	10.0	10.0	9.5	7.0	7.0	7.0	7.0	3.5*	3.5*	3.5*	3.5*	10.0	10.0	
136			2	10.4		2400	RIDE	7.7	7.7	7.7	8.2	8.4	8.3	8.3	8.2	7.1	6.7	6.3*	8.0	8.5	
EXIT FARMERS MARKET(0.5R)							FC125														
2107752	0.424	0.789	C	2006		0012	CRACKING	10.0	10.0	10.0	10.0	9.0	8.5	8.5	7.5	7.0	7.0	6.5	6.5	6.0*	4.5
ANDERSON COLUMBIA CO., INC(2007)							RIDE	8.3	8.2	8.3	8.2	8.1	8.3	8.2	8.0	7.9	7.9	7.8	7.9	7.9	7.7
37060000	0.000	17.455	C	1	1	60	CRACKING	8.5	7.0	5.5*	3.5*	3.5*	0.0*	0.0*	10.0	10.0	10.0	10.0	10.0	10.0	
51			2	7.0		4700	RIDE	8.2	8.2	8.0	8.5	8.5	8.3	8.3	8.8	8.5	8.4	8.4	8.4	8.4	
COUNTY LINE INSPECTION S(1.3C)							FC125M														
4322611	0.000	16.658	C	2016		0012	CRACKING	10.0	8.5	7.0	7.0	7.0	5.5*	5.5*	5.5*	10.0	10.0	10.0	10.0	10.0	10.0
ANDERSON COLUMBIA CO., INC(2017)							SPRIDE	8.3	8.3	8.2	8.0	8.0	7.9	7.8	7.8	8.6	8.5	8.3	8.0	7.8	6.8
37060000	17.455	17.491	C	1	6	35	CRACKING	8.5	7.0	5.5*	3.5*	3.5*	0.0*	0.0*		10.0	10.0	10.0	10.0	10.0	
51			1	7.0		9200	RIDE	8.2	8.2	8.0	8.5	8.5	8.3	8.3							
S WALKER AVE(17.5R)							FC95														
(2004)							CRACKING									8.5	8.5	8.5	8.5	8.5	7.8
							RIDE														
37060000	17.491	17.994	C	1	1	35	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	6.5	6.5	10.0	8.5	8.5	7.5	
51			2	7.0		9200	RIDE	7.9	8.1	7.7	7.1	6.9	6.7	6.8	6.1	5.8	7.3	6.9	6.6	6.2	
BYNUM AVE SW(17.6R)							FC95														
(2010)							CRACKING	7.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	7.5	7.5	7.0	7.0	7.0	4.9
							RIDE	5.5	7.7	7.5	7.3	7.2	7.0	6.9	6.4	6.3	6.2	6.0	6.0	6.1	5.0
37070000	0.000	2.755	C	1	1	60	CRACKING	10.0	10.0	10.0	9.0	9.0	8.5	8.5	7.5	7.5	7.0	7.0	5.5*	5.5*	
49 129			2	12.6		3200	RIDE	8.7	8.8	8.4	8.7	8.4	8.6	8.5	8.4	8.1	8.0	7.9	7.6	7.4	
SANDY POINT RD(0.0L)							FC125														
2107762	0.000	2.648	C	2009		0012	CRACKING	5.5*	10.0	10.0	8.5	8.5	8.5	8.5	8.5	8.5	8.5	7.0	7.0	7.0	5.8
ANDERSON COLUMBIA CO., INC(2010)							RIDE	7.4	8.7	8.2	8.2	8.2	8.3	8.2	8.2	8.1	8.0	7.9	7.9	7.8	7.5
37080000	0.000	0.600	C	1	1	35	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	6.0*	5.5*	5.5*	5.5*	
247			2	15.3		3220	RIDE	8.2	8.4	8.2	8.5	8.5	8.4	8.3	8.3	7.8	7.6	7.4	7.2	6.5	
SR 249(0.0C)							FC125M														
2107192	0.000	0.600	C	2008		0221	CRACKING	5.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5
ANDERSON COLUMBIA CO., INC(2010)							RIDE	6.8	8.4	7.9	7.8	8.0	8.0	8.0	7.8	7.8	7.8	7.8	7.8	7.8	7.6
37080000	0.600	10.700	C	1	1	60	CRACKING	9.0	9.0	9.0	9.0	9.0	9.0	9.0	7.0	7.0	6.0*	5.5*	5.5*	5.0*	
247			2	15.0		4300	RIDE	8.2	8.4	8.2	8.5	8.5	8.4	8.3	8.3	7.8	7.6	7.4	7.2	7.1	
SIDE ROAD(1.2C)							FC125M														
2107192	0.690	10.700	C	2008		0221	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.5	8.5	8.5	7.0	6.7
ANDERSON COLUMBIA CO., INC(2010)							RIDE	8.7	8.6	8.5	8.4	8.1	8.1	8.2	8.1	8.1	8.1	7.9	7.9	7.8	7.4
37120000	0.000	5.861	R	4	1	70	CRACKING	9.0	7.0		4.5*	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	10.0	
8 110	268.2	274.1	2	22.7		23500	RIDE	8.4	8.5		8.4	8.6	8.9	8.9	8.9	8.4	8.4	8.0	8.3	8.0	
							FC5M														
2135602	0.000	5.861	C	2007		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	6.5	6.5	6.0
ANDERSON COLUMBIA CO., INC(2008)							RIDE	8.1	8.2	8.2	8.1	8.1	8.1	8.0	8.3	8.3	8.5	8.4	8.4	8.4	8.4
4413371	0.000	5.861	C	2021		0012															
37120000	5.861	15.099	R	4	1	70	CRACKING	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	8.0	7.5	7.5	
8 110	274.1	283.3	2	26.4		26000	RIDE	7.7	8.3		9.0	9.0	8.9	8.9	8.9	8.3	8.2	8.0	8.0	7.7	
							FC5M														
2135603	5.861	15.099	C	2011		0012	CRACKING	7.5	6.5	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.3
PREFERRED MATERIALS, INC. (2013)							SPRIDE	7.6	7.3	7.0		8.7	8.7	8.6	8.9	8.9	9.1	9.0	9.0	9.1	9.1
37120000	15.099	25.508	R	4	1	70	CRACKING	4.5*		10.0	10.0	10.0	10.0	9.0	6.5	6.5	3.5*	1.0*	10.0	10.0	
8 110	283.3	293.8	2	23.3		31865	RIDE	7.7		8.0	9.2	9.1	9.0	8.6	8.3	7.7	6.8	6.4*	8.4	8.5	
							FC5M														
2135202	15.144	25.523	C	2006		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	9.0	9.0	7.5	7.5	4.5*	4.5*	4.5*	3.3	
ANDERSON COLUMBIA CO., INC(2007)							RIDE	8.5	8.5	8.5	8.4	8.3	8.1	7.9	8.3	8.3	8.6	8.5	8.5	8.5	8.4
4455441	15.099	25.508	C	2023		0012															
37120000	15.099	25.508	L	4	1	70	CRACKING	4.5*		10.0	10.0	10.0	10.0	9.0	6.5	6.5	3.5*	1.0*	10.0	10.0	
8 110	283.3	293.8	2	23.3		31865	RIDE	8.0		8.0	9.1	9.0	8.9	8.7	8.3	7.4	7.0	6.7	8.5	8.5	
							FC5M														
2135202	15.144	25.523	C	2006		0012	CRACKING	10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	4.5*	4.5*	4.5*	4.1
ANDERSON COLUMBIA CO., INC(2007)							RIDE	8.5	8.5	8.4	8.3	8.2	8.1	7.9	8.4	8.3	8.7	8.5	8.5	8.4	8.4
4455441	15.099	25.508	C	2023		0012															

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 *@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2026 FORECASTED BY SIMPLE LINEAR REGRESSION (REG).

FLORIDA DEPARTMENT OF TRANSPORTATION**ALL SYSTEM PAVEMENT CONDITION FORECAST****PAVEMENT IMPROVEMENT PROJECTS IN FM WPA TENTATIVE PLAN – 2021 - 2026, EXTRACTED ON 02/16/2021**

SORT BY RDWYID MILEPOST R ASCENDING L DESCENDING

DISTRICT = 2 COUNTY = SUWANNEE																					
RDWYID	BMP	EMP	RW	SYS	TYP	SPD	DISTRESS	SURVEYED YEAR												FUTURE	
SR US	G_BMP	G_EMP	LN	%T	AADT	RATINGS	=====	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	
INTERSECT AT (MP SIDE)	W_BMP	W_EMP	RW	FY-P	WKMX-P	ASTYPE															
ITMSEG-P	(AGE_ONE YEAR)							2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2026 (REG)
CONTRACTOR	W_BMP	W_EMP	RW	FY-F	WKMX-F																
ITMSEG-F																					
37120000	5.861	15.099	L	4	1	70	CRACKING	4.5*	4.5*		10.0	10.0	10.0	10.0	10.0	9.0	9.0	8.0	7.5	7.5	
8 I10	274.1	283.3	2	26.4	26000	RIDE		8.0	8.3		8.9	8.9	8.8	8.8	8.8	8.2	8.1	7.9	7.7	7.4	
					FC5M																
2135603	5.861	15.099	C	2011	0012	CRACKING		6.5	6.0*	6.0*		10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	8.3
PREFERRED MATERIALS, INC. (2013)					SPRIDE			7.4	7.1	6.6		8.7	8.7	8.6	8.8	8.8	9.0	8.9	8.9	9.1	9.1
37120000	0.000	5.861	L	4	1	70	CRACKING	8.0	6.5		4.5*	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	10.0	
8 I10	268.2	274.1	2	22.7	23500	RIDE		8.6	8.5		8.4	8.8	8.8	8.9	8.9	8.4	8.3	8.2	8.2	8.1	
					FC5M																
2135602	0.000	5.861	C	2007	0012	CRACKING		10.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	6.5	6.5	6.5	5.7
ANDERSON COLUMBIA CO., INC (2008)					RIDE			8.1	8.2	8.2	8.1	8.1	8.0	7.8	8.3	8.2	8.5	8.4	8.4	8.4	8.4
4413371	0.000	5.861	C	2021	0012																
37130000	0.000	3.656	R	4	1	70	CRACKING	3.5*	3.5*	3.5*	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	8.5	
93 I75	438.4	442.0	3	27.8	36500	RIDE		7.8	8.1	8.0	9.0	8.9	8.5	8.9	8.9	8.3	8.3	8.1	7.9	7.7	
					FC5M																
2135542	0.000	3.656	R	2009	0012	CRACKING		7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	7.5	6.3
(2010)					RIDE			7.5	8.7	8.7	8.6	8.6	8.5	8.3	8.7	8.6	9.0	8.8	8.9	8.9	8.9
4455451	0.000	3.656	C	2022	0012																
37130000	0.000	3.656	L	4	1	70	CRACKING	6.5	6.5	6.5	10.0	10.0	10.0	10.0	10.0	10.0	10.0	8.5	8.5	7.5	
93 I75	438.4	442.0	3	27.8	36500	RIDE		7.9	8.0	7.8	8.6	8.9	8.9	8.9	8.8	8.4	8.3	8.2	8.1	8.0	
					FC5M																
2135542	0.000	3.656	L	2009	0012	CRACKING		7.0	10.0	10.0	10.0	10.0	10.0	10.0	9.0	9.0	9.0	7.5	7.5	7.5	6.3
PREFERRED MATERIALS, INC. (2010)					SPRIDE			7.7	8.6	8.6	8.5	8.5	8.4	8.2	8.5	8.5	8.7	8.6	8.6	8.6	8.6
4455451	0.000	3.656	C	2022	0012																

*** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2006, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 50 MPH.
 *** INDICATES PAVEMENT DEFICIENT (ANY RATING <=6); START 2002, RIDE RATING OF 6 NOT CONSIDERED DEFICIENT WHEN SPEED LIMIT < 45 MPH.
 "@@ INDICATES G1 PROJECT LENGTH SHORTER THAN ROADWAY SEGMENT 1 MILE OR MORE.
 2026 FORECASTED BY SIMPLE LINEAR REGRESSION (REG).