

**524 CONCRETE DITCH AND SLOPE PAVEMENT – METHOD OF MEASUREMENT.**

**(REV 6-23-00) (FA 9-7-00) (7-01)**

ARTICLE 524-9 (Page 656) is deleted and the following substituted:

**524-9 Method of Measurement.**

**524-9.1 Concrete Ditch Pavement:** The quantities to be paid for will be the plan quantity, in square yards [square meters], completed and accepted. Where the plans show headers or cut-off walls at the end or edge of the pavement, the volume of the additional thickness of pavement that constitutes the headers, calculated in accordance with plan dimensions, will be converted into equivalent square yards [square meters] of standard thickness pavement and included in the quantity to be paid for.

No deduction will be made for any areas occupied by manholes, inlets, or other drainage structures or by public utility appurtenances within the pavement area.

**524-9.2 Concrete Slope Pavement:** The quantity to be paid for will be the plan quantity, in square yards [square meters], completed and accepted. Where the plans show headers or cut-off walls at the end or edge of the pavement, the volume of the additional thickness of pavement that constitutes the headers, calculated in accordance with plan dimensions, will be converted into equivalent square yards [square meters] of standard thickness pavement and included in the quantity to be paid for.

No deduction will be made for any areas occupied by manholes, inlets, or other drainage structures or by public utility appurtenances within the pavement area.