



# Florida Department of Transportation

JEB BUSH  
GOVERNOR

605 Suwannee Street  
Tallahassee, FL 32399-0450

THOMAS F. BARRY, JR.  
SECRETARY

January 7, 2003

Mr. Donald Davis  
Program Operations Engineer  
Federal Highway Administration  
227 N. Bronough Street, Suite 2015  
Tallahassee, Florida 32301

Re: Office of Design, Specifications  
Section 339  
Proposed Specification: D3390007.D01 – Miscellaneous Asphalt Pavement –  
Method of Measurement

Dear Mr. Davis:

We are submitting, for your approval, two copies of a proposed Supplemental Specification for Miscellaneous Asphalt Pavement – Method of Measurement.

This change has been developed by David Chason, of the State Construction Office to submit requirement of Certification of Quantities.

Please review and transmit your comments, if any, within two weeks. Comments should be sent via Email to SP965DB or [duane.brautigam@dot.state.fl.us](mailto:duane.brautigam@dot.state.fl.us).

If you have any questions relating to this specification change, please call Duane F. Brautigam, State Specifications Engineer at 414-4110.

Sincerely,

Duane F. Brautigam, P.E.  
State Specifications Engineer

DFB/sh  
Attachment

cc: General Counsel  
Florida Transportation Builders' Assoc.  
State Construction Engineer

**MISCELLANEOUS ASPHALT PAVEMENT – METHOD OF MEASUREMENT.**  
**(REV 11-4-02)**

ARTICLE 339-7 (of the Supplemental Specifications) is deleted and the following substituted:

**339-7 Method of Measurement.**

The quantity to be paid for will be the weight, in tons [metric tons], determined by an electronic weighing system as described in 320-2.2. The pay quantity will be based on the average spread rate *of the area shown on the plans or authorized by the Engineer* ~~or dimensions for the project~~, limited to a maximum of 105% of the plan ~~thickness~~ ~~quantity~~. For calculation, a weight of 100 lbs/yd<sup>2</sup> per inch [22 kg/m<sup>2</sup> per 10 mm] thickness of asphalt will be used.

*Prepare a Certification of Quantities, using the Department's current approved form, for the certified miscellaneous asphalt pavement pay item. Submit this certification to the Engineer no later than Twelve O'clock noon Monday after the estimate cut-off or as directed by the Engineer, based on the quantity of asphalt produced and accepted on the Contract. The certification must include the Contract Number, FPID Number, Certification Number, Certification Date, period represented by Certification and the tons [metric tons] produced for each asphalt pay item.*

**MISCELLANEOUS ASPHALT PAVEMENT – METHOD OF  
MEASUREMENT.  
(REV 11-4-02)**

ARTICLE 339-7 (of the Supplemental Specifications) is deleted and the following substituted:

**339-7 Method of Measurement.**

The quantity to be paid for will be the weight, in tons [metric tons], determined by an electronic weighing system as described in 320-2.2. The pay quantity will be based on the average spread rate of the area shown on the plans or authorized by the Engineer, limited to a maximum of 105% of the plan thickness. For calculation, a weight of 100 lbs/yd<sup>2</sup> per inch [22 kg/m<sup>2</sup> per 10 mm] thickness of asphalt will be used.

Prepare a Certification of Quantities, using the Department's current approved form, for the certified miscellaneous asphalt pavement pay item. Submit this certification to the Engineer no later than Twelve O'clock noon Monday after the estimate cut-off or as directed by the Engineer, based on the quantity of asphalt produced and accepted on the Contract. The certification must include the Contract Number, FPID Number, Certification Number, Certification Date, period represented by Certification and the tons [metric tons] produced for each asphalt pay item.