



Florida Department of Transportation

JEB BUSH
GOVERNOR

605 Suwannee Street
Tallahassee, FL 32399-0450

THOMAS F. BARRY, JR.
SECRETARY

MEMORANDUM

DATE: September 16, 2002

TO: Specification Review Distribution List

FROM: Duane F. Brautigam, P.E., State Specifications Engineer

SUBJECT: **Proposed Specifications Change – D3300911 - Placing Mixture-Alignment of Edges**

In accordance with Specification Development Procedures, we are sending you a copy of a proposed specification change to Section 330.

This change was proposed by David Wang of the State Construction Office to establish a construction tolerance so that the Contractor (QC) and the Department (Verification) can use this tolerance to control the uniformity of alignment of the pavement edge during construction.

Please share this proposal with others within your responsibility. Review comments are due within four weeks and should be sent to Mail Station 75 or to my attention via e-mail at SP965DB or duane.brautigam@dot.state.fl.us. Comments received after October 14, 2002 may not be considered. Your input is encouraged.

DFB/jf

Attachment

COMMENTS:

Submitted by:

Phone #:

**PLACING MIXTURE-ALIGNMENT OF EDGES.
(REV 8-28-02)**

SUBARTICLE 330-9.1.1 (of the Supplemental Specifications) is deleted and the following substituted:

330-9.1.1 Alignment of Edges: Lay all asphaltic concrete mixtures, including leveling courses, other than *the pavement edge just* adjacent to curb and gutter or other true edges, by the stringline method to obtain an accurate, uniform alignment of the pavement edge. *Control the unsupported pavement edge to ensure that it will not deviate more than 3 inches [76 mm] from the stringline.*