

700 HIGHWAY SIGNING – SIGN PANELS.
(REV 7-26-02) (FA 7-30-02) (7-03)

SUBARTICLE 700-2.2 (Page 758). The fourth paragraph is deleted and the following substituted:

If the size of a sign is not specified in the plans, provide the size sign for conventional roadways as shown in the MUTCD.

SUBARTICLE 700-2.5 (Page 762) is deleted and the following substituted:

700-2.5 Sign Background: Meet the requirements of Section 994. Use Type III, IV or V sheeting for background sheeting, white legends, borders and shields on all signs, excluding STOP, DO NOT ENTER, and WRONG WAY. Use Type VII sheeting for STOP, DO NOT ENTER and WRONG WAY signs. Use Type III, IV, V or VII yellow-green fluorescent sheeting only for S1-1 school advance signs and S2-1 school crossing signs. Do not mix work zone signs having fluorescent orange sheeting with signs having orange reflective sheeting.

SUBARTICLE 700-3.8 (Page 763) is deleted and the following substituted:

700-3.8 Process Colors: Use transparent and black opaque process colors meeting the requirements of 994-4 on reflective sheeting.

SUBARTICLE 700-5.5 (Page 765) is deleted and the following substituted:

700-5.5 Stenciling: For permanent roadway signs, mark the back of all finished panels at the bottom edge with “FDOT”, the date of fabrication, the date of installation, and the fabricator’s initials. For construction signs, mark the back of all finished panels at the bottom edge with the date of fabrication and the fabricator’s initials. Make the markings unobtrusive, but legible enough to be easily read by an observer on the ground when the sign is in its final position. Apply the markings in a manner that is at least as durable as the sign face.